

Barry

Go alone, get home.

Project overview · October 2026 · barry.support



FEATURES 1 OF 2

Before You Go and While You Are Out

Tell Barry where you are going and when you will be back. If you don't check in by then, Barry tells the people you chose.

BEFORE YOU GO

A Plan and a Deadline

Destination, route, starting point, notes such as what you are wearing, and the time you will be back.

Emergency Contacts

Chosen per adventure from a saved list. They need no app and no account. Barry reaches them by email, text message, or both.

A Heads-Up at the Start

Each contact learns that you are heading out, with your plan, your deadline and their own link to your adventure page.

Plans for Later

Save an adventure for later and start it with one tap when you leave.

WHILE YOU ARE OUT

Your Trail

With location access set to Always, Barry records a position about once a minute and keeps readings on the phone without signal.

A Live Adventure Page

Contacts see your trail, last known position and plan at barry.support/adventure. It updates every minute and never shows the deadline.

Need More Time?

Move the deadline later with one tap, even when you are already overdue. Edit the plan, and contacts get a plan update.

Reminder and Overdue Notice

The phone itself reminds you 30 minutes before the deadline and tells you when you are overdue, even without signal.



FEATURES 2 OF 2

Coming Back, or Not in Time

Barry's server keeps the time, so it raises the alarm even when your phone is off or out of signal.

Coming back

Hold to Check In

A deliberate press and hold, so a pocket cannot check you in by accident. A check-in without signal is kept and sent when the phone is online again.

Coming back

Contacts See You Are Back

After the check-in the adventure page shows the time you checked in, with your trail up to then.

Not in time

An Alert to Every Contact

One minute after the deadline, then every hour, up to three alerts. Only an alert carries your phone number, car and medical notes.

Coming back

An All-Clear

When you check in, on time or late, every contact hears that you are back safe.

Not in time

Messages That Did Not Arrive

If an email or text message fails, the app shows you which contact did not get it. Contacts who share an address get one message.

Your data

History and Deleting

Past adventures with plan, check-in time and trail. Delete an adventure or the whole account, and the contacts' links stop working.

Barry is not an emergency service. It never calls rescue services. It tells the people you chose, and they decide what to do.



DELIVERABLES

The Components of Barry

iPhone

The Barry App

- Expo SDK 58, React Native, Expo Router
- Tabs: Adventure, History, Contacts, Profile
- Liquid Glass buttons through SwiftUI
- Background trail with a 200 m geofence
- Local Reminder and Overdue Notice
- Offline check-in queue

Supabase

Backend and Clock

- Postgres schema with row-level security
- 25 migrations, commands as functions
- A clock in `pg_cron`, every minute
- Auth with email confirmation
- Vault for the delivery secret

Edge Function

`deliver`

- Renders heads-up, plan update, alert and all-clear
- Email through Resend as "🐶 Barry"
- Text messages through LINK Mobility
- Retries and delivery failures

barry.support

Web Pages

- Landing page with all features
- Adventure page for contacts, with an OpenStreetMap trail
- Email confirmation page
- Published by a GitHub Pages workflow

Quality

Tests

- 11 database test files (pgTAP)
- Unit tests for the app (Jest)
- Tests for `deliver` (Deno)
- 6 end-to-end scripts against the local stack

Tooling

Scripts and Skills

- `hosted-secrets.mjs` sets the hosted secrets
- `make-icons.py` draws icon and launch screen
- `without-push.js` config plugin
- A verify skill with 8 feature maps



TECHNICAL DOCUMENTS 1 OF 2

Specification and Design

Barry was designed before it was built. These documents describe what Barry does and why it is shaped this way.

docs/spec.md

Barry Specification

The product reference: accounts, profile, contacts, adventures and their stages, deadline and grace period, messages, location, the adventure page, monitoring and what is out of scope.

CONTEXT.md

Glossary

The domain language, one definition per term: Adventurer, Emergency Contact, Plan, Deadline, Grace Period, Heads-up, Alert, All-clear, Trail and more.

docs/adr/0001

The Server Owns the Deadline

The decision record why Supabase, not the phone, decides when an alert goes out, so the alarm works when the phone is off.

docs/design/backend

Backend Design

The design sketch for the schema, row-level security, the clock and message delivery, with `schema.sql`, `barry.ts` and `deliver.ts`.

docs/design/trail

Trail Design

The design for background recording, offline readings, the geofence and the contacts' live page.

AGENTS.md

Rules for Coding Agents

How to work in the repository: Expo version, commands, routing, the build without push, and the checks to run before a task is done.



TECHNICAL DOCUMENTS 2 OF 2

Guides and the Build Process

311
prompts to Claude

166
commits

1.8 M
output tokens

1.5 B
tokens in total

2 days
15 to 16 October 2026

README.md

Run and Check

Setup, the local stack, and every test command.

docs/iphone.md

Barry on an iPhone

Prebuild, signing and installing a build on a phone.

docs/hosted-supabase.md

The Hosted Project

What is deployed, how to ship a change, secrets and health.

docs/text-messages.md

Text Messages

LINK Mobility setup, sender, costs and segment counts.

docs/local-messages.md

Messages Locally

How to see what Barry sends, in Mailpit and Studio.

docs/trail-map-hosting.md

Hosting the Web Pages

The GitHub Pages workflow for barry.support.

.claude/skills/verify

Verify Skill

How an agent drives the app in the simulator, with 8 feature maps.

barry-prompts.html

Prompt Overview

Every prompt of the project with the tokens it used, by session.



PRODUCTION

External Services

The services the live Barry depends on. The app talks only to Supabase; Supabase talks to the rest.

Backend

Supabase

Hosted project `kizggaicooqhdzpqzawu`: Postgres, Auth, the `deliver` Edge Function, `pg_cron` and Vault.

Email

Resend

Heads-ups, plan updates, alerts and all-clears from `barry@barry.support`, and sign-up emails over SMTP from `help@barry.support`.

Text messages

LINK Mobility

The websms API sends every message as a text message to contacts with a phone number.

Web hosting

GitHub

The repository `mircowidmer/barry`, Actions for the deploy, and Pages serving `barry.support`.

Maps

OpenStreetMap

Map tiles for the adventure page, drawn with Leaflet. The app uses Apple Maps.

Platform

Apple

Signing and installing the iPhone app, background location and local notifications. The domain `barry.support` points at GitHub Pages.



NEXT

Steps to a Production-Ready App

1. **Join the Apple Developer Program**
   A paid team for TestFlight and the App Store. Today the app is installed by hand.

2. **Set up release builds**
   Add `eas.json` or an Xcode archive, version numbers and TestFlight testers.

3. **Prepare the App Store listing**
   Screenshots, privacy labels and the reason for "Always" location for App Review.

4. **Publish privacy policy and terms**
   On barry.support, for Swiss and EU data protection, with the "not an emergency service" disclaimer.

5. **Move LINK Mobility to production**
   The test account reaches only one verified number. Register the sender "Barry".

6. **Upgrade the Supabase plan**
   Daily backups, no pausing, and a higher limit for sign-up emails.

7. **Monitor the clock and delivery**
   Set `HEALTHCHECK_URL` to an uptime monitor and report app errors.

8. **Rotate exposed keys**
   Rotate the Resend key, close Twilio and delete the Azure Communication Services resource.

9. **Run every test in CI**
   Database, Deno, unit and end-to-end tests on each push, not only the Pages deploy.

10. **Merge or close open branches**
    The Plan screen fix, the Maestro end-to-end tests and the check-in wake branch.