

# Algorithmic Analysis of Code-Breaking Games

Mgr. Miroslav Klimoš, prof. RNDr. Antonín Kučera Ph.D.  
Faculty of Informatics, Masaryk University, Brno




## Code-Breaking Games

- ▶ 2 players: *codemaker* and *codebreaker*
- ▶ Codemaker selects a *secret code*
- ▶ Codebreaker strives to reveal the code through a series of *experiments* whose outcomes give partial information about the code

Example: Mastermind

- ▶ Secret code: combination of  $n$  coloured pegs
- ▶ Codebreaker makes guesses (experiments)
- ▶ Guesses are evaluated with *black and white markers*
- ▶ Black marker = correct both colour and position
- ▶ White marker = the colour is present at a different position



Example: Counterfeit Coin

- ▶ Problem of finding an odd-weight coin using balance scale
- ▶ Secret code: identity of the unique counterfeit coin
- ▶ Codebreaker puts coins on the balance scale and observes the outcome

## Questions and Problems

- ▶ How should the codebreaker play in order to minimize the number of experiments needed to undoubtedly determine the code?
- ▶ Is there a strategy for experiment selection that guarantees revealing the code after at most  $k$  experiments?
- ▶ What strategy is optimal with respect to the average-case number of experiments, given that the code is selected from the given set with uniform distribution?

## Challenges and Solutions

### 1. Create a general, formal model of code-breaking games

- ▶ Model based on propositional logic
- ▶ Secret code = valuation of variables
- ▶ Partial information = logical formula

$$\Phi_t = \{ (f_x(\$1) \wedge \neg y) \vee (f_x(\$2) \wedge y), \\ (f_x(\$1) \wedge y) \vee (f_x(\$2) \wedge \neg y), \\ \neg f_x(\$1) \wedge \neg f_x(\$2) \}.$$

### 2. Suggest general strategies for experiment selection

- ▶ “Select an experiment that minimizes the maximal number of possibilities for the code in the next round”
- ▶ Several strategies of this kind formalized within the model

$$f(\Psi) = \frac{\sum_{\varphi \in \Psi} (\#\varphi)^2}{\sum_{\varphi \in \Psi} \#\varphi}$$

### 3. Propose algorithms for strategy evaluation and synthesis

- ▶ Based on intelligent backtracking
- ▶ Symmetry detection reduces the size of the state-space



### 4. Design a computer language for game specification

- ▶ Corresponds to the formal model
- ▶ Built on top of Python for easier generation

```
for m in range(1, N//2 + 1):  
    EXPERIMENT("weighing" + str(m), 2*m)  
    OUTCOME("lighter", "(!s) & !y) ...  
    OUTCOME("heavier", "(!s) & y) ...
```

### 5. Implement proposed algorithms in a computer program

- ▶ Command-line tool COBRA written in C++
- ▶ Use of modern SAT solvers for satisfiability queries needed by the algorithms

### 6. Use the tool to create new and reproduce existing results

- ▶ COBRA can easily reproduce some existing results for Mastermind
- ▶ Automatic analysis of generalizations and other code-breaking games

