

# Decidability of Termination Problems for Sequential P Systems with Active Membranes

Michal Kováč

FMFI UK, Slovakia

2.7.2015



## 1 P systems

- Overview
- Computational power



## 2 Termination problems

- Halting problem
- Termination problems in active membranes

# Membrane structure





# Membrane structure





- Multisets

# Membrane structure



- Multisets
- Rewriting rules

# Membrane structure



- Multisets
- Rewriting rules
- Passive vs. Active

# P system with active membranes

- $\Pi = (\Sigma, C_0, R_1, \dots, R_m)$

# P system with active membranes

- $\Pi = (\Sigma, C_0, R_1, \dots, R_m)$
- $C = (T, l, c)$ 
  - $l: V(T) \rightarrow \{1, \dots, m\}$
  - $c: V(T) \rightarrow \mathbb{N}^\Sigma$



# P system with active membranes

- $\Pi = (\Sigma, C_0, R_1, \dots, R_m)$
- $C = (T, l, c)$ 
  - $l: V(T) \rightarrow \{1, \dots, m\}$
  - $c: V(T) \rightarrow \mathbb{N}^\Sigma$
- Rewriting rules
  - $u \rightarrow v$
  - $u \rightarrow v\delta$
  - $u \rightarrow [{}_j v]_j,$   
 where  $u \in \mathbb{N}^\Sigma, |u| \geq 1$  and  $v \in \mathbb{N}^{\Sigma \times \{\cdot, \uparrow, \downarrow, j\}}$


# Computation

- Maximal parallel vs. sequential


# Computation

- Maximal parallel vs. sequential
- Language
  - generating mode
  - accepting mode


# Chomski hierarchy




# Chomski hierarchy




# Chomski hierarchy



# Chomski hierarchy




# Chomski hierarchy






# Chomski hierarchy



# Chomski hierarchy



# Termination problems

- Halting problem

# Termination problems

- Halting problem
- Existence of (in)finite computation

# Termination problems

- Halting problem
- Existence of (in)finite computation
- Reachability graph

# Termination problems

- Halting problem
- Existence of (in)finite computation
- Reachability graph
- Two conditions:
  - $C_1 \leq C_2 \Rightarrow$  each transition in  $C_1$  can be fired in  $C_2$

# Termination problems

- Halting problem
- Existence of (in)finite computation
- Reachability graph
- Two conditions:
  - $C_1 \leq C_2 \Rightarrow$  each transition in  $C_1$  can be fired in  $C_2$
  - for each infinite computation there is  $C_1, C_2$ , such that  $C_1 \rightarrow^* C_2$  and  $C_1 \leq C_2$

# Termination problems

- Halting problem
- Existence of (in)finite computation
- Reachability graph
- Two conditions:
  - $C_1 \leq C_2 \Rightarrow$  each transition in  $C_1$  can be fired in  $C_2$
  - for each infinite computation there is  $C_1, C_2$ , such that  $C_1 \rightarrow^* C_2$  and  $C_1 \leq C_2$
- Dickson's lemma: For every infinite sequence of tuples over  $\mathbb{N}$   $\{a_i\}_{i=0}^{\infty}$  there are  $i < j$  such that  $a_i \leq a_j$



# Termination problems in active membranes

- How to use Dickson's lemma for active membranes?
- Idea: encode configuration to k-tuple maintaining two conditions

# Termination problems in active membranes

- How to use Dickson's lemma for active membranes?
- Idea: encode configuration to k-tuple maintaining two conditions

## Definition

$C_1 = (T_1, l_1, c_1) \leq C_2 = (T_2, l_2, c_2) \Leftrightarrow$   
 $\exists$  isomorphism  $f : T_1 \rightarrow T_2$  such that  $\forall d \in V(T_1) :$

- $l_1(d) = l_2(f(d))$
- $c_1(d) \subseteq c_2(f(d))$

# Termination problems in active membranes

- How to use Dickson's lemma for active membranes?
- Idea: encode configuration to k-tuple maintaining two conditions

## Definition

$C_1 = (T_1, l_1, c_1) \leq C_2 = (T_2, l_2, c_2) \Leftrightarrow$   
 $\exists$  isomorphism  $f : T_1 \rightarrow T_2$  such that  $\forall d \in V(T_1) :$

- $l_1(d) = l_2(f(d))$
- $c_1(d) \subseteq c_2(f(d))$

## Lemma

$C_1 = (T_1, l_1, c_1) \leq C_2 = (T_2, l_2, c_2) \Rightarrow \exists$  isomorphism  $f : T_1 \rightarrow T_2$   
*such that rule  $r$  is applicable in  $d \in T_1 \Rightarrow r$  is applicable in  $f(d)$ .*

# Termination problems in active membranes

## Definition

Define  $enc(C)$  as k-tuple satisfying  
 $enc(C_1) \leq enc(C_2) \Rightarrow C_1 \leq C_2$ .

# Termination problems in active membranes

## Definition

Define  $enc(C)$  as k-tuple satisfying  
 $enc(C_1) \leq enc(C_2) \Rightarrow C_1 \leq C_2$ .

## Lemma

*For every infinite computation there is  $i < j$  such that  $C_i \leq C_j$ .*

# Termination problems in active membranes

## Definition

Define  $enc(C)$  as k-tuple satisfying  
 $enc(C_1) \leq enc(C_2) \Rightarrow C_1 \leq C_2$ .

## Lemma

*For every infinite computation there is  $i < j$  such that  $C_i \leq C_j$ .*

## Proof.

Assume infinite sequence  $\{enc(C_i)\}_{i=0}^{\infty}$ . From Dickson's lemma there is  $i < j$  such that  $enc(C_1) \leq enc(C_2)$ . Our property of  $enc$  implies  $C_i \leq C_j$ . □

# Termination problems in active membranes

## Theorem

*Existence of infinite computation in sequential P systems with active membranes is decidable.*

# Termination problems in active membranes

## Theorem

*Existence of infinite computation in sequential P systems with active membranes is decidable.*

## Theorem

*Existence of finite computation in sequential P systems with active membranes is undecidable.*



# Termination problems in active membranes

## Theorem

*Existence of infinite computation in sequential P systems with active membranes is decidable.*

## Theorem

*Existence of finite computation in sequential P systems with active membranes is undecidable.*

## Proof.

Reduction to reachability of register machines. ☐



Ibarra (2005).

On sequential and 1-deterministic p systems.

In Wang, L., editor, *Computing and Combinatorics*, volume 3595 of *Lecture Notes in Computer Science*, pages 905–914. Springer Berlin Heidelberg.

Thanks for your attention!