Inhibiting the parallelism of P systems

Michal Kováč


FMFI UK

24.6.2014

- Overview of P systems
 - P systems
 - Variants

- Sequential P systems with inhibitors
 - Accepting case
 - Generating case

Membrane structure



Contents of the membrane

- multiset of objects
 - a | b | b
- rewriting rules
 - $\bullet \ a \mid b \mid b \rightarrow a \mid a_{out} \mid b_{in_6}$
 - $\bullet \ b \to a \mid \delta$

P system

We define a P system as

$$\Pi = (V, \mu, w_1, w_2, \dots, w_m, R_1, R_2, \dots, R_m)$$
, where:

- V is an alphabet of objects
- ullet μ is a membrane structure
- $w_1, w_2, \dots w_m$ are initial multisets of objects in membranes $1 \dots m, w_i \subseteq \mathbb{N}^V$
- $R_1, R_2, ..., R_m$ are sets of rewriting rules in membranes 1...m, where

$$R_i \subseteq (\mathbb{N}^V \setminus 0^V) \times \mathbb{N}^{V \times (\{here, out\} \cup \{in_1, ... in_m\})}$$

.




- configuration = membrane structure + contents
- computational step: maximal parallelism

- configuration = membrane structure + contents
- computational step: maximal parallelism

$$egin{array}{ccccc} a \mid b \mid b
ightarrow c & (r_1) \ b
ightarrow c \mid c & (r_2) \end{array}$$

- configuration = membrane structure + contents
- computational step: maximal parallelism

- configuration = membrane structure + contents
- computational step: maximal parallelism



Language

- result of the computation is a multiset of objects, which:
 - have passed the outer membrane
 - is present in a specific membrane at the end

Language

- result of the computation is a multiset of objects, which:
 - have passed the outer membrane
 - is present in a specific membrane at the end
- generating vs. accepting mode

Language

- result of the computation is a multiset of objects, which:
 - have passed the outer membrane
 - is present in a specific membrane at the end
- generating vs. accepting mode
- Parikh mapping: PsRE

context (PsRE)

- context (PsRE)
- cooperative (PsRE) [Păun, 1998]

- context (PsRE)
- cooperative (PsRE) [Păun, 1998]
- catalytic
 - with 2 catalysts (PsRE) [Freund et al., 2005]
 - with 1 catalyst (open problem)
 - with 1 catalyst and inhibitors (PsRE) [lonescu and Sburlan, 2004]

- context (PsRE)
- cooperative (PsRE) [Păun, 1998]
- catalytic
 - with 2 catalysts (PsRE) [Freund et al., 2005]
 - with 1 catalyst (open problem)
 - with 1 catalyst and inhibitors (PsRE) [Ionescu and Sburlan, 2004]
- context-free (PsCF) [Sburlan, 2005]

- context (PsRE)
- cooperative (PsRE) [Păun, 1998]
- catalytic
 - with 2 catalysts (PsRE) [Freund et al., 2005]
 - with 1 catalyst (open problem)
 - with 1 catalyst and inhibitors (PsRE) [Ionescu and Sburlan, 2004]
- context-free (PsCF) [Sburlan, 2005]
- context-free with inhibitors (PsET0L) [Ionescu and Sburlan, 2004]

maximal parallelism (PsRE)

- maximal parallelism (PsRE)
- sequential (equals to VASS, [Ibarra et al., 2005])

- maximal parallelism (PsRE)
- sequential (equals to VASS, [Ibarra et al., 2005])
- asynchronous (∼ sequential in most cases) [Freund, 2005]

- maximal parallelism (PsRE)
- sequential (equals to VASS, [Ibarra et al., 2005])
- ullet asynchronous (\sim sequential in most cases) [Freund, 2005]
- minimal parallelism (PsRE) [Ciobanu et al., 2007]

Extensions of sequential P systems

- priorities [Ibarra et al., 2005]
- unbounded membrane creation [Ibarra et al., 2005]

Extensions of sequential P systems

- priorities [Ibarra et al., 2005]
- unbounded membrane creation [Ibarra et al., 2005]
- inhibitors [Kováč, 2014, submitted]

Extensions of sequential P systems

- priorities [Ibarra et al., 2005]
- unbounded membrane creation [Ibarra et al., 2005]
- inhibitors [Kováč, 2014, submitted]
- further study (rules with emptyness detection, ...)

Register machine

Minsky register machine is M = (n, P, i, h), where:

- n is the number of registers
- *P* is a set of labeled instructions of type:
 - (add(r), k, l)
 - (sub(r), k, l)
 - halt
- i is the initial instruction
- h is the final instruction

Simulation of register machine

- Contents of register j is represented by the multiplicity of the object a_j
- For an instruction (add(r), k, l) there is a rule $e \rightarrow a_j | f$
- For an instruction (sub(r), k, l) there are rules
 - $e|a_j \rightarrow f$
 - $e \rightarrow z | a_j$
- Halting rules
 - $h|a_j \to h|\#$ for all $a \le j \le n$
 - \bullet # \rightarrow #

Overview of the simulation for the generating case

- Simulation of a maximal parallel step
- Phases of membranes: RUN and SYNCHRONIZE, represented by objects


 Preventing the rule application on already rewritten objects in the same maximal parallel step

- Preventing the rule application on already rewritten objects in the same maximal parallel step
 - replace objects on the right side a with a'
 - add RESTORE phase

- Preventing the rule application on already rewritten objects in the same maximal parallel step
 - replace objects on the right side a with a'
 - add RESTORE phase
- Sending objects via membranes


- Preventing the rule application on already rewritten objects in the same maximal parallel step
 - replace objects on the right side a with a'
 - add RESTORE phase
- Sending objects via membranes
 - add SENDDOWN phase

Parent and child membrane phases



Obr. : Possible pairs of states of parent and child membrane

Snapshot of all membrane states



Thanks for your attention