

Using Inhibitors to Achieve Universality of Sequential P Systems

Michal Kováč



FMFI UK, Slovakia

24.6.2014

- 1 Overview of P systems
 - P systems
 - Variants

- 2 Sequential P systems with inhibitors
 - Accepting case
 - Generating case

Membrane structure



Sequential vs. maximal parallel rule application

- Sequential: in each step apply 1 rule
- Maximal parallel: in each step apply a maximal multiset of rules


Sequential vs. maximal parallel rule application

- Sequential: in each step apply 1 rule
- Maximal parallel: in each step apply a maximal multiset of rules

$$\begin{array}{lcl} a & | & a \rightarrow a & | & b & (r_1) \\ a & | & b & | & b \rightarrow b & (r_2) \\ & & b \rightarrow c & (r_3) \end{array}$$
$$a & | & a & | & b$$


Sequential vs. maximal parallel rule application

- Sequential: in each step apply 1 rule
- Maximal parallel: in each step apply a maximal multiset of rules



Sequential vs. maximal parallel rule application

- Sequential: in each step apply 1 rule
- Maximal parallel: in each step apply a maximal multiset of rules




Sequential vs. maximal parallel rule application

- Sequential: in each step apply 1 rule
- Maximal parallel: in each step apply a maximal multiset of rules

$$\begin{array}{lcl} a & | & a \rightarrow a & | & b & (r_1) \\ a & | & b & | & b \rightarrow b & (r_2) \\ & & b \rightarrow c & (r_3) \end{array}$$
$$a & | & a & | & b$$


Sequential vs. maximal parallel rule application

- Sequential: in each step apply 1 rule
- Maximal parallel: in each step apply a maximal multiset of rules




Sequential vs. maximal parallel rule application

- Sequential: in each step apply 1 rule
- Maximal parallel: in each step apply a maximal multiset of rules




Sequential vs. maximal parallel rule application

- Sequential: in each step apply 1 rule
- Maximal parallel: in each step apply a maximal multiset of rules




Sequential vs. maximal parallel rule application

- Sequential: in each step apply 1 rule
- Maximal parallel: in each step apply a maximal multiset of rules



Sequential vs. maximal parallel rule application

- Sequential: in each step apply 1 rule
- Maximal parallel: in each step apply a maximal multiset of rules



Language of a P system

- The result of the computation is a multiset of objects, which is present in a specific membrane at a halting configuration
- The language generated by a P system is a set of results of all possible computations.

Variants of rules

- cooperative $(a \mid b \mid b \rightarrow b)$ (universal [Păun, 1998])

Variants of rules

- cooperative ($a \mid b \mid b \rightarrow b$) (universal [Păun, 1998])
- non-cooperative ($b \rightarrow c$) (PsCF [Sburlan, 2005])

Variants of rules

- cooperative ($a \mid b \mid b \rightarrow b$) (universal [Păun, 1998])
- non-cooperative ($b \rightarrow c$) (PsCF [Sburlan, 2005])
- non-cooperative with inhibitors ($a \rightarrow b \mid \neg c, d$) (PsETOL [Ionescu and Sburlan, 2004])

Variants of rules

- cooperative ($a \mid b \mid b \rightarrow b$) (universal [Păun, 1998])
- non-cooperative ($b \rightarrow c$) (PsCF [Sburlan, 2005])
- non-cooperative with inhibitors ($a \rightarrow b \mid_{\neg c, d}$) (PsETOL [Ionescu and Sburlan, 2004])
- catalytic ($a \mid b \rightarrow a \mid c \mid d$)

Variants of rules

- cooperative ($a \mid b \mid b \rightarrow b$) (universal [Păun, 1998])
- non-cooperative ($b \rightarrow c$) (PsCF [Sburlan, 2005])
- non-cooperative with inhibitors ($a \rightarrow b \mid_{\neg c, d}$) (PsETOL [Ionescu and Sburlan, 2004])
- catalytic ($a \mid b \rightarrow a \mid c \mid d$)
 - catalytic with 2 catalysts (universal [Freund et al., 2005])
 - with 1 catalyst (open problem)
 - with 1 catalyst and inhibitors (universal [Ionescu and Sburlan, 2004])

Sequential P systems

Sequential P systems with cooperative rules

Sequential P systems

Sequential P systems with cooperative rules

- are equal to VASS \Rightarrow not universal [Ibarra et al., 2005]
- with priorities are universal [Ibarra et al., 2005]
- with unbounded membrane creation are universal [Ibarra et al., 2005]

Sequential P systems

Sequential P systems with cooperative rules

- are equal to VASS \Rightarrow not universal [Ibarra et al., 2005]
- with priorities are universal [Ibarra et al., 2005]
- with unbounded membrane creation are universal [Ibarra et al., 2005]
- **with inhibitors [Kováč, 2014]**

Overview of the simulation for the accepting case

- Simulation of a register machine
- Contents of register j is represented by the multiplicity of the object a_j
- SUB instruction is simulated by inhibitors

Overview of the simulation for the generating case

- Simulation of a maximal parallel P system
- Start with the same rules


Overview of the simulation for the generating case

- Simulation of a maximal parallel P system
- Start with the same rules

$$a \mid a \rightarrow a \mid b \quad (r_1)$$
$$a \mid b \mid b \rightarrow b \quad (r_2)$$
$$b \rightarrow c \quad (r_3)$$
$$a \mid a \mid b$$


Overview of the simulation for the generating case

- Simulation of a maximal parallel P system
- Start with the same rules



Overview of the simulation for the generating case

- Simulation of a maximal parallel P system
- Start with the same rules




Overview of the simulation for the generating case

- Simulation of a maximal parallel P system
- Start with the same rules

$$a \mid a \rightarrow a \mid b \quad (r_1)$$
$$a \mid b \mid b \rightarrow b \quad (r_2)$$
$$b \rightarrow c \quad (r_3)$$
$$a \mid a \mid b$$


Overview of the simulation for the generating case

- Simulation of a maximal parallel P system
- Start with the same rules




Overview of the simulation for the generating case

- Simulation of a maximal parallel P system
- Start with the same rules




Overview of the simulation for the generating case

- Simulation of a maximal parallel P system
- Start with the same rules




Overview of the simulation for the generating case

- Simulation of a maximal parallel P system
- Start with the same rules



Overview of the simulation for the generating case

- Simulation of a maximal parallel P system
- Start with the same rules



Two phases

- Prevent the rule application on already rewritten objects

Two phases

- Prevent the rule application on already rewritten objects
 - replace objects on the right side a with a'
 - add *RESTORE* phase

Two phases


- Prevent the rule application on already rewritten objects
 - replace objects on the right side a with a'
 - add *RESTORE* phase
- $RUN \mid a \mid a \rightarrow RUN \mid a' \mid b'$
- $RUN \mid a \mid b \mid b \rightarrow RUN \mid b'$
- $RUN \mid b \rightarrow RUN \mid c'$

Two phases


- Prevent the rule application on already rewritten objects
 - replace objects on the right side a with a'
 - add *RESTORE* phase
- $RUN \mid a \mid a \rightarrow RUN \mid a' \mid b'$
- $RUN \mid a \mid b \mid b \rightarrow RUN \mid b'$
- $RUN \mid b \rightarrow RUN \mid c'$
- $RESTORE \mid a' \rightarrow RESTORE \mid a$
- $RESTORE \mid b' \rightarrow RESTORE \mid b$
- $RESTORE \mid c' \rightarrow RESTORE \mid c$

Switching the phases


applying rules




restoring objects



Switching the phases




Switching the phases



- $RUN \mid UNUSABLE_1 \mid UNUSABLE_2 \mid UNUSABLE_3 \rightarrow RESTORE$

Switching the phases



- $RUN \mid UNUSABLE_1 \mid UNUSABLE_2 \mid UNUSABLE_3 \rightarrow RESTORE$
- $RESTORE \rightarrow RUN \mid \neg a' b' c'$

Creating UNUSABLE objects (simple case)

- $(3) : b \rightarrow c$
- $RUN \rightarrow RUN \mid UNUSABLE_3 \mid \neg b, UNUSABLE_3$

Creating UNUSABLE objects (complicated case)

- $(1) : a \mid a \rightarrow a \mid b$
- $RUN \rightarrow RUN \mid UNUSABLE_1 \mid_{\neg a, UNUSABLE_1}$
- Wrong for exactly 1 occurrence of a

Promoting objects

- $RUN \mid a \rightarrow RUN \mid \dot{a} \mid \neg \dot{a}$
- $RUN \mid b \rightarrow RUN \mid \dot{b} \mid \neg \dot{b}$
- $RUN \mid c \rightarrow RUN \mid \dot{c} \mid \neg \dot{c}$
- At most 1 object can be promoted.

Using promoted objects

- $RUN \mid a \mid \dot{a} \rightarrow a' \mid b'$
- $RUN \mid \dot{a} \mid b \mid b \rightarrow b'$
- $RUN \mid \dot{a} \mid \dot{b} \mid b \rightarrow b'$
- $RUN \mid a \mid \dot{b} \mid b \rightarrow b'$
- $RUN \mid \dot{b} \rightarrow c'$

Using promoted objects


- $RUN \mid a \mid \dot{a} \rightarrow a' \mid b'$
- $RUN \mid \dot{a} \mid b \mid b \rightarrow b'$
- $RUN \mid \dot{a} \mid \dot{b} \mid b \rightarrow b'$
- $RUN \mid a \mid \dot{b} \mid b \rightarrow b'$
- $RUN \mid \dot{b} \rightarrow c'$
- $RUN \rightarrow RUN \mid UNUSABLE_3 \mid \neg b, \dot{b}, UNUSABLE_3$
- $RUN \rightarrow RUN \mid UNUSABLE_1 \mid \neg a, UNUSABLE_1$

Multiple different objects on the left side

- $(2) : a \mid b \mid b \rightarrow b$
- $RUN \rightarrow RUN \mid UNUSABLE_2 \mid \neg a, a, UNUSABLE_2$
- $RUN \rightarrow RUN \mid UNUSABLE_2 \mid \neg b, UNUSABLE_2$

Thanks for your attention!

Parent and child membrane phases



The pairs of states of parent and child membrane are joined with possible transitions between two consecutive global synchronizations - after the maximal parallel steps i and $i+1$

Obr. : Possible pairs of states of parent and child membrane

Snapshot of all membrane states

