

PCI Class Codes

Base Class, Sub Class, Extended

Class codes

Base Class	Meaning
00h	Device was built before Class Code definitions were finalized
01h	Mass storage controller
02h	Network controller
03h	Display controller
04h	Multimedia device
05h	Memory controller
06h	Bridge device
07h	Simple communication controllers
08h	Base system peripherals
09h	Input devices
0Ah	Docking stations
0Bh	Processors
0Ch	Serial bus controllers
0Dh	Wireless controller
0Eh	Intelligent I/O controllers
0Fh	Satellite communication controllers
10h	Encryption/Decryption controllers
11h	Data acquisition and signal processing controllers
12h	Processing accelerators
13h	Non-Essential Instrumentation
14h - FEh	Reserved
FFh	Device does not fit in any defined classes

Base Class 00h

Base Class	Sub-Class	Programming Interface	Meaning
00h	00h	00h	All currently implemented devices except VGA-compatible devices
	01h	00h	VGA-compatible device

Base Class 01h

Base Class	Sub-Class	Programming Interface	Meaning
01h	00h	00h	SCSI controller - vendor-specific interface
		11h	SCSI storage device (e.g., hard disk drive (HDD), solid state drive (SSD), or RAID controller) - SCSI over PCI Express (SOP) target port using PCI Express Queuing Interface (PQI) (see Notes 3 and 4)
		12h	SCSI controller (i.e., host bus adapter) - SCSI over PCI Express (SOP) target port using PCI Express Queuing Interface (PQI) (see Notes 3 and 4)
		13h	SCSI storage device and SCSI controller - SCSI over PCI Express (SOP) target port using PCI Express Queuing Interface (PQI) (see Notes 3 and 4)
		21h	SCSI storage device - SCSI over PCI Express (SOP) target port using the queueing interface portion of the NVM Express interface (see Notes 3 and 6)
	01h	xxh	IDE controller (see Note 1)
	02h	00h	Floppy disk controller - vendor-specific interface
	03h	00h	IPI bus controller - vendor-specific interface
	04h	00h	RAID controller - vendor-specific interface
	Table continues on the following page		

Base Class 01h

Base Class	Sub-Class	Programming Interface	Meaning
01h	05h	20h	ATA controller with ADMA interface - single stepping (see Note 2)
		30h	ATA controller with ADMA interface - continuous operation (see Note 2)
	06h	00h	Serial ATA controller - vendor-specific interface
		01h	Serial ATA controller - AHCI interface (see note 7)
		02h	Serial Storage Bus Interface
	07h	00h	Serial Attached SCSI (SAS) controller - vendor-specific interface
		01h	Obsolete
	08h	00h	Non-volatile memory subsystem - vendor-specific interface
		01h	Non-volatile memory subsystem - NVMHCI interface (see note 8)
		02h	NVM Express (NVMe) I/O controller (see Note 6)
		03h	NVM Express (NVMe) administrative controller (see Note 6)
	09h	00h	Universal Flash Storage (UFS) controller - vendor-specific interface
		01h	Universal Flash Storage (UFS) controller - Universal Flash Storage Host Controller Interface (UFSHCI) (see Note 5)
	80h	00h	Other mass storage controller - vendor-specific interface

Base Class 02h

Base Class	Sub-Class	Programming Interface	Meaning
02h	00h	00h	Ethernet controller
	01h	00h	Token Ring controller
	02h	00h	FDDI controller
	03h	00h	ATM controller
	04h	00h	ISDN controller
	05h	00h	WorldFip controller
	06h	xxh (see Note 1 below)	PICMG 2.14 Multi Computing
	07h	00h	InfiniBand* Controller
	08h	00h	Host fabric controller – vendor-specific
	80h	00h	Other network controller

Base Class 03h

Base Class	Sub-Class	Programming Interface	Meaning
03h	00h	0000 0000b	VGA-compatible controller. Memory addresses 0A 0000h through 0B FFFFh. I/O addresses 3B0h to 3BBh and 3C0h to 3DFh and all aliases of these addresses.
		0000 0001b	8514-compatible controller. I/O addresses 2E8h and its aliases, 2EAh-2EFh
	01h	00h	XGA controller
	02h	00h	3D controller
	80h	00h	Other display controller

Base Class 04h

Base Class	Sub-Class	Programming Interface	Meaning
04h	00h	00h	Video device – vendor specific interface
	01h	00h	Audio device – vendor specific interface
	02h	00h	Computer telephony device – vendor specific interface
	03h	00h	High Definition Audio (HD-A) 1.0 compatible (see Note 1)
		80h	High Definition Audio (HD-A) 1.0 compatible (see Note 1) with additional vendor specific extensions
	80h	00h	Other multimedia device – vendor specific interface

Base Class 05h

Base Class	Sub-Class	Programming Interface	Meaning
05h	00h	00h	RAM
	01h	00h	Flash
	80h	00h	Other memory controller

Base Class 06h

Base Class	Sub-Class	Programming Interface	Meaning
06h	00h	00h	Host bridge
	01h	00h	ISA bridge
	02h	00h	EISA bridge
	03h	00h	MCA bridge
	04h	00h	PCI-to-PCI bridge
		01h	Subtractive Decode PCI-to-PCI bridge. This interface code identifies the PCI-to-PCI bridge as a device that supports subtractive decoding in addition to all the currently defined functions of a PCI-to-PCI bridge.
	05h	00h	PCMCIA bridge
	06h	00h	NuBus bridge
	07h	00h	CardBus bridge
	08h	xxh	RACEway bridge (see Note 1 below)
	09h	40h	Semi-transparent PCI-to-PCI bridge with the primary PCI bus side facing the system host processor
		80h	Semi-transparent PCI-to-PCI bridge with the secondary PCI bus side facing the system host processor
	0Ah	00h	InfiniBand-to-PCI host bridge
	0Bh	00h	Advanced Switching to PCI host bridge—Custom Interface
		01h	Advanced Switching to PCI host bridge—ASI-SIG Defined Portal Interface
	80h	00h	Other bridge device

Base Class 07h

Base Class	Sub-Class	Programming Interface	Meaning
07h	00h	00h	Generic XT-compatible serial controller
		01h	16450-compatible serial controller
		02h	16550-compatible serial controller
		03h	16650-compatible serial controller
		04h	16750-compatible serial controller
		05h	16850-compatible serial controller
		06h	16950-compatible serial controller
	01h	00h	Parallel port
		01h	Bi-directional parallel port
		02h	ECP 1.X compliant parallel port
		03h	IEEE1284 controller
		FEh	IEEE1284 target device (not a controller)
	02h	00h	Multiport serial controller
	03h	00h	Generic modem
		01h	Hayes compatible modem, 16450-compatible interface (see Note 1 below)
		02h	Hayes compatible modem, 16550-compatible interface (see Note 1 below)
		03h	Hayes compatible modem, 16650-compatible interface (see Note 1 below)
		04h	Hayes compatible modem, 16750-compatible interface (see Note 1 below)
	04h	00h	GPIB (IEEE 488.1/2) controller
	05h	00h	Smart Card
	80h	00h	Other communications device

Base Class 08h

Base Class	Sub-Class	Programming Interface	Meaning
08h	00h	00h	Generic 8259 PIC
		01h	ISA PIC
		02h	EISA PIC
		10h	I/O APIC interrupt controller (see Note 1 below)
		20h	I/O(x) APIC interrupt controller
	01h	00h	Generic 8237 DMA controller
		01h	ISA DMA controller
		02h	EISA DMA controller
	02h	00h	Generic 8254 system timer
		01h	ISA system timer
		02h	EISA system timers (two timers)
		03h	High Performance Event Timer
	03h	00h	Generic RTC controller
		01h	ISA RTC controller
	04h	00h	Generic PCI Hot-Plug controller
	05h	00h	SD Host controller
	06h	00h	IOMMU
	07h	00h	Root Complex Event Collector (see Note 2 below)
	80h	00h	Other system peripheral

Notes:

Base Class 09h

Base Class	Sub-Class	Programming Interface	Meaning
09h	00h	00h	Keyboard controller
	01h	00h	Digitizer (pen)
	02h	00h	Mouse controller
	03h	00h	Scanner controller
	04h	00h	Gameport controller (generic)
		10h	Gameport controller (see Note 1 below)
	80h	00h	Other input controller

Notes:

Base Class 0Ah

Base Class	Sub-Class	Programming Interface	Meaning
0Ah	00h	00h	Generic docking station
	80h	00h	Other type of docking station

Base Class 0Bh

Base Class	Sub-Class	Programming Interface	Meaning
0Bh	00h	00h	386
	01h	00h	486
	02h	00h	Pentium
	10h	00h	Alpha
	20h	00h	PowerPC
	30h	00h	MIPS
	40h	00h	Co-processor
	80h	00h	Other processors

Base Class 0Ch

Base Class	Sub-Class	Programming Interface	Meaning
0Ch	00	00h	IEEE 1394 (FireWire)
		10h	IEEE 1394 following the 1394 OpenHCI specification
	01h	00h	ACCESS.bus
	02h	00h	SSA
	03h	00h	Universal Serial Bus (USB) following the Universal Host Controller Specification
		10h	Universal Serial Bus (USB) following the Open Host Controller Specification
		20h	USB 2 host controller following the Intel Enhanced Host Controller Interface Specification
		30h	Universal Serial Bus (USB) Host Controller following the Intel eXtensible Host Controller Interface (xHCI) Specification
		80h	Universal Serial Bus with no specific Programming Interface
		FEh	USB device (not host controller)
	04h	00h	Fibre Channel
	05h	00h	SMBus (System Management Bus)
	06h	00h	InfiniBand—This sub-class is deprecated. New InfiniBand adapters should use the base class and sub-class defined in Section 1.3 .
	07h (see Note 1 below)	00h	IPMI SMIC Interface
		01h	IPMI Keyboard Controller Style Interface
		02h	IPMI Block Transfer Interface
	08h (see Note 2 below)	00h	SERCOS Interface Standard (IEC 61491)
	09h	00h	CANbus
	0Ah (see Note 3 below)	00h	MIPI I3C℠ Host Controller Interface
	80h	00h	Other Serial Bus Controllers

Notes:

Base Class 0Dh

Base Class	Sub-Class	Programming Interface	Meaning
0Dh	00	00h	iRDA compatible controller
	01h	00h	Consumer IR controller
		10h	UWB Radio controller
	10h	00h	RF controller
	11h	00h	Bluetooth
	12h	00h	Broadband
	20h	00h	Ethernet (802.11a – 5 GHz)
	21h	00h	Ethernet (802.11b – 2.4 GHz)
	40h	00h	Cellular controller/modem
	41h	00h	Cellular controller/modem plus Ethernet (802.11)
	80h	00h	Other type of wireless controller

Base Class 0Eh

Base Class	Sub-Class	Programming Interface	Meaning
0Eh	00	xxh	*Intelligent I/O (I2O) Architecture Specification 1.0*
		00h	Message FIFO at offset 040h

Base Class 0Fh

Base Class	Sub-Class	Programming Interface	Meaning
0Fh	01h	00h	TV
	02h	00h	Audio
	03h	00h	Voice
	04h	00h	Data
	80h	00h	Other satellite communication controller

Base Class 10h

Base Class	Sub-Class	Programming Interface	Meaning
10h	00h	00h	Network and computing encryption and decryption controller
	10h	00h	Entertainment encryption and decryption controller
	80h	00h	Other encryption and decryption controller

Base Class 11h

Base Class	Sub-Class	Programming Interface	Meaning
11h	00h	00h	DPIO modules
	01h	00h	Performance counters
	10h	00h	Communications synchronization plus time and frequency test/measurement
	20h	00h	Management card
	80h	00h	Other data acquisition/signal processing controllers

Base Class 12h

Base Class	Sub-Class	Programming Interface	Meaning
12h	00h	00h	Processing Accelerator – vendor-specific interface

Base Class 13h

Base Class	Sub-Class	Programming Interface	Meaning
13h	00h	00h	Non-Essential Instrumentation Function – Vendor-specific interface

PCI Express Capability Structure



Capability IDs

ID	Capability
00h	Null Capability – This capability contains no registers other than those described below. It may be present in any Function. Functions may contain multiple instances of this capability. The Null Capability is 16 bits and contains an 8-bit Capability ID followed by an 8-bit Next Capability Pointer.
01h	PCI Power Management Interface – This Capability structure provides a standard interface to control power management features in a device Function. It is fully documented in the *PCI Bus Power Management Interface Specification*.
02h	AGP – This Capability structure identifies a controller that is capable of using Accelerated Graphics Port features. Full documentation can be found in the *Accelerated Graphics Port Interface Specification*.
03h	VPD – This Capability structure identifies a device Function that supports Vital Product Data. Full documentation of this feature can be found in the *PCI Local Bus Specification*.
04h	Slot Identification – This Capability structure identifies a bridge that provides external expansion capabilities. Full documentation of this feature can be found in the *PCI-to-PCI Bridge Architecture Specification*.
05h	Message Signaled Interrupts – This Capability structure identifies a device Function that can do message signaled interrupt delivery. Full documentation of this feature can be found in the *PCI Local Bus Specification*.
06h	CompactPCI Hot Swap – This Capability structure provides a standard interface to control and sense status within a device that supports Hot Swap insertion and extraction in a CompactPCI system. This Capability is documented in the *CompactPCI Hot Swap Specification PICMG 2.1, R1.0* available at http://www.picmg.org.
07h	PCI-X – Refer to the *PCI-X Protocol Addendum to the PCI Local Bus Specification* for details.

Capability IDs

ID	Capability
08h	HyperTransport – This Capability structure provides control and status for devices that implement HyperTransport Technology links. For details, refer to the *HyperTransport I/O Link Specification* available at http://www.hypertransport.org.
09h	Vendor Specific – This Capability structure allows device vendors to use the Capability mechanism to expose vendor-specific registers. The byte immediately following the Next Pointer in the Capability structure is defined to be a length field. This length field provides the number of bytes in the Capability structure (including the Capability ID and Next Pointer bytes). All remaining bytes in the capability structure are vendor-specific.
0Ah	Debug port
0Bh	CompactPCI central resource control – Definition of this Capability can be found in the *PICMG 2.13 Specification* (http://www.picmg.com).
0Ch	PCI Hot-Plug – This Capability ID indicates that the associated device conforms to the Standard Hot-Plug Controller model.
0Dh	PCI Bridge Subsystem Vendor ID
0Eh	AGP 8x
0Fh	Secure Device
10h	PCI Express
11h	MSI-X – This Capability ID identifies an optional extension to the basic MSI functionality.
12h	Serial ATA Data/Index Configuration
13h	Advanced Features (AF) – Full documentation of this feature can be found in the *Advanced Capabilities for Conventional PCI ECN*.
14h	Enhanced Allocation
15h	Flattening Portal Bridge
Others	Reserved

PCIe Extended Capability Structure



Extended Capability ID

ID	Extended Capability
0000h	Null Capability – This capability contains no registers other than those in the Extended Capability Header. It may be present in any Function. Functions may contain multiple instances of this capability. The Null Extended Capability is 32 bits and contains only an Extended Capability Header. The Capability Version field of a Null Extended Capability is not meaningful and may contain any value.
0001h	Advanced Error Reporting (AER)
0002h	Virtual Channel (VC) – used if an MFVC Extended Cap structure is not present in the device
0003h	Device Serial Number
0004h	Power Budgeting
0005h	Root Complex Link Declaration
0006h	Root Complex Internal Link Control
0007h	Root Complex Event Collector Endpoint Association
0008h	Multi-Function Virtual Channel (MFVC)
0009h	Virtual Channel (VC) – used if an MFVC Extended Cap structure is present in the device
000Ah	Root Complex Register Block (RCRB) Header
000Bh	Vendor-Specific *Extended Capability* (VSEC)
000Ch	Configuration Access Correlation (CAC) – defined by the *Trusted Configuration Space (TCS) for PCI Express ECN*, which is no longer supported
000Dh	Access Control Services (ACS)
000Eh	Alternative Routing-ID Interpretation (ARI)
000Fh	Address Translation Services (ATS)
0010h	Single Root I/O Virtualization (SR-IOV)

Extended Capability ID

ID	Extended Capability
0011h	Multi-Root I/O Virtualization (MR-IOV) — defined in the *Multi-Root I/O Virtualization and Sharing Specification*
0012h	Multicast
0013h	Page Request Interface (PRI)
0014h	Reserved for AMD
0015h	Resizable BAR
0016h	Dynamic Power Allocation (DPA)
0017h	TPH Requester
0018h	Latency Tolerance Reporting (LTR)
0019h	Secondary PCI Express
001Ah	Protocol Multiplexing (PMUX)
001Bh	Process Address Space ID (PASID)
001Ch	LN Requester (LNR)
001Dh	Downstream Port Containment (DPC)
001Eh	L1 PM Substates
001Fh	Precision Time Measurement (PTM)
0020h	PCI Express over M-PHY (M-PCIe)
0021h	FRS Queueing
0022h	Readiness Time Reporting
0023h	Designated Vendor-Specific Extended Capability
0024h	VF Resizable BAR
0025h	Data Link Feature
0026h	Physical Layer 16.0 GT/s
0027h	Lane Margining at the Receiver
0028h	Hierarchy ID
0029h	Native PCIe Enclosure Management (NPEM)
002Ah	Physical Layer 32.0 GT/s
002Bh	Alternate Protocol
002Ch	System Firmware Intermediary (SFI)
Others	Reserved

Extended Capability ID

Web : www.neeveetech.com
E-Mail : nvhariharan@neeveetech.com
Youtube : https://www.youtube.com/user/neeveehariharan
Facebook : https://www.facebook.com/neeveetech/
Linkedin : https://www.linkedin.com/in/neeveehariharan/

Thank You.