



## --NOTE--

- \* `A` 4개소 V컷팅 후 용접 할 것. \* 일반 모따기는 (0.2~0.5로 할 것. \* 날카로운 모서리 제거 할 것.

	CLASS OF	FINISH	GENERAL	TOL.(MAC	CHINE)	015		FFU_B	RACH	KET	ST	S304 (	00.	D 1232.0 X 1232.0 X 3.0T	E	. P
	~	_	NORMAL DIM.(MM) TOL.			NO	DESCRIPTION			MAT	MATERIAL		SIZE REMARK		MARK	
		50 S	S OVER 0.5 UNDER 6 ±0.1					DE:	SIGNED	CHECKED	APPROVED					
		$ 12.5 \text{ S} $ 6 $ 30 \pm 0.2 $		ł							]_,,,	GLASS ROLLER C/V				
$\neg$ [		3.2 \$	30	120	<u></u> ±0.3	1							TITLE	 	DII	
		0.8 \$	120	315	±0.5	1								삼성전자/탕정/#T	-     -	
			315		±0.8	1			DEI	-		l	DWC			R00
$\exists$			1000		<u> ±1.2</u>	UNIT 1	MM S	CALE 1/1	0 NO	·			DWG.	3-GUC   NL0 -00 5		
<u> </u>			OVER	2000	土1.5				_ N(	J			INU			2008.07.30

NO	REVISION	발 생 내 용	DATE	APPROVED

