

Lab: Data Aggregation

This document defines the **lab exercise assignments** for the ["Databases Basics - MySQL" course @ Software University](#).

Download and get familiar with the **restaurant** database. You will use it in the assignments bellow.

1. Departments Info

Write a query to **count** the number of employees in each department by **id**. Order the information by **department_id**, then by **employees count**. Submit your queries with the **MySQL prepare DB & run queries** strategy.

Example

department_id	Number of employees
1	2
2	4
3	3
...	...

2. Average Salary

Write a query to calculate the **average salary** in each department. Order the information by **department_id**. **Round** the salary result to **two digits after the decimal point**. Submit your queries with the **MySQL prepare DB & run queries** strategy.

Example

department_id	Average Salary
1	2050
2	1090
3	736.67

3. Min Salary

Write a query to retrieve information about the departments grouped by **department_id** with **minumum salary higher than 800**. **Round** the salary result to **two digits after the decimal point**. Submit your queries with the **MySQL prepare DB & run queries** strategy.

Example

department_id	Min Salary
1	1700

4. Appetizers Count

Write a query to retrieve the count of all **appetizers** (**category id = 2**) with price **higher than 8**. Submit your queries with the **MySQL prepare DB & run queries** strategy.

5. Menu Prices

Write a query to retrieve information about the prices of each category. The output should consist of:

- **Category_id**
- **Average Price**
- **Cheapest Product**
- **Most Expensive Product**

See the **examples** for more information. **Round** the results to **2 digits after the decimal point**. Submit your queries with the **MySQL prepare DB & run queries** strategy.

Example

category_id	Average Price	Cheapest Product	Most Expensive Product
1	7.49	6.79	8.79
2	10.93	7.99	14.89
3	7.90	6.90	8.89
4	12.79	11.69	13.69
5	5.37	4.90	5.60

Exercises: Data Aggregation

This document defines the **exercise assignments** for the ["Databases Basics - MySQL" course @ Software University](#).

Mr. Bodrog is a greedy small goblin. His most precious possession is a small database of the deposits in the wizard's world. Mr. Bodrog wants you to send him some reports.

Get familiar with the **gringotts** database. You will use it in the assignments below.

1. Records' Count

Import the database and send the **total count of records** to Mr. Bodrog. Make sure nothing got lost.

Example:

count
162

2. Longest Magic Wand

Select the size of the **longest magic wand**. Rename the new column appropriately.

Example:

longest_magic_wand
31

3. Longest Magic Wand per Deposit Groups

For wizards in each deposit group show the longest magic wand. **Sort result by longest magic wand** for each deposit group in **increasing order**, then by **deposit_group** alphabetically. Rename the new column appropriately.

Example:

deposit_group	longest_magic_wand
Human Pride	30
...	...

4. Smallest Deposit Group per Magic Wand Size*

Select the deposit group with the **lowest** average wand size.

Example:

deposit_group
Troll Chest

5. Deposits Sum

Select all deposit groups and its **total deposit sum**. Sort result by **total_sum** in **increasing order**.

Example:

deposit_group	total_sum
Blue Phoenix	819598.73
...	...

6. Deposits Sum for Ollivander family

Select all deposit groups and its total deposit sum but **only for the wizards who has their magic wand crafted by Ollivander family**. Sort result by **deposit_group** alphabetically.

Example:

deposit_group	total_sum
Blue Phoenix	52968.96
Human Pride	188366.86
...	...

7. Deposits Filter

Select all deposit groups and its total deposit sum but **only for the wizards who has their magic wand crafted by Ollivander family**. After this, **filter** total deposit sums **lower than 150000**. Order by total deposit sum in **descending order**.

Example:

deposit_group	total_sum
Troll Chest	126585.18
...	...

8. Deposit charge

Create a query that selects:

- **Deposit group**
- **Magic wand creator**
- **Minimum deposit charge for each group**

Group by **deposit_group** and **magic_wand_creator**.

Select the data in **ascending order** by **magic_wand_creator** and **deposit_group**.

Example:

deposit_group	magic_wand_creator	min_deposit_charge
Blue Phoenix	Antioch Peverell	30.00
...	...	

9. Age Groups

Write down a query that creates 7 different groups **based on their age**.

Age groups should be as follows:

- [0-10]
- [11-20]
- [21-30]
- [31-40]
- [41-50]
- [51-60]
- [61+]

The query should return:

- Age groups
- Count of wizards in it

Sort result by **increasing size** of age groups.

Example:

age_group	wizard_count
[11-20]	21
...	...

10. First Letter

Write a query that returns all **unique** wizard **first letters of their first names only if they have deposit of type Troll Chest**. Order them **alphabetically**. Use **GROUP BY** for uniqueness.

Example:

first_letter
A
...

11. Average Interest

Mr. Bodrog is highly interested in profitability. He wants to know the average interest of all deposits groups split by whether the deposit **has expired** or **not**. But that's not all. He wants you to select deposits with **start date after 01/01/1985**. Order the data **descending** by Deposit Group and **ascending** by Expiration Flag.

Example:

deposit_group	is_deposit_expired	average_interest
Venomous Tongue	0	16.698947
...

12. Rich Wizard, Poor Wizard*

Give Mr. Bodrog some data to play his favorite game Rich Wizard, Poor Wizard. The rules are simple: You compare the deposits of every wizard with the wizard after him. If a wizard is the last one in the database, simply ignore it. At the end you have to sum the difference between the deposits.

host_wizard	host_wizard_deposit	guest_wizard	guest_wizard_deposit	difference
Harry	10 000	Tom	12 000	-2000
Tom	12 000

At the end your query should return a single value: the **SUM** of all differences.

Example:

sum_difference
44393.97

13. Employees Minimum Salaries

That's it! You no longer work for Mr. Bodrog. You have decided to find a proper job as an analyst in **SoftUni**.

It's not a surprise that you will use the **soft_uni** database.

Select the minimum salary from the employees for departments with **ID (2,5,7)** but only for those who are **hired after 01/01/2000**. Sort result by **department_id** in **ascending** order.

Your query should return:

- **department_id**

Example:

department_id	minimum_salary
2	25000.00
...	...

14. Employees Average Salaries

Select all high paid employees who earn **more than 30000** into a new table. Then **delete** all high paid employees who have **manager_id = 42** from the new table; Then **increase** the salaries of all high paid employees with **department_id = 1 with 5000** in the new table. Finally, select the **average** salaries in each department from the new table. Sort result by **department_id** in **increasing** order.

Example:

department_id	avg_salary
1	45166.6666
...	...

15. Employees Maximum Salaries

Find the **max** salary for each department. Filter those which have max salaries **not in the range 30000 and 70000**. Sort result by **department_id** in **increasing** order.

Example:

department_id	max_salary
2	29800.00
...	...

16. Employees Count Salaries

Count the salaries of all employees who **don't have a manager**.

17. 3rd Highest Salary*

Find the **third highest salary** in each department if there is such. Sort result by **department_id** in **increasing** order.

Example:

department_id	third_highest_salary
1	36100.00
2	25000.00
...	...

18. Salary Challenge**

Write a query that returns:

- **first_name**
- **last_name**
- **department_id**

for all employees who have salary **higher than the average salary** of their respective departments. Select only the **first 10 rows**. Order by **department_id**.

Example:

first_name	last_name	department_id
Roberto	Tamburello	1
Terri	Duffy	1
Rob	Walters	2
...

19. Departments Total Salaries

Create a query which shows the **total sum of salaries** for each department. Order by **department_id**.

Your query should return:

- **department_id**

Example:

department_id	total_salary
1	241000.00
...	...