Activity 11 - Verify Feature Store Point-in-Time Parity

Course: Google Professional Machine Learning Engineer Training Course code: C740 Version: v2.0 | 12 September 2026 Evidence: activity artifacts

Objective

Model offline/online feature definitions and detect stale or leaked features.

Deliverables

- offline_features.csv
- online_features.csv
- check_parity.py
- feature_view.yaml
- A completed evidence/ folder with decision notes and verification output

Prerequisites

- Python 3.11 or later and a terminal; Docker only where the activity explicitly uses it.
- For optional live Google Cloud steps: the safe training project created in Activity 01.
- Start in this activity folder so relative paths and cleanup commands remain scoped.

Safety, cost and privacy

- Use a training project that contains no production or personal data.
- Replace every placeholder such as <PROJECT_ID> and <REGION> before a cloud command.
- Do not paste API keys or service-account JSON into notebooks, scripts or screenshots.
- Prefer Cloud Shell and Application Default Credentials. Never commit .env or credentials.
- Verify the result against the acceptance checklist, then run the cleanup section.

Evidence to retain

Create an evidence/ folder locally. Save command output, job or revision IDs, metric tables, screenshots without secrets, and a short decision note. Use filenames that include the activity number and date. Evidence is part of the learning outcome, not an optional extra.

Detailed step-by-step guide

Step 1 - Inspect feature_view.yaml and identify the entity key, feature names, online TTL and source timestamp

Inspect feature_view.yaml and identify the entity key, feature names, online TTL and source timestamp.

Check: Record the observable result or explain the error before continuing.

Step 2 - Run the parity checker on the offline and online snapshots

Run the parity checker on the offline and online snapshots.

```
python3 check_parity.py --offline offline_features.csv --online online_features.csv
```

Check: Record the observable result or explain the error before continuing.

Step 3 - Separate point-in-time leakage from stale online values; they require different fixes

Separate point-in-time leakage from stale online values; they require different fixes.

Check: Record the observable result or explain the error before continuing.

Step 4 - Trace a mismatched entity through key normalization and timestamp selection

Trace a mismatched entity through key normalization and timestamp selection.

Check: Record the observable result or explain the error before continuing.

Step 5 - Set a freshness SLO and specify the monitoring window and alert persistence

Set a freshness SLO and specify the monitoring window and alert persistence.

Check: Record the observable result or explain the error before continuing.

Step 6 - Create a golden entity lookup and assert identical transformed values for batch and online paths

Create a golden entity lookup and assert identical transformed values for batch and online paths.

Check: Record the observable result or explain the error before continuing.

Step 7 - Record mismatches, root cause, remediation and the feature-definition version

Record mismatches, root cause, remediation and the feature-definition version.

Check: Record the observable result or explain the error before continuing.

Acceptance checklist

[ ] Every required artifact exists and opens without error.

[ ] Results are tied to the supplied mock data or an approved training project.

[ ] The conclusion cites metrics, IDs or command output rather than opinion alone.

[ ] No credentials, tokens, personal data or unredacted sensitive prompts are present.

[ ] Cleanup is completed or the retained resource is documented with an owner and expiry.

Troubleshooting

Symptom	Likely cause	Corrective action
403 PERMISSION_DENIED	API disabled, wrong project, or IAM role missing	Verify gcloud config get-value project, API state and the least-privilege role.
429 RESOURCE_EXHAUSTED	Quota or rate limit reached	Stop retries, inspect quota, add exponential backoff, and ask the trainer before increasing quota.
Region/location mismatch	Dataset, bucket, model or endpoint uses another location	Recreate only the training resource in one approved region; do not copy sensitive data casually.
Result differs from expected	Data, dependency or configuration version drifted	Compare file hashes, pinned versions and parameters; retain the diff as evidence.

Cleanup

Stop local processes and remove only resources created for this activity. For live cloud work, use the Console resource views and activity evidence to verify deletion. Do not delete a shared project, dataset, bucket, registry or endpoint unless the trainer identifies it as disposable.