Activity 13 - Serve a Model on Cloud Run

Course: Google Professional Machine Learning Engineer Training Course code: C740 Version: v2.0 | 12 September 2026 Evidence: activity artifacts

Objective

Package a Flask prediction API, test its contract and analyze load-test results.

Deliverables

- app.py
- Dockerfile
- requirements.txt
- test_api.py
- load_results.csv
- A completed evidence/ folder with decision notes and verification output

Prerequisites

- Python 3.11 or later and a terminal; Docker only where the activity explicitly uses it.
- For optional live Google Cloud steps: the safe training project created in Activity 01.
- Start in this activity folder so relative paths and cleanup commands remain scoped.

Safety, cost and privacy

- Use a training project that contains no production or personal data.
- Replace every placeholder such as <PROJECT_ID> and <REGION> before a cloud command.
- Do not paste API keys or service-account JSON into notebooks, scripts or screenshots.
- Prefer Cloud Shell and Application Default Credentials. Never commit .env or credentials.
- Verify the result against the acceptance checklist, then run the cleanup section.

Evidence to retain

Create an evidence/ folder locally. Save command output, job or revision IDs, metric tables, screenshots without secrets, and a short decision note. Use filenames that include the activity number and date. Evidence is part of the learning outcome, not an optional extra.

Detailed step-by-step guide

Step 1 - Create a virtual environment and install pinned dependencies

Create a virtual environment and install pinned dependencies.

```
python3 -m venv .venv
source .venv/bin/activate
pip install -r requirements.txt
```

Check: Record the observable result or explain the error before continuing.

Step 2 - Run the Flask service locally and verify /health before using /predict

Run the Flask service locally and verify /health before using /predict.

```
python3 app.py
```

Check: Record the observable result or explain the error before continuing.

Step 3 - In another terminal, run the API contract tests

In another terminal, run the API contract tests.

```
python3 test_api.py --base-url http://127.0.0.1:8080
```

Check: Record the observable result or explain the error before continuing.

Step 4 - Build the container and run the same health and prediction tests against it

Build the container and run the same health and prediction tests against it.

```
docker build -t pmle-api:v8 .
docker run --rm -p 8080:8080 pmle-api:v8
```

Check: Record the observable result or explain the error before continuing.

Step 5 - Inspect load_results.csv; plot QPS against p95 latency and identify saturation

Inspect load_results.csv; plot QPS against p95 latency and identify saturation.

Check: Record the observable result or explain the error before continuing.

Step 6 - Draft a Cloud Run deployment with authenticated ingress, min/max instances and region

Draft a Cloud Run deployment with authenticated ingress, min/max instances and region.

Check: Record the observable result or explain the error before continuing.

Step 7 - Deploy only if approved, then record revision ID and image digest

Deploy only if approved, then record revision ID and image digest.

Check: Record the observable result or explain the error before continuing.

Step 8 - Test one invalid schema and confirm the service returns a controlled 4xx response without secrets

Test one invalid schema and confirm the service returns a controlled 4xx response without secrets.

Check: Record the observable result or explain the error before continuing.

Acceptance checklist

[ ] Every required artifact exists and opens without error.

[ ] Results are tied to the supplied mock data or an approved training project.

[ ] The conclusion cites metrics, IDs or command output rather than opinion alone.

[ ] No credentials, tokens, personal data or unredacted sensitive prompts are present.

[ ] Cleanup is completed or the retained resource is documented with an owner and expiry.

Troubleshooting

Symptom	Likely cause	Corrective action
403 PERMISSION_DENIED	API disabled, wrong project, or IAM role missing	Verify gcloud config get-value project, API state and the least-privilege role.
429 RESOURCE_EXHAUSTED	Quota or rate limit reached	Stop retries, inspect quota, add exponential backoff, and ask the trainer before increasing quota.
Region/location mismatch	Dataset, bucket, model or endpoint uses another location	Recreate only the training resource in one approved region; do not copy sensitive data casually.
Result differs from expected	Data, dependency or configuration version drifted	Compare file hashes, pinned versions and parameters; retain the diff as evidence.

Cleanup

Stop local processes and remove only resources created for this activity. For live cloud work, use the Console resource views and activity evidence to verify deletion. Do not delete a shared project, dataset, bucket, registry or endpoint unless the trainer identifies it as disposable.