

```
# -*- coding: utf-8 -*-
"""
=====
=====
HUNTER MAFIA – TO'LIQ VERSIYA v7
(pyTelegramBotAPI / telebot, sinxron)
=====
=====

YANGI (v7) – Admin panelga 3 ta yangi,
TO'LIQ ISHLAYDIGAN owner-funksiyasi
qo'shildi (mavjud hech bir funksiya
o'chirilmadi/qisqartirilmadi, faqat
qo'shildi):

1) 🔍 /useri <user_id yoki reply> –
istalgan foydalanuvchining TO'LIQ
profilini (balans, statistika, ELITE
holati, oila, geroy, ban holati)
bitta xabarda ko'rsatadi, tagida
tezkor "Ban/Unban" va "30 kun ELITE
berish" tugmalari bilan.

2) 📭 /guruhdan_chiq <chat_id> – botni
istalgan guruhdan HAQIQIY Telegram
API (leave_chat) orqali chiqaradi va
known_groups bazasidan o'chiradi.

3) 🗑️ /elite_ber <kun> (reply) –
istalgan foydalanuvchiga qo'lda, xohlagan
muddatga HUNTER ELITE (VIP) beradi;
mavjud grant_elite_days() ustiga
```

qurilgan – sotib olingan ELITE bilan
100% mos (muddatlar qo'shiladi).

Har uchulasi ham  Admin panel
tugmalari orqali ham chaqiriladi.

YANGI (v6) – "Almex Black Bot" tahlili
asosida qo'shilgan, TO'LIQ ISHLAYDIGAN
HUNTER ELITE tizimi (fayl oxirida, "ISHGA
TUSHIRISH" bo'limidan oldin joylashgan):

-  /elite – tarifli VIP obuna (7 / 15
/ 30 kun), narxi Olmosda YOKI

Telegram Stars'da ko'rsatiladi,
ikkalasi ham haqiqiy ishlaydi (Olmos –
darhol balamcdan yechiladi; Stars –
send_invoice orqali, to'lov
muvaqqiyatli o'tgach avtomatik
faollashadi). Mavjud "VIP" (charges
ustunidagi vip_until) infratuzilmasi
ustiga qurilgan – eski /birja
orqali olingan VIP bilan TO'LIQ mos,
muddatlar bir-biriga QO'SHILADI.

-  /taxallus <laqab> – faqat ELITE
a'zolar uchun shaxsiy laqab. Guruhda
chaqirilsa, Almex'dagidek  / 
jamoaviy tasdiqlash ovoz berishi ochiladi
(30 soniya); DM'da chaqirilsa darhol
o'rnatiladi. Tasdiqlangan laqab
keyin BUTUN botda (o'yin e'lonlari,
o'lim xabarlari, reyting)  nishoni
bilan birga ko'rinadi (mention()
funksiyasi kengaytirildi).

-  /til – 7 tilli

(Turkcha/English/Rus/Ukrain/Qozoq/O'zbek/Indonez) til

tanlash menyusi. Tanlangan til ELITE/laqab/sovg'a xabarlarida ishlaydi – botning asosiy o'yin matnlari ataylab o'zbekcha qoladi (soxta "to'liq tarjima" va'da qilinmadi, faqat haqiqatan tarjima qilingan qism ishlaydi).

- 📁 /sovg'a – ro'yxatdan o'tgan boshqa foydalanuvchiga Olmos sovg'a qilish (reply orqali yoki Telegram ID orqali) – real balans o'tkazmasi.

- 🏠 /chiqish – ELITE a'zolari uchun o'yin lobbysidan istalgan payt chiqish.

Bularning barchasi UCHUN yangi DB ustuni QO'SHILMAGAN – hammasi mavjud "charges" JSON ustunida saqlanadi, shuning uchun eski foydalanuvchilarning balansi, inventari, statistikasi va h.k. 100% saqlanib qoladi.

=====

YANGI (v5) – QO'SHIMCHA FAYLLARDAN QO'SHILGAN BARCHA FUNKSIYALAR:

kod1.py / kod4.py g'oyasi:

- 🧑 Har bir o'yinchiga o'yin boshida shaxsiy MAXFIY MISSIYA beriladi (DM orqali).

- 🎲 Kunduzi 15% ehtimol bilan kutilmagan RANDOM EVENT chiqadi.

- 🇺🇦 VIP tushunchasi allaqachon

do'konda "🏠 VIP Litsenziya" sifatida mavjud.

kod2.py g'oyasi:

- 🌙 Tun boshlanganda, tirik o'yinchilarning rollariga qarab har xil ATMOSFERA (hikoya) matnlari guruhga yuboriladi (23 ta qo'shimcha rol uchun).

kod3.py g'oyasi:

- Do'kon menyusi va foydalanuvchi statistikasi (o'ynagan o'yinlar, g'alabalar)

allaqachon asosiy botning /profile va do'kon tizimida to'liq mavjud edi.

kod5.py g'oyasi:

- 🛒 QORA BOZOR – o'yinchilar o'rtasidagi savdo tizimi TO'LIQ qo'shildi:

/sell (inventarni ko'rish yoki sotuvga qo'yish), /market (faol e'lonlar), /buy (xarid), xarid tasdiqlash/bekor qilish tugmalari – barchasi endi

haqiqiy SQLite bazasida (market_listings jadvali) ishlaydi.

kod6.py g'oyasi (aiogram'dan telebot'ga moslashtirildi):

- 🎉 SOVG'A TARQATISH – /tarqatish buyrug'i, "olish" tugmasi bilan.

kod8.py g'oyasi:

- ⚡ Admin panelga qo'shimcha bo'limlar: Promo-kod va Balans boshqaruvi.
- 📺 PROMO-KOD tizimi to'liq qo'shildi: /promo_create (admin), /promo (foydalanuvchi).

kod9.py g'oyasi:

- 🏰 KLANLAR JANGI – foydalanuvchi yuborgan TXT texnik topshiriq asosida TO'LIQ tizim:

klan darajalari (1-3, xarajat va cheklovlar bilan), lider/o'rinbosar, a'zo darajalari,

Ritsar/Sehrgar maqomlari, klan xazinasi (dollar+olmos), jang taklifi (jangga chiqish /

taslim bo'lish / rad etish), g'alaba-mag'lubiyat iqtisodiyoti, ketma-ket g'alaba uchun

olmos mukofoti, 3 oylik TOP klan mukofotlari, 30 kunlik faolsizlik jarimasi.

Buyruqlar: /klan, /klanim, /klanga_qoshil, /klan_tark, /klan_chetlash, /klan_orinbosar,

/klan_azo_daraja, /klan_lvl, /klan_nomi, /klan_maqom, /klan_hazna, /klan_taqsimla,

/klanlar, /klanjang, /klan_mukofot.

- 😊 Duelda va klan jangida yutqazganlarga hazil-mutoyiba xabarlari (DEFEAT_JOKES).

botMalumotlari.py g'oyasi:
- get_or_create_user / add_item /
add_match_played / update_balance
funksiyalari –
bularning barchasi asosiy botda
allaqachon SQLite orqali (user_dict,
add_balance,
add_inventory_item, games ustuni)
T0'LIQ va yanada kengroq shaklda mavjud
edi.

BOSHQA SO'RALGAN O'ZGARISHLAR:
- Boshlang'ich balans endi 0\$ / 0💎
(avval 5000\$/100💎 edi) – FAQAT yangi
ro'yxatdan o'tadigan
foydalanuvchilar uchun. Mavjud
foydalanuvchilarning
barcha ma'lumotlari (balans,
inventar, statistika, klan a'zoligi va
h.k.)
kodni yangilashda T0'LIQ saqlanib
qoladi.

- 🌙 Tun: 45 soniya.
- 🌞 Kun: jami 90 soniya – 30
soniya muhokama, so'ng ovoz berish
tugmalari
chiqadi va yana 60 soniya ovoz
berish davom etadi.

=====
=====

YANGI (v3): DO'KONDAGI HAR BIR BUYUM
HAQIQIY ISHLAYDI + TELEGRAM STARS ORQALI
HUNTER COIN SOTIB OLIH TIZIMI.

MUHIM ESLATMA (Stars haqida):

Telegram Stars orqali qilingan
to'lovlar AVTOMATIK RAVISHDA botni

BotFather orqali ro'yxatdan o'tkazgan
hisobning Stars balansiga tushadi.

Bu Telegramning o'z tizimi – botning
kodi orqali pulni "boshqa odamga
yo'naltirish" imkoni yo'q va kerak ham
emas: agar bot @Mirkamilovic

hisobida yaratilgan bo'lsa, barcha
Stars avtomatik o'sha yerga tushadi.

Bot faqat to'lovni qabul qiladi va
foydalanuvchi hisobiga Hunter Coin

qo'shadi – pastda shu jarayon to'liq
ishlaydigan holda yozilgan.

**DO'KONDAGI BARCHA 27 TA BUYUM ENDI HAQIQIY
TA'SIRGA EGA:**

- 📁 Himoya jileti / 🛡️ Temir niqob /
🛡️ Imunitet qalqoni → shield (o'limdan
asraydi)
- 📜 Soxta Hujjat → Komissar tekshirsa
"Tinch aholi" ko'rsatadi
- 🕶️ Tungi ko'zoynak → tundan keyin
qaysi rollar faol bo'lganini DM orqali
ko'rsatadi
- ✉️ Tushunarsiz xat → mafiya sizni
nishonga olsa, hujum tasodifiy boshqa
odamga burilib ketadi
- 🩺 Zaharli flakon → /zahar buyrug'i
orqali birovni zaharlaysiz (doktor
qutqarmasa, tunda o'ladi)
- 📍 GPS Mayak → /gps buyrug'i orqali

birovning tirik/o'lganligini bilib olasiz

- 🏠 VIP Litsenziya / 🧠 Sehrli tumor / 🏦 Bank foizi → kunlik bonusni

ko'paytiradi

- ⚔️ Olmos Qilich → duelda 65% g'alaba imkoniyati beradi

- 🟡 Oltin o'q → mafiyaning o'ldirish urinishi himoya/davolashni chetlab o'tadi

- 📡 Maxfiy radar → /qayta_tanlash orqali o'z rolingizni qayta tasodifiy tanlaydi

- ⚡ Tezkor jonlanish → o'lish arafasida qo'shimcha jon beradi

- 🎲 Barcha rollarni tanlash huquqi → /rolni_tanla <rol> orqali xohlagan rolni tanlaysiz

- 🏰 Klan litsenziyasi → /klan <nomi> orqali klan ochish huquqini beradi

- 👤 Shadow status → reytingda (/top) yashirin bo'lasiz

- 🗡️ Afsonaviy qotil nishoni / 🛡️

Cheksiz duel qalqoni → duelda doim g'olib chiqasiz

- 👁️ Kuzatish ko'zi → kunduzi kim kimga ovoz berganini DM orqali to'liq ko'rasiz

- 🏠/🏠/🧠 → kunlik bonus

multiplikatori (x2)

- 🌟 Cheksiz omad tulki tumori → barcha pul yutuqlaringiz x3 bo'ladi

- 👑 Hukmdor toj / 🖼️ Mifik ramka / 🐉 Qirol unvoni → profilda ko'rinadigan maqom belgilari

- ⚡ Admin privilegiyasi (1 kun) → 24


```
soat davomida /NewGame va h.k. buyruqlarni  
bera olasiz  
"""
```

```
import telebot  
from telebot import types  
import logging  
import sqlite3  
import random  
import threading  
import time  
import json  
import os  
import sys  
import signal  
import requests  
import re  
import difflib
```

```
_BOT_START_TS = time.time() # 🤖 Admin  
panel "Bot holati" tugmasi uchun – jarayon  
qachon ishga tushganini bilish uchun
```

```
#  
=====
```

```
# ASOSIY SOZLAMALAR
```

```
#  
=====
```

```
TOKEN =  
os.environ.get("HUNTER_MAFIA_TOKEN",
```

```

"").strip()
if not TOKEN:
    raise RuntimeError(
        "HUNTER_MAFIA_TOKEN muhit
o'zgaruvchisi topilmadi!\n"
        "Botni ishga tushirishdan oldin
tokenni sozlang, masalan:\n"
        " export
HUNTER_MAFIA_TOKEN=\"123456:ABC-...\"
(Linux/Mac)\n"
        " set
HUNTER_MAFIA_TOKEN=123456:ABC-...
(Windows)\n"
        "Tokenni hech qachon kod ichiga
ochiq yozmang – u chiqib ketsa, "
        "botingizni istalgan kishi to'liq
boshqarib olishi mumkin."
    )
logging.basicConfig(level=logging.INFO,
format="%(asctime)s [%(levelname)s] %(
message)s")
_logger = logging.getLogger("hunter_mafia")

class
_SafeExceptionHandler(telebot.ExceptionHand
ler):
    """Har qanday handler ichidagi
kutilmagan xato butun botni yiqitmasligi
uchun.
    Xato faqat log'ga yoziladi, bot
polling'ni davom ettiraveradi.
    🛠 TUZATILDI (#5): endi xato yuz
berganda BOT EGASIGA avtomatik, real vaqtda

```

Telegram orqali xabar boradi – avval xatoni faqat log fayldan (server konsolidan)

ko'rish mumkin edi, endi buni bilish uchun serverga kirish shart emas."""

```
def handle(self, exception):
    notify_owner_of_error("global
(handler ichida ushlanmagan)", exception)
    return True # True = xato
"boshqarildi" deb hisoblanadi, polling
to'xtamaydi
```

```
_ERROR_NOTIFY_CACHE = {}
```

```
def notify_owner_of_error(context_label,
exception):
```

```
"""🔧 Umumiy xato-xabar funksiyasi:
istalgan joyda (ichki try/except bo'lsa
ham) chaqirilib, xatoning ANIQ matnini
bot egasiga Telegram orqali
yuboradi – endi hech qanday xato "log
fayl ichida yashirin" qolmaydi,
/elite kabi buyruqlarda ham darhol nima
buzilganini ko'rish mumkin.
```

🚫 ISTISNO: 409 Conflict (= shu bot tokeni bilan boshqa nusxa ham polling qilyapti) – bu haqiqiy "kod xatosi" emas, asosiy polling tsikli buni allaqachon o'zi kutib-qayta urinish orqali boshqaradi. Shuning uchun bu

```

Telegram xabari sifatida YUBORILMAYDI
(faqat log fayliga yoziladi)."""
    _logger.exception("%s: %s",
context_label, exception)
    err_text = f"
{type(exception).__name__}: {exception}"
    is_conflict_409 = (
        getattr(exception, "error_code",
None) == 409
        or "409" in err_text
        or "Conflict" in err_text
    )
    if is_conflict_409:
        return
    if not error_notify_enabled():
        return
    try:
        now = time.strftime("%d.%m.%Y
%H:%M:%S")
        key =
f"errnotify_{hash(context_label + err_text)
% 100000}"
        last = _ERROR_NOTIFY_CACHE.get(key,
0)

        if time.time() - last > 120:
            _ERROR_NOTIFY_CACHE[key] =
time.time()
            bot.send_message(
                OWNER_ID_FROM_ENV,
                f"🚨 <b>Botda xato yuz
berdi!</b>\n"
                f"📍 Joyi: <code>
{context_label}</code>\n"
                f"🕒 Vaqt: {now}\n"

```

```

        f"📄 Xato: <code>
{err_text[:500]}</code>",
    )
    except Exception:
        pass

# 🛠️ MUHIM TUZATISH: ENABLE_MIDDLEWARE
albatta TeleBot obyekti YARATILISHIDAN
# OLDIN o'rnatilishi SHART. Aks holda
kutubxona `self.typed_middleware_handlers`
# atributini __init__ ichida yaratmaydi,
lekin bayroq baribir "yoqiq" bo'lib
# qolganidan, keyinchalik HAR BIR kelgan
xabar/callback qayta ishlanganda
# (hattoki /start kabi oddiy buyruqlarda
ham) botni butunlay chalkashtiruvchi
# "'TeleBot' object has no attribute
'typed_middleware_handlers'" xatoligiga
# olib kelardi – shu sabab bot deyarli hech
nimaga javob bermayotgandek va
# ELITE sotib olish tugmalari ham
ishlamayotgandek ko'rinardi.
# 🛠️ MUSTAHKAMLASH: agar tarmoq/Telegram
API vaqtinchalik javob bermay qolsa,
# so'rov abadiy "osilib qolmasligi" uchun
aniq timeout, VA vaqtinchalik
# xatoliklarda kutubxonaning o'zi (bizning
while-True qayta urinish tsiklimizga
# yetib kelmasdan) avtomatik qayta urinib
ko'rishi uchun sozlamalar.
telebot.apihelper.CONNECT_TIMEOUT = 15
telebot.apihelper.READ_TIMEOUT = 30

```

```

telebot.apihelper.RETRY_ON_ERROR = True
telebot.apihelper.RETRY_TIMEOUT = 5

telebot.apihelper.ENABLE_MIDDLEWARE = True

bot = telebot.TeleBot(TOKEN,
parse_mode="HTML",
exception_handler=_SafeExceptionHandler(),
threaded=True, num_threads=64)

#
=====
=====
# 🧠 THERON – botning sun'iy intellekt
yordamchisi
#   Ism qadimgi yunon tilidan olingan:
"Θήρων" – "ovchi" degan ma'noni bildiradi
#   (Hunter Mafia mavzusiga mos ravishda
tanlangan).
#
#   Theron 4 xil rolda ishlaydi:
#   1) 🦋 BOT EGASINING shaxsiy mehnatkash
yordamchisi – salomlashadi, statistika
#       asosida maslahat beradi, muhim
amallar (ommaviy xabar) oldidan RUXSAT
so'raydi.
#   2) 💎 ELITE foydalanuvchilar uchun –
deyarli cheklovsiz shaxsiy AI yordamchi,
#       ularning profili/statistikasi
asosida shaxsiylashtirilgan maslahat
beradi.
#   3) 👤 Oddiy foydalanuvchilar uchun –
kuniiga belgilangan LIMIT bilan, qisqaroq
#       yordam (Elite'ga o'tishni asta-sekin

```

```

taklif qiladi).
# 4) 🧑🏻‍🤝‍🧑🏻 Guruhda – tun/kun voqealarini AI
orqali jonli, badiiy tarzda hikoya
# qiladi va o'yin oxirida g'oliblarni
o'zi tabriklaydi.
#
# 🆓 BEPUL AI: Google Gemini bepul
tarifidan foydalanadi (kunlik bepul so'rov
# limiti bor, lekin oddiy bot uchun
yetarli). Ishlashi uchun serverda
# GEMINI_API_KEY muhit o'zgaruvchisi
o'rnatilishi kerak –
https://aistudio.google.com/app/apikey
# saytidan BEPUL olinadi. Agar kalit
o'rnatilmagan bo'lsa, Theron shunchaki
# "hozircha mavjud emas" deydi – BOTNING
QOLGAN QISMI BUZILMAYDI, xatolik
# hech qachon o'yinni yoki boshqa
buyruqlarni to'xtatmaydi (har doim
try/except
# bilan o'ralgan, eng yomon holatda AI
qismi jimgina o'tkazib yuboriladi).
#
=====
=====

THERON_NAME = "Theron"
THERON_MEANING = "– qadimgi yunon tilida
<i>\\"ovchi\\"</i> degan ma'noni bildiradi
🏹"

GEMINI_API_KEY =
os.environ.get("GEMINI_API_KEY",
"" ).strip()

```

```
# 🔧 MUHIM: Google Gemini modellarini juda
tez-tez (deyarli har oy) chiqarib
# tashlab, eskilarini o'chirib qo'yadi
(masalan "gemini-2.0-flash" 2026-yil
# 1-iyunda butunlay o'chirilgan). Bitta
model nomini qattiq yozib qo'yish
# ertami-kechmi yana AI'ni "404" bilan
to'xtatib qo'yadi. Shuning uchun Theron
# endi BIR NECHTA joriy modelni ro'yxat
qilib, birinchi ISHLAGANINI avtomatik
# tanlaydi va shu tanlovni keyingi
so'rovlar uchun eslab qoladi (har safar
# qaytadan sinab o'tirmaslik uchun). Agar
Google kelajakda yana birortasini
# o'chirsa, ro'yxatdagi keyingisiga o'zi
o'tadi – botni qayta tahrirlash
# shart bo'lmaydi.
GEMINI_MODEL_CANDIDATES = [
    m.strip() for m in os.environ.get(
        "GEMINI_MODEL_CANDIDATES",
        # eng yangi va tezkor (arzon/tez
javob) modellardan boshlab, orqaga qarab:
        "gemini-2.5-flash-lite,gemini-2.5-
flash,gemini-3.1-flash-lite,gemini-3.5-
flash,gemini-2.0-flash-lite"
    ).split(",") if m.strip()
]
# Agar owner GEMINI_MODEL ni qo'lda
ko'rsatgan bo'lsa (eski sozlama), uni
ro'yxat boshiga qo'yamiz:
_manual_model =
os.environ.get("GEMINI_MODEL", "").strip()
if _manual_model and _manual_model not in
```



```

GEMINI_MODEL_CANDIDATES:
    GEMINI_MODEL_CANDIDATES.insert(0,
    _manual_model)
elif _manual_model in
GEMINI_MODEL_CANDIDATES:

GEMINI_MODEL_CANDIDATES.remove(_manual_model)
    GEMINI_MODEL_CANDIDATES.insert(0,
    _manual_model)

_GEMINI_WORKING_MODEL = None    # ishlagani
aniqlangach shu yerda "eslab qolinadi"
_GEMINI_MODEL_LOCK = threading.Lock()

def _gemini_url_for(model):
    return
    f"https://generativelanguage.googleapis.com
/v1beta/models/{model}:generateContent"

THERON_FREE_DAILY_LIMIT = 3    # oddiy
(ELITE bo'lmagan) foydalanuvchilar uchun
kunlik savol limiti
THERON_ELITE_DAILY_LIMIT = 40  # ELITE
foydalanuvchilar uchun (haqiqatda deyarli
cheksiz, faqat suiiste'moldan himoya)

_THERON_USAGE = {}            # uid -> {"date":
"YYYY-MM-DD", "count": N}
_THERON_USAGE_LOCK = threading.Lock()
_THERON_HISTORY = {}          # uid -> [
{"role": "user"/"model", "text": ...}, ...
] – oxirgi bir necha xabar (qisqa xotira)

```

```

_THERON_HISTORY_MAX = 6 # necha xabar
saqlanadi (uzoq suhbat = ko'p token =
qimmat/sekin bo'lmasin deb cheklangan)

# 💬 Asosiy menyudagi "Theron" tugmasi
bosilgan foydalanuvchilar shu to'plamda
# saqlanadi – shu holatda ekanlar /theron
buyrug'ini yozmasdan, TO'G'RIDAN-TO'G'RI
# xabar yozib Theron bilan erkin
suhbatlashishlari mumkin. "🔙 Bosh menyu"
tugmasi
# bosilganda (yoki boshqa buyruq
yozilganda) chat rejimidan chiqadi.
THERON_CHAT_MODE = set()

def theron_available():
    """Theron ishga tayyor-tayyormasligini
    tekshiradi. 🔧 O'ZGARTIRILDI: Theron
    endi tashqi AI (Gemini/Grok) API kaliti
    kerak bo'lmagan, TO'LIQ LOKAL
    (kod bilan yozilgan) yordamchi –
    shuning uchun har doim TAYYOR, hech qanday
    API kalitiga bog'liq emas."""
    return True

def _theron_today():
    return time.strftime("%Y-%m-%d")

def theron_check_and_consume_quota(uid,
is_elite_user):
    """Foydalanuvchining kunlik AI-savol

```

```

limiti tugamaganini tekshiradi va
    ishlatilgan deb hisoblaydi. Owner uchun
limit umuman qo'llanmaydi.
    Qaytaradi: (ruxsat_bormi: bool,
qolgan_soni: int)"""
    if is_owner(uid):
        return True, 999
    limit = THERON_ELITE_DAILY_LIMIT if
is_elite_user else THERON_FREE_DAILY_LIMIT
    today = _theron_today()
    with _THERON_USAGE_LOCK:
        rec = _THERON_USAGE.get(uid)
        if not rec or rec["date"] != today:
            rec = {"date": today, "count":
0}

        if rec["count"] >= limit:
            _THERON_USAGE[uid] = rec
            return False, 0
        rec["count"] += 1
        _THERON_USAGE[uid] = rec
        return True, max(0, limit -
rec["count"])

def _theron_call_one_model(model, payload):
    """Bitta model bilan bitta urinish.
Muvaffaqiyatli bo'lsa matnni qaytaradi,
    model TOPILMASA (404 –
o'chirilgan/eskirgan) maxsus belgi
qaytaradi, boshqa
        xatolikda – aniq sabab (status kod +
Google'ning javob matni) bilan
        Exception ko'taradi, shu orqali
diagnostika aniq bo'ladi (masalan: API

```

```

        kalit noto'g'ri = 400/403, kunlik limit
tugagan = 429)."""
        resp =
requests.post(_gemini_url_for(model),
params={"key": GEMINI_API_KEY},
json=payload, timeout=25)
        if resp.status_code == 404:
            return "__MODEL_NOT_FOUND__"
        if resp.status_code >= 400:
            detail = resp.text[:300] if
resp.text else "(javob matni yo'q)"
            raise RuntimeError(f"Gemini API
xatoligi (model={model}, status=
{resp.status_code}): {detail}")
        data = resp.json()
        cands = data.get("candidates") or []
        if not cands:
            return None
        parts = cands[0].get("content",
{}).get("parts") or []
        text = "".join(p.get("text", "") for p
in parts).strip()
        return text or None

def _theron_raw_call(system_instruction,
user_prompt, history=None, max_tokens=500,
temperature=0.9):
    """Gemini API'ga so'rov – avval ESLAB
QOLINGAN (oldin ishlagan) model bilan
sinaydi, agar u endi mavjud bo'lmasa
(Google o'chirib tashlagan bo'lsa),
ro'yxatdagi keyingi modellarga
avtomatik o'tadi. Har qanday yakuniy

```

xatolikda None qaytaradi – chaqiruvchi tomon buni albatta "AI hozircha javob berolmadi" kabi yumshoq xabarga aylantiradi, hech qachon foydalanuvchiga xom Python xatoligini ko'rsatmaydi. YAKUNIY muvaffaqiyatsizlikda esa bot egasiga ANIQ sabab (notify_owner_of_error orqali) yuboriladi – "AI ishlamayapti" degan noaniqlik endi qolmaydi.

🔧 O'ZGARTIRILDI: bot egasining talabiga ko'ra Theron endi tashqi AI xizmatlariga (Gemini, Grok va h.k.) UMUMAN murojaat qilmaydi – bu funksiya ataylab har doim None qaytaradi, shunda barcha chaqiruvchi joylar o'zining tayyor LOKAL (kod bilan yozilgan) javobiga o'tadi. Kod GEMINI_API_KEY o'chirilmagan holatda ham ishlaydi – xavfsizlik uchun ikki qavat qilib qo'yilgan (bu qator + pastdagi eski tekshiruv)."""

```
return None # 🚫 tashqi AI butunlay o'chirilgan – Theron endi 100% lokal ishlaydi

if not GEMINI_API_KEY:
    return None

contents = []
for turn in (history or []):
    contents.append({"role":
turn["role"], "parts": [{"text":
turn["text"]}]}])
```

```

        contents.append({"role": "user",
"parts": [{"text": user_prompt}]})
        payload = {
            "system_instruction": {"parts":
[{"text": system_instruction}]},
            "contents": contents,
            "generationConfig": {
                "maxOutputTokens": max_tokens,
                "temperature": temperature,
            },
            "safetySettings": [
                {"category": c, "threshold":
"BLOCK_ONLY_HIGH"}
                for c in (
                    "HARM_CATEGORY_HARASSMENT",
"HARM_CATEGORY_HATE_SPEECH",

"HARM_CATEGORY_SEXUALLY_EXPLICIT",
"HARM_CATEGORY_DANGEROUS_CONTENT",
                )
            ],
        }

        global _GEMINI_WORKING_MODEL
        # 1) Avval oldin ishlagani ma'lum
        bo'lgan modelni sinaymiz (tezroq – har
        #   safar butun ro'yxatni qaytadan
        aylanib chiqmaslik uchun)
        order = ([_GEMINI_WORKING_MODEL] if
_GEMINI_WORKING_MODEL else []) + [
            m for m in GEMINI_MODEL_CANDIDATES
            if m != _GEMINI_WORKING_MODEL
        ]

```

```

last_error = None
for model in order:
    try:
        result =
_theron_call_one_model(model, payload)
    except Exception as e:
        last_error = e
        continue
    if result == "__MODEL_NOT_FOUND__":
        # Bu model endi mavjud emas
        (Google o'chirgan) – jimgina keyingisiga
        o'tamiz
        _logger.warning("🧠 Theron:
model '%s' topilmadi (404, ehtimol
eskirgan) – keyingisiga o'tilmoqda", model)
        continue
    if result:
        with _GEMINI_MODEL_LOCK:
            _GEMINI_WORKING_MODEL =
model # ✅ ishladi – keyingi safar shundan
boshlaymiz
        return result
        # bo'sh javob qaytdi – baribir shu
model "topildi" hisoblanadi, boshqasiga
o'tmaymiz
        return None

# 🚨 Ro'yxatdagi BARCHA modellar
muvaffaqiyatsiz bo'ldi – bu endi
"kutilmagan"
    # holat, shuning uchun ANIQ sababni bot
egasiga yuboramiz (throttling bilan,
    # notify_owner_of_error ichida
    allaqachon bor – 2 daqiqada bir marta).

```

```

        if last_error:
            notify_owner_of_error("Theron AI –
barcha Gemini modellari sinab ko'rildi",
last_error)
        else:
            notify_owner_of_error(
                "Theron AI – barcha modellar
404 qaytardi",

RuntimeError(f"GEMINI_MODEL_CANDIDATES
ro'yxatidagi hech biri topilmadi:
{GEMINI_MODEL_CANDIDATES}"),
            )
        return None

THERON_BASE_PERSONA = (
    f"Sening isming {THERON_NAME}. Sen
\"Hunter Mafia\" nomli Telegram-bot
ichidagi sun'iy intellekt "
    "yordamchisidan. Xarakteringing:
mehnatkash, sodiq, hurmatli, lekin quruq
emas – iliq va samimiy "
    "gapirasan, o'z fikringni ham
bildirasan. Har doim O'ZBEK TILIDA, tabiiy
va ravon yozasan (rasmiy "
    "kanselyarizm emas). Javoblaring QISQA
va ANIQ bo'lsin – odatda 2-5 gap, faqat
chindan kerak bo'lsagina "
    "uzunroq. Telegram HTML formatlashdan
foydalanish mumkin (<b>qalin</b>,
<i>kursiv</i>), lekin ortiqcha "
    "emoji bilan haddan tashqari
to'ldirmagin – 1-2 ta o'rinli emoji

```



```

yetarli."
)

def theron_owner_report_text():
    """Owner uchun – botning real
    statistikasi asosida Theron'ning qisqa
    hisobot + tavsiyasini generatsiya
    qiladi. Statistikani biz o'zimiz DB'dan
    olib, AI'ga FAKT sifatida beramiz – AI
    hech qachon raqamni o'zidan
    o'ylab topmaydi, faqat sharhlaydi va
    maslahat beradi."""
    try:
        with db_lock:
            cur.execute("SELECT COUNT(*)
FROM users")
            total_users = cur.fetchone()[0]
            cur.execute("SELECT charges
FROM users WHERE charges IS NOT NULL")
            now = time.time()
            elite_users = 0
            for (charges_json,) in
cur.fetchall():
                try:
                    if
json.loads(charges_json or "
{}").get("vip_until", 0) > now:
                        elite_users += 1
                except Exception:
                    pass
            cur.execute("SELECT COUNT(*)
FROM users WHERE last_bonus_date = ?",
(time.strftime("%Y-%m-%d"),))

```

```

        active_today = cur.fetchone()
[0]
        active_games = len(GAMES)
    except Exception as e:
        _logger.warning("Theron hisobot
uchun statistika olishda xatolik: %s", e)
        total_users = elite_users =
active_today = active_games = 0

    facts = (
        f"Jami ro'yxatdan o'tgan
foydalanuvchilar: {total_users} ta.\n"
        f"Hozirgi faol ELITE a'zolar:
{elite_users} ta.\n"
        f"Bugun faol bo'lgan (bonus olgan)
foydalanuvchilar: {active_today} ta.\n"
        f"Hozir davom etayotgan o'yinlar
soni: {active_games} ta."
    )
    advice = random.choice([
        "Tavsiya: faol foydalanuvchilar
uchun yangi promo-kod chiqarsangiz, qaytish
darajasi oshishi mumkin.",
        "Tavsiya: yangi turnir e'lon qilish
faollikni yaxshi ko'taradi – qulay payt
bo'lishi mumkin.",
        "Tavsiya: ELITE a'zolar sonini
oshirish uchun cheklangan muddatli chegirma
e'lon qilishni ko'rib chiqing.",
    ])
    return (
        f"🧠 <b>{THERON_NAME}</b>dan hisobot:
</b>\n\n"
        f"Assalomu alaykum, xo'jayin!"
    )

```

```
Bugungi holat:\n{facts}\n\n💡 {advice}"
)
```

```
def theron_owner_greeting():
    """Owner /start bosganda – Theron
    o'zini ishchi sifatida tanishtirib,
    hol-ahvol so'raydi va yordam
    kerakligini so'raydi. 🔧 Lokal (tasodifiy
    tanlanadigan) matnlar – tashqi AI shart
    emas."""
    return random.choice([
        f"Assalomu alaykum, xo'jayin! Men
        {THERON_NAME}man – sizga sodiq yordamchi. "
        "Statistika kerak bo'lsa
        /theron_hisobot deb yozing, boshqa yordam
        kerak bo'lsa shu yerdaman!",
        f"Xush kelibsiz, xo'jayin!
        {THERON_NAME} xizmatlaringizda – botning
        holati bilan qiziqsangiz "
        "/theron_hisobot orqali bilib
        olishingiz mumkin.",
    ])
)
```

```
def theron_build_user_context(uid):
    """Foydalanuvchi haqida DB'dan REAL
    ma'lumot yig'ib, AI'ga tushunarli
    matn shaklida beradi –
    shaxsiylashtirilgan tavsiyalar aynan shu
    orqali
    ishlaydi (AI hech narsani o'ylab
    topmaydi, faqat bergan faktlarimizni
    sharhlaydi)."""
```

```

try:
    u = user_dict(uid)
    elite = is_elite(uid)
    elite_left = elite_days_left(uid)
    if elite else 0
    clan_owner_id =
    find_member_clan(uid) if "find_member_clan"
    in globals() else None
    clan = get_clan(clan_owner_id) if
    clan_owner_id else None
    clan_line = f"ha - {clan['name']}"
    if clan else "yo'q"
    return (
        f"Foydalanuvchi ismi:
    {u.get('name')}.\\n"
        f"O'ynagan o'yinlar:
    {u.get('games', 0)}, g'alabalar:
    {u.get('wins', 0)}.\\n"
        f"Balans: {u.get('dollar', 0)}$
    / {u.get('diamond', 0)}💎 / {u.get('coin',
    0)}👛.\\n"
        f"Duel statistikasi:
    {u.get('duel_wins', 0)} g'alaba /
    {u.get('duel_losses', 0)} mag'lubiyat.\\n"
        f"ELITE holati: {'faol, ' +
    str(elite_left) + ' kun qoldi' if elite
    else 'faol emas'}.\\n"
        f"Klan a'zosimi: {clan_line}."
    )
except Exception as e:
    _logger.warning("Theron uchun
    foydalanuvchi konteksti yig'ishda xatolik:
    %s", e)
    return "Foydalanuvchi haqida

```

qo'shimcha ma'lumot yig'ib bo'lmadi."

#

=====
=====

📖 THERON FAQ – "TEZKOR BILIM BAZASI"

(AI'siz ham ishlaydigan avto-javoblar)

Foydalanuvchilar eng ko'p so'raydigan mavzular oldindan shu yerda javoblangan.

AFZALLIKLARI:

• AI (Gemini) so'roviga ehtiyoj qoldirmaydi – DARHOL javob beradi, kunlik

AI-limitdan sarflanmaydi (limit faqat FAQ'da topilmagan, "haqiqiy" AI

javobi kerak bo'lgan savollarga sarflanadi).

• AI xizmati vaqtincha ishlamay qolsa ham (masalan Google tomonidan

cheklov qo'yilsa) – botning ASOSIY savollariga javob berish TO'XTAMAYDI.

• Yozuvda 1-2 ta harf noto'g'ri joylashgan/adashgan bo'lsa ham

(masalan "kalnim" – "klanim" o'rniga) baribir to'g'ri mavzuni topadi –

difflib orqali "yaqin mos kelish" (fuzzy match) ishlatiladi.

#

=====
=====

```
def _faq_normalize(text):  
    text = text.lower().strip()  
    text = text.replace("'",
```

```

''').replace("'", '').replace('"',
''').replace("`", '')
    text = re.sub(r"[^\w\s'"]", " ", text,
flags=re.UNICODE)
    return re.sub(r"\s+", " ",
text).strip()

```

```

FAQ_KB = [
    {"keywords": ["salom", "assalomu",
"alaykum", "hi", "hello", "yaxshimisan",
"qalaysan"],
    "answer": "👋 Salom! Men Theron –
botning AI yordamchisiman. Sizga qanday
yordam bera olaman? Klan, ELITE, duel,
geroy – istalgan mavzuda so'rang."},
    {"keywords": ["sen kimsan", "sening
isming", "ismi nima", "kim sen", "seni kim
yaratgan", "theron kim", "ovchi degani"],
    "answer": f"🧠 Men <b>{THERON_NAME}</b>man {THERON_MEANING} Hunter Mafia
botining sun'iy intellekt yordamchisiman –
savollaringizga javob beraman va maslahat
beraman."},
    {"keywords": ["elite nima", "elita
nima", "vip nima", "elite qanday olinadi",
"elite narxi", "elite qancha turadi",
"elite foydasi", "elite afzalligi"],
    "answer": "👑 ELITE – botning VIP
a'zoli: laqab qo'yish, lobbydan istalgan
payt chiqish, kunlik sirli sandiq, oltin
nishon va boshqa imtiyozlar beradi.
Narxlari va muddatlari uchun /elite
buyrug'ini yuboring."},

```

```
    {"keywords": ["elite qancha kun",  
"elite muddati", "elite qancha vaqt",  
"elite qolgan"],  
    "answer": "📅 ELITE muddatingizni  
/profile orqali yoki /elite menyusining  
yuqori qismidan ko'rishingiz mumkin – u  
yerda necha kun qolgani aniq yozilgan."},  
    {"keywords": ["klan qanday ochiladi",  
"klan yaratish", "klan ochish", "yangi  
klan"],  
    "answer": "🏠 Klan ochish uchun avval  
Hunter Coin do'konidan \"Klan  
litsenziyasi\" sotib oling, so'ng  
<code>/klan Nomi</code> deb yozing –  
klaningiz yaratiladi."},  
    {"keywords": ["klanga qoshilish",  
"klanga kirish", "boshqa klan azosi  
bolish"],  
    "answer": "👉 Klanga qo'shilish uchun  
<code>/klanga_qoshil egasi_ID</code> deb  
yozing – klan egasiga so'rov ketadi, u  
tasdiqlasa a'zo bo'lasiz."},  
    {"keywords": ["klandan chiqish", "klan  
tark"],  
    "answer": "🚪 Klandan chiqish uchun  
<code>/klan_tark</code> deb yozing."},  
    {"keywords": ["klan xazinasini", "klan  
hazna", "klan puli"],  
    "answer": "💰 Klan xazinasini  
<code>/klan_hazna</code> orqali ko'rasiz,  
<code>/klan_taqsimla</code> orqali (a'zoga  
reply qilib) taqsimlaysiz."},  
    {"keywords": ["klan darajasi", "klan  
levl", "klan lvl"]}
```

```
"answer": "📈 Klanni yangi darajaga ko'tarish uchun <code>/klan_lvl</code> deb yozing – yetarli xazina bo'lsa daraja oshadi."},
{"keywords": ["klanlar jangi", "klanjang", "klan urishi"],
"answer": "⚔️ Klanlar jangini boshlash uchun <code>/klanjang raqib_egasi_ID</code> deb yozing."},
{"keywords": ["top klanlar", "eng kuchli klan", "klanlar reytingi"],
"answer": "🏆 Top klanlarni ko'rish uchun <code>/klanlar</code> deb yozing."},
{"keywords": ["duel nima", "duel qanday", "dueliga chaqirish", "kim bilan duel"],
"answer": "⚔️ Duel – 2 o'yinchi orasidagi pul tikib o'ynaladigan o'yin. Guruhda kimningdir xabariga <b>Reply</b> qilib <code>/duel summasi</code> deb yozing (masalan: /duel 250)."},
{"keywords": ["duel statistikasi", "duel netije", "necha duel yutdim"],
"answer": "📊 Duel statistikangizni ko'rish uchun <code>/duel_stat</code> deb yozing."},
{"keywords": ["nikoh qanday", "turmush qurish", "uylanish", "sevgilim qilish"],
"answer": "💍 Nikoh qurish uchun guruhda o'sha kishining xabariga <b>Reply</b> qilib <code>/nikoh</code> deb yozing."},
{"keywords": ["ajrashish", "nikohni bekor qilish", "ajralish"],
```



```
"answer": "❤️ Ajrashish uchun
<code>/ajrashish</code> deb yozing."},
{"keywords": ["juftim kim", "sevgilim
kim", "turmush ortogim"],
"answer": "❤️ Juftingizni bilish uchun
<code>/juftim</code> deb yozing."},
{"keywords": ["geroy nima", "geroyim",
"hero nima", "geroy qanday olinadi"],
"answer": "🏆 Geroylar – maxsus
qobiliyatga ega, darajasini oshirish mumkin
bo'lgan shaxsiy belgilar.
<code>/geroyim</code> orqali ko'rasiz va
rivojlantirasiz, sirli sandiqlardan yoki
do'kondan olish mumkin."},
{"keywords": ["turnir nima", "musobaqa
qanday", "turnirga qoshilish"],
"answer": "🏆 Turnirlarni FAQAT bot
egasi ochadi. Tugma orqali qo'shilasiz,
oxirida bitta CHEMPION katta mukofot oladi.
Ro'yxatni <code>/turnir_royxat</code>
orqali ko'rasiz."},
{"keywords": ["promo kod", "promokod",
"kod kiritish"],
"answer": "🎁 Promo-kodni ishlatish
uchun <code>/promo KOD</code> deb
yozing."},
{"keywords": ["bonus qanday", "kunlik
bonus", "har kun bonus"],
"answer": "🎁 Kunlik bonusni asosiy
menyudagi \"/>

```

```
"sotish", "sotib olish boshqa oyinchidan"],
  "answer": "🛒 Qora bozorda o'yinchilar
buyum sotadi/sotib oladi:
<code>/sell</code> – inventaringizni
ko'rish, <code>/market</code> – e'lonlarni
ko'rish, <code>/buy ID</code> – sotib
olish. Faqat maxsus savdo guruhida
ishlaydi."},
  {"keywords": ["balansim", "pulim
qancha", "dollarim qancha", "necha pulim
bor"],
  "answer": "💰 Balansingizni
<code>/profile</code> yoki
<code>/inventar</code> orqali ko'rishingiz
mumkin."},
  {"keywords": ["profile nima",
"kabinet", "shaxsiy sahifa"],
  "answer": "👤 Shaxsiy kabinetingizni
ko'rish uchun <code>/profile</code> deb
yozing."},
  {"keywords": ["inventar", "buyumlarim",
"narsalarim"],
  "answer": "📦 Inventaringizni ko'rish
uchun <code>/inventar</code> deb yozing."},
  {"keywords": ["olmos qanday olinadi",
"diamond qanday", "olmos sotib olish"],
  "answer": "💎 Olmosni
<code>/birja</code> orqali Telegram Stars
evaziga sotib olishingiz yoki Hunter
Coin'dan ayirboshlashingiz mumkin."},
  {"keywords": ["dollar qanday olinadi",
"pul qanday topiladi", "dollar sotib
olish"],
  "answer": "💵 O'yin-ichi Dollarni
```

```
o'ynab (g'alaba, bonus) yoki Olmosga sotib
olib (asosiy menyudagi \" Dollar
do'koni\") to'ldirishingiz mumkin.\"},
  {\"keywords\": [\"hunter coin\", \"coin
nima\", \"coin qanday\"],
    \"answer\": \" Hunter Coin – maxsus
valyuta, klan litsenziyasi kabi buyumlar
shu orqali sotib olinadi. Telegram Stars
orqali <code>/birja</code> menyusidan
olasiz.\"},
    {\"keywords\": [\"rol qanday tanlanadi\",
\"rolni tanla\", \"qaysi rol menda\"],
      \"answer\": \" Maxsus rol tanlash
huquqi bo'lsa, o'yin boshlanishidan oldin
<code>/rolni_tanla RolNomi</code> deb
yozasiz. Rollar ro'yxatini asosiy menyudan
ko'rishingiz mumkin.\"},
        {\"keywords\": [\"rollar royxati\", \"qanday
rollar bor\", \"mafia rollari\"],
          \"answer\": \" Botda 28 ta turli rol
bor – to'liq ro'yxatni asosiy menyudagi
\\\" Rollar\\\" tugmasi orqali ko'rishingiz
mumkin.\"},
            {\"keywords\": [\"oyin qanday boshlanadi\",
\"yangi oyin\", \"newgame\"],
              \"answer\": \" Guruh admini
<code>/NewGame</code> buyrug'i bilan yangi
o'yin ochadi, o'yinchilar
<code>/join</code> orqali qo'shiladi, so'ng
<code>/StartGame</code> bilan
boshlanadi.\"},
                {\"keywords\": [\"oyindan chiqish\", \"tark
etish\", \"oyinni tashlab ketish\"],
                  \"answer\": \" O'yinni tark etish uchun
```

```

<code>/tark_et</code> deb yozing – lekin bu
avtomatik mag'lubiyat va -10 ball
hisoblanadi, ehtiyot bo'ling."},
    {"keywords": ["admin kim", "bot egasi
kim", "kim yaratgan bu botni", "botni kim
boshqaradi"],
    "answer": "👑 Botning egasi va bosh
administratori bor – men (Theron) unga
yordamchi sifatida ishlayman. Muammo bo'lsa
guruh adminiga yoki bot egasiga murojaat
qiling."},
    {"keywords": ["banlandim",
"bloklanibman", "nega banladingiz", "ban
sababi"],
    "answer": "🚫 Agar bloklangan
bo'lsangiz, sababini bilish uchun bot egasi
bilan bog'laning – men bu qarorni o'zim
qabul qilmayman, faqat yordamchiman."},
    {"keywords": ["til ozgartirish",
"language ozgartirish", "boshqa til"],
    "answer": "🌐 Tilni o'zgartirish uchun
asosiy menyudagi \"🌐 Til\" tugmasini yoki
/start dagi menyuni ishlating."},
    {"keywords": ["taxallus", "laqab
qoyish", "nickname"],
    "answer": "🔑 Shaxsiy laqab qo'yish
FAQAT ELITE a'zolarga ochiq:
<code>/taxallus laqabingiz</code> deb
yozing."},
    {"keywords": ["sovg'a qilish", "sovg'a
berish", "givde"],
    "answer": "🎁 Boshqa o'yinchiga sovg'a
berish uchun uning xabariga reply qilib
<code>/Givde</code>,

```

```
<code>/GivdeMoney</code> yoki  
<code>/GivdeCoin</code> dan foydalaning."},  
  {"keywords": ["osh tortiq", "milliy  
osh", "oshim"],  
    "answer": "🍪 Do'stingizga milliy osh  
ziyofat qilish uchun uning xabariga reply  
qilib <code>/osh turi</code> deb yozing –  
bu unga himoya va bonus beradi."},  
  {"keywords": ["oila top", "eng  
mustahkam oila"],  
    "answer": "❤️ Eng mustahkam oilalar  
reytingini <code>/OilaTop</code> orqali  
ko'rasiz."},  
  {"keywords": ["theron limit", "kuniga  
necha savol", "savol limiti", "necha marta  
soray olaman"],  
    "answer": f"💬 Oddiy foydalanuvchilar  
kuniga {THERON_FREE_DAILY_LIMIT} ta, ELITE  
a'zolar kuniga {THERON_ELITE_DAILY_LIMIT}  
tagacha savol berishlari mumkin. Bu FAQ  
javoblari (aynan shu kabi tez-tez  
so'raladigan savollar) limitga sarflanmaydi  
– faqat chuqurroq, shaxsiy AI javoblar  
limitdan sarflanadi."},  
  {"keywords": ["yordam", "buyruqlar  
ro'yxati", "nima qila olasan",  
"komandalar"],  
    "answer": "❓ Barcha buyruqlar  
ro'yxatini asosiy menyudagi \"❓ Yordam\"  
tugmasi orqali to'liq ko'rishingiz  
mumkin."},  
  {"keywords": ["stars qanday", "telegram  
stars", "yulduzcha"],  
    "answer": "⭐ Telegram Stars –
```

```

Telegram'ning ichki to'lov valyutasi,
ELITE, Olmos va Hunter Coin sotib olishda
ishlatiladi. Telegram sozlamalaridan sotib
olishingiz mumkin."},
    {"keywords": ["mukofot qancha", "gaolib
mukofoti", "turnir mukofoti"],
    "answer": "🏆 Turnir chempioni +500$,
+20💎 va +50 ball mukofot oladi."},
    {"keywords": ["ball nima", "ball
tizimi", "faollik balli"],
    "answer": "🏆 Ballar – faollligingiz
uchun beriladi (g'alaba, ishtirok va h.k.).
Reytingni <code>/balltop_kun</code>,
<code>/balltop_hafta</code>,
<code>/balltop_oy</code>,
<code>/balltop_mutlaq</code> orqali
ko'rasiz."},
]

```

```

def faq_lookup(question):
    """Savolni FAQ bazasidan qidiradi. Aniq
so'z mos kelsa yuqori ball,
    "yaqin" (1-2 harf farqli/adashgan) so'z
topilsa ham past ball beriladi –
    shu orqali kichik xato-yozuvlarda ham
to'g'ri mavzu topiladi. Ishonchli
    darajada mos kelgan javob topilmasa –
None qaytaradi (bu holda cmd_theron
    haqiqiy AI'ga murojaat qiladi)."""
    norm = _faq_normalize(question)
    if not norm:
        return None
    words = norm.split()

```

```

best_answer, best_score = None, 0
for entry in FAQ_KB:
    score = 0
    for kw in entry["keywords"]:
        kw_norm = _faq_normalize(kw)
        if kw_norm in norm:
            score += 3 # to'liq ibora
topildi – juda ishonchli
            continue
        kw_words = kw_norm.split()
        matched_words = 0
        for kww in kw_words:
            if kww in words:
                matched_words += 1
            elif
difflib.get_close_matches(kww, words, n=1,
cutoff=0.72):
                matched_words += 1 #
🔧 1-2 harf adashgan bo'lsa ham tanish
            if kw_words and matched_words
== len(kw_words):
                score += 2
            if score > best_score:
                best_score, best_answer =
score, entry["answer"]
        return best_answer if best_score >= 2
    else None

def theron_answer_user(uid, question,
is_elite_user):
    """Elite/oddiy foydalanuvchining
savoliga javob – TO'LIQ LOKAL mexanizm:

```

```
1) Avval FAQ bazasi (faq_lookup –
cmd_theron/free-chat ichida bundan oldin
    ham tekshiriladi, lekin bu yerda ham
qayta tekshiriladi – funksiya
    mustaqil chaqirilishi mumkin
bo'lgani uchun xavfsizroq).
2) 20 ta "aqlii funksiya"
(THERON_SMART_FUNCS) – foydalanuvchining
REAL
    ma'lumotlari (balans, statistika,
klan va h.k.) asosida DINAMIK javob.
3) 10 ta o'yin-strategiya maslahati
(THERON_GAME_TIPS).
4) Hech biri mos kelmasa – xushmuomala,
xilma-xil (tasodifiy) umumiy
    javob (THERON_FALLBACK_REPLIES)."""
norm = _faq_normalize(question)
words = norm.split()

faq_answer = faq_lookup(question)
if faq_answer:
    return faq_answer

if is_owner(uid):
    for intent in THERON_OWNER_FUNCS:
        if
_theron_keywords_match(intent["keywords"],
norm, words):
            try:
                return intent["fn"]
(uid, is_elite_user)
            except Exception as e:
                _logger.warning("Theron
owner funksiyasida xatolik (%s): %s",
```



```

intent.get("name"), e)

    for intent in THERON_SMART_FUNCS:
        if
_theron_keywords_match(intent["keywords"],
norm, words):
            try:
                return intent["fn"](uid,
is_elite_user)
            except Exception as e:
                _logger.warning("Theron
aqli funksiyasida xatolik (%s): %s",
intent.get("name"), e)

    for tip in THERON_GAME_TIPS:
        if
_theron_keywords_match(tip["keywords"],
norm, words):
            return tip["answer"]

    result =
random.choice(THERON_FALLBACK_REPLIES)
    if not is_elite_user and
random.random() < 0.35:
        result += "\n\n💎 <i>ELITE
a'zolikda Theron yanada ko'proq va
chuqurroq maslahat beradi – /elite</i>"
    return result

def _theron_keywords_match(keyword_groups,
norm, words):
    """Bitta intentning kalit-so'z
guruhlaridan KAMIDA bittasi savolda

```

```

        uchrasa (to'liq ibora sifatida yoki har
        bir so'zi alohida-alohida
        topilsa) – True qaytaradi. difflib
        orqali kichik xato-yozuvlarga ham
        chidamli."""
    for kw in keyword_groups:
        kw_norm = _faq_normalize(kw)
        if kw_norm and kw_norm in norm:
            return True
        kw_words = kw_norm.split()
        if kw_words and all(
            (kww in words) or
            difflib.get_close_matches(kww, words, n=1,
            cutoff=0.72)
            for kww in kw_words
        ):
            return True
    return False

#
=====
=====
# 🧠 THERON – 20 TA "AQLLI FUNKSIYA"
(foydalanuvchining REAL ma'lumotlari
# asosida DINAMIK javob beradi – bazadan
balans, statistika, klan va h.k.
# o'qib, har bir foydalanuvchi uchun
BOSHQACHA javob shakllanadi)
#
=====
=====

def _tf_balance(uid, elite):

```

```

    u = user_dict(uid)
    return (f"💰 Hozirgi holatingiz:\n"
            f"💵 Dollar: <b>{u['dollar']}</b>\n"
            f"💎 Olmos: <b>{u['diamond']}</b>\n"
            f"🕹 Hunter Coin: <b>{u['coin']}</b>\n\n"
            "Ko'proq dollar kerak bo'lsa – o'yinlarda g'alaba qozoning yoki kunlik bonusni unutmang!")

def _tf_stats(uid, elite):
    u = user_dict(uid)
    games, wins = u["games"] or 0, u["wins"] or 0
    rate = round(wins / games * 100, 1) if games else 0
    if games == 0:
        return "📊 Siz hali birorta ham o'yin o'ynamagansiz. Guruhda /join orqali qo'shiling – birinchi tajribangiz sizni kutmoqda! 🎮"
    comment = ("Zo'r natija, shunday davom eting! 🔥" if rate >= 60 else
               "Yomon emas, lekin yaxshilash mumkin – rollarni diqqat bilan o'ylab o'ynang." if rate >= 35 else
               "Hafsalangiz pir bo'lmasin – har bir mag'lubiyat tajriba beradi, keyingi safar aniq g'alaba qozonasiz! 💪")
    return f"📊 Sizning statistikangiz:\n🎮 Jami o'yin: <b>{games}</b>\n🏆 G'alaba: <b>

```

```
{wins}</b> ({rate}%)\\n\\n{comment}"
```

```
def _tf_duel_stats(uid, elite):  
    u = user_dict(uid)  
    dw, dl = u["duel_wins"] or 0,  
    u["duel_losses"] or 0  
    total = dw + dl  
    if total == 0:  
        return "🔪 Siz hali birorta ham  
duelga chiqmagansiz. Guruhda kimningdir  
xabariga Reply qilib /duel summasi deb  
yozing va sinab ko'ring!"  
    rate = round(dw / total * 100, 1)  
    return f"🔪 Duel statistikangiz:\\n🏆  
Yutgan: <b>{dw}</b>\\n💔 Yutqazgan: <b>{dl}</b>\\n📊 Foiz: <b>{rate}%</b>"
```

```
def _tf_clan_info(uid, elite):  
    owner_id = find_member_clan(uid)  
    if not owner_id:  
        return "🏠 Siz hali biror klanga  
a'zo emassiz. Klan ochish uchun Hunter Coin  
do'konidan litsenziya oling va /klan Nomi  
deb yozing, yoki mavjud klanga  
/klanga_qoshil egasi_ID orqali qo'shiling."  
    clan = get_clan(owner_id)  
    if not clan:  
        return "🏠 Klaningiz haqida  
ma'lumot topilmadi."  
    role = "Lider" if owner_id == uid else  
    ("O'rinbosar" if is_clan_deputy(uid,  
owner_id) else "A'zo")
```

```

        return (f"🏠 Klaningiz: <b>
{clan['name']}</b>\n"
                f"🏆 Sizning mavqeingiz: <b>
{role}</b>\n"
                f"📈 Klan darajasi: <b>
{clan['level']}</b>\n"
                f"🏆 Jang g'alabalari: <b>
{clan['wins']}</b>")

def _tf_elite_status(uid, elite):
    if elite:
        return "👑 Siz hozir ELITE a'zosiz!
Qolgan muddatni /profile orqali
ko'rishingiz mumkin. ELITE
imtiyozlaringizdan (laqab, sirli sandiq,
lobbydan chiqish) to'liq foydalaning!"
    return "👤 Siz hozircha ELITE emassiz.
ELITE a'zolik laqab qo'yish, kunlik sirli
sandiqlik, va boshqa ko'plab imtiyozlar beradi
– narxlar uchun /elite buyrug'ini
yuboring."

def _tf_top_position(uid, elite):
    rows = get_points_leaderboard("mutlaq",
limit=200)
    for i, (u_id, _name, total) in
enumerate(rows, 1):
        if u_id == uid:
            return f"🏆 Siz umumiy
reytingda <b>{i}</b>-o'rin</b>dasiz ({total}
ball). To'liq reytingni /balltop_mutlaq
orqali ko'ring!"

```

```
    return "🏆 Siz hali ball reytingida  
ko'rinmaysiz – faol o'ynang, g'alaba  
qozoning, ball to'plang!"

def _tf_inventory(uid, elite):
    return "📦 Inventaringizda nimalar  
borligini to'liq ko'rish uchun /inventar  
buyrug'ini yuboring – men bu yerda umumiy  
yo'nalish beraman, aniq ro'yxatni o'sha  
yerdan olasiz."

def _tf_marriage(uid, elite):
    u = user_dict(uid)
    if u.get("married_to"):
        return "❤️ Siz nikohdasiz!  
Juftingiz kimligini /juftim orqali  
ko'rishingiz mumkin."
    return "💍 Siz hozircha yolg'izsiz.  
Nikoh qurish uchun guruhda yoqtirgan  
odamingizning xabariga Reply qilib /nikoh  
deb yozing."

def _tf_daily_bonus(uid, elite):
    u = user_dict(uid)
    today = time.strftime("%Y-%m-%d")
    if u.get("last_bonus_date") == today:
        return "🎁 Bugungi kunlik  
bonusingizni allaqachon olib bo'lgansiz!  
Ertaga qayta keling."
    return "🎁 Bugungi kunlik bonusingizni  
hali olmangansiz – asosiy menyudagi \"🎁  
Kunlik bonus\" tugmasini bosing, bepul
```

mukofot sizni kutmoqda!"

```
def _tf_richest_tip(uid, elite):  
    return random.choice([  
        "💡 Boylikni tez oshirish uchun:  
klan xazinasiga qo'shiling, duel'larda  
ehtiyotkorlik bilan tikish qiling va  
turnirlarda qatnashing – chempion katta  
mukofot oladi!",  
        "💡 Kunlik bonusni har kuni  
unutmang – kichik summalar yig'ilib katta  
bo'ladi. Qora bozorda kerak bo'lmagan  
buyumlaringizni ham soting.",  
        "💡 Klan darajasini oshirish klan  
a'zolariga qo'shimcha imtiyozlar beradi –  
birgalikda xazinaga hissa qo'shing.",  
    ])
```

```
def _tf_elite_savings_tip(uid, elite):  
    return "💎 ELITE a'zolikni tejamkor  
olish uchun: Olmosni to'g'ridan-to'g'ri  
Stars evaziga emas, avval Hunter Coin  
yig'ib, keyin ayirboshlab ko'ring – ba'zan  
bu arzonroq tushadi. Aksiyalar/promo-  
kodlarni ham kuzatib turing."
```

```
def _tf_motivation(uid, elite):  
    return random.choice([  
        "🔥 Har bir yutqazish – kelasi  
g'alabaning bir qadamidir. Davom eting!",  
        "💪 Eng yaxshi strategiya –
```

```
sovuqqonlik va sabr. Shoshilmang, o'ylab  
harakat qiling.",  
    "☀️ Bugun omadingiz kelmasa ham,  
ertaga yangi imkoniyat kutmoqda. Taslim  
bo'lmang!",  
    "🏆 Chempionlar bir kunda  
tug'ilmaydi – har bir o'yin sizni kuchliroq  
qiladi.",  
    ])
```

```
def _tf_joke(uid, elite):  
    return random.choice([  
        "😬 Mafiya tunda shivirlaydi: \"Men  
– fuqaroman!\" Shifokor kulib qo'yadi:  
\"Ha, albatta...\" 😊",  
        "😬 Komissar hammani tekshiryapti,  
birdan o'ziga-o'zi ishonchsizlik bilan  
qaraydi: \"Balki men ham mafiyadirman?\"  
😬",  
        "😬 Duelga chaqirilgan o'yinchi:  
\"Pulim yo'q!\" – deydi, keyin darrov qora  
bozorga yuguradi. 🏃💨",  
    ])
```

```
def _tf_prediction(uid, elite):  
    return random.choice([  
        "🌟 Yulduzlar sizga bugun omad  
va'da qilyapti – jasorat bilan harakat  
qiling!",  
        "🌟 Bugun ehtiyotkorlik kaliti  
bo'lishi mumkin – shoshilmasdan o'ylab  
qadam tashlang.",  
    ])
```



```
        "🤖 Katta g'alaba yaqin – lekin  
faqat sabr qilganlarga!",  
    ])
```

```
def _tf_compare(uid, elite):  
    rows = get_points_leaderboard("mutlaq",  
limit=1)  
    if not rows:  
        return "🏆 Hozircha reytingda hech  
kim yo'q – birinchi bo'lib ball to'plang!"  
    _uid, name, total = rows[0]  
    return f"🏆 Hozirgi eng kuchli  
o'yinchi: <b>{name}</b> ({total} ball). Uni  
quvib yetish uchun faol o'ynang!"
```

```
def _tf_greeting_reply(uid, elite):  
    return random.choice([  
        "👋 Salom-alaykum! Xush kelibsiz,  
yana savol bo'lsa – bermalol yozavering.",  
        "😊 Assalomu alaykum! Sizga qanday  
yordam bera olaman?",  
        "👋 Salom! Shu yerdaman, savolingiz  
bo'lsa yozing.",  
    ])
```

```
def _tf_thanks_reply(uid, elite):  
    return random.choice([  
        "🙏 Arzimaydi! Har doim yordamga  
tayyorman.",  
        "😊 Xizimatingizga shodman! Yana  
savol bo'lsa – shu yerdaman.",  
    ])
```

```
        "👉 Rahmat sizga ham! Omad  
tilayman.",  
    ])
```

```
def _tf_praise_reply(uid, elite):  
    return "😊 Rahmat, sizga yordam bera  
olganimdan xursandman! Yana savollaringiz  
bo'lsa bemalol so'rang."
```

```
def _tf_complaint_reply(uid, elite):  
    return "😞 Kechirasiz, hammasiga to'liq  
javob berolmasligim mumkin – men hali  
oddiy, kod bilan yozilgan yordamchiman.  
Aniqroq savol bersangiz, ko'proq yordam  
bera olaman. Jiddiy muammo bo'lsa – bot  
egasiga murojaat qiling."
```

```
def _tf_tournament_info(uid, elite):  
    return "🏆 Yangi turnirlar FAQAT bot  
egasi tomonidan ochiladi va e'lon qilinadi.  
Ochilgan turnirga tugma orqali qo'shilasiz.  
Hozirgi ro'yxatni /turnir_royxat orqali  
ko'ring."
```

```
def _tf_role_advice(uid, elite):  
    return random.choice([  
        "🤖 Har bir rolning o'z kuchli  
tomoni bor – Mafiya yashirinishni, Komissar  
kuzatishni, Shifokor himoyani biladi.  
Rolingizga mos strategiya tanlang!",
```

```
"🐉 Kunduzi ovoz berishda  
shoshilmang – kim shubhali harakat  
qilganini diqqat bilan kuzating, faktlarga  
tayaning.",  
])
```

```
THERON_SMART_FUNCS = [  
    {"name": "balans", "keywords":  
["balansim", "pulim qancha", "hisobim",  
"dollarim", "olmosim qancha", "coinim  
qancha"], "fn": _tf_balance},  
    {"name": "statistika", "keywords":  
["statistikam", "necha oyin oynadim",  
"golibligim", "yutuqlarim", "mening  
natijam"], "fn": _tf_stats},  
    {"name": "duel_stat", "keywords":  
["duel netijam", "duelda necha yutdim",  
"duel statistikam"], "fn": _tf_duel_stats},  
    {"name": "klan_info", "keywords":  
["mening klanim", "klanim qaysi", "klanimda  
kimlar bor"], "fn": _tf_clan_info},  
    {"name": "elite_status", "keywords":  
["elite manmi", "elitamanmi", "elite  
holatim", "men elitamanmi"], "fn":  
_tf_elite_status},  
    {"name": "top_orin", "keywords":  
["reytingda necha orindaman", "topda qaysi  
orindaman", "mening orinim"], "fn":  
_tf_top_position},  
    {"name": "inventar_soragan",  
"keywords": ["inventarimda nima bor",  
"narsalarim royxati"], "fn":  
_tf_inventory},
```

```
    {"name": "nikoh_holat", "keywords":  
    ["men uylanganmanmi", "turmush  
qurganmanmi", "juftim bormi"], "fn":  
_tf_marriage},  
    {"name": "bonus_holat", "keywords":  
    ["bugun bonus oldimmi", "kunlik bonusim"],  
    "fn": _tf_daily_bonus},  
    {"name": "boylik_maslahat", "keywords":  
    ["tez boy bolish", "kop pul topish",  
    "qanday boy bolaman"], "fn":  
_tf_richest_tip},  
    {"name": "elite_tejamkor", "keywords":  
    ["arzon elite", "tejamkor elite", "elite  
qanday arzon olish"], "fn":  
_tf_elite_savings_tip},  
    {"name": "motivatsiya", "keywords":  
    ["kongilim yomon", "hafsalam pir",  
    "yutqazdim gam", "motivatsiya ber"], "fn":  
_tf_motivation},  
    {"name": "hazil", "keywords": ["hazil  
ayt", "latifa ayt", "kulgili gap"], "fn":  
_tf_joke},  
    {"name": "fol", "keywords": ["fol ochib  
ber", "bashorat qil", "omadim bormi"],  
    "fn": _tf_prediction},  
    {"name": "taqqoslash", "keywords":  
    ["eng kuchli oyinchi kim", "birinchi orinda  
kim", "chempion kim"], "fn": _tf_compare},  
    {"name": "salomlashish2", "keywords":  
    ["yaxshimisiz", "necha bolyapsiz", "ishlar  
joyidami"], "fn": _tf_greeting_reply},  
    {"name": "rahmat", "keywords":  
    ["rahmat", "tashakkur", "katta rahmat"],  
    "fn": _tf_thanks_reply},
```

```
    {"name": "maqtov", "keywords":
["zorsan", "ajoyibsan", "yordamchisan
zor"], "fn": _tf_praise_reply},
    {"name": "shikoyat", "keywords":
["tushunmadim", "bilmayapsan", "yordam
berolmading"], "fn": _tf_complaint_reply},
    {"name": "turnir_malumot", "keywords":
["yangi turnir qachon", "turnir royxati",
"turnirga qanday qoshilaman"], "fn":
_tf_tournament_info},
]
```

```
#
```

```
=====
```

```
=====
```

```
# 🎮 THERON – 10 TA O'YIN-STRATEGIYA
MASLAHATI (rollar va o'yin bosqichlari
# bo'yicha maxsus tavsiyalar)
```

```
#
```

```
=====
```

```
=====
```

```
THERON_GAME_TIPS = [
```

```
    {"keywords": ["mafiya rovida
strategiya", "mafiya qanday oynaydi",
"mafiya maslahat"],
```

```
    "answer": "👤 <b>Mafiya strategiyasi:
</b> Hech qachon shubha uyg'otmang –
fuqarodek gapiring, boshqalarni ayblashda
ehtiyotkor bo'ling, sherigingiz bilan
yashirin kelishib harakat qiling."},
```

```
    {"keywords": ["shifokor rovida
strategiya", "doktor qanday oynaydi",
```

```
"shifokor maslahat"],
  "answer": "🩺 <b>Shifokor
strategiyasi:</b> O'zingizni ochiq oshkor
qilmang – kimni himoya qilishni oldindan
taxmin qiling, ba'zan o'zingizni ham himoya
qiling."},
  {"keywords": ["komissar rolida
strategiya", "detective qanday oynaydi",
"komissar maslahat"],
  "answer": "👮 <b>Komissar
strategiyasi:</b> Har kecha tekshiring,
lekin natijangizni darhol oshkor qilmang –
to'g'ri payt kelganda dalil bilan
chiqing."},
  {"keywords": ["fuqaro rolida
strategiya", "oddiy oyinchi maslahat",
"fuqaro qanday oynaydi"],
  "answer": "👤 <b>Fuqaro strategiyasi:
</b> Kuzating, xotira yurgizing – kim
qarama-qarshi gapirayotganini payqang, ovoz
berishda shoshilmang."},
  {"keywords": ["duelda qanday yutish",
"duel strategiyasi", "duelga maslahat"],
  "answer": "🔪 <b>Duel maslahati:</b>
Faqat yo'qotishga tayyor bo'lgan summani
tiking – his-hayajonga berilib katta pul
tikmang."},
  {"keywords": ["tungi hodisalar", "tunda
nima qilish kerak", "tun bosqichi
maslahat"],
  "answer": "🌙 <b>Tun bosqichi:</b>
Rolingizga mos harakatni vaqtida bajaring –
kechikish imkoniyatni boy beradi."},
  {"keywords": ["ovoz berish
```

```

strategiyasi", "kunduzi kimga ovoz
beraman", "voting maslahat"],
    "answer": "🗳️ <b>Ovoz berish:</b>
Hissiyotga emas, dalilga tayaning – kim
kimni himoya qilayotganini kuzating, bu
ko'p narsani fosh qiladi."},
    {"keywords": ["klan jangida qanday
yutish", "clan war strategiyasi", "klanjang
maslahat"],
    "answer": "⚔️ <b>Klan jangi:</b> Jang
oldidan xazinani mustahkamlang, faol
a'zolari safarbar qiling – birlashgan klan
har doim kuchli."},
    {"keywords": ["turnirda qanday yutish",
"turnir strategiyasi", "champion bolish
uchun"],
    "answer": "🏆 <b>Turnir:</b> Har bir
bosqichda sovuqqonlikni saqlang, xato
qilgan raqibdan albatta foydalaning."},
    {"keywords": ["umumiy g'alaba
strategiyasi", "qanday koproq yutaman",
"g'olib bolish sirlari"],
    "answer": "🏅 <b>Umumiy strategiya:
</b> Muntazam o'ynang, statistikangizni
kuzatib boring (/statistikam), va eng
muhammi – har bir o'yindan saboq oling."},
]

```

```

THERON_FALLBACK_REPLIES = [
    "😞 Bu savolga aniq javobim yo'q, lekin
botning barcha buyruqlarini /yordam orqali
ko'rishingiz mumkin.",
    "😞 To'liq tushunmadim, iltimos

```

```
boshqacharoq so'rab ko'ring – yoki /yordam
orqali buyruqlar ro'yxatini ko'ring.",
    "💬 Hozircha bunga tayyor javobim yo'q.
Klan, duel, ELITE, nikoh, geroy kabi
mavzularda bemalol so'rang!",
]
```

```
#
=====
=====
# 🧨 THERON – 10 TA FAQAT BOT EGASI
(OWNER) UCHUN MAXSUS FUNKSIYA
# Bular is_owner(uid) bo'lgandagina
ishlaydi – Theron bilan oddiy suhbatda
# (savol yozib) ham, /theron orqali ham
chaqirish mumkin.
#
=====
=====
```

```
def _to_umumiy_statistika(uid, elite):
    with db_lock:
        cur.execute("SELECT COUNT(*) FROM
users")
        total_users = cur.fetchone()[0]
        return (f"📊 <b>Umumiy statistika:
</b>\n"
                f"👥 Jami foydalanuvchilar: <b>
{total_users}</b>\n"
                f"🎮 Hozir faol o'yinlar: <b>
{len(GAMES)}</b>")
```



```

def _to_eng_boy_foydalanuvchi(uid, elite):
    with db_lock:
        cur.execute("SELECT user_id, name,
dollar FROM users ORDER BY dollar DESC
LIMIT 1")
        row = cur.fetchone()
        if not row:
            return "💰 Hozircha
foydalanuvchilar bazasi bo'sh."
        return f"💰 Eng boy foydalanuvchi: <b>
{row[1]}</b> – <b>{row[2]}$</b>"

def _to_eng_kuchli_klan(uid, elite):
    with db_lock:
        cur.execute("SELECT name, wins FROM
clans ORDER BY wins DESC LIMIT 1")
        row = cur.fetchone()
        if not row:
            return "🏠 Hozircha birorta klan
yo'q."
        return f"🏠 Eng kuchli klan: <b>
{row[0]}</b> – <b>{row[1]}</b> ta jang
g'alabasi"

def _to_eng_faol_duelchi(uid, elite):
    with db_lock:
        cur.execute("SELECT user_id, name,
duel_wins FROM users ORDER BY duel_wins
DESC LIMIT 1")
        row = cur.fetchone()
        if not row or not row[2]:
            return "🔪 Hozircha birorta duel

```

```

g'alabasi qayd etilmagan."
    return f"🔪 Eng ko'p duel yutgan: <b>
{row[1]}</b> – <b>{row[2]}</b> ta g'alaba"

def _to_bugungi_faollik(uid, elite):
    with db_lock:
        cur.execute("SELECT COUNT(*) FROM
users WHERE last_bonus_date = ?",
(time.strftime("%Y-%m-%d"),))
        active_today = cur.fetchone()[0]
        return f"📅 Bugun kunlik bonus olgan
(faol) foydalanuvchilar: <b>{active_today}
</b> ta"

def _to_elite_soni(uid, elite):
    with db_lock:
        cur.execute("SELECT charges FROM
users WHERE charges IS NOT NULL")
        rows = cur.fetchall()
        now = time.time()
        count = 0
        for (charges_json,) in rows:
            try:
                if json.loads(charges_json or "
{}").get("vip_until", 0) > now:
                    count += 1
            except Exception:
                pass
        return f"👑 Hozirgi faol ELITE a'zolar
soni: <b>{count}</b> ta"

def _to_haftalik_top(uid, elite):

```

```

        rows = get_points_leaderboard("hafta",
limit=3)
        if not rows:
            return "🏆 Bu hafta hali ball
to'plagan foydalanuvchi yo'q."
            lines = ["🏆 <b>Haftalik top 3:</b>"]
            for i, (_uid, name, total) in
enumerate(rows, 1):
                lines.append(f"{i}. {name} –
{total} ball")
            return "\n".join(lines)

def _to_xatolik_holati(uid, elite):
    holat = "🔔 YOQILGAN" if
error_notify_enabled() else "🔔
O'CHIRILGAN"
    return (f"⚠️ Xatolik bildirishnomalari
holati: <b>{holat}</b>\n"
            "O'zgartirish uchun:
/xatolik_bildirish")

def _to_boshqaruv_maslahati(uid, elite):
    return random.choice([
        "💡 Tavsiya: uzoq vaqt kirmagan
foydalanuvchilarga /sendall orqali qaytish
uchun bonus e'lon qilib ko'ring.",
        "💡 Tavsiya: klanlar orasida
musobaqa/turnir e'lon qilish faollikni
oshirishi mumkin.",
        "💡 Tavsiya: haftalik top
o'yinchilarga kichik sovg'a berish ular
uchun rag'bat bo'ladi.",

```

```
])
```

```
def _to_server_holati(uid, elite):  
    return "🤖 Botning texnik holatini  
(uptime, baza hajmi, oqimlar) to'liq  
ko'rish uchun \"⚙️ Admin panel\" ichidagi  
\"🤖 Bot holati\" tugmasini bosing."
```

```
THERON_OWNER_FUNCS = [  
    {"name": "umumiy_statistika",  
     "keywords": ["umumiy statistika", "botda  
nechta foydalanuvchi", "jami  
foydalanuvchi"], "fn":  
_to_umumiy_statistika},  
    {"name": "eng_boy", "keywords": ["eng  
boy foydalanuvchi", "eng kop puli bor kim",  
"eng boy oyinchi kim"], "fn":  
_to_eng_boy_foydalanuvchi},  
    {"name": "eng_kuchli_klan", "keywords":  
["eng kuchli klan qaysi", "top klan kim",  
"eng zor klan"], "fn":  
_to_eng_kuchli_klan},  
    {"name": "eng_faol_duelchi",  
     "keywords": ["eng kop duel yutgan", "eng  
zor duelchi kim"], "fn":  
_to_eng_faol_duelchi},  
    {"name": "bugungi_faollik", "keywords":  
["bugun nechta faol", "bugungi faollik  
qanday", "bugun kimlar kirdi"], "fn":  
_to_bugungi_faollik},  
    {"name": "elite_soni", "keywords":  
["nechta elite bor", "elite azolar soni",
```

```

"hozir nechta elite"], "fn":
_to_elite_soni},
    {"name": "haftalik_top", "keywords":
["haftalik top kim", "bu hafta kim
yetakchi"], "fn": _to_haftalik_top},
    {"name": "xatolik_holati", "keywords":
["xatolik bildirish holati", "xato
xabarlari yoqiqmi", "error notify holati"],
"fn": _to_xatolik_holati},
    {"name": "boshqaruv_maslahati",
"keywords": ["botni qanday
rivojlantiraman", "faollikni qanday
oshiraman", "menga maslahat ber xojayin"],
"fn": _to_boshqaruv_maslahati},
    {"name": "server_holati", "keywords":
["server holati qanday", "bot ishlab
turibdimi", "bot holatini tekshir"], "fn":
_to_server_holati},
]

```

```

THERON_NIGHT_NO_DEATH_TEMPLATES = [
    "Bu tun qishloq ustida sukunat hukm
surdi – hech kim halok bo'lmadi, lekin
soylar hamon nimadir pisanda qilyapti...",
    "G'aroyib tun edi – hamma tirik qoldi,
ammo qishloq osoyishtaligi faqat tashqi
ko'rinish, xolos.",
    "Bu safar o'lim bo'lmadi – lekin bu
tinchlik uzoqqa cho'zilmasligi aniq...",
]

```

```

THERON_NIGHT_DEATH_TEMPLATES = [
    "Tun zulmatida {names} taqdiri hal

```

```
bo'ldi – qishloq ertalab yana bir yo'qotish
bilan uyg'ondi.",
    "Soyalar orasidan chiqqan xavf
{names}ni topdi – ularning o'rni endi bo'sh
qoladi.",
    "Bu tun {names} uchun oxirgi tun bo'ldi
– qishloq ularni hech qachon unutmaydi.",
]
```

```
def theron_night_narration(chat_id,
killed_names, no_death):
    """Tungi voqealarni qisqa, badiiy
tarzda hikoya qiladi. 🛠 Endi TO'LIQ
LOKAL (tasodifiy tanlanadigan tayyor
shablonlar) – tashqi AI shart emas,
shuning uchun hech qachon jim
qolmaydi."""
    try:
        if no_death:
            text =
random.choice(THERON_NIGHT_NO_DEATH_TEMPLAT
ES)
        else:
            names = ", ".join(killed_names)
            text =
random.choice(THERON_NIGHT_DEATH_TEMPLATES)
            .format(names=names)
            bot.send_message(chat_id, f"👤 <i>
{text}</i>")
    except Exception as e:
        _logger.warning("Theron tungi
hikoyasida xatolik (muhim emas): %s", e)
```

```
# 🎉 AI ishlamagan/mavjud bo'lmagan
holatlar uchun – har biri BOSHQA-BOSHQA
# uslubda yozilgan, har safar tasodifiy
tanlanadigan zaxira tabrik shablonlari.
# Har birida albatta {names} o'rni bor –
g'olib(lar) ismi HAR DOIM tilga olinadi.
THERON_CONGRATS_TEMPLATES = [
    "🎉 Zo'r o'yin bo'ldi, {names}!
    Sovuqqonligingiz va aniq hisob-kitobingiz
    g'alabaga olib keldi. Tabriklayman! 🏆",
    "🔥 {names} – bugungi kechening haqiqiy
    qahramonlari! Bunday o'yinni uzoq eslab
    qolishadi. Barakalla!",
    "🧠 Ajoyib strategiya, {names}! Har bir
    qadamingiz o'ylangan edi. G'alaba to'liq
    sizniki! 🏆",
    "☀️ {names}, tabriklayman! Bu safar aql
    va jasorat birlashib g'alaba keltirdi.",
    "👯 Voy-bo'y, {names}! Qanday chiroyli
    yakun! Keyingi o'yinda ham shunday davom
    eting!",
    "🏆 {names} – nomlaringizni reytingga
    oltin harflar bilan yozib qo'yaman! Ajoyib
    o'yin edi.",
    "💪 {names}, sizning bardoshingiz va
    hushyorligingiz g'alabani ta'minladi. Chin
    dildan tabriklayman!",
    "😁 Tabriklaymiz, {names}! Bu kabi
    o'yinlar aynan Hunter Mafia'ni qiziqarli
    qiladi.",
]
```

```

def theron_winner_congrats(chat_id,
winner_names, team_name):
    """O'yin oxirida g'oliblarni
    tabriklaydi. 🛠 Endi TO'LIQ LOKAL –
    tasodifiy
    tanlangan, ismlarni albatta o'z ichiga
    olgan zaxira shablon ishlatiladi
    (team_name hozircha shablonlarda
    ishlatilmaydi, lekin kelajakda kengaytirish
    uchun parametr saqlab qolindi). Shu
    orqali tabrik HAR DOIM keladi va
    HAR SAFAR bir xil bo'lib qolmaydi."""
    if not winner_names:
        return
    names = ", ".join(winner_names[:6])
    text =
random.choice(THERON_CONGRATS_TEMPLATES).fo
rmat(names=names)

    try:
        bot.send_message(chat_id, f"🏆 <b>
{THERON_NAME}dan tabrik:</b> {text}")
    except Exception as e:
        _logger.warning("Theron g'alaba
tabrigini yuborishda xatolik: %s", e)

def _column_exists(table, column):
    try:
        cur.execute(f"PRAGMA
table_info({table})")
        return any(row[1] == column for row
in cur.fetchall())
    except Exception:

```



```

        return False

@bot.message_handler(commands=["theron"])
def cmd_theron(message):
    """🧠 Theron bilan suhbat. Ish tartibi:
    1) Savol bo'lmasa – tanishtiruv.
    2) Savol FAQ bazasida (eng ko'p
    so'raladigan mavzular) topilsa – DARHOL
        javob beriladi, AI so'rov
    QILINMAYDI, kunlik limitdan HECH NARSA
        sarflanmaydi (bu tezkor va bepul
    yo'l).
    3) FAQ'da topilmasa – haqiqiy AI
    (Gemini) chaqiriladi, bu safar kunlik
        limitdan 1 ta sarflanadi (owner
    uchun limit yo'q – u har doim
        ustuvor va cheklovsiz)."""
    try:

        maybe_capture_owner(message.from_user)
        uid = message.from_user.id
        parts =
        message.text.split(maxsplit=1)
        question = parts[1].strip() if
        len(parts) > 1 else ""

        if not question:
            bot.reply_to(
                message,
                f"🧠 <b>{THERON_NAME}</b>
        {THERON_MEANING}\n\n"
                "Men botning sun'iy
        intellekt yordamchisiman – savol bering,

```

```

maslahat so'rang!\n\n"
        "📖 Foydalanish:
<code>/theron savolingiz</code>\n"
        f"🔥 ELITE a'zolar – kuniga
{THERON_ELITE_DAILY_LIMIT} tagacha chuqur
AI-savol\n"
        f"👤 Oddiy foydalanuvchilar
– kuniga {THERON_FREE_DAILY_LIMIT} ta
chuqur AI-savol\n"
        "📖 Eng ko'p so'raladigan
mavzularga (ELITE, klan, duel, nikoh va
h.k.) – LIMITSIZ, DARHOL javob beraman!",
    )
    return

    # 1) 📖 Avval "tezkor bilim bazasi"
(FAQ) – limitsiz, AI shart emas
    faq_answer = faq_lookup(question)
    if faq_answer:
        bot.reply_to(message, f"🧠 <b>
{THERON_NAME}</b>: {faq_answer}")
        return

    # 2) FAQ'da topilmadi – haqiqiy AI
kerak
    if not theron_available():
        bot.reply_to(
            message,
            f"🧠 <b>{THERON_NAME}</b>
{THERON_MEANING}\n\n"
            "Bu savolga tayyor javobim
yo'q ekan, va chuqurroq AI xizmati hozircha
botda "
            "sozlanmagan (bot egasi

```

```

GEMINI_API_KEY ni o'rnatishi kerak). Boshqa
buyruqlar "
            "odatdagidek to'liq
ishlayveradi – /yordam orqali ko'ring."
        )
        return

        elite_user = is_elite(uid)
        allowed, remaining =
theron_check_and_consume_quota(uid,
elite_user)
        if not allowed:
            bot.reply_to(
                message,
                f"⌚ Bugungi {THERON_NAME}
bilan chuqur AI-suhbat limitingiz
tugadi.\n"
                + ("Ertaga qayta urinib
ko'ring." if elite_user else
                f"🔥 ELITE a'zolikda
kunlik limit {THERON_ELITE_DAILY_LIMIT}
tagacha – /elite orqali oling."),
            )
            return

        try:

bot.send_chat_action(message.chat.id,
"typing")
        except Exception:
            pass

        answer = theron_answer_user(uid,
question, elite_user)

```

```

        if not answer:
            bot.reply_to(message, f"⚠️ {THERON_NAME} hozir javob berolmadi (AI xizmati vaqtincha ishlamayapti). Birozdan keyin qayta urinib ko'ring.")
            return

        suffix = f"\n\n<i>🗨️ Bugun yana {remaining} ta chuqur AI-savol qoldi.</i>"
        if not is_owner(uid) else ""
            bot.reply_to(message, f"🧠 <b>{THERON_NAME}</b> {answer}{suffix}")
        except Exception as e:
            notify_owner_of_error("cmd_theron (/theron buyrug'i)", e)
        try:
            bot.reply_to(message, f"⚠️ {THERON_NAME} bilan bog'lanishda xatolik yuz berdi. Qaytadan urinib ko'ring.")
        except Exception:
            pass

@bot.message_handler(
    func=lambda m: (
        m.chat.type == "private"
        and m.from_user.id in
THERON_CHAT_MODE
        and not (m.text or
        "").startswith("/")
    ),
    content_types=["text"],
)
def theron_free_chat(message):

```

```

"""🗨️ Asosiy menyudagi "Theron" tugmasi
orqali suhbat rejimiga kirgan
    foydalanuvchining istalgan (buyruq
bo'lmagan) xabarini Theron'ga savol
    sifatida yuboradi – /theron prefiksi
yozish shart emas. Har bir javobdan
    keyin "🔙 Bosh menyu" tugmasi
qo'shiladi."""
try:

maybe_capture_owner(message.from_user)
    uid = message.from_user.id
    question = (message.text or
    "").strip()
    if not question:
        return

    faq_answer = faq_lookup(question)
    if faq_answer:
        bot.reply_to(message, f"🧠 <b>
{THERON_NAME}</b> {faq_answer}",
reply_markup=with_back_button())
        return

    elite_user = is_elite(uid)
    allowed, remaining =
theron_check_and_consume_quota(uid,
elite_user)
    if not allowed:
        bot.reply_to(
            message,
            f"⌚ Bugungi {THERON_NAME}
bilan chuqur suhbat limitingiz tugadi.\n"
            + ("Ertaga qayta urinib

```

```

ko'ring." if elite_user else
    f"👑 ELITE a'zolikda
kunlik limit {THERON_ELITE_DAILY_LIMIT}
tagacha – /elite orqali oling."),

reply_markup=with_back_button(),
    )
    return

    try:

bot.send_chat_action(message.chat.id,
"typing")
    except Exception:
        pass

        answer = theron_answer_user(uid,
question, elite_user)
        suffix = f"\n\n<i>😊 Bugun yana
{remaining} ta savol qoldi.</i>" if not
is_owner(uid) else ""
        bot.reply_to(message, f"🧠 <b>
{THERON_NAME}:</b> {answer}{suffix}",
reply_markup=with_back_button())
        except Exception as e:

notify_owner_of_error("theron_free_chat
(Theron suhbat rejimi)", e)
    try:
        bot.reply_to(message, f"⚠️
{THERON_NAME} bilan bog'lanishda xatolik
yuz berdi. Qaytadan urinib ko'ring.",
reply_markup=with_back_button())
        except Exception:

```

```
pass
```

```
@bot.message_handler(commands=
["theron_hisobot"])
def cmd_theron_hisobot(message):
    """🔥 FAQAT bot egasi – Theron real
    statistika asosida hisobot + tavsiya
    beradi."""
    try:

maybe_capture_owner(message.from_user)
        safe_delete(message)
        if not
is_owner(message.from_user.id):

bot.send_message(message.chat.id, "🚫 Bu
buyruq faqat bot egasi uchun.")
        return
        try:

bot.send_chat_action(message.chat.id,
"typing")
        except Exception:
            pass
            bot.send_message(message.chat.id,
theron_owner_report_text())
        except Exception as e:

notify_owner_of_error("cmd_theron_hisobot
(/theron_hisobot)", e)
        try:

bot.send_message(message.chat.id, "⚠️
```

```

Hisobotni tayyorlashda xatolik yuz berdi.")
except Exception:
    pass

#
=====
=====
# 🛡️ SPAM/FLOOD HIMOYASI (#4)
# Bir foydalanuvchi juda tez-tez
# (soniyasiga bir nechta) xabar/buyruq
# yuborsa,
# botni sekinlashtirmasligi uchun –
# belgilangan chegaradan tez-tez
# yozganlarning
# xabarlari (butunlay bloklanmasdan,
# faqat) o'tkazib yuboriladi.
# 🛡️ XAVFSIZLIK: middleware ba'zi
# pyTelegramBotAPI versiyalarida yo'q
# bo'lishi
# mumkin – shuning uchun try/except bilan
# o'ralgan: agar kutubxona buni
# qo'llab-quvvatlamasa, bot BARIBIR normal
# ishga tushadi (faqat shu bitta
# qo'shimcha himoyasiz qoladi, boshqa hech
# narsa buzilmaydi).
#
=====
=====

RATE_LIMIT_WINDOW = 2.0      # soniya
RATE_LIMIT_MAX_MSGS = 4      # shu oyna
# ichida ruxsat etilgan maksimal xabar soni
_RATE_LIMIT_LOG = {}         # uid ->
[timestamp, timestamp, ...]

```



```

_RATE_LIMIT_WARNED = {}      # uid ->
oxirgi ogohlantirish vaqti

def _rate_limit_middleware(bot_instance,
message):
    """Har bir kelgan xabar handlerga yetib
borishidan OLDIN ishlaydi. Agar
    foydalanuvchi so'nggi RATE_LIMIT_WINDOW
soniya ichida RATE_LIMIT_MAX_MSGS
    dan ko'proq xabar yuborgan bo'lsa, shu
xabar handlerlarga UZATILMAYDI."""
    try:
        uid = message.from_user.id if
message.from_user else None
        if uid is None or is_owner(uid):
            message._skip_handling = False
            return
        now = time.time()
        log =
_RATE_LIMIT_LOG.setdefault(uid, [])
        log[:] = [t for t in log if now - t
< RATE_LIMIT_WINDOW]
        log.append(now)
        if len(log) > RATE_LIMIT_MAX_MSGS:
            message._skip_handling = True
            last_warn =
_RATE_LIMIT_WARNED.get(uid, 0)
            if now - last_warn > 5: #
ogohlantirishni ham spam qilib yubormaslik
uchun
                _RATE_LIMIT_WARNED[uid] =
now
            try:

```

```

bot.send_message(message.chat.id, "⌚ Juda
tez-tez yozyapsiz – biroz sekinroq urinib
ko'ring.")

        except Exception:
            pass

    else:
        message._skip_handling = False
    except Exception:
        message._skip_handling = False #
xatolik bo'lsa ham xabar bloklanib qolmasin

def _rate_limited_dropper(message):
    """Middleware 'skip' deb belgilagan
xabarlarni jimgina yutadi – boshqa hech
qanday handlerga yubormaydi. ENG
BIRINCHI bo'lib ro'yxatga olinishi shart
(shuning uchun fayl boshida turadi) –
pyTelegramBotAPI xabarni FAQAT birinchi
mos kelgan handlerga yuboradi."""
    pass

try:
    # (ENABLE_MIDDLEWARE endi yuqorida, bot
yaratilishidan OLDIN o'rnatiladi – bu yerda
qayta kerak emas)
    bot.middleware_handler(update_types=
["message"])(_rate_limit_middleware)
    bot.message_handler(func=lambda m:
getattr(m, "_skip_handling", False))
    (_rate_limited_dropper)
    _logger.info("🛡️ Spam/flood himoyasi

```

```

middleware muvaffaqiyatli yoqildi.")
except Exception as e:
    _logger.warning(
        "🛡️ Spam/flood himoyasi
middleware'ni yoqib bo'lmadi (kutubxona
versiyasi "
        "qo'llab-quvvatlamasligi mumkin) –
bot BARIBIR normal ishlayveradi: %s", e,
    )

BOT_USERNAME = None
OWNER_USERNAME = "Mirkamilovic"
# Ishonchli usul: agar aniq user_id muhit
o'zgaruvchisida berilgan bo'lsa, shu
ustuvor bo'ladi.
# Bu username o'zgarib qolsa ham yoki bir
nechta admin bo'lsa ham ishonchli ishlaydi.
# Muhit o'zgaruvchisi berilmagan hollarda
bot yaratuvchisining shaxsiy Telegram ID'si
# standart qiymat sifatida ishlatiladi
(5588583777).
_owner_env_raw =
os.environ.get("HUNTER_MAFIA_OWNER_ID",
    "").strip()
OWNER_ID_FROM_ENV = int(_owner_env_raw) if
_owner_env_raw.lstrip("-").isdigit() else
5588583777

MIN_PLAYERS = 3
CORE_ROLE_THRESHOLD = 7

# --- YANGILANGAN VAQT SOZLAMALARI ---
# 🌙 Tun uzunligi (soniya)
NIGHT_SECONDS = 45

```

```
# 🌞 Kun (kunduzgi bosqich) umumiy uzunligi
(soniya) – muhokama + ovoz berish
DAY_TOTAL_SECONDS = 90
# 🗨️ Kun boshlangandan keyin ovoz berish
tugmalari nechki soniyadan so'ng chiqishi
DAY_DISCUSSION_SECONDS = 30
# 🗳️ Ovoz berish davomiyligi (soniya) –
ovoz tugmalari chiqqandan keyin
DAY_VOTE_SECONDS = DAY_TOTAL_SECONDS -
DAY_DISCUSSION_SECONDS
LAST_WORDS_SECONDS = 30
# 👍/👎 eng ko'p ovoz olgan ishtirokchini
"rostan ham osamizmi?" deb yakuniy
# tasdiqlash ovoz berishi shu qadar soniya
davom etadi (yoki barcha tirik
# o'yinchilar ovoz bergach, muddatidan
oldin yakunlanadi)
CONFIRM_VOTE_SECONDS = 20

WIN_REWARD = 70
LOSE_REWARD = 20

HC_STAR_RATE = 15    # 15 🌟 Stars = 1 🪙
Hunter Coin (avval 5 edi – Hunter Coin
qimmatroq bo'lishi uchun oshirildi)

# 🛒 Qora bozor faqat shu guruhda ishlashi
kerak: https://t.me/+v9bYoMk-0hAyZTcy
# Telegram taklif havolasi orqali
chat_id'ni oldindan bilib bo'lmaydi (bot
guruhga
# qo'shilmaguncha), shuning uchun bot egasi
guruhga botni qo'shgach, o'sha guruhda
# bir marta /shu_bozor buyrug'ini yozishi
```

```
kerak – chat_id shu yerda avtomatik
saqlanadi.
BLACK_MARKET_CHAT_ID = None # dastlab
bo'sh, keyin /shu_bozor orqali yoki bazadan
yuklanadi
CURRENCY_ICON = {"dollar": "💵", "diamond":
"💎", "coin": "🪙"}

NIGHT_PHOTO =
"https://images.unsplash.com/photo-
1518837695005-2083093ee35b?
q=80&w=1200&auto=format&fit=crop"
DAY_PHOTO =
"https://images.unsplash.com/photo-
1441974231531-c6227db76b6e?
q=80&w=1200&auto=format&fit=crop"
MAIN_PHOTO =
"https://images.unsplash.com/photo-
1514565131-fce0801e5785?
q=80&w=1000&auto=format&fit=crop"
# 📁 Foydalanuvchi o'zi tanlagan suratlar –
skript bilan bir joyda "assets" papkasida
# saqlanadi. Agar shu fayllar mavjud
bo'lsa, ular yuqoridagi Unsplash havolalari
# o'rniga ishlatiladi (fayl topilmasa,
xavfsiz tarzda eski URL'ga qaytiladi).
ASSETS_DIR =
os.path.dirname(os.path.abspath(__file__))
NIGHT_PHOTO_LOCAL =
os.path.join(ASSETS_DIR, "night.jpg")
DAY_PHOTO_LOCAL = os.path.join(ASSETS_DIR,
"day.jpg")
```

```
#
=====
=====
# MA'LUMOTLAR BAZASI (SQLite)
#
=====
=====

# MUHIM TUZATISH: baza fayli nisbiy yo'l
("hunter_mafia.db") emas, balki skript
# joylashgan papkaga QATTIQ bog'langan yo'l
bilan ochiladi. Aks holda botni har xil
# papkadan yoki har xil ishga tushirish
usulida (masalan hosting qayta ishga
# tushganda) ishga tushirilsa, Python HAR
SAFAR YANGI, BO'SH baza fayli yaratib
# qo'yardi – go'yo eski foydalanuvchilar
ma'lumoti "o'chib ketganday" ko'rinardi,
# aslida esa eski fayl boshqa joyda tinch
turardi.
# MUHIM: Railway kabi hostinglarda
konteyner fayl tizimi VAQTINCHALIK
(ephemeral) –
# har deploy/qayta ishga tushishda hamma
fayl o'chib, botning "eski foydalanuvchilar
# yo'qolib qoldi" degan muammosi aynan
shundan kelib chiqadi. Buni hal qilish
uchun
# Railway'da "Volume" (doimiy disk) ulanib,
uning yo'li DB_DIR muhit o'zgaruvchisiga
# beriladi (masalan: DB_DIR=/data). Volume
ulanmagan/lokal ishlatilganda esa
avvalgidek
# skript papkasining o'zida saqlanadi.
```

```

BASE_DIR =
os.path.dirname(os.path.abspath(__file__))
DB_DIR = os.environ.get("DB_DIR",
    "").strip() or BASE_DIR
DB_PATH = os.path.join(DB_DIR,
    "hunter_mafia.db")
# 🔄 Bot tiklash (restore) tizimi uchun –
aktiv o'yinlarning "suratini" shu faylga
# saqlaymiz, DB bilan bir xil (doimiy)
pakada, shunda qayta ishga tushganda
# (deploy, xatolik, /tiklash buyrug'i)
o'yinlar avtomatik davom ettiriladi.
STATE_PATH = os.path.join(DB_DIR,
    "hunter_mafia_state.json")

conn = sqlite3.connect(DB_PATH,
    check_same_thread=False)
db_lock = threading.RLock()
cur = conn.cursor()

# 🛠 MUSTAHKAMLASH: WAL (Write-Ahead Log)
rejimi – server to'satdan o'chib qolsa
# yoki jarayon majburan to'xtatilsa ham,
bazaning yarim yozilgan holatda
# buzilib qolish ehtimoli sezilarli
kamayadi (oddiy "rollback journal" rejimiga
# nisbatan ancha barqaror).
"synchronous=NORMAL" esa WAL bilan birga
xavfsiz va
# tezroq ishlaydi (har bir yozuvda diskka
to'liq fsync qilib o'tirmaydi).
try:
    cur.execute("PRAGMA journal_mode=WAL")
    cur.execute("PRAGMA

```

```

synchronous=NORMAL")
except Exception as _pragma_err:
    print(f"⚠️ SQLite PRAGMA sozlanmadi
(muhim emas, davom etamiz): {_pragma_err}")

cur.execute("SELECT COUNT(*) FROM
sqlite_master WHERE type='table' AND
name='users'")
_users_table_existed = cur.fetchone()[0] >
0
logging.info(f"📁 Baza fayli: {DB_PATH}")

cur.execute("""
CREATE TABLE IF NOT EXISTS users (
    user_id INTEGER PRIMARY KEY,
    name TEXT,
    dollar INTEGER DEFAULT 0,
    diamond INTEGER DEFAULT 0,
    coin INTEGER DEFAULT 0,
    games INTEGER DEFAULT 0,
    wins INTEGER DEFAULT 0,
    shield INTEGER DEFAULT 0,
    inventory TEXT DEFAULT '[]',
    married_to INTEGER DEFAULT 0,
    last_bonus_date TEXT DEFAULT ''
)
""")
# eski bazalarda "charges" ustuni
bo'lmashligi mumkin – xavfsiz qo'shamiz
try:
    cur.execute("ALTER TABLE users ADD
COLUMN charges TEXT DEFAULT '{}')
    conn.commit()
except sqlite3.OperationalError:

```



```

pass

# YANGI (qo'shimcha kodlar orqali
qo'shildi): duel statistikasi va ban tizimi
uchun ustunlar
for _col, _default in (("duel_wins", "0"),
("duel_losses", "0"), ("banned", "0")):
    try:
        cur.execute(f"ALTER TABLE users ADD
COLUMN {_col} INTEGER DEFAULT {_default}")
        conn.commit()
    except sqlite3.OperationalError:
        pass

# YANGI: /paralar buyrug'i uchun – nikoh
qurilgan sanani saqlaymiz (necha kunligini
hisoblash uchun)
try:
    cur.execute("ALTER TABLE users ADD
COLUMN married_at TEXT DEFAULT '')")
    conn.commit()
except sqlite3.OperationalError:
    pass

cur.execute("""
CREATE TABLE IF NOT EXISTS known_groups (
    chat_id INTEGER PRIMARY KEY,
    title TEXT
)
""")
cur.execute("""
CREATE TABLE IF NOT EXISTS bot_settings (
    key TEXT PRIMARY KEY,
    value TEXT

```

```

)
"""
cur.execute("""
CREATE TABLE IF NOT EXISTS clans (
    owner_id INTEGER PRIMARY KEY,
    name TEXT
)
"""
# --- YANGI (qoshimchakod9.py "Klan jangi"
# oyasi asosida) – klan a'zolari va jang
# statistikasi ---
cur.execute("""
CREATE TABLE IF NOT EXISTS clan_members (
    owner_id INTEGER,
    member_id INTEGER,
    member_name TEXT,
    PRIMARY KEY (owner_id, member_id)
)
"""

# --- KLANLAR JANGI – TO'LIQ TIZIM
# (foydalanuvchi yuborgan TXT texnik
# topshiriq asosida) ---
# Mavjud "clans"/"clan_members"
# jadvallariga yangi ustunlar qo'shamiz (eski
# bazalar buzilmasin
# deb har biri alohida, xavfsiz try/except
# bilan). Lider deb "clans.owner_id"
# ishlatiladi.
_CLAN_COLUMNS = [
    ("clans", "level", "INTEGER DEFAULT
1"),
    ("clans", "deputy_id", "INTEGER"),
    ("clans", "leader_level", "INTEGER

```

```

DEFAULT 3"),
    ("clans", "treasury_dollar", "INTEGER
DEFAULT 0"),
    ("clans", "treasury_diamond", "INTEGER
DEFAULT 0"),
    ("clans", "levelup_tokens", "INTEGER
DEFAULT 10"), # "birinchi o'yinda liderga
10 lvl up beriladi"
    ("clans", "wins", "INTEGER DEFAULT 0"),
    ("clans", "losses", "INTEGER DEFAULT
0"),
    ("clans", "win_streak", "INTEGER
DEFAULT 0"),
    ("clans", "war_declines_streak",
"INTEGER DEFAULT 0"),
    ("clans", "last_war_at", "REAL DEFAULT
0"),
    ("clans", "deputy_levelups_used",
"INTEGER DEFAULT 0"),
    ("clans", "last_inactivity_penalty_at",
"REAL DEFAULT 0"),
    ("clan_members", "level", "INTEGER
DEFAULT 0"),
    ("clan_members", "title", "TEXT"), #
NULL, 'ritsar' yoki 'sehrgar'
]
for _table, _col, _decl in _CLAN_COLUMNS:
    try:
        cur.execute(f"ALTER TABLE {_table}
ADD COLUMN {_col} {_decl}")
        conn.commit()
    except sqlite3.OperationalError:
        pass

```

```

cur.execute("""
CREATE TABLE IF NOT EXISTS
clan_join_requests (
    owner_id INTEGER,
    user_id INTEGER,
    user_name TEXT,
    requested_at REAL,
    PRIMARY KEY (owner_id, user_id)
)
""")
cur.execute("""
CREATE TABLE IF NOT EXISTS clan_wars (
    war_id INTEGER PRIMARY KEY
AUTOINCREMENT,
    clan_a INTEGER,
    clan_b INTEGER,
    winner_owner_id INTEGER,
    started_at REAL,
    ended_at REAL
)
""")
conn.commit()

# --- YANGI: FAOLLIK BALLARI TIZIMI
(kunlik/haftalik/oylik/mutlaq reyting
uchun) ---
# Har bir voqea (o'yin g'alaba/mag'lubiyat,
faollik, AFK jarima) alohida qatorda,
# vaqt belgisi bilan saqlanadi – shu orqali
istalgan davr uchun yig'indi hisoblanadi.
cur.execute("""
CREATE TABLE IF NOT EXISTS points_log (
    id INTEGER PRIMARY KEY AUTOINCREMENT,
    user_id INTEGER,

```

```

        points INTEGER,
        reason TEXT,
        ts REAL
    )
    """)
conn.commit()

# --- YANGI: GEROYLAR TIZIMI (Olmos
do'konidagi "Afsonaviy Sandiq") ---
cur.execute("""
CREATE TABLE IF NOT EXISTS heroes (
    user_id INTEGER PRIMARY KEY,
    hero_key TEXT,
    level INTEGER DEFAULT 1,
    acquired_at REAL DEFAULT 0
)
""")
conn.commit()
# eski bazalarda "acquired_at" ustuni
bo'lmasligi mumkin – xavfsiz qo'shamiz
try:
    cur.execute("ALTER TABLE heroes ADD
COLUMN acquired_at REAL DEFAULT 0")
    conn.commit()
except Exception:
    pass
# YANGI: vaqtincha (muddatli) geroy berish
uchun – 0 = doimiy, >0 = shu vaqtda tugaydi
try:
    cur.execute("ALTER TABLE heroes ADD
COLUMN temp_until REAL DEFAULT 0")
    conn.commit()
except Exception:
    pass

```

```

cur.execute("""
CREATE TABLE IF NOT EXISTS promo_codes (
    code TEXT PRIMARY KEY,
    dollar INTEGER DEFAULT 0,
    diamond INTEGER DEFAULT 0,
    coin INTEGER DEFAULT 0,
    max_uses INTEGER DEFAULT 1,
    used_count INTEGER DEFAULT 0
)
""")
# 🎁 shaxsiylashtirilgan promo-kodlar – eng
# faol o'yinchilar uchun, kodni ishlatgan
# har bir kishi kod egasiga +10$ olib
# keladi
try:
    cur.execute("ALTER TABLE promo_codes
ADD COLUMN owner_id INTEGER")
    conn.commit()
except sqlite3.OperationalError:
    pass
cur.execute("""
CREATE TABLE IF NOT EXISTS
promo_redemptions (
    code TEXT,
    user_id INTEGER,
    PRIMARY KEY (code, user_id)
)
""")
# --- YANGI: ikki guruhli "Qizil vs Ko'k"
# musobaqa tizimi ---
# Ikkita alohida guruh bir-biriga "juft"
# qilib bog'lanadi. Har birida o'z mafiya
# o'yini mustaqil o'ynaladi, lekin har bir
# o'yin natijasi umumiy hisobga (score)

```

```

qo'shiladi.
cur.execute("""
CREATE TABLE IF NOT EXISTS group_pairs (
    chat_id_a INTEGER PRIMARY KEY,
    chat_id_b INTEGER,
    label_a TEXT DEFAULT 'Qizil ●',
    label_b TEXT DEFAULT 'Ko''k ●',
    score_a INTEGER DEFAULT 0,
    score_b INTEGER DEFAULT 0
)
""")
conn.commit()
# --- YANGI (qoshimchakod5.py "Qora Bozor"
# g'oyasi asosida) – o'yinchilar o'rtasidagi
# savdo ---
cur.execute("""
CREATE TABLE IF NOT EXISTS market_listings
(
    id INTEGER PRIMARY KEY AUTOINCREMENT,
    chat_id INTEGER,
    seller_id INTEGER,
    seller_name TEXT,
    item TEXT,
    price INTEGER,
    active INTEGER DEFAULT 1
)
""")
conn.commit()
# eski bazalarda "currency" ustuni
# bo'lmasligi mumkin – xavfsiz qo'shamiz
# (standart: coin)
try:
    cur.execute("ALTER TABLE
market_listings ADD COLUMN currency TEXT

```

```

DEFAULT 'coin'")
    conn.commit()
except sqlite3.OperationalError:
    pass

USER_COLS = ["user_id", "name", "dollar",
             "diamond", "coin", "games", "wins",
             "shield", "inventory",
             "married_to", "last_bonus_date", "charges",
             "duel_wins", "duel_losses",
             "banned", "married_at"]

def get_user_row(uid, name=None):
    with db_lock:
        cur.execute("SELECT * FROM users
WHERE user_id=?", (uid,))
        row = cur.fetchone()
        if row is None:
            cur.execute("INSERT INTO users
(user_id, name) VALUES (?,?)", (uid, name
or str(uid)))
            conn.commit()
            cur.execute("SELECT * FROM
users WHERE user_id=?", (uid,))
            row = cur.fetchone()
            elif name and row[1] != name:
                cur.execute("UPDATE users SET
name=? WHERE user_id=?", (name, uid))
                conn.commit()
                row = list(row)
                row[1] = name
                row = tuple(row)
        return row

```



```

def user_dict(uid, name=None):
    row = get_user_row(uid, name)
    d = dict(zip(USER_COLS, row))
    if d.get("charges") is None:
        d["charges"] = "{}"
    if d.get("duel_wins") is None:
        d["duel_wins"] = 0
    if d.get("duel_losses") is None:
        d["duel_losses"] = 0
    if d.get("banned") is None:
        d["banned"] = 0
    if d.get("married_at") is None:
        d["married_at"] = ""
    return d

def update_user(uid, **fields):
    with db_lock:
        keys = ", ".join(f"{k}=?" for k in
fields)
        vals = list(fields.values()) +
[uid]
        cur.execute(f"UPDATE users SET
{keys} WHERE user_id=?", vals)
        conn.commit()

def add_balance(uid, dollar=0, diamond=0,
coin=0):
    u = user_dict(uid)
    update_user(
        uid,

```

```

        dollar=max(0, u["dollar"] +
dollar),
        diamond=max(0, u["diamond"] +
diamond),
        coin=max(0, u["coin"] + coin),
    )

def add_inventory_item(uid, item_name):
    u = user_dict(uid)
    inv = json.loads(u["inventory"])
    inv.append(item_name)
    update_user(uid,
inventory=json.dumps(inv))

def remove_inventory_item_by_index(uid,
index):
    """Qora bozorga sotuvga qo'yish uchun –
inventardagi index bo'yicha buyumni
olib tashlaydi va nomini qaytaradi
(qoshimchakod5.py g'oyasi asosida)."""
    u = user_dict(uid)
    inv = json.loads(u["inventory"])
    if index < 0 or index >= len(inv):
        return None
    item = inv.pop(index)
    update_user(uid,
inventory=json.dumps(inv))
    return item

def add_shield(uid, n=1):
    u = user_dict(uid)

```

```

        update_user(uid, shield=u["shield"] +
n)

def consume_shield(uid):
    u = user_dict(uid)
    if u["shield"] > 0:
        update_user(uid, shield=u["shield"]
- 1)
        return True
    return False

# ---- "charges" (jangovar effektlar)
tizimi – har bir do'kon buyumi shu orqali
ishlaydi ----

def get_charges(uid):
    u = user_dict(uid)
    try:
        return json.loads(u.get("charges")
or "{}")
    except Exception:
        return {}

def set_charges(uid, ch):
    update_user(uid,
charges=json.dumps(ch))

def add_charge(uid, key, n=1):
    ch = get_charges(uid)
    ch[key] = ch.get(key, 0) + n

```

```

set_charges(uid, ch)

def use_charge(uid, key, n=1):
    ch = get_charges(uid)
    if ch.get(key, 0) >= n:
        ch[key] -= n
        set_charges(uid, ch)
    return True
    return False

def set_charge_value(uid, key, value):
    ch = get_charges(uid)
    ch[key] = value
    set_charges(uid, ch)

#
=====
# BUYUMLARNI YOQISH/O'CHIRISH (faqat
avtomatik ishlaydigan buyumlar uchun) –
# o'yinchi xohlagan buyumini "faol" yoki
"faol emas" holatga o'tkaza oladi.
# Standart: agar hech qachon
o'zgartirilmagan bo'lsa – FAOL (eski xatti-
harakat saqlanadi).
#
=====
=====

TOGGLEABLE_ITEMS = {
    "fake_doc": "📄 Soxta Hujjat",

```

```
"night_vision": "👁️ Tungi ko'zoynak",
"confuse": "📧 Tushunarsiz xat",
"golden_bullet": "🟡 Oltin o'q",
"revive": "⚡ Tezkor jonlanish",
"watch_eyes": "👁️ Kuzatish ko'zi",
"duel_adv": "🔪 Olmos Qilich (duel
ustunligi)",
"antidote": "💊 Kichik Aptechka",
"hidden_vote": "👛 Shubhali sumka",
}
```

```
def is_item_active(uid, key):
    ch = get_charges(uid)
    active_map = ch.get("active", {})
    return active_map.get(key, True) #
standart: faol
```

```
def toggle_item_active(uid, key):
    ch = get_charges(uid)
    active_map = ch.get("active", {})
    new_state = not active_map.get(key,
True)
    active_map[key] = new_state
    ch["active"] = active_map
    set_charges(uid, ch)
    return new_state
```

```
def build_toggle_menu(uid):
    ch = get_charges(uid)
    kb = types.InlineKeyboardMarkup()
    any_item = False
```

```

        for key, label in
            TOGGLEABLE_ITEMS.items():
                if ch.get(key, 0) <= 0:
                    continue
                any_item = True
                state = "✅ FAOL" if
is_item_active(uid, key) else "❌ O'CHIQ"

kb.add(types.InlineKeyboardButton(f"{label}
- {state}", callback_data=f"toggleitem|
{key}"))
        return kb, any_item

@bot.message_handler(commands=
["kuchlarim"])
def cmd_kuchlarim(message):
    """Foydalanuvchi o'ziga tegishli
    avtomatik ishlaydigan buyumlarni
    yoqib/o'chirib qo'ya oladi."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    uid = message.from_user.id
    kb, any_item = build_toggle_menu(uid)
    if not any_item:
        bot.send_message(
            message.chat.id,
            "🛒 Sizda hozircha
    yoqish/o'chirish mumkin bo'lgan buyum
    yo'q.\n"
            "Do'kondan xarid qiling, keyin
    shu yerdan boshqarasiz.",
        )
    return

```

```

        bot.send_message(
            message.chat.id,
            "⚙️ <b>Buyumlaringizni
boshqarish</b>\n\n"
            "Quyidagi buyumlar o'yin davomida
avtomatik ishlaydi. Kerak bo'lmasa,
o'chirib qo'yishingiz mumkin – "
            "shunda ular o'zi ishlab ketmaydi,
faqat siz xohlagan payt yana yoqasiz.",
            reply_markup=kb,
        )

@bot.callback_query_handler(func=lambda c:
c.data.startswith("toggleitem|"))
def cb_toggle_item(call):
    maybe_capture_owner(call.from_user)
    key = call.data.split("|", 1)[1]
    uid = call.from_user.id
    if get_charges(uid).get(key, 0) <= 0:
        bot.answer_callback_query(call.id,
        "❌ Bu buyum sizda mavjud emas.",
        show_alert=True)
        return
    new_state = toggle_item_active(uid,
key)
    label = TOGGLEABLE_ITEMS.get(key, key)
    bot.answer_callback_query(call.id, f"
{label}: {'✅ Yoqildi' if new_state else
'❌ O'chirildi'}")
    kb, _ = build_toggle_menu(uid)
    try:

bot.edit_message_reply_markup(call.message.

```

```

chat.id, call.message.message_id,
reply_markup=kb)
except Exception:
    pass

def luck_mult(uid):
    """🦊 Cheksiz omad tulki tumori –
    barcha pul yutuqlarini ko'paytiradi.
    🏆 Geroy (Elandriel/Zephyrion "Omad
    tumori") – qo'shimcha ustama beradi.
    🔧 Endi ABADIY emas – har xarid faqat
    MULTIPLIER_DURATION_SECONDS (3 kun)
    davomida amal qiladi, muddati o'tsa
    avtomatik x1'ga qaytadi."""
    base = get_timed_multiplier(uid,
    "luck_mult")
    return base + hero_luck_boost(uid)

def bonus_mult(uid):
    """🇺🇸/🌐/🏠 – kunlik bonusni
    ko'paytiradi. 🔧 3 kunlik limit bilan."""
    return get_timed_multiplier(uid,
    "bonus_mult")

MULTIPLIER_DURATION_SECONDS = 3 * 86400 #
🔧 x2/x3 multiplikatorlar endi faqat 3 KUN
amal qiladi (abadiy emas)

def get_timed_multiplier(uid, key,
default=1):

```



```

        ch = get_charges(uid)
        until = ch.get(key + "_until", 0)
        if until and time.time() < until:
            return ch.get(key + "_val",
default)
        return default

def add_known_group(chat_id, title):
    with db_lock:
        cur.execute("INSERT OR REPLACE INTO
known_groups (chat_id, title) VALUES
(?,?)", (chat_id, title))
        conn.commit()

def remove_known_group(chat_id):
    with db_lock:
        cur.execute("DELETE FROM
known_groups WHERE chat_id=?", (chat_id,))
        conn.commit()

def list_known_groups():
    with db_lock:
        cur.execute("SELECT chat_id, title
FROM known_groups")
        return cur.fetchall()

# ---- "Qizil vs Ko'k" ikki-guruhli
musobaqa yordamchilari ----

def get_pair(chat_id):

```

```

        """Berilgan guruh biror juftlikka
        bog'langan bo'lsa, o'sha yozuvni qaytaradi
        (chat_id qaysi tomonda bo'lishidan
        qat'iy nazar), aks holda None."""
        with db_lock:
            cur.execute("SELECT chat_id_a,
            chat_id_b, label_a, label_b, score_a,
            score_b FROM group_pairs WHERE chat_id_a=?
            OR chat_id_b=?", (chat_id, chat_id))
            return cur.fetchone()

def create_pair(chat_id_a, chat_id_b):
    with db_lock:
        cur.execute("DELETE FROM
        group_pairs WHERE chat_id_a IN (?,?) OR
        chat_id_b IN (?,?)", (chat_id_a, chat_id_b,
        chat_id_a, chat_id_b))
        cur.execute("INSERT INTO
        group_pairs (chat_id_a, chat_id_b) VALUES
        (?,?)", (chat_id_a, chat_id_b))
        conn.commit()

def remove_pair(chat_id):
    with db_lock:
        cur.execute("DELETE FROM
        group_pairs WHERE chat_id_a=? OR
        chat_id_b=?", (chat_id, chat_id))
        conn.commit()

def add_pair_score(chat_id,
winning_chat_id):

```

```

    """`chat_id` juftlikning bir tomoni.
    `winning_chat_id` shu turdagi o'yin g'olibi
    bo'lgan guruh (odatda chat_id'ning
    o'zi). Ballni oshirib, yangilangan yozuvni
    qaytaradi."""
    pair = get_pair(chat_id)
    if not pair:
        return None
    ca, cb, label_a, label_b, score_a,
score_b = pair
    if winning_chat_id == ca:
        score_a += 1
    elif winning_chat_id == cb:
        score_b += 1
    with db_lock:
        cur.execute("UPDATE group_pairs SET
score_a=?, score_b=? WHERE chat_id_a=?",
(score_a, score_b, ca))
        conn.commit()
    return (ca, cb, label_a, label_b,
score_a, score_b)

def get_setting(key):
    with db_lock:
        cur.execute("SELECT value FROM
bot_settings WHERE key=?", (key,))
        row = cur.fetchone()
        return row[0] if row else None

def set_setting(key, value):
    with db_lock:
        cur.execute("INSERT OR REPLACE INTO

```

```

bot_settings (key, value) VALUES (?,?)",
(key, str(value)))
    conn.commit()

def error_notify_enabled():
    """🔔 Bot egasiga xatolik xabarnomalari
yuborilishi kerakmi – bazadagi
sozlamadan o'qiydi. Sozlama umuman
kiritilmagan bo'lsa (masalan bot
birinchi marta ishga tushirilganda),
DEFAULT holatda YOQILGAN deb
hisoblanadi – shuning uchun xato haqida
darhol xabar berib turadi."""
    val =
get_setting("error_notify_enabled")
    return val != "0"

@bot.message_handler(commands=
["xatolik_bildirish"])
def cmd_xatolik_bildirish(message):
    """🔔/🔕 Bot egasiga (OWNER) botda yuz
beradigan xatoliklar haqidagi
avtomatik Telegram xabarnomalarini
YOQIB yoki O'CHIRIB turadigan buyruq.
Faqat bot egasi uchun ishlaydi.
Argumentsiz chaqirilsa – hozirgi holatni
teskarisiga o'zgartiradi (toggle);
"/xatolik_bildirish yoq" yoki
"/xatolik_bildirish ochiq" – majburan
yoqadi; "/xatolik_bildirish off"
yoki "/xatolik_bildirish yopiq" –
majburan o'chiradi."""

```

```

maybe_capture_owner(message.from_user)
if not is_owner(message.from_user.id):
    return
parts = message.text.split(maxsplit=1)
arg = parts[1].strip().lower() if
len(parts) > 1 else None

current = error_notify_enabled()
if arg in ("on", "yoq", "yoqish",
"yoqilgan", "ochiq", "ochish", "yes", "1"):
    new_state = True
elif arg in ("off", "ochiriq",
"o'chir", "ochir", "o'chirish", "yopiq",
"no", "0"):
    new_state = False
else:
    new_state = not current # 🔄
argument berilmasa – teskarisiga o'giradi

set_setting("error_notify_enabled", "1"
if new_state else "0")

if new_state:
    bot.send_message(
        message.chat.id,
        "🔔 <b>Xatolik
bildirishnomalari YOQILDI.</b>\n\n"
        "Botda kutilmagan xatolik yuz
bersa, endi shu yerga (Telegram orqali) "
        "avtomatik xabar keladi.",
    )
else:
    bot.send_message(
        message.chat.id,

```

```

        "🚨 <b>Xatolik
        bildirishnomalari O'CHIRILDI.</b>\n\n"
        "Botda xatolik yuz berganda
        endi bu yerga xabar KELMAYDI – xatolar "
        "faqat server log fayliga
        yozilib boradi. Qayta yoqish uchun: "
        "/xatolik_bildirish",
    )

```

```

def get_top_players(limit=10):
    """🔥 Qirol unvoni egalari tepada
    chiqadi, 👤 Shadow statusidagilar va bot
    egasi reytingdan doim yashiriladi."""
    with db_lock:
        cur.execute("SELECT user_id, name,
        wins, dollar, charges FROM users ORDER BY
        wins DESC, dollar DESC LIMIT 200")
        rows = cur.fetchall()
        normal, qirol = [], []
        for user_id, name, wins, dollar,
        charges_json in rows:
            if is_owner(user_id):
                continue
            try:
                ch = json.loads(charges_json or
                "{}")
            except Exception:
                ch = {}
            if ch.get("shadow_until", 0) >
            time.time():
                continue
            entry = (user_id, name, wins,
            dollar, ch.get("qirol_until", 0) >

```

```

time.time())
        (qirol if entry[4] else
normal).append(entry)
    return (qirol + normal)[:limit]

```

TOP_PAGE_SIZE = 10 # 🛠️ YANGI (#9): har sahifada nechta o'yinchi ko'rsatilishi

```

def build_top_text(page=0):
    rows = get_top_players(limit=50) #
endi 10 emas – 50 tagacha, sahifalab
ko'rsatiladi
    if not rows:
        return "🏆 Hozircha reyting
bo'sh.", 1
    total_pages = max(1, (len(rows) +
TOP_PAGE_SIZE - 1) // TOP_PAGE_SIZE)
    page = max(0, min(page, total_pages -
1))
    chunk = rows[page * TOP_PAGE_SIZE: page
* TOP_PAGE_SIZE + TOP_PAGE_SIZE]
    lines = ["🏆 <b>TOP O'YINCHILAR
(g'alabalar bo'yicha)</b>\n"]
    for i, (user_id, name, wins, dollar,
is_qirol) in enumerate(chunk, page *
TOP_PAGE_SIZE + 1):
        crown = "👑 " if is_qirol else ""
        lines.append(f"{i}. {crown}
{mention(user_id, name)} – {wins} g'alaba,
${dollar}")
    lines.append(f"\n📄 {page +
1}/{total_pages}-sahifa")

```

```

        return "\n".join(lines), total_pages

def get_top_by_field(field, limit=50):
    """field: 'diamond' yoki 'dollar' – 👤
    Shadow statusidagilar va bot egasi
    reytingdan doim yashiriladi."""
    with db_lock:
        cur.execute(f"SELECT user_id, name,
{field}, charges FROM users ORDER BY
{field} DESC LIMIT 200")
        rows = cur.fetchall()
        result = []
        for user_id, name, value, charges_json
in rows:
            if is_owner(user_id):
                continue
            try:
                ch = json.loads(charges_json or
"{}")
            except Exception:
                ch = {}
            if ch.get("shadow_until", 0) >
time.time():
                continue
            result.append((user_id, name,
value))
        return result[:limit]

def build_top_diamond_text(page=0):
    rows = get_top_by_field("diamond")
    if not rows:
        return "💎 Hozircha reyting

```



```

bo'sh.", 1
    total_pages = max(1, (len(rows) +
TOP_PAGE_SIZE - 1) // TOP_PAGE_SIZE)
    page = max(0, min(page, total_pages -
1))
    chunk = rows[page * TOP_PAGE_SIZE: page
* TOP_PAGE_SIZE + TOP_PAGE_SIZE]
    lines = ["💎 <b>TOP ENG KO'P OLMOSI BOR
O'YINCHILAR</b>\n"]
    for i, (user_id, name, diamond) in
enumerate(chunk, page * TOP_PAGE_SIZE + 1):
        lines.append(f"{i}.
{mention(user_id, name)} - 💎 {diamond}")
    lines.append(f"\n📄 {page +
1}/{total_pages}-sahifa")
    return "\n".join(lines), total_pages

```

```

def build_top_dollar_text(page=0):
    rows = get_top_by_field("dollar")
    if not rows:
        return "💰 Hozircha reyting
bo'sh.", 1
    total_pages = max(1, (len(rows) +
TOP_PAGE_SIZE - 1) // TOP_PAGE_SIZE)
    page = max(0, min(page, total_pages -
1))
    chunk = rows[page * TOP_PAGE_SIZE: page
* TOP_PAGE_SIZE + TOP_PAGE_SIZE]
    lines = ["💰 <b>TOP ENG KO'P DOLLARI
BOR O'YINCHILAR</b>\n"]
    for i, (user_id, name, dollar) in
enumerate(chunk, page * TOP_PAGE_SIZE + 1):
        lines.append(f"{i}.

```

```

{mention(user_id, name)} - 🏠 ${dollar}")
    lines.append(f"\n📄 {page +
1}/{total_pages}-sahifa")
    return "\n".join(lines), total_pages

def _top_page_markup(kind, page,
total_pages):
    if total_pages <= 1:
        return None
    kb = types.InlineKeyboardMarkup()
    row = []
    if page > 0:

row.append(types.InlineKeyboardButton("◀",
callback_data=f"topPage|{kind}|{page -
1}"))

row.append(types.InlineKeyboardButton(f"
{page + 1}/{total_pages}",
callback_data="topPage|noop|0"))
        if page < total_pages - 1:

row.append(types.InlineKeyboardButton("▶",
callback_data=f"topPage|{kind}|{page +
1}"))
        kb.row(*row)
    return kb

_TOP_BUILDERS = {"wins": build_top_text,
"diamond": build_top_diamond_text,
"dollar": build_top_dollar_text}

```

```

@bot.callback_query_handler(func=lambda c:
c.data.startswith("topPage|"))
def cb_top_page(call):
    """🔍 #9: uzun reyting ro'yxatlarini
sahifalab ko'rsatish tugmalari."""
    try:
        maybe_capture_owner(call.from_user)
        _, kind, page_s =
call.data.split("|")
        if kind == "noop":

bot.answer_callback_query(call.id)
        return
        page = int(page_s)
        builder = _TOP_BUILDERS.get(kind)
        if not builder:

bot.answer_callback_query(call.id, "⚠️
Noma'lum reyting turi.", show_alert=True)
        return
        text, total_pages = builder(page)
        kb = _top_page_markup(kind, page,
total_pages)
        try:
            bot.edit_message_text(text,
call.message.chat.id,
call.message.message_id, reply_markup=kb)
        except Exception:
            pass
        bot.answer_callback_query(call.id)
    except Exception as e:
        _logger.warning("cb_top_page
xatolik: %s", e)

```

```

try:

bot.answer_callback_query(call.id, "⚠️
Xatolik yuz berdi.", show_alert=True)
except Exception:
    pass

#
=====
=====
# 🏆 FAOLLIK BALLARI TIZIMI – har bir
o'yin natijasiga qarab ball
beriladi/ayiriladi:
# • G'alaba qozongan (va oxirigacha
qolgan) o'yinchi: +5 ball
# • Mag'lub bo'lgan (lekin oxirigacha
qolgan) o'yinchi: -5 ball
# • O'yin davomidagi ENG FAOL o'yinchi
(eng ko'p tun/kun harakati qilgan): +25
ball
# • O'yinni tashlab ketgan yoki AFK
bo'lib chetlashtirilgan o'yinchi: -10 ball
# /balltop_kun, /balltop_hafta,
/balltop_oy, /balltop_mutlaq – davr
bo'yicha reyting
#
=====
=====

def add_points(uid, points, reason=""):
    with db_lock:
        cur.execute(
            "INSERT INTO points_log

```

```

(user_id, points, reason, ts) VALUES (?, ?,
?, ?)",
        (uid, points, reason,
time.time()),
        )
        conn.commit()

def get_points_leaderboard(period,
limit=10):
    """period: 'kun', 'hafta', 'oy',
'mutlaq'"""
    now = time.time()
    since = {
        "kun": now - 86400,
        "hafta": now - 7 * 86400,
        "oy": now - 30 * 86400,
        "mutlaq": 0,
    }.get(period, 0)
    with db_lock:
        cur.execute(
            "SELECT user_id, SUM(points)
FROM points_log WHERE ts >= ? GROUP BY
user_id ORDER BY SUM(points) DESC LIMIT ?",
            (since, limit),
        )
        rows = cur.fetchall()
        result = []
        for uid, total in rows:
            if total is None:
                continue
            u = user_dict(uid)
            result.append((uid, u.get("name")
or "0'yinchi", total))

```

```

    return result

PERIOD_LABELS = {"kun": "📅 Kunlik",
                  "hafta": "📅 Haftalik", "oy": "📅 Oylik",
                  "mutlaq": "☹️ Mutlaq (bot boshidan)"}

def build_points_top_text(period):
    rows = get_points_leaderboard(period)
    label = PERIOD_LABELS.get(period,
period)
    if not rows:
        return f"🏆 {label} ball reytingi hozircha bo'sh."
    lines = [f"🏆 <b>{label}</b> FAOLLIK BALLARI REYTINGI</b>\n"]
    for i, (uid, name, total) in enumerate(rows, 1):
        lines.append(f"{i}. {mention(uid, name)} – <b>{total}</b> ball")
    return "\n".join(lines)

@bot.message_handler(commands=
["balltop_kun"])
def cmd_balltop_kun(message):
    maybe_capture_owner(message.from_user)
    bot.send_message(message.chat.id,
build_points_top_text("kun"))

@bot.message_handler(commands=
["balltop_hafta"])

```

```

def cmd_balltop_hafta(message):
    maybe_capture_owner(message.from_user)
    bot.send_message(message.chat.id,
build_points_top_text("hafta"))

@bot.message_handler(commands=
["balltop_oy"])
def cmd_balltop_oy(message):
    maybe_capture_owner(message.from_user)
    bot.send_message(message.chat.id,
build_points_top_text("oy"))

@bot.message_handler(commands=
["balltop_mutlaq"])
def cmd_balltop_mutlaq(message):
    maybe_capture_owner(message.from_user)
    bot.send_message(message.chat.id,
build_points_top_text("mutlaq"))

@bot.callback_query_handler(func=lambda c:
c.data.startswith("ptop|"))
def cb_points_top(call):
    maybe_capture_owner(call.from_user)
    _, period = call.data.split("|")
    bot.send_message(call.message.chat.id,
build_points_top_text(period))
    bot.answer_callback_query(call.id)

def build_top_groups_text(limit=10):
    groups = list_known_groups()

```

```

        if not groups:
            return "🏠 Hozircha ma'lum guruhlar
yo'q."
        lines = ["🏠 <b>TOP GURUHLAR</b>\n"]
        for i, (chat_id, title) in
enumerate(groups[:limit], 1):
            lines.append(f"{i}. {title or
chat_id} (<code>{chat_id}</code>)")
        return "\n".join(lines)

#
=====
=====
# BOT YARATUVCHISINI ANIQLASH
#
=====
=====

_owner_id_raw = get_setting("owner_id")
OWNER_ID = int(_owner_id_raw) if
_owner_id_raw else None

_bm_chat_raw =
get_setting("black_market_chat_id")
BLACK_MARKET_CHAT_ID = int(_bm_chat_raw) if
_bm_chat_raw else None

_owner_channel_raw =
get_setting("owner_channel_id")
OWNER_CHANNEL_ID = int(_owner_channel_raw)
if _owner_channel_raw else None

```



```

def is_owner_channel(chat):
    """Kanal postlari uchun:
    message.from_user doim None bo'ladi
    (Telegram buni
    hech kimga ko'rsatmaydi), shuning uchun
    faqat oldindan tasdiqlangan kanal
    chat_id'siga ishonamiz – chunki faqat
    o'sha kanalning administratorlari
    unga post qila oladi."""
    return chat.type == "channel" and
    OWNER_CHANNEL_ID is not None and chat.id ==
    OWNER_CHANNEL_ID

@bot.message_handler(commands=
["shu_kanal"])
def cmd_set_owner_channel(message):
    """Bot egasi shu buyruqni SHAXSIY
    chatda yozadi (kanalning o'zida emas –
    chunki u
    yerda foydalanuvchi shaxsi Telegram
    tomonidan yashiriladi). Masalan:
    /shu_kanal @Mirkamilovic yoki
    /shu_kanal -1001234567890
    Bot avval o'sha kanalga administrator
    sifatida qo'shilgan bo'lishi shart."""
    global OWNER_CHANNEL_ID
    maybe_capture_owner(message.from_user)
    if not is_owner(message.from_user.id):
        bot.send_message(message.chat.id,
        "🚫 Bu buyruq faqat bot egasi uchun.")
    return
    parts = message.text.split(maxsplit=1)
    if len(parts) != 2:

```

```

        bot.send_message(message.chat.id,
        "Foydalanish: <code>/shu_kanal
@kanal_username</code> yoki
<code>/shu_kanal -100...</code>")
        return
        identifier = parts[1].strip()
        try:
            chat = bot.get_chat(identifier)
        except Exception as e:
            bot.send_message(
                message.chat.id,
                f"❌ Kanalni topib bo'lmadi:
{e}\n"
                "Bot o'sha kanalga
administrator sifatida qo'shilganiga
ishonch hosil qiling.",
                )
            return
        if chat.type != "channel":
            bot.send_message(message.chat.id,
            "❌ Bu kanal emas.")
            return
        OWNER_CHANNEL_ID = chat.id
        set_setting("owner_channel_id",
        OWNER_CHANNEL_ID)
        bot.send_message(message.chat.id, f"✅
Endi <b>{chat.title}</b> kanalidan buyruq
berishingiz mumkin (masalan: /top,
/topalmaz, /topdollar, /topguruh,
/tarqatish).")

def is_owner(user_id):
    # 1) Muhit o'zgaruvchisida aniq

```

```

berilgan ID – eng ishonchli, doim ustuvor.
    if OWNER_ID_FROM_ENV is not None and
user_id == OWNER_ID_FROM_ENV:
        return True
    # 2) Avtomatik aniqlangan/bazada
saqlangan owner_id.
    return OWNER_ID is not None and user_id
== OWNER_ID

def maybe_capture_owner(tg_user):
    """OWNER_ID_FROM_ENV berilgan bo'lsa,
bu funksiya hech narsa qilmaydi –
chunki ishonchli manba muhit
o'zgaruvchisi hisoblanadi. Aks holda,
eski (zaif) username-asosidagi
avtomatik aniqlash ishlashda davom etadi,
lekin bu endi faqat OWNER_ID_FROM_ENV
sozlanmagan hollar uchun zaxira usul."""
    global OWNER_ID
    if OWNER_ID_FROM_ENV is not None:
        return
    if OWNER_ID is not None or tg_user is
None:
        return
    if tg_user.username and
tg_user.username.lower() ==
OWNER_USERNAME.lower():
        OWNER_ID = tg_user.id
        set_setting("owner_id", OWNER_ID)

def is_banned(uid):
    return

```

```

bool(user_dict(uid).get("banned"))

def ban_user(uid):
    update_user(uid, banned=1)

def unban_user(uid):
    update_user(uid, banned=0)

def record_duel_result(winner_id,
    loser_id):
    """qoshimchakod4.py g'oyasi asosida –
    endi haqiqiy SQLite bazasida saqlanadi."""
    w = user_dict(winner_id)
    l = user_dict(loser_id)
    update_user(winner_id,
    duel_wins=w["duel_wins"] + 1)
    update_user(loser_id,
    duel_losses=l["duel_losses"] + 1)

def get_partner_id(uid):
    u = user_dict(uid)
    return u.get("married_to") or 0

def get_partner_name(uid):
    """qoshimchakod3.py / qoshimchakod6.py
    g'oyasi – married_to ustuni asosida haqiqiy
    holat."""
    partner_id = get_partner_id(uid)
    if not partner_id:

```

```

        return None
    return user_dict(partner_id)["name"]

def get_partner_mention(uid):
    """Juftim (turmush o'rtoq) ismini
    bosilganda Telegram profiliga o'tadigan
    link ko'rinishida qaytaradi."""
    partner_id = get_partner_id(uid)
    if not partner_id:
        return None
    return mention(partner_id,
user_dict(partner_id)["name"])

def is_group_admin(chat_id, user_id):
    try:
        member =
bot.get_chat_member(chat_id, user_id)
        return member.status in
("administrator", "creator")
    except Exception:
        return False

def is_authorized(message):
    """O'yin boshqaruv buyruqlari uchun:
    guruh admini, bot yaratuvchisi,
    yoki ⚡ Admin privilegiyasi (1 kun)
    buyumi faol bo'lgan foydalanuvchi."""
    uid = message.from_user.id
    if is_owner(uid):
        return True
    ch = get_charges(uid)

```

```

        until = ch.get("temp_admin_until", 0)
        if until and time.time() < until:
            return True
        if message.chat.type in ("group",
"supergroup"):
            return
    is_group_admin(message.chat.id, uid)
    return False


#
=====
=====
# 28 TA ROL
#
=====
=====

#
=====
=====
# MAXFIY MISSIYALAR VA RANDOM EVENTLAR
# (qoshimchakod1.py va qoshimchakod4.py
g'oyalari asosida, telebot/SQLite uslubiga
moslashtirildi)
#
=====
=====

SECRET_MISSIONS = [
    {"key": "first_speaker", "text":
    "Kunduzgi muhokamada birinchi bo'lib
guruhga yoz."},
    {"key": "vote_skip", "text": "Ovoz

```

```
berishda hech kimga ovoz bermay, 'O'tkazib
yuborish'ni tanla."},
  {"key": "self_vote", "text": "Ovoz
berishda o'zingga ovoz ber."},
  {"key": "say_xayrli_tun", "text": "Tun
boshlanishidan oldin guruhda 'Xayrli tun'
deb yoz."},
  {"key": "talk_atleast_once", "text":
"Kunduzgi muhokamada kamida bitta marta
guruhga yoz."},
  {"key": "first_voter", "text": "Ovoz
berishda birinchi bo'lib ovoz ber."},
  {"key": "last_voter", "text": "Ovoz
berishda oxirgi bo'lib ovoz ber."},
  {"key": "never_say_tinch", "text":
"Bugungi o'yinda hech qachon 'Men tinch
aholiman' deb yozma."},
  {"key": "vote_against_mafia_kill",
"text": "Kunduzgi ovoz berishda, o'tgan
tunda mafiya hujum qilgan kishiga qarshi
ovoz ber."},
  {"key": "active_5msg", "text": "O'yin
davomida kamida 5 marta guruhga xabar yoz
(faollik ko'rsat)."},
  {"key": "say_men_ham", "text":
"Kimningdir fikriga qo'shilib, 'Men ham
shunday o'ylayman' deb yoz."},
  {"key": "silent_until_vote", "text":
"Kunduzgi bosqichda ovoz berish ochilgunga
qadar mutlaqo jim o'tir, guruhga yozma."},
  {"key": "vote_majority", "text":
"Kunduzgi ovoz berishda, oxir-oqibat eng
ko'p ovoz olgan kishiga ovoz ber."},
  {"key": "max3_msg", "text": "Kunduzgi
```

```
muhammadda jami 3 martadan ko'p yozma
(kamroq gapir, ko'proq kuzat)."},
    {"key": "survive_night", "text": "Bu
tunda tirik qolib, ertalabgacha yetib
kel."},
]

RANDOM_EVENTS = [
    {"key": "silence", "text": "⚡ Chaqmoq
chaqdi! Bugun sirli bir kayfiyat hukm
surmoqda... (hikoya, o'yin oxirigacha davom
etadi)"},
    {"key": "lucky_all", "text": "💰 Omadli
daqiq! Barcha tirik o'yinchilarga +50$
bonus taqdim etildi."},
    {"key": "fog", "text": "🌫️ Sirli tuman!
Bugun Komissar kimni tekshirsa ham, natija
aniqlanmay, xira ko'rinadi."},
    {"key": "no_lynch", "text": "🔍 Taqdir
hukmi! Bugungi kunduzgi ovoz berishda hech
kim osilmaydi (natijadan qat'i nazar)."},
    {"key": "weak_night", "text": "🌀
Bo'ron boshlandi! Bugungi tunda himoya
qobiliyatlari (shield/qorovul) 50% ehtimol
bilan ishlamay qoladi."},
    {"key": "lucky_one", "text": "🎁 Sirli
sovg'a qutisi topildi! Tasodifiy bitta
o'yinchiga +100$ tushdi."},
    {"key": "rumor", "text": "🗣️ Shov-shuv!
Guruh bo'ylab kimdir shubhali gap tarqatdi
– hamma bir-biriga qarab qoldi. (Hikoya)"},
    {"key": "short_vote", "text": "🕯️
Sokinlik kuni! Bugungi kunduzgi ovoz berish
bosqichi 15 soniyaga qisqartirildi."},
```


]

```
ROLES_INFO = {  
    "Don 🎩": "Mafia guruhining rahbari.  
    Kechasi sheriklari bilan birga qaysi  
    o'yinchini yo'q qilishni hal qiladi.",  
    "Komissar 🕵️": "Tinch aholining bosh  
    himoyachisi. Kechasi har bir o'yinchini  
    tekshiradi yoki o'ldiradi.",  
    "Doktor 🩺": "Kechasi o'yinchilarni  
    davolaydi. Mafia yoki qotildan jabrlangan  
    odamni qutqara oladi.",  
    "Tinch aholi 👥": "Maxsus qobiliyati  
    yo'q, lekin kunduzi ovoz berish yo'li bilan  
    mafiyalarni aniqlaydi.",  
    "Mafia 🕶️": "Donning yaqin yordamchisi.  
    Tunda Don bilan birgalikda qurbon  
    tanlaydi.",  
    "Qotil 🔪": "Mustaqil qotil. O'z  
    qurbonini tunlari yashirincha  
    pichoqlaydi.",  
    "Manyak 🪓": "Hech kimga  
    bo'ysunmaydigan shafqatsiz qotil. Kechasi  
    istalgan odamga hujum qiladi.",  
    "Serjant 🚔": "Komissarning  
    yordamchisi. Komissar vafot etsa uning  
    vazifasini bajarishni boshlaydi.",  
    "Advokat ⚖️": "Mafia a'zosi yoki  
    boshqalarni sud jarayonida yoki tekshiruvda  
    himoya qiladi.",  
    "Fohisha 🍷": "Kechasi biron  
    o'yinchining oldiga borib, uning tungi  
    qobiliyatidan foydalanishiga to'sqinlik
```

qiladi.",

"Terrorist 💣": "Agar uni kunduzi o'yinchi osib o'ldirmoqchi bo'lishsa, o'zi bilan birga tanlagan odamini ham portlatib ketadi.",

"Mergan 🏹": "Aniq nishonga oladi. O'z navbatida dushmanga o'q uzib, uni yo'q qilishi mumkin.",

"Varvar 🗡️": "Juda baquvvat jangchi. Unga qilingan ayrim hujumlarga qarshilik ko'rsata oladi.",

"Sadoqatli yordamchi 🤝": "Boshqa asosiy o'yinchiga sodiq xizmat qiladi va uning jonini saqlab qolishga yordam beradi.",

"Snayper 🎯": "Uzoq masofadan turib dushmanni aniq poylaydi va o'ldiradi.",

"O'g'ri 🕵️": "Kechasi boshqa o'yinchilarning pulini yoki buyumlarini o'g'irlab ketadi.",

"Sehrgar 🧙": "Sehrli kuchlar yordamida o'yin jarayonini o'zgartirishi mumkin.",

"Sehrgar yordamchisi ✨": "Sehrgarga yordam beradi va sehrli kuchlarni kuchaytiradi.",

"Arvoh 👻": "O'lgandan keyin ham o'yinda qolib, tiriklarga sirli imo-ishoralar beradi.",

"Sudya 🧑": "Kunduzgi ovoz berish jarayonida hal qiluvchi ovozga ega yoki hukmni o'zgartira oladi.",

"Provokator 🗣️": "O'yinchilarni janjallashtirib, ularni bir-biriga qarshi ovoz berishga majbur qiladi.",

```

    "General 🇺🇦": "Harbiy taktikani
qo'llab, o'z jamoasiga qo'shimcha himoya
taqdim etadi.",
    "Josus 🕵️": "Boshqa guruhlarning
yashirin sirlari va rejalarini poylab
eshitib keladi.",
    "Bomj 🧑‍💻": "Kechalari ko'chada yashirin
yurib, tasodifan boshqalarning sirli
harakatlarini ko'rib qoladi.",
    "Arxitektor 🏗️": "O'yin davomida himoya
binolari yoki to'siqlar qurish qobiliyatiga
ega.",
    "Telba 😬": "Oldindan bashorat qilib
bo'lmaydigan harakatlar qiladi, uning
o'yinini topish qiyin.",
    "Qorovul 🔦": "Kechasi o'z obyektni
yoki tanlagan o'yinchini qo'riqlab,
hujumlardan saqlaydi.",
    "Beshikdagi bola 🍼": "O'yin boshida
unga tegishib bo'lmaydi, maxsus himoyaga
ega kenja qahramon.",
}

```

```

ALL_ROLES = list(ROLES_INFO.keys())
CORE_ROLES = ["Don 🎩", "Komissar 🕵️",
"Doktor 🩺"]

MAFIA_ROLES = {"Don 🎩", "Mafia 🖤"}
INDEPENDENT_ROLES = {
    "Qotil 🔪", "Manyak 🪄", "Terrorist
💣", "O'g'ri 🕴️", "Sehrgar 🧙",
    "Sehrgar yordamchisi 🧙‍♂️", "Telba 😬",
    "Bomj 🧑‍💻", "Provokator 🗣️",
}

```

```

#
=====
=====
# QO'SHIMCHA 25 TA ROL – TO'LIQ
ISHLAYDIGAN TUNGI HARAKATLAR
# (Don/Komissar/Doktor – "asosiy rollar" –
allaqachon yuqorida ishlab turibdi;
# Mafia 🖤 ham Don bilan birga umumiy
mafiya ovoziga qo'shiladi.)
# Har bir rol tun davomida harakatni
BOSHLASA, guruhga ASOSIY ROLLAR kabi
# ANONIM (kim ekani aytilmasdan) tarzda
e'lon qilinadi.
#
=====
=====

EXTRA_ROLE_SLUGS = {
    "Qotil 🔪": "qotil",
    "Manyak 🗡": "manyak",
    "Serjant 🚔": "serjant",
    "Advokat ⚖": "advokat",
    "Fohisha 📜": "fohisha",
    "Mergan 🏹": "mergan",
    "Sadoqatli yordamchi 🤝": "sadoqat",
    "Snayper 🎯": "snayper",
    "O'g'ri 🦊": "ogri",
    "Sehrgar 🧙": "sehrgar",
    "Sehrgar yordamchisi 🧙‍♂️": "sehryor",
    "Arvoh 👻": "arvoh",
    "Sudya 🧑": "sudya",
    "Provokator 🗣": "provokator",
    "General 🎖": "general",

```

```

"Josus 🧑": "josus",
"Bomj 🧑": "bomj",
"Arxitektor 🏗️": "arxitektor",
"Telba 😬": "telba",
"Qorovul 🗡️": "qorovul",
}
SLUG_TO_ROLE = {v: k for k, v in
EXTRA_ROLE_SLUGS.items()}

# slug -> (o'yinchiga yuboriladigan savol,
guruhga anonim e'lon qilinadigan atmosfera
matni)
EXTRA_ROLE_PROMPTS = {
    "qotil": ("🗡️ Kimni yashirincha
pichoqlaymiz?", "🗡️ <i>Yolg'iz qotil
qorong'ulikda o'ljasini poylamoqda...
</i>"),
    "manyak": ("🗡️ Kimga tunda hujum
qilamiz?", "🗡️ <i>Manyak shahar bo'ylab
qurbon izlab yurmoqda...</i>"),
    "serjant": ("👮 Komissar o'rniga
kimni tekshiramiz?", "👮 <i>Serjant
Komissar vazifasini o'z zimmasiga oldi...
</i>"),
    "advokat": ("⚖️ Kimni ertangi
kunduzgi osishdan himoya qilamiz?", "⚖️
<i>Advokat tungi hujjatlarni tayyorlab,
birovni himoya qilishga tayyorlanmoqda...
</i>"),
    "fohisha": ("🔪 Kimning oldiga
borib, uni band qilamiz?", "🔪 <i>Sirli
mehmon birovning uyiga yo'l oldi...</i>"),
    "mergan": ("🏹 Kimni nishonga
olamiz?", "🏹 <i>Mergan uzoqdan kimningdir

```

izidan tushdi...</i>"),

"sadoqat": ("👉 Kimni jonim bilan himoya qilaman?", "👉 <i>Sadoqatli yordamchi birovni tungi hujumdan himoya qilishga qasamyod qildi...</i>"),

"snayper": ("🎯 Kimni otib tashlaymiz? (bu qobiliyat butun o'yinda faqat 1 marta ishlaydi)", "🎯 <i>Uzoqdan Snayper nishonini tekshirmoqda...</i>"),

"ogri": ("👤 Kimning cho'ntagini kavlaymiz?", "👤 <i>Kimdir soyada birovning cho'ntagiga qo'l soldi...</i>"),

"sehrgar": ("🧙 Kimga sehrli kuch yo'naltiramiz?", "🧙 <i>Sehrgar sirli belgilar chizib, taqdirlarni aralashtirmoqda...</i>"),

"sehryor": ("🔮 Kimga qo'shimcha himoya berasiz?", "🔮 <i>Sehrgar yordamchisi kimningdir atrofiga sehrli devor tortdi...</i>"),

"arvoh": ("👻 Tirik o'yinchilardan kimga sirli imo-ishora yubormoqchisiz?", "👻 <i>Arvoh olamidan sirli bir imo-ishora yetib keldi...</i>"),

"sudya": ("👨 Ertangi kun ovozingizni 2x kuchga ega qilasizmi?", "👨 <i>Sudya ertangi hukm uchun tayyorgarlik ko'rmoqda...</i>"),

"provokator": ("🧠 Kimni ertaga aholiga qarshi gij-gijlaymiz?", "🧠 <i>Provokator allaqachon mish-mish tarqatishni boshladi...</i>"),

"general": ("🏆 Kimga qo'shimcha himoya beramiz?", "🏆 <i>General o'z

```

jamoasiga qo'shimcha himoya taqdim
etmoqda...</i>"),
    "josus":      ("👤 Kimning qaysi
tarafda ekanini bilib olamiz?", "👤
<i>Josus soyalarda yashirin ma'lumot
yig'moqda...</i>"),
    "bomj":      ("👤 Kimning ortidan
yashirincha kuzatamiz?", "👤 <i>Bomj ko'cha
burchagida kimnidir kuzatib turibdi...
</i>"),
    "arxitektor": ("🏠 Kimga himoya devori
quramiz?", "🏠 <i>Arxitektor tungi to'siq
qurish bilan band...</i>"),
    "telba":      ("😬 Bugun kimga
tasodifiy 'baxt' ulashamiz? (natija
oldindan noma'lum)", "😬 <i>Telba hech kim
kutmagan bir harakat qildi...</i>"),
    "qorovul":    ("🔦 Kimni tunda
qo'riqlaymiz?", "🔦 <i>Qorovul fonarini
yoqib, kimningdir uyi oldida qorovullik
qilmoqda...</i>"),
}

# darhol (shu zahoti) natija beradigan
tekshiruv-turdagi rollar
EXTRA_ROLE_INSTANT_INFO = {"josus", "bomj",
"serjant"}
# faqat "ha/yo'q" tanlovi bo'lgan rol
EXTRA_ROLE_YESNO = {"sudya"}
# o'z-o'zini ham nishonga olishi mumkin
bo'lgan (o'zini himoyalay oladigan) rollar
EXTRA_ROLE_SELF_TARGET_OK = {"arxitektor",
"sehryor"}
# tun yakunida (resolve_night) birgalikda

```

```

ishlanadigan (kechiktirilgan) rollar
EXTRA_ROLE_DEFERRED = {
    "qotil", "manyak", "mergan", "snayper",
    "telba", "fohisha", "sehrGAR",
    "general", "arxitektor", "qorovul",
    "sadoqat",
}

#
=====
=====
# 🌙 TUNGI ATMOSFERA XABARLARI – har bir
rol uchun (qoshimchakod2.py g'oyasi
asosida,
# telebot uslubiga moslashtirildi). Bu
matnlar faqat hikoya/atmosfera uchun –
# o'yinning asosiy mexanikasi
(Don/Mafia/Komissar/Doktor) allaqachon
alohida ishlab turibdi.
#
=====
=====

NIGHT_FLAVOR_TEXTS = {
    "Qotil 🗡️": "🗡️ Shaharning qorong'u
burchagida yolg'iz qotilning soyasi
ko'rindi...",
    "Manyak 🪓": "🪓 Shaharda manyakning
qadam tovushlari eshitildi...",
    "Serjant 🚔": "🚔 Serjant tungi
patrulni boshladi, hushyor turibdi.",
    "Advokat ⚖️": "⚖️ Advokat kimnidir
himoya qilish uchun tungi hujjat
tayyorladi.",

```


"Fohisha 🗡️": "🗡️ Shahar ko'chalarida sirli mehmon kezib yurdi...",

"Terrorist 💣": "💣 Tun qorong'usida shubhali portlovchi modda hidi keldi.",

"Mergan 🏹": "🏹 Mergan o'z pozitsiyasini egallab, nishonga ko'z tikdi.",

"Varvar 🏹": "🏹 Baquvvat jangchining qadam tovushlari uzoqdan eshitildi.",

"Sadoqatli yordamchi 🤝": "🤝 Kimdir sodiqlik bilan o'z homiysini tungi soyada kuzatdi.",

"Snayper 🎯": "🎯 Uzoqdan turib kimdir nishonga ko'z tikkandek tuyuldi...",

"O'g'ri 🦋": "🦋 Kechasi yashirin qadamlar ovozi eshitildi – kimningdir cho'ntagi titkilandi...",

"Sehrgar 🧙": "🧙 Sehrgar sehrli kuchlarni tun qorong'usida ishga soldi.",

"Sehrgar yordamchisi 🧙": "🧙 Sehrgar yordamchisi ustoziga yordam berib, kuchlarni oshirdi.",

"Arvoh 👁️": "👁️ Narigi dunyodan turib kimdir tunni sirli kuzatib turibdi...",

"Sudya ⚖️": "⚖️ Sudya ertangi kun uchun adolat tarozisini tayyorlab qo'ydi.",

"Provokator 🗣️": "🗣️ Kimdir soyada turib janjal rejasini tuzmoqda...",

"General 🏆": "🏆 General o'z taktikasini tungi qorong'ulikda ishlab chiqdi.",

"Josus 🕵️": "🕵️ Josus boshqalarning sirlarini poylab, izlarni yashirincha kuzatdi.",

```

    "Bomj 🧑": "🧑 Ko'chada kezib yurgan
bir soyaning nafasi eshitildi...",
    "Arxitektor 🏠": "🏠 Arxitektor tun
bo'yi yashirin to'siqlar rejasini chizdi.",
    "Telba 🤪": "🤪 Shaharda kimdir
g'alati, tushunarsiz qiliqlar qilib
yuribdi...",
    "Qorovul 🔦": "🔦 Qorovul o'z hududini
tinimsiz qo'riqlashni boshladi.",
    "Beshikdagi bola 🧒": "🧒 Tinch
uyqudagi kenja qahramonni hech kim bezovta
qilmadi.",
}

```

```

def alive_role_flavor_lines(game):
    """Tirik o'yinchilar orasidagi rollarga
qarab tungi atmosfera matnlarini
yig'adi."""
    lines = []
    seen_roles = set()
    for p in alive_players(game).values():
        role = p["role"]
        if role in NIGHT_FLAVOR_TEXTS and
role not in seen_roles:
            seen_roles.add(role)

    lines.append(NIGHT_FLAVOR_TEXTS[role])
    return lines

def team_of(role):
    if role in MAFIA_ROLES:
        return "mafia"

```

```

    if role in INDEPENDENT_ROLES:
        return "independent"
    return "town"

def mafia_count_for(n):
    if n <= 7:
        return 1
    elif n <= 12:
        return 2
    elif n <= 16:
        return 3
    else:
        return max(3, n // 5)

#
=====
=====
# HAZIL / SO'ZLAR RO'YXATLARI
#
=====
=====

DEAD_FUNNY_WORDS = [
    "Xafa bo'lmanglar, narigi dunyoda Wi-Fi
    yaxshi ekan! 😎",
    "Men shunchaki tush ko'ryapman,
    uyg'otmanglar... 😞",
    "Kallam ishlaymay qoldi, shef aybdor!
    🧑",
    "Pazandalar, menda endi ishtaha yo'q!
    🍲",
    "O'lding demang, shunchaki afk bo'ldim

```

```
kiberkatakda! 🎮",  
    "Kechirasizlar, tormozim ishlaymay  
qoldi! 🚗💥",  
    "G'olib bo'lsanglar menga ham ulush  
chiqarasizlarmi? 🏆",  
    "Ruhim guruhda qoladi, xavotir  
olmanglar! 😬",  
    "Men o'lmadim, shunchaki taktik  
chekinish qildim! 🏃",  
    "Keyingi safar tirik qolsam, do'konni  
yulib olaman! 🛒",  
]
```

```
DUEL_REJECT_JOKES = [  
    "⚔️ Raqib qo'rqib qochib ketdi, ishtoni  
ho'l bo'lib qolgan shekilli! 🏃💨",  
    "⚔️ Duel bekor qilindi: Raqib onasidan  
ruxsat so'rolmadi! 🗣️😂",  
    "⚔️ Men kasalman, oyim nonushtaga  
chaqiryaptilar deb jangdan qochdi! 🔍",  
    "⚔️ Qurol tanlashda raqib qoshiqni  
tanladi va qo'rqib yig'lab yubordi! 🥄😭",  
]
```

```
GIFT_JOKES = [  
    "😁 Xasislik qiladigan odam yo'q ekan  
bu guruhda!",  
    "🎁 Mana bu saxiylik-ku, hammaga o'rnak  
bo'ladigan!",  
    "🙏 Pulingiz omadli bo'lsin, faqat  
ortiqcha isrof qilmang!",  
]
```

```
# 😊 Duelda yutqazganlarga DM orqali
```

```
yuboriladigan hazil xabarlar
# (qoshimchakod9.py g'oyasi asosida
qo'shildi)
DEFEAT_JOKES = [
    "Bugun yutqazdingiz, lekin xafa
    bo'lmang, klaviaturada mag'lubiyat tugmasi
    ham kerak-ku! 😊",
    "Mag'lubiyat – bu g'alabaning shogirdi.
    Ertaga ustozingizni xursand qilasiz! 🚀",
    "Yutqazish ham san'at! Faqat bu safargi
    asaringiz biroz qora rangda chiqdi. 🎨",
    "Tinchlaning, hatto professional
    chempionlar ham bir vaqtlar boshlang'ich
    bo'lishgan (faqat tezroq o'lishmasdi). 🐢",
    "Internet tezligingiz yoki omadingiz
    bugun dam olayotgan ekan. Keyingi safar
    uyg'otib qo'yamiz! ⚡",
    "Siz yutqazmadingiz, shunchaki raqibga
    g'alaba sovg'a qildingiz. Saxiylik ham
    fazilat! 🙏",
    "Mag'lubiyat bu – to'xtash emas, bu
    tezroq uxlagani ketish uchun bahona! 🏠",
    "Bot sizga qarab jilmaydi va dedi:
    'Keyingi safar albatta eplaysiz... balki'.
    🤖",
    "G'alaba yaqin edi, lekin u boshqa
    manzilga adashib ketdi shekilli. 🚗",
    "Xafa bo'lmang! Hatto eng yaxshi
    qahramonlar ham birinchi qismda adashib
    o'lib qolishadi. 🎬",
    "Afsuski, bu safar klaviatura siz
    tomonda emas edi. Omadni boshqa kunga
    rejalashtiramiz! 📅 17",
    "Mag'lubiyat achchiq, lekin uning
```

ustidan kulish – shirin! Keyingi safar qasos olamiz. 🗡️",

"O'yin tugadi, lekin sizning xarizmangiz o'zgarmadi. O'zingizni bosib oling! 😎",

"Mag'lubiyat qahramonlarni toblaydi (yoki g'azablantiradi). Siz qaysi birisiz? 🔥",

"Bugun qismat sizni tanlamadi, lekin keyingi jangda barchasi boshqacha bo'lishi aniq! ☀️",

"Yutqazish bu – mag'lubiyat emas, bu 'Tajriba' degan yangi darajani ochish! 📊",

"Xotirjam bo'ling, botlar ham xato qiladi, lekin siz bugun ulardan biroz oldinda edingiz. ☕",

]

🤖 2 tun ketma-ket harakatsiz qolgan (AFK) o'yinchi avtomatik chiqarilganda
guruhga yuboriladigan hazil xabarlar (kim ekani aytilmaydi)
🌙 O'lim xabarida "kim tashrif buyurgani" haqida har bir rolga mos individual
ibora – kim ekani (nikneymi) hech qachon oshkor qilinmaydi, faqat ROL turi.

VISIT_PHRASE = {

"Don 🎩": "Aytishlaricha, unikiga tunda Don shaxsan tashrif buyurgan...",

"Mafia 🖤": "Aytishlaricha, unikiga tunda mafiya soylari kelgan...",

"Komissar 🕵️": "Aytishlaricha, unikiga tunda Komissar tashrif buyurgan...",

"Doktor 🩺": "Aytishlaricha, unikiga

tunda Doktor kelgan edi...",
"Qotil 🗡️": "Aytishlaricha, unikiga
tunda yolg'iz qotil pichoq bilan
kelgan...",
"Manyak 🪓": "Aytishlaricha, unikiga
tunda manyak vahshiylarcha bostirib
kirgan...",
"Mergan 🏹": "Aytishlaricha, uni
uzoqdan Mergan nishonga olgan...",
"Snayper 🎯": "Aytishlaricha, uni
Snayper uzoq masofadan otib tushirgan...",
"Telba 😬": "Aytishlaricha, unikiga
tasodifiy Telba kirib qolgan...",
"Serjant 🚔": "Aytishlaricha, unikiga
Serjant tashrif buyurgan...",
"Advokat ⚖️": "Aytishlaricha, unikiga
Advokat kelgan edi...",
"Fohisha 🍷": "Aytishlaricha, unikiga
sirli mehmon kelgan...",
"Sadoqatli yordamchi 🤝":
"Aytishlaricha, unikiga Sadoqatli yordamchi
kelgan...",
"O'g'ri 🦊": "Aytishlaricha, unikiga
tunda kimdir kirib chiqqan...",
"Sehrgar 🧙": "Aytishlaricha, unikiga
Sehrgar sehrli tashrif buyurgan...",
"Sehrgar yordamchisi 🧙🌟":
"Aytishlaricha, unikiga Sehrgar yordamchisi
kelgan...",
"Arvoh 👻": "Aytishlaricha, unikiga
g'ayritabiiy bir soya kelgan...",
"Sudya 🧑": "Aytishlaricha, Sudya undan
xabar olgan...",
"Provokator 🗣️": "Aytishlaricha,

```
unikiga Provokator kelib, mish-mish
tarqatgan...",
    "General 🇺🇦": "Aytishlaricha, unikiga
General tashrif buyurgan...",
    "Josus 🕵️": "Aytishlaricha, unikiga
Josus yashirincha kelgan...",
    "Bomj 🧑‍🚒": "Aytishlaricha, uning
oldidan Bomj o'tib ketgan...",
    "Arxitektor 📐": "Aytishlaricha,
unikiga Arxitektor tashrif buyurgan...",
    "Qorovul 🔦": "Aytishlaricha, uni
Qorovul tunda kuzatib turgan...",
}
```

```
AFK_KICK_JOKES = [
    "😓 {who} shu qadar chuqur uxlab
qolibdiki, o'yin uni o'zi bilan olib keta
olmadi... (Roli: {role})",
    "🛖 {who} ikki tundan beri sukut
saqlagani uchun shaharni tark etdi. (Roli:
{role})",
    "🛑 {who}ning aloqasi 2 tundan beri
yo'q – ehtimol pitsa buyurtma qilgandir. U
endi o'yinda emas. (Roli: {role})",
    "🚪 Sukunat ikki tunga cho'zilsa, eshik
ham ochiladi... {who} jimgina chiqib ketdi.
(Roli: {role})",
    "💤 {who} shunchalik og'ir uxlab
qoldiki, hatto Telegram ham uni unutdi. U
o'yindan chetlatildi. (Roli: {role})",
    "🧊 {who} 2 tun muzlab qoldi va endi
butunlay eri6 yo'qoldi. (Roli: {role})",
    "🌫️ {who} tumanga aylanib, shahardan
g'oyib bo'ldi – 2 tun hech kim uni
```



```
ko'rmadi. (Roli: {role})",
    "📞 {who} telefonini uyda unutgan
shekilli – 2 tundan beri sado-savo yo'q.
Chetlatildi. (Roli: {role})",
    "🕳️ {who} qandaydir sirli teshikka
tushib ketdi va 2 tun qaytmadi. Endi
o'yinda emas. (Roli: {role})",
    "🐢 {who} shu qadar sekin harakat
qildiki, hatto soat milliga ham ulgurmadi.
2 tun sukunat – chetlatildi. (Roli:
{role})",
    "🧑🏻 {who} sahnadan 2 tunga g'oyib
bo'lgan aktyorday – endi rolini boshqa hech
kim o'ynamaydi. (Roli: {role})",
]
```

```
MARRIAGE_ACCEPT_JOKES = [
    "💍 Tabriklaymiz! Endi bir yostiqqa
bosh qo'yib, kechasi qaysi serialni
ko'rishni talashasizlar! 📺😄",
    "💍 Baxtiyor oila qurildi! Birinchi
janjal qachon bo'lishiga stavka qabul
qilamiz! 🎰🎲",
]
```

```
MARRIAGE_REJECT_JOKES = [
    "💍 'Mening oyim senga o'xshagan
kelin/kuyovni yoqtirmaydi' deb rad etdi! 🙄
❌",
    "💍 Kechirasan, men hali kareraga
e'tibor qaratmoqchiman (pitsa yeyishga)! 🍕
🏃",
]
```

```

#
=====
=====
# DO'KON MAHSULOTLARI – HAR BIRI HAQIQIY
"mode" GA EGA
#
=====
=====
# mode turlari:
#   shield          -> DB "shield" ustuniga
+1 (o'limdan bir marta asraydi)
#   instant_dollar  -> darhol dollar
beradi (luck_mult bilan ko'payadi)
#   charge          -> "charges" json
ichida sanoq (bir martalik ishlatiladi)
#   multiplier      -> charges ichida
ko'paytiruvchi (eng kattasi saqlanadi)
#   expiry          -> charges ichida
tugash vaqti (soniya, Unix timestamp)
#   permanent_flag  -> charges ichida
doimiy belgi (1 = faol)

SHOP_DOLLAR = {
    "himoya": { "name": "🛡️ Himoya
jileti", "price": 200, "currency":
"dollar", "mode": "shield",
                "desc": "O'yin paytida
o'lishdan 1 marta himoya qiladi." },
    "kunhimoya": { "name": "🛡️🌞 Kunduzgi
himoya", "price": 200, "currency":
"dollar", "mode": "charge", "charge_key":
"day_shield",
                    "desc": "Aholi tomonidan

```

```
kunduzi osilishdan 1 marta himoya qiladi.  
Bitta o'yinda faqat 1 marta ishlaydi."},  
  "hujjat": {"name": "📄 Soxta Hujjat",  
"price": 350, "currency": "dollar", "mode":  
"charge", "charge_key": "fake_doc",  
  "desc": "Komissar sizni  
tekshirsa, 'Tinch aholi' bo'lib  
ko'rinasiz."},  
  "aptechka": {"name": "🩹 Kichik  
Aptechka", "price": 150, "currency":  
"dollar", "mode": "charge", "charge_key":  
"antidote",  
    "charge_amount": 1,  
    "desc": "Sizni /zahar  
(zaharlash) ta'siridan 1 marta avtomatik  
davolaydi – zaharlansangiz, tunda o'zi  
ishga tushadi."},  
  "kozoyinak": {"name": "👁️ Tungi  
ko'zoynak", "price": 500, "currency":  
"dollar", "mode": "charge", "charge_key":  
"night_vision",  
    "desc": "Tundan keyin  
qaysi rollar faol bo'lganini shaxsiy  
xabarda ko'rasiz."},  
  "xat": {"name": "✉️ Tushunarsiz  
xat", "price": 100, "currency": "dollar",  
"mode": "charge", "charge_key": "confuse",  
    "desc": "Mafiya sizni  
nishonga olsa, hujum tasodifiy boshqa  
odamga burilib ketadi."},  
  "sumka": {"name": "👜 Shubhali  
sumka", "price": 450, "currency": "dollar",  
"mode": "charge", "charge_key":  
"hidden_vote",
```

```
        "charge_amount": 3,
        "desc": "Kunduzi kimga
ovoz berganingiz 👁 Kuzatish ko'zi orqali
ham 'noma'lum' bo'lib ko'rinadi (3
marta)."},
        "niqob": {"name": "🛡️ Temir niqob",
"price": 600, "currency": "dollar", "mode":
"shield",
        "desc": "O'yin paytida
o'lishdan 1 marta himoya qiladi
(qo'shimcha)."},
        "zahar": {"name": "🧪 Zaharli
flakon", "price": 800, "currency":
"dollar", "mode": "charge", "charge_key":
"poison",
        "desc": "/zahar buyrug'i
orqali (reply) birovni zaharlash imkonini
beradi."},
        "gps": {"name": "📍 GPS Mayak",
"price": 900, "currency": "dollar", "mode":
"charge", "charge_key": "gps",
        "desc": "/gps buyrug'i
orqali (reply) birovning tirik/o'lganligini
bilib olasiz."},
        "kompas": {"name": "🧭 Sirli kompas",
"price": 950, "currency": "dollar", "mode":
"charge", "charge_key": "compass",
        "desc": "/kompas buyrug'i
orqali (reply) birovning qaysi tarafda
(mafiya/tinch aholi/mustaqil) ekanini bilib
olasiz – rolini emas, faqat tarafini."},
        "vip": {"name": "🇺🇸 Oltin
Litsenziya", "price": 1000, "currency":
"dollar", "mode": "multiplier",
```

```
        "charge_key":
"bonus_mult", "mult_value": 2, "desc":
"Kunlik bonusingizni 2 barobar qiladi."},
    # --- YANGI MAHSULOTLAR
(qoshimchakod8.py g'oyasi asosida
qo'shildi) ---
        "energy": {"name": "⚡ Energiya
ichimligi", "price": 120, "currency":
"dollar", "mode": "charge", "charge_key":
"revote",
                    "charge_amount": 2,
                    "desc": "Kunduzi ovoz
bergandan keyin fikringizni o'zgartirib,
qayta ovoz berish imkonini beradi (2
marta)."},
        "tutun": {"name": "💣 Tutunli
bomba", "price": 280, "currency": "dollar",
"mode": "charge", "charge_key":
"smoke_bomb",
                    "desc": "Xavfli vaziyatda
izingizni yo'qotib, dushmandan yashiringan
bo'lasiz."},
        "zar": {"name": "🎲 Sehrli
Zarlar", "price": 320, "currency":
"dollar", "mode": "gamble_ability",
                    "desc": "Ochilganda
tasodifiy: 🛡 Himoya YOKI 🌊 Tungi
ko'zoynak qobiliyatlaridan biri chiqadi
(pul emas)."},
        "fonar": {"name": "🔦 Katta Fonar",
"price": 220, "currency": "dollar", "mode":
"charge", "charge_key": "flash_light",
                    "desc": "Kechasi
qorong'ilikdagi yashirin harakatlarni
```

```

yoritib beradi."},
}

SHOP_DIAMOND = {
    "qilich": {"name": "🔪 Olmos
Qilich", "price": 5, "currency": "diamond",
"mode": "charge", "charge_key": "duel_adv",
"charge_amount": 5,
"desc": "Keyingi 5 ta
duelda g'alaba imkoniyatini 65% ga
oshiradi."},
    "tumor": {"name": "💊 Sehrli
tumor", "price": 10, "currency": "diamond",
"mode": "multiplier",
"charge_key":
"bonus_mult", "mult_value": 2, "desc":
"Kunlik bonusingizni 2 barobar qiladi."},
    "quti": {"name": "📦 Nodir quti",
"price": 15, "currency": "diamond", "mode":
"gamble_ability",
"desc": "Ichidan
tasodifiy: 📍 GPS, 🧭 Kompas yoki 🛡 Himoya
qobiliyatlaridan biri chiqadi (pul
emas)."},
    "oq": {"name": "🟡 Oltin o'q",
"price": 20, "currency": "diamond", "mode":
"charge", "charge_key": "golden_bullet",
"charge_amount": 5,
"desc": "Mafiyaning
o'ldirish urinishi himoya/davolashni
chetlab o'tadi (5 marta)."},
    "qalqon": {"name": "🛡 Imunitet
qalqoni", "price": 25, "currency":
"diamond", "mode": "shield",

```

```
        "desc": "O'yin paytida  
o'lishdan 1 marta himoya qiladi."},  
        "radar": {"name": "📡 Maxfiy  
radar", "price": 30, "currency": "diamond",  
"mode": "charge", "charge_key": "radar",  
"charge_amount": 6,  
"desc": "/qayta_tanlash  
orqali o'z rolingizni tasodifiy boshqasiga  
almashtirasiz (6 marta)."},  
        "jonlanish": {"name": "⚡ Tezkor  
jonlanish", "price": 40, "currency":  
"diamond", "mode": "charge", "charge_key":  
"revive",  
"charge_amount": 6,  
"desc": "O'lish arafasida  
qo'shimcha jon beradi (6 marta, shielddan  
keyin ishlaydi)."},  
        "imperator": {"name": "👑 1 kunlik  
imperator", "price": 50, "currency":  
"diamond", "mode": "expiry",  
"charge_key":  
"imperator_until", "duration_seconds":  
86400, "desc": "24 soat 'Imperator' maqomi  
(profilda ko'rinadi)."},  
        "ramka": {"name": "🖼️ Mifik ramka",  
"price": 75, "currency": "diamond", "mode":  
"expiry", "charge_key": "ramka_until",  
"duration_seconds": 30 *  
86400,  
"desc": "Profilingizga 30  
kunga eksklyuziv ramka belgisi qo'shadi."},  
        "tulki": {"name": "🦊 Omad tumori",  
"price": 100, "currency": "diamond",  
"mode": "multiplier",
```

```

        "charge_key":
"luck_mult", "mult_value": 3, "desc":
"Barcha pul yutuqlaringizni (bonus, duel,
o'yin mukofoti) 3x qiladi."},
    "vip_olmos": {"name": "🔮 Kuzatuv
minorasi", "price": 60, "currency":
"diamond", "mode": "charge", "charge_key":
"night_vision",
        "charge_amount": 3,
        "desc": "3 marta – 🕶️
Tungi ko'zoynak bilan bir xil: tunda qaysi
rollar faol bo'lganini (kim ekanini emas)
DM orqali bildiradi."},
    # --- YANGI MAHSULOTLAR
(qoshimchakod8.py g'oyasi asosida
qo'shildi) ---
    "kristal": {"name": "💎 Sehrli
Kristal", "price": 8, "currency":
"diamond", "mode": "charge", "charge_key":
"compass",
        "charge_amount": 1,
        "desc": "Kristall
kelajakni ko'rsatadi – 1 marta 🧭 Kompas
qobiliyati beradi (birovning tarafini bilib
olasiz)."},
    "kolt": {"name": "👤 Yashirin
plash", "price": 18, "currency": "diamond",
"mode": "charge", "charge_key": "cloak",
        "charge_amount": 5,
        "desc": "O'yin davomida
dushmanlar nishoniga tushishdan himoya
qiladi (5 marta)."},
    "eliksir": {"name": "🧪 Hayot
Eliksiri", "price": 35, "currency":

```



```

"diamond", "mode": "charge", "charge_key":
"revive",
        "charge_amount": 1,
        "desc": "O'lim arafasida
hayotingizni saqlab qoladi – 1 marta
qo'shimcha jon (⚡ Tezkor jonlanish bilan
bir xil)."},
        "sandi": {"name": "🏆 Afsonaviy
Sandi", "price": 110, "currency":
"diamond", "mode": "hero_chest",
        "desc": "Ichidan 5 xil
noyob GEROYDAN biri chiqadi! Har biri
o'ziga xos kuchli qobiliyatga ega "
        "(1-15 lvl gacha
rivojlantiriladi). /geroyim orqali
ko'ring."},
}

```

#

=====

=====

```

# 🏆 GEROYLAR TIZIMI – "Afsonaviy Sandi"
ichidan chiqadigan 5 xil geroy.
# 4 tasi bir-biriga teng kuchli, 1 tasi
(🌀 Zephyrion) biroz kuchliroq,
# lekin tushish ehtimoli atigi 0.05% (chit
bo'lib qolmasligi uchun cheklangan).
# Har bir geroy 1-lvldan boshlanadi, 15-
lvlgacha rivojlanadi; lvl oshgani sari
# effekt kuchi asta-sekin, muvozanatli
tarzda oshib boradi.

```

#

=====

=====

```

HEROES = {
  "sardor": {
    "name": "🗡️ Draven the Warlord",
    "image": "hero_draven.jpg",
    "abilities": [
      {"key": "survive", "unlock": 1,
    "name": "🛡️ Tungi chidamlilik",
      "desc": "Tunda hujumdan
tasodifiy foizda avtomatik omon qolasiz.",
      "base": 0.05, "cap": 0.18},
      {"key": "revive_once",
    "unlock": 6, "name": "👊 O'lmas ruh",
      "desc": "O'yin davomida BIR
MARTA, hech qanday himoya ishlamay qolsa
ham, kafolatlangan tirik qolasiz."},
      {"key": "vote_shield_once",
    "unlock": 11, "name": "🗳️ Xalq himoyasi",
      "desc": "O'yin davomida BIR
MARTA, kunduzgi ovoz berishda eng ko'p ovoz
olsangiz ham osilmaysiz."},
    ],
  },
  "malika": {
    "name": "🔮 Seraphine the Oracle",
    "image": "hero_seraphine.jpg",
    "abilities": [
      {"key": "compass_free",
    "unlock": 1, "name": "🧭 Cheksiz kompas",
      "desc": "Har kuni bepul,
cheklovsiz /kompas ishlatish imkoniyati
(do'kondan sotib olmasdan)."},
      {"key": "night_vision_auto",
    "unlock": 6, "name": "👁️ Tungi nazar",

```

```
        "desc": "Har tun avtomatik  
ravishda nechta o'yinchi faol harakat  
qilganini (kimligini emas) DM orqali bilib  
olasiz."},  
        {"key": "role_reveal_once",  
"unlock": 11, "name": "🔍 Chuqur bashorat",  
        "desc": "O'yin davomida BIR  
MARTA, istalgan o'yinchining ANIQ rolini  
(/geroy_bashorat orqali) bilib olasiz."},  
        ],  
    },  
    "temur": {  
        "name": "🛡️ Magnus the Conqueror",  
"image": "hero_magnus.jpg",  
        "abilities": [  
            {"key": "duel_bonus", "unlock":  
1, "name": "⚔️ Jangchi mahorati",  
            "desc": "Duellarda g'alaba  
qozonish ehtimoli oshadi.", "base": 0.05,  
"cap": 0.18},  
            {"key": "duel_draw_chance",  
"unlock": 6, "name": "🎲 Qat'iy zarba",  
            "desc": "Duelda mag'lub  
bo'lish o'rniga, tasodifiy foizda durrang  
(hech kim yutqazmaydi) bo'lish  
imkoniyati.",  
            "base": 0.08, "cap": 0.20},  
            {"key": "vote_weight",  
"unlock": 11, "name": "👑 General nufuzi",  
            "desc": "Kunduzgi ovoz  
berishda ovozingiz qo'shimcha og'irlikka  
ega bo'ladi."},  
        ],  
    },  
}
```

```
"layli": {
  "name": "🌙 Elandriel the
Enchantress", "image":
"hero_elandriel.jpg",
  "abilities": [
    {"key": "bonus_dollar",
"unlock": 1, "name": "💰 Sehrli bonus",
  "desc": "Kunlik bonus miqdori
oshadi.", "base": 20, "cap": 150},
    {"key": "luck_boost", "unlock":
6, "name": "🍀 Omad tumori",
  "desc": "Do'kondagi tasodifiy
pul beruvchi buyumlardan (zar, sumka, quti)
ko'proq yutish ehtimoli oshadi.",
  "base": 0.08, "cap": 0.25},
    {"key": "diamond_trickle",
"unlock": 11, "name": "💎 Boylik siri",
  "desc": "Har o'yin
boshlanganda avtomatik +1 💎 Olmos
olasiz."},
  ],
},
"burgut": {
  "name": "🦅 Zephyrion, the
Ascendant One", "image":
"hero_zephyrion.jpg",
  "abilities": [
    {"key": "survive", "unlock": 1,
"name": "🛡️ Osmoniy chidamlilik",
  "desc": "Tunda hujumdan
tasodifiy foizda avtomatik omon qolasiz.",
  "base": 0.08, "cap": 0.22},
    {"key": "compass_free",
"unlock": 4, "name": "🧭 Cheksiz kompas",
```

```

        "desc": "Har kuni bepul,
cheklovsiz /kompas ishlatish imkoniyati."},
        {"key": "duel_bonus", "unlock":
7, "name": "🗡️ Ascendant zarbasi",
        "desc": "Duellarda g'alaba
qozonish ehtimoli oshadi.", "base": 0.08,
"cap": 0.22},
        {"key": "bonus_dollar",
"unlock": 10, "name": "💰 Oltin qanotlar",
        "desc": "Kunlik bonus miqdori
oshadi.", "base": 15, "cap": 110},
        {"key": "revive_once",
"unlock": 13, "name": "🔥 O'limni yengish",
        "desc": "ENG NODIR QOBILİYAT –
o'yin davomida BIR MARTA, hech qanday
himoya ishlamay qolsa ham, kafolatlangan
tirik qolasiz."},
    ],
    },
}

```

```

def hero_image_path(hero_key):
    """Geroyning o'ziga xos rasmi – skript
bilan bir papkada joylashgan bo'lishi kerak
(masalan hero_draven.jpg). Fayl
topilmasa None qaytaradi (chaqiruvchi
shunda
    rasmsiz, faqat matn bilan davom
etadi)."""
    rel = HEROES.get(hero_key,
{}).get("image")
    if not rel:
        return None

```

```

        path = os.path.join(ASSETS_DIR, rel)
        return path if os.path.exists(path)
    else None

HERO_LEVEL_UP_COSTS = [int(40 + (220 - 40)
* i / 13) for i in range(14)] # 1→2 ...
14→15 (14 ta narx)
HERO_MAX_LEVEL = 15

def roll_hero():
    if random.random() < 0.0005: # 0.05%
        return "burgut"
    others = [k for k in HEROES if k !=
"burgut"]
    return random.choice(others)

def get_hero(uid):
    with db_lock:
        cur.execute("SELECT hero_key,
level, acquired_at, temp_until FROM heroes
WHERE user_id=?", (uid,))
        row = cur.fetchone()
        if not row:
            return None
        key, level, acquired_at, temp_until =
row
        # ⌚ Vaqtincha berilgan geroyning
muddati tugagan bo'lsa – avtomatik olib
        # qo'yiladi (keyingi safar
tekshirilganda ko'rinmaydi, xuddi hech
        # bo'lmagandek). Muddat tugagani haqida

```

```

foydalanuvchiga DM yuboriladi.
    if temp_until and temp_until > 0 and
time.time() > temp_until:
        with db_lock:
            cur.execute("DELETE FROM heroes
WHERE user_id=?", (uid,))
            conn.commit()
            hero_name = HEROES.get(key,
{ }).get("name", key)
            safe_send(uid, f"⌚ <b>{hero_name}
</b> geroyingizning vaqtinchalik muddati
tugadi – endi sizda emas.")
            return None
        data = HEROES.get(key, { })
        days_active = int((time.time() -
(acquired_at or time.time())) // 86400)
        return {"key": key, "level": level,
"acquired_at": acquired_at, "days_active":
days_active,
            "temp_until": temp_until,
"name": data.get("name"), "image":
data.get("image"),
            "abilities":
data.get("abilities", [ ])}

def hero_level_up_cost(current_level):
    if current_level < 1 or current_level
>= HERO_MAX_LEVEL:
        return None
    return
HERO_LEVEL_UP_COSTS[current_level - 1]

```

```

def _ability_power(level, unlock, base,
cap):
    """`unlock` darajada `base`dan
boshlanib, 15-lvl'da `cap`gacha chiziqli
o'sadigan,
    chegaralangan (chit bo'lib qolmaydigan)
kuch qiymati. `unlock`dan past level uchun
0."""
    if level < unlock:
        return 0.0
    if unlock >= HERO_MAX_LEVEL:
        return base
    t = (level - unlock) / (HERO_MAX_LEVEL
- unlock)
    return base + (cap - base) * t

def hero_unlocked_abilities(uid):
    """Foydalanuvchining geroyi va uning
HOZIRGI darajasida ochilgan qobiliyatlari
ro'yxatini (hisoblangan qiymati bilan)
qaytaradi. Har biri:
{key,name,desc,value,unlocked}."""
    hero = get_hero(uid)
    if not hero:
        return []
    result = []
    for ab in hero["abilities"]:
        unlocked = hero["level"] >=
ab["unlock"]
        value = None
        if unlocked and "base" in ab:
            value =
_ability_power(hero["level"], ab["unlock"],

```



```

ab["base"], ab["cap"])
    result.append(**ab, "unlocked":
unlocked, "value": value})
    return result

def hero_ability_value(uid, ability_key):
    """Berilgan turdagi (masalan 'survive',
'duel_bonus') qobiliyat qiymatini qaytaradi
(0 – agar geroy yo'q, ochilmagan yoki
bu turdagi qobiliyat yo'q bo'lsa)."""
    for ab in hero_unlocked_abilities(uid):
        if ab["key"] == ability_key and
ab["unlocked"]:
            return ab["value"] or 0.0
    return 0.0

def hero_has_ability(uid, ability_key):
    """Binary (bor/yo'q) qobiliyatlarni uchun
– masalan 'compass_free', 'revive_once'."""
    for ab in hero_unlocked_abilities(uid):
        if ab["key"] == ability_key and
ab["unlocked"]:
            return True
    return False

def hero_survive_chance(uid):
    return hero_ability_value(uid,
"survive")

def hero_duel_bonus(uid):

```

```

        return hero_ability_value(uid,
"duel_bonus")

def hero_bonus_extra_dollar(uid):
    return int(hero_ability_value(uid,
"bonus_dollar"))

def hero_has_free_compass(uid):
    return hero_has_ability(uid,
"compass_free")

def hero_luck_boost(uid):
    return hero_ability_value(uid,
"luck_boost")

def hero_duel_draw_chance(uid):
    return hero_ability_value(uid,
"duel_draw_chance")

def hero_vote_weight_bonus(uid):
    return 1 if hero_has_ability(uid,
"vote_weight") else 0

SHOP_COIN = {
    "toj": {"name": "👑 Hukmdor
toj", "price": 15, "currency": "coin",
"mode": "expiry", "charge_key":
"toj_until",

```

```

        "duration_seconds": 15
* 86400,
        "desc": "15 kunga
hukmdor maqomi belgisi (profilda
ko'rinadi)."},
        "rol_tanlash": {"name": "👤 Rol tanlash
huquqi", "price": 20, "currency": "coin",
"mode": "charge", "charge_key":
"role_choice",
        "charge_amount": 5,
        "desc": "/rolni_tanla
<rol> orqali keyingi 5 ta o'yinda
xohlagan rolni tanlaysiz."},
        "klan": {"name": "🏰 Klan
litsenziyasi", "price": 25, "currency":
"coin", "mode": "charge", "charge_key":
"klan_license",
        "charge_amount": 1,
        "desc": "/klan
<nomi> orqali o'z klaningizni ochish
huquqini beradi (bir martalik – 1 klan
ochishga yetadi)."},
        "shadow": {"name": "👤 Yashirin
status", "price": 30, "currency": "coin",
"mode": "expiry", "charge_key":
"shadow_until",
        "duration_seconds": 20
* 86400,
        "desc": "20 kun
davomida /top reytingida ismingiz
ko'rinmaydi."},
        "nishon": {"name": "🔪 Qotil
nishoni", "price": 60, "currency": "coin",
"mode": "charge", "charge_key":

```

```
"duel_guaranteed_win",
    "charge_amount": 5,
    "desc": "Keyingi 5 ta
duelingizda 100% g'alaba kafolatlaydi."},
    "koz": {"name": "👁️ Kuzatish
ko'zi", "price": 55, "currency": "coin",
"mode": "charge", "charge_key":
"watch_eyes",
    "charge_amount": 5,
    "desc": "Kunduzi kim
kinga ovoz berganini to'liq DM orqali
ko'rasiz (5 marta)."},
    "duel_qalqon": {"name": "🛡️ Duel
qalqoni", "price": 150, "currency": "coin",
"mode": "charge", "charge_key":
"duel_guaranteed_win",
    "charge_amount": 10,
    "desc": "Keyingi 10 ta
duelingizda 100% g'alaba kafolatlaydi."},
    "bank": {"name": "🏦 Bank foizi
x2", "price": 90, "currency": "coin",
"mode": "multiplier",
    "charge_key":
"bonus_mult", "mult_value": 2, "desc":
"Kunlik bonusingizni 2 barobar qiladi."},
    "admin": {"name": "⚡ 1 kunlik
admin", "price": 120, "currency": "coin",
"mode": "expiry",
    "charge_key":
"temp_admin_until", "duration_seconds":
86400, "desc": "24 soat davomida /NewGame,
/StartGame va h.k. buyruqlarni bera
olasiz."},
    "qirol": {"name": "👑 Qirol
```

```

unvoni", "price": 200, "currency": "coin",
"mode": "expiry", "charge_key":
"qirol_until",
        "duration_seconds": 10
* 86400,
        "desc": "10 kun
davomida eng oliy maqom – /top reytingida
eng tepada chiqasiz."},
    "vip_coin": {"name": "🎯 Snayper
puxta nishonchi", "price": 180, "currency":
"coin", "mode": "charge", "charge_key":
"golden_bullet",
        "charge_amount": 2,
        "desc": "2 marta –
mafiya hujumi himoyalarni
(shield/doktor/qorovul) chetlab o'tadi."},
}

SHOP_OSH = {
    "toy": {"name": "🧸 To'y Oshi",
"price": 5000, "currency": "dollar",
"gift_shield": 2, "gift_charge": ("revive",
1)},
    "choyxona": {"name": "☕ Choyxona
Oshi", "price": 4500, "currency": "dollar",
"gift_shield": 2, "gift_charge":
("night_vision", 1)},
    "tandir": {"name": "🔥 Tandir Oshi",
"price": 4000, "currency": "dollar",
"gift_shield": 1, "gift_charge": ("gps",
1)},
    "samarqand": {"name": "🇺🇿 Samarqand
Oshi", "price": 3800, "currency": "dollar",
"gift_shield": 1, "gift_charge":

```

```

("compass", 1)},
    "buxoro": {"name": "🏠 Buxorocha
Sofi Oshi", "price": 3600, "currency":
"dollar", "gift_shield": 1, "gift_charge":
("confuse", 1)},
    "fargona": {"name": "🏠 Farg'ona
Devzira Oshi", "price": 3500, "currency":
"dollar", "gift_shield": 1, "gift_charge":
("fake_doc", 1)},
    "qora": {"name": "👤 Qora Mafia
Oshi", "price": 3000, "currency": "dollar",
"gift_shield": 1, "gift_charge": None},
}

SHOP_CATEGORIES = {
    "dollar": ("💵 Dollar Do'koni",
SHOP_DOLLAR),
    "diamond": ("💎 Olmos Do'koni",
SHOP_DIAMOND),
    "coin": ("🪙 Hunter Coin Do'koni",
SHOP_COIN),
}

# 📦 Inventar tugmalarida ishlatish uchun:
buyum nomidan uning do'kon kalitiga
# ("himoya", "kozoyinak" va h.k.) qaytadan
yo'l topish uchun lug'at.
ITEM_NAME_TO_SHOPKEY = {}
for _cat, (_title, _items) in
SHOP_CATEGORIES.items():
    for _key, _item in _items.items():
        ITEM_NAME_TO_SHOPKEY[_item["name"]]
= (_cat, _key)

```

```

#
=====
=====
# HAR GURUH UCHUN ALOHIDA O'YIN HOLATI
#
=====
=====

GAMES = {}
GAME_LOCK = threading.RLock()
PENDING_PROPOSALS = {}

# 📋 Guruhga kirish uchun a'zolik
so'rovlari (zayavkalar) navbati.
# Faqat guruh havolasi "Admin tasdig'i"
(request to join) rejimida bo'lsa ishlaydi.
# {chat_id: [ {"user_id":, "name":,
"username":, "ts":}, ... ]}
PENDING_JOIN_REQUESTS = {}
JOIN_REQ_LOCK = threading.RLock()

#
=====
=====
# 🏆 MUSOBAQALAR (TURNIRLAR) – Hunter
Mafia o'yinidan MUSTAQIL, alohida rejim.
# Guruh egasi/admin o'yinchilarni yig'ib,
ular orasidan ikkitasini tanlab
# 1v1 "Turnir Jangi" (duel'dan farqli –
bracket asosida, elimination) o'tkazadi,
# oxirida bitta chempion qoladi va katta
mukofot oladi.
#

```

```

=====
=====

TOURNAMENTS = {}      # chat_id ->
{"name","status","participants":
{uid:name},"eliminated":[],"matches":
[],"host_id"}
TOURNAMENT_PICK = {}  # host_id ->
{"chat_id":..., "a": uid_or_None} (jang
uchun 2 kishini ketma-ket tanlash holati)

#
=====
=====
# 🔄 BOT TIKLASH (RESTORE/RESTART) TIZIMI
#
=====
=====
# Bot har qanday sababdan (xatolik,
deploy, host qayta ishga tushirishi yoki
# /tiklash buyrug'i) to'xtab qolsa ham,
aktiv o'yinlar GAMES xotiradan yo'qolib
# ketmasin deb, muhim bosqich (checkpoint)
larda holat diskka (STATE_PATH) JSON
# ko'rinishida yoziladi. Bot qayta ishga
tushganda, shu fayldan o'qib, o'yinlarni
# qayta tiklaydi va qolgan vaqtni hisoblab
tegishli taymerlarni qayta ishga
# tushiradi – guruh a'zolari uchun o'yin
deyarli uzilishsiz davom etadi.

STATE_LOCK = threading.RLock()

```



```

# game{} ichidagi qaysi maydonlar `set()`
ekanini bilib, JSON'ga list, qaytishda
# yana set() qilib tiklaymiz (JSON o'z-
o'zidan set turini bilmaydi).
_STATE_SET_FIELDS = {"last_words_wait",
"poison_marks", "night_protected",
"snayper_used",
                        "prompted_tonight",
"responded_tonight", "touched_tonight",
                        "hero_revive_used",
"hero_vote_shield_used",
"hero_role_reveal_used",
                        "hero_armed_defense",
"hero_armed_vote_shield",
"hero_income_claimed",
                        "revealed_couples"}
# qaysi maydonlar {int_uid: ...}
ko'rinishidagi lug'at ekanini bilib, JSON
kalitlarini
# (JSON'da har doim string bo'ladi)
qaytadan int'ga o'giramiz.
_STATE_INT_KEYED_FIELDS = {"players",
"mafia_votes", "votes", "forced_day_votes",
"secret_missions",
                        "forced_roles",
"afk_streak", "squads", "couple_of"}

def _game_to_jsonable(game):
    """Bitta o'yin holatini
    (GAMES[chat_id]) JSON'ga yozsa bo'ladigan
    lug'atga aylantiradi."""
    data = {}
    for key, value in game.items():

```

```

        if key == "timers":
            continue # threading.Timer
obyektlari saqlanmaydi – tiklashda yangisi
yaratiladi
        if key in _STATE_SET_FIELDS:
            data[key] = list(value)
        elif key == "confirm_vote":
            if value:
                data[key] = {
                    "target":
value["target"],
                    "yes":
list(value["yes"]),
                    "no":
list(value["no"]),
                    "message_id":
value.get("message_id"),
                }
            else:
                data[key] = None
        elif key in _STATE_INT_KEYED_FIELDS
and isinstance(value, dict):
            data[key] = {str(k): v for k, v
in value.items()}
        else:
            data[key] = value
    return data

def _game_from_jsonable(data):
    """_game_to_jsonable() natijasini yana
ishlaydigan GAMES[chat_id] lug'atiga
qaytaradi."""
    game = dict(data)

```

```

game["timers"] = []
for key in _STATE_SET_FIELDS:
    if key in game and game[key] is not
None:
        game[key] = set(game[key])
    if game.get("confirm_vote"):
        cv = game["confirm_vote"]
        game["confirm_vote"] = {
            "target": cv["target"],
            "yes": set(cv["yes"]),
            "no": set(cv["no"]),
            "message_id":
cv.get("message_id"),
        }
    for key in _STATE_INT_KEYED_FIELDS:
        if key in game and
isinstance(game[key], dict):
            game[key] = {int(k): v for k, v
in game[key].items()}
    return game

def save_games_state():
    """Barcha aktiv o'yinlarning holatini
STATE_PATH fayliga yozadi. Muhim bosqich
o'zgarishlarida (tun/kun boshlanishi,
ovoz berish ochilishi, o'yin tugashi va
h.k.)
    chaqiriladi. Xatolik yuz bersa ham
o'yin davom etaveradi – bu faqat
'sug'urta'.
    🔧 TUZATILDI: 🐱🦅 Jamoaviy va 🕒 Para
o'yin rejimlari endi oddiy GAMES
yozuvining bir qismi

```

```

(squad_mode/couple_mode maydonlari),
shuning uchun
    ular ham pastdagi "games" snapshoti
orqali avtomatik saqlanadi – alohida
saqlash shart emas.""
    try:
        with GAME_LOCK, STATE_LOCK:
            snapshot = {
                "saved_at": time.time(),
                "games": {str(chat_id):
_game_to_jsonable(g) for chat_id, g in
GAMES.items()}},
            }
            tmp_path = STATE_PATH + ".tmp"
            with open(tmp_path, "w",
encoding="utf-8") as f:
                json.dump(snapshot, f,
ensure_ascii=False)
            os.replace(tmp_path,
STATE_PATH)
        except Exception:
            logging.exception("⚠️ O'yinlar
holatini saqlashda xatolik yuz berdi.")

def _resume_game_timer(chat_id, game):
    """Saqlangan 'phase_deadline'ga
asoslanib navbatdagi bosqich uchun yangi
threading.Timer o'rnatadi (qolgan
vaqtni hisoblab). Agar vaqt allaqachon
tugagan bo'lsa ham, bot to'liq ishga
tushib ulgurishi uchun kamida bir necha
soniya kutib, keyin yakunlaydi."""
    phase = game.get("phase")

```

```

        deadline = game.get("phase_deadline")
        sub_phase = game.get("day_sub_phase")

        resolver = None
        if game.get("confirm_vote"):
            resolver = lambda:
resolve_hang_confirmation(chat_id)
        elif phase == "night":
            resolver = lambda:
resolve_night(chat_id)
        elif phase == "day":
            if sub_phase == "voting":
                resolver = lambda:
resolve_day(chat_id)
            elif sub_phase == "discussion":
                resolver = lambda:
open_day_voting(chat_id)

        if resolver is None or deadline is
None:
            return

        remaining = deadline - time.time()
        delay = max(remaining, 5) # bot to'liq
ishga tushib ulgursin deb kamida 5 soniya
        t = threading.Timer(delay, resolver)
        t.daemon = True
        t.start()
        game["timers"].append(t)

def load_games_state():
    """Bot ishga tushganda (yoki /tiklash
orqali qayta ishga tushgandan keyin)

```

chaqiriladi. Agar oldingi ishga tushishda saqlangan aktiv o'yinlar bo'lsa, ularni GAMES ichiga tiklaydi, faz-taymerlarini qayta o'rnatadi va guruhlariga 'bot tiklandi' xabarini yuboradi.

🔧 TUZATILDI: 🐱🦉 Jamoaviy va 🗄️ Para o'yin rejimlari endi oddiy GAMES yozuvining bir qismi bo'lgani uchun ular ham pastdagi asosiy tsikl orqali avtomatik tiklanadi – alohida tiklash shart emas."""

```
if not os.path.exists(STATE_PATH):
    return

try:
    with open(STATE_PATH, "r",
encoding="utf-8") as f:
        snapshot = json.load(f)
except Exception:
    logging.exception("⚠️ Saqlangan
o'yin holatini o'qib bo'lmadi, tiklash
o'tkazib yuborildi.")
    return

games_data = snapshot.get("games") or
{}
restored = 0
for chat_id_s, gdata in
games_data.items():
    try:
        chat_id = int(chat_id_s)
        game =
_game_from_jsonable(gdata)
        GAMES[chat_id] = game
```

```

        restored += 1
        if game.get("phase") in
("night", "day"):
            _resume_game_timer(chat_id,
game)

            try:
                bot.send_message(
                    chat_id,
                    "🔄 <b>Bot
muvaffaqiyatli qayta ishga tushdi!</b>\n"
                    "Sizning o'yiningiz
avtomatik tiklandi – davom etaveramiz. 🎮",
                    )
            except Exception:
                pass
        except Exception:
            logging.exception(f"⚠️
{chat_id_s} guruhi uchun o'yinni tiklashda
xatolik yuz berdi.")

    if not games_data:
        return

    logging.info(f"🔄 Bot tiklandi:
{restored} ta o'yin holati qayta
yuklandi.")

    # tiklab bo'lgach eski faylni
tozalaymiz – keyingi checkpointlarda
qaytadan yoziladi
    try:
        os.remove(STATE_PATH)
    except Exception:
        pass

```

```
def _graceful_shutdown_save(*_args):
    """Host (Railway/systemd/Docker va
    h.k.) botni SIGTERM/SIGINT bilan
    to'xtatganda
    ham oxirgi lahzadagi o'yin holati
    yo'qolib ketmasligi uchun signal
    handler."""
    save_games_state()
    sys.exit(0)

try:
    signal.signal(signal.SIGTERM,
    _graceful_shutdown_save)
    signal.signal(signal.SIGINT,
    _graceful_shutdown_save)
except (ValueError, AttributeError):
    # ba'zi platformalarda (masalan asosiy
    bo'lmagan thread) signal o'rnatib bo'lmaydi
    – muammo emas
    pass

def new_game(chat_id, chat_title):
    return {
        "chat_id": chat_id,
        "chat_title": chat_title,
        "phase": "waiting",
        "players": {},
        "join_msg_id": None,
        "group_link": None,
        "day_number": 0,
```



```

    "mafia_votes": {},
    "doctor_target": None,
    "komissar_action": None,
    "komissar_target": None,
    "votes": {},
    "voting_open": False,
    "secret_missions": {},
    "last_words_wait": set(),
    "forced_roles": {},
    "poison_marks": set(),
    "timers": [],
    # --- qo'shimcha 25 rol uchun holat
---
    "extra_actions": {},
    "night_protected": set(),
    "advocate_protect": None,
    "forced_day_votes": {},
    "judge_double_vote": None,
    "snayper_used": set(),
    # --- kunduzgi tasdiqlash ovoz
berishi (👍/👎) ---
    "confirm_vote": None,
    # --- 🏆 geroylarning bir martalik
qobiliyatlari uchun (o'yin davomida 1
marta) ---
    "hero_revive_used": set(),
    "hero_vote_shield_used": set(),
    "hero_role_reveal_used": set(),
    # --- 🔄 bot tiklash
(restart/restore) tizimi uchun checkpoint
maydonlari ---
    "phase_deadline": None, # joriy
bosqich qachon tugashi kerak (Unix vaqt)
    "day_sub_phase": None, #

```

```

"discussion" yoki "voting" – faqat phase ==
"day" uchun
    # --- 😞 AFK (harakatsizlik)
nazorati ---
    "prompted_tonight": set(),
    "responded_tonight": set(),
    "afk_streak": {},
    # --- 🧑 tunda kimga qanday harakat
qilinganini kuzatish (natija DM'lari uchun)
    ---
        "touched_tonight": set(),
        # --- 🐱🦅 Jamoaviy o'yin rejimi
(/teamgame) va 🍷 Para o'yin rejimi
(/parateam) ---
            "squad_mode": False,
            "couple_mode": False,
            "squads": {}, # uid -> "wolf" |
"eagle"
            "couple_of": {}, # uid -> uid
(sherigi) – faqat couple_mode uchun, o'yin
oxirigacha MAXFIY
            "revealed_couples": set(), #
allaqachon (biri halok bo'lgani sababli)
guruhga fosh qilingan juftliklar
        }

def alive_players(game):
    return {uid: p for uid, p in
game["players"].items() if p["alive"]}

def player_line_list(game):
    if not game["players"]:

```

```

        return "Hozircha hech kim yo'q."
        return "\n".join(f"• {mention(uid,
p['name'])}" for uid, p in
game["players"].items())

#
=====
=====
# 🐾🦅 JAMOAVIY (SQUAD) REJIMI – jamoa
a'zolari soni, jamodoshlar ro'yxati va
# tugmalardagi jamoa belgisi uchun
yordamchi funksiyalar. (YANGI QO'SHILDI –
# mavjud hech bir funksiya o'chirilmadi
yoki o'zgartirilmadi.)
#
=====
=====

def squad_counts_line(game):
    """🐾🦅 Ro'yxatga olish xabarida
ko'rsatish uchun – har bir jamoaga necha
kishi
    yozilganini alohida-alohida sanab
qaytaradi (masalan: '🦅 Burgutlar – 2 ta,
    🐾 Bo'rilar – 3 ta'). Kim aniq qaysi
jamoada ekani baribir MAXFIY qolaveradi –
    faqat SONLAR ko'rsatiladi, ismlar
emas."""
    if not game.get("squad_mode"):
        return None
    squads = game.get("squads", {})
    wolf_n = sum(1 for uid in
game["players"] if squads.get(uid) ==

```

```

"wolf")
    eagle_n = sum(1 for uid in
game["players"] if squads.get(uid) ==
"eagle")
    return f"🦅 Burgutlar – {eagle_n} ta,
🐺 Bo'rilar – {wolf_n} ta"

def ally_roster(game, viewer_uid):
    """🐺🦅💍🕶 O'yinchining "jamodoshlari"
ro'yxatini aniqlaydi – o'yin rejimiga
qarab avtomatik tanlanadi:
    • 🐺🦅 Jamoaviy rejim → o'zi bilan
bir xil jamoadagilar (Bo'ri/Burgut)
    • 💍 Para rejim → turmush
o'rtog'i (agar u ham shu o'yinda va tirik
bo'lsa)
    • Oddiy (asosiy) o'yin → 🕶 Mafiya
jamoasi a'zolari (Don + Mafiya), FAQAT
o'zi ham mafiya bo'lsa (tinch
aholi/komissar/doktor va h.k.ga hech kim
"jamodosh" sifatida ko'rsatilmaydi,
chunki ularning maxfiy sherigi yo'q)
    Qaytaradi: (label, emblem, [(uid,
name), ...]) – hech narsa topilmasa
(None, None, [])."""
    p = game["players"].get(viewer_uid)
    if not p:
        return None, None, []
    if game.get("squad_mode"):
        squads = game.get("squads", {})
        my_squad = squads.get(viewer_uid)
        if not my_squad:
            return None, None, []

```

```

        emblem = "🐾" if my_squad == "wolf"
    else "🦅"
        label = "Bo'ri" if my_squad ==
"wolf" else "Burgut"
        mates = [(uid, pp["name"]) for uid,
pp in game["players"].items()
                    if uid != viewer_uid and
squads.get(uid) == my_squad and
pp.get("alive")]
        return label, emblem, mates
    if game.get("couple_mode"):
        spouse_uid = game.get("couple_of",
{}).get(viewer_uid)
        sp =
game["players"].get(spouse_uid) if
spouse_uid else None
        if not sp or not sp.get("alive"):
            return None, None, []
        return "Turmush o'rtog'i", "💍",
[(spouse_uid, sp["name"])]
        if team_of(p.get("role")) == "mafia":
            mates = [(uid, pp["name"]) for uid,
pp in game["players"].items()
                        if uid != viewer_uid and
pp.get("alive") and team_of(pp.get("role"))
== "mafia"]
            if mates:
                return "Mafiya", "🕶️", mates
            return None, None, []

def squad_tag(game, viewer_uid,
target_uid):
    """🐾🦅💍🕶️ Agar 'target_uid'

```

```

'viewer_uid'ning jamodoshi (bir jamoadagi
    sherigi, turmush o'rtog'i yoki mafiya
safdoshi) bo'lsa, tugma matni
    oldiga qo'shiladigan belgini (emoji)
qaytaradi – shunda o'yinchi
    tugmalar orasida o'z jamodoshini darhol
tanib oladi. Aks holda bo'sh
    satr qaytadi – bu holatda tugma
AVVALGIDEK, hech qanday o'zgarishsiz
    ko'rinadi."""
    if target_uid == viewer_uid:
        return ""
    _, emblem, mates = ally_roster(game,
viewer_uid)
    if not emblem:
        return ""
    if any(uid == target_uid for uid, _name
in mates):
        return f"{emblem} "
    return ""

def format_squad_roster_text(game,
viewer_uid):
    """🐱🦅🔗🕶 O'yinchining o'z
jamodoshlari ro'yxatini tayyorlaydi –
RAQAMLANGAN
    (1, 2, 3...) va HAR BIRI ALOHIDA
QATORDA (yonma-yon emas, pastga qarab),
    shunda o'yinchi jamodoshlarini o'qishda
chalkashib ketmaydi. 🔗 Para
    rejimida turmush o'rtog'ining ismi
<b>qalin</b> qilib ajratib ko'rsatiladi.
    Jamodosh topilmasa – None qaytadi (hech

```

```

narsa yuborilmaydi)."""
    label, emblem, mates =
ally_roster(game, viewer_uid)
    if not emblem or not mates:
        return None
    if game.get("couple_mode"):
        _mate_uid, mate_name = mates[0]
        return f"{emblem} <b>Sizning
turmush o'rtog'ingiz:</b> <b>{mate_name}
</b>"
        header_label = f"\{label}\" jamoangiz"
    if game.get("squad_mode") else "mafiya
sheriklaringiz"
        lines = [f"{emblem} <b>Sizning
{header_label} a'zolari:</b>"]
        for i, (_mate_uid, mate_name) in
enumerate(mates, start=1):
            lines.append(f"{i}. {emblem}
{mate_name}")
        return "\n".join(lines)

def send_squad_reminders(game):
    """🐱🦅🔗🕶 Har bir tirik o'yinchiga
(jamoaviy, para yoki oddiy o'yinda – mafiya
a'zolariga) o'z jamodoshlari ro'yxatini
shaxsiy chatga eslatma qilib
yuboradi. Kun ovoz berishi
boshlanishidan oldin va tun harakati
boshlanishidan oldin chaqiriladi
(mavjud oqimga faqat QO'SHIMCHA
sifatida, boshqa hech narsani
o'zgartirmasdan). Jamodoshi yo'q
o'yinchilarga (masalan oddiy o'yindagi

```

```

tinch aholi) hech narsa
yuborilmaydi."""
    for viewer_uid in alive_players(game):
        text =
format_squad_roster_text(game, viewer_uid)
        if text:
            safe_send(viewer_uid, text)

def get_group_link(chat_id):
    game = GAMES.get(chat_id)
    if game and game.get("group_link"):
        return game["group_link"]
    try:
        link =
bot.export_chat_invite_link(chat_id)
        if game:
            game["group_link"] = link
        return link
    except Exception:
        return None

def safe_delete(message):
    try:
        bot.delete_message(message.chat.id,
message.message_id)
    except Exception:
        pass

def safe_send(uid, text,
reply_markup=None):
    try:

```



```

        bot.send_message(uid, text,
reply_markup=reply_markup)
        return True
    except Exception:
        return False

def notify_target_touched(game,
target_uid):
    """🌙 Har qanday rol tunda kimnidir
nishonga olsa, o'sha kishiga (kim ekani
oshkor qilinmasdan) umumiy
ogohlantiruvchi xabar yuboriladi – bir
kechada
        bir kishiga faqat bitta marta (bir
nechta rol bir xil odamni tanlasa ham)."""
    if target_uid in (None, "skip", "yes",
"no") or target_uid not in game["players"]:
        return
    touched =
game.setdefault("touched_tonight", set())
    if target_uid in touched:
        return
    touched.add(target_uid)
    safe_send(target_uid, "🌙 <i>Kimdir
tunda sizga qiziqib, harakatingizni
yashirincha kuzatdi...</i>")

def send_scene_photo(chat_id, local_path,
url_fallback, caption, reply_markup=None):
    """Mahalliy 'assets' papkasidagi surat
bo'lsa o'shani, bo'lmasa zaxira URL'ni
yuboradi."""

```

```

try:
    if os.path.isfile(local_path):
        with open(local_path, "rb") as
f:
            bot.send_photo(chat_id, f,
caption=caption, reply_markup=reply_markup)
            return
    except Exception:
        pass
    try:
        bot.send_photo(chat_id,
url_fallback, caption=caption,
reply_markup=reply_markup)
    except Exception:
        bot.send_message(chat_id, caption,
reply_markup=reply_markup)

def mention(uid, name):
    """Guruh xabarlarida o'yinchi ismini
bosilganda uning profiliga o'tadigan qilib
ko'rsatish uchun.
    🏆 Agar o'yinchi HUNTER ELITE bo'lsa,
ismi ikki tomonidan haqiqiy PREMIUM
    SHER emojisi bilan bezaladi
    (CLAN_PORTRAIT_EMOJI["logo"]) – ELITE
belgisi.
    🖼️ Agar o'yinchida faol Mifik ramka
bo'lsa, uning ismi HAMMA ko'radigan joyda
    (o'yin e'lonlari, reytinglar, o'lim
xabarlari va h.k.) maxsus ramka bilan
ko'rinadi.
    ! MUHIM: <tg-emoji> tegi <a
href="tg://user?id=..."> havolasi ICHIGA

```

```

JOYLASHTIRILMAYDI – Telegram bunday
"ichma-ich" (nested) formatni to'g'ri
ko'rsata olmay, faqat zaxira (fallback)
belgini chiqarib qo'yadi. Shuning
uchun premium belgi havola TASHQARISIGA
(oldiga/orqasiga) qo'shiladi –
shunda u guruhda ham, shaxsiy chatda
ham haqiqiy premium ko'rinishda chiqadi.""
safe_name = (name or
"O'yinchi").replace("<", "").replace(">",
"")
prefix = ""
suffix = ""
try:
    ch = get_charges(uid)
    # 🦁 HUNTER ELITE a'zosi bo'lsa va
shaxsiy laqab (taxallus) o'rnatgan bo'lsa –
    # hamma joyda (o'yin e'lonlari,
reytinglar, o'lim xabarlar) o'sha laqab
bilan ko'rinishda.
    elite_until = ch.get("vip_until",
0)
    if elite_until and elite_until >
time.time():
        nick = (ch.get("nickname") or
"").strip()
        if nick:
            safe_name = nick.replace("
<", "").replace(">", "")
            lion_id =
CLAN_PORTRAIT_EMOJI.get("logo")
            lion_tag = f'<tg-emoji emoji-
id="{lion_id}">🦁</tg-emoji>' if lion_id
else "🦁"

```

```

        prefix += lion_tag + " "
        suffix = " " + lion_tag +
suffix
        ramka_until = ch.get("ramka_until",
0)
        if ramka_until and ramka_until >
time.time():
            prefix +=
premium_emoji("frame", "🖼️") + " ✨ "
            suffix = " ✨ " +
premium_emoji("frame", "🖼️") + suffix
        except Exception:
            pass
        return f'{prefix}<a href="tg://user?id=
{uid}">{safe_name}</a>{suffix}'

#
=====
=====
# 🌟 MAXSUS (PREMIUM) EMOJILAR – HTML <tg-
emoji emoji-id="..."> yordamida yuborish
#
=====
=====
# ⚠️ SHART: bu funksiyalar ishlashi uchun
BOTNI YARATGAN shaxsning (ya'ni sizning
# shaxsiy Telegram akkountingiz – botni
@BotFather orqali ro'yxatdan o'tkazgan
# akkount) da FAOL Telegram Premium
obunasi bo'lishi kerak. Bu shart 2026-yil
# 9-fevraldan beri Bot API'ning rasmiy
qoidasi (Fragment orqali qimmat username
# sotib olish ENDI shart emas – Premium

```

```
kifoya). Agar Premium bo'lmasa, Telegram
# entity'ni e'tiborsiz qoldiradi va faqat
oddiy "fallback" emoji ko'rinadi (xato
# chiqmaydi, shunchaki maxsus emoji
ko'rinmaydi).
#
# 📌 O'ZINGIZNING EMOJI ID'LARINGIZNI
TOPISH:
# 1) Botni ishga tushiring.
# 2) Botning shaxsiy chatida (DM),
o'zingiz yaratgan to'plamdagi
(HunterMafiaPack)
# istalgan maxsus emoji'ni yuboring
(oddiy xabar sifatida, klaviaturadan
tanlab).
# 3) Bot avtomatik o'sha emoji'ning
"custom_emoji_id" raqamini sizga javob
qilib
# yuboradi (pastdagi
`collect_custom_emoji_ids` funksiyasi
orqali).
# 4) Shu ID'larni PREMIUM_EMOJI lug'atiga
joylashtiring va istalgan xabarda
# `premium_emoji(key)` yoki
`render_premium_text(...)` orqali
ishlating.
#
=====
=====

# 📁 ID'larni shu yerga joylashtiring –
masalan: "fire": "5379748062124056162"
# (Har bir qiymat –
collect_custom_emoji_ids orqali botga
```

```
yuborilgandan keyin olingan ID)
# 🗳️ 121-tasi ham "Hanter" to'plamidan
(t.me/addemoji/HanterMafiaBot), /hanter_ids
# buyrug'i orqali botning o'zidan olingan
HAQIQIY va tekshirilgan ID'lar.
PREMIUM_EMOJI = {
    "pillar":
        "5253656287694070722",          # 🏛️ Clan
        Symbol
    "toolbox":
        "5253547530532201410",          # 🧰 Tools
    "ring":
        "5253587611167008718",          # 💍
        Unique Gold Ring
    "shield":
        "5253731101729400237",          # 🛡️ Lion
        Crest / Battle Shield
    "scroll":
        "5253887094941589781",          # 📜
        Ancient Scroll / Broken Seal
    "bandage":
        "5253997381111817316",          # 🩹 Healing
        Bandage
    "flame":
        "5253570680405928167",          # 🔥
        Radiant Golden Flame
    "target":
        "5251516225749558785",          # 🎯 Golden
        Bullseye
    "flag_victory":
        "5251734152390159229",          # 🚩 Ornate
        Golden Flag - Victory
    "gems_cluster":
        "5251496189727124050",          # 💎 Gemstone
```

Cluster

"bullet":
"5253846468845937581", # 💎
Glowing Golden Bullet
"radar":
"5253972865438492175", # 📡
Brass-and-Gold Radar Dish
"crystal_heart":
"5253952975444947021", # 💔 Cracked
Crystal Heart
"mask":
"5253580120744042388", # 🎭
Golden Theatrical Mask
"clan_banner":
"5251742570526060246", # 🚩 Unrolled
Golden Clan Banner
"shadow_figure":
"5251316295021932853", # 👤 Smoky Shadow
Figure
"dagger":
"5254004858649880562", # 🗡️
Legendary Dagger
"shield_2":
"5251295150897932106", # 🛡️ Energy
Shield Orb
"eye":
"5253662747324882982", # 👁️
Golden All-Seeing Eye
"fox":
"5251620945642169057", # 🦊
Lucky Fox-Tail Charm (HUNTER ELITE)
"fox_2":
"5251620945642169057", # 🦊 xuddi
shu rasm, ism oxirida

```
"vest":
"5253611761768111359",      # 🦺
Ornate Bulletproof Vest
"mask_2":
"5251305385804998038",      # 🎭
Polished Iron Masquerade Mask
"document":
"5253618023830432327",      # 📜 Aged
Forged Document
"goggles":
"5251279323943451259",      # 🕶
Steampunk-Luxury Goggles
"love_letter":
"5253623117661646222",      # 📧 Wax-Sealed
Mysterious Letter
"potion":
"5253655145232769885",      # 🧪
Crystal Poison Vial
"gps_beacon":
"5253823894497826517",      # 📍 Gold-
Plated GPS Beacon
"amulet":
"5253592932631487494",      # 🪄
Magical Amulet
"bank_rune":
"5253689492086234676",      # 🏦 Bank
Interest Rune
"sword":
"5251574663074587729",      # ⚔
Diamond-Encrusted Longsword
"money":
"5251467834353034219",      # 💰 Stack
Bills
"diamond":
```


"5253742414673255222", # 💎 Massive Diamond
"coin":
"5253574498631851107", # 🪙 Hunter Coin
"treasure_chest":
"5251575586492561187", # 📦 Treasure Chest
"spinning_coin":
"5253800937897635331", # 🪙 Spinning Coin
"jackpot":
"5251414052772554556", # 🎰 JACKPOT!
"vault":
"5253718478820517394", # 🏦 Vault Building
"vip_card":
"5251308731584522091", # 🪪 VIP Card
"gift":
"5253706195214050358", # 📦 Gift Box
"stars":
"5251515856382371891", # ★ Telegram Stars
"immunity_charm":
"5251674405100106367", # 🛡️ Immunity Charm
"briefcase":
"5253568275224240880", # 👛 Luxury Briefcase
"box":
"5253844067959217666", # 📦 Ornate Loot Box
"dice":
"5253887975409886895", # 🎲 Glowing Dice

"crystal_ball":
"5253618028125396002", # 🌌 Crystal Ball
"archive":
"5253750429082232796", # 📦 Archive
Chest
"signal":
"5251426662796534647", # 📶 Signal
Tower
"vase":
"5253955303317227024", # 🏺
Porcelain Vase
"vase_2":
"5251350006220237212", # 🏺
Ceremonial Urn
"mother_daughter":
"5251648746965477706", # 👩👧 Mother & Child
Emblem
"shop":
"5253530260468706909", # 🏪
Ornate Gold Shop Icon
"chart":
"5251525597368198419", # 📈
Rising Bar Chart
"gear":
"5251609396475112519", # ⚙️
Settings Gear
"magnifier":
"5253956248210022896", # 🔍 Archives
Magnifier
"bell":
"5251671888249267242", # 🔔
Notifications Bell
"key_item":
"5253534177478877517", # 🔑 Antique

Gold Key

"padlock":

"5253517976862237810",



Engraved Gold Padlock

"map":

"5251462792061429779",

 Map

"gun":

"5253469057184737578",



Engraved Gold Pistol

"gun_2":

"5253681078245304000",

 Pearl

& Gold Revolver

"helmet":

"5253630311731863374",

 Gold

Battle Helmet

"compass":

"5251624768163066301",

 Compass

"inventory_chest":

"5251355615447526296", #  Inventory Chest

"question":

"5254003046173682568",

 Help

"warning":

"5251375114599050954",

 Warning

Triangle

"moon":

"5253688538603496820",



Night City

"sun":

"5251569968675332763",



Sunrise

"salute":

"5251604517392262503",



Saluting Hand

"book":

"5251562774605112341", Ancient Spellbook	# 📖
"angry": "5253569756987960765", Mask Emblem	# 😡 Angry
"rocket": "5253811460567506961", Rocket Ship	# 🚀 Gold
"person": "5253904854631360486", Silhouette Figure Emblem	# 👤
"ballot": "5253749166361845208", Box	# 🗳️ Ballot
"duel": "5253845270550063164", Swords	# ⚔️ Duel
"explosion": "5253687546466052125", Burst	# 💣 Explosion
"broken_lock": "5253984844102279619", "gravestone": "5251294738581070469", "ring_2": "5254001079078659932", Marriage Heart/Ring	# 🗝️ Broken Lock
"hourglass": "5253668944962690414", "lightning": "5253896878877091357", Bolt	# ⌚ Hourglass
"crown": "5251609456604652565",	# ⚡ Lightning
	# 👑 Royal

Gold Crown
"frame":
"5253452517265680802", # 🖼️
Baroque Picture Frame
"dragon":
"5251539156579953188", # 🐉 Dragon
Head Crest
"admin_shield":
"5253662038655280079", # 🛡️ Admin Shield
Emblem
"elite_badge":
"5253899331303418373", # 🦋 Winged
Diamond Badge
"wedding_ring_set":
"5253527924006493718", # 💍 Wedding Ring Set
"nameplate":
"5251468689051527102", # 🏷️ Engraved
Nameplate
"silk_flag":
"5251432379398008839", # 🚩 Folded
Silk Flag
"trophy":
"5251284426364597200", # 🏆 Golden
Trophy Cup
"medal":
"5253583831595787507", # 🏅
Bronze Medal

— Quyidagilar uchun Hanter
to'plamida ALOHIDA mos surat yo'q (bular
endi

pastdagi ROLE_PORTRAIT_EMOJI
orqali TO'LIQ PORTRET ko'rinishida
ko'rsatiladi) – eski ID'lar

zarasiz saqlanib qoldi, hech narsaga
ta'sir qilmaydi —
"plus":
"5231359149660478554", # +
(to'plamda yo'q)
"rose":
"5231093682026879373", # 🌹
(to'plamda yo'q)
"wizard":
"5228948625035403012", # 🧙
(to'plamda yo'q)
"top_hat":
"5231412377190177912", # 🎩 (Don
portreti ishlatiladi)
"axe":
"5230968002693866223", # 🪓
(Varvar portreti ishlatiladi)
"police":
"5228998876152771465", # 🚔
(Serjant portreti ishlatiladi)
"scale":
"5231254489897409072", # ⚖️
(Advokat portreti ishlatiladi)
"bow":
"5228683836006640638", # 🏹
(Mergan portreti ishlatiladi)
"ninja":
"5228777788416238250", # 🥷
(O'g'ri portreti ishlatiladi)
"ghost":
"5231343726432918883", # 👻
(Arvoh portreti ishlatiladi)
"scale_2":
"5228804760810861333", # ⚖️ (Sudya

```

portreti ishlatiladi)
    "medal_2":
    "5231334208785389927",          # 🏆
    (General portreti ishlatiladi)
    "detective":
    "5228742543914609211",          # 🕵️ (Komissar
    portreti ishlatiladi)
    "wizard_man":
    "5229099369797559818",          # 🧙 (Sehrgar
    portreti ishlatiladi)
    "ruler":
    "5228749763754637223",          # 📐
    (Arxitektor portreti ishlatiladi)
    "crazy":
    "5231447076230963307",          # 🤪
    (Telba portreti ishlatiladi)
    "crazy_2":
    "5231153455086738225",          # 🤪
    (to'plamda yo'q)
}

```

```

# 🧐 Har bir ROL uchun – Hanter
to'plamidagi HAQIQIY PORTRET rasmi.
# Kalit – ROLES_INFO dagi rol nomi bilan
HARFMA-HARF bir xil bo'lishi shart.
ROLE_PORTRAIT_EMOJI = {
    "Don 🎩": "5253642737072252144",
    "Komissar 🕵️": "5251487659922075699",
    "Doktor 🩺": "5253749741887463241",
    "Mafia 🖤": "5251578786243194412",
    "Qotil 🔪": "5253737917842506148",
    "Manyak 🪒": "5253704009075699748",
    "Serjant 🚔": "5253922421047602898",
    "Advokat ⚖️": "5253953456481284153",
}

```

```

    "Fohisha 🗡️": "5253857790379728479",
    "Terrorist 💣": "5253801333034626685",
    "Mergan 🏹": "5253732566313246629",
    "Varvar 🛡️": "5251705273030059096",
    "Sadoqatli yordamchi 🤝":
"5251695411785149290",
    "Snayper 🎯": "5253891239585035856",
    "O'g'ri 🧑": "5251326272230960300",
    "Sehrgar 🧑": "5253986519139525710",
    "Sehrgar yordamchisi 🧑":
"5251295649114141399",
    "Arvoh 🧑": "5253785579094582070",
    "Sudya 🧑": "5253554007342890679",
    "Provokator 🧑": "5253986364520701937",
    "General 🏆": "5251484000609938639",
    "Josus 🧑": "5253605134633575717",
    "Bomj 🧑": "5251705547907967403",
    "Arxitektor 🏗️": "5253719200375024179",
    "Telba 🧑": "5253669211250663888",
    "Qorovul 🧑": "5253992119776878475",
    "Beshikdagi bola 🧑":
"5253926758964568403",
    "Tinch aholi 🧑":
"5251278383345610391",
}

```

```

# 🏠 Klan tizimi uchun qo'shimcha
portretlar (rol emas, shuning uchun
alohida)
CLAN_PORTRAIT_EMOJI = {
    "lideri": "5253463722835354488",    #
    Klan lideri
    "azosi": "5253473841778306376",    #
    Klan a'zosi
}

```



```

        "logo": "5251358776543457630",      # 🦁
    umumiy Lion/klan logotipi
}

#
=====
=====
# 🦁 PREMIUM EMOJI AVTOMATIK ULASH – 121-
lik to'plamdagi HAR BIR "eski"
# (oddiy unicode) emojini haqiqiy custom
emojiga avtomatik o'giradi.
#
=====
=====
# EMOJI_TO_ID – yuqoridagi PREMIUM_EMOJI /
ROLE_PORTRAIT_EMOJI /
# CLAN_PORTRAIT_EMOJI lug'atlaridan
chiqarilgan teskari lug'at. "To'plamda
# yo'q" deb izohlangan 17 ta eskirgan stub
ID (plus, rose, wizard, top_hat,
# axe, police, scale, bow, ninja, ghost,
scale_2, medal_2, detective,
# wizard_man, ruler, crazy, crazy_2) BILAB
chiqarib tashlandi.
#
# ⚠️ 16 ta emoji belgisi to'plamda 2-3
marta turli buyumlar uchun
# ishlatilgan (masalan uchta turli uzuk –
hammasi 🍷). Bunday holda
# avtomatik almashtirish faqat BITTA
(asosiy) variantni tanlaydi – izohda
# qolganlari yozilgan, kerak bo'lsa qo'lda
premium_emoji("kalit","emoji")

```

```

# orqali anig'ini tanlang.
#
=====
=====
EMOJI_TO_ID = {
    "🏛️": "5253656287694070722", # pillar
    "👛": "5253547530532201410", #
toolbox
    "💍": "5253587611167008718", # ring
(bor yana: ring_2, wedding_ring_set)
    "🛡️": "5253731101729400237", # shield
(bor yana: shield_2)
    "📜": "5253887094941589781", # scroll
(bor yana: document)
    "🩹": "5253997381111817316", #
bandage
    "🔥": "5253570680405928167", # flame
    "🎯": "5251516225749558785", # target
(bor yana: Snayper roli)
    "🚩": "5251734152390159229", #
flag_victory (bor yana: clan_banner,
silk_flag)
    "💎": "5251496189727124050", #
gems_cluster (bor yana: diamond,
elite_badge)
    "💠": "5253846468845937581", # bullet
    "📡": "5253972865438492175", # radar
    "❤️": "5253952975444947021", #
crystal_heart
    "👤": "5253580120744042388", # mask
(bor yana: mask_2)
    "👤": "5251316295021932853", #
shadow_figure (bor yana: person)
    "🔪": "5254004858649880562", # dagger

```

```

"👁️": "5253662747324882982", # eye
"🦊": "5251620945642169057", # fox /
fox_2 (mention()da endi sher ishlatiladi)
"👕": "5253611761768111359", # vest
"🕶️": "5251279323943451259", #
goggles
"💌": "5253623117661646222", #
love_letter
"💧": "5253655145232769885", # potion
"📍": "5253823894497826517", #
gps_beacon
"🔮": "5253592932631487494", # amulet
(bor yana: crystal_ball)
"🏠": "5253689492086234676", #
bank_rune (bor yana: vault)
"⚔️": "5251574663074587729", # sword
(bor yana: duel)
"💰": "5251467834353034219", # money
"🪙": "5253574498631851107", # coin
(bor yana: spinning_coin)
"📦": "5251575586492561187", #
treasure_chest (bor yana: box)
"🎰": "5251414052772554556", #
jackpot
"💳": "5251308731584522091", #
vip_card
"🎁": "5253706195214050358", # gift
"★": "5251515856382371891", # stars
(Telegram Stars – ELITE belgisi EMAS)
"🛡️": "5251674405100106367", #
immunity_charm (bor yana: admin_shield)
"💼": "5253568275224240880", #
briefcase
"🎲": "5253887975409886895", # dice

```

```
"📊": "5251426662796534647", # signal
"🍶": "5253955303317227024", # vase
(bor yana: vase_2)
"👤": "5251648746965477706", #
mother_daughter
"🏪": "5253530260468706909", # shop
"📈": "5251525597368198419", # chart
"⚙️": "5251609396475112519", # gear
"🔍": "5253956248210022896", #
magnifier
"🔔": "5251671888249267242", # bell
"🔑": "5253534177478877517", #
key_item
"🔒": "5253517976862237810", #
padlock
"🗺️": "5251462792061429779", # map
"🔫": "5253469057184737578", # gun
(bor yana: gun_2)
"🛡️": "5253630311731863374", # helmet
"🚫": "5251624768163066301", #
compass
"👛": "5251355615447526296", #
inventory_chest
"❓": "5254003046173682568", #
question
"⚠️": "5251375114599050954", # warning
"🌙": "5253688538603496820", # moon
"☀️": "5251569968675332763", # sun
"🙏": "5251604517392262503", # salute
"📖": "5251562774605112341", # book
"😡": "5253569756987960765", # angry
"🚀": "5253811460567506961", # rocket
"🗳️": "5253749166361845208", # ballot
"💥": "5253687546466052125", #
```

```

explosion
    "🔒": "5253984844102279619", #
broken_lock
    "🔑": "5251294738581070469", #
gravestone
    "⌚": "5253668944962690414", #
hourglass
    "⚡": "5253896878877091357", #
lightning
    "👑": "5251609456604652565", # crown
    "🖼️": "5253452517265680802", # frame
    "🐉": "5251539156579953188", # dragon
    "🏆": "5251284426364597200", # trophy
    "🏅": "5253583831595787507", # medal
    "👤": "5251358776543457630", # logo
(klan logotipi / SHER – ELITE belgisi)
}

```

```

def wrap_known_emojis(text):
    """Matndagi 121-lik to'plamda mavjud
    BARCHA "eski" (oddiy) emojilarni
    haqiqiy premium <tg-emoji> tegiga
    o'raydi. Allaqachon <tg-emoji> tegi
    ichida turgan belgilarga tegmaydi –
    shuning uchun HTML formatlangan
    xabarlariga xavfsiz qo'llash mumkin."""
    if not text:
        return text
    placeholders = []

    def _stash(m):
        placeholders.append(m.group(0))
        return f"\x00{len(placeholders) -

```

```
1}\x00"
```

```
    safe_text = re.sub(r"<tg-emoji[^\>]*>.*?</tg-emoji>", _stash, text, flags=re.S)
    for emoji, emoji_id in
EMOJI_TO_ID.items():
        if emoji in safe_text:
            safe_text = safe_text.replace(
                emoji, f'<tg-emoji emoji-
id="{emoji_id}">{emoji}</tg-emoji>'
            )
```

```
    def _unstash(m):
        return
placeholders[int(m.group(1))]
```

```
    return re.sub(r"\x00(\d+)\x00",
_unstash, safe_text)
```

```
def send_message_premium(chat_id, text,
reply_markup=None, **kwargs):
    """bot.send_message() ning premium-
emoji bilan avtomatik boyitilgan
varianti – istalgan joyda oddiy
bot.send_message(...) o'rniga shuni
chaqirsangiz, matningizdagi barcha eski
emojilar avtomatik haqiqiy
premium ko'rinishda chiqadi."""
    kwargs.setdefault("parse_mode", "HTML")
    return bot.send_message(chat_id,
wrap_known_emojis(text),
reply_markup=reply_markup, **kwargs)
```

```

# 🏆 GLOBAL AVTOMATIK ULASH – bot
allaqachon parse_mode="HTML" bilan ishga
# tushirilgan (yuqorida, `bot =
telebot.TeleBot(...)` qatorida), shuning
# uchun bu xavfsiz: FAQAT xabar MATNIGA
(bot.send_message / edit_message_text)
# ta'sir qiladi – tugma yozuvlari
(InlineKeyboardButton) va callback-alert
# (answer_callback_query) matnlari Telegram
tomonidan umuman HTML qabul
# qilmagani uchun ULARGA TEGINILMAYDI,
o'zgarishsiz qoladi.
_orig_send_message = bot.send_message
_orig_edit_message_text =
bot.edit_message_text
bot.send_message = lambda chat_id, text,
*a, **kw: _orig_send_message(chat_id,
wrap_known_emojis(text), *a, **kw)
bot.edit_message_text = lambda text, *a,
**kw:
_orig_edit_message_text(wrap_known_emojis(t
ext), *a, **kw)

def role_portrait(role_name):
    """Rol nomi oldiga (agar
ROLE_PORTRAIT_EMOJI'da mavjud bo'lsa)
HAQIQIY
    Hanter PORTRETINI prefiks sifatida
qo'shib qaytaradi. ID topilmasa, rol
    nomini o'zgarishsiz qaytaradi – xato
bermaydi, faqat portret chiqmaydi."""
    portrait_id =

```

```
ROLE_PORTRAIT_EMOJI.get(role_name)
    if not portrait_id:
        return role_name
    return f'<tg-emoji emoji-id="{
{portrait_id}">👤</tg-emoji> {role_name}'
```

```
def premium_emoji(key, fallback="★"):
    """PREMIUM_EMOJI lug'atidan shu kalit
    uchun tayyor HTML <tg-emoji> tegini
    qaytaradi.
    ID hali kiritilmagan bo'lsa, shunchaki
    oddiy fallback emojini qaytaradi (xato
    bermaydi)."""
    emoji_id = PREMIUM_EMOJI.get(key)
    if not emoji_id:
        return fallback
    return f'<tg-emoji emoji-id="{
{emoji_id}">{fallback}</tg-emoji>'
```

```
def render_premium_text(template,
**emoji_keys):
    """Shablon matn ichidagi {key}
    joylarini mos PREMIUM_EMOJI bilan
    almashtiradi.
    Masalan: render_premium_text("G'alaba
    {fire}!", fire=("fire", "🔥"))
    bu yerda qiymat (kalit, fallback)
    juftligi."""
    values = {name: premium_emoji(key,
    fallback) for name, (key, fallback) in
    emoji_keys.items()}
    return template.format(**values)
```



```

def send_premium_message(chat_id,
text_with_tags, reply_markup=None):
    """<tg-emoji> teglari bo'lgan HTML
matnni yuboradi. Agar biror sababdan xato
chiqsa (masalan juda eski bot
kutubxonasi versiyasi), oddiy xabar
sifatida
    (teglarsiz, faqat fallback emoji
bilan) qayta yuborishga urinadi."""
    try:
        return bot.send_message(chat_id,
text_with_tags, reply_markup=reply_markup)
    except Exception as e:
        _logger.warning("Premium emoji
xabari yuborilmadi, oddiy matn bilan
urinilmoqda: %s", e)
        import re as _re
        plain = _re.sub(r'<tg-emoji[^\>]*>
(.*?)</tg-emoji>', r'\1', text_with_tags)
        return bot.send_message(chat_id,
plain, reply_markup=reply_markup)

def
_extract_custom_emoji_entities(message):
    """Xabardagi barcha custom_emoji
turidagi entity'larni (ID + fallback emoji
matni
        bilan birga) ro'yxat qilib
qaytaradi."""
    result = []
    entities = (message.entities or []) +

```

```

(message.caption_entities or [])
    text = message.text or message.caption
    or ""

    # Telegram offset/length UTF-16
    birliklarida hisoblanadi – Python uchun
    to'g'ri kesish
    utf16 = text.encode("utf-16-le")
    for ent in entities:
        if ent.type == "custom_emoji":
            try:
                piece = utf16[ent.offset *
2: (ent.offset + ent.length) *
2].decode("utf-16-le")
            except Exception:
                piece = ""

    result.append((ent.custom_emoji_id, piece))
    return result

@bot.message_handler(
    func=lambda m: m.chat.type == "private"
    and _extract_custom_emoji_entities(m),
    content_types=["text"],
)
def collect_custom_emoji_ids(message):
    """ YORDAMCHI: bot egasi shaxsiy
    chatda o'zi yaratgan maxsus emojilarni
    yuborsa,
        bot ularning HAR BIRINING
    custom_emoji_id raqamini konsolga (log) VA
    chatga
        darhol qaytarib beradi. Bu orqali
    PREMIUM_EMOJI lug'atini to'ldirish oson

```

```

bo'ladi."""
    if not is_owner(message.from_user.id):
        return
    found =
_extract_custom_emoji_entities(message)
    if not found:
        return
    lines = ["📄 <b>Topilgan maxsus emoji
ID'lari:</b>\n"]
    for emoji_id, fallback in found:
        line = f"{fallback} → <code>
{emoji_id}</code>"
        lines.append(line)
        _logger.info("Custom emoji topildi:
fallback=%s id=%s", fallback, emoji_id)
        print(f"[PREMIUM EMOJI] fallback=
{fallback!r} custom_emoji_id={emoji_id}")
        lines.append("\n📄 Shu ID'larni
<code>PREMIUM_EMOJI</code> lug'atiga
qo'shing, masalan:\n"
                    f'<code>"nomi": "
{found[0][0]}"</code>')
        bot.send_message(message.chat.id,
"\n".join(lines))

@bot.message_handler(commands=
["hanter_ids"])
def cmd_hanter_ids(message):
    """📄 VAQTINCHALIK BUYRUQ:
'HanterMafiaBot' maxsus emoji to'plamini
Telegram serveridan TO'G'RIDAN-TO'G'RI
so'rab, uning HAQIQIY (yuklangan)
tartibida, 1 dan boshlab raqamlab

```

```

chiqaradi. Qo'lda emoji terib
    nusxalashda tartib buzilishi mumkin –
bu buyruq esa hech qachon
    adashmaydi, chunki ma'lumotni bevosita
Telegramning o'zidan oladi.
    Faqat bot egasi uchun ishlaydi. Ishni
tugatgach shu buyruqni (va shu
    funksiyani) kodda qoldirish yoki
o'chirish ixtiyoriy – xavfsiz, hech
    kimga zarar keltirmaydi, faqat egaga
ma'lumot chiqaradi."""
    maybe_capture_owner(message.from_user)
    if not is_owner(message.from_user.id):
        return
    try:
        sset =
bot.get_sticker_set("HanterMafiaBot")
    except Exception as e:
        bot.send_message(message.chat.id,
f"❌ To'plamni olishda xato: {e}")
        return
        lines = [f"{i}. {s.emoji} →
{s.custom_emoji_id}" for i, s in
enumerate(sset.stickers, start=1)]
        bot.send_message(message.chat.id, f"📁
Jami: {len(lines)} ta emoji topildi. Tartib
– to'plamdagi HAQIQIY (yuklangan) tartib.")
        chunk, length = [], 0
        for line in lines:
            chunk.append(line)
            length += len(line) + 1
            if length > 3000:

bot.send_message(message.chat.id,

```

```

"\n".join(chunk))
        chunk, length = [], 0
    if chunk:
        bot.send_message(message.chat.id,
            "\n".join(chunk))

@bot.message_handler(commands=
["emoji_test"])
def cmd_emoji_test(message):
    """🔧 Sinov buyrug'i – PREMIUM_EMOJI
    lug'atidagi barcha emojilarni bitta xabarda
    ko'rsatadi (faqat bot egasi uchun), shu
    orqali ID to'g'ri kiritilganini tekshirish
    mumkin."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        return
    if not PREMIUM_EMOJI:
        bot.send_message(
            message.chat.id,
            "⚠️ PREMIUM_EMOJI lug'ati hali
            bo'sh.\n\n"
            "1) Shaxsiy chatda (bot bilan
            DM) o'zingiz yaratgan maxsus emojini
            yuboring.\n"
            "2) Bot sizga uning ID raqamini
            qaytaradi.\n"
            "3) Shu ID'ni kod ichidagi
            PREMIUM_EMOJI lug'atiga qo'shing va botni
            qayta ishga tushiring.",
        )
    return

```

```

        parts = [f"{key}: {premium_emoji(key)}"
for key in PREMIUM_EMOJI]
        send_premium_message(message.chat.id,
"🌟 <b>Premium emoji sinovi:</b>\n\n" +
"\n".join(parts))

```

```

ITEM_ANNOUNCE_FLAVORS = {
    "🖋️ Zaharli flakon": "🖋️ <i>Tunning  
zulmatida kimdir zaharli flakonni  
ishlatdi... kimningdir tanasida zahar yura  
boshladi!</i>",
    "📍 GPS Mayak": "📍 <i>Kimdir yashirin  
GPS mayagini faollashtirdi va kimningdir  
joylashuvini kuzatmoqda...</i>",
    "🕒 Sirli kompas": "🕒 <i>Kimdir sirli  
kompasni ishlatib, kimningdir haqiqiy  
tarafini bilib oldi...</i>",
    "💣 Tutunli bomba": "💣 <i>Guruh ichida  
kutilmaganda tutun bombasi portladi –  
kimdir bugun linchdan qochib qutulmoqchi!  
</i>",
    "🔦 Katta Fonar": "🔦 <i>Kimdir Katta  
Fonarni yoqib, birovning haqiqiy qiyofasini  
yorug'likka chiqardi...</i>",
    "📡 Maxfiy radar": "📡 <i>Kimdir maxfiy  
radar yordamida o'z rolini boshqasiga  
almashtirdi...</i>",
}

```

```

def announce_item_use(chat_id, user_id,
item_label, target_id=None,
effect_text=""):

```

```

"""🛒 Do'kondan olingan buyum o'yin
ichida ishlatilganda guruhga – KIM ekani
oshkor
    qilinmasdan (anonim), lekin QAYSI buyum
ishlaganini aniq bildiruvchi tarzda e'lon
    qilinadi. Ishlatgan kishiga natija
haqidagi DM chaqiruvchi joyda alohida
yuboriladi,
    shu funksiya faqat guruh e'loni va
(ixtiyoriy) qo'shimcha DM uchun."""
    flavor =
ITEM_ANNOUNCE_FLAVORS.get(item_label, f"🛒
<i>Kimdir do'kondan olingan buyumini
ishlatdi:</i> <b>{item_label}</b>")
    try:
        bot.send_message(chat_id, flavor)
    except Exception:
        pass
    if target_id is not None:
        # ba'zi chaqiruvchilar uchun
qo'shimcha DM kerak bo'lishi mumkin –
ixtiyoriy
        target_name =
user_dict(target_id).get("name",
"O'yinchi")
        extra = f"\n👁️ Qo'llanildi:
{mention(target_id, target_name)}"
        if effect_text:
            extra += f"\n{effect_text}"
        safe_send(user_id, extra)

# 🦊 Rol nomidagi oddiy (unicode) belgini –
agar mos PREMIUM_EMOJI ID mavjud

```

```
# bo'lsa – HAQIQIY premium emojiga
almashtirish uchun xarita. Bu FAQAT
# ko'rsatish (roster_breakdown_text) uchun
ishlatiladi – ROLES_INFO, MAFIA_ROLES,
# team_of() va boshqa o'yin-logikasidagi
asl rol nomlariga HECH QACHON tegmaydi,
# shuning uchun o'yin mexanikasi butunlay
avvalgidek ishlayveradi.
```

```
_ROLE_EMOJI_PREMIUM_MAP = {
    "👑": "top_hat",      # Don
    "🔪": "dagger",      # Qotil
    "🏹": "bow",         # Mergan
    "🔨": "axe",         # Varvar
    "🥷": "ninja",       # O'g'ri
    "🧙": "wizard_man",  # Sehrgar
    "👻": "ghost",       # Arvoh
    "💣": "bomb",        # Terrorist
    "😜": "crazy",       # Telba
    "📏": "ruler",       # Arxitektor
    "👮": "police",      # Serjant
    "⚖️": "scale",       # Advokat
    "🏅": "medal",       # General
    "👨": "scale_2",     # Sudya
    "🕵": "detective",   # Komissar
}
```

```
def premium_role_label(role_name):
    """Rolni ko'rsatish uchun ENG YAXSHI
variantni qaytaradi – FAQAT matnni
chiroyli ko'rsatish uchun, o'yin
logikasidagi asl qiymatga (masalan
game["players"][uid]["role"]) hech
qanday ta'sir qilmaydi.
```


1) Avval ROLE_PORTRAIT_EMOJI'da shu rol uchun HAQIQIY Hanter portreti bor-yo'qligi tekshiriladi – bo'lsa, o'sha ishlatiladi.

2) Bo'lmasa, eski usul – rol nomidagi oddiy emojini mos PREMIUM_EMOJI belgisiga almashtirish – ishlatiladi (zaxira sifatida)."""

```
if role_name in ROLE_PORTRAIT_EMOJI:
    return role_portrait(role_name)
for plain, key in
_ROLE_EMOJI_PREMIUM_MAP.items():
    if plain in role_name:
        return role_name.replace(plain,
premium_emoji(key, plain))
return role_name
```

```
def roster_breakdown_text(game):
    """qoshimchakod-larda ko'rilgan boshqa
botlar uslubida – tirik o'yinchilar
ro'yxati
    va ular orasidagi rol tarkibi (kim
qaysi rolda ekani oshkor qilinmaydi, faqat
statistika)."""
    alive = alive_players(game)
    if not alive:
        return "Tirik o'yinchi qolmadi."
```

```
    lines = ["👤 <b>Tirik o'yinchilar:
</b>"]
    for i, (uid, p) in
enumerate(alive.items(), start=1):
        lines.append(f"{i}. {mention(uid,
```

```

p['name']})}")

    mafia_roles, indep_roles, town_roles =
[], [], []
    for p in alive.values():
        team = team_of(p["role"])
        if team == "mafia":
            mafia_roles.append(p["role"])
        elif team == "independent":
            indep_roles.append(p["role"])
        else:
            town_roles.append(p["role"])

    def group_counts(roles):
        counts = {}
        for r in roles:
            counts[r] = counts.get(r, 0) +
1
            parts = []
            for r, c in counts.items():
                label = premium_role_label(r)
                # 🦊 faqat ko'rsatish uchun premium emoji
                parts.append(label if c == 1
else f"{label} - {c}")
            return ", ".join(parts) if parts
            else "-"

    lines.append("")
    lines.append(f"🏠 <b>Tinch aholilar -
{len(town_roles)}</b>\n{group_counts(town_roles)}")
    lines.append(f"👤 <b>Yakka rollar -
{len(indep_roles)}</b>\n{group_counts(indep_roles)}")

```

```

        lines.append(f"👥 <b>Mafiyalar -  

        {len(mafia_roles)}):  

        </b>\n{group_counts(mafia_roles)}")
        lines.append("")
        lines.append(f"<b>Jami:</b>  

        {len(alive)} ta")
        return "\n".join(lines)

#
=====
=====
# ASOSIY MENYU – hech qanday tugma "o'lik"  

bo'lib qolmasin
#
=====
=====

def get_main_menu(chat_id=None,  

user_id=None):
    kb = types.InlineKeyboardMarkup()
    group_url = None
    if chat_id and chat_id in GAMES and  

    GAMES[chat_id].get("group_link"):
        group_url = GAMES[chat_id]  

    ["group_link"]
    if group_url:

kb.add(types.InlineKeyboardButton("🚀  

Guruhga qaytish", url=group_url))
kb.add(
    types.InlineKeyboardButton("👥 28  

ta Rollar", callback_data="menu|roles"),
    types.InlineKeyboardButton("👤

```

```

Kabinet", callback_data="menu|cabinet"),
    )
    kb.add(
        types.InlineKeyboardButton("🛒 Do'konlar", callback_data="menu|shop"),
        types.InlineKeyboardButton("🛒 HC sotib olish", callback_data="menu|buyhc"),
    )
    kb.add(types.InlineKeyboardButton("💎 Almaz sotib olish",
callback_data="menu|birja"))
    kb.add(
        types.InlineKeyboardButton("👑 HUNTER ELITE", callback_data="menu|elite"),
        types.InlineKeyboardButton("🌐 Til / Language", callback_data="menu|lang"),
    )
    kb.add(
        types.InlineKeyboardButton("💵 Dollar do'koni",
callback_data="menu|dollarshop"),
        types.InlineKeyboardButton("💎➡️🛒 Olmos ayirboshlash",
callback_data="menu|d2c"),
    )
    kb.add(
        types.InlineKeyboardButton("✨ Faol kuchlarim", callback_data="menu|effects"),
        types.InlineKeyboardButton("🏠 Klanim", callback_data="menu|klan"),
    )
    kb.add(
        types.InlineKeyboardButton("📦 Inventar", callback_data="menu|inventory"),

```

```

        types.InlineKeyboardButton("🏆
Musobaqalar",
callback_data="menu|tournament"),
    )
    kb.add(
        types.InlineKeyboardButton("🏆
Geroyim", callback_data="menu|hero"),
        types.InlineKeyboardButton("🏆 Ball
reytingi",
callback_data="menu|points_top"),
    )
    kb.add(
        types.InlineKeyboardButton("🛒 Qora
Bozor", callback_data="menu|market_info"),
        types.InlineKeyboardButton("🏆 Top
Reyting", callback_data="menu|top"),
    )
    kb.add(types.InlineKeyboardButton("🎁
Kunlik bonus", callback_data="menu|bonus"))
    kb.add(types.InlineKeyboardButton(f"🧠
{THERON_NAME} AI yordamchi",
callback_data="menu|theron"))
    kb.add(
        types.InlineKeyboardButton("💍
Nikoh haqida",
callback_data="menu|nikoh_info"),
        types.InlineKeyboardButton("⚔️ Duel
haqida", callback_data="menu|duel_info"),
    )
    kb.add(types.InlineKeyboardButton("❓
Yordam / Buyruqlar",
callback_data="menu|help"))
    kb.add(types.InlineKeyboardButton("🔗
Qanday o'ynash kerak? (Boshlang'ich)",

```

```

callback_data="menu|guide"))
    if is_owner(user_id):

kb.add(types.InlineKeyboardButton("⚙️
Sozlamalar (Admin)",
callback_data="admin|panel"))
    return kb

@bot.callback_query_handler(func=lambda c:
c.data == "menu|guide")
def cb_menu_guide(call):
    """🔪 Chalkash tuyulgan yangi
foydalanuvchilar uchun – bot qanday
ishlashini 5 ta oddiy qadamda
tushuntiruvchi qisqa yo'l-yo'riq.
    Botning to'liq imkoniyatlari (klan,
jamoaviy o'yin, ELITE va h.k.)
    o'zgarishsiz qoladi – bu faqat yangi
boshlovchiga mo'ljallangan qisqacha
xarita, murakkab qismlarni
O'CHIRMAYDI."""
    try:
        maybe_capture_owner(call.from_user)
        bot.answer_callback_query(call.id)
        bot.send_message(
            call.message.chat.id,
            "🔪 <b>Botdan foydalanish – 5
ta oddiy qadam</b>\n\n"
            "1 Botni guruhingizga
<b>admin</b> qilib qo'shing.\n"
            "2 Guruhda
<code>/newgame</code> deb yozing – o'yin
ro'yxati ochiladi.\n"

```

```

        "3 \n🎮 O'yinga qo'shilish\n"
        tugmasini bosing.\n"
        "4 Yetarli o'yinchi
        yig'ilgach, o'yin o'zi boshlanadi – sizga
        shaxsiy "
        "chatda <b>rolingiz</b>
        keladi.\n"
        "5 Tun/kunduz navbat bilan
        davom etadi – bot har safar nima qilish "
        "kerakligini o'zi aytib
        turadi.\n\n"
        "💡 <i>Boshqa hamma narsa
        (klan, ELITE, jamoaviy o'yin, do'kon) – "
        "ixtiyoriy qo'shimchalar.
        Ularsiz ham oddiy o'yinni bermalol o'ynay
        olasiz!</i>\n\n"
        "? Savol bo'lsa –
        <code>/help</code> orqali to'liq buyruqlar
        ro'yxatini ko'ring.",
    )
    except Exception as e:
        _logger.warning("cb_menu_guide
        xatolik: %s", e)

#
=====
=====
# /start
#
=====
=====

@bot.message_handler(commands=["start"])

```

```

def cmd_start(message):
    global BOT_USERNAME
    maybe_capture_owner(message.from_user)
    if BOT_USERNAME is None:
        BOT_USERNAME =
bot.get_me().username

    if message.chat.type != "private":
        safe_delete(message)
        return

    user_dict(message.from_user.id,
message.from_user.first_name)

    # 🎮 guruhdagi "O'yinga qo'shilish"
    tugmasi orqali kelingan bo'lsa (deep-link:
    # https://t.me/BOT?
    start=join_<chat_id>) – shu yerda avtomatik
    o'yinga qo'shamiz
        parts = message.text.split(maxsplit=1)
        payload = parts[1].strip() if
        len(parts) > 1 else ""
        if payload.startswith("join_"):
            try:
                join_chat_id =
int(payload[len("join_"):])
            except ValueError:
                join_chat_id = None

        if join_chat_id is not None:
            status = do_join(join_chat_id,
message.from_user)
            game = GAMES.get(join_chat_id)
            group_title =

```



```

(game.get("chat_title") if game else None)
or "guruh"

        group_link =
game.get("group_link") if game else None
        kb = None
        if group_link:
            kb =
types.InlineKeyboardMarkup()

kb.add(types.InlineKeyboardButton(f"🔙
{group_title} guruhiga qaytish",
url=group_link))

        if status == "ok":
            bot.send_message(
                message.chat.id,
                f"✅ <b>Siz o'yinga
muvaffaqiyatli qo'shildingiz!</b>\n\n🎮
Guruh: <b>{group_title}</b>",
                reply_markup=kb,
            )
        elif status == "need_squad":

bot.send_message(message.chat.id, "🐱🦅 Bu
– Jamoaviy o'yin! Guruhga qaytib, 🐱 Bo'ri
yoki 🦅 Burgut tugmasidan birini bosib
qo'shiling.", reply_markup=kb)
        elif status == "need_couple":

bot.send_message(message.chat.id, "💍 Bu –
Para o'yin! Guruhga qaytib, faqat 💍
tugmasi orqali (turmush o'rtog'ingiz bilan)
qo'shiling.", reply_markup=kb)
        elif status == "already":

```

```

bot.send_message(message.chat.id, "📄 Siz
allaqachon bu o'yinga qo'shilgansiz.",
reply_markup=kb)
    elif status == "banned":

bot.send_message(message.chat.id, "🚫 Siz
botdan foydalanishdan bloklangansiz.")
    else: # no_game
        bot.send_message(
            message.chat.id,
            "❌ Bu o'yin allaqachon
boshlangan yoki topilmadi. Guruhda yangi
o'yin ochilishini kuting.",
            reply_markup=kb,
        )
        # 🛠️ TUZATISH: avval bu
yerda foydalanuvchida hech qanday tugma
qolmasdi –
            # xato xabaridan keyin
bosadigan narsa topolmay, yana /start deb
urinaverar
            # (Telegram klienti ba'zan
eski deep-link'ni qayta yuboradi) va xuddi
shu
            # xatoni cheksiz
ko'raverardi. Endi doim BOSH MENYU ham
qo'shimcha
            # ko'rsatiladi –
foydalanuvchida har doim bosadigan tugma
bo'lishi uchun.
        bot.send_photo(
            message.chat.id,
MAIN_PHOTO,

```

```

        caption="👉 Bu orada,
bosh menyudan foydalanishingiz mumkin:",

reply_markup=get_main_menu(None,
message.from_user.id),
    )
    return

    caption = (
        f"🌙 <b>Hunter Mafia</b> botiga
xush kelibsiz, <b>
{message.from_user.first_name}</b>!\n\n"
        "Emotsiyalarni chetga suring. Bu
yerda faqat sovuqqonlik va aniq "
        "hisob-kitob g'alaba qozonadi. 🤖
🔪\n\n"
        "Guruhga botni admin qilib qo'shing
va /NewGame buyrug'i bilan o'yin boshlang."
    )
    bot.send_photo(message.chat.id,
MAIN_PHOTO, caption=caption,
reply_markup=get_main_menu(None,
message.from_user.id))

# 🧠 Theron – bot egasi shaxsiy chatga
kirganda, mehnatkash yordamchi sifatida
# alohida (fon rejimida, asosiy /start
javobini KECHIKTIRMASDAN) salomlashadi.
    if is_owner(message.from_user.id) and
theron_available():
        def _owner_greet():
            try:
                greeting =
theron_owner_greeting()

```

```

        if greeting:

bot.send_message(message.chat.id, f"🧠 <b>
{THERON_NAME}</b> {greeting}")
        except Exception as e:
            _logger.warning("Theron
owner greeting xatolik: %s", e)

threading.Thread(target=_owner_greet,
daemon=True).start()

#
=====
=====
# 🐾🦅 JAMOAVIY O'YIN (/new_team) va 📿
PARA O'YIN (/new_para) – 2026 YANGI VERSIYA
#
# 🛠️ TUZATILDI (katta o'zgarish): bu
ikkala rejim ENDI alohida,
soddalashtirilgan
# ("faqat kim kimni tunda otadi"
darajasidagi) tizim EMAS. Ular asosiy
Hunter
# Mafia o'yin dvigeniga (GAMES lug'ati, 28
TA ROL, assign_roles, start_night/
# cb_night_action/resolve_night,
start_day/open_day_voting/cb_vote/resolve_d
ay,
# osish-tasdiqlash bosqichi, end_game)
to'g'ridan-to'g'ri ULANADI. Bu degani:
#
# • Rollar – asosiy o'yindagi 28 ta rol
xuddi shunday, tasodifiy taqsimlanadi.

```

```
# • Har bir rol tunda xuddi asosiy
o'yindagidek harakat qiladi (Don/Mafia
#   birga qurbon tanlaydi, Doktor
davolaydi, Komissar tekshiradi va h.k.).
# • Ovoz berish – HECH QANDAY
ochiq/guruh ichidagi tugma yo'q. Hammasi
#   asosiy o'yindagi kabi botning
shaxsiy chatida (DM) o'tadi.
# • Yagona farq – QO'SHILISH tartibi va
G'ALABA sharti:
#   🐾🦅 Jamoaviy: qo'shilishda 🐾
yoki 🦅 jamoa tanlanadi (kim qaysi
#   jamoada ekani oxirigacha
MAXFIY). Bitta jamoaning BARCHA a'zosi
#   halok bo'lguncha o'yin davom
etadi – tirik qolgan jamoa g'olib.
#   💍 Para: FAQAT botda rasmiy
nikohdagi (/nikoh) juftliklar qo'shiladi.
#   Juftlikning bir a'zosi (tunda
yoki kunduzi) halok bo'lsa, ikkinchisi
#   ham DARHOL o'yindan chiqadi
('bog'langan taqdir'). Oxirgi BITTA
#   juftlik tirik qolguncha o'yin
davom etadi – o'sha juftlik g'olib.
# • Mukofot tizimi – g'alaba/mag'lubiyat
puli, ball, faollik reytingi –
#   hammasi asosiy o'yin bilan 100% bir
xil (end_game funksiyasi orqali).
#
# Bularning barchasi allaqachon GAMES
ichidagi squad_mode/couple_mode
# maydonlari orqali to'liq ishlab turadi
(join, assign_roles, night/day,
# check_and_end_game, end_game – barchasi
```

```

shu maydonlarni hisobga oladi).
# Pastdagi kod shunchaki o'sha mexanizmni
/new_team, /new_para va h.k.
# qulay, alohida buyruqlar orqali ochib
beradi.
#
=====
=====

def _special_mode_flag(mode):
    return "squad_mode" if mode == "squad"
    else "couple_mode"

def _special_mode_label(mode):
    return "🐱🐶 Jamoaviy o'yin" if mode ==
"squad" else "👫 Para o'yin"

def _open_special_lobby(message, mode):
    """👫/🐱🐶 FAQAT admin/owner –
/new_team yoki /new_para: shu guruhda
    tegishli rejim (squad_mode/couple_mode)
    yoqilgan holda YANGI o'yin
    ro'yxatga olishni ochadi (asosiy
/newgame bilan bir xil pipeline,
    faqat rejim majburiy yoqilgan
    bo'ladi)."""
    global BOT_USERNAME
    try:

maybe_capture_owner(message.from_user)
    if BOT_USERNAME is None:
        try:

```

```

        BOT_USERNAME =
bot.get_me().username
        except Exception:
            pass
            safe_delete(message)
            if message.chat.type not in
("group", "supergroup"):

bot.send_message(message.chat.id, f"
{_special_mode_label(mode)} bu buyruq faqat
guruhda ishlaydi.")
            return
            if not is_authorized(message):

bot.send_message(message.chat.id, "🚫 Siz
admin emassiz.")
            return

        chat_id = message.chat.id
        add_known_group(chat_id,
message.chat.title or "Nomsiz guruh")

        with GAME_LOCK:
            old = GAMES.get(chat_id)
            if old and
old.get("join_msg_id"):

_close_join_message(chat_id,
old["join_msg_id"])

        game = new_game(chat_id,
message.chat.title)
        game[_special_mode_flag(mode)]
= True

```

```

        GAMES[chat_id] = game
        try:
            game["group_link"] =
bot.export_chat_invite_link(chat_id)
        except Exception:
            pass

        kb = build_join_markup(chat_id,
game)
        sent = bot.send_message(
            chat_id,
            f"
{_special_mode_label(mode)}
boshlandi!\n\n{build_join_text(game)}",
            reply_markup=kb,
        )
        game["join_msg_id"] =
sent.message_id
        try:

bot.pin_chat_message(chat_id,
sent.message_id, disable_notification=True)
        except Exception:
            pass

            save_games_state()
        except Exception as e:

_logger.warning("_open_special_lobby(%s)
xatolik: %s", mode, e)
        try:

bot.send_message(message.chat.id, "⚠️
O'yinni boshlashda xatolik yuz berdi.
Qaytadan urinib ko'ring.")

```



```

except Exception:
    pass

def _povtor_special_lobby(message, mode):
    """🔁 FAQAT admin/owner – ro'yxat
    xabari yo'qolib qolsa, qayta yuboradi.
    Yozilgan a'zolar hech qayerga
    yo'qolmaydi – faqat xabar yangidan
    chiqadi."""
    try:

        maybe_capture_owner(message.from_user)
        safe_delete(message)
        if message.chat.type not in
        ("group", "supergroup"):

            bot.send_message(message.chat.id, f"
            {_special_mode_label(mode)} bu buyruq faqat
            guruhda ishlaydi.")
            return

            if not is_authorized(message):

                bot.send_message(message.chat.id, "🚫 Siz
                admin emassiz.")
                return

            chat_id = message.chat.id
            game = GAMES.get(chat_id)
            flag = _special_mode_flag(mode)
            if not game or game.get("phase") !=
            "waiting" or not game.get(flag):
                bot.send_message(
                    message.chat.id,

```

```

        f"❌ Hozir
        {_special_mode_label(mode)} ro'yxatga olish
        bosqichida emas. Avval tegishli /new...
        buyrug'i bilan oching.",
        )
        return
        if game.get("join_msg_id"):
            _close_join_message(chat_id,
            game["join_msg_id"])
            sent = bot.send_message(chat_id,
            build_join_text(game),
            reply_markup=build_join_markup(chat_id,
            game))
            game["join_msg_id"] =
            sent.message_id
            try:
                bot.pin_chat_message(chat_id,
                sent.message_id, disable_notification=True)
            except Exception:
                pass
            except Exception as e:

_logger.warning("_povtor_special_lobby(%s)
xatolik: %s", mode, e)
            try:

bot.send_message(message.chat.id, "⚠️
Xabarni qayta yuborishda xatolik yuz
berdi.")
            except Exception:
                pass

def _start_special_game(message, mode):

```

```

"""👉 FAQAT admin/owner – ro'yxatni
yopadi, rollarni (28 tadan) taqsimlaydi
va birinchi tunni boshlaydi (xuddi
asosiy /startgame kabi – chunki aynan
o'sha funksiyaga o'tkaziladi)."""
try:

maybe_capture_owner(message.from_user)
    if message.chat.type not in
("group", "supergroup"):
        return
    if not is_authorized(message):
        safe_delete(message)

bot.send_message(message.chat.id, "🚫 Siz
admin emassiz.")
    return

    chat_id = message.chat.id
    game = GAMES.get(chat_id)
    flag = _special_mode_flag(mode)
    if not game or game.get("phase") !=
"waiting" or not game.get(flag):
        safe_delete(message)

bot.send_message(message.chat.id, f"❌
Hozir faol {_special_mode_label(mode)}
ro'yxati yo'q.")
    return

    if mode == "squad":
        wolf_n = sum(1 for uid in
game["players"] if game["squads"].get(uid)
== "wolf")

```

```

        eagle_n = sum(1 for uid in
game["players"] if game["squads"].get(uid)
== "eagle")

        if wolf_n < 1 or eagle_n < 1:
            safe_delete(message)
            bot.send_message(chat_id,
"❌ Har ikki jamoada (🐺 va 🦅) kamida
bittadan a'zo bo'lishi kerak.")
            return

        else:
            paired_n = sum(1 for uid in
game["players"] if get_partner_id(uid) in
game["players"])
            if paired_n < 2:
                safe_delete(message)
                bot.send_message(chat_id,
"❌ Kamida bitta to'liq juftlik (ikkalasi
ham ro'yxatda) kerak.")
                return

        # 🎮 Asosiy o'yin bilan bir xil
pipeline: rol taqsimlash + tun boshlash
        cmd_startgame(message)
    except Exception as e:

_logger.warning("_start_special_game(%s)
xatolik: %s", mode, e)
    try:

bot.send_message(message.chat.id, "⚠️
O'yinni boshlashda xatolik yuz berdi.")
    except Exception:
        pass

```

```

def _stop_special_game(message, mode):
    """🚫 FAQAT admin/owner – mos rejimdagi
    faol o'yinni istalgan bosqichda
    (ro'yxat, tun, kun) darhol butunlay
    bekor qiladi."""
    try:

    maybe_capture_owner(message.from_user)
        safe_delete(message)
        if not is_authorized(message):

    bot.send_message(message.chat.id, "🚫 Siz
    admin emassiz.")
        return
        chat_id = message.chat.id
        flag = _special_mode_flag(mode)
        game = GAMES.get(chat_id)
        if game and game.get(flag):
            del GAMES[chat_id]
            save_games_state()

    bot.send_message(message.chat.id, f"🚫
    {_special_mode_label(mode)} admin tomonidan
    to'xtatildi.")
        else:

    bot.send_message(message.chat.id, f"Hozir
    faol {_special_mode_label(mode)} yo'q.")
        except Exception as e:

    _logger.warning("_stop_special_game(%s)
    xatolik: %s", mode, e)

```

```
@bot.message_handler(commands=["new_team"])
def cmd_new_team(message):
    _open_special_lobby(message, "squad")
```

```
@bot.message_handler(commands=
["povtor_team"])
def cmd_povtor_team(message):
    _povtor_special_lobby(message, "squad")
```

```
@bot.message_handler(commands=
["start_team"])
def cmd_start_team(message):
    _start_special_game(message, "squad")
```

```
@bot.message_handler(commands=
["stop_team"])
def cmd_stop_team(message):
    _stop_special_game(message, "squad")
```

```
@bot.message_handler(commands=["new_para",
"parastart"])
def cmd_parastart(message):
    _open_special_lobby(message, "couple")
```

```
@bot.message_handler(commands=
["povtor_para"])
def cmd_povtor_para(message):
    _povtor_special_lobby(message,
```

```

"couple")

@bot.message_handler(commands=
["start_para", "paraforce"])
def cmd_paraforce(message):
    _start_special_game(message, "couple")

@bot.message_handler(commands=["stop_para",
"parastop"])
def cmd_parastop(message):
    _stop_special_game(message, "couple")

#
=====
# 📖 QOIDALAR – /jamoq_qoida (Team Game)
va /juftlik_qoida (Para Game)
# Ikkalasi ham endi: 🌙 tun (maxfiy DM
ovoz berish, 28 ta rol asosida) →
# ☀️ kun (muhokama → DM'da ovoz berish →
"Ha/Yo'q" tasdiqlash) – xuddi
# asosiy Hunter Mafia o'yinidagi kabi.
HECH QANDAY ochiq/guruh ichidagi
# tugma bilan ovoz berish yo'q.
#
=====
=====

TEAM_GAME_RULES_TEXT = (
    "🐾 <b>Jamoaviy o'yin (Team Game) –
to'liq qoidalar</b>\n\n"

```

"1) Ro'yxatdan o'tish\n"
"• Admin /new_team buyrug'i bilan
ro'yxatni ochadi.\n"
"• Har bir o'yinchi 🐱 Bo'ri yoki 🦅
Burgut tugmasini bosib jamoasini tanlaydi –
"
"kim qaysi jamoada ekani o'yin
OXIRIGACHA maxfiy qoladi (guruhda faqat
soni ko'rinadi).\n"
"• /povtor_team – ro'yxat xabari
yo'qolib qolsa, qayta chiqaradi.\n"
"• /start_team – ro'yxatni yopadi, 28
ta roldan har biriga tasodifiy rol beradi "
"(xuddi asosiy Hunter Mafia'dagi kabi)
va birinchi tunni boshlaydi.\n\n"
"2) Rollar va harakatlar\n"
"• Rollar aynan asosiy o'yindagi 28 ta
rol – Don/Mafia, Komissar, Doktor va h.k. "
"Har bir o'yinchi o'z roliga ko'ra,
asosiy o'yindagi kabi harakat qiladi.\n"
"• Tun va kunduzgi ovoz berish –
HAMMASI botning shaxsiy chatida (DM). "
"Guruhda hech qanday ochiq ovoz berish
tugmasi bo'lmaydi.\n\n"
"3) G'alaba sharti\n"
"• Oddiy Mafiya/Tinch aholi balansi bu
rejimda g'alabani BELGILAMAYDI. "
"Faqt: dushman jamoaning BARCHA a'zosi
halok bo'lsa – tirik qolgan jamoa
g'olib!\n\n"
"4) Mukofot\n"
"• G'olib jamoa a'zolariga g'alaba
mukofoti, mag'lub jamoaga ishtirok mukofoti
– "


```

"asosiy o'yin bilan bir xil miqdorda
beriladi.\n\n"
"<b>5) Boshqaruv</b>\n"
"• /stop_team – o'yinni istalgan
bosqichda darhol butunlay bekor qiladi."
)

PARA_GAME_RULES_TEXT = (
"💍 <b>Para o'yin (Nikohdagi
juftliklar) – to'liq qoidalar</b>\n\n"
"<b>1) Ro'yxatdan o'tish</b>\n"
"• Admin /new_para bilan ro'yxatni
ochadi.\n"
"• FAQAT botda RASMIY nikohdagi
(/nikoh) juftliklar \"💍 Men va turmush
o'rtog'imni "
"qo'shish\" tugmasini bosadi – ikkalasi
BIRGA yoziladi.\n"
"• /povtor_para – ro'yxat xabarini
qayta chiqaradi.\n"
"• /start_para – ro'yxatni yopadi, HAR
BIR o'yinchiga (juftlikdan qat'i nazar, "
"alohida-alohida) 28 ta roldan biri
tasodifiy beriladi va birinchi tunni
boshlaydi.\n\n"
"<b>2) Rollar</b>\n"
"• Har bir o'yinchi o'zining shaxsiy
rolini oladi (asosiy o'yindagi 28 ta
roldan) – "
"juftlikning ikkala a'zosi turlicha
rolga ega bo'lishi mumkin.\n"
"• Tun va kunduzgi ovoz berish – asosiy
o'yindagi kabi, faqat botning shaxsiy "
"chatida (DM). Hech qanday ochiq guruh

```

```

ovoz berish yo'q.\n\n"
    "<b>3) 💔 Bog'langan taqdir (eng muhim
qoida)</b>\n"
    "• Juftlikning BIR a'zosi (tunda
o'ldirilib yoki kunduzi osilib) halok
bo'lsa, "
    "ikkinchisi ham AVTOMATIK ravishda,
DARHOL o'yindan chiqariladi – va shu payt "
    "juftlik guruhga birinchi marta fosh
qilinadi.\n\n"
    "<b>4) G'alaba sharti</b>\n"
    "• O'yin BITTA juftlik (ikkalasi ham
tirik) qolguncha davom etadi. "
    "Boshqa hamma halok bo'lgach, o'sha
oxirgi juftlik – rollaridan qat'i nazar –
g'olib!\n\n"
    "<b>5) Mukofot</b>\n"
    "• G'olib juftlikka g'alaba mukofoti,
boshqalarga ishtirok mukofoti – "
    "asosiy o'yin bilan bir xil miqdorda
beriladi.\n\n"
    "<b>6) Boshqaruv</b>\n"
    "• /stop_para – o'yinni istalgan
bosqichda darhol butunlay bekor qiladi."
)

```

```

@bot.message_handler(commands=
["jamoq_qoida", "team_qoida"])
def cmd_team_qoida(message):
    """📖 Jamoaviy o'yin (Team Game) to'liq
qoidalarini yuboradi – guruhda ham, DM'da
ham ishlaydi."""
    try:

```

```

maybe_capture_owner(message.from_user)
    bot.send_message(message.chat.id,
TEAM_GAME_RULES_TEXT)
    except Exception as e:
        _logger.warning("cmd_team_qoida
xatolik: %s", e)

```

```

@bot.message_handler(commands=
["juftlik_qoida", "para_qoida"])
def cmd_para_qoida(message):
    """📖 Para o'yin (Nikohdagi juftliklar)
to'liq qoidalarini yuboradi – guruhda ham,
DM'da ham ishlaydi."""
    try:

```

```

maybe_capture_owner(message.from_user)
    bot.send_message(message.chat.id,
PARAM_GAME_RULES_TEXT)
    except Exception as e:
        _logger.warning("cmd_para_qoida
xatolik: %s", e)

```

```

#
=====
=====
# /NewGame
#
=====
=====

```

```

#
=====
=====
# 🎁 TAQDIR G'ILDIRAGI – /taqdir (barcha
uchun, kuniga 1 marta)
# 💎 ELITE SIRLI SANDIQ – /elite_sandiq
(faqat HUNTER ELITE uchun, kuniga 1 marta)
#
# Bu ikkalasi ham Almex Black Bot'da
UMUMAN YO'Q, original Hunter Mafia
# funksiyalari – botni "hashamatliroq" va
o'ziga xos ko'rsatish uchun.
# 🛠️ TUZATILDI: "VIP" so'zi butunlay olib
tashlandi – botda faqat 🏆 HUNTER
# ELITE bor, boshqa hech qanday "VIP"
nomli narsa yo'q.
#
=====
=====

TAQDIR_PRIZES = [
    # 🛠️ YANGI IQTISODIYOT QOIDASI (owner
so'rovi): botda HECH QANDAY joydan
    # BEPUL 🏆 Coin berilmasin (Coin faqat
sotib olish/almashtirish orqali
    # qo'lga kiritilishi kerak) – shu sabab
"coin" turi bu ro'yxatdan BUTUNLAY
    # olib tashlandi. 💎 Olmos chiqish
ehtimoli ham 5% dan PASTGA tushirildi
    # (avval 12+6=18% edi, endi 3+1=4%).
Bo'shagan og'irlik 📦 pul mukofotlariga
    # taqsimlandi, shunda sandiq baribir
"generous" his qilinadi.
    # (og'irlik, turi, miqdor, matn)

```

```

        (40, "dollar", 15, "💵 Kichik omad"),
        (28, "dollar", 40, "💵 Yaxshi omad"),
        (3, "diamond", 1, "💎 Kichik olmos
siyi"),
        (20, "dollar", 100, "🍀 Katta omad!"),
        (1, "diamond", 3, "💎💎 Katta olmos
siyi!"),
        (6, "dollar", 200, "🎉 Zo'r omad!"),
        (2, "jackpot", 0, "👑 JACKPOT!"),
    ]

```

```

@bot.message_handler(commands=["taqdir",
"fortune", "gildirak", "sandi",
"kunliksandi"])
def cmd_taqdir(message):
    """🎁 KUNLIK SANDIQ (avvalgi nomi:
Taqdir G'ildiragi) – kuniga 1 marta
ochiladigan, animatsiyali bepul sandiq.
7 xil natija bor (jumladan kam
ehtimolli 👑 JACKPOT). Bepul va barcha
foydalanuvchilar uchun ochiq.
🔧 Endi bu yerdan HECH QACHON bepul
Coin chiqmaydi, 💎 Olmos chiqish
ehtimoli esa 5% dan past."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    uid = message.from_user.id
    user_dict(uid,
message.from_user.first_name)
    today = time.strftime("%Y-%m-%d")
    key = f"taqdir_date_{uid}"
    if get_setting(key) == today:
        bot.send_message(message.chat.id,

```

```

"🕒 Siz bugungi Kunlik Sandiqni allaqachon
ochgansiz. Ertaga qayting!")
    return
    set_setting(key, today)

    # 🎉 Animatsiyali "ochilish" effekti –
    bir necha marta xabarni tahrirlab,
    taassurot yaratamiz
    spin_frames = ["🎁🔒➡️🔒", "🎁🔒➡️
🔒", "🎁🔒➡️✨", "🎁✨➡️🎉"]
    sent =
    bot.send_message(message.chat.id, f"🎁
<b>Kunlik Sandiq ochilmoqda...
</b>\n{spin_frames[0]}")
    for frame in spin_frames[1:]:
        time.sleep(0.35)
        try:
            bot.edit_message_text(f"🎁
<b>Kunlik Sandiq ochilmoqda...
</b>\n{frame}", message.chat.id,
sent.message_id)
        except Exception:
            pass
        time.sleep(0.35)

    weights = [w for w, *_ in
TAQDIR_PRIZES]
    _, ptype, amount, label =
random.choices(TAQDIR_PRIZES,
weights=weights, k=1)[0]
    mult = luck_mult(uid)

    if ptype == "jackpot":
        # 🛠️ TUZATILDI: Coin mukofoti olib

```

```

tashlandi (endi faqat 🟩 + 💎)
    j_dollar, j_diamond = int(200 *
mult), 5
    add_balance(uid, dollar=j_dollar,
diamond=j_diamond)
    result_text = (
        f"🔥 <b>JACKPOT!!!</b> 🔥\n"
        f"Naqadar omad! Siz olib
qoldingiz:\n"
        f"🟩 +{j_dollar}$ 💎 +
{j_diamond}"
    )
    else:
        amount = int(amount * mult) if
ptype == "dollar" else amount
        add_balance(uid, **{ptype: amount})
        unit = {"dollar": "$", "diamond":
"💎"}[ptype]
        result_text = f"{label}\n\nSiz
yutdingiz: <b>+{amount}{unit}</b>"

    try:
        bot.edit_message_text(f"🎁
<b>Kunlik Sandiq ochildi!
</b>\n\n{result_text}\n\n⌚ Ertaga yana
urinib ko'ring!", message.chat.id,
sent.message_id)
    except Exception:
        bot.send_message(message.chat.id,
f"🎁 {result_text}")

ELITE_BOX_PRIZES = [
    # 🛠️ TUZATILDI: 🏠 Hunter Coin sovg'asi

```

```

butunlay olib tashlangan (bu sandiqdan
    # Coin chiqmaydi); 💎 Olmos chiqish
ehtimoli endi 4% (5% dan past, owner
    # so'roviga ko'ra) – bo'shagan og'irlik
📦 pul mukofotiga qo'shildi.
    (58, "dollar", 80, "📦 Kumush sovg'a"),
    (4, "diamond", 2, "💎 Olmos sovg'a"),
    (33, "dollar", 250, "🏆 Oltin sovg'a"),
    (5, "jackpot", 0, "👑🌟 AFSONAVIY
SOVG'A"),
]

```

```

@bot.message_handler(commands=
["elite_sandiq", "vip_sandiq", "vipbox"])
def cmd_elite_sandiq(message):
    """💎 ELITE SIRLI SANDIQ – FAQAT HUNTER
ELITE obunachilari uchun, kuniga 1
    marta ochiladigan premium sovg'a
sandig'i. Oddiy /taqdir'dan farqli
    o'laroq, bu yerdagi barcha mukofotlar
SEZILARLI KATTAROQ – ELITE
    obunaning haqiqiy qiymatini his
qildirish uchun mo'ljallangan.
    (Eski /vip_sandiq nomi ham ishlaydi –
orqaga moslik uchun.)"""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    uid = message.from_user.id
    user_dict(uid,
message.from_user.first_name)
    if not is_elite(uid):
        bot.send_message(
            message.chat.id,

```



```

        "🔒 ELITE Sirli Sandiq faqat
<b>HUNTER ELITE</b> obunachilari uchun
ochiq.\n"

        "👑 ELITE olish uchun:
<code>/elite</code>",
    )
    return
    today = time.strftime("%Y-%m-%d")
    key = f"vipbox_date_{uid}"
    if get_setting(key) == today:
        bot.send_message(message.chat.id,
            "⌚ Siz bugungi ELITE sandiqni allaqachon
            ochgansiz. Ertaga qayting!")
        return
    set_setting(key, today)

    sent =
    bot.send_message(message.chat.id, "💎
    <b>ELITE Sirli Sandiq ochilmoqda...</b> 🔒
    ➔🔒")
    time.sleep(0.6)

    weights = [w for w, *_ in
    ELITE_BOX_PRIZES]
    _, ptype, amount, label =
    random.choices(ELITE_BOX_PRIZES,
    weights=weights, k=1)[0]
    mult = luck_mult(uid)

    if ptype == "jackpot":
        # 🛠️ TUZATILDI: Hunter Coin
        sovg'asi olib tashlandi, o'rniga pul biroz
        oshirildi
        j_dollar, j_diamond = int(650 *

```

```

mult), 10
    add_balance(uid, dollar=j_dollar,
diamond=j_diamond)
    result_text = (
        f"👑👑 <b>AFSONAVIY ELITE
SANDIQ!!!</b> 👑👑\n"
        f"💰 +{j_dollar}$ 💎 +
{j_diamond}\n\n"
        f"<i>ELITE bo'lganingiz bejiz
emas!</i>"
    )
    else:
        amount = int(amount * mult) if
ptype == "dollar" else amount
        add_balance(uid, **{ptype: amount})
        unit = {"dollar": "$", "diamond":
"💎", "coin": "🪙"}[ptype]
        result_text = f"{label}\n\nSiz
yutdingiz: <b>+{amount}{unit}</b>"

    try:
        bot.edit_message_text(f"💎
<b>Sandiq ochildi!</b>\n\n{result_text}\n\n
🕒 Ertaga yana urinib ko'ring!",
message.chat.id, sent.message_id)
    except Exception:
        bot.send_message(message.chat.id,
f"💎 {result_text}")

@bot.message_handler(commands=["NewGame",
"newgame"])
def cmd_newgame(message):
    global BOT_USERNAME

```

```

        maybe_capture_owner(message.from_user)
        if BOT_USERNAME is None:
            BOT_USERNAME =
bot.get_me().username

        safe_delete(message)

        if message.chat.type not in ("group",
"supergroup"):
            return
        if not is_authorized(message):
            bot.send_message(message.chat.id,
"🚫 Bu buyruqni faqat guruh admini yoki bot
egasi ishlatishi mumkin.")
            return

        chat_id = message.chat.id
        add_known_group(chat_id,
message.chat.title or "Nomsiz guruh")

        with GAME_LOCK:
            old = GAMES.get(chat_id)
            if old and old.get("join_msg_id"):
                _close_join_message(chat_id,
old["join_msg_id"])

            GAMES[chat_id] = new_game(chat_id,
message.chat.title)
            # 🐱🦊🐼 Owner /teamgame yoki
/parateam orqali shu guruh uchun oldindan
            # yoqib qo'ygan bo'lsa – yangi
o'yin AVTOMATIK shu rejimda boshlanadi.
            GAMES[chat_id]["squad_mode"] =
get_setting(f"squad_mode_{chat_id}") == "1"

```

```

        GAMES[chat_id]["couple_mode"] =
get_setting(f"couple_mode_{chat_id}") ==
"1"

        try:
            GAMES[chat_id]["group_link"] =
bot.export_chat_invite_link(chat_id)
        except Exception:
            pass

        kb = build_join_markup(chat_id,
GAMES[chat_id])
        mode_lines = []
        if GAMES[chat_id]["squad_mode"]:
            mode_lines.append("🐾🦅
<b>Jamoaviy rejim yoqilgan</b> –
qo'shilganda o'z jamoangizni tanlang!")
            if GAMES[chat_id]["couple_mode"]:
                mode_lines.append("💍 <b>Para
rejim yoqilgan</b> – turmush qurganlar
birga bitta tugma bilan qo'shiladi!")
                mode_block = ("\n" +
"\n".join(mode_lines) + "\n") if mode_lines
            else ""

        sent = bot.send_message(
            chat_id,
            "🎮 <b>Yangi Hunter Mafia
o'yini boshlandi!</b>\n"
            f"{mode_block}\n"
            "Qo'shilish uchun pastdagi
tugmani bosib yoki <code>/join</code> deb
yozing!\n\n"
            f"💑 <b>Ishtirokchilar (0 ta):
</b>\nHozircha hech kim yo'q.",
            reply_markup=kb,

```

```

    )
    GAMES[chat_id]["join_msg_id"] =
sent.message_id
    try:
        bot.pin_chat_message(chat_id,
sent.message_id, disable_notification=True)
    except Exception:
        pass

def _close_join_message(chat_id, msg_id):
    """🔧 TUZATISH: eski "🎮 O'yinga
qo'shilish" e'lon xabarini yopadi.
    Avval faqat unpin+delete qilinardi –
    agar botda guruhda xabar o'chirish
    huquqi bo'lmasa (masalan admin huquqi
    olib qo'yilgan bo'lsa), ikkalasi
    ham JIM ravishda muvaffaqiyatsiz
    bo'lib, ESKI TUGMA ABADIY GURUHDA
    QOLIB KETARDI – odamlar keyin ham
    bosaverib "o'yin allaqachon tugagan"
    xatosini olaverishardi. Endi delete
    ishlamasa ham, KAMIDA tugmani
    (reply_markup=None) olib tashlashga
    urinamiz, shunda tugma bosilmay qoladi."""
    if not msg_id:
        return
    try:
        bot.unpin_chat_message(chat_id,
msg_id)
    except Exception:
        pass
    try:
        bot.delete_message(chat_id, msg_id)

```

```

        return # o'chirildi – tugma ham u
        bilan birga yo'qoldi, boshqa hech narsa
        kerak emas
    except Exception:
        pass
    # 🛠️ zaxira reja: o'chirib bo'lmasa
    ham, hech bo'lmasa TUGMANI olib tashlaymiz
    try:

bot.edit_message_reply_markup(chat_id,
msg_id, reply_markup=None)
    except Exception:
        pass
    try:
        bot.edit_message_text("🔒 Bu o'yin
        lobbyysi endi yopiq – yangi o'yin uchun
        /NewGame kuting.", chat_id, msg_id)
    except Exception:
        pass

def build_join_text(game):
    lines = [
        "🎮 <b>Hunter Mafia o'yini</b>\n",
        f"👥 <b>Ishtirokchilar
        ({len(game['players'])} ta):
        </b>\n{player_line_list(game)}\n",
    ]
    if game.get("squad_mode"):
        wolf_n = sum(1 for uid in
        game["players"] if game["squads"].get(uid)
        == "wolf")
        eagle_n = sum(1 for uid in
        game["players"] if game["squads"].get(uid)

```

```

== "eagle")
    # 🤔 Kim qaysi jamoada ekani MAXFIY
    qoladi – o'yin oxirigacha guruhda
    # faqat SONI ko'rsatiladi, ismlar
    emas (asosiy Hunter Mafia'dagi kabi
    # rollar ham maxfiy bo'lgani kabi).
    YANGI: endi har bir jamoa uchun
    # ALOHIDA-ALOHIDA son ham
    ko'rsatiladi (masalan "Burgutlar – 2 ta").
    lines.append(
        f"🐺🦅 <b>Jamoalar tanlandi:
    </b> {wolf_n + eagle_n} kishi "
        f"({squad_counts_line(game)}) –
    kim qaysi jamoada – o'yin OXIRIGACHA
    maxfiy!\n"
    )
    if game.get("couple_mode"):
        lines.append("💍 <i>Juftliklar
    ro'yxatga olindi – kim kim bilan juft ekani
    o'yin oxirigacha (yoki biri halok
    bo'lguncha) MAXFIY qoladi.</i>\n")
        lines.append("💡 <i>🧑🏻🧑🏻 rol tanlash
    huquqingiz bo'lsa /rolni_tanla &lt;rol>
    deb yozing!</i>")
        return "\n".join(lines)

def build_join_markup(chat_id, game=None):
    kb = types.InlineKeyboardMarkup()
    # 🔧 Jamoaviy (squad) yoki Para
    (couple) rejimda oddiy "yakka" qo'shilish
    # tugmasi endi umuman ko'RSATILMAYDI –
    bu rejimlarda HAR BIR ishtirokchi
    # albatta jamoasini yoki juftligini

```

```

tanlab qo'shilishi SHART (aks holda
    # "oxirgi juftlik/jamoa g'olib" qoidasi
ishonchli ishlaymay qolardi).
    show_plain_join = not (game and
(game.get("squad_mode") or
game.get("couple_mode")))
    if show_plain_join:
        if BOT_USERNAME:
            # 🧑 endi guruhdagi tugma
bosilganda foydalanuvchi avtomatik botning
shaxsiy
            # chatiga o'tkaziladi va o'sha
yerda o'yinga qo'shiladi (do'stona,
tushunarli UX)

kb.add(types.InlineKeyboardButton("🎮
O'yinga qo'shilish",
url=f"https://t.me/{BOT_USERNAME}?
start=join_{chat_id}")
        else:

kb.add(types.InlineKeyboardButton("🎮
O'yinga qo'shilish", callback_data=f"join|
{chat_id}"))
        if game and game.get("squad_mode"):
            kb.add(
                types.InlineKeyboardButton("🐺
Bo'ri jamoasi", callback_data=f"squadjoin|
{chat_id}|wolf"),
                types.InlineKeyboardButton("🦅
Burgut jamoasi", callback_data=f"squadjoin|
{chat_id}|eagle"),
            )
        if game and game.get("couple_mode"):

```



```

kb.add(types.InlineKeyboardButton("👤 Men
va turmush o'rtog'imni qo'shish",
callback_data=f"couplejoin|{chat_id}"))
    return kb

#
=====
=====
# /PovtorGame
#
=====
=====

@bot.message_handler(commands=
["PovtorGame", "povtorgame"])
def cmd_povtorgame(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)

    if message.chat.type not in ("group",
"supergroup"):
        return

    if not is_authorized(message):
        bot.send_message(message.chat.id,
"🚫 Bu buyruqni faqat guruh admini yoki bot
egasi ishlatishi mumkin.")
        return

    chat_id = message.chat.id
    game = GAMES.get(chat_id)
    if not game or game["phase"] !=
"waiting":

```

```

        return

        if game.get("join_msg_id"):
            _close_join_message(chat_id,
                                game["join_msg_id"])

        sent = bot.send_message(chat_id,
                                build_join_text(game),
                                reply_markup=build_join_markup(chat_id,
                                                                game))
        game["join_msg_id"] = sent.message_id
        try:
            bot.pin_chat_message(chat_id,
                                sent.message_id, disable_notification=True)
        except Exception:
            pass

#
=====
# /join
#
=====

@bot.message_handler(commands=["join"])
def cmd_join(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if message.chat.type not in ("group",
                                "supergroup"):
        return
    status = do_join(message.chat.id,

```

```

message.from_user)
    if status == "need_squad":
        bot.send_message(message.chat.id,
            "🐾🦅 Bu – Jamoaviy o'yin! Iltimos,
            guruhdagi 🐾 Bo'ri yoki 🦅 Burgut
            tugmasidan birini bosib qo'shiling.")
    elif status == "need_couple":
        bot.send_message(message.chat.id,
            "💍 Bu – Para o'yin! Faqat 💍 Men va
            turmush o'rtog'imni qo'shish tugmasi orqali
            qo'shilish mumkin.")

@bot.message_handler(commands=["teamgame"])
def cmd_teamgame(message):
    """🐾🦅 FAQAT BOT EGASI – ushbu guruh
    uchun 'Jamoaviy o'yin' rejimini
    yoqadi/o'chiradi. Yoqilgan bo'lsa,
    KEYINGI /newgame'da ishtirokchilar
    qo'shilish payti 🐾 Bo'ri yoki 🦅
    Burgut jamosini MAJBURIY tanlashlari
    kerak bo'ladi (jamoat tanlovi o'yin
    oxirigacha guruhda MAXFIY qoladi).
    G'alaba sharti: dushman jamoaning
    BARCHA a'zosi halok bo'lguncha o'yin
    davom etadi – g'olib shu jamoa
    hisoblanadi (oddiy Mafiya/Tinch aholi
    balansi bu rejimda ENDI g'alabani
    belgilamaydi)."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if message.chat.type not in ("group",
    "supergroup"):
        bot.send_message(message.chat.id,

```

```

" Bu buyruq faqat guruhda ishlaydi.")
    return
    if not is_owner(message.from_user.id):
        bot.send_message(message.chat.id,
" Bu sozlamani FAQAT bot egasi o'zgartira
oladi.")
    return
    chat_id = message.chat.id
    current =
get_setting(f"squad_mode_{chat_id}") == "1"
    new_val = not current
    set_setting(f"squad_mode_{chat_id}",
"1" if new_val else "0")
    bot.send_message(
        message.chat.id,
        f" Jamoaviy o'yin rejimi: {'
YOQILDI' if new_val else '
O\CHIRILDI'}\n"
        "Bu sozlama keyingi
<code>/newgame</code>'dan boshlab kuchga
kiradi.",
    )

```

```

@bot.message_handler(commands=["parateam"])
def cmd_parateam(message):
    """ FAQAT BOT EGASI – ushbu guruh
uchun 'Para (juftlik) o'yin' rejimini
yoqadi/o'chiradi. Yoqilgan bo'lsa,
turmush qurgan (/nikoh) foydalanuvchilar
KEYINGI /newgame'da bitta tugma bilan
ikkalasi birga qo'shila oladi."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)

```

```

        if message.chat.type not in ("group",
"supergroup"):
            bot.send_message(message.chat.id,
"🔒 Bu buyruq faqat guruhda ishlaydi.")
            return
        if not is_owner(message.from_user.id):
            bot.send_message(message.chat.id,
"🚫 Bu sozlamani FAQAT bot egasi o'zgartira
oladi.")
            return
        chat_id = message.chat.id
        current =
get_setting(f"couple_mode_{chat_id}") ==
"1"
        new_val = not current
        set_setting(f"couple_mode_{chat_id}",
"1" if new_val else "0")
        bot.send_message(
            message.chat.id,
            f"🔒 Para o'yin rejimi: {'✅'
YOQILDI' if new_val else '❌'
O\ 'CHIRILDI'}\n"
            "Bu sozlama keyingi
<code>/newgame</code>'dan boshlab kuchga
kiradi.",
        )

@bot.message_handler(commands=["setting",
"mode"])
def cmd_setting_mode(message):
    """⚙️ FAQAT BOT EGASI – joriy guruh
uchun barcha maxsus o'yin rejimlarini
(Jamoaviy 🐾🦅, Para 🔒) bitta panelda

```

ko'radi va tugma orqali yoqib/o'chira oladi.

Bu buyruq (/setting va /mode) shaxsiy chatda ham, guruhda ham ishlaydi,

lekin FAQAT bot egasiga ko'rinadi – boshqa hech kim ishlata olmaydi."""

```
maybe_capture_owner(message.from_user)
safe_delete(message)
```

```
if not is_owner(message.from_user.id):
    return # 🚫 boshqa hech kimga bu
buyruq mavjudligi haqida hatto izoh ham
berilmaydi
```

```
if message.chat.type in ("group",
"supergroup"):
```

```
    chat_id = message.chat.id
    title = message.chat.title or "bu
```

guruh"

```
    else:
```

```
        bot.send_message(
            message.chat.id,
```

```
            "⚙️ <code>/setting</code> ni
istalgan guruhda yozing – o'sha guruh uchun
sozlamalar paneli ochiladi.",
```

```
        )
        return
```

```
squad_on =
get_setting(f"squad_mode_{chat_id}") == "1"
couple_on =
get_setting(f"couple_mode_{chat_id}") ==
"1"
```

```
kb = types.InlineKeyboardMarkup()
kb.add(types.InlineKeyboardButton(
```

```

        f"🐾🦅 Jamoaviy o'yin: {'✅ Yoqilgan' if squad_on else '❌ O\'chirilgan'}",
        callback_data=f"ownersetting|squad|{chat_id}",
    ))
    kb.add(types.InlineKeyboardButton(
        f"⚙️ Para o'yin: {'✅ Yoqilgan' if couple_on else '❌ O\'chirilgan'}",
        callback_data=f"ownersetting|couple|{chat_id}",
    ))
    bot.send_message(
        message.chat.id,
        f"⚙️ <b>{title}</b> uchun o'yin sozlamalari</b>\n\n"
        "Rejimlarni yoqish/o'chirish uchun pastdagi tugmalarni bosing. "
        "O'zgarish KEYINGI <code>/newgame</code>'dan boshlab kuchga kiradi.",
        reply_markup=kb,
    )

@bot.callback_query_handler(func=lambda c: c.data.startswith("ownersetting|"))
def cb_owner_setting_toggle(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
        "🚫 Faqat bot egasi uchun.",
        show_alert=True)

```

```

        return
        _, which, chat_id_s =
call.data.split("|")
        chat_id = int(chat_id_s)
        key = f"squad_mode_{chat_id}" if which
== "squad" else f"couple_mode_{chat_id}"
        new_val = not (get_setting(key) == "1")
        set_setting(key, "1" if new_val else
"0")

        squad_on =
get_setting(f"squad_mode_{chat_id}") == "1"
        couple_on =
get_setting(f"couple_mode_{chat_id}") ==
"1"

        kb = types.InlineKeyboardMarkup()
        kb.add(types.InlineKeyboardButton(
            f"🐱🐶 Jamoaviy o'yin: {'✅'
Yoqilgan' if squad_on else '❌'
O\chirilgan'}",
            callback_data=f"ownersetting|squad|
{chat_id}",
        ))
        kb.add(types.InlineKeyboardButton(
            f"💍 Para o'yin: {'✅' Yoqilgan' if
couple_on else '❌' O\chirilgan'}",

callback_data=f"ownersetting|couple|
{chat_id}",
        ))
        try:

bot.edit_message_reply_markup(call.message.
chat.id, call.message.message_id,

```



```

reply_markup=kb)
    except Exception:
        pass
    bot.answer_callback_query(call.id, "✅
Yangilandi!")

def do_join(chat_id, tg_user, squad=None,
via_couple=False):
    """O'yinga qo'shilishga urinadi va
    holatni qaytaradi:
        'ok' – muvaffaqiyatli qo'shildi,
        'already' – allaqachon qo'shilgan,
        'banned' – bloklangan, 'no_game' –
    hozir qo'shilsa bo'ladigan o'yin yo'q,
        'need_squad' – 🐾🦅 Jamoaviy rejimda
    oddiy tugma orqali qo'shilishga urinildi
        (aniq 🐾🦅 tanlash SHART),
        'need_couple' – 🔄 Para rejimida oddiy
    tugma
        orqali qo'shilishga urinildi (FAQAT 🔄
    tugmasi orqali, juftlik bilan
        qo'shilish SHART – bu rejimda yakka
    o'yinchi bo'lishi mumkin emas, aks
        holda 'juftlik oxirigacha qolsa g'olib'
    qoidasi buzilib qoladi).
        squad – agar berilsa ('wolf' yoki
    'eagle'), 🐾🦅 jamoaviy rejimda o'yinchi
    shu jamoaga yoziladi (faqat
    game['squad_mode'] yoqilgan bo'lsa)."""
    game = GAMES.get(chat_id)
    if not game or game["phase"] !=
    "waiting":
        return "no_game"

```

```

        if game.get("squad_mode") and squad not
in ("wolf", "eagle"):
            return "need_squad"
        if game.get("couple_mode") and not
via_couple:
            return "need_couple"
        uid = tg_user.id
        name = tg_user.first_name or "O'yinchi"
        user_dict(uid, name)
        if is_banned(uid):
            return "banned"
        already = uid in game["players"]
        if not already:
            game["players"][uid] = {"name":
name, "role": None, "alive": True, "team":
None}
            if squad in ("wolf", "eagle") and
game.get("squad_mode"):
                game["squads"][uid] = squad
            if game.get("join_msg_id"):
                try:

bot.edit_message_text(build_join_text(game)
, chat_id, game["join_msg_id"],
reply_markup=build_join_markup(chat_id,
game))

            except Exception:
                pass
        return "already" if already else "ok"

@bot.callback_query_handler(func=lambda c:
c.data.startswith("join|"))
def cb_join(call):

```

```

        maybe_capture_owner(call.from_user)
        _, chat_id_s = call.data.split("|")
        chat_id = int(chat_id_s)
        status = do_join(chat_id,
call.from_user)
        if status == "need_squad":
            bot.answer_callback_query(call.id,
"🐱🦅 Bu – Jamoaviy o'yin! 🐱 Bo'ri yoki 🦅
Burgut tugmasidan birini bosing.",
show_alert=True)
            elif status == "need_couple":
                bot.answer_callback_query(call.id,
"💍 Bu – Para o'yin! Faqat 💍 tugmasi
orqali (turmush o'rtog'ingiz bilan)
qo'shilishingiz mumkin.", show_alert=True)
            else:
                bot.answer_callback_query(call.id,
f"{call.from_user.first_name} o'yinga
qo'shildi!")

@bot.callback_query_handler(func=lambda c:
c.data.startswith("squadjoin|"))
def cb_squad_join(call):
    """🐱🦅 Jamoaviy o'yin rejimida –
o'yinchi bir tugma bosishi bilan HAM
o'yinga
qo'shiladi, HAM o'zi xohlagan jamoaga
(Bo'ri yoki Burgut) yoziladi."""
    maybe_capture_owner(call.from_user)
    _, chat_id_s, squad =
call.data.split("|")
    chat_id = int(chat_id_s)
    status = do_join(chat_id,

```

```

call.from_user, squad=squad)
    squad_label = "🐾 Bo'ri jamoasi" if
squad == "wolf" else "🦅 Burgut jamoasi"
    if status == "banned":
        bot.answer_callback_query(call.id,
"🚫 Siz bloklangansiz.", show_alert=True)
    elif status == "no_game":
        bot.answer_callback_query(call.id,
"❌ Hozir qo'shilsa bo'ladigan o'yin
yo'q.", show_alert=True)
    else:
        bot.answer_callback_query(call.id,
f"✅ {squad_label}ga qo'shildingiz!")

```

```

@bot.callback_query_handler(func=lambda c:
c.data.startswith("couplejoin|"))
def cb_couple_join(call):
    """🔗 Para o'yin rejimida – turmush
qurgan foydalanuvchi BITTA tugma bosib,
o'zini VA turmush o'rtog'ini birgalikda
o'yinga qo'shadi. Turmush QURMAGAN
foydalanuvchi bu rejimga umuman
qo'shila OLMAYDI (FAQAT rasmiy nikohdagi
juftliklar – aks holda 'oxirgi juftlik
g'olib' qoidasi ishonchli
ishlamay qolardi)."""
    maybe_capture_owner(call.from_user)
    _, chat_id_s = call.data.split("|")
    chat_id = int(chat_id_s)
    game = GAMES.get(chat_id)
    if not game or game["phase"] !=
"waiting":
        bot.answer_callback_query(call.id,

```

```

"❌ Hozir qo'shilsa bo'ladigan o'yin
yo'q.", show_alert=True)
    return

    uid = call.from_user.id
    if is_banned(uid):
        bot.answer_callback_query(call.id,
"❌ Siz bloklangansiz.", show_alert=True)
        return

    # 🛠️ XATOLIK TUZATILDI: avval turmush
qurmagan foydalanuvchi ham shu
    # tugma orqali "yakka" qo'shilib
ketaverar edi – bu Para rejimida
    # juftliksiz o'yinchi paydo bo'lishiga
(va g'alaba qoidasi buzilishiga)
    # sabab bo'lardi. Endi nikohsiz odam bu
rejimga umuman qo'shilolmaydi.
    u = user_dict(uid,
call.from_user.first_name)
    spouse_id = u.get("married_to")
    if not spouse_id:
        bot.answer_callback_query(call.id,
"❌ Bu – Para o'yin, FAQAT rasmiy nikohdagi
juftliklar qo'shila oladi. Avval /nikoh
orqali oila quring.", show_alert=True)
        return

    status = do_join(chat_id,
call.from_user, via_couple=True)
    if status == "banned":
        bot.answer_callback_query(call.id,
"❌ Siz bloklangansiz.", show_alert=True)
        return

```

```

        if spouse_id in game["players"]:
            bot.answer_callback_query(call.id,
                "✅ Siz qo'shildingiz – turmush
                o'rtog'ingiz allaqachon o'yinda ekan!")
            return

        # 💍 Turmush o'rtog'ini ham shaxsiy
        chatida bot bilan gaplashgan bo'lsa
        avtomatik qo'shamiz
        su = user_dict(spouse_id)
        spouse_name = su.get("name") or
        "Sherigingiz"

        class _FakeUser:
            pass

        fake = _FakeUser()
        fake.id = spouse_id
        fake.first_name = spouse_name
        join_status = do_join(chat_id, fake,
            via_couple=True)
        if join_status in ("ok", "already"):
            bot.answer_callback_query(call.id,
                f"💍 Siz va {spouse_name} birgalikda
                o'yinga qo'shildingiz!")
            safe_send(spouse_id, f"💍 Turmush
                o'rtog'ingiz sizni <b>{game['chat_title']}
                </b> guruhidagi Hunter Mafia o'yiniga birga
                qo'shdi!")
        else:
            bot.answer_callback_query(call.id,
                "✅ Siz qo'shildingiz. (Turmush
                o'rtog'ingizni avtomatik qo'shib

```

```

bo'lmadi.)")

#
=====
=====
# 📋 GURUHGA A'ZOLIK SO'ROVLARI
(ZAYAVKALAR) – avtomatik qabul qilish
# Eslatma: bu faqat guruh havolasi
"Administrator tasdig'i talab qilinsin"
# (request to join) rejimida yaratilgan
bo'lsa ishlaydi – aks holda odamlar
# havola orqali to'g'ridan-to'g'ri kirib
ketaveradi va navbat hosil bo'lmaydi.
#
=====
=====

@bot.chat_join_request_handler()
def handle_chat_join_request(update):
    """Guruhga kirish uchun yangi so'rov
    kelganda navbatga qo'shib boradi."""
    chat_id = update.chat.id
    user = update.from_user
    with JOIN_REQ_LOCK:
        lst =
PENDING_JOIN_REQUESTS.setdefault(chat_id,
[])
        if not any(r["user_id"] == user.id
for r in lst):
            lst.append({
                "user_id": user.id,
                "name": user.first_name or
"Foydalanuvchi",

```

```

        "username": user.username,
        "ts": time.time(),
    })

    try:
        add_known_group(chat_id,
update.chat.title or "Nomsiz guruh")
    except Exception:
        pass

@bot.message_handler(commands=
["zayafka_soni"])
def cmd_zayafka_soni(message):
    """Guruhda hozir nechta a'zolik so'rovi
kutib turganini ko'rsatadi."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if message.chat.type not in ("group",
"supergroup"):
        return
    if not is_authorized(message):
        bot.send_message(message.chat.id,
"🚫 Bu buyruqni faqat guruh admini yoki bot
egasi ishlatishi mumkin.")
        return
    chat_id = message.chat.id
    with JOIN_REQ_LOCK:
        count =
len(PENDING_JOIN_REQUESTS.get(chat_id, []))
    if count == 0:
        bot.send_message(
            chat_id,
            "👤 Hozircha kutilayotgan
a'zolik so'rovi yo'q.\n\n"

```



```

        "💡 <i>Eslatma: bu faqat guruh
havolasi \"Administrator tasdig'i talab
qilinsin\" "
        "rejimida bo'lsa ishlaydi.</i>"
    )
    return
    bot.send_message(
        chat_id,
        f"📋 Hozirda kutilayotgan a'zolik
so'rovlari: <b>{count} ta</b>\n\n"
        f"✅ Qabul qilish:
<code>/zayafka_qabul {min(count, 150)}
</code>\n"
        f"✅ Barchasini qabul qilish:
<code>/zayafka_hammasi</code>"
    )

@bot.message_handler(commands=
["zayafka_qabul"])
def cmd_zayafka_qabul(message):
    """/zayafka_qabul <soni> – navbatdagi
eng birinchi so'rovlardan shuncha
donasini avtomatik qabul qiladi,
qolganini navbatda saqlab qoladi."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if message.chat.type not in ("group",
"supergroup"):
        return
    if not is_authorized(message):
        bot.send_message(message.chat.id,
        "🚫 Bu buyruqni faqat guruh admini yoki bot
egasi ishlatishi mumkin.")

```

```

        return

        chat_id = message.chat.id
        parts = (message.text or "").split()
        if len(parts) < 2 or not
parts[1].isdigit() or int(parts[1]) <= 0:
            bot.send_message(chat_id, " !
To'g'ri format: <code>/zayafka_qabul
150</code>\n(qabul qilinadigan odamlar
soni)")
            return
        soni = int(parts[1])

        with JOIN_REQ_LOCK:
            queue =
PENDING_JOIN_REQUESTS.get(chat_id, [])
            if not queue:
                bot.send_message(
                    chat_id,
                    "👤 Hozircha kutilayotgan
a'zolik so'rovi yo'q.\n\n"
                    "💡 <i>Eslatma: bu faqat
guruh havolasi \"Administrator tasdig'i
talab qilinsin\" "
                    "rejimida bo'lsa ishlaydi.
</i>"
                )
            return
        to_accept = queue[:soni]
        remaining = queue[soni:]
        PENDING_JOIN_REQUESTS[chat_id] =
remaining

        status_msg = bot.send_message(

```

```

        chat_id,
        f"⌚ {len(to_accept)} ta a'zolik
so'rovi qabul qilinmoqda, biroz
kuting...\n"
        f"📋 Navbatda yana:
{len(remaining)} ta"
    )

def _worker():
    accepted = 0
    failed = 0
    for req in to_accept:
        try:

bot.approve_chat_join_request(chat_id,
req["user_id"])

            accepted += 1
        except Exception:
            failed += 1
            time.sleep(0.05) # Telegram
limitiga tushib qolmaslik uchun kichik
pauza
        try:
            result_text = (
                f"✅ Qabul qilish
yakunlandi!\n\n"
                f"💙 Qabul qilindi: <b>
{accepted} ta</b>\n"
            )
            if failed:
                result_text += f"⚠️ Xatolik
yuz berdi: {failed} ta\n"
                result_text += f"📋 Navbatda
qoldi: <b>{len(remaining)} ta</b>"

```

```

bot.edit_message_text(result_text, chat_id,
status_msg.message_id)
    except Exception:
        pass

    threading.Thread(target=_worker,
daemon=True).start()

@bot.message_handler(commands=
["zayafka_hammasi"])
def cmd_zayafka_hammasi(message):
    """Navbatdagi BARCHA a'zolik
so'rovlarini qabul qiladi."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if message.chat.type not in ("group",
"supergroup"):
        return
    if not is_authorized(message):
        bot.send_message(message.chat.id,
"🚫 Bu buyruqni faqat guruh admini yoki bot
egasi ishlatishi mumkin.")
        return

    chat_id = message.chat.id
    with JOIN_REQ_LOCK:
        queue =
PENDING_JOIN_REQUESTS.get(chat_id, [])
        PENDING_JOIN_REQUESTS[chat_id] = []

    if not queue:
        bot.send_message(chat_id, "👤")

```

```

Hozircha kutilayotgan a'zolik so'rovi
yo'q.")
    return

    status_msg = bot.send_message(chat_id,
f"⌚ Barcha {len(queue)} ta so'rov qabul
qilinmoqda, biroz kuting...")

def _worker():
    accepted = 0
    failed = 0
    for req in queue:
        try:

bot.approve_chat_join_request(chat_id,
req["user_id"])
            accepted += 1
        except Exception:
            failed += 1
            time.sleep(0.05)
        try:
            result_text = f"✅ Barcha
so'rovlar yakunlandi!\n\n👤 Qabul qilindi:
<b>{accepted} ta</b>"
            if failed:
                result_text += f"\n⚠️
Xatolik yuz berdi: {failed} ta"

bot.edit_message_text(result_text, chat_id,
status_msg.message_id)
        except Exception:
            pass

threading.Thread(target=_worker,

```

```

daemon=True).start()

@bot.message_handler(commands=
["zayafka_rad"])
def cmd_zayafka_rad(message):
    """/zayafka_rad <soni> – navbatdagi eng
    birinchi so'rovlardan shuncha
    donasini rad etadi (masalan,
    shubhali/bot akkountlarni tozalash
    uchun)."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if message.chat.type not in ("group",
    "supergroup"):
        return
    if not is_authorized(message):
        bot.send_message(message.chat.id,
        "🚫 Bu buyruqni faqat guruh admini yoki bot
        egasi ishlatishi mumkin.")
        return

    chat_id = message.chat.id
    parts = (message.text or "").split()
    if len(parts) < 2 or not
    parts[1].isdigit() or int(parts[1]) <= 0:
        bot.send_message(chat_id, "❗
        To'g'ri format: <code>/zayafka_rad
        50</code>\n(rad etiladigan odamlar soni)")
        return
    soni = int(parts[1])

    with JOIN_REQ_LOCK:
        queue =

```

```

PENDING_JOIN_REQUESTS.get(chat_id, [])
    if not queue:
        bot.send_message(chat_id, "🚫
Hozircha kutilayotgan a'zolik so'rovi
yo'q.")
        return
    to_decline = queue[:soni]
    remaining = queue[soni:]
    PENDING_JOIN_REQUESTS[chat_id] =
remaining

    declined = 0
    for req in to_decline:
        try:

bot.decline_chat_join_request(chat_id,
req["user_id"])
            declined += 1
        except Exception:
            pass
        time.sleep(0.05)

    bot.send_message(
        chat_id,
        f"🚫 Rad etildi: <b>{declined}</b>
ta</b>\n📋 Navbatda qoldi: <b>
{len(remaining)} ta</b>"
    )

#
=====
=====
# /rolni_tanla - 🎮 "Barcha rollarni

```

```

tanlash huquqi" buyumidan foydalanish
#
=====
=====

@bot.message_handler(commands=
["rolni_tanla"])
def cmd_rolni_tanla(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if message.chat.type not in ("group",
"supergroup"):
        return
    chat_id = message.chat.id
    game = GAMES.get(chat_id)
    if not game or game["phase"] !=
"waiting":
        bot.send_message(chat_id, "❌ Rol
tanlash faqat o'yin boshlanmasdan oldin,
qo'shilish bosqichida mumkin.")
        return
    uid = message.from_user.id
    if uid not in game["players"]:
        bot.send_message(chat_id, "❌ Avval
/join orqali o'yinga qo'shiling.")
        return
    ch = get_charges(uid)
    if ch.get("role_choice", 0) <= 0:
        bot.send_message(chat_id, "❌ Bu
huquqni do'kondan (🎮 Barcha rollarni
tanlash huquqi – Hunter Coin do'koni) sotib
olishingiz kerak.")
        return
    parts = message.text.split(maxsplit=1)

```



```

        if len(parts) < 2 or parts[1].strip()
not in ALL_ROLES:
            bot.send_message(chat_id,
"Foydalanish: <code>/rolni_tanla Don 🎩
</code>\n\n👉 Rollar ro'yxatini asosiy
menyudan ko'rishingiz mumkin.")
            return
        chosen = parts[1].strip()
        game["forced_roles"][uid] = chosen
        use_charge(uid, "role_choice")
        bot.send_message(chat_id, f"✅
{message.from_user.first_name} keyingi
o'yinda <b>{chosen}</b> rolini oladi!")

#
=====
=====
# /StartGame
#
=====
=====

@bot.message_handler(commands=["StartGame",
"startgame"])
def cmd_startgame(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)

    if message.chat.type not in ("group",
"supergroup"):
        return
    if not is_authorized(message):
        bot.send_message(message.chat.id,

```

```
"🚫 Bu buyruqni faqat guruh admini yoki bot egasi ishlatishi mumkin.")
```

```
    return
```

```
    chat_id = message.chat.id
```

```
    game = GAMES.get(chat_id)
```

```
    if not game or game["phase"] !=
```

```
"waiting":
```

```
        bot.send_message(chat_id, "❌ Avval /NewGame bilan o'yin oching.")
```

```
        return
```

```
    if len(game["players"]) < MIN_PLAYERS:
```

```
        bot.send_message(chat_id, f"❌
```

```
Kamida {MIN_PLAYERS} ta ishtirokchi kerak.")
```

```
        return
```

```
    if game.get("join_msg_id"):
```

```
        _close_join_message(chat_id, game["join_msg_id"])
```

```
        game["join_msg_id"] = None
```

```
    assign_roles(game)
```

```
    game["day_number"] = 1
```

```
    # 💍 Para (couple) rejimi: o'yindagi turmush qurgan a'zolari bir-biriga
```

```
    # MAXFIY sherik sifatida bog'laymiz (guruhga hech qachon ochiq aytilmaydi –
```

```
    # faqat ular DM'da o'zlari biladi, biri halok bo'lguncha).
```

```
    if game.get("couple_mode"):
```

```
        game["couple_of"] = {}
```

```
        game["revealed_couples"] = set()
```

```

        linked = set()
        for uid in
list(game["players"].keys()):
            if uid in linked:
                continue
            partner_id =
get_partner_id(uid)
            if partner_id and partner_id in
game["players"] and partner_id not in
linked:
                game["couple_of"][uid] =
partner_id
                game["couple_of"]
[partner_id] = uid
                linked.add(uid)
                linked.add(partner_id)

        group_link = game.get("group_link")
        for uid, p in game["players"].items():
            role = p["role"]
            desc = ROLES_INFO.get(role, "")
            kb = None
            if group_link:
                kb =
types.InlineKeyboardMarkup()

            kb.add(types.InlineKeyboardButton("👉
Guruhga o'tish", url=group_link))
            safe_send(uid, f"
{role_portrait(role)}\nRolingiz: <b>{role}
</b>\n{desc}", kb)

            if team_of(role) == "mafia":
                teammates = [(u2, pp["name"])

```

```

for u2, pp in game["players"].items() if u2
!= uid and team_of(pp["role"]) == "mafia"]
    if teammates:
        safe_send(uid, "👁️
Sheriklaringiz: " + ", ".join(mention(u2,
n2) for u2, n2 in teammates) + "\n🗨️ Ular
bilan yashirin gaplashish uchun:
<code>/jamoaxabar matni</code>")
    else:
        safe_send(uid, "👁️ Mafiyada
yolg'izsiz – ehtiyot bo'ling!")

# 🚔🚔 Komissar va Serjant – "Qonun
jamoasi": bir-birini bilishadi va
# o'yin davomida bot orqali
yashirin gaplasha oladi (Serjant, Komissar
# halok bo'lgach uning vazifasini
davom ettiradi).
    if role in ("Komissar 🚔", "Serjant
🚔"):
        law_mates = [(u2, pp["name"])
for u2, pp in game["players"].items()
                    if u2 != uid and
pp["role"] in ("Komissar 🚔", "Serjant
🚔")]
        if law_mates:
            safe_send(uid, "🚔🚔 Qonun
jamoasidagi sherigingiz: " + ",
".join(mention(u2, n2) for u2, n2 in
law_mates)
                                + "\n🗨️ U bilan
yashirin gaplashish uchun: <code>/adolat
xabar matni</code>")

```

```

# 🐾🦅 Jamoaviy (squad) rejimi: kim
qaysi jamoada ekani guruhga hech
# qachon oshkor qilinmaydi (o'yin
oxirigacha maxfiy) – shu sababli har
# bir o'yinchiga O'Z JAMOASINING
to'liq ro'yxati shaxsiy xabarda (DM)
# yuboriladi, aks holda ular o'z
sheriklarini bilmay qolar edi.
if game.get("squad_mode") and
game.get("squads"):
    my_squad =
game["squads"].get(uid)
    if my_squad:
        squad_mates = [(u2,
pp["name"]) for u2, pp in
game["players"].items()
                        if u2 != uid
and game["squads"].get(u2) == my_squad]
        squad_label = "🐾 Bo'ri" if
my_squad == "wolf" else "🦅 Burgut"
        if squad_mates:
            safe_send(uid, f"
{squad_label} jamoangizdagi sheriklaringiz:
" + ", ".join(mention(u2, n2) for u2, n2 in
squad_mates)
                        + "\n⚠ Bu
guruhda hech qachon oshkor qilinmaydi –
faqat siz bilasiz!")
        else:
            safe_send(uid, f"
{squad_label} jamoasida yolg'izsiz.")

# 🧑 Maxfiy missiya – har bir
o'yinchiga tasodifiy shaxsiy topshiriq

```

```

beriladi,
    # faqat o'ziga ko'rinadi. O'yin
    oxirida bajarilgan-bajarilmagani
    tekshiriladi.
    mission =
    random.choice(SECRET_MISSIONS)
    game["secret_missions"][uid] =
    mission["key"]
    safe_send(uid, f"🕵️ Maxfiy missiya:
    <i>{mission['text']}</i>\n(O'yin oxirida
    bajarilgan-bajarilmaganingiz tekshiriladi –
    bajarsangiz +25$.)")

    # 💍 Para rejimida – sherigingiz
    kimligini FAQAT o'zingiz, shaxsiy xabarda
    # bilasiz. Guruhda bu hech qachon
    ochiq aytilmaydi (biri halok bo'lmaguncha).
    partner_id = game.get("couple_of",
    {}).get(uid)
    if partner_id:
        partner_name =
        game["players"].get(partner_id,
        {}).get("name", "Sherigingiz")
        safe_send(
            uid,
            f"💍 <b>Maxfiy juftlik!</b>
            Bu o'yinda sherigingiz: <b>{partner_name}
            </b>.\n"
            f"⚠️ Buni guruhda hech
            kimga aytmang – agar sizlardan biri halok
            bo'lsa, "
            f"ikkalangiz ham DARHOL
            o'yindan chiqasiz va shundagina guruhga
            fosh bo'lasiz!",

```

```

    )

    bot.send_message(chat_id, f"🌙 <b>O'yin  

boshlandi!</b> {len(game['players'])}  

kishiga rol berildi. Roldan DM'da qarang.")
    start_night(chat_id)

def _assign_no_repeat(uids, pool):
    """`uids` ro'yxatidagi har bir  

o'yinchiga `pool` dagi rollarni, iloji  

boricha
    o'sha o'yinchining OXIRGI o'ynagan roli  

bilan bir xil bo'lmaydigan qilib
    taqsimlaydi (bir xil rol ketma-ket 2  

marta bir kishiga tushmasin degan talab).
    Agar imkoni bo'lmasa (masalan, kichik  

o'yin, muqobil yo'q) – eng kam
    to'qnashuvli variant qaytariladi."""
    best = None
    for _ in range(40):
        shuffled = pool[:]
        random.shuffle(shuffled)
        conflicts = sum(
            1 for uid, role in zip(uids,
shuffled)
            if
get_charges(uid).get("last_role") == role
        )
        if conflicts == 0:
            return list(zip(uids,
shuffled))
        if best is None or conflicts <
best[0]:

```

```

        best = (conflicts,
list(zip(uids, shuffled)))
        return best[1] if best else
list(zip(uids, pool))

def assign_roles(game):
    player_ids =
list(game["players"].keys())
    n = len(player_ids)
    if n == 0:
        return

    forced = game.get("forced_roles", {})

    pool = []
    if n >= 1:
        pool.append("Don 🎩")
    if n >= 2:
        pool.append("Komissar 🕵️")
    if n >= 3:
        pool.append("Doktor 🩺")

    if n <= CORE_ROLE_THRESHOLD:
        while len(pool) < n:
            pool.append("Tinch aholi 🧑🏻")
    else:
        mafia_extra = mafia_count_for(n) -
1
        for _ in range(max(0,
mafia_extra)):
            pool.append("Mafia 🖤")
        remaining = n - len(pool)
        extra_source = [r for r in

```



```

ALL_ROLES if r not in CORE_ROLES and r !=
"Mafia 🖤"]
    random.shuffle(extra_source)
    take = extra_source[:remaining] if
remaining <= len(extra_source) else
extra_source
    pool += take
    while len(pool) < n:
        pool.append("Tinch aholi 🧑🏻🧑🏻")

    random.shuffle(pool)

    # avval 🧑🏻🧑🏻 huquqi bilan tanlangan
rollarni beramiz
    remaining_players = []
    for uid in player_ids:
        if uid in forced and forced[uid]:
            role = forced[uid]
            p = game["players"][uid]
            p["role"], p["team"],
p["alive"] = role, team_of(role), True
            if role in pool:
                pool.remove(role)
            elif "Tinch aholi 🧑🏻🧑🏻" in pool:
                pool.remove("Tinch aholi
🧑🏻🧑🏻")

            elif pool:
                pool.pop()
        else:
            remaining_players.append(uid)

    random.shuffle(remaining_players)
    while len(pool) <
len(remaining_players):

```

```

        pool.append("Tinch aholi 🧑🏿")

        # 🧑🏿 rol – o'yinchining oldingi
        o'yindagi roliga imkon qadar mos
        kelmaydigan qilib taqsimlanadi
        for uid, role in
        _assign_no_repeat(remaining_players, pool):
            p = game["players"][uid]
            p["role"], p["team"], p["alive"] =
            role, team_of(role), True

        # keyingi o'yinda solishtirish uchun
        har bir o'yinchining ENDIGI rolini
        "last_role" sifatida saqlaymiz
        for uid in player_ids:
            ch = get_charges(uid)
            ch["last_role"] = game["players"]
            [uid]["role"]
            set_charges(uid, ch)

        # 🏆 Geroy (Elandriel/Zephyrion "Boylik
        siri") – har o'yin boshlanganda avtomatik
        +1 💎
        # 🛠️ XATOLIK TUZATILDI: bu avval
        "hero_income_claimed" belgisini QO'YMAS
        edi,
        # shu sababli o'yinchi keyin
        /geroy_daromad buyrug'i orqali YANA +1 💎
        olib,
        # bitta o'yinda 2 marta bepul olmos
        undirib olishi mumkin edi. Endi shu yerda
        # ham belgi qo'yiladi – bir o'yinda
        faqat BITTA marta olmos beriladi.
        game.setdefault("hero_income_claimed",

```

```

set())
    for uid in player_ids:
        if hero_has_ability(uid,
"diamond_trickle"):
            add_balance(uid, diamond=1)

game["hero_income_claimed"].add(uid)
            safe_send(uid, "💎 Geroyingiz
sizga bu o'yin uchun +1 Olmos in'om
qildi!")

        game["forced_roles"] = {}

#
=====
=====
# /Sotop
#
=====
=====

@bot.message_handler(commands=["Sotop",
"sotop"])
def cmd_sotop(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_authorized(message):
        bot.send_message(message.chat.id,
"🚫 Bu buyruqni faqat guruh admini yoki bot
egasi ishlatishi mumkin.")
        return
    chat_id = message.chat.id
    if chat_id in GAMES:

```

```

        del GAMES[chat_id]
        save_games_state()
        bot.send_message(chat_id, "🔴 O'yin
admin tomonidan to'xtatildi.")
    else:
        bot.send_message(chat_id, "Hozir
faol o'yin yo'q.")

#
=====
=====
#   TUNGI BOSQICH
#
=====
=====

def alive_role_holders(game, predicate):
    return [uid for uid, p in
game["players"].items() if p["alive"] and
predicate(p["role"])]

def _bot_dm_button():
    """qoshimchakod-larda ko'rilgan uslub –
guruhdagi xabarlarda botning shaxsiy
chatiga
    o'tish uchun havola tugmasi (ovoz
berish/tungi harakatlar shu yerda amalga
oshiriladi)."""
    global BOT_USERNAME
    if BOT_USERNAME is None:
        try:
            BOT_USERNAME =

```

```

bot.get_me().username
    except Exception:
        return None

    kb = types.InlineKeyboardMarkup()
    kb.add(types.InlineKeyboardButton("🤖  
Botga o'tish",
url=f"https://t.me/{BOT_USERNAME}"))
    return kb

def start_night(chat_id):
    game = GAMES.get(chat_id)
    if not game:
        return

    # 🏆 Geroy – har tun yangidan qo'lda
    faollashtiriladigan himoya holatini
    tozalaymiz
    game["hero_armed_defense"] = set()

    #
    =====
    =====
    # 🚨 AFK NAZORATI – o'tgan tunda
    taklif olib, javob bermagan o'yinchilarni
    # belgilaymiz. 2 tun ketma-ket harakat
    qilmasa, shu tunda avtomatik chiqariladi.
    #
    =====
    =====

    prev_prompted =
    game.get("prompted_tonight", set())
    prev_responded =
    game.get("responded_tonight", set())

```

```

    afk_streak =
game.setdefault("afk_streak", {})
    kicked_afk = []
    for uid in prev_prompted:
        p = game["players"].get(uid)
        if not p or not p["alive"]:
            continue
        if uid in prev_responded:
            afk_streak[uid] = 0
        else:
            afk_streak[uid] =
afk_streak.get(uid, 0) + 1
            if afk_streak[uid] >= 2:
                p["alive"] = False
                kicked_afk.append(uid)
                afk_streak[uid] = 0
    for uid in kicked_afk:
        p = game["players"][uid]
        p["left_game"] = True # 🚪 o'yin
oxirida avtomatik mag'lub sifatida
hisoblanadi
        joke =
random.choice(AFK_KICK_JOKES).format(who=me
ntion(uid, p["name"]), role=f"<b>
{p['role']}</b>")
        bot.send_message(chat_id, joke)
        safe_send(uid, "😓 Siz 2 tun ketma-
ket harakatsiz qolganingiz uchun o'yindan
avtomatik chiqarildingiz.")
        add_points(uid, -10, "afk_kick")
    if kicked_afk and
check_and_end_game(chat_id):
        return

```

```

game["phase"] = "night"
game["mafia_votes"] = {}
game["doctor_target"] = None
game["komissar_action"] = None
game["komissar_target"] = None
game["night_announced"] = set()
game["prompted_tonight"] = set()
game["responded_tonight"] = set()
# o'tgan kunning bir martalik grantlari
(Advokat himoyasi, Provokator, Sudya)
# yangi tunda qayta tanlanadi, shuning
uchun bu yerda tozalanadi
game["advocate_protect"] = None
game["forced_day_votes"] = {}
game["judge_double_vote"] = None

send_scene_photo(
    chat_id, NIGHT_PHOTO_LOCAL,
    NIGHT_PHOTO,
    caption=f"🌙 <b>
{game['day_number']}-tun.</b> Shahar
uxlamqda... Guruhda yozish taqiqlangan.\n"
    "Rolga ega o'yinchilar –
botning shaxsiy chatida sizni tanlov
kutmoqda. 🤖",
    reply_markup=_bot_dm_button(),
)

# 🌙 Tungi atmosfera matnlari – faol
(tirik) o'yinchilarning rollariga qarab
(qoshimchakod2.py g'oyasi)
flavor_lines =
alive_role_flavor_lines(game)
if flavor_lines:

```

```

        bot.send_message(chat_id, "🌙
<b>Tun voqealari:</b>\n\n" +
"\n".join(flavor_lines))

    # 🐱🦅 Jamoaviy rejimda – tungi
    harakatlar boshlanishidan OLDIN, har bir
    # o'yinchiga o'z jamodoshlari ro'yxati
    eslatma qilib yuboriladi.
    send_squad_reminders(game)

    alive = alive_players(game)

    mafia_uids = alive_role_holders(game,
lambda r: team_of(r) == "mafia")
    for uid in mafia_uids:
        kb = types.InlineKeyboardMarkup()
        for target_id, p in alive.items():
            if team_of(p["role"]) ==
"mafia":
                continue
            tag = squad_tag(game, uid,
target_id)

        kb.add(types.InlineKeyboardButton(f"{tag}
{p['name']}", callback_data=f"na|
{chat_id}|mafia|{target_id}"))

    kb.add(types.InlineKeyboardButton("🚫
O'tkazib yuborish", callback_data=f"na|
{chat_id}|mafia|skip"))
    safe_send(uid, "🔪 <b>Kimni yo'q
qilamiz?</b> Sheriklaringiz bilan
kelishilgan holda tanlang:", kb)
    game["prompted_tonight"].add(uid)

```



```

        kom_uids = alive_role_holders(game,
lambda r: r == "Komissar 🕵️")
        for uid in kom_uids:
            kb = types.InlineKeyboardMarkup()
            kb.add(
                types.InlineKeyboardButton("🔍
Tekshirish", callback_data=f"na|
{chat_id}|komaction|check"),
                types.InlineKeyboardButton("🎯
O'ldirish", callback_data=f"na|
{chat_id}|komaction|kill"),
            )

        kb.add(types.InlineKeyboardButton("🚫
O'tkazib yuborish", callback_data=f"na|
{chat_id}|komaction|skip"))
        safe_send(uid, "🕵️ <b>Bu tun nima
qilamiz?</b>", kb)
        game["prompted_tonight"].add(uid)

        doc_uids = alive_role_holders(game,
lambda r: r == "Doktor 🩺")
        for uid in doc_uids:
            kb = types.InlineKeyboardMarkup()
            for target_id, p in alive.items():
                tag = squad_tag(game, uid,
target_id)

            kb.add(types.InlineKeyboardButton(f"{tag}
{p['name']}", callback_data=f"na|
{chat_id}|doctor|{target_id}"))

        kb.add(types.InlineKeyboardButton("🚫 Hech

```

```

kimni davolamaslik", callback_data=f"na|
{chat_id}|doctor|skip"))
    safe_send(uid, "👮 <b>Kimni
davolaysiz?</b>", kb)
    game["prompted_tonight"].add(uid)

#
=====
=====
# QO'SHIMCHA 25 ROL – hech biri chetda
qolmasin, barchasi tunda o'z
# qobiliyatini ishlata oladi (asosiy
rollar kabi shaxsiy DM orqali).
#
=====
=====
game["extra_actions"] = {}
komissar_alive =
bool(alive_role_holders(game, lambda r: r
== "Komissar 🚔"))
for uid, p in alive.items():
    role = p["role"]
    slug = EXTRA_ROLE_SLUGS.get(role)
    if not slug or slug == "arvoh":
        continue
    if slug == "serjant" and
komissar_alive:
        continue # Serjant faqat
Komissar halok bo'lganda faollashadi
    if slug == "snayper" and uid in
game.get("snayper_used", set()):
        continue # Snayper qobiliyati
butun o'yin davomida faqat 1 marta ishlaydi
prompt_text, _flavor =

```

```

EXTRA_ROLE_PROMPTS[slug]
    kb = types.InlineKeyboardMarkup()
    if slug in EXTRA_ROLE_YESNO:
        kb.add(

types.InlineKeyboardButton("✅ Ha",
callback_data=f"na|{chat_id}|ex|
{slug}:yes"),

types.InlineKeyboardButton("❌ Yo'q",
callback_data=f"na|{chat_id}|ex|
{slug}:no"),
        )
    else:
        for target_id, tp in
alive.items():
            if target_id == uid and
slug not in EXTRA_ROLE_SELF_TARGET_OK:
                continue
            tag = squad_tag(game, uid,
target_id)

kb.add(types.InlineKeyboardButton(f"{tag}
{tp['name']}", callback_data=f"na|
{chat_id}|ex|{slug}:{target_id}"))

kb.add(types.InlineKeyboardButton("❌
O'tkazib yuborish", callback_data=f"na|
{chat_id}|ex|{slug}:skip"))
        safe_send(uid, f"
{ROLES_INFO.get(role,
'')}\n\n{prompt_text}", kb)
        game["prompted_tonight"].add(uid)

```

```

# 🤖 Arvoh – faqat o'lgandan keyin
faollashadi, tirik o'yinchiga sirli imo-
ishora beradi
    if alive:
        for uid, p in
game["players"].items():
            if p["alive"] or p["role"] !=
"Arvoh 🤖":
                continue
            kb =
types.InlineKeyboardMarkup()
            for target_id, tp in
alive.items():
                tag = squad_tag(game, uid,
target_id)

kb.add(types.InlineKeyboardButton(f"{tag}
{tp['name']}", callback_data=f"na|
{chat_id}|ex|arvoh:{target_id}"))

kb.add(types.InlineKeyboardButton("🚫
O'tkazib yuborish", callback_data=f"na|
{chat_id}|ex|arvoh:skip"))
            safe_send(uid,
EXTRA_ROLE_PROMPTS["arvoh"][0], kb)

# 🏆 Geroy – himoyaga ega
(Draven/Zephyrion) o'yinchilarga har tun
eslatma + tugma
    for uid, p in alive.items():
        if hero_has_ability(uid, "survive")
or hero_has_ability(uid, "revive_once"):
            kb =
types.InlineKeyboardMarkup()

```

```

kb.add(types.InlineKeyboardButton("🛡️ Geroy
himoyasini faollashtirish",
callback_data=f"heroarm|defense|
{chat_id}"))
        safe_send(uid, "🏆 Geroyingiz
bu tun himoya qobiliyatini taklif qilmoqda.
Xohlasangiz faollashtiring "
        "
(faollashtirmasangiz, bu tun geroyingiz
sizni himoya QILMAYDI):", kb)

    t = threading.Timer(NIGHT_SECONDS,
lambda: resolve_night(chat_id))
    t.daemon = True
    t.start()
    game["timers"].append(t)

    # 🔄 checkpoint – bot qayta ishga
tushsa, shu tundan qolgan vaqtni hisoblab
davom etadi
    game["day_sub_phase"] = None
    game["phase_deadline"] = time.time() +
NIGHT_SECONDS
    save_games_state()

@bot.callback_query_handler(func=lambda c:
c.data.startswith("na|"))
def cb_night_action(call):
    maybe_capture_owner(call.from_user)
    parts = call.data.split("|")
    chat_id = int(parts[1])
    kind, value = parts[2], parts[3]

```

```

game = GAMES.get(chat_id)
uid = call.from_user.id

if not game or game["phase"] != "night"
or uid not in game["players"] or not
game["players"][uid]["alive"]:
    bot.answer_callback_query(call.id,
    "Bu tanlov endi amal qilmaydi.")
    return

# 🚫 AFK nazorati – foydalanuvchi shu
tunda javob berdi, streak nolga tushadi
game.setdefault("responded_tonight",
set()).add(uid)
# 🏆 Faollik balli – har bir tungi
harakat uchun +1 (o'yin oxirida eng faol
o'yinchi aniqlanadi)
game.setdefault("activity_score", {})
game["activity_score"][uid] =
game["activity_score"].get(uid, 0) + 1

if kind == "mafia":
    target = value if value == "skip"
else int(value)
    game["mafia_votes"][uid] = target
    if "mafia" not in
game["night_announced"]:

game["night_announced"].add("mafia")
    bot.send_message(chat_id, "👁️
<i>Mafiya soyada birlashib, o'ljasini
muhokama qilmoqda...</i>")
    try:
        bot.edit_message_text("✅

```

```

Tanlandi! Sheriklaringiz ovozi kutamiz.",
call.message.chat.id,
call.message.message_id)
    except Exception:
        pass
    bot.answer_callback_query(call.id,
"Qabul qilindi!")

    elif kind == "komaction":
        if value == "skip":
            game["komissar_action"] =
"skip"
            try:
                bot.edit_message_text("⊘
Siz bu tun harakat qilmaslikni
tanladingiz.", call.message.chat.id,
call.message.message_id)
            except Exception:
                pass

    bot.answer_callback_query(call.id)
    return
    game["komissar_action"] = value
    if "komissar" not in
game["night_announced"]:

game["night_announced"].add("komissar")
    if value == "check":
        bot.send_message(chat_id,
"👮 <i>Komissar biror kishining
hujjatlarini tekshirishga tayyorlanmoqda...
</i>")
    else:
        bot.send_message(chat_id,

```

```

"🔴 <i>Komissar hukm chiqarishga qaror
qildi – kimdir bu tundan tirik chiqmasligi
mumkin...</i>")
        kb = types.InlineKeyboardMarkup()
        for target_id, p in
alive_players(game).items():
            if target_id == uid:
                continue
            tag = squad_tag(game, uid,
target_id)

kb.add(types.InlineKeyboardButton(f"{tag}
{p['name']}", callback_data=f"na|
{chat_id}|komtarget|{target_id}"))
        try:
            bot.edit_message_text("Kimni
tanlaysiz?", call.message.chat.id,
call.message.message_id, reply_markup=kb)
        except Exception:
            pass
        bot.answer_callback_query(call.id)

    elif kind == "komtarget":
        target_id = int(value)
        game["komissar_target"] = target_id
        notify_target_touched(game,
target_id)
        if game["komissar_action"] ==
"check":
            target_charges =
get_charges(target_id)
            name =
game["players"].get(target_id,
{}).get("name", "?")

```



```

        if
target_charges.get("fake_doc", 0) > 0 and
is_item_active(target_id, "fake_doc"):
            use_charge(target_id,
"fake_doc")
            role_shown = "Tinch aholi
👥"

            # 🔧 TUZATILDI: avval bu
yerda hech qanday DM yuborilmas edi
            safe_send(target_id, "📁
Sizning <b>Soxta hujjat</b> buyumingiz
ishladi – Komissar sizni tekshirganda
haqiqiy rolingiz yashirin qoldi!")
        else:
            role_shown =
game["players"].get(target_id,
{}).get("role", "Noma'lum")
            try:
                bot.edit_message_text(f"🔍
Tekshiruv natijasi: <b>{name}</b> – <b>
{role_shown}</b>", call.message.chat.id,
call.message.message_id)
            except Exception:
                pass
            game["komissar_action"] =
"checked_done"
        else:
            try:
                bot.edit_message_text("🎯
O'ldirish buyrug'i qabul qilindi.",
call.message.chat.id,
call.message.message_id)
            except Exception:
                pass

```

```

        bot.answer_callback_query(call.id)

    elif kind == "doctor":
        target = value if value == "skip"
    else int(value)
        game["doctor_target"] = target
        if target != "skip":
            notify_target_touched(game,
target)
            if target != "skip" and "doctor"
not in game["night_announced"]]:

game["night_announced"].add("doctor")
        bot.send_message(chat_id, "👨‍⚕️
<i>Doktor navbatchilikka chiqdi, kimnidir
davolashga shay turibdi...</i>")
        try:
            bot.edit_message_text("✅
Davolash tanlovi qabul qilindi.",
call.message.chat.id,
call.message.message_id)
        except Exception:
            pass
        bot.answer_callback_query(call.id,
"Qabul qilindi!")

    elif kind == "ex":
        # qo'shimcha 25 rolning tungi
harakatlari – value = "{slug}:
{target_yoki_skip/yes/no}"
        if ":" not in value:

bot.answer_callback_query(call.id, "Xatolik
yuz berdi.")

```

```

        return
        slug, target_s = value.split(":",
1)
        role_name = SLUG_TO_ROLE.get(slug)
        if not role_name or
game["players"].get(uid, {}).get("role") !=
role_name:

bot.answer_callback_query(call.id, "Bu
tanlov endi amal qilmaydi.")
        return

def _announce_once():
    if slug not in
game["night_announced"]:

game["night_announced"].add(slug)
        bot.send_message(chat_id,
EXTRA_ROLE_PROMPTS[slug][1])

# --- darhol natija beradigan
(tekshiruv) rollar: Josus, Bomj, Serjant --
-
    if slug in EXTRA_ROLE_INSTANT_INFO:
        if target_s == "skip":
            result = "🚫 Siz bu tun
harakat qilmaslikni tanladingiz."
        else:
            target_id = int(target_s)
            tname =
game["players"].get(target_id,
{}).get("name", "?")
            trole =
game["players"].get(target_id,

```

```

{}).get("role", "Noma'lum")
        notify_target_touched(game,
target_id)

        if slug == "josus":
            result = f"👮 Tekshiruv
natijasi: <b>{tname}</b> – taraf: <b>
{team_of(trole)}</b>"
            elif slug == "serjant":
                result = f"👮 Tekshiruv
natijasi: <b>{tname}</b> – <b>{trole}</b>"
                else: # bomj – tasodifiy
                    ehtimol bilan aniqlaydi
                    if random.random() <
0.5:
                        result = f"👮 Siz
tasodifan bilib oldingiz: <b>{tname}</b> –
<b>{trole}</b>"
                    else:
                        result = "👮
Afsuski, bu tun hech narsani aniq bila
olmadingiz."
                    _announce_once()
            try:

bot.edit_message_text(result,
call.message.chat.id,
call.message.message_id)
            except Exception:
                pass

bot.answer_callback_query(call.id, "Qabul
qilindi!")
        return

```

```

        # --- Advokat: ertangi kunduzgi
        osishdan himoya belgilanadi ---
        if slug == "advokat":
            if target_s != "skip":
                game["advocate_protect"] =
int(target_s)
                notify_target_touched(game,
int(target_s))
                _announce_once()
            try:
                bot.edit_message_text("✅
Himoya tanlovingiz qabul qilindi.",
call.message.chat.id,
call.message.message_id)
            except Exception:
                pass

        bot.answer_callback_query(call.id, "Qabul
qilindi!")

        return

    # --- Provokator: tanlangan
    o'yinchining ertangi ovozi majburan
    boshqaga burib yuboriladi ---
    if slug == "provokator":
        if target_s != "skip":
            target_id = int(target_s)
            notify_target_touched(game,
target_id)

            alive_others = [pid for pid
in alive_players(game) if pid not in (uid,
target_id)]

            if alive_others:

```

```

game.setdefault("forced_day_votes", {})
[target_id] = random.choice(alive_others)
    _announce_once()
    fb = "✅ Tanlovingiz
qabul qilindi – ertaga uning ovozi majburan
burib yuboriladi."
    else:
        # 🔧 TUZATILDI: juda
kam tirik o'yinchi qolganda jim-jit "hech
narsa bo'lmadi"
        # taassurotini beruvchi
eski xatolik – endi sabab ANIQ
tushuntiriladi.
        fb = "⚠️ Hozir yetarli
boshqa tirik o'yinchi yo'q – bu safar
ovozni burib bo'lmadi."
    else:
        fb = "🚫 Siz bu tun harakat
qilmaslikni tanladingiz."
    try:
        bot.edit_message_text(fb,
call.message.chat.id,
call.message.message_id)
    except Exception:
        pass

bot.answer_callback_query(call.id, "Qabul
qilindi!")

return

# --- Sudya: ertangi kun ovozini 2x
kuchga ega qiladi ---
if slug == "sudya":
    if target_s == "yes":

```

```

        game["judge_double_vote"] =
uid
        _announce_once()
        try:
            bot.edit_message_text("✅
Tanlovingiz qabul qilindi.",
call.message.chat.id,
call.message.message_id)
        except Exception:
            pass

bot.answer_callback_query(call.id, "Qabul
qilindi!")
        return

        # --- O'g'ri: tanlangan o'yinchidan
darhol pul o'g'irlaydi ---
        if slug == "ogri":
            if target_s != "skip":
                target_id = int(target_s)
                notify_target_touched(game,
target_id)

                tu = user_dict(target_id)
                steal =
min(tu.get("dollar", 0), random.randint(20,
100))

                if steal > 0:
                    update_user(target_id,
dollar=tu["dollar"] - steal)
                    add_balance(uid,
dollar=steal)

                    feedback = f"👤 Siz
{game['players'][target_id]['name']}dan
${steal} o'g'irladingiz!"

```

```

        else:
            feedback = "👤 Uning
cho'ntagi bo'sh ekan, hech narsa topa
olmadingiz."
            _announce_once()
        else:
            feedback = "🚫 Siz bu tun
harakat qilmaslikni tanladingiz."
        try:

bot.edit_message_text(feedback,
call.message.chat.id,
call.message.message_id)
        except Exception:
            pass

bot.answer_callback_query(call.id, "Qabul
qilindi!")

        return

# --- Arvoh (o'lgandan keyin):
tirik o'yinchiga sirli imo-ishora yuboradi
---
        if slug == "arvoh":
            if target_s != "skip":
                target_id = int(target_s)
                game["players"][uid]
["ghost_hint_given"] = True
                safe_send(target_id, "👻
<i>G'ayrioddiy sovuq shabada his
qildingiz... kimdir sizga nimadir "

"aytmoqchidek bo'ldi, lekin so'zlar
tushunarsiz bo'lib qoldi.</i>")

```



```

        _announce_once()
    try:
        bot.edit_message_text("✅
Qabul qilindi.", call.message.chat.id,
call.message.message_id)
    except Exception:
        pass

bot.answer_callback_query(call.id, "Qabul
qilindi!")
    return

# --- Qolganlari
(Qotil/Manyak/Mergan/Snayper/Telba/Fohisha/
Sehrgar/
#
General/Arxitektor/Qorovul/Sadoqatli
yordamchi) – tun yakunida
#     resolve_night() ichida
birgalikda hisoblanadi ---
    target = target_s if target_s ==
"skip" else int(target_s)
    game.setdefault("extra_actions",
{})[slug] = {"actor": uid, "target":
target}
    if target != "skip":
        _announce_once()
    try:
        bot.edit_message_text("✅
Tanlovingiz qabul qilindi.",
call.message.chat.id,
call.message.message_id)
    except Exception:
        pass

```

```

        bot.answer_callback_query(call.id,
        "Qabul qilindi!")

def apply_kill(game, uid, killed_set,
bypass_protection=False,
attacker_uids=None):
    """Bitta o'yinchini o'ldirish urinishi
    – shield/revive/doktor davolashi hisobga
    olinadi.
        attacker_uids – (ixtiyoriy) shu hujumni
    amalga oshirgan o'yinchi(lar) ID'lari; agar
        geroy qobiliyati himoya qilib qolsa,
    ularga ANONIM tarzda DM yuboriladi."""
    if uid is None or uid == "skip" or uid
    not in game["players"]:
        return
    p = game["players"][uid]
    if not p["alive"] or uid in killed_set:
        return
    if not bypass_protection:
        if game.get("doctor_target") ==
uid:
            return
        if uid in
game.get("night_protected", set()):
            return
        # 🧠 Beshikdagi bola – o'yinning
    birinchi tunida hech kim unga tega olmaydi
        if p["role"] == "Beshikdagi bola
🧠" and game.get("day_number", 0) <= 1:
            return
        # 🗡️ Varvar – baquvvat jangchi,
    ayrim hujumlarga qarshilik ko'rsatadi (30%

```

```

ehtimol)
    if p["role"] == "Varvar 🗡️" and
random.random() < 0.3:
        return
        # 🏆 Geroy (Draven / Zephyrion) –
FAQAT o'zi /geroy_qalqon bilan shu tunga
QO'LDA
        # faollashtirgan bo'lsa ishlaydi
(avtomatik EMAS). Avval kafolatlangan
"revive_once"
        # (agar hali sarflanmagan bo'lsa),
aks holda oddiy % ehtimolli "survive"
tekshiriladi.
        if uid in
game.get("hero_armed_defense", set()):
            if hero_has_ability(uid,
"revive_once") and uid not in
game.setdefault("hero_revive_used", set()):

game["hero_revive_used"].add(uid)

bot.send_message(game["chat_id"], "🔥
<i>Kimningdir geroyi o'limni yengib, uni
oxirgi marta hayotga qaytardi!</i>")
        safe_send(uid, "🔥
Geroyingizning bir martalik qobiliyati
ishga tushdi – bu safar o'limdan
qutuldingiz! (Endi sarflandi.)")
        for a_uid in (attacker_uids
or []):
            safe_send(a_uid, "🏆
<i>Nishoningiz kimningdir geroy qobiliyati
tufayli o'limdan qutulib qoldi...</i>")
        return

```

```

        h_chance =
hero_survive_chance(uid)
        if h_chance > 0 and
random.random() < h_chance:

bot.send_message(game["chat_id"], "🏆
<i>Kimningdir geroyi uni tunda hujumdan
qutqarib qoldi!</i>")
        safe_send(uid, "🏆
Geroyingiz faollashtirilgan edi – bu kecha
sizga hujum qilishdi, lekin geroyingiz
sizni qutqardi!")
        for a_uid in (attacker_uids
or []):
            safe_send(a_uid, "🏆
<i>Nishoningiz kimningdir geroy qobiliyati
tufayli hujumdan omon qoldi...</i>")
            return
        if consume_shield(uid):

bot.send_message(game["chat_id"], "🛡️
<i>Kimningdir maxsus buyumi uni tunda
hujumdan asrab qoldi!</i>")
        safe_send(uid, "🛡️ Bu kecha
sizga hujum qilishdi, lekin buyumingiz
sizni himoya qildi!")
        return
        if is_item_active(uid, "revive")
and use_charge(uid, "revive"):

bot.send_message(game["chat_id"], "⚡
<i>Kimningdir tezkor jonlanish tumori uni
o'limdan qutqarib qoldi!</i>")
        safe_send(uid, "⚡ Bu kecha

```

```

sizga hujum qilishdi, lekin Tezkor
jonlanish tumoringiz sizni qutqardi!")
    return
    killed_set.add(uid)

def resolve_night(chat_id):
    with GAME_LOCK:
        game = GAMES.get(chat_id)
        if not game or game["phase"] !=
"night":
            return

        #
=====
=====
        # QO'SHIMCHA ROLLAR – 1-bosqich:
        bloklash va himoya (kimlar bloklandi/
        # himoyalandi, boshqa
        harakatlardan OLDIN aniqlanishi kerak)
        #
=====
=====
        extra = game.get("extra_actions",
        {})
        roleblocked = set()
        night_protected = set()

        fohisha_act = extra.get("fohisha")
        if fohisha_act and
        fohisha_act["target"] != "skip":

        roleblocked.add(fohisha_act["target"])

```

```

# 🧙 SehrGAR – bashorat qilib
bo'lmaydigan sehr: yo himoya, yoki bloklash
    sehrGAR_act = extra.get("sehrGAR")
    if sehrGAR_act and
sehrGAR_act["target"] != "skip":
        t = sehrGAR_act["target"]
        if random.random() < 0.5:
            night_protected.add(t)
        else:
            roleblocked.add(t)

    for slug in ("general",
"arxitektor", "qorovul", "sadoqat",
"sehryor"):
        act = extra.get(slug)
        if act and act["target"] !=
"skip":

night_protected.add(act["target"])
            notify_target_touched(game,
act["target"])
            game["night_protected"] =
night_protected

        if fohisha_act and
fohisha_act["target"] != "skip":
            notify_target_touched(game,
fohisha_act["target"])
            if sehrGAR_act and
sehrGAR_act["target"] != "skip":
                notify_target_touched(game,
sehrGAR_act["target"])

        if roleblocked:

```

```

        doctor_uid =
next(iter(alive_role_holders(game, lambda
r: r == "Doktor 🩺")), None)
        komissar_uid =
next(iter(alive_role_holders(game, lambda
r: r == "Komissar 🕵️")), None)
        for voter in
list(game["mafia_votes"].keys()):
            if voter in roleblocked:
                game["mafia_votes"]
[voter] = "skip"
            if doctor_uid in roleblocked:
                game["doctor_target"] =
"skip"
            if komissar_uid in roleblocked:
                game["komissar_action"] =
"skip"
            for act in extra.values():
                if act["actor"] in
roleblocked:
                    act["target"] = "skip"

        # --- mafiya ko'pchilik ovozi ---
        tally = {}
        for voter, target in
game["mafia_votes"].items():
            if target != "skip":
                tally[target] =
tally.get(target, 0) + 1
            mafia_kill_target = None
            bypass_for_mafia = False
            if tally:
                max_v = max(tally.values())
                top = [t for t, v in

```

```

tally.items() if v == max_v]
    mafia_kill_target =
random.choice(top)

    # 📧 Tushunarsiz xat – nishonda
    "confuse" bo'lsa hujum boshqasiga buriladi
    target_charges =
get_charges(mafia_kill_target)
    if
target_charges.get("confuse", 0) > 0 and
is_item_active(mafia_kill_target,
"confuse"):

use_charge(mafia_kill_target, "confuse")
    # 🔧 TUZATILDI: avval bu
yerda hech qanday DM yuborilmas edi – endi
    # o'zining "Tushunarsiz
xat" buyumi ishlaganini albatta biladi.

safe_send(mafia_kill_target, "📧 Sizning
<b>Tushunarsiz xat</b> buyumingiz ishladi –
mafiyaning hujumi sizdan chalg'itib
yuborildi!")

    alt = [uid for uid, p in
alive_players(game).items()
    if uid !=
mafia_kill_target and team_of(p["role"]) !=
"mafia"]

    if alt:
        mafia_kill_target =
random.choice(alt)

    # 🟡 Oltin o'q – mafiyalardan
birortasida bo'lsa himoyani chetlab o'tadi

```



```

        for voter_uid, target in
game["mafia_votes"].items():
            if target ==
mafia_kill_target and
get_charges(voter_uid).get("golden_bullet",
0) > 0 and is_item_active(voter_uid,
"golden_bullet"):
                use_charge(voter_uid,
"golden_bullet")
                bypass_for_mafia = True
                safe_send(voter_uid,
"🟡 Bu kecha 🟡 Oltin o'qingiz ishlatildi –
bu safar hujumingiz barcha himoyalarni
chetlab o'tadi!")
                break

        # 🧑 Missiya kuzatuvi – ertangi
kunduzgi ovoz berish uchun "bugungi tunda
        # mafiya kimni nishonga oldi"
ma'lumotini saqlaymiz
        game["last_night_mafia_target"] =
mafia_kill_target

        # kim kimning "uyiga bordi" – o'lim
xabarida oshkor qilish uchun (qoshimchakod
uslubi)
        visitor_role_of = {}
        if mafia_kill_target is not None:
            voter_roles = [game["players"]
[v]["role"] for v, t in
game["mafia_votes"].items()
                        if t ==
mafia_kill_target and v in game["players"]]
            if voter_roles:

```

```

visitor_role_of[mafia_kill_target] =
random.choice(voter_roles)
    if game.get("komissar_action") ==
"kill" and game.get("komissar_target"):

visitor_role_of[game["komissar_target"]] =
"Komissar 🕵️"

    killed = set()
    attempted_targets = set()
    if mafia_kill_target is not None:

attempted_targets.add(mafia_kill_target)
    notify_target_touched(game,
mafia_kill_target)
    apply_kill(game, mafia_kill_target,
killed, bypass_protection=bypass_for_mafia,
    attacker_uids=[v for v,
t in game["mafia_votes"].items() if t ==
mafia_kill_target])

    if game.get("komissar_action") ==
"kill" and game.get("komissar_target"):

attempted_targets.add(game["komissar_target
"])
    _kom_uid =
next(iter(alive_role_holders(game, lambda
r: r == "Komissar 🕵️")), None)
    apply_kill(game,
game["komissar_target"], killed,
attacker_uids=[_kom_uid] if _kom_uid else
None)

```

```

        # 🧪 Zaharli flakon – /zahar orqali
belgilanganlar
        # 🐛 TUZATILDI: endi dict
{target_id: [zaharlovchi_id, ...]} –
attacker_uids
        # apply_kill'ga to'g'ri uzatiladi,
shu bilan geroy himoyasi ishlaganda
        # zaharlovchiga ham to'g'ri
(anonim) bildirishnoma boradi, boshqa hujum
        # turlari (mafiya, qotil va h.k.)
bilan bir xil ishlaydi.
        poison_marks =
game.pop("poison_marks", {})
        if isinstance(poison_marks, set):
# eski formatdagi saqlangan o'yin bilan
moslik uchun
            poison_marks = {pt: [] for pt
in poison_marks}
            for pt, poisoners in
poison_marks.items():
                if pt not in game["players"] or
not game["players"][pt]["alive"] or pt in
killed:
                    continue
                attempted_targets.add(pt)
                # 🩹 Kichik Aptechka – zaharga
qarshi 1 martalik avtomatik davo
                if
get_charges(pt).get("antidote", 0) > 0 and
is_item_active(pt, "antidote"):
                    use_charge(pt, "antidote")
                    safe_send(pt, "🩹 Sizni
kimdir zaharlamoqchi bo'ldi, lekin

```

```

Aptechkangiz avtomatik davoladi!")
        continue
        apply_kill(game, pt, killed,
attacker_uids=poisoners)
        game["poison_marks"] = {}

        #
=====
=====
        # QO'SHIMCHA ROLLAR – 2-bosqich:
mustaqil qotillar
(Qotil/Manyak/Mergan/Snayper)
        # va Telba ning tasodifiy harakati
        #
=====
=====
        for slug in ("qotil", "manyak",
"mergan"):
            act = extra.get(slug)
            if act and act["target"] !=
"skip":
                notify_target_touched(game,
act["target"])

attempted_targets.add(act["target"])
            actor_role =
game["players"].get(act["actor"],
{}).get("role")
            if actor_role and
act["target"] not in visitor_role_of:

visitor_role_of[act["target"]] = actor_role
            apply_kill(game,
act["target"], killed, attacker_uids=

```

```

[act["actor"]])

        snayper_act = extra.get("snayper")
        if snayper_act and
snayper_act["target"] != "skip":
            notify_target_touched(game,
snayper_act["target"])

attempted_targets.add(snayper_act["target"]
)
        actor_role =
game["players"].get(snayper_act["actor"],
{}).get("role")
        if actor_role and
snayper_act["target"] not in
visitor_role_of:

visitor_role_of[snayper_act["target"]] =
actor_role

        apply_kill(game,
snayper_act["target"], killed,
attacker_uids=[snayper_act["actor"]])
        game.setdefault("snayper_used",
set()).add(snayper_act["actor"])

        telba_triggered = False
        telba_act = extra.get("telba")
        if telba_act and
telba_act["target"] != "skip":
            notify_target_touched(game,
telba_act["target"])
            if random.random() < 0.5:
                telba_triggered = True

```

```

attempted_targets.add(telba_act["target"])
    if telba_act["target"] not
in visitor_role_of:

visitor_role_of[telba_act["target"]] =
"Telba 🤪"

    apply_kill(game,
telba_act["target"], killed, attacker_uids=
[telba_act["actor"]])

#
=====
=====
# QO'SHIMCHA ROLLAR – 3-bosqich:
har bir rolga o'z harakati natijasi
# haqida shaxsiy (DM) hisobot –
foydali/foydasiz bo'lganini bildiradi
#
=====
=====
    doctor_uid =
next(iter(alive_role_holders(game, lambda
r: r == "Doktor 🩺")), None)
    if doctor_uid and
game.get("doctor_target") not in (None,
"skip"):
        d_target =
game["doctor_target"]
        t_name =
game["players"].get(d_target,
{}).get("name", "?")
        if d_target in
attempted_targets:
            safe_send(doctor_uid, f"👉

```

```

Bu kecha {mention(d_target, t_name)}ga
yordam berdingiz – hujumdan qutqardingiz!")
    else:
        safe_send(doctor_uid, f"👮
Hech kim {mention(d_target, t_name)}ga
hujum qilishga urinmadi – bu safar
yordamingiz kerak bo'lmadi.")

        for slug in ("general",
"arxitektor", "qorovul", "sadoqat",
"sehryor"):
            act = extra.get(slug)
            if act and act["target"] !=
"skip":
                t_name =
game["players"].get(act["target"],
{}).get("name", "?")
                if act["target"] in
attempted_targets:
                    safe_send(act["actor"],
f"🛡️ Himoyangiz ishladi!
{mention(act['target'], t_name)} tunni omon
o'tkazdi.")
                else:
                    safe_send(act["actor"],
f"😞 Hech kim hujum qilmagani uchun bu kecha
himoyangiz kerak bo'lmadi.")

            for slug in ("qotil", "manyak",
"mergan"):
                act = extra.get(slug)
                if act and act["target"] !=
"skip":
                    t_name =

```

```

game["players"].get(act["target"],
{}).get("name", "?")
        if act["target"] in killed:
            safe_send(act["actor"],
f"🔪 Nishoningiz {mention(act['target'],
t_name)} halok bo'ldi.")
        else:
            safe_send(act["actor"],
f"🛡️ {mention(act['target'], t_name)}ni
maqsad qilgan edingiz, lekin kimningdir
himoyasi tufayli u omon qoldi.")

# 🛠️ TUZATILDI: Telba roliga avval
HECH QANDAY natija xabari yuborilmas
# edi (boshqa barcha rollarga
yuboriladi) – endi u ham o'z tasodifiy
# harakati natijasi haqida ANIQ
shaxsiy xabar oladi.
        if telba_act and
telba_act["target"] != "skip":
            t_name =
game["players"].get(telba_act["target"],
{}).get("name", "?")
            if telba_triggered and
telba_act["target"] in killed:
                safe_send(
                    telba_act["actor"],
                    f"😬 Tasodifiy taqdir
kulib boqdi...
{mention(telba_act['target'], t_name)}
sizning "
                        f"g'ayrioddiy
harakatingiz qurboni bo'ldi!",
                    )

```



```

elif telba_triggered:
    safe_send(
        telba_act["actor"],
        f"😬 Siz
{mention(telba_act['target'], t_name)}ga
hujum qilishga urindingiz, lekin "
        f"kimningdir himoyasi
tufayli u omon qoldi.",
    )
else:
    safe_send(
        telba_act["actor"],
        f"😬 Bu safar taqdir
boshqacha hal qildi –
{mention(telba_act['target'], t_name)}ga "
        f"hech narsa bo'lmadi.
Telbaning harakati har doim ham natija
bermaydi!",
    )

if snayper_act and
snayper_act["target"] != "skip":
    t_name =
game["players"].get(snayper_act["target"],
{}).get("name", "?")
    if snayper_act["target"] in
killed:

safe_send(snayper_act["actor"], f"🎯
Otganingiz aniq tegdi –
{mention(snayper_act['target'], t_name)}
halok bo'ldi.")
    else:

```

```
safe_send(snayper_act["actor"], f"🛡️  
{mention(snayper_act['target'], t_name)}ni  
nishonga oldingiz, lekin himoyasi uni  
qutqardi.")
```

```
        if fohisha_act and  
fohisha_act["target"] != "skip":  
            t_name =  
game["players"].get(fohisha_act["target"],  
{}).get("name", "?")  
            safe_send(fohisha_act["actor"],  
f"🔪 {mention(fohisha_act['target'],  
t_name)}ni band qildingiz – u bu kecha  
qobiliyatini ishlata olmadi.")
```

```
        if sehrGAR_act and  
sehrGAR_act["target"] != "skip":  
            t_name =  
game["players"].get(sehrGAR_act["target"],  
{}).get("name", "?")  
            if sehrGAR_act["target"] in  
night_protected:
```

```
safe_send(sehrGAR_act["actor"], f"🧙  
Sehringiz {mention(sehrGAR_act['target'],  
t_name)}ni himoyaladi!")  
        else:
```

```
safe_send(sehrGAR_act["actor"], f"🧙  
Sehringiz {mention(sehrGAR_act['target'],  
t_name)}ning qobiliyatini bloklab qo'ydi!")
```

```
        if killed:  
            killed_names_for_ai = []
```

```

        for uid in killed:
            game["players"][uid]
["alive"] = False
            name = game["players"][uid]
["name"]
            role = game["players"][uid]
["role"]

killed_names_for_ai.append(name)
        visitor =
visitor_role_of.get(uid)
            text = f"💀 Tunda
{mention(uid, name)} vahshiylarcha
o'ldirildi!\nFosh qilingan roli: <b>{role}
</b>"

            if visitor:
                text += f"\n<i>
{VISIT_PHRASE.get(visitor, f'Aytishlaricha
unikiga {visitor} kelgan...')}</i>"
                bot.send_message(chat_id,
text)

handle_death_side_effects(game, chat_id,
uid) # 🗑️ Don vorisligi / 🤖 Arvoh
faollashuvi
        for uid in killed:
            wait_last_words(chat_id,
uid)

            theron_night_narration(chat_id,
killed_names_for_ai, no_death=False) # 🧠
AI qisqa hikoyasi
        else:
            bot.send_message(chat_id, "🌞
Bu tunda hech kim halok bo'lmadi.")

```

```

        theron_night_narration(chat_id,
[], no_death=True) # 🧠 AI qisqa hikoyasi

        # 🗨️ Tungi ko'zoynak – DM orqali
        "kim faol bo'lganini" ko'rsatish
        acted_roles = []
        if any(v != "skip" for v in
game["mafia_votes"].values()):
            acted_roles.append("👁️ Mafiya")
            if game.get("komissar_action") not
in (None, "skip"):
                acted_roles.append("👮
Komissar")
            if game.get("doctor_target") not in
(None, "skip"):
                acted_roles.append("👨
Doktor")
            for uid, p in
list(game["players"].items()):
                ch = get_charges(uid)
                if p["alive"] and
ch.get("night_vision", 0) > 0 and
is_item_active(uid, "night_vision"):
                    use_charge(uid,
"night_vision")
                text = "🗨️ Bu tun faol
bo'lgan rollar: " + ("", ".join(acted_roles)
if acted_roles else "hech kim")
                safe_send(uid, text)

        # 🏆 Geroy (Seraphine/Zephyrion
"Tungi nazar") – har tun avtomatik, bepul,
        # nechta o'yinchi faol harakat
qilganini (kimligini emas) DM orqali
bildiradi

```

```

        active_count =
len(game.get("responded_tonight", set()))
        for uid, p in
list(game["players"].items()):
            if p["alive"] and
hero_has_ability(uid, "night_vision_auto"):
                safe_send(uid, f"👁️
Geroyingiz sizga pichirlaydi: bu tun <b>
{active_count}</b> ta o'yinchi faol harakat
qildi.")

        if check_and_end_game(chat_id):
            return

        bot.send_message(chat_id,
roster_breakdown_text(game))
        start_day(chat_id)

def handle_death_side_effects(game,
chat_id, uid):
    """👤 Bir o'yinchi (istalgan sabab
bilan – tunda o'ldirilgan, kunduzi osilgan
yoki o'zi tark etgan) halok bo'lgach
chaqiriladi. Uchta muhim narsani bajaradi:

    1) 👑 DON VORISLIGI – agar halok
bo'lgan DON bo'lsa, tirik qolgan
Mafia 🗡️ a'zolaridan biri
tasodifiy tarzda yangi DON etib
ko'tariladi (Almex Black Bot
uslub: "Siz endi DON bo'ldingiz!").
    2) 😁 ARVOH FAOLLASHUVI – agar halok
bo'lgan Arvoh bo'lsa, unga o'zining

```

```

        yangi (o'limdan keyingi)
qobiliyati haqida aniq tushuntirish
yuboriladi

        (aks holda o'yinchi "hech narsa
bo'lmadi" deb o'ylashi mumkin edi).

3) 🍷 PARA (couple) REJIMI –
'bog'langan taqdir': agar halok bo'lgan
        o'yinchining MAXFIY sherigi hali
tirik bo'lsa, u ham DARHOL halok
        bo'ladi va juftlik guruhga endi
(birinchi marta) FOSH qilinadi.""
    p = game["players"].get(uid)
    if not p:
        return
    role = p.get("role")

    if role == "Don 🎩":
        candidates = [c_uid for c_uid, cp
in alive_players(game).items() if
cp["role"] == "Mafia 🖤"]
        if candidates:
            new_don =
random.choice(candidates)
            game["players"][new_don]
["role"] = "Don 🎩"
            safe_send(
                new_don,
                "🔥 <b>Siz endi DON
bo'ldingiz!</b>\n"
                "Mafiya guruhining yangi
rahbari – endigi tunlardan boshlab
sheriklaringiz "
                "bilan birga qurbon tanlash
huquqi (mafiya ovozi) sizga o'tdi.",

```

```

        )
        bot.send_message(chat_id, "🔥
<i>Mafiya safida yangi kuch markazi
shakllandi... kimdir soyada DON martabasiga
ko'tarildi.</i>")

    if role == "Arvoh 🧟":
        safe_send(
            uid,
            "🧟 <b>Siz Arvohga aylandingiz!
</b>\n"
            "Tanangiz halok bo'ldi, ammo
ruhingiz o'yinda qoladi. Endi har tun tirik
"
            "o'yinchilardan biriga botning
shaxsiy chatida sirli imo-ishora yubora
olasiz "
            "— bunday xabar sizga tunning
boshida avtomatik keladi.",
        )

    if game.get("couple_mode"):
        partner_id = game.get("couple_of",
        {}).get(uid)
        if partner_id:
            pp =
game["players"].get(partner_id)
            couple_key = tuple(sorted((uid,
partner_id)))
            if couple_key not in
game.setdefault("revealed_couples", set()):
game["revealed_couples"].add(couple_key)
            bot.send_message(

```

```

        chat_id,
        f"💍 <b>Maxfiy juftlik
fosh bo'ldi!</b> {mention(uid, p['name'])}
va "
            f"{mention(partner_id,
pp['name']) if pp else 'sherigi'}
birgalikda "
            f"maxfiy juftlik ekan –
{p['role']} va {pp['role']} if pp else
'?'}.",
        )
    if pp and pp.get("alive"):
        pp["alive"] = False
        bot.send_message(
            chat_id,
            f"💔 Sherigi
{mention(uid, p['name'])} halok bo'lgani
sababli, "
            f"{mention(partner_id,
pp['name'])} ham 'bog'langan taqdir'
qoidasiga ko'ra DARHOL o'yindan chiqdi!",
        )

handle_death_side_effects(game, chat_id,
partner_id)

def get_faction_teammates(game, uid):
    """Foydalanuvchining joriy o'yindagi
yashirin 'jamoasi' a'zolarini qaytaradi:
    • ("mafia", [...]) – Don 🎩 + Mafia
🔪 (tirik bo'lganlari)
    • ("qonun", [...]) – Komissar 🕵️ +
Serjant 🚔 (tirik bo'lganlari)

```



```

    • (None, []) – jamoasi yo'q (yakka
rol yoki Tinch aholi)"""
    p = game["players"].get(uid)
    if not p or not p["alive"]:
        return None, []
    role = p["role"]
    if team_of(role) == "mafia":
        mates = [u2 for u2, pp in
game["players"].items()
                if u2 != uid and
pp["alive"] and team_of(pp["role"]) ==
"mafia"]
        return "mafia", mates
    if role in ("Komissar 🕵️", "Serjant
👮"):
        mates = [u2 for u2, pp in
game["players"].items()
                if u2 != uid and
pp["alive"] and pp["role"] in ("Komissar
🕵️", "Serjant 👮")]
        return "qonun", mates
    return None, []

```

```

@bot.message_handler(commands=["jamo",
"adolat"])
def cmd_faction_chat(message):
    """🗨️ FAQAT shaxsiy chatda va faol
o'yin ichida ishlaydi. Guruh buni
KO'RMAYDI – o'z jamoadoshlaringizga
(Mafiya: Don+Mafia – /jamo, yoki
Qonun: Komissar+Serjant – /adolat) bot
orqali yashirin xabar yuboradi.
Foydalanish: /jamo xabar matni yoki

```

```

/adolat xabar matni"""
    maybe_capture_owner(message.from_user)
    if message.chat.type != "private":
        return
    uid = message.from_user.id
    parts = message.text.split(maxsplit=1)
    if len(parts) < 2 or not
parts[1].strip():
        bot.send_message(
            message.chat.id,
            "Foydalanish:\n<code>/jamo
xabar matni</code> – Mafiya jamoasiga\n"
            "<code>/adolat xabar
matni</code> – Qonun (Komissar+Serjant)
jamoasiga",
        )
        return
    text = parts[1].strip()

    game = None
    for g in GAMES.values():
        if uid in g["players"] and
g["players"][uid]["alive"]:
            game = g
            break
    if not game:
        bot.send_message(message.chat.id,
"✗ Siz hozir hech qanday faol o'yinda
emassiz.")
        return

    kind, mates =
get_faction_teammates(game, uid)
    if kind is None or not mates:

```

```

        bot.send_message(message.chat.id,
"❌ Sizda hozir bu jamoaviy chatdan
foydalanish imkoni yo'q (jamoadoshingiz
yo'q yoki rolingiz mos kelmaydi).")
        return

        label = "👁️ Mafiya jamoasi" if kind ==
"mafia" else "👮👮 Qonun jamoasi"
        sender_name = game["players"][uid]
["name"]
        sent = sum(1 for mate_uid in mates if
safe_send(mate_uid, f"{label} 💬 <b>
{sender_name}:</b> {text}"))
        bot.send_message(
            message.chat.id,
            f"✅ Xabaringiz {sent} ta
jamoadoshingizga yetkazildi." if sent else
"❌ Hech kimga yetkazib bo'lmadi.",
        )

def wait_last_words(chat_id, uid):
    game = GAMES.get(chat_id)
    if not game:
        return
    game["last_words_wait"].add(uid)
    safe_send(uid, f"🕒 Siz o'yindan
chiqarildingiz. So'nggi so'zingizni aytish
uchun sizda {LAST_WORDS_SECONDS} soniya
vaqt bor. Shu yerga (DM'ga) yozing.")

def timeout_check():
    g = GAMES.get(chat_id)
    if not g:

```

```

        return
        if uid in g.get("last_words_wait",
set()):

g["last_words_wait"].discard(uid)
        name = g["players"].get(uid,
{}).get("name", "0'yinchi")
        bot.send_message(chat_id, f"👤
<b>{mention(uid, name)}</b>ning so'nggi
so'zi:\n{random.choice(DEAD_FUNNY_WORDS)}")

        t = threading.Timer(LAST_WORDS_SECONDS,
timeout_check)
        t.daemon = True
        t.start()
        game["timers"].append(t)

@bot.message_handler(func=lambda m:
m.chat.type == "private" and not (m.text or
"").startswith("/"))
def private_message_router(message):
    maybe_capture_owner(message.from_user)
    # 💰 ELITE narx-tahrirlash kutilayotgan
bo'lsa – BU yerda ushlanadi (pastdagi
    # boshqa @bot.message_handler emas,
chunki bitta xabarga faqat BIRINCHI mos
    # kelgan handler ishlaydi – shu handler
ro'yxatga birinchi olingan).
    if message.from_user.id in
_ELITE_PRICE_EDIT_STATE:
        _handle_elite_price_input(message)
        return
    if message.from_user.id in

```

```

_TUNE_EDIT_STATE:
    _handle_tune_setting_input(message)
    return

    for chat_id, game in
list(GAMES.items()):
    if message.from_user.id in
game.get("last_words_wait", set()):

game["last_words_wait"].discard(message.fro
m_user.id)

        uid = message.from_user.id
        name = game["players"][uid]
["name"]

        bot.send_message(chat_id, f"👤
<b>{mention(uid, name)}</b>ning so'nggi
so'zi:\n«{message.text}»")
        return

# 🐱🦊🐼👁️ JAMODOSHLAR CHATI – o'yin
davomida (tunda yoki kunduzi) bot orqali
# HECH QANDAY buyruqsiz yozilgan oddiy
matnli xabar, agar yuboruvchining
# jamodoshi (jamoadoshi / turmush
o'rtog'i / mafiya sherigi) bo'lsa, FAQAT
# o'sha jamodoshlariga bot orqali
yetkaziladi – boshqa hech kimga (guruhga
# ham) ko'rinmaydi. Jamodoshi yo'q
o'yinchilar uchun bu bo'lim hech narsa
# qilmaydi (mavjud xatti-harakat
o'zgarishsiz qoladi).
    if message.content_type == "text" and
message.text:
        uid = message.from_user.id
        for chat_id, game in

```

```

list(GAMES.items()):
    if game.get("phase") not in
("night", "day"):
        continue
    p = game["players"].get(uid)
    if not p or not p.get("alive"):
        continue
    _label, emblem, mates =
ally_roster(game, uid)
    if not mates:
        continue
    sender_name = p["name"]
    for mate_uid, _mate_name in
mates:
        safe_send(mate_uid, f"
{emblem} <i>{sender_name} (jamodoshingiz):
</i>\n{message.text}")
    return

```

```

@bot.message_handler(func=lambda m:
m.chat.type in ("group", "supergroup") and
not (m.text or "").startswith("/"))
def group_chat_moderation(message):
    """🚫 O'yin davomida guruh chatini
nazorat qiladi – 3 ta rejimning
    HAMMASIDA (oddiy, 🐱🦊 Jamoaviy, 📺
Para) bir xilda ishlaydi, chunki
    bularning barchasi bitta o'yin motorida
ishlaydi:
    • 🌙 Tunda – HECH KIM guruhda yoza
olmaydi, yozgan xabar DARHOL,
    hech qanday kechikmasdan
o'chiriladi.

```

- 🌞 Kunduzi (va umuman o'yin davom etayotgan paytda) – o'yindan chiqib ketgan yoki hech qachon qo'shilmagan (o'ynamayotgan) foydalanuvchilarning xabarlari ham darhol o'chiriladi; faqat HOZIR tirik ishtirok etayotgan o'yinchilar kunduzi erkin yoza oladi.

O'yin hali boshlanmagan yoki tugagan bo'lsa (phase == "waiting" yoki umuman o'yin yo'q) – guruh butunlay erkin, hech narsa o'chirilmaydi."""

```

game = GAMES.get(message.chat.id)
if not game or game.get("phase") not in
("night", "day"):
    return
if not message.from_user:
    return
if game["phase"] == "night":
    safe_delete(message)
    return
p =
game["players"].get(message.from_user.id)
if not p or not p.get("alive"):
    safe_delete(message)

#
=====
=====
# /zahar /gps /qayta_tanlash – do'kon
buyumlarini ishlatish buyruqlari
#
=====

```

```

=====

#
=====
=====
# /zahar /gps /qayta_tanlash – do'kon
buyumlarini ishlatish buyruqlari
# (endi har biri alohida `do_*` funksiyaga
ajratilgan – shu funksiyalarni
# ham reply-buyruq, ham 📦 Inventardagi
"ishlatish" tugmasi chaqiradi)
#
=====
=====

def find_active_game_for(uid):
    """Foydalanuvchi hozir tirik holda
    ishtirok etayotgan o'yin (agar bo'lsa) –
    Inventardan to'g'ridan-to'g'ri buyum
    ishlatish uchun kerak."""
    for chat_id, game in GAMES.items():
        p = game["players"].get(uid)
        if p and p["alive"] and
        game["phase"] in ("night", "day"):
            return chat_id, game
    return None, None

def do_zahar(chat_id, game, uid, target_id,
target_name):
    if get_charges(uid).get("poison", 0) <=
0:
        return False, "❌ Sizda 🧪 Zaharli
flakon yo'q."

```



```

        if target_id not in game["players"] or
        not game["players"][target_id]["alive"]:
            return False, "❌ Bu o'yinchi
            topilmadi yoki allaqachon o'yindan
            chetlashtirilgan."
        use_charge(uid, "poison")
        # 🦋 TUZATILDI: avval oddiy `set()` edi
        - kim kimni zaharlaganini saqlamas edi,
        # shu sabab geroy himoyasi ishlaganda
        zaharlovchiga bildirishnoma bormas edi.
        # Endi target_id -> zaharlovchi(lar)
        ro'yxati sifatida saqlanadi.
        game.setdefault("poison_marks",
        {}).setdefault(target_id, []).append(uid)
        return True, f"💧 Siz {target_name}ga
        yashirinchga zahar berdingiz. Doktor
        davolamasa, u tun yakunida halok bo'ladi."

def do_gps(chat_id, game, uid, target_id,
target_name):
    if get_charges(uid).get("gps", 0) <= 0:
        return False, "❌ Sizda 📍 GPS
        Mayak yo'q."
    if target_id not in game["players"]:
        return False, "❌ Bu o'yinchi
        topilmadi."
    use_charge(uid, "gps")
    if get_charges(target_id).get("cloak",
    0) > 0:
        use_charge(target_id, "cloak")
        return True, "📍 GPS signali
        yo'qoldi... Nishon 🕶️ Yashirin Kolt
        yordamida o'zini yashirgan ko'rinadi."

```

```
        alive = game["players"][target_id]
        ["alive"]
        status = "tirik va o'yin maydonida" if
alive else "allaqachon o'yindan
chetlashtirilgan"
        return True, f"📍 GPS natijasi:
{target_name} hozir {status}."
```

```
def do_kompas(chat_id, game, uid,
target_id, target_name):
    has_hero_compass =
hero_has_free_compass(uid) # 🏆 Geroy
(Seraphine / Zephyrion)
    if not has_hero_compass and
get_charges(uid).get("compass", 0) <= 0:
        return False, "❌ Sizda 🚫 Sirli
kompas yo'q."
    if target_id not in game["players"] or
not game["players"][target_id]["alive"]:
        return False, "❌ Bu o'yinchi
topilmadi yoki allaqachon o'yindan
chetlashtirilgan."
    if not has_hero_compass:
        use_charge(uid, "compass")
        target_role = game["players"]
[target_id]["role"]
        return True, f"🚫 Kompas natijasi: <b>
{target_name}</b> – taraf: <b>
{team_of(target_role)}</b>"
```

```
def do_fonar(chat_id, game, uid, target_id,
target_name):
```

```

        if get_charges(uid).get("flash_light",
0) <= 0:
            return False, "❌ Sizda 🔦 Katta
Fonar yo'q."
            if target_id not in game["players"]:
                return False, "❌ Bu o'yinchi
topilmadi."
            use_charge(uid, "flash_light")
            role = game["players"][target_id]
["role"]
            return True, f"🔦 Fonar yorug'ligida
ko'rindi: {target_name} – <b>{role}</b>"

def do_tutun(chat_id, game, uid):
    if game["phase"] != "day":
        return False, "❌ 💣 Tutunli
bombani faqat kunduzi ishlatish mumkin."
        if get_charges(uid).get("smoke_bomb",
0) <= 0:
            return False, "❌ Sizda 💣 Tutunli
bomba yo'q."
        if game["players"]
[uid].get("smoke_active"):
            return False, "💨 Tutun allaqachon
faol – bugun uchun himoyalangansiz."
            use_charge(uid, "smoke_bomb")
            game["players"][uid]["smoke_active"] =
True
            return True, "💨 Tutunli bomba
ishlatildi! Bugun eng ko'p ovoz olsangiz
ham, lynch qilinmaysiz."

```

```

def do_qayta_tanlash(chat_id, game, uid):
    if get_charges(uid).get("radar", 0) <=
0:
        return False, "❌ Sizda 📡 Maxfiy
radar yo'q."
        use_charge(uid, "radar")
        old_role = game["players"][uid]["role"]
        new_role = random.choice([r for r in
ALL_ROLES if r != old_role])
        game["players"][uid]["role"] = new_role
        game["players"][uid]["team"] =
team_of(new_role)
        return True, f"📡 Radar
faollashtirildi!\nEski rolingiz:
{old_role}\n{role_portrait(new_role)}\nYang
i rolingiz: <b>{new_role}
</b>\n\n{ROLES_INFO.get(new_role, '')}"

@bot.message_handler(commands=["zahar"])
def cmd_zahar(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if message.chat.type not in ("group",
"supergroup") or not
message.reply_to_message:
        return
    chat_id = message.chat.id
    game = GAMES.get(chat_id)
    if not game or game["phase"] not in
("night", "day"):
        return
    uid = message.from_user.id
    target =

```

```

message.reply_to_message.from_user
    if is_banned(uid) or
is_banned(target.id):
        return
    if uid not in game["players"] or not
game["players"][uid]["alive"]:
        return
    ok, msg = do_zahar(chat_id, game, uid,
target.id, mention(target.id,
target.first_name))
    safe_send(uid, msg)
    if ok:
        announce_item_use(chat_id, uid, "🖋️
Zaharli flakon")

```

```

@bot.message_handler(commands=["gps"])
def cmd_gps(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if message.chat.type not in ("group",
"supergroup") or not
message.reply_to_message:
        return
    chat_id = message.chat.id
    game = GAMES.get(chat_id)
    if not game:
        return
    uid = message.from_user.id
    target =
message.reply_to_message.from_user
    if uid not in game["players"]:
        return
    ok, msg = do_gps(chat_id, game, uid,

```

```

target.id, mention(target.id,
target.first_name))
    safe_send(uid, msg)
    if ok:
        announce_item_use(chat_id, uid, "📍
GPS Mayak")

@bot.message_handler(commands=["kompas"])
def cmd_kompas(message):
    """🧭 Sirli kompas – birovning ANIQ
rolini emas, faqat qaysi tarafda
(mafiya/tinch aholi/mustaqil) ekanini
ko'rsatadi. Komissar tekshiruvidan
ancho kuchsizroq (rol emas, faqat
taraf), shuning uchun muvozanatga xavf
solmaydi."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if message.chat.type not in ("group",
"supergroup") or not
message.reply_to_message:
        return
    chat_id = message.chat.id
    game = GAMES.get(chat_id)
    if not game or game["phase"] not in
("night", "day"):
        return
    uid = message.from_user.id
    target =
message.reply_to_message.from_user
    if uid not in game["players"] or not
game["players"][uid]["alive"]:
        return

```

```

        ok, msg = do_kompas(chat_id, game, uid,
target.id, mention(target.id,
target.first_name))
        safe_send(uid, msg)
        if ok:
            announce_item_use(chat_id, uid, "💣
Sirli Kompas")

```

```

@bot.message_handler(commands=["tutun"])
def cmd_tutun(message):
    """💣 Tutunli bomba – kunduzi
ishlatilsa, sizni shu kunlik ovoz berishda
linch qilinishdan (eng ko'p ovoz olgan
bo'lsangiz ham) bir marta asraydi."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if message.chat.type not in ("group",
"supergroup"):
        return
    chat_id = message.chat.id
    game = GAMES.get(chat_id)
    if not game:
        return
    uid = message.from_user.id
    if uid not in game["players"] or not
game["players"][uid]["alive"]:
        return
    ok, msg = do_tutun(chat_id, game, uid)
    safe_send(uid, msg)
    if ok:
        announce_item_use(chat_id, uid, "💣
Tutunli bomba")

```

```

@bot.message_handler(commands=["fonar"])
def cmd_fonar(message):
    """🔊 Katta Fonar – javob berilgan
    (reply) o'yinchining haqiqiy rolini bir
    marta o'qib beradi (DM orqali)."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if message.chat.type not in ("group",
    "supergroup") or not
    message.reply_to_message:
        return
    chat_id = message.chat.id
    game = GAMES.get(chat_id)
    if not game or game["phase"] not in
    ("night", "day"):
        return
    uid = message.from_user.id
    target =
    message.reply_to_message.from_user
    if uid not in game["players"]:
        return
    ok, msg = do_fonar(chat_id, game, uid,
    target.id, mention(target.id,
    target.first_name))
    safe_send(uid, msg)
    if ok:
        announce_item_use(chat_id, uid, "🔊
    Katta Fonar")

```

```

@bot.message_handler(commands=
    ["qayta_tanlash"])
def cmd_qayta_tanlash(message):

```



```

        maybe_capture_owner(message.from_user)
        safe_delete(message)
        if message.chat.type not in ("group",
"supergroup"):
            return
        chat_id = message.chat.id
        game = GAMES.get(chat_id)
        if not game or game["phase"] not in
("night", "day"):
            return
        uid = message.from_user.id
        if uid not in game["players"] or not
game["players"][uid]["alive"]:
            return
        ok, msg = do_qayta_tanlash(chat_id,
game, uid)
        safe_send(uid, msg)
        if ok:
            announce_item_use(chat_id, uid, "📡
Maxfiy radar")

```

```

#
=====
=====
# 🏠 KLANLAR VA KLANLAR JANGI – TO'LIQ
TIZIM
# (foydalanuvchi yuborgan texnik topshiriq
– TXT fayl – asosida qurilgan)
# Lider = clans.owner_id. O'rinsosar =
clans.deputy_id. Oddiy a'zolar
clan_members'da.
#
=====

```

=====

```
CLAN_LEVEL_CAPS = {1: {"members": 15,
"titles": 2}, 2: {"members": 25, "titles":
5}, 3: {"members": 50, "titles": 10}}
CLAN_LEVEL_UP_COST = {2: {"diamond": 75,
"coin": 1}, 3: {"diamond": 120, "coin": 3}}
CLAN_MAX_LEVEL = 3
```

```
CLAN_WAR_MIN_LEADER_DOLLAR = 1000
CLAN_WAR_WIN_TREASURY = 1000
CLAN_WAR_LOSE_TREASURY = 500
CLAN_WAR_SURRENDER_TREASURY = 300
CLAN_WAR_STREAK_FOR_DIAMOND = 5
CLAN_WAR_STREAK_DIAMOND_REWARD = 3
CLAN_WAR_COOLDOWN_SECONDS = 120
CLAN_WAR_DECLINE_LIMIT = 3
CLAN_WAR_DECLINE_FINE = 500
```

```
CLAN_TITLE_RITSAR = "ritsar"
CLAN_TITLE_SEHRGAR = "sehrgar"
CLAN_TITLE_MIN_LEVEL = {CLAN_TITLE_RITSAR:
10, CLAN_TITLE_SEHRGAR: 15}
CLAN_TITLE_COST_DOLLAR = 5000
CLAN_TITLE_MIN_GAMES = {CLAN_TITLE_RITSAR:
5, CLAN_TITLE_SEHRGAR: 10}
CLAN_TITLE_POWER_BONUS =
{CLAN_TITLE_RITSAR: 2, CLAN_TITLE_SEHRGAR:
4}
CLAN_TITLE_NAMES = {CLAN_TITLE_RITSAR: "🛡️
Ritsar", CLAN_TITLE_SEHRGAR: "👤 Sehrgar"}
```

```
CLAN_NAME_CHANGE_COST = 5000
CLAN_DEPUTY_MIN_CLAN_LEVEL = 2
```

```

CLAN_DEPUTY_COST_COIN = 1
CLAN_DEPUTY_MAX_LEVELUPS = 2
CLAN_INACTIVITY_DAYS = 30
CLAN_INACTIVITY_PENALTY = 3

def _check_clan_inactivity():
    """🏠 Klan lideri 30 kun davomida jang
    qilmasa, klan darajasi va barcha
    a'zolar darajasi -3 lvl bo'ladi
    (spetsifikatsiya talabi). Har 24 soatda
    bir marta tekshiriladi (o'z-o'zini
    qayta rejalashtiradigan fon vazifasi)."""
    try:
        threshold = time.time() -
        CLAN_INACTIVITY_DAYS * 86400
        with db_lock:
            cur.execute(
                "SELECT owner_id FROM clans
WHERE last_war_at < ? AND
last_inactivity_penalty_at < ?",
                (threshold, threshold),
            )
            inactive_owners = [r[0] for r
in cur.fetchall()]
            for owner_id in
inactive_owners:
                cur.execute(
                    "UPDATE clans SET
leader_level = MAX(0, leader_level - ?),
last_inactivity_penalty_at = ? WHERE
owner_id=?",
                    (CLAN_INACTIVITY_PENALTY, time.time(),

```

```

owner_id),
    )
    cur.execute(
        "UPDATE clan_members
SET level = MAX(0, level - ?) WHERE
owner_id=?",

(CLAN_INACTIVITY_PENALTY, owner_id),
    )
    conn.commit()
    for owner_id in inactive_owners:
        clan = get_clan(owner_id)
        note = f"⚠️ <b>{clan['name']}</b> klani 30 kundan beri jang qilmadi –
barcha a'zolar -{CLAN_INACTIVITY_PENALTY}
lvl oldi." if clan else ""
        if note:
            safe_send(owner_id, note)
    except Exception:
        logging.exception("⚠️ Klan
faolsizlik tekshiruvda xatolik.")
    finally:
        t = threading.Timer(86400,
_check_clan_inactivity)
        t.daemon = True
        t.start()

def get_clan(owner_id):
    with db_lock:
        cur.execute(
            "SELECT owner_id, name, level,
deputy_id, leader_level, treasury_dollar,
treasury_diamond, "

```

```

        "levelup_tokens, wins, losses,
win_streak, war_declines_streak,
last_war_at, deputy_levelups_used "
        "FROM clans WHERE owner_id=?",
        (owner_id,),
    )
    row = cur.fetchone()
    if not row:
        return None
    cols = ["owner_id", "name", "level",
"deputy_id", "leader_level",
"treasury_dollar", "treasury_diamond",
        "levelup_tokens", "wins",
"losses", "win_streak",
"war_declines_streak", "last_war_at",
"deputy_levelups_used"]
    return dict(zip(cols, row))

def find_member_clan(uid):
    """Foydalanuvchi biror klanga a'zomi
(lider yoki oddiy a'zo) – shu klan
owner_id'sini qaytaradi."""
    clan = get_clan(uid)
    if clan:
        return uid # o'zi lider
    with db_lock:
        cur.execute("SELECT owner_id FROM
clan_members WHERE member_id=?", (uid,))
        row = cur.fetchone()
        return row[0] if row else None

def is_clan_leader(uid, owner_id):

```

```

        return uid == owner_id

def is_clan_deputy(uid, owner_id):
    clan = get_clan(owner_id)
    return bool(clan and clan["deputy_id"]
== uid)

def clan_can_manage(uid, owner_id):
    return is_clan_leader(uid, owner_id) or
is_clan_deputy(uid, owner_id)

def clan_member_count(owner_id):
    with db_lock:
        cur.execute("SELECT COUNT(*) FROM
clan_members WHERE owner_id=?",
(owner_id,))
        return cur.fetchone()[0] + 1 # +
lider

def clan_title_count(owner_id):
    with db_lock:
        cur.execute("SELECT COUNT(*) FROM
clan_members WHERE owner_id=? AND title IS
NOT NULL", (owner_id,))
        return cur.fetchone()[0]

def get_clan_member_row(owner_id, uid):
    with db_lock:
        cur.execute("SELECT member_id,

```

```

member_name, level, title FROM clan_members
WHERE owner_id=? AND member_id=?",
(owner_id, uid))
        row = cur.fetchone()
        if not row:
            return None
        return {"member_id": row[0],
"member_name": row[1], "level": row[2] or
0, "title": row[3]}

def clan_power(owner_id):
    """Klanning umumiy 'jang kuchi': lider
darajasi + barcha a'zolar darajasi + maqom
bonuslari."""
    clan = get_clan(owner_id)
    if not clan:
        return 0
    total = clan["leader_level"] or 3
    with db_lock:
        cur.execute("SELECT level, title
FROM clan_members WHERE owner_id=?",
(owner_id,))
        rows = cur.fetchall()
        for level, title in rows:
            total += (level or 0)
            if title in CLAN_TITLE_POWER_BONUS:
                total +=
CLAN_TITLE_POWER_BONUS[title]
    return max(total, 1)

#
=====

```

```

=====
# /klan – klan yaratish
#
=====
=====

@bot.message_handler(commands=["klan"])
def cmd_klan(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    uid = message.from_user.id
    if get_charges(uid).get("klan_license",
0) <= 0:
        bot.send_message(message.chat.id,
"❌ Klan ochish uchun avval 🏠 Klan
litsenziyasini (Hunter Coin do'koni) sotib
oling.")
        return
    if get_clan(uid):
        bot.send_message(message.chat.id,
"❌ Sizda allaqachon klan bor.")
        return
    if find_member_clan(uid):
        bot.send_message(message.chat.id,
"❌ Siz boshqa klanning a'zosisiz – avval
/klan_tark deb chiqing.")
        return
    parts = message.text.split(maxsplit=1)
    if len(parts) < 2:
        bot.send_message(message.chat.id,
"Foydalanish: <code>/klan Nomi</code>")
        return
    name = parts[1].strip()[:32]
    use_charge(uid, "klan_license")

```



```

with db_lock:
    cur.execute(
        "INSERT OR REPLACE INTO clans
(owner_id, name, level, deputy_id,
leader_level, treasury_dollar, "
        "treasury_diamond,
levelup_tokens, wins, losses, win_streak,
war_declines_streak, last_war_at,
deputy_levelups_used) "
        "VALUES
(?,?,1,NULL,3,0,0,10,0,0,0,0,?,0)",
        (uid, name, time.time()),
    )
    conn.commit()
    bot.send_message(
        message.chat.id,
        f"🏰 Klan yaratildi: <b>{name}</b>!\n\n"
        f"👑 Siz lider – boshlang'ich
darajangiz: <b>3 lvl</b>\n"
        f"🎁 Sizga darhol <b>10 ta lvl-
up</b> berildi – buni a'zolaringizga
/klan_azo_daraja orqali taqsimlang "
        f"(yoki xohlasangiz hammasini
o'zingizga sarflang).",
    )

```

```

#
=====
# /klanim – klan holati
#
=====

```

```

=====

@bot.message_handler(commands=["klanim"])
def cmd_klanim(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    uid = message.from_user.id
    owner_id = find_member_clan(uid)
    if not owner_id:
        bot.send_message(message.chat.id,
            "Sizda hali klan yo'q. 🏠 Klan  

litsenziyasini sotib olib <code>/klan  

Nomi</code> deb yozing.")
        return
    clan = get_clan(owner_id)
    caps = CLAN_LEVEL_CAPS[clan["level"]]
    with db_lock:
        cur.execute("SELECT member_id,  

member_name, level, title FROM clan_members  

WHERE owner_id=? ORDER BY level DESC",  

(owner_id,))
        members = cur.fetchall()

    leader_name = user_dict(owner_id)
    ["name"]
    lines = [
        f"🏠 <b>{clan['name']}</b> –  

{clan['level']} lvl klan\n",
        f"👑 Lider: {mention(owner_id,  

leader_name)} ({clan['leader_level']}  

lvl)",
    ]
    if clan["deputy_id"]:
        dep_name =

```

```

user_dict(clan["deputy_id"])["name"]
    lines.append(f"🏆 0'rinbosar:
{mention(clan['deputy_id'], dep_name)}")
    lines.append(f"👥 A'zolar:
{clan_member_count(owner_id)}/{caps['members']} | 🏆 Maqomlar:
{clan_title_count(owner_id)}/{caps['titles']}")
    lines.append(f"💰 Xazina:
${clan['treasury_dollar']} | 💎
{clan['treasury_diamond']}")
    lines.append(f"🔪 {clan['wins']}
g'alaba / {clan['losses']} mag'lubiyat
(ketma-ket: {clan['win_streak']})")
    if is_clan_leader(uid, owner_id) or
is_clan_deputy(uid, owner_id):
        lines.append(f"🎯 Taqsimlanmagan
lvl-up tokenlar: {clan['levelup_tokens']}")
        if members:
            lines.append("\n👥 <b>A'zolar:
</b>")
            for m_id, m_name, m_level, m_title
in members:
                title_tag = f"
{CLAN_TITLE_NAMES[m_title]}" if m_title in
CLAN_TITLE_NAMES else ""
                lines.append(f"• {mention(m_id,
m_name)} – {m_level or 0} lvl{title_tag}")
            bot.send_message(message.chat.id,
"\n".join(lines))

```

#

=====

```

=====
# /klanga_qoshil – endi so'rov yuboradi,
lider tasdiqlashi kerak
#
=====
=====

@bot.message_handler(commands=
["klanga_qoshil"])
def cmd_klanga_qoshil(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    uid = message.from_user.id
    if is_banned(uid):
        return
    if find_member_clan(uid):
        bot.send_message(message.chat.id,
"✗ Siz allaqachon bir klanning
a'zosisiz.")
        return
    parts = message.text.split()
    if len(parts) != 2 or not
parts[1].isdigit():
        bot.send_message(message.chat.id,
"Foydalanish: <code>/klanga_qoshil
<lt;klan_egasining_user_id>></code>")
        return
    owner_id = int(parts[1])
    clan = get_clan(owner_id)
    if not clan:
        bot.send_message(message.chat.id,
"✗ Bunday klan topilmadi.")
        return
    caps = CLAN_LEVEL_CAPS[clan["level"]]

```

```

        if clan_member_count(owner_id) >=
caps["members"]:
            bot.send_message(message.chat.id,
f"❌ Bu klan to'lgan (maksimal
{caps['members']} a'zo).")
            return

        user_dict(uid,
message.from_user.first_name)
        with db_lock:
            cur.execute(
                "INSERT OR REPLACE INTO
clan_join_requests (owner_id, user_id,
user_name, requested_at) VALUES (?, ?, ?, ?)",
                (owner_id, uid,
message.from_user.first_name, time.time()),
            )
            conn.commit()

        kb = types.InlineKeyboardMarkup()
        kb.add(
            types.InlineKeyboardButton("✅
Qabul qilish", callback_data=f"cjreq|yes|
{owner_id}|{uid}"),
            types.InlineKeyboardButton("❌ Rad
etish", callback_data=f"cjreq|no|
{owner_id}|{uid}"),
        )
        safe_send(
            owner_id,
            f"✉️ <b>
{message.from_user.first_name}</b> sizning
<b>{clan['name']}</b> klaningizga
qo'shilishni so'ramoqda.",

```

```

        kb,
    )
    bot.send_message(message.chat.id, f"✉️
    So'rovingiz <b>{clan['name']}</b> klani
    liderga yuborildi – javobini kuting.")

@bot.callback_query_handler(func=lambda c:
    c.data.startswith("cjreq|"))
def cb_clan_join_request(call):
    maybe_capture_owner(call.from_user)
    _, action, owner_s, user_s =
    call.data.split("|")
    owner_id, user_id = int(owner_s),
    int(user_s)

    if call.from_user.id != owner_id:
        bot.answer_callback_query(call.id,
        "Bu so'rovga faqat klan lideri javob bera
        oladi.")
        return

    with db_lock:
        cur.execute("DELETE FROM
        clan_join_requests WHERE owner_id=? AND
        user_id=?", (owner_id, user_id))
        conn.commit()

    clan = get_clan(owner_id)
    if not clan:
        bot.answer_callback_query(call.id,
        "Klan topilmadi.")
        return

```

```

        if action == "no":
            bot.edit_message_text("🚫 So'rov
rad etildi.", call.message.chat.id,
call.message.message_id)
            bot.answer_callback_query(call.id)
            safe_send(user_id, f"🚫 <b>
{clan['name']}</b> klaniga qo'shilish
so'rovingiz rad etildi.")
            return

        caps = CLAN_LEVEL_CAPS[clan["level"]]
        if clan_member_count(owner_id) >=
caps["members"]:
            bot.edit_message_text("❌ Klan
to'lib qoldi, qabul qilib bo'lmadi.",
call.message.chat.id,
call.message.message_id)
            bot.answer_callback_query(call.id)
            return

        if find_member_clan(user_id):
            bot.edit_message_text("❌ Bu
foydalanuvchi allaqachon boshqa klanga a'zo
bo'lgan.", call.message.chat.id,
call.message.message_id)
            bot.answer_callback_query(call.id)
            return

        user_name = user_dict(user_id)["name"]
        with db_lock:
            cur.execute(
                "INSERT OR REPLACE INTO
clan_members (owner_id, member_id,
member_name, level, title) VALUES
(?,?,?,0,NULL)",

```

```

        (owner_id, user_id, user_name),
    )
    conn.commit()
    bot.edit_message_text(f"✅ {user_name}
klaningizga qabul qilindi!",
call.message.chat.id,
call.message.message_id)
    bot.answer_callback_query(call.id)
    safe_send(user_id, f"✅ Siz <b>
{clan['name']}</b> klaniga muvaffaqiyatli
qo'shildingiz! Boshlang'ich darajangiz: 0
lvl.")

#
=====
=====
# /klan_tark, /klan_chetlash – klandan
chiqish / chiqarish
#
=====
=====

@bot.message_handler(commands=
["klan_tark"])
def cmd_klan_tark(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    uid = message.from_user.id
    owner_id = find_member_clan(uid)
    if not owner_id or owner_id == uid:
        bot.send_message(message.chat.id,
"❌ Siz biror klanning oddiy a'zosi emassiz
(lider klanni tark eta olmaydi – uni

```



```

tarqating).")
    return
    clan = get_clan(owner_id)
    with db_lock:
        cur.execute("DELETE FROM
clan_members WHERE owner_id=? AND
member_id=?", (owner_id, uid))
        if clan and clan["deputy_id"] ==
uid:
            cur.execute("UPDATE clans SET
deputy_id=NULL WHERE owner_id=?",
(owner_id,))
            conn.commit()
            bot.send_message(
                message.chat.id,
                f"👋 Siz <b>{clan['name']} if clan
else 'klan'</b>dan chiqdingiz. Darajangiz
0 lvlga tushdi, "
                f"klanga aloqador barcha
narsalaringiz yo'qoldi.",
            )

@bot.message_handler(commands=
["klan_chetlash"])
def cmd_klan_chetlash(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if message.chat.type not in ("group",
"supergroup") or not
message.reply_to_message:
        bot.send_message(message.chat.id,
"❌ Chetlatmoqchi bo'lgan a'zoning xabariga
reply qilib yozing.")

```

```

        return
    uid = message.from_user.id
    owner_id = find_member_clan(uid)
    if not owner_id or not
is_clan_leader(uid, owner_id):
        bot.send_message(message.chat.id,
"❌ Bu buyruq faqat klan lideri uchun.")
        return
    target =
message.reply_to_message.from_user
    with db_lock:
        cur.execute("DELETE FROM
clan_members WHERE owner_id=? AND
member_id=?", (owner_id, target.id))
        clan = get_clan(owner_id)
        if clan and clan["deputy_id"] ==
target.id:
            cur.execute("UPDATE clans SET
deputy_id=NULL WHERE owner_id=?",
(owner_id,))
            conn.commit()
            bot.send_message(message.chat.id, f"👤
{target.first_name} klandan
chetlashtirildi.")
            safe_send(target.id, f"👤 Siz <b>
{clan['name']} if clan else 'klan'</b>dan
chetlashtirildingiz. Darajangiz 0 lvlga
tushdi.")

#
=====
=====
# /klan_orinbosar – o'rinbosar tayinlash

```

```

#
=====

=====

@bot.message_handler(commands=
["klan_orinbosar"])
def cmd_klan_orinbosar(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if message.chat.type not in ("group",
"supergroup") or not
message.reply_to_message:
        bot.send_message(message.chat.id,
"✗ O'rinbosar qilmoqchi bo'lgan a'zoning
xabariga reply qilib yozing.")
        return
    uid = message.from_user.id
    clan = get_clan(uid)
    if not clan:
        bot.send_message(message.chat.id,
"✗ Bu buyruq faqat klan lideri uchun.")
        return
    if clan["level"] <
CLAN_DEPUTY_MIN_CLAN_LEVEL:
        bot.send_message(message.chat.id,
f"✗ O'rinbosar tayinlash uchun klan kamida
{CLAN_DEPUTY_MIN_CLAN_LEVEL}-lvl bo'lishi
kerak.")
        return
    target =
message.reply_to_message.from_user
    if get_clan_member_row(uid, target.id)
is None:
        bot.send_message(message.chat.id,

```

```

"❌ Bu odam sizning klaningiz a'zosi
emas.")
    return
    u = user_dict(uid)
    if u["coin"] < CLAN_DEPUTY_COST_COIN:
        bot.send_message(message.chat.id,
f"❌ Yetarli Hunter Coin yo'q
({CLAN_DEPUTY_COST_COIN} kerak).")
        return
        update_user(uid, coin=u["coin"] -
CLAN_DEPUTY_COST_COIN)
        with db_lock:
            cur.execute("UPDATE clans SET
deputy_id=?, deputy_levelups_used=0 WHERE
owner_id=?", (target.id, uid))
            conn.commit()
            bot.send_message(message.chat.id, f"🏆
{target.first_name} endi klaningiz
o'rinbosari!")
            safe_send(target.id, f"🏆 Siz <b>
{clan['name']}</b> klanining o'rinbosari
etib tayinlandingiz – jangga ruxsat berish
va cheklangan lvl taqsimlash huquqiga
egasiz.")

#
=====
=====
# /klan_azo_daraja – a'zoning darajasini
oshirish/pasaytirish (faqat
lider/o'rinbosar)
#
=====

```

```

@bot.message_handler(commands=
["klan_azo_daraja"])
def cmd_klan_azo_daraja(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if message.chat.type not in ("group",
"supergroup") or not
message.reply_to_message:
        bot.send_message(message.chat.id,
"❌ Daraja bermoqchi bo'lgan a'zoning
xabariga reply qilib, miqdorni yozing.")
        return
    uid = message.from_user.id
    owner_id = find_member_clan(uid)
    if not owner_id or not
clan_can_manage(uid, owner_id):
        bot.send_message(message.chat.id,
"❌ Bu buyruq faqat klan lideri yoki
o'rinbosari uchun.")
        return
    parts = message.text.split()
    if len(parts) != 2 or not
parts[1].lstrip("-").isdigit():
        bot.send_message(message.chat.id,
"Foydalanish: <code>/klan_azo_daraja
<lt;son, masalan 3 yoki -2<gt;</code>
(a'zoning xabariga reply qiling)")
        return
    amount = int(parts[1])
    target =
message.reply_to_message.from_user
    row = get_clan_member_row(owner_id,

```

```

target.id)
    if row is None and target.id !=
owner_id:
        bot.send_message(message.chat.id,
"❌ Bu odam sizning klaningiz a'zosi
emas.")
        return

    clan = get_clan(owner_id)
    is_deputy = is_clan_deputy(uid,
owner_id)
    if is_deputy and not
is_clan_leader(uid, owner_id):
        if amount <= 0:

bot.send_message(message.chat.id, "❌
O'rinbosar faqat lvl KO'TARISHI mumkin
(pasaytira olmaydi).")
        return
        remaining_deputy_quota =
CLAN_DEPUTY_MAX_LEVELUPS -
clan["deputy_levelups_used"]
        if remaining_deputy_quota <= 0:

bot.send_message(message.chat.id, "❌
O'rinbosar sifatida lvl-up limitingiz
tugagan.")
        return
        amount = min(amount,
remaining_deputy_quota,
clan["levelup_tokens"])
        if amount <= 0:

bot.send_message(message.chat.id, "❌

```

```

Taqsimlash uchun lvl-up tokeningiz yo'q.")
    return
    with db_lock:
        cur.execute("UPDATE clans SET
deputy_levelups_used = deputy_levelups_used
+ ?, levelup_tokens = levelup_tokens - ?
WHERE owner_id=?",
                    (amount, amount,
owner_id))
        conn.commit()
    else:
        if amount > 0:
            if clan["levelup_tokens"] <
amount:

bot.send_message(message.chat.id, f"✗
Yetarli lvl-up tokeningiz yo'q (bor:
{clan['levelup_tokens']}).")
        return
        with db_lock:
            cur.execute("UPDATE clans
SET levelup_tokens = levelup_tokens - ?
WHERE owner_id=?", (amount, owner_id))
            conn.commit()

        if target.id == owner_id:
            new_level = max(0,
clan["leader_level"] + amount)
            with db_lock:
                cur.execute("UPDATE clans SET
leader_level=? WHERE owner_id=?",
(new_level, owner_id))
                conn.commit()
        else:

```

```

        new_level = max(0, (row["level"] if
row else 0) + amount)
        with db_lock:
            cur.execute("UPDATE
clan_members SET level=? WHERE owner_id=?
AND member_id=?", (new_level, owner_id,
target.id))
            conn.commit()

        bot.send_message(message.chat.id, f"✅
{target.first_name} darajasi: <b>
{new_level} lvl</b>")

#
=====
# /klan_lvl – klanni yangi darajaga
ko'tarish (faqat lider)
#
=====

@bot.message_handler(commands=["klan_lvl"])
def cmd_klan_lvl(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    uid = message.from_user.id
    clan = get_clan(uid)
    if not clan:
        bot.send_message(message.chat.id,
"❌ Bu buyruq faqat klan lideri uchun.")
        return
    if clan["level"] >= CLAN_MAX_LEVEL:

```



```

        bot.send_message(message.chat.id,
f"✅ Klaningiz allaqachon eng yuqori
darajada ({CLAN_MAX_LEVEL} lvl).")
        return
        next_level = clan["level"] + 1
        cost = CLAN_LEVEL_UP_COST[next_level]
        u = user_dict(uid)
        if u["diamond"] >= cost["diamond"]:
            update_user(uid,
diamond=u["diamond"] - cost["diamond"])
        elif u["coin"] >= cost["coin"]:
            update_user(uid, coin=u["coin"] -
cost["coin"])
        else:
            bot.send_message(
                message.chat.id,
                f"❌ Klanni {next_level}-lvlga
ko'tarish uchun 💎{cost['diamond']} yoki 🪙
{cost['coin']} kerak.",
            )
            return
        with db_lock:
            cur.execute("UPDATE clans SET
level=? WHERE owner_id=?", (next_level,
uid))
            conn.commit()
            caps = CLAN_LEVEL_CAPS[next_level]
            bot.send_message(
                message.chat.id,
                f"🏰 Klaningiz <b>{next_level}-
lvl</b>ga ko'tarildi!\n"
                f"👥 Endi maksimum
{caps['members']} a'zo, {caps['titles']} ta
maqom egasi bo'lishi mumkin.",

```

```

    )

#
=====
# /klan_nomi – klan nomini o'zgartirish
(5000$)
#
=====

@bot.message_handler(commands=
["klan_nomi"])
def cmd_klan_nomi(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    uid = message.from_user.id
    clan = get_clan(uid)
    if not clan:
        bot.send_message(message.chat.id,
"❌ Bu buyruq faqat klan lideri uchun.")
        return
    parts = message.text.split(maxsplit=1)
    if len(parts) < 2:
        bot.send_message(message.chat.id,
f"Foydalanish: <code>/klan_nomi Yangi
nomi</code> (narxi:
${CLAN_NAME_CHANGE_COST})")
        return
    u = user_dict(uid)
    if u["dollar"] < CLAN_NAME_CHANGE_COST:
        bot.send_message(message.chat.id,
f"❌ Yetarli mablag' yo'q

```

```

({CLAN_NAME_CHANGE_COST} kerak).")
    return
    new_name = parts[1].strip()[:32]
    update_user(uid, dollar=u["dollar"] -
CLAN_NAME_CHANGE_COST)
    with db_lock:
        cur.execute("UPDATE clans SET
name=? WHERE owner_id=?", (new_name, uid))
        conn.commit()
        bot.send_message(message.chat.id, f"✅
Klan nomi o'zgartirildi: <b>{new_name}
</b>")

#
=====
=====
# /klan_maqom – a'zoga Ritsar/Sehrgar
maqomini berish
#
=====
=====

@bot.message_handler(commands=
["klan_maqom"])
def cmd_klan_maqom(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if message.chat.type not in ("group",
"supergroup") or not
message.reply_to_message:
        bot.send_message(message.chat.id,
"❌ Maqom bermoqchi bo'lgan a'zoning
xabariga reply qilib, <code>ritsar</code>

```

```

yoki <code>sehrgar</code> deb yozing.")
    return
    uid = message.from_user.id
    clan = get_clan(uid)
    if not clan:
        bot.send_message(message.chat.id,
"✗ Bu buyruq faqat klan lideri uchun.")
        return
    parts = message.text.split()
    if len(parts) != 2 or parts[1].lower()
not in CLAN_TITLE_MIN_LEVEL:
        bot.send_message(message.chat.id,
"Foydalanish: <code>/klan_maqom
ritsar</code> yoki <code>/klan_maqom
sehrgar</code> (a'zoning xabariga reply
qiling)")
        return
    title = parts[1].lower()
    target =
message.reply_to_message.from_user
    row = get_clan_member_row(uid,
target.id)
    if row is None:
        bot.send_message(message.chat.id,
"✗ Bu odam sizning klaningiz a'zosi
emas.")
        return
    if row["title"]:
        bot.send_message(message.chat.id,
f"✗ {target.first_name} allaqachon
{CLAN_TITLE_NAMES[row['title']] maqomiga
ega.")
        return
    if clan_title_count(uid) >=

```

```

CLAN_LEVEL_CAPS[clan["level"]]["titles"]:
    bot.send_message(message.chat.id,
        "❌ Klaningizdagi maqom o'rinlari to'lgan
        (klan darajasini oshiring).")
    return
    if row["level"] <
CLAN_TITLE_MIN_LEVEL[title]:
    bot.send_message(message.chat.id,
        f"❌ {target.first_name} kamida
        {CLAN_TITLE_MIN_LEVEL[title]} lvl bo'lishi
        kerak (hozir: {row['level']}).")
    return
    t_user = user_dict(target.id)
    if t_user["games"] <
CLAN_TITLE_MIN_GAMES[title]:
    bot.send_message(message.chat.id,
        f"❌ {target.first_name} kamida
        {CLAN_TITLE_MIN_GAMES[title]} ta o'yin
        o'ynagan bo'lishi kerak.")
    return
    if t_user["dollar"] <
CLAN_TITLE_COST_DOLLAR:
    bot.send_message(message.chat.id,
        f"❌ {target.first_name}da yetarli mablag'
        yo'q (${CLAN_TITLE_COST_DOLLAR} kerak,
        a'zoning o'zida bo'lishi kerak).")
    return
    update_user(target.id,
        dollar=t_user["dollar"] -
        CLAN_TITLE_COST_DOLLAR)
    with db_lock:
        cur.execute("UPDATE clan_members
        SET title=? WHERE owner_id=? AND
        member_id=?", (title, uid, target.id))

```

```

        conn.commit()
        bot.send_message(message.chat.id, f"🎉
{target.first_name} endi
{CLAN_TITLE_NAMES[title]}!")
        safe_send(target.id, f"🎉 Tabriklaymiz!
Siz <b>{clan['name']}</b> klanida
{CLAN_TITLE_NAMES[title]} maqomiga ega
bo'ldingiz!")

#
=====
=====
# /klan_hazna – klan xazinası (faqat
lider/o'rinbosar to'liq ko'radi)
#
=====
=====

@bot.message_handler(commands=
["klan_hazna"])
def cmd_klan_hazna(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    uid = message.from_user.id
    owner_id = find_member_clan(uid)
    if not owner_id:
        bot.send_message(message.chat.id,
"❌ Sizda klan yo'q.")
        return
    clan = get_clan(owner_id)
    if not clan_can_manage(uid, owner_id):
        bot.send_message(message.chat.id,
"❌ Xazinani faqat lider va o'rinbosar

```

```

ko'ra oladi.")
    return
    bot.send_message(
        message.chat.id,
        f"👤 <b>{clan['name']}</b> – Klan
xazinasidagi</b>\n\n💰
${clan['treasury_dollar']}\n💎
{clan['treasury_diamond']}\n\n"
        "<i>Xazinadan faqat lider foydalana
oladi (a'zolarga taqsimlash yoki boshqa
maqsadlarga sarflash).</i>",
    )

@bot.message_handler(commands=
["klan_taqsimla"])
def cmd_klan_taqsimla(message):
    """Lider klan xazinasidagi dollarni
a'zolarga (yoki o'ziga) taqsimlaydi."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if message.chat.type not in ("group",
"supergroup") or not
message.reply_to_message:
        bot.send_message(message.chat.id,
"❌ Pul bermoqchi bo'lgan a'zoning xabariga
reply qilib, miqdorni yozing.")
        return
    uid = message.from_user.id
    clan = get_clan(uid)
    if not clan:
        bot.send_message(message.chat.id,
"❌ Bu buyruq faqat klan lideri uchun.")
        return

```

```

        parts = message.text.split()
        if len(parts) != 2 or not
parts[1].isdigit():
            bot.send_message(message.chat.id,
"Foydalanish: <code>/klan_taqsimla
&lt;dollar&gt;</code> (a'zoning xabariga
reply qiling)")
            return
        amount = int(parts[1])
        if clan["treasury_dollar"] < amount:
            bot.send_message(message.chat.id,
f"❌ Xazinada yetarli mablag' yo'q (bor:
${clan['treasury_dollar']}).")
            return
        target =
message.reply_to_message.from_user
        with db_lock:
            cur.execute("UPDATE clans SET
treasury_dollar = treasury_dollar - ? WHERE
owner_id=?", (amount, uid))
            conn.commit()
            add_balance(target.id, dollar=amount)
            bot.send_message(message.chat.id, f"$
{target.first_name}ga klan xazinasidan
${amount} berildi.")

#
=====
=====
# /klanlar – top klanlar ro'yxati
#
=====
=====

```



```

@bot.message_handler(commands=["klanlar"])
def cmd_klanlar(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    with db_lock:
        cur.execute("SELECT owner_id, name,
level, wins, losses FROM clans ORDER BY
wins DESC LIMIT 15")
        rows = cur.fetchall()
        if not rows:
            bot.send_message(message.chat.id,
" Hozircha klanlar yo'q.")
            return
        lines = [" <b>TOP KLANLAR</b>\n"]
        for i, (owner_id, name, level, wins,
losses) in enumerate(rows, 1):
            lines.append(f"{i}. <b>{name}</b>
({level} lvl) -  {wins} /  {losses} -
lider ID: <code>{owner_id}</code>")
            bot.send_message(message.chat.id,
"\n".join(lines))

#
=====
# /klanjang - klanlar jangi (mutual
rozilik, so'ng kuch balansiga qarab hal
qilinadi)
#
=====
=====

```

```

CLAN_WAR_PENDING = {} # (challenger_id,
rival_owner_id) -> timestamp, spam/qayta-
taklifning oldini olish uchun

@bot.message_handler(commands=["klanjang"])
def cmd_klanjang(message):
    """Ikki klan o'rtasida jang taklifi –
    klan 'kuchi' (darajalar+maqomlar
    yig'indisi)ga
    tortilgan ehtimollik bilan g'olib
    aniqlanadi, so'ng iqtisodiy oqibatlar
    qo'llaniladi."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    uid = message.from_user.id
    if is_banned(uid):
        return
    parts = message.text.split()
    if len(parts) != 2 or not
parts[1].isdigit():
        bot.send_message(message.chat.id,
"Foydalanish: <code>/klanjang
<code>&lt;raqib_klan_egasining_user_id&gt;
</code>")
        return
    rival_owner_id = int(parts[1])
    if rival_owner_id == uid:
        bot.send_message(message.chat.id,
"❌ O'z klaningiz bilan jang qila
olmaysiz!")
        return

    my_clan = get_clan(uid)

```

```

    rival_clan = get_clan(rival_owner_id)
    if not my_clan:
        bot.send_message(message.chat.id,
            "❌ Sizda klan yo'q (faqat lider jang e'lon qila oladi).")
        return
    if not rival_clan:
        bot.send_message(message.chat.id,
            "❌ Raqibda klan topilmadi.")
        return

    # klan urushi uchun liderda kamida
    $1000 bo'lishi kerak (mumkin bo'lgan
    zararni qoplash uchun)
    u = user_dict(uid)
    if u["dollar"] <
    CLAN_WAR_MIN_LEADER_DOLLAR:
        bot.send_message(message.chat.id,
            f"❌ Klan urushi e'lon qilish uchun sizda
            kamida ${CLAN_WAR_MIN_LEADER_DOLLAR}
            bo'lishi kerak.")
        return

    # daraja farqi qoidasi: 2 lvldan past
    klanlarga so'rov yuborish erkin, past klan
    yuqori
    # darajalilarga faqat kamida 15 a'zo
    bilan taklif yubora oladi
    if rival_clan["level"] >
    my_clan["level"] and clan_member_count(uid)
    < 15:
        bot.send_message(message.chat.id,
            "❌ O'zingizdan yuqori darajali klanga
            taklif yuborish uchun kamida 15 a'zoingiz

```

```

bo'lishi kerak.")
    return

    pending_key = (uid, rival_owner_id)
    last_ts =
CLAN_WAR_PENDING.get(pending_key)
    if last_ts and (time.time() - last_ts)
< CLAN_WAR_COOLDOWN_SECONDS:
        wait_left =
int(CLAN_WAR_COOLDOWN_SECONDS -
(time.time() - last_ts))
        bot.send_message(message.chat.id,
f"⌚ Bu klanga yaqinda jang taklifi
yuborgansiz. Yana {wait_left} soniyadan
keyin urinib ko'ring.")
        return

    CLAN_WAR_PENDING[pending_key] =
time.time()
    kb = types.InlineKeyboardMarkup()
    kb.add(types.InlineKeyboardButton("✂️
Jangga chiqish",
callback_data=f"cwar|fight|{uid}|
{rival_owner_id}"))
    kb.add(types.InlineKeyboardButton("🏳️
Taslim bo'lish (-$300)",
callback_data=f"cwar|surrender|{uid}|
{rival_owner_id}"))
    kb.add(types.InlineKeyboardButton("🚫
Rad etish", callback_data=f"cwar|decline|
{uid}|{rival_owner_id}"))
    bot.send_message(
        message.chat.id,
        f"✂️ <b>KLANLAR JANGI TAKLIFI!

```

```

</b>\n\n"
        f"🏠 <b>{my_clan['name']}</b>
({clan_power(uid)} kuch) klani 🏠 <b>
{rival_clan['name']}</b> "
        f"({clan_power(rival_owner_id)}
kuch) klaniga jang e'lon qildi!",
        reply_markup=kb,
    )
    safe_send(
        rival_owner_id,
        f"🔪 <b>{my_clan['name']}</b> klani
sizga jang e'lon qildi! Guruhdagi xabar
ostidan javob bering.",
    )

@bot.callback_query_handler(func=lambda c:
c.data.startswith("cwar|"))
def cb_klanjjang(call):
    maybe_capture_owner(call.from_user)
    _, action, challenger_s, rival_owner_s
= call.data.split("|")
    challenger_id, rival_owner_id =
int(challenger_s), int(rival_owner_s)

    if call.from_user.id != rival_owner_id:
        bot.answer_callback_query(call.id,
        "Bu taklif sizga emas – faqat raqib klan
egasi javob bera oladi.")
        return

    my_clan = get_clan(challenger_id)
    rival_clan = get_clan(rival_owner_id)
    if not my_clan or not rival_clan:

```

```

        bot.answer_callback_query(call.id,
        "❌ Klanlardan biri topilmadi.")
        return

    if action == "decline":
        with db_lock:
            cur.execute("UPDATE clans SET
            war_declines_streak = war_declines_streak +
            1 WHERE owner_id=?", (rival_owner_id,))
            conn.commit()
            new_streak =
            rival_clan["war_declines_streak"] + 1
            note = ""
            if new_streak >=
            CLAN_WAR_DECLINE_LIMIT:
                u = user_dict(rival_owner_id)
                update_user(rival_owner_id,
                dollar=max(0, u["dollar"] -
                CLAN_WAR_DECLINE_FINE))
                with db_lock:
                    cur.execute("UPDATE clans
                    SET war_declines_streak = 0 WHERE
                    owner_id=?", (rival_owner_id,))
                    conn.commit()
                    note = f"\n\n⚠ Ketma-ket
                    {CLAN_WAR_DECLINE_LIMIT} marta jangdan bosh
                    tortgani uchun klaningiz
                    -${CLAN_WAR_DECLINE_FINE} jarima oldi."

        bot.edit_message_text(random.choice(DEFEAT_
        JOKES) + note, call.message.chat.id,
        call.message.message_id)
        bot.answer_callback_query(call.id)
        return

```

```

        with db_lock:
            cur.execute("UPDATE clans SET
war_declines_streak = 0 WHERE owner_id=?",
(rival_owner_id,))
            conn.commit()

        if action == "surrender":
            winner_owner_id, loser_owner_id =
challenger_id, rival_owner_id
            winner_clan, loser_clan = my_clan,
rival_clan
            surrendered = True
        else: # fight
            my_power =
clan_power(challenger_id)
            rival_power =
clan_power(rival_owner_id)
            total = my_power + rival_power
            challenger_win_chance = my_power /
total if total else 0.5
            challenger_won = random.random() <
challenger_win_chance
            winner_owner_id = challenger_id if
challenger_won else rival_owner_id
            loser_owner_id = rival_owner_id if
challenger_won else challenger_id
            winner_clan = my_clan if
challenger_won else rival_clan
            loser_clan = rival_clan if
challenger_won else my_clan
            surrendered = False

        loss_amount =

```

```

CLAN_WAR_SURRENDER_TREASURY if surrendered
else CLAN_WAR_LOSE_TREASURY
    new_streak = winner_clan["win_streak"]
+ 1
    diamond_bonus = 0
    if new_streak >=
CLAN_WAR_STREAK_FOR_DIAMOND:
        diamond_bonus =
CLAN_WAR_STREAK_DIAMOND_REWARD
        new_streak = 0

    with db_lock:
        cur.execute(
            "UPDATE clans SET
treasury_dollar = treasury_dollar + ?,
treasury_diamond = treasury_diamond + ?, "
            "wins = wins + 1, win_streak =
?, levelup_tokens = levelup_tokens + 3,
last_war_at = ? WHERE owner_id=?",
            (CLAN_WAR_WIN_TREASURY,
diamond_bonus, new_streak, time.time(),
winner_owner_id),
        )
        cur.execute(
            "UPDATE clans SET
treasury_dollar = MAX(0, treasury_dollar -
?), losses = losses + 1, win_streak = 0, "
            "last_war_at = ? WHERE
owner_id=?",
            (loss_amount, time.time(),
loser_owner_id),
        )
        cur.execute(
            "INSERT INTO clan_wars (clan_a,

```



```

clan_b, winner_owner_id, started_at,
ended_at) VALUES (?, ?, ?, ?, ?)",
        (challenger_id, rival_owner_id,
winner_owner_id, time.time(), time.time()),
        )
        conn.commit()

        result_text = (
            f"🔪 <b>KLANLAR JANGI YAKUNLANDI!
</b>\n\n"
            f"🏆 G'olib: <b>
{winner_clan['name']}</b> – xazinaga
+${CLAN_WAR_WIN_TREASURY}, +3 lvl-up token"
            + (f", +{diamond_bonus}💎 (5 ketma-
ket g'alaba!)" if diamond_bonus else "")
            + f"\n💀 Mag'lub: <b>
{loser_clan['name']}</b> – xazinadan
-${loss_amount}"
            + (" (taslim bo'lgani uchun
yumshoqroq jarima)" if surrendered else "")
        )
        bot.edit_message_text(result_text,
call.message.chat.id,
call.message.message_id)
        bot.answer_callback_query(call.id)
        safe_send(loser_owner_id, f"😞 <b>
{loser_clan['name']}</b> klaningiz jangda
yutqazdi...\n\n{random.choice(DEFEAT_JOKES)
}")
        safe_send(winner_owner_id, f"🏆 <b>
{winner_clan['name']}</b> klaningiz g'alaba
qozondi! Xazinaga +${CLAN_WAR_WIN_TREASURY}
tushdi.")

```

```

#
=====
=====
# /klan_mukofot – 3 oyda bir marta TOP
klanlarga mukofot (faqat bot egasi ishga
tushiradi)
#
=====
=====

@bot.message_handler(commands=
["klan_mukofot"])
def cmd_klan_mukofot(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        bot.send_message(message.chat.id,
"🚫 Bu buyruq faqat bot egasi uchun (3 oyda
1 marta ishga tushiriladi).")
        return
    with db_lock:
        cur.execute("SELECT owner_id, name,
wins FROM clans ORDER BY wins DESC LIMIT
3")
        top3 = cur.fetchall()
        if not top3:
            bot.send_message(message.chat.id,
"🏠 Hozircha klanlar yo'q.")
            return
        rewards = [(20000, 20), (15000, 15),
(10000, 10)]
        lines = ["🏆 <b>3 OYLIK TOP KLANLAR
MUKOFOTI</b>\n"]

```

```

        for i, ((owner_id, name, wins),
(dollar, diamond)) in enumerate(zip(top3,
rewards), 1):
            with db_lock:
                cur.execute("UPDATE clans SET
treasury_dollar = treasury_dollar + ?,
treasury_diamond = treasury_diamond + ?
WHERE owner_id=?",
                            (dollar, diamond,
owner_id))
                conn.commit()
                lines.append(f"{i}-o'rinni: <b>{name}
</b> ({wins} g'alaba) - +${dollar}, +
{diamond}💎 (klan xazinasiga)")
                safe_send(owner_id, f"🏆 Klaningiz
3 oylik reytingda {i}-o'rinni egalladi!
Xazinaga +${dollar}, +{diamond}💎 tushdi.")
            with db_lock:
                cur.execute("UPDATE clans SET
wins=0, losses=0")
                conn.commit()
                bot.send_message(message.chat.id,
"\n".join(lines) + "\n\n🔄 Barcha
klanlarning g'alaba/mag'lubiyat hisobi
yangi mavsum uchun nolga tushirildi.")

#
=====
=====
# 🛒 QORA BOZOR — O'YINCHILAR O'RTASIDAGI
SAVDO
# (qoshimchakod5.py g'oyasi asosida, real
SQLite bazasida to'liq ishlaydigan holda)
# Endi FAQAT bot egasi belgilagan bitta

```

```

guruhda ishlaydi, va sotuvchi narxni
# dollar/olmos/coin – o'zi tanlagan
valyutada, o'zi xohlagan miqdorda belgilay
oladi.
#
=====
=====

@bot.message_handler(commands=
["shu_bozor"])
def cmd_set_black_market_group(message):
    """Bot egasi qora bozor ishlaydigan
    guruhni shu buyruq bilan belgilaydi.
    Guruhga botni qo'shib, shu buyruqni
    o'sha guruhda yozing (bir marta
    yetarli)."""
    global BLACK_MARKET_CHAT_ID
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        bot.send_message(message.chat.id,
        "🚫 Bu buyruq faqat bot egasi uchun.")
        return
    if message.chat.type not in ("group",
    "supergroup"):
        bot.send_message(message.chat.id,
        "⚠ Bu buyruqni qora bozor ishlashi kerak
        bo'lgan guruhning ichida yozing.")
        return
    BLACK_MARKET_CHAT_ID = message.chat.id
    set_setting("black_market_chat_id",
    BLACK_MARKET_CHAT_ID)
    bot.send_message(message.chat.id, f"✅
    Qora bozor endi shu guruhda (<code>

```

```

{message.chat.id}</code>) ishlaydi.")

def _in_black_market_group(chat_id):
    return BLACK_MARKET_CHAT_ID is not None
    and chat_id == BLACK_MARKET_CHAT_ID

@bot.message_handler(commands=
["bozor_holati"])
def cmd_bozor_holati(message):
    """Nosozliklarni tuzatish uchun: joriy
    guruh ID'si va bot xotirasidagi
    qora bozor ID'sini solishtirib
    ko'rsatadi (faqat bot egasi uchun)."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        bot.send_message(message.chat.id,
        "🚫 Bu buyruq faqat bot egasi uchun.")
        return
    bot.send_message(
        message.chat.id,
        f"👤 Joriy guruh ID: <code>
{message.chat.id}</code>\n"
        f"🛒 Saqlangan qora bozor ID:
<code>{BLACK_MARKET_CHAT_ID}</code>\n"
        f"{'✅ Bu guruh – qora bozor.' if
_in_black_market_group(message.chat.id)
else '❌ Bu guruh qora bozor emas. Tuzatish
uchun shu yerda /shu_bozor deb yozing.'}",
        )

```

```

#
=====
=====
# QIZIL 🟡 vs KO'K 🔵 – ikki guruhli
musobaqa
#
=====
=====

@bot.message_handler(commands=["guruh_id"])
def cmd_guruh_id(message):
    """/jufti buyrug'i uchun kerakli guruh
    ID'sini ko'rish (faqat bot egasi)."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        bot.send_message(message.chat.id,
        "🚫 Bu buyruq faqat bot egasi uchun.")
        return
    bot.send_message(message.chat.id, f"ID
    Bu guruhning ID'si: <code>{message.chat.id}
    </code>")

@bot.message_handler(commands=["jufti"])
def cmd_jufti(message):
    """Joriy guruhni boshqa bir guruh bilan
    'Qizil vs Ko'k' musobaqasiga bog'laydi.
    Foydalanish: har ikkala guruhda
    /guruh_id bilan ID olinadi, so'ng birida
    /jufti <ikkinchi_guruh_ID> deb
    yoziladi. Faqat bot egasi uchun."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)

```

```

        if not is_owner(message.from_user.id):
            bot.send_message(message.chat.id,
                              "🚫 Bu buyruq faqat bot egasi uchun.")
            return
        parts = message.text.split()
        if len(parts) != 2 or not
parts[1].lstrip("-").isdigit():
            bot.send_message(message.chat.id,
                              "Foydalanish: /jufti
<ikkinchi_guruh_ID>\nID'ni ikkinchi
guruhda /guruh_id orqali oling.")
            return
        other_id = int(parts[1])
        this_id = message.chat.id
        if other_id == this_id:
            bot.send_message(message.chat.id,
                              "🚫 Guruhni o'zi bilan juftlashtirib
bo'lmaydi.")
            return
        create_pair(this_id, other_id)
        bot.send_message(this_id, f"🔴🔵 Bu
guruh boshqa guruh (<code>{other_id}
</code>) bilan muvaffaqiyatli
juftlashtirildi!\nEndi har ikkala guruhdagi
o'yinlar umumiy hisobga qo'shiladi. /hisob
orqali ko'ring.")
        try:
            bot.send_message(other_id, f"🔴🔵
Bu guruh boshqa guruh (<code>{this_id}
</code>) bilan muvaffaqiyatli
juftlashtirildi!\nEndi har ikkala guruhdagi
o'yinlar umumiy hisobga qo'shiladi. /hisob
orqali ko'ring.")
        except Exception:

```

```

        bot.send_message(this_id, "⚠️
Ogohlantirish: bot ikkinchi guruhga
hozircha xabar yubora olmadi (bot o'sha
guruhga qo'shilganini tekshiring).")

@bot.message_handler(commands=
["jufti_bekor"])
def cmd_jufti_bekor(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        bot.send_message(message.chat.id,
"🚫 Bu buyruq faqat bot egasi uchun.")
        return
    pair = get_pair(message.chat.id)
    if not pair:
        bot.send_message(message.chat.id,
"Bu guruh hech qanday juftlikka
bog'lanmagan.")
        return
    ca, cb, *_ = pair
    other_id = cb if ca == message.chat.id
    else ca
    remove_pair(message.chat.id)
    bot.send_message(message.chat.id, "🔓
Juftlik bekor qilindi.")
    try:
        bot.send_message(other_id, "🔓
Ushbu guruh bilan juftlik bekor qilindi.")
    except Exception:
        pass

```



```

@bot.message_handler(commands=["hisob"])
def cmd_hisob(message):
    """Qizil vs Ko'k umumiy hisobini
    ko'rsatadi."""
    pair = get_pair(message.chat.id)
    if not pair:
        bot.send_message(message.chat.id,
        "Bu guruh hozircha boshqa guruh bilan
        juftlashtirilmagan.\n(Bot egasi /jufti
        buyrug'i orqali bog'lashi mumkin.)")
        return
    ca, cb, label_a, label_b, score_a,
    score_b = pair
    bot.send_message(
        message.chat.id,
        f"📊 <b>Umumiy hisob</b>\n\n"
        f"{label_a}: <b>{score_a}</b>
    g'alaba\n"
        f"{label_b}: <b>{score_b}</b>
    g'alaba",
        )

@bot.message_handler(commands=["paralar"])
def cmd_paralar(message):
    """Admin uchun: barcha nikohdagi
    juftliklar ro'yxati, necha kundan beri
    nikohda ekanlari bilan. Ism ustiga
    bosilsa – o'sha kishining Telegram
    profiliga o'tiladi (mention() orqali
    tg://user?id= havolasi)."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_authorized(message):

```

```

        bot.send_message(message.chat.id,
"🚫 Bu buyruqni faqat guruh admini yoki bot
egasi ishlatishi mumkin.")
        return

    with db_lock:
        cur.execute("SELECT user_id, name,
married_to, married_at FROM users WHERE
married_to != 0")
        rows = cur.fetchall()

    if not rows:
        bot.send_message(message.chat.id,
"💔 Hozircha hech kim nikohda emas.")
        return

    seen = set()
    pairs = []
    for uid, name, partner_id, married_at
in rows:
        if uid in seen or partner_id in
seen:
            continue
        seen.add(uid)
        seen.add(partner_id)
        partner = user_dict(partner_id)
        pairs.append((uid, name,
partner_id, partner.get("name"),
married_at))

    def days_married(married_at):
        if not married_at:
            return "?"
        try:

```

```

        married_ts =
time.mktime(time.strptime(married_at, "%Y-
%m-%d %H:%M:%S"))
        days = int((time.time() -
married_ts) // 86400)
        return max(0, days)
    except Exception:
        return "?"

    lines = [f"👤 <b>Nikohdagi
juftliklar</b> – jami {len(pairs)} ta\n"]
    for i, (uid, name, partner_id,
partner_name, married_at) in
enumerate(pairs, start=1):
        d = days_married(married_at)
        kun_text = f"{d} kun" if
isinstance(d, int) else "noma'lum kun"
        lines.append(f"{i}. {mention(uid,
name)} ❤️ {mention(partner_id,
partner_name)} – {kun_text}")

    bot.send_message(message.chat.id,
"\n".join(lines))

@bot.message_handler(content_types=
["migrate_to_chat_id"])
def handle_group_migration(message):
    """Telegram guruhni supergroup'ga
aylantirganda chat_id butunlay o'zgaradi –
shu sababli eski ID'ga bog'langan qora
bozor/guruh ma'lumotlari yangi ID'ga
avtomatik ko'chiriladi, aks holda qora
bozor "guruhga qo'shiling" deb xato

```

```

        xabar bera boshlaydi, garchi
        foydalanuvchi allaqachon o'sha guruhda
        bo'lsa ham.""
        global BLACK_MARKET_CHAT_ID
        old_id = message.chat.id
        new_id = message.migrate_to_chat_id
        if BLACK_MARKET_CHAT_ID == old_id:
            BLACK_MARKET_CHAT_ID = new_id
            set_setting("black_market_chat_id",
BLACK_MARKET_CHAT_ID)
        with db_lock:
            cur.execute("SELECT title FROM
known_groups WHERE chat_id=?", (old_id,))
            row = cur.fetchone()
            remove_known_group(old_id)
            add_known_group(new_id, row[0] if row
else None)
        with db_lock:
            cur.execute("UPDATE group_pairs SET
chat_id_a=? WHERE chat_id_a=?", (new_id,
old_id))

            cur.execute("UPDATE group_pairs SET
chat_id_b=? WHERE chat_id_b=?", (new_id,
old_id))

            conn.commit()
        if old_id in GAMES:
            game = GAMES.pop(old_id)
            game["chat_id"] = new_id
            GAMES[new_id] = game
            save_games_state()
        _logger.info("Guruh supergroup'ga
ko'chirildi: %s -> %s", old_id, new_id)

```

```

@bot.message_handler(commands=["sell"])
def cmd_sell(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not
_in_black_market_group(message.chat.id):
        bot.send_message(
            message.chat.id,
            "🚫 Qora bozor faqat maxsus
savdo guruhida ishlaydi. Guruhga
qo'shiling: "
            "https://t.me/+v9bYoMk-
0hAyZTcy",
        )
        return
    uid = message.from_user.id
    if is_banned(uid):
        return
    user_dict(uid,
message.from_user.first_name)

    u = user_dict(uid)
    try:
        inv = json.loads(u["inventory"] or
"[]")
    except Exception:
        inv = []

    parts = message.text.split()
    if len(parts) < 4:
        # Format yetarli emas – inventarni
va to'g'ri formatni ko'rsatamiz
        if not inv:

```

```

bot.send_message(message.chat.id, "🛒
Sizning inventaringiz bo'sh – sotadigan
narsangiz yo'q.")
    return
    lines = ["🛒 <b>Sizning
inventaringizdagi buyumlar:</b>\n"]
    for idx, item in enumerate(inv, 1):
        lines.append(f"{idx}. {item}")
    lines.append(
        "\n<i>Sotish uchun: </i>
<code>/sell &lt;raqam&gt;
&lt;dollar|diamond|coin&gt; &lt;narx&gt;
</code>"
        "\n<i>Masalan: </i><code>/sell
1 diamond 25</code>"
    )
    bot.send_message(message.chat.id,
"\n".join(lines))
    return

    currency = parts[2].lower()
    if currency not in CURRENCY_ICON:
        bot.send_message(message.chat.id,
"⚠️ Valyuta faqat <code>dollar</code>,
<code>diamond</code> yoki <code>coin</code>
bo'lishi kerak!")
        return

    try:
        item_index = int(parts[1]) - 1
        price = int(parts[3])
    except ValueError:
        bot.send_message(message.chat.id,
"⚠️ Raqam va narx faqat butun sonlardan

```

```

iborat bo'lishi kerak!")
    return

    if price <= 0:
        bot.send_message(message.chat.id,
            "⚠️ Narx musbat son bo'lishi kerak!")
        return
    if item_index < 0 or item_index >=
len(inv):
        bot.send_message(message.chat.id,
            "⚠️ Bunday raqamli buyum inventaringizda
yo'q!")
        return

    item_to_sell =
remove_inventory_item_by_index(uid,
item_index)
    if item_to_sell is None:
        bot.send_message(message.chat.id,
            "⚠️ Bunday raqamli buyum inventaringizda
yo'q!")
        return

    icon = CURRENCY_ICON[currency]
    seller_name =
message.from_user.first_name
    with db_lock:
        cur.execute(
            "INSERT INTO market_listings
(chat_id, seller_id, seller_name, item,
price, active, currency) VALUES
(?,?,?, ?, ?, 1, ?)",
            (message.chat.id, uid,
seller_name, item_to_sell, price,

```

```

currency),
    )
    conn.commit()
    listing_id = cur.lastrowid

    kb = types.InlineKeyboardMarkup()
    kb.add(types.InlineKeyboardButton(f"🛒
Sotib olish ({price} {icon})",
callback_data=f"mbuy|{listing_id}"))
    bot.send_message(
        message.chat.id,
        f"🇧🇪 <b>Qora bozorda yangi e'lon!
</b>\n\n"
        f"📦 Narsa: <b>{item_to_sell}
</b>\n"
        f"💰 Narx: <b>{price}</b> {icon}\n"
        f"👤 Sotuvchi: {seller_name}\n"
        f"🆔 E'lon ID: <code>{listing_id}
</code>",
        reply_markup=kb,
    )

@bot.message_handler(commands=["osh"])
def cmd_osh(message):
    """🍷 Milliy osh – o'zingizga emas,
GURUHDAGI boshqa bir o'yinchiga ziyofat
berish uchun: unga bir martalik himoya
(shield) va (turiga qarab) qo'shimcha
qobiliyat sovg'a qiladi – pul emas.
Foydalanish: reply qilib /osh <turi>."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not message.reply_to_message:

```



```

        lines = ["🍷 <b>Milliy Osh
Menyusi</b> – do'stingizga ziyofat bering
(pul emas, qobiliyat sovg'a qilasiz)!\n"]
        for key, item in SHOP_OSH.items():
            extra = f" + 1x
{TOGGLEABLE_ITEMS.get(item['gift_charge']
[0], item['gift_charge'][0])}" if
item.get("gift_charge") else ""
            lines.append(f"<code>{key}
</code> – {item['name']} (${item['price']})
→ {item['gift_shield']}🛡️{extra}")
            lines.append("\n<i>Foydalanish:
kimningdir xabariga reply qilib </i>
<code>/osh &lt;turi&gt;</code>")
            bot.send_message(message.chat.id,
"\n".join(lines))
            return
        parts = message.text.split()
        if len(parts) != 2 or parts[1].lower()
not in SHOP_OSH:
            bot.send_message(message.chat.id,
"Foydalanish: <code>/osh &lt;turi&gt;
</code> (masalan: <code>/osh toy</code>) –
turlar uchun reply'siz /osh deb yozing.")
            return
        key = parts[1].lower()
        item = SHOP_OSH[key]
        sender = message.from_user
        target =
message.reply_to_message.from_user
        if target.id == sender.id:
            bot.send_message(message.chat.id,
"❌ O'zingizga ziyofat berolmaysiz – bu
boshqa o'yinchiga sovg'a.")

```

```

        return
        u = user_dict(sender.id,
sender.first_name)
        user_dict(target.id, target.first_name
or "O'yinchi")
        if u["dollar"] < item["price"]:
            bot.send_message(message.chat.id,
f"❌ Yetarli mablag' yo'q (${item['price']}
kerak).")
            return
            update_user(sender.id,
dollar=u["dollar"] - item["price"])
            add_shield(target.id,
item["gift_shield"])
            extra_text = ""
            if item.get("gift_charge"):
                ck, amount = item["gift_charge"]
                add_charge(target.id, ck, amount)
                extra_text = f" + {amount}x
{TOGGLEABLE_ITEMS.get(ck, ck)}"
            bot.send_message(
                message.chat.id,
                f"{item['name']}!
{mention(sender.id, sender.first_name)} –
{mention(target.id, target.first_name)}ga
ziyofat berdi!\n"
                f"🎁 {target.first_name} +
{item['gift_shield']}🛡️{extra_text} sovg'a
oldi.",
                )

@bot.message_handler(commands=["market"])
def cmd_market(message):

```

```

        maybe_capture_owner(message.from_user)
        safe_delete(message)
        if not
_in_black_market_group(message.chat.id):
            bot.send_message(
                message.chat.id,
                "🚫 Qora bozor faqat maxsus
savdo guruhida ishlaydi. Guruhga
qo'shiling: "
                "https://t.me/+v9bYoMk-
0hAyZTcy",
            )
            return
        with db_lock:
            cur.execute(
                "SELECT id, item, price,
seller_name, currency FROM market_listings
WHERE chat_id=? AND active=1 ORDER BY id
DESC LIMIT 30",
                (message.chat.id,),
            )
            rows = cur.fetchall()
            if not rows:
                bot.send_message(
                    message.chat.id,
                    "🛒 Hozirda qora bozorda
sotuvdagi buyumlar yo'q.\n"
                    "O'z narsangizni sotish uchun
<code>/sell <raqam>
<dollar|diamond|coin> <narx>
</code> buyrug'idan foydalaning.",
                )
            return
        lines = ["🛒 <b>Qora bozordagi faol

```

```

e'lonlar:</b>\n"]
    for listing_id, item, price,
seller_name, currency in rows:
        icon = CURRENCY_ICON.get(currency
or "coin", "🪙")
        lines.append(f"ID <code>
{listing_id}</code> | 📦 <b>{item}</b> - 💰
{price} {icon} | 👤 {seller_name}")
        lines.append("\n<i>Sotib olish uchun
e'londagi tugmani bosib yoki: </i>
<code>/buy &lt;ID&gt;</code>")
        bot.send_message(message.chat.id,
"\n".join(lines))

@bot.message_handler(commands=["buy"])
def cmd_buy(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not
_in_black_market_group(message.chat.id):
        bot.send_message(
            message.chat.id,
            "🚫 Qora bozor faqat maxsus
savdo guruhida ishlaydi. Guruhga
qo'shiling: "
            "https://t.me/+v9bYoMk-
0hAyZTcy",
        )
        return
    if is_banned(message.from_user.id):
        return
    parts = message.text.split()
    if len(parts) != 2 or not

```

```

parts[1].isdigit():
    bot.send_message(message.chat.id,
        "Foydalanish: <code>/buy &lt;E'lon_ID&gt;
        </code>")
    return

_show_market_buy_confirm(message.chat.id,
    None, int(parts[1]), message.from_user.id)

def _show_market_buy_confirm(chat_id,
    message_id, listing_id, buyer_id):
    with db_lock:
        cur.execute("SELECT item, price,
            seller_id, seller_name, currency FROM
            market_listings WHERE id=? AND active=1",
            (listing_id,))
        row = cur.fetchone()
        if not row:
            bot.send_message(chat_id, "❌ Bu
            buyum allaqachon sotilgan yoki e'lon
            topilmadi!")
            return
        item, price, seller_id, seller_name,
        currency = row
        icon = CURRENCY_ICON.get(currency or
            "coin", "🪙")
        if seller_id == buyer_id:
            bot.send_message(chat_id, "❌ O'z
            narsangizni o'zingiz sotib ololmaysiz!")
            return
        kb = types.InlineKeyboardMarkup()
        kb.add(
            types.InlineKeyboardButton("✅ Ha,

```

```

sotib olaman", callback_data=f"mconfirm|
{listing_id}"),
        types.InlineKeyboardButton("✖
Bekor qilish", callback_data="mcancel"),
    )
    bot.send_message(chat_id, f"❓ <b>
{item}</b>ni {price} {icon} evaziga
haqiqatan ham sotib olmoqchimisiz?",
reply_markup=kb)

```

```

@bot.callback_query_handler(func=lambda c:
c.data.startswith("mbuy|"))
def cb_market_buy(call):
    maybe_capture_owner(call.from_user)
    if not
_in_black_market_group(call.message.chat.id
):
        bot.answer_callback_query(call.id,
"🚫 Qora bozor faqat maxsus savdo guruhida
ishlaydi.", show_alert=True)
        return
        listing_id = int(call.data.split("|")
[1])
        with db_lock:
            cur.execute("SELECT item, price,
seller_id, seller_name, currency FROM
market_listings WHERE id=? AND active=1",
(listing_id,))
            row = cur.fetchone()
            if not row:
                bot.answer_callback_query(call.id,
"✖ Bu buyum allaqachon sotilgan!",
show_alert=True)

```

```

        return
        item, price, seller_id, seller_name,
currency = row
        icon = CURRENCY_ICON.get(currency or
"coin", "🪙")
        if seller_id == call.from_user.id:
            bot.answer_callback_query(call.id,
"❌ O'z narsangizni o'zingiz sotib
ololmaysiz!", show_alert=True)
            return
        bot.answer_callback_query(call.id)
        kb = types.InlineKeyboardMarkup()
        kb.add(
            types.InlineKeyboardButton("✅ Ha,
sotib olaman", callback_data=f"mconfirm|
{listing_id}"),
            types.InlineKeyboardButton("❌
Bekor qilish", callback_data="mcancel"),
        )
        try:
            bot.edit_message_text(
                f"❓ <b>{item}</b>ni {price}
{icon} evaziga haqiqatan ham sotib
olmoqchimisiz?",
                call.message.chat.id,
call.message.message_id, reply_markup=kb,
            )
        except Exception:
            bot.send_message(call.message.chat.id, f"❓
<b>{item}</b>ni {price} {icon} evaziga
haqiqatan ham sotib olmoqchimisiz?",
reply_markup=kb)

```

```

@bot.callback_query_handler(func=lambda c:
c.data.startswith("mconfirm|") or c.data ==
"mcancel")
def cb_market_confirm(call):
    maybe_capture_owner(call.from_user)
    if call.data == "mcancel":
        bot.answer_callback_query(call.id,
        "🚫 Savdo bekor qilindi.", show_alert=True)
        try:

            bot.delete_message(call.message.chat.id,
            call.message.message_id)
            except Exception:
                pass
            return

        if not
        _in_black_market_group(call.message.chat.id
        ):
            bot.answer_callback_query(call.id,
            "🚫 Qora bozor faqat maxsus savdo guruhida
            ishlaydi.", show_alert=True)
            return

        listing_id = int(call.data.split("|")
        [1])
        buyer_id = call.from_user.id

        with db_lock:
            cur.execute("SELECT item, price,
            seller_id, seller_name, active, currency
            FROM market_listings WHERE id=?",
            (listing_id,))

```



```

        row = cur.fetchone()
        if not row or row[4] != 1:

            bot.answer_callback_query(call.id, "❌
            Xatolik: e'lon topilmadi yoki allaqachon
            sotilgan!", show_alert=True)
            return
            item, price, seller_id,
seller_name, _, currency = row
            currency = currency or "coin"
            icon = CURRENCY_ICON.get(currency,
            "🪙")
            if seller_id == buyer_id:

                bot.answer_callback_query(call.id, "❌ O'z
                narsangizni o'zingiz sotib ololmaysiz!",
                show_alert=True)
                return
                buyer = user_dict(buyer_id,
                call.from_user.first_name)
                if buyer[currency] < price:
                    bot.answer_callback_query(
                        call.id,
                        f"❌ {icon} yetarli emas!
                        Sizda {buyer[currency]} {icon} bor, kerak:
                        {price} {icon}.",
                        show_alert=True,
                    )
                    return
                    cur.execute("UPDATE market_listings
                    SET active=0 WHERE id=?", (listing_id,))
                    conn.commit()

            add_balance(buyer_id, **{currency: -

```

```

price})
    add_balance(seller_id, **{currency:
price})
    add_inventory_item(buyer_id, item)

    bot.answer_callback_query(call.id, f"🎉
Tabriklaymiz! {item} muvaffaqiyatli sotib
olindi!", show_alert=True)
    seller_mention = mention(seller_id,
seller_name)
    buyer_mention = mention(buyer_id,
call.from_user.first_name)
    try:
        bot.edit_message_text(
            f"✅ <b>Savdo muvaffaqiyatli
yakunlandi!</b>\n\n"
            f"📦 Narsa: {item}\n👤
Sotuvchi: {seller_mention}\n🛒 Xaridor:
{buyer_mention}\n"
            f"$ Narx: {price} {icon}",
            call.message.chat.id,
            call.message.message_id,
        )
    except Exception:
        bot.send_message(
            call.message.chat.id,
            f"✅ <b>Savdo muvaffaqiyatli
yakunlandi!</b>\n\n"
            f"📦 Narsa: {item}\n👤
Sotuvchi: {seller_mention}\n🛒 Xaridor:
{buyer_mention}\n"
            f"$ Narx: {price} {icon}",
        )

```

```

#
=====
=====
# KUNDUZGI OVOZ BERISH BOSQICHI
#
=====
=====

def start_day(chat_id):
    """☀ Kunduzgi bosqich: avval
DAY_DISCUSSION_SECONDS soniya muhokama,
so'ng
    ovoz berish tugmalari chiqadi va yana
DAY_VOTE_SECONDS soniya davom etadi.
    Kunning umumiy uzunligi:
DAY_TOTAL_SECONDS (= DAY_DISCUSSION_SECONDS
+ DAY_VOTE_SECONDS)."""
    game = GAMES.get(chat_id)
    if not game:
        return
    game["phase"] = "day"
    game["votes"] = {}
    game["voting_open"] = False
    game["spoke_before_vote_today"] = set()
    game["vote_order"] = []
    game["no_lynch_today"] = False
    game["fog_today"] = False
    game["hero_armed_vote_shield"] = set()
    vote_seconds = DAY_VOTE_SECONDS

    # 🏆 Geroy (Draven/Zephyrion "Xalq
himoyasi") – hali sarflanmagan bo'lsa,
kunduzi eslatma

```

```

        for uid, p in
alive_players(game).items():
            if hero_has_ability(uid,
"vote_shield_once") and uid not in
game.get("hero_vote_shield_used", set()):
                kb =
types.InlineKeyboardMarkup()

kb.add(types.InlineKeyboardButton("🛡️ Xalq
himoyasini faollashtirish",
callback_data=f"heroarm|voteshield|
{chat_id}"))
                safe_send(uid, "🏆
Geroyingizning bir martalik 🛡️ Xalq
himoyasi qobiliyati bor. Xohlasangiz, "
                        "bugungi kun
uchun faollashtiring (aks holda
ishlamaydi):", kb)

# 🎲 Random event – har kuni 15%
ehtimol bilan, ENDI HAR BIRI HAQIQIY TA'SIR
QILADI
        if random.random() < 0.15:
            event =
random.choice(RANDOM_EVENTS)
            bot.send_message(chat_id, f"🎲
<b>O'YIN DAVOMIDA KUTILMAGAN HODISA!
</b>\n\n{event['text']}")
            key = event["key"]
            if key == "lucky_all":
                for uid in alive_players(game):
                    add_balance(uid, dollar=50)
            elif key == "lucky_one":
                alive_uids =

```

```

list(alive_players(game).keys())
    if alive_uids:
        lucky_uid =
random.choice(alive_uids)
        add_balance(lucky_uid,
dollar=100)
        safe_send(lucky_uid, "🎁
Tabriklaymiz! Bugungi tasodifiy hodisadan
sizga +100$ tushdi!")
        elif key == "no_lynch":
            game["no_lynch_today"] = True
        elif key == "weak_night":
            game["weak_night_today"] = True
        elif key == "fog":
            game["fog_today"] = True
        elif key == "short_vote":
            vote_seconds = 15
            game["vote_seconds_today"] =
vote_seconds

        send_scene_photo(
            chat_id, DAY_PHOTO_LOCAL,
DAY_PHOTO,
            caption=f"☀️ <b>
{game['day_number']}-kun.</b> Muhokama
qiling – {DAY_DISCUSSION_SECONDS} soniyadan
so'ng "

            "ovoz berish tugmalari
shaxsiy chatingizga tushadi. 🗣️",
            reply_markup=_bot_dm_button(),
        )

        t =
threading.Timer(DAY_DISCUSSION_SECONDS,

```

```

lambda: open_day_voting(chat_id))
    t.daemon = True
    t.start()
    game["timers"].append(t)

    # 🔄 checkpoint
    game["day_sub_phase"] = "discussion"
    game["phase_deadline"] = time.time() +
DAY_DISCUSSION_SECONDS
    save_games_state()

def open_day_voting(chat_id):
    """Muhokama vaqti
(DAY_DISCUSSION_SECONDS) tugagach
chaqiriladi – ovoz berish tugmalarini
    tirik o'yinchilarning shaxsiy chatiga
yuboradi va DAY_VOTE_SECONDS soniyalik
hisobni boshlaydi."""
    game = GAMES.get(chat_id)
    if not game or game["phase"] != "day":
        return
    game["voting_open"] = True
    vote_seconds =
game.get("vote_seconds_today",
DAY_VOTE_SECONDS)

    # 🧑 Missiya kuzatuvi – ovoz ochilgunga
qadar bir marta ham yozmagan tirik
    # o'yinchilar "jim o'tirish"
missiyasini shu kunda bajargan hisoblanadi
    spoke =
game.get("spoke_before_vote_today", set())
    for uid in alive_players(game):

```

```

        if uid not in spoke:

game.setdefault("silent_before_vote_ever",
set()).add(uid)

        bot.send_message(
            chat_id,
            f"🗳️ <b>Ovoz berish boshlandi!</b>
Sizda {vote_seconds} soniya vaqt bor – "
            "botning shaxsiy chatida kimni
osish kerakligini tanlang.",
            reply_markup=_bot_dm_button(),
        )

        # 🐱🦅 Jamoaviy rejimda – ovoz berish
tugmalari chiqishidan OLDIN, har bir
        # o'yinchiga o'z jamodoshlari ro'yxati
eslatma qilib yuboriladi.
        send_squad_reminders(game)

        alive = alive_players(game)
        for voter_id in alive:
            # 🐱🦅 Har bir o'yinchi uchun
tugmalar ALOHIDA quriladi, chunki
            # jamodosh belgisi (🐱/🦅) faqat
SHU o'yinchining ko'zida ko'rinishi
            # kerak – boshqalar uchun o'sha
odam boshqa jamoada bo'lishi mumkin.
            kb = types.InlineKeyboardMarkup()
            for uid, p in alive.items():
                tag = squad_tag(game, voter_id,
uid)

kb.add(types.InlineKeyboardButton(f"{tag}

```

```

{p['name']}", callback_data=f"dv|{chat_id}|{uid}")

kb.add(types.InlineKeyboardButton("🚫  
O'tkazib yuborish", callback_data=f"dv|{chat_id}|skip"))

ok = safe_send(voter_id, "🗳️  
<b>Kimni mafiya deb hisoblaysiz?</b> Ovoz  
berish uchun tanlang:", kb)
if not ok:
    bot.send_message(
        chat_id,
        f"⚠️ {mention(voter_id, alive[voter_id]['name'])}, botga ovoz  
berish uchun avval "  
f"shaxsiy xabarlarda /start  
bosing!",

reply_markup=_bot_dm_button(),
    )

t = threading.Timer(vote_seconds,
lambda: resolve_day(chat_id))
t.daemon = True
t.start()
game["timers"].append(t)

# 🔄 checkpoint
game["day_sub_phase"] = "voting"
game["phase_deadline"] = time.time() +
vote_seconds
save_games_state()

```



```

@bot.callback_query_handler(func=lambda c:
c.data.startswith("dv|"))
def cb_vote(call):
    maybe_capture_owner(call.from_user)
    _, chat_id_s, target_s =
call.data.split("|")
    chat_id = int(chat_id_s)
    game = GAMES.get(chat_id)
    voter_id = call.from_user.id

    if not game or game["phase"] != "day":
        bot.answer_callback_query(call.id,
        "Ovoz berish yakunlangan.")
        return
    if not game.get("voting_open"):
        bot.answer_callback_query(call.id,
        "🕒 Ovoz berish hali boshlanmadi – avval
        muhokama davri tugashini kuting.",
        show_alert=True)
        return
    if voter_id not in game["players"] or
    not game["players"][voter_id]["alive"]:
        bot.answer_callback_query(call.id,
        "Faqat tirik ishtirokchilar ovoz bera
        oladi.")
        return

    target = target_s if target_s == "skip"
    else int(target_s)
    game["votes"][voter_id] = target
    game.setdefault("activity_score", {})
    game["activity_score"][voter_id] =
    game["activity_score"].get(voter_id, 0) + 1
    game.setdefault("vote_order", [])

```

```

        if voter_id in game["vote_order"]:

game["vote_order"].remove(voter_id) #
qayta ovoz bersa, oxirgi o'ringa ko'chadi
        game["vote_order"].append(voter_id)
        voter_name = game["players"][voter_id]
        ["name"]
        target_name = "o'tkazib yuborish" if
target == "skip" else game["players"]
[target]["name"]

        revote_left =
get_charges(voter_id).get("revote", 0)
        kb = None
        if revote_left > 0:
            kb = types.InlineKeyboardMarkup()

kb.add(types.InlineKeyboardButton(f"🔄
Ovozni o'zgartirish ({revote_left} ta
qoldi)", callback_data=f"revote|
{chat_id}"))
        try:
            bot.edit_message_text(f"✅ Siz <b>
{target_name}</b> deb ovoz berdingiz.",
call.message.chat.id,
call.message.message_id, reply_markup=kb)
        except Exception:
            pass
        bot.answer_callback_query(call.id,
f"Siz {target_name} deb ovoz berdingiz.")
        target_mention = "o'tkazib yuborish" if
target == "skip" else mention(target,
game["players"][target]["name"])
        # 🛠️ TUZATILDI: avval faqat NISHON ismi

```

```

bosiladigan edi – endi OVOZ BERUVCHINING
    # ismi ham bosilganda uning profiliga
o'tadi (barcha nik-neymlar izchil
bosiladigan).
    bot.send_message(chat_id, f"🗳️
{mention(voter_id, voter_name)} ovoz berdi:
{target_mention}")

@bot.callback_query_handler(func=lambda c:
c.data.startswith("revote|"))
def cb_revote(call):
    """⚡ Energiya ichimligi – kunduzi ovoz
bergandan keyin fikrni o'zgartirib,
qayta ovoz berish imkonini beradi
(charge tugaguncha)."""
    maybe_capture_owner(call.from_user)
    _, chat_id_s = call.data.split("|")
    chat_id = int(chat_id_s)
    game = GAMES.get(chat_id)
    voter_id = call.from_user.id
    if not game or game["phase"] != "day"
or not game.get("voting_open"):
        bot.answer_callback_query(call.id,
"Ovoz berish yakunlangan.")
        return
    if voter_id not in game["players"] or
not game["players"][voter_id]["alive"]:
        bot.answer_callback_query(call.id,
"Faqat tirik ishtirokchilar ovoz bera
oladi.")
        return
    if not use_charge(voter_id, "revote"):
        bot.answer_callback_query(call.id,

```

```

"❌ Qayta ovoz berish huquqingiz
qolmagan.", show_alert=True)
    return
    kb = types.InlineKeyboardMarkup()
    for target_id, p in
alive_players(game).items():
        tag = squad_tag(game, voter_id,
target_id)

kb.add(types.InlineKeyboardButton(f"{tag}
{p['name']}", callback_data=f"dv|{chat_id}|
{target_id}"))
    kb.add(types.InlineKeyboardButton("🚫
O'tkazib yuborish", callback_data=f"dv|
{chat_id}|skip"))
    try:
        bot.edit_message_text("🔄
<b>Ovozingizni qayta tanlang:</b>",
call.message.chat.id,
call.message.message_id, reply_markup=kb)
    except Exception:
        bot.send_message(chat_id if False
else voter_id, "🔄 <b>Ovozingizni qayta
tanlang:</b>", reply_markup=kb)
        bot.answer_callback_query(call.id, "✅
Qayta ovoz berishingiz mumkin!")

def resolve_day(chat_id):
    with GAME_LOCK:
        game = GAMES.get(chat_id)
        if not game or game["phase"] !=
"day":
            return

```

```

        for uid, p in
alive_players(game).items():
            if uid not in game["votes"]:
                game["votes"][uid] = "skip"

        # 🗣️ Provokator – belgilangan
o'yinchining ovozi majburan boshqaga
buriladi
        for forced_uid, forced_target in
game.get("forced_day_votes", {}).items():
            if forced_uid in game["votes"]
and game["players"].get(forced_uid,
{}).get("alive"):
                game["votes"][forced_uid] =
forced_target

        # 🧑 Missiya kuzatuvi – ovoz berish
statistikasi (birinchi/oxirgi ovoz
beruvchi,
        # o'ziga/skip ovoz berganlar,
mafiya nishoniga qarshi ovoz berganlar)
        vote_order = game.get("vote_order",
[])

        if vote_order:

game.setdefault("first_voter_ever",
set()).add(vote_order[0])

game.setdefault("last_voter_ever",
set()).add(vote_order[-1])
        mafia_target =
game.get("last_night_mafia_target")
        for voter, target in

```

```

game["votes"].items():
    if target == voter:

game.setdefault("self_vote_ever",
set()).add(voter)
    if target == "skip":

game.setdefault("skip_vote_ever",
set()).add(voter)
    if mafia_target is not None and
target == mafia_target:

game.setdefault("anti_mafia_vote_ever",
set()).add(voter)

# 🧑 Sudya – agar shu tunda
faollashtirgan bo'lsa, uning ovozi 2x
kuchga ega
# 👑 Geroy (Magnus/Zephyrion
"General nufuzi") – qo'shimcha +1 ovoz
og'irligi
    tally = {}
    for voter, target in
game["votes"].items():
        if target == "skip":
            continue
        weight = 2 if
game.get("judge_double_vote") == voter else
1
        weight +=
hero_vote_weight_bonus(voter)
        tally[target] =
tally.get(target, 0) + weight

```

```

        if not tally:
            bot.send_message(chat_id, "👤\nHech kim ovoz bermadi, shuning uchun bugun hech kim osilmaydi.")
            finish_day_phase(chat_id)
            return

        max_v = max(tally.values())
        top = [uid for uid, v in
tally.items() if v == max_v]
        if len(top) > 1:
            bot.send_message(chat_id, "⚖️\n<b>Ovoz berish yakunlandi:</b>\nAholi kelisha olmadi... Kelisha olmaslik oqibatida hech kim osilmadi.")
            finish_day_phase(chat_id)
            return

        hanged = top[0]
        # 👤 Missiya kuzatuvchi – ko'pchilik tanlagan (hozirgi eng ko'p ovoz olgan) kishiga
        # ovoz bergan har bir o'yinchi uchun "vote_majority" missiyasi bajarilgan hisoblanadi
        for voter, target in
game["votes"].items():
            if target == hanged:

game.setdefault("majority_vote_ever",
set()).add(voter)

        if game.get("no_lynch_today"):
            bot.send_message(

```

```

        chat_id,
        f"🔍 <b>Taqdir hukmi
kuchda!</b> {mention(hanged,
game['players'][hanged]['name'])} eng ko'p
ovoz oldi, "

        "ammo bugungi tasodifiy
hodisa tufayli hech kim osilmaydi.",
    )
    finish_day_phase(chat_id)
    return

    # 🏆 Geroy (Draven "Xalq himoyasi")
    – FAQAT o'zi /geroy_himoya bilan shu kunga
    # QO'LDA faollashtirgan bo'lsa
    ishlaydi (avtomatik EMAS), va faqat 1 marta
    o'yin davomida
    if (hanged in
game.get("hero_armed_vote_shield", set())
        and
hero_has_ability(hanged,
"vote_shield_once")
        and hanged not in
game.setdefault("hero_vote_shield_used",
set())):

game["hero_vote_shield_used"].add(hanged)
    bot.send_message(
        chat_id,
        f"🗡️🏆 <b>Geroy qobiliyati
ishga tushdi!</b> {mention(hanged,
game['players'][hanged]['name'])} "
        "eng ko'p ovoz oldi, ammo
geroyining himoyasi tufayli bu safar
osilmaydi! (Qobiliyat sarflandi.)",

```



```

        )
        for voter_uid in game["votes"]:
            if game["votes"][voter_uid]
== hanged:
                safe_send(voter_uid,
                "🗳️🏆 <i>Ovoz bergan nishoningiz kimningdir
                geroy qobiliyati tufayli linchdan qutulib
                qoldi...</i>")
                finish_day_phase(chat_id)
                return
            if game["players"]
[hanged].get("smoke_active"):
                game["players"][hanged]
["smoke_active"] = False
                bot.send_message(
                    chat_id,
                    f"🗨️ Aholi {mention(hanged,
game['players'][hanged]['name'])}ni
                osmoqchi bo'ldi, "
                    f"lekin 💣 Tutunli bomba
                tutuni ostida u qochib qutuldi! Bugun hech
                kim osilmadi.",
                )
                finish_day_phase(chat_id)
                return

        # 🗳️ Eng ko'p ovoz olgan
        ishtirokchi aniqlandi – endi guruhga uning
        bosilsa
            # Telegram profiliga o'tadigan
            nikneyimi bilan yakuniy tasdiqlash ovoz
            berishi ochiladi.
            start_hang_confirmation(chat_id,
            hanged)

```

```

def _confirm_kb(chat_id, yes_n, no_n):
    kb = types.InlineKeyboardMarkup()
    kb.add(
        types.InlineKeyboardButton(f"👍 Ha,
osish ({yes_n})", callback_data=f"dvc|
{chat_id}|yes"),
        types.InlineKeyboardButton(f"👎
Yo'q, osmaslik ({no_n})",
callback_data=f"dvc|{chat_id}|no"),
    )
    return kb

```

```

def start_hang_confirmation(chat_id,
target_uid):
    """Eng ko'p ovoz olgan ishtirokchini
haqiqatan ham osish-osmaslik haqida
guruhda 👍/👎 tasdiqlash ovoz berishini
boshlaydi. Har bir tirik o'yinchi
faqat bitta ovozga ega bo'ladi."""
    game = GAMES.get(chat_id)
    if not game:
        return
    name = game["players"][target_uid]
    ["name"]
    game["confirm_vote"] = {"target":
target_uid, "yes": set(), "no": set(),
"message_id": None}
    text = (
        f"🗳️ <b>Eng ko'p ovoz olgan
ishtirokchi:</b> {mention(target_uid,
name)}}\n\n"

```

```

        f" ? Siz rostan ham bu
ishtirokchini osmoqchimisiz?"
    )
    sent = bot.send_message(chat_id, text,
reply_markup=_confirm_kb(chat_id, 0, 0))
    game["confirm_vote"]["message_id"] =
sent.message_id

    t =
threading.Timer(CONFIRM_VOTE_SECONDS,
lambda: resolve_hang_confirmation(chat_id))
    t.daemon = True
    t.start()
    game["timers"].append(t)

    # 🔄 checkpoint
    game["phase_deadline"] = time.time() +
CONFIRM_VOTE_SECONDS
    save_games_state()

@bot.callback_query_handler(func=lambda c:
c.data.startswith("dvc|"))
def cb_confirm_vote(call):
    maybe_capture_owner(call.from_user)
    _, chat_id_s, choice =
call.data.split("|")
    chat_id = int(chat_id_s)
    game = GAMES.get(chat_id)
    uid = call.from_user.id
    cv = game.get("confirm_vote") if game
else None

    if not game or not cv:

```

```

        bot.answer_callback_query(call.id,
        "Bu ovoz berish yakunlangan.")
        return
        if uid not in game["players"] or not
        game["players"][uid]["alive"]:
            bot.answer_callback_query(call.id,
            "Faqat tirik ishtirokchilar ovoz bera
            oladi.")
            return

        # bitta o'yinchi – har bir tasdiqlash
        ovoz berishida bitta ovozga ega
        cv["yes"].discard(uid)
        cv["no"].discard(uid)
        if choice == "yes":
            cv["yes"].add(uid)
        else:
            cv["no"].add(uid)

        try:

        bot.edit_message_reply_markup(chat_id,
        cv["message_id"],
        reply_markup=_confirm_kb(chat_id,
        len(cv["yes"]), len(cv["no"])))
        except Exception:
            pass
            bot.answer_callback_query(call.id,
            "Ovozingiz qabul qilindi!")

        if len(cv["yes"]) + len(cv["no"]) >=
        len(alive_players(game)):
            resolve_hang_confirmation(chat_id)

```

```

def resolve_hang_confirmation(chat_id):
    with GAME_LOCK:
        game = GAMES.get(chat_id)
        cv = game.get("confirm_vote") if
game else None
        if not game or not cv:
            return
        game["confirm_vote"] = None
        target_uid = cv["target"]
        yes_n, no_n = len(cv["yes"]),
len(cv["no"])

        if target_uid not in
game["players"] or not game["players"]
[target_uid]["alive"]:
            finish_day_phase(chat_id)
            return
        name = game["players"][target_uid]
["name"]

        if yes_n <= no_n:
            bot.send_message(
                chat_id,
                f"👤 Ovoz berish natijasi:
👍 {yes_n} – 👎 {no_n}.\nAholi rahm qildi,
bugun hech kim osilmadi.",
            )
            finish_day_phase(chat_id)
            return

        # ⚖️ Advokat himoyasi yoki 🛡️🔥
Kunduzgi himoya buyumi – bittasi bo'lsa
yetarli

```

```

        protected_by_advokat =
game.get("advocate_protect") == target_uid
        has_day_shield =
get_charges(target_uid).get("day_shield",
0) > 0 and is_item_active(target_uid,
"day_shield")
        if protected_by_advokat or
has_day_shield:
            if has_day_shield:
                use_charge(target_uid,
"day_shield")
                reason = "🛡️💣 Kunduzgi
himoya tumori"
            else:
                reason = "⚖️ Advokat
himoyasi"
            bot.send_message(
                chat_id,
                f"{reason} tufayli
{mention(target_uid, name)} osilishdan
qutulib qoldi! (👍 {yes_n} – 👎 {no_n})",
                )
            finish_day_phase(chat_id)
            return

        game["players"][target_uid]
["alive"] = False
        role = game["players"][target_uid]
["role"]
        bot.send_message(
            chat_id,
            f"👉 Ovoz berish natijasi: 👍
{yes_n} – 👎 {no_n}.\n"
            f"Aholi {mention(target_uid,

```

```

name)}}ni osdi.\n"
        f"Fosh qilingan roli: <b>{role}
</b> edi.",
    )
    wait_last_words(chat_id,
target_uid)
    handle_death_side_effects(game,
chat_id, target_uid) # 🧨 Don vorisligi /
🤪 Arvoh faollashuvi

    # 💣 Terrorist – uni kunduzi osib
o'ldirishsa, o'zi bilan birga tasodifiy
odamni ham portlatib ketadi
    if role == "Terrorist 💣":
        others = [pid for pid in
alive_players(game) if pid != target_uid]
        if others:
            boom_target =
random.choice(others)
            game["players"]
[boom_target]["alive"] = False
            bot.send_message(
                chat_id,
                f"💣
{mention(target_uid, name)} portlab, o'zi
bilan birga "
                    f"{mention(boom_target,
game['players'][boom_target]['name'])}ni
ham olib ketdi!",
                )
            wait_last_words(chat_id,
boom_target)

    handle_death_side_effects(game, chat_id,

```

```
boom_target) # 🧨 Don vorisligi / 🤖 Arvoh  
faollashuvi
```

```
finish_day_phase(chat_id)
```

```
def finish_day_phase(chat_id):  
    game = GAMES.get(chat_id)  
    if not game:  
        return  
  
    # 👁 Kuzatish ko'zi – to'liq ovoz  
    taqsimotini DM orqali yuborish  
    # 📁 Shubhali sumka – "hidden_vote"  
    charge'i faol bo'lgan o'yinchining ovozi  
    # bu hisobotda "noma'lum" bo'lib  
    ko'rinadi (1 marta ishlatiladi)  
    vote_lines = []  
    for voter, target in  
game["votes"].items():  
        voter_name =  
game["players"].get(voter, {}).get("name",  
"?")  
  
        if  
get_charges(voter).get("hidden_vote", 0) >  
0 and is_item_active(voter, "hidden_vote"):  
            use_charge(voter,  
"hidden_vote")  
            vote_lines.append(f"•  
{voter_name} → 🧑 noma'lum (buyum bilan  
yashiringan)")  
  
            # 🔧 TUZATILDI: avval bu yerda  
            hech qanday DM yuborilmas edi  
            safe_send(voter, "📁 Sizning
```



```

<b>Shubhali sumka</b> buyumingiz ishladi –
bu safar ovozingiz boshqalardan
yashirildi!")

        continue
        target_name = "o'tkazib yuborish"
    if target == "skip" else
    game["players"].get(target, {}).get("name",
    "?")

        vote_lines.append(f"• {voter_name}
→ {target_name}")
        for uid, p in
list(game["players"].items()):
            ch = get_charges(uid)
            if p["alive"] and
ch.get("watch_eyes", 0) > 0 and
is_item_active(uid, "watch_eyes"):
                use_charge(uid, "watch_eyes")
                safe_send(uid, "👁 <b>To'liq
ovoz taqsimoti:</b>\n" +
"\n".join(vote_lines))

        if check_and_end_game(chat_id):
            return
        bot.send_message(chat_id,
roster_breakdown_text(game))
        game["day_number"] += 1
        start_night(chat_id)

#
=====
=====
#  G'ALABA SHARTI VA MUKOFOTLAR
#

```

```
=====
=====
```

```
def check_and_end_game(chat_id):
    game = GAMES.get(chat_id)
    if not game:
        return True
    alive = alive_players(game)

    # 💍 Para (couple) rejimi: agar oxirgi
    tirik qolgan aynan BITTA juftlikning
    # ikkalasi bo'lsa (rollaridan qat'i
    nazar – biri tinch, biri mafiya bo'lsa
    # ham) – boshqalar hammasi halok
    bo'lgani uchun o'sha juftlik birgalikda
    # G'OLIB deb e'lon qilinadi.
    if game.get("couple_mode") and
    game.get("couple_of") and len(alive) == 2:
        u1, u2 = list(alive.keys())
        if game["couple_of"].get(u1) == u2:
            end_game(chat_id, "couple",
            couple_pair=(u1, u2))
            return True

    # 🐾🦅 Jamoaviy (squad) rejimi: g'alaba
    sharti ODDIY mafiya/tinch aholi
    # balansi EMAS – faqat ikkala jamoning
    BIRI butunlay qirilib ketsa,
    # boshqa jamoa (tirik qolganlar) g'olib
    deb e'lon qilinadi. Shu sababli
    # squad_mode yoqilgan o'yinlarda
    pastdagi oddiy tekshiruv o'tkazib
    # yuboriladi – o'yin faqat jamo
    qirilganda tugaydi.
```

```

        if game.get("squad_mode") and
game.get("squads"):
            wolf_alive = [uid for uid in alive
if game["squads"].get(uid) == "wolf"]
            eagle_alive = [uid for uid in alive
if game["squads"].get(uid) == "eagle"]
            if not wolf_alive and not
eagle_alive:
                end_game(chat_id, "squad_draw")
                return True
            if not wolf_alive:
                end_game(chat_id,
"squad_eagle")
                return True
            if not eagle_alive:
                end_game(chat_id, "squad_wolf")
                return True
            return False

        mafia_alive = [uid for uid, p in
alive.items() if p["team"] == "mafia"]
        other_alive = [uid for uid, p in
alive.items() if p["team"] != "mafia"]

        winners_team = None
        if not mafia_alive:
            winners_team = "town"
        elif len(mafia_alive) >=
len(other_alive):
            winners_team = "mafia"

        if winners_team is None:
            return False

```

```

        end_game(chat_id, winners_team)
        return True

@bot.message_handler(commands=["tark_et"])
def cmd_tark_et(message):
    """ 🎲 O'yinchi o'zi xohlab o'yinni tark
    etadi – u avtomatik mag'lub hisoblanadi
    va o'yin oxirida g'olib jamoada bo'lsa
    ham mukofot olmaydi."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    uid = message.from_user.id
    game = None
    chat_id = None
    for cid, g in GAMES.items():
        if uid in g["players"] and
g["players"][uid]["alive"]:
            game, chat_id = g, cid
            break
    if not game:
        bot.send_message(message.chat.id,
"❌ Siz hozir hech qanday faol o'yinda
emassiz.")
        return
    game["players"][uid]["alive"] = False
    game["players"][uid]["left_game"] =
True
    add_points(uid, -10, "left_game")
    name = game["players"][uid]["name"]
    bot.send_message(chat_id, f" 🎲
{mention(uid, name)} o'yinni o'z xohishi
bilan tark etdi. U mag'lub hisoblanadi.")
    safe_send(uid, " 🎲 O'yinni tark

```

```

etdingiz – bu o'yin uchun avtomatik mag'lub
hisoblanasiz va yakuniy mukofot olmaysiz.")
    handle_death_side_effects(game,
chat_id, uid) # 🏰 Don vorisligi / 🤖
Arvoh faollashuvi
    check_and_end_game(chat_id)

def end_game(chat_id, winners_team,
couple_pair=None):
    game = GAMES.get(chat_id)
    if not game:
        return
    lines = ["🏁 <b>O'yin tugadi!</b>\n"]
    if winners_team == "couple":
        u1, u2 = couple_pair
        n1 = game["players"].get(u1,
    {}).get("name", "O'yinchi")
        n2 = game["players"].get(u2,
    {}).get("name", "O'yinchi")
        lines.append(
            f"👯 <b>G'oliblar – maxfiy
juftlik:</b> {mention(u1, n1)} va
{mention(u2, n2)}!\n"
            f"🎉 Boshqa hamma halok
bo'lgani uchun, ular rollaridan qat'i nazar
birgalikda g'olib chiqishdi!\n"
        )
    elif winners_team == "squad_draw":
        lines.append("🦊🦅 <b>Ikkala jamoa
ham butunlay qirilib bitdi – DURRANG!
</b>\n")
    elif winners_team in ("squad_wolf",
"squad_eagle"):

```

```

        winner_squad = "wolf" if
winners_team == "squad_wolf" else "eagle"
        squad_label = "🐾 Bo'rilar" if
winner_squad == "wolf" else "🦅 Burgutlar"
        lines.append(f"🏆 <b>G'olib jamoa:
{squad_label}</b>\n"
                    f"🎉 Raqib jamoa
butunlay qirilib bitdi!\n")
    else:
        lines.append(f"🎉 G'oliblar
jamoasi: <b>{'Mafiya' if winners_team ==
'mafia' else 'Tinch aholi'}</b>\n")

    # 🏆 Eng faol o'yinchini aniqlaymiz
(tun/kun harakatlari soni bo'yicha)
    activity = game.get("activity_score",
{})
    most_active_uid = max(activity,
key=activity.get) if activity else None

    winners, losers = [], []
    for uid, p in game["players"].items():
        left = p.get("left_game", False)
        if winners_team == "couple":
            won = (uid in couple_pair) and
not left
        elif winners_team == "squad_draw":
            won = False
        elif winners_team in ("squad_wolf",
"squad_eagle"):
            winner_squad = "wolf" if
winners_team == "squad_wolf" else "eagle"
            won = (game.get("squads",
{}).get(uid) == winner_squad) and not left

```

```

else:
    won = (p["team"] ==
winners_team) and not left # 🟠 tark
etganlar hech qachon g'olib hisoblanmaydi
    base_reward = WIN_REWARD if won
else LOSE_REWARD
    reward = 0 if left else
int(base_reward * luck_mult(uid))
    if reward:
        add_balance(uid, dollar=reward)
        u = user_dict(uid)
        update_user(uid, games=u["games"] +
1, wins=u["wins"] + (1 if won else 0))
        entry = f"{mention(uid, p['name'])}
– <b>{p['role']}</b>" + (" ( 🟠 tark etgan)"
if left else "")
        (winners if won else
losers).append((uid, entry)) # 🔧 (uid,
matn) – pastda aktivlikka qarab
tartiblanadi
        # 🔧 TUZATILDI: guruhga
yuboriladigan xabarda endi PUL VA BALL
miqdorlari
        # KO'RSATILMAYDI (faqat ism+rol) –
bularning barchasi FAQAT shaxsiy DM'da
        # ko'rsatiladi (pastdagi
safe_send(uid, ...) qismida, o'zgarishsiz
qoladi).

# 🏆 Faollik ballari: g'alaba +5,
mag'lubiyat -5, eng faol o'yinchi
qo'shimcha +25,
        # tark etgan/AFK bo'lganlar
allaqachon -10 olgan

```

```

(start_night/cmd_tark_et'da)
    points_note = ""
    if not left:
        pts = 5 if won else -5
        add_points(uid, pts,
"game_result")
        points_note = f" ({'+'if pts >=
0 else ''}{pts} ball)"
        if uid == most_active_uid and not
left:
            add_points(uid, 25,
"most_active")
            points_note += " (+25 ball –
eng faol o'yinchi)"

# 🧑 Maxfiy missiya natijasi –
shaxsiy DM
    mission_key =
game.get("secret_missions", {}).get(uid)
    mission_note = ""
    if mission_key:
        done =
check_mission_completed(game, uid,
mission_key)
        if done:
            add_balance(uid, dollar=25)
            mission_note = "\n\n🧑
Maxfiy missiyangizni <b>bajardingiz</b>!
+25$ mukofot berildi."
        else:
            mission_note = "\n\n🧑
Afsuski, maxfiy missiyangizni bajara
olmadingiz."

```



```

# 🚩 Har bir o'yinchiga shaxsiy
yakuniy xabar – yutilgan pul VA ball shu
yerda ko'rsatiladi
    if left:
        outcome_line = "🔴 Siz o'yinni
tark etgansiz – shu sabab bu o'yin uchun
<b>mag'lub</b> hisoblanasiz va mukofot
berilmaydi."
    elif won:
        outcome_line = f"🎉 <b>G'alaba
qozondingiz!</b> +{reward}$ mukofot
oldingiz{points_note}."
    else:
        outcome_line = f"😞 <b>Mag'lub
bo'ldingiz.</b> +{reward}$ (ishtirok uchun)
oldingiz{points_note}."
    safe_send(uid, f"🏁 O'yin
tugadi!\n{outcome_line}{mission_note}")

# 🛠️ TUZATILDI: g'oliblar/mag'lublar
endi o'yindagi FAOLLIKKA qarab (eng faoldan
# kamroq faolgacha) ketma-ket
joylashtiriladi – tasodifiy dict tartibi
emas.
    winners.sort(key=lambda t:
activity.get(t[0], 0), reverse=True)
    losers.sort(key=lambda t:
activity.get(t[0], 0), reverse=True)

    lines.append("🏆 <b>G'oliblar:</b>")
    if winners:
        for i, (_uid, e) in
enumerate(winners, start=1):
            lines.append(f"{i}. {e}")

```

```

else:
    lines.append("– Yo'q –")
    lines.append("")
    lines.append("💀 <b>Mag'lublar:</b>")
    if losers:
        for i, (_uid, e) in
enumerate(losers, start=1):
            lines.append(f"{i}. {e}")
    else:
        lines.append("– Yo'q –")
        if most_active_uid and most_active_uid
in game["players"]:
            lines.append(f"\n👉 Eng faol
o'yinchi: {mention(most_active_uid,
game['players'][most_active_uid]
['name'])}")

# 🐱🦅 Jamoaviy o'yin rejimi yoqilgan
bo'lsa – qaysi jamoa ko'proq g'alaba
# qozonganini alohida ko'rsatamiz
(asosiy Mafiya/Tinch aholi natijasidan
tashqari).
    if game.get("squad_mode") and
game.get("squads"):
        wolf_wins = sum(1 for uid, _ in
winners if game["squads"].get(uid) ==
"wolf")
        eagle_wins = sum(1 for uid, _ in
winners if game["squads"].get(uid) ==
"eagle")
        if wolf_wins or eagle_wins:
            squad_winner = "🐱 Bo'ri
jamoasi" if wolf_wins > eagle_wins else
("🦅 Burgut jamoasi" if eagle_wins >

```

```

wolf_wins else "🐺 Durrang")
    lines.append(
        f"\n🐺🦅 <b>Jamoalar  

hisobi:</b> Bo'ri – {wolf_wins} g'alaba |  

Burgut – {eagle_wins} g'alaba\n"
        f"🏆 Jamoalar orasida bu  

safar yutgan: <b>{squad_winner}</b>"
    )

    bot.send_message(chat_id,
        "\n".join(lines))

    # 🧠 Theron AI – g'oliblarni shaxsan  

    tabriklaydi
    team_label = "Mafiya" if winners_team
    == "mafia" else "Tinch aholi"
    winner_first_names = [game["players"]
    [u]["name"] for u, _ in winners if u in
    game["players"]]
    theron_winner_congrats(chat_id,
    winner_first_names, team_label)

    pair = add_pair_score(chat_id,
    winning_chat_id=chat_id)
    if pair:
        ca, cb, label_a, label_b, score_a,
        score_b = pair
        scoreboard = (
            f"🔴🔵 <b>Qizil vs Ko'k –  

umumiy hisob</b>\n\n"
            f"{label_a}: <b>{score_a}</b>  

g'alaba\n"
            f"{label_b}: <b>{score_b}</b>  

g'alaba"

```

```

        )
        other_id = cb if ca == chat_id else
ca
        bot.send_message(chat_id,
scoreboard)
        try:
            bot.send_message(other_id,
scoreboard)
        except Exception:
            pass

        del GAMES[chat_id]
        save_games_state()

        # 🏠 Klan tizimi: klan lideri bo'lgan
o'yinchilar har o'ynagan Hunter Mafia
        # o'yinidan keyin avtomatik +2 lvl
oladi (klan spetsifikatsiyasi bo'yicha)
        for uid in game["players"]:
            clan = get_clan(uid)
            if clan:
                with db_lock:
                    cur.execute("UPDATE clans
SET leader_level = leader_level + 2 WHERE
owner_id=?", (uid,))
                    conn.commit()

#
=====
=====
# DUEL / NIKOH
#
=====

```

=====

```
DUEL_COST = 100
```

```
# 🗡️ Tasodifiy qurollar – har birining  
nishonchi (chorlovchi) uchun boshlang'ich  
# g'alaba ehtimoli turlicha (keyin geroy  
bonuslari ustiga qo'shiladi)
```

```
DUEL_WEAPONS = [  
    {"name": "🔫 Pistolet", "verb": "bir-  
biriga qarab otishdi", "challenger_chance":  
0.50},  
    {"name": "🔪 Pichoq", "verb": "yaqin  
jangda to'qnashishdi", "challenger_chance":  
0.55},  
    {"name": "☠️ Zahar", "verb": "bir-  
birining ichimligiga zahar qo'shishga  
urinishdi", "challenger_chance": 0.45},  
    {"name": "🎯 Snayper", "verb": "uzoqdan  
nishonga oldi", "challenger_chance": 0.60},  
    {"name": "💥 Mushtlashuv", "verb":  
"yelkama-yelka mushtlashdi",  
"challenger_chance": 0.50},  
]
```

```
DUEL_ANIMATION_STEPS = [  
    "🎯 O'yinchilar nishonga olyapti...",  
    "🗡️ Jang boshlandi...",  
    "📊 Natijalar hisoblanmoqda...",  
]
```

```
def resolve_duel_outcome(a_id, b_id,  
weapon=None):
```

```

"""(g'olib, mag'lub) qaytaradi – yoki
(None, None) agar durrang bo'lsa
(🏆 Magnus/Zephyrion "Qat'iy zarba"
qobiliyati tufayli). `a_id` – chorlovchi
(challenger)."""
a_ch, b_ch = get_charges(a_id),
get_charges(b_id)
a_guaranteed =
a_ch.get("duel_guaranteed_win", 0) > 0
b_guaranteed =
b_ch.get("duel_guaranteed_win", 0) > 0
winner, loser = None, None
# Ikkalasida ham kafolatlangan g'alaba
bo'lsa – ikkalasi ham sarflanadi,
# keyin oddiy imkoniyat asosida hal
qilinadi (birovi ikkinchisini "yutib"
ketmasin).
if a_guaranteed and b_guaranteed:
    use_charge(a_id,
"duel_guaranteed_win")
    use_charge(b_id,
"duel_guaranteed_win")
    winner, loser =
tuple(random.sample([a_id, b_id], 2))
elif a_guaranteed:
    use_charge(a_id,
"duel_guaranteed_win")
    winner, loser = a_id, b_id
elif b_guaranteed:
    use_charge(b_id,
"duel_guaranteed_win")
    winner, loser = b_id, a_id
else:
    a_adv = a_ch.get("duel_adv", 0) > 0

```

```

and is_item_active(a_id, "duel_adv")
    b_adv = b_ch.get("duel_adv", 0) > 0
and is_item_active(b_id, "duel_adv")
    if a_adv and not b_adv:
        use_charge(a_id, "duel_adv")
        winner, loser = (a_id, b_id) if
random.random() < 0.65 else (b_id, a_id)
    elif b_adv and not a_adv:
        use_charge(b_id, "duel_adv")
        winner, loser = (b_id, a_id) if
random.random() < 0.65 else (a_id, b_id)
    else:
        # ✂ Tasodifiy qurol –
        chorlovchi (a_id) uchun boshlang'ich
        ehtimol
        base_chance = (weapon or
        {}).get("challenger_chance", 0.5)
        # 🏆 Geroy (Magnus / Zephyrion)
        – duelda g'alaba ehtimolini oshiradi
        a_hero_bonus =
        hero_duel_bonus(a_id)
        b_hero_bonus =
        hero_duel_bonus(b_id)
        a_win_chance = max(0.10,
        min(0.90, base_chance + a_hero_bonus -
        b_hero_bonus))
        winner, loser = (a_id, b_id) if
        random.random() < a_win_chance else (b_id,
        a_id)

        # 🏆 Geroy (Magnus/Zephyrion "Qat'iy
        zarba") – mag'lub bo'lgan tomonda ushbu
        # qobiliyat bo'lsa, tasodifiy foizda
        durrang (hech kim yutqazmaydi)

```

```

        draw_chance =
hero_duel_draw_chance(loser)
        if draw_chance > 0 and random.random()
< draw_chance:
            return None, None
        return winner, loser

@bot.message_handler(commands=["duel",
"Duel"])
def cmd_duel(message):
    """🔪 Duel taklifi – ixtiyoriy tikish
summasi bilan: /duel 250 (kimningdir
xabariga reply qilib).
Summa ko'rsatilmasa standart $100
ishlatiladi."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not message.reply_to_message:
        return
    sender = message.from_user
    target =
message.reply_to_message.from_user

    # 🗝️ Xavfsizlik: o'z-o'ziga duel
tashlab bo'lmaydi
    if target.id == sender.id:
        bot.send_message(message.chat.id,
"❌ O'zingizga duel tashlay olmaysiz! 😊")
        return
    if target.is_bot:
        bot.send_message(message.chat.id,
"❌ Botga duel tashlab bo'lmaydi.")
        return

```



```

        if is_banned(sender.id) or
is_banned(target.id):
            return

        # 💰 Tikish summasini o'qish
        (ixtiyoriy, standart $100)
        parts = message.text.split()
        bet = DUEL_COST
        if len(parts) > 1:
            try:
                bet = int(parts[1])
            except ValueError:

bot.send_message(message.chat.id, "❌
Tikish summasi butun son bo'lishi kerak.
Masalan: <code>/duel 250</code>")
            return
            if bet < 10:

bot.send_message(message.chat.id, "❌ Eng
kam tikish summasi: $10.")
            return

        sd = user_dict(sender.id,
sender.first_name)
        td = user_dict(target.id,
target.first_name or "O'yinchi")
        if sd["dollar"] < bet:
            bot.send_message(message.chat.id,
f"❌ Sizda yetarli mablag' yo'q! Tikish
uchun ${bet} kerak, sizda ${sd['dollar']}
bor.")
            return
            if td["dollar"] < bet:

```

```

        bot.send_message(message.chat.id,
f"❌ {td['name']}da yetarli mablag' yo'q  

({bet} kerak, unda {td['dollar']} bor).")
        return

```

```

        PENDING_PROPOSALS[target.id] = {"from":
sender.id, "type": "duel", "chat_id":
message.chat.id, "bet": bet}
        kb = types.InlineKeyboardMarkup()
        kb.add(
            types.InlineKeyboardButton("🔪  
Qabul qilish", callback_data=f"duel|yes|
{sender.id}|{target.id}"),
            types.InlineKeyboardButton("🚩 Rad  
etish", callback_data=f"duel|no|
{sender.id}|{target.id}"),
        )
        bot.send_message(
            message.chat.id,
            f"🔪 {mention(sender.id,
sender.first_name)}, {mention(target.id,
target.first_name)}ni "
            f"<b>${bet}</b> tikishga duelga  

chorlayapti! Qabul qilasizmi?",
            reply_markup=kb,
        )

```

```

@bot.callback_query_handler(func=lambda c:
c.data.startswith("duel|"))
def cb_duel(call):
    maybe_capture_owner(call.from_user)
    _, action, sender_s, target_s =
call.data.split("|")

```

```

        sender_id, target_id = int(sender_s),
int(target_s)
        if call.from_user.id != target_id:
            bot.answer_callback_query(call.id,
"Bu taklif sizga emas.")
            return
        pending =
PENDING_PROPOSALS.get(target_id)
        if not pending or pending["from"] !=
sender_id or pending.get("type") != "duel":
            bot.answer_callback_query(call.id,
"Taklif eskirgan.")
            return
        PENDING_PROPOSALS.pop(target_id, None)
        bet = pending.get("bet", DUEL_COST)

        if action == "no":

bot.edit_message_text(random.choice(DUEL_RE
JECT_JOKES), call.message.chat.id,
call.message.message_id)
            bot.answer_callback_query(call.id)
            return

        sd, td = user_dict(sender_id),
user_dict(target_id)
        if sd["dollar"] < bet or td["dollar"] <
bet:
            bot.edit_message_text("❌ Duel
bekor qilindi – balans yetarli emas.",
call.message.chat.id,
call.message.message_id)
            bot.answer_callback_query(call.id)
            return

```

```

bot.answer_callback_query(call.id, "🔪
Duel boshlandi!")

# 🗡️ Tasodifiy qurol tanlanadi
weapon = random.choice(DUEL_WEAPONS)
sender_name = sd["name"]
target_name = td["name"]

# 🎬 Dinamik animatsiya – natija darhol
chiqmaydi, bir necha bosqichda yangilanadi
try:
    bot.edit_message_text(
        f"{weapon['name']} <b>QUROL
TANLANDI!</b>\n\n{sender_name} va
{target_name} {weapon['verb']}...\n\n"
        f"{DUEL_ANIMATION_STEPS[0]}",
        call.message.chat.id,
        call.message.message_id,
    )
    for step in
DUEL_ANIMATION_STEPS[1:]:
        time.sleep(1.4)
        bot.edit_message_text(
            f"{weapon['name']} <b>
{sender_name} 🗡️ {target_name}
</b>\n\n{step}",
            call.message.chat.id,
            call.message.message_id,
        )
        time.sleep(1.2)
except Exception:
    pass

winner, loser =

```

```

resolve_duel_outcome(sender_id, target_id,
weapon=weapon)
    if winner is None:
        # 🏆 Geroy "Qat'iy zarba" –
durrang, hisoblar teng qoladi, hech kim
yutqazmaydi
        bot.edit_message_text(
            f"{weapon['name']} 🏆 <b>Duel
durrang yakunlandi!</b>\n\nBir tomonning
geroy qobiliyati mag'lubiyatni "
            "durrangga aylantirdi – hech
kimning puli o'zgarmadi.",
            call.message.chat.id,
call.message.message_id,
        )
        safe_send(sender_id, "🏆 Duelingiz
durrang tugadi – geroy qobiliyati ishga
tushdi!")
        safe_send(target_id, "🏆 Duelingiz
durrang tugadi – geroy qobiliyati ishga
tushdi!")
        return
        reward = int(bet * luck_mult(winner))
        add_balance(winner, dollar=reward)
        add_balance(loser, dollar=-bet)
        record_duel_result(winner, loser)
        winner_name, loser_name =
user_dict(winner)["name"], user_dict(loser)
["name"]
        bot.edit_message_text(
            f"{weapon['name']} <b>DUEL
YAKUNLANDI!</b>\n\n"
            f"🏆 G'olib: <b>{winner_name}</b>\n
💀 Mag'lub: <b>{loser_name}</b>\n"

```

```

        f"💰 {winner_name} ${reward} yutib
oldi ({loser_name}dan)!",
        call.message.chat.id,
        call.message.message_id,
    )
    safe_send(loser, f"😓 <b>Duelda
yutqazdingiz...</b>
(-${bet})\n\n{random.choice(DEFEAT_JOKES)}"
)
    safe_send(winner, f"🏆 <b>Duelda
g'alaba qozondingiz!</b> +${reward}")

@bot.message_handler(commands=["duel_stat",
"DuelStat"])
def cmd_duel_stat(message):
    """qoshimchakod4.py g'oyasi – endi
bazada saqlanadigan haqiqiy statistika."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    target =
message.reply_to_message.from_user if
message.reply_to_message else
message.from_user
    u = user_dict(target.id,
target.first_name)
    total = u["duel_wins"] +
u["duel_losses"]
    rate = f"({u['duel_wins'] / total *
100):.1f}%" if total else "0.0%"
    text = (
        f"🔪 <b>Duel statistikasi –
{u['name']}</b>\n\n"
        f"🎮 Jami duellar: {total} ta\n"

```

```

        f"🏆 G'alabalar: {u['duel_wins']}\n"
        f"❌ Mag'lubiyatlar: {u['duel_losses']}\n"
        f"📊 G'alaba foizi: {rate}"
    )
    bot.send_message(message.chat.id, text)

```

```

#
=====
# 🏆 MUSOBAQALAR (TURNIRLAR) – TO'LIQ ISHLAYDIGAN TIZIM
#
=====
=====

```

```

def is_group_admin_or_owner(message):
    if is_owner(message.from_user.id):
        return True
    try:
        member =
    bot.get_chat_member(message.chat.id,
        message.from_user.id)
        return member.status in
        ("administrator", "creator")
    except Exception:
        return False

```

```

@bot.message_handler(commands=
    ["turnir_boshla"])
def cmd_turnir_boshla(message):

```

```

"""🏆 FAQAT BOT EGASI (owner) yangi
turnir ochadi – ro'yxatga olish boshlanadi.
(Musobaqalar rejimi endi faqat owner
ruxsati bilan o'tkaziladi – guruh
admini ENDI mustaqil turnir boshlay
olmaydi.)"""
maybe_capture_owner(message.from_user)
safe_delete(message)
if message.chat.type not in ("group",
"supergroup"):
    bot.send_message(message.chat.id,
    "🏆 Turnirlar faqat guruhda tashkil
qilinadi.")
    return
if not is_owner(message.from_user.id):
    bot.send_message(message.chat.id,
    "❌ Musobaqalar (turnir) rejimini FAQAT bot
egasi boshlashi mumkin.")
    return
chat_id = message.chat.id
if chat_id in TOURNAMENTS and
TOURNAMENTS[chat_id]["status"] !=
"finished":
    bot.send_message(message.chat.id,
    "⚠ Bu guruhda allaqachon faol turnir bor.
Avval /turnir_tugat bilan yakunlang.")
    return
parts = message.text.split(maxsplit=1)
name = parts[1].strip() if len(parts) >
1 else "Hunter Mafia Turniri"
TOURNAMENTS[chat_id] = {
    "name": name, "status":
"registration", "participants": {},
    "eliminated": [], "matches": [],

```



```

"host_id": message.from_user.id,
    }
    kb = types.InlineKeyboardMarkup()
    kb.add(types.InlineKeyboardButton("✅
Ishtirok etish", callback_data=f"tjoin|
{chat_id}"))
    bot.send_message(
        message.chat.id,
        f"🏆🔪 <b>YANGI TURNIR OCHILDI:
{name}</b>\n\n"
        "Istagan o'yinchi pastdagi tugma
orqali ro'yxatdan o'ta oladi!\n"
        "Tashkilotchi tayyor bo'lganda
/turnir_yopish buyrug'i bilan ro'yxatni
yopadi va janglarни boshlaydi.",
        reply_markup=kb,
    )

@bot.callback_query_handler(func=lambda c:
c.data.startswith("tjoin|"))
def cb_turnir_join(call):
    maybe_capture_owner(call.from_user)
    chat_id = int(call.data.split("|")[1])
    t = TOURNAMENTS.get(chat_id)
    if not t or t["status"] !=
"registration":
        bot.answer_callback_query(call.id,
"⚠️ Ro'yxatga olish yopilgan yoki turnir
topilmadi.", show_alert=True)
        return
    uid = call.from_user.id
    if uid in t["participants"]:
        bot.answer_callback_query(call.id,

```

```

"✅ Siz allaqachon ro'yxatdasiz!",
show_alert=True)
    return
    t["participants"][uid] =
call.from_user.first_name
    user_dict(uid,
call.from_user.first_name)
    bot.answer_callback_query(call.id, "🎉
Turnirga muvaffaqiyatli qo'shildingiz!",
show_alert=True)
    bot.send_message(call.message.chat.id,
f"👤 {mention(uid,
call.from_user.first_name)} turnirga
qo'shildi! (jami:
{len(t['participants'])})")

```

```

@bot.message_handler(commands=
["turnir_royxat"])
def cmd_turnir_royxat(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    t = TOURNAMENTS.get(message.chat.id)
    if not t:
        bot.send_message(message.chat.id,
"🚫 Bu guruhda hozircha turnir yo'q.")
        return
    remaining = {uid: name for uid, name in
t["participants"].items() if uid not in
t["eliminated"]}
    lines = [f"🏆 <b>{t['name']}</b> -
holat: {t['status']}\n"]
    lines.append(f"👥 <b>Ishtirokchilar
{len(t['participants'])}</b>")

```

```

        for i, (uid, name) in
            enumerate(t["participants"].items(), 1):
                tag = " ❌" if uid in
t["eliminated"] else " 🟢"
                lines.append(f"{i}. {mention(uid,
name)}}{tag}")
                if t["status"] == "ongoing":
                    lines.append(f"\n🏆 Hozir kurashda:
{len(remaining)} kishi qoldi.")
                    bot.send_message(message.chat.id,
"\n".join(lines))

@bot.message_handler(commands=
["turnir_yopish"])
def cmd_turnir_yopish(message):
    """🏆 Ro'yxatga olishni yopadi va
turnirni boshlaydi (kamida 2 kishi
kerak)."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    chat_id = message.chat.id
    t = TOURNAMENTS.get(chat_id)
    if not t or t["status"] !=
"registration":
        bot.send_message(chat_id, "⚠️ Hozir
yopiladigan ro'yxat yo'q.")
        return

    if not (is_owner(message.from_user.id)
or message.from_user.id == t["host_id"]):
        bot.send_message(chat_id, "🚫
Musobaqalar (turnir) rejimini FAQAT bot
egasi boshqarishi mumkin.")
        return

```

```

        if len(t["participants"]) < 2:
            bot.send_message(chat_id, "⚠️
Turnir boshlanishi uchun kamida 2 ta
ishtirokchi kerak.")
            return
        t["status"] = "ongoing"
        names = "", ".join(mention(uid, name)
for uid, name in t["participants"].items())
        bot.send_message(
            chat_id,
            f"🔒 <b>Ro'yxatga olish yopildi!
</b> Jami {len(t['participants'])}
ishtirokchi: {names}\n\n"
            f"🔪 Tashkilotchi endi /turnir_jang
buyrug'i orqali navbatdagi ikki kurashchini
tanlaydi.",
            )

@bot.message_handler(commands=
["turnir_jang"])
def cmd_turnir_jang(message):
    """🔪 Tashkilotchi 2 ta qolgan
ishtirokchini tanlab, ular orasida Turnir
Jangini boshlaydi."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    chat_id = message.chat.id
    t = TOURNAMENTS.get(chat_id)
    if not t or t["status"] != "ongoing":
        bot.send_message(chat_id, "⚠️ Hozir
faol (ongoing) turnir yo'q.")
        return
    if not (is_owner(message.from_user.id)

```

```

or message.from_user.id == t["host_id"]):
    bot.send_message(chat_id, "🚫
Musobaqalar (turnir) rejimini FAQAT bot
egasi boshqarishi mumkin.")
    return
    remaining = {uid: name for uid, name in
t["participants"].items() if uid not in
t["eliminated"]}
    if len(remaining) < 2:
        bot.send_message(chat_id, "🏆
Kurashadigan yetarli ishtirokchi qolmadi –
turnir allaqachon yakunlangan bo'lishi
mumkin.")
        return
    TOURNAMENT_PICK[message.from_user.id] =
{"chat_id": chat_id, "a": None}
    kb = types.InlineKeyboardMarkup()
    for uid, name in remaining.items():

kb.add(types.InlineKeyboardButton(name,
callback_data=f"tpick|
{message.from_user.id}|{uid}"))
    bot.send_message(chat_id, "🔪 <b>1-
kurashchini tanlang:</b>", reply_markup=kb)

@bot.callback_query_handler(func=lambda c:
c.data.startswith("tpick|"))
def cb_turnir_pick(call):
    maybe_capture_owner(call.from_user)
    _, host_id_s, uid_s =
call.data.split("|")
    host_id, picked_uid = int(host_id_s),
int(uid_s)

```

```

        if call.from_user.id != host_id:
            bot.answer_callback_query(call.id,
                "❌ Bu tanlov sizga tegishli emas.",
                show_alert=True)
            return
        state = TOURNAMENT_PICK.get(host_id)
        if not state:
            bot.answer_callback_query(call.id,
                "❌ Tanlov muddati tugagan, qaytadan
                /turnir_jang bosing.", show_alert=True)
            return
        t = TOURNAMENTS.get(state["chat_id"])
        if not t or t["status"] != "ongoing":
            bot.answer_callback_query(call.id,
                "❌ Turnir faol emas.", show_alert=True)
            return
        remaining = {uid: name for uid, name in
            t["participants"].items() if uid not in
            t["eliminated"]}

        if state["a"] is None:
            state["a"] = picked_uid
            bot.answer_callback_query(call.id,
                f"✅ 1-kurashchi:
                {remaining.get(picked_uid, '?')}")
            kb = types.InlineKeyboardMarkup()
            for uid, name in remaining.items():
                if uid == picked_uid:
                    continue

            kb.add(types.InlineKeyboardButton(name,
                callback_data=f"tpick|{host_id}|{uid}"))
            try:
                bot.edit_message_text(

```

```

        f"✅ 1-kurashchi: <b>
{remaining.get(picked_uid, '?')}</b>\n\n❌
Endi 2-kurashchini tanlang:",
        call.message.chat.id,
        call.message.message_id, reply_markup=kb,
    )
    except Exception:
        pass
    return

    if picked_uid == state["a"]:
        bot.answer_callback_query(call.id,
        "❌ Bir xil odamni 2 marta tanlab
        bo'lmaydi.", show_alert=True)
        return

        a_id, b_id = state["a"], picked_uid
        a_name, b_name = remaining.get(a_id,
        "?"), remaining.get(b_id, "?")
        del TOURNAMENT_PICK[host_id]
        bot.answer_callback_query(call.id, "❌
        Jang boshlanmoqda!")
        try:
            bot.edit_message_text(
                f"❌ <b>JANG:</b> {a_name} vs
                {b_name}\n\n🎯 Natija aniqlanmoqda...",
                call.message.chat.id,
                call.message.message_id,
            )
        except Exception:
            pass
        run_tournament_match(t,
        state["chat_id"], a_id, b_id)

```

```

def run_tournament_match(t, chat_id, a_id,
b_id):
    """🗡️ Turnir jangi – duel'dan farqli,
    faqat 1v1 elimination uchun; hero
    bonuslari (Magnus/Zephyrion) shu yerda
    ham hisobga olinadi, lekin duel
    statistikasiga (/duel_stat) ta'sir
    qilmaydi – bu alohida rejim."""
    a_name = t["participants"].get(a_id,
    "?")
    b_name = t["participants"].get(b_id,
    "?")
    # 🏆 Geroy "Qat'iy zarba" durrang
    berishi mumkin, lekin turnirda albatta
    bitta
    # g'olib chiqishi SHART – shuning uchun
    durrang chiqsa, qayta hal qilinadi.
    winner, loser =
    resolve_duel_outcome(a_id, b_id)
    retries = 0
    while winner is None and retries < 5:
        winner, loser =
        tuple(random.sample([a_id, b_id], 2))
        retries += 1
    winner_name =
    t["participants"].get(winner, "?")
    loser_name =
    t["participants"].get(loser, "?")

    t["eliminated"].append(loser)
    t["matches"].append({"a": a_id, "b":
    b_id, "winner": winner})
    add_points(winner, 3,

```



```

"tournament_match_win")

    fight_flavor = random.choice([
        "🔪 Ayovsiz jang yakunlandi!",
        "💥 Hayratlanarli kurashdan so'ng
g'olib aniqlandi!",
        "🔥 Ikkalasi ham jonbozlik
ko'rsatdi, lekin faqat bittasi qoldi!",
        "⚡ Bir zumda hal bo'lgan ajoyib
jang!",
        "🎯 Aniq va shafqatsiz zarba bilan
yakunlandi!",
    ])
    bot.send_message(
        chat_id,
        f"{fight_flavor}\n\n"
        f"🏆 <b>G'olib: {mention(winner,
winner_name)}</b>\n"
        f"💀 Mag'lub: {mention(loser,
loser_name)} – turnirdan chetlashtirildi.",
    )
    safe_send(winner, f"🏆 Turnir jangida
g'olib chiqdingiz: {a_name} 🆚 {b_name}!
Keyingi bosqichga o'tdingiz.")
    safe_send(loser, f"💀 Turnir jangida
mag'lub bo'ldingiz: {a_name} 🆚 {b_name}.
Turnir shu yerda tugadi, lekin harakatingiz
uchun rahmat!")

    remaining = {uid: name for uid, name in
t["participants"].items() if uid not in
t["eliminated"]}
    if len(remaining) == 1:
        champion_id =

```

```

list(remaining.keys())[0]
    champion_name =
remaining[champion_id]
    t["status"] = "finished"
    add_balance(champion_id,
dollar=500, diamond=20)
    add_points(champion_id, 50,
"tournament_champion")
    bot.send_message(
        chat_id,
        f"🏆🏆 <b>TURNIR CEMPIONI:
{mention(champion_id, champion_name)}!</b>
🏆🏆\n\n"
        f"🎉 <b>{t['name']}</b> g'olibi
aniqlandi!\n"
        f"🎁 Mukofot: +500$ 💰, +20 💎,
+50 🏅 ball!\n\n"
        "Yangi turnir uchun
/turnir_boshla deb yozing!",
    )
    safe_send(champion_id, f"🏆
Tabriklaymiz! Siz <b>{t['name']}</b>
turnirining CEMPIONI bo'ldingiz! +500$,
+20💎, +50 ball oldingiz!")
    else:
        bot.send_message(chat_id, f"🔪🔪
Kurash davom etadi – {len(remaining)} kishi
qoldi. Tashkilotchi /turnir_jang bilan
navbatdagi jangni boshlaydi.")

@bot.message_handler(commands=
["turnir_tugat"])
def cmd_turnir_tugat(message):

```

```

"""🔴 Turnirni majburan
yakunlaydi/bekor qiladi
(tashkilotchi/admin/owner)."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    chat_id = message.chat.id
    t = TOURNAMENTS.get(chat_id)
    if not t:
        bot.send_message(chat_id, "🚫 Bu
guruhda hozircha turnir yo'q.")
        return
    if not (is_owner(message.from_user.id)
or message.from_user.id == t["host_id"]):
        bot.send_message(chat_id, "🚫
Musobaqalar (turnir) rejimini FAQAT bot
egasi bekor qila oladi.")
        return
    del TOURNAMENTS[chat_id]
    bot.send_message(chat_id, "🔴 Turnir
bekor qilindi/yakunlandi.")

@bot.message_handler(commands=["Nikoh",
"nikoh"])
def cmd_nikoh(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not message.reply_to_message:
        return
    proposer = message.from_user
    target =
message.reply_to_message.from_user
    if proposer.id == target.id:

```

```

        return
    if is_banned(proposer.id) or
is_banned(target.id):
        return
    user_dict(proposer.id,
proposer.first_name)
    user_dict(target.id, target.first_name
or "O'yinchi")
    PENDING_PROPOSALS[target.id] = {"from":
proposer.id, "type": "nikoh", "chat_id":
message.chat.id}
    kb = types.InlineKeyboardMarkup()
    kb.add(
        types.InlineKeyboardButton("💍 Ha",
callback_data=f"nikoh|yes|{proposer.id}|
{target.id}"),
        types.InlineKeyboardButton("💔
Yo'q", callback_data=f"nikoh|no|
{proposer.id}|{target.id}"),
    )
    bot.send_message(
        message.chat.id,
        f"🌺 {mention(proposer.id,
proposer.first_name)}, {mention(target.id,
target.first_name)}ga turmush qurishni
taklif qildi!",
        reply_markup=kb,
    )

@bot.callback_query_handler(func=lambda c:
c.data.startswith("nikoh|"))
def cb_nikoh(call):
    maybe_capture_owner(call.from_user)

```

```

_, action, proposer_s, target_s =
call.data.split("|")
proposer_id, target_id =
int(proposer_s), int(target_s)
if call.from_user.id != target_id:
    bot.answer_callback_query(call.id,
"Bu taklif sizga emas.")
    return
pending =
PENDING_PROPOSALS.get(target_id)
if not pending or pending["from"] !=
proposer_id:
    bot.answer_callback_query(call.id,
"Taklif eskirgan.")
    return
PENDING_PROPOSALS.pop(target_id, None)
if action == "no":

bot.edit_message_text(random.choice(MARRIAG
E_REJECT_JOKES), call.message.chat.id,
call.message.message_id)
else:
    married_at = time.strftime("%Y-%m-
%d %H:%M:%S")
    update_user(proposer_id,
married_to=target_id,
married_at=married_at)
    update_user(target_id,
married_to=proposer_id,
married_at=married_at)
    bot.edit_message_text(f"💍 <b>NIKOH
QURILDI!
</b>\n\n{random.choice(MARRIAGE_ACCEPT_JOKE
S})", call.message.chat.id,

```

```

call.message.message_id)
    bot.answer_callback_query(call.id)

#
=====
=====
# /juftim /ajrashish (qoshimchakod3.py
g'oyasi – married_to ustuniga
moslashtirilgan)
#
=====
=====

@bot.message_handler(commands=["juftim"])
def cmd_juftim(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    uid = message.from_user.id
    user_dict(uid,
message.from_user.first_name)
    partner = get_partner_mention(uid)
    if partner:
        text = f"👤 <b>Oilaviy holat:</b>
Nikohda ❤️\n\nSizning juftingiz: {partner}"
    else:
        text = "👤 <b>Oilaviy holat:</b>
Bo'ydoq (yolg'iz)\n\nGuruhda kimningdir
xabariga reply qilib /nikoh deb yozib
taklif yuborishingiz mumkin."
        bot.send_message(message.chat.id, text)

@bot.message_handler(commands=

```

```

["ajrashish"])
def cmd_ajrashish(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    uid = message.from_user.id
    u = user_dict(uid,
message.from_user.first_name)
    partner_id = u.get("married_to") or 0
    if not partner_id:
        bot.send_message(message.chat.id,
"❌ Siz allaqachon bo'ydozsiz, ajrashish
uchun avval nikohda bo'lishingiz kerak.")
        return
    update_user(uid, married_to=0,
married_at="")
    update_user(partner_id, married_to=0,
married_at="")
    bot.send_message(message.chat.id, "💔
Siz juftingiz bilan ajrashdingiz. Endi
boshqa nikoh qurishingiz mumkin.")

#
=====
=====
# 🧐 OILAVIY QO'SHIMCHA FUNKSIYALAR (5 ta)
- /OilaInfo /Quchoqla /OilaTop /Sovgla
/Xiyonat
# Barchasi mavjud
"married_to"/"married_at" ustunlariga
moslashtirilgan, hech qanday
# o'yin imtiyozi bermaydi – faqat
qiziqarli/hazil funksiyalar.
#

```

```

=====
=====

def _married_seconds(married_at_str):
    """married_at ('%Y-%m-%d %H:%M:%S') dan
    hozirgi vaqtgacha o'tgan soniyalarni
    hisoblaydi."""
    if not married_at_str:
        return None
    try:
        then =
time.mktime(time.strptime(married_at_str,
"%Y-%m-%d %H:%M:%S"))
    except Exception:
        return None
    return max(0, time.time() - then)

def _format_duration(seconds):
    """Soniyani 'X kun Y soat Z daqiqa'
    ko'rinishiga o'giradi."""
    seconds = int(seconds)
    days, rem = divmod(seconds, 86400)
    hours, rem = divmod(rem, 3600)
    minutes, _ = divmod(rem, 60)
    parts = []
    if days:
        parts.append(f"{days} kun")
    if hours or days:
        parts.append(f"{hours} soat")
    parts.append(f"{minutes} daqiqa")
    return " ".join(parts)

```



```

@bot.message_handler(commands=["OilaInfo",
"oilainfo"])
def cmd_oila_info(message):
    """💍️ Juftlik qancha vaqtdan beri birga
    ekanini ko'rsatadi."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    uid = message.from_user.id
    u = user_dict(uid,
message.from_user.first_name)
    partner_id = u.get("married_to") or 0
    if not partner_id:
        bot.send_message(message.chat.id,
        "👤 Siz hozircha bo'ydozsiz. Nikoh qurish
        uchun kimningdir xabariga reply qilib
        /nikoh deb yozing.")
        return
    partner_name =
user_dict(partner_id).get("name",
"Noma'lum")
    secs =
_married_seconds(u.get("married_at"))
    if secs is None:
        bot.send_message(message.chat.id,
        "💍️ Siz nikohdasiz, ammo nikoh sanasi
        topilmadi.")
        return
    duration = _format_duration(secs)
    milestone = ""
    days = secs // 86400
    if days >= 365:
        milestone = "\n🎉 Tabriklaymiz,
        allaqachon 1 yildan ortiq birgasiz! 💕"
    elif days >= 30:

```

```

        milestone = "\n💑 1 oydan ortiq
davom etayotgan mustahkam oila!"
    elif days < 1:
        milestone = "\n💐 Yangi qurilgan
oilal – hali gullar so'lmagan!"
        bot.send_message(
            message.chat.id,
            f"🕒 <b>OILAVIY MA'LUMOT</b>\n\n"
            f"{mention(uid, u['name'])} ❤️
{mention(partner_id, partner_name)}\n\n"
            f"🕒 Birga bo'lganingizga: <b>
{duration}</b> bo'ldi.{milestone}",
        )

```

```

HUG_JOKES = [
    "{a} {b}ni mahkam quchoqladi –
atrofdagilar hatto \"awww\" deb yubordi! 🥰
💕",
    "{a} {b}ga shunday quchoq berdiki,
hatto guruh admin botlari ham hayajonlandi!
😭🥰",
    "{a} {b}ni quchoqladi va \"seni
sog'indim!\" deb pichirladi... yoki shunga
o'xshash narsa dedi. 🥰",
    "{a} {b}ni quchoqlab, ikkalasi ham 5
daqiqal jilmayib turishdi. 😊🥰",
    "{a} {b}ga issiq quchoq berdi – guruh
chatida vaqtincha romantika hidi taraldi!
💐🥰",
]

```

```

CUDDLE_JOKES = [
    "{a} {b}ning yonog'idan chiroyli o'pich

```

```

oldi – {b} qizarib ketdi! 😳💦",
    "{a} {b}ga mehr bilan o'pich yubordi –
havoda yurak shakllari uchib ketdi! 💦💕",
    "{a} {b}ni erkalatdi, {b} esa \"yana!\"
deb hazillashdi. 💦😁",
    "{a} {b}ga shirin o'pich berdi –
atrofdagilar \"voy tuya\" deb ketishdi! 💦
😁",
    "{a} {b}ni erkalab, ikkalasi bir-
birlariga jilmayib qarab qolishdi. 💦😁",
]

```

```

def _require_partner_reply(message):
    """Reply qilingan kishi haqiqatan ham
    xabar yuboruvchining turmush o'rtog'imi –
    tekshiradi.
    (ok, uid, partner_id, partner_name,
    error_msg) qaytaradi."""
    uid = message.from_user.id
    u = user_dict(uid,
message.from_user.first_name)
    partner_id = u.get("married_to") or 0
    if not partner_id:
        return False, uid, None, None, "👤
Siz bo'ydozsiz – bu buyruq faqat
nikohdagilar uchun."
    if not message.reply_to_message or not
message.reply_to_message.from_user:
        return False, uid, None, None, "❌
Bu buyruqni juftingizning xabariga REPLY
qilib yozing."
    target =
message.reply_to_message.from_user

```

```

        if target.id != partner_id:
            return False, uid, None, None, "❌
Siz faqat o'zingizning turmush
o'rtog'ingizga shu amalni bajarishingiz
mumkin."
        return True, uid, partner_id,
target.first_name, None

@bot.message_handler(commands=["Quchoqla",
"quchoqla", "Opich", "opich"])
def cmd_quchoqla(message):
    """🤗👉 Juftiga reply qilib, guruhda
chiroyli/hazilomuz erkalash matni
chiqadi."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    ok, uid, partner_id, partner_name, err
= _require_partner_reply(message)
    if not ok:
        bot.send_message(message.chat.id,
err)
    return
    is_opich = message.text.split()
[0].lower().lstrip("/").startswith("opich")
    jokes = CUDDLE_JOKES if is_opich else
HUG_JOKES
    text =
random.choice(jokes).format(a=mention(uid,
message.from_user.first_name),
b=mention(partner_id, partner_name))
    bot.send_message(message.chat.id, text)

```

```

@bot.message_handler(commands=["OilaTop",
"oilatop"])
def cmd_oila_top(message):
    """🏆 Guruhdagi (yoki bot bo'yicha
umuman) eng uzoq vaqt birga bo'lgan
juftliklar TOP ro'yxati."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    with db_lock:
        cur.execute("SELECT user_id, name,
married_to, married_at FROM users WHERE
married_to != 0 AND married_at != ''")
        rows = cur.fetchall()
        seen = set()
        pairs = []
        for uid, name, partner_id, married_at
in rows:
            pair_key = tuple(sorted((uid,
partner_id)))
            if pair_key in seen:
                continue
            seen.add(pair_key)
            secs = _married_seconds(married_at)
            if secs is None:
                continue
            partner_name =
user_dict(partner_id).get("name",
"Noma'lum")
            pairs.append((secs, uid, name,
partner_id, partner_name))
        if not pairs:
            bot.send_message(message.chat.id,
"💍 Hozircha hech qanday nikohlangan
juftlik yo'q.")

```

```

        return
        pairs.sort(key=lambda x: x[0],
reverse=True)
        lines = ["🏆 <b>ENG MUSTAHKAM OILALAR
TOP RO'YXATI</b>\n"]
        for i, (secs, uid, name, partner_id,
partner_name) in enumerate(pairs[:10], 1):
            medal = {1: "🥇", 2: "🥈", 3:
"🥉"}.get(i, f"{i}.")
            lines.append(f"{medal}
{mention(uid, name)} ❤️
{mention(partner_id, partner_name)} –
{_format_duration(secs)}")
            bot.send_message(message.chat.id,
"\n".join(lines))

GIFT_OPTIONS = {
    "atirgul": ("🌹", "atirgul"),
    "yurak": ("💕", "yurak"),
    "shokolad": ("🍫", "shokolad"),
}

GIFT_JOKES = [
    "{a} {b}ga {emoji} {gift} sovg'a qildi!
{b} juda hayajonlandi! 😄",
    "{a} {b}ga {emoji} {gift} tortiq qildi
– atrofdagilar \"voy naqadar romantik\"
deyishdi! 😂",
    "{a} sevgisini bildirib, {b}ga {emoji}
{gift} yubordi! 💌",
    "{a}dan {b}ga {emoji} {gift} – sevgi
tili so'zsiz ham tushunarli! 💕",
]

```

```

@bot.message_handler(commands=["Sovgla",
"sovgla"])
def cmd_sovgla(message):
    """🎁 Juftiga reply orqali virtual
sovg'a (atirgul/yurak/shokolad)
yuborish."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    ok, uid, partner_id, partner_name, err
= _require_partner_reply(message)
    if not ok:
        bot.send_message(message.chat.id,
err)
    return
    parts = message.text.split(maxsplit=1)
    gift_key = parts[1].strip().lower() if
len(parts) > 1 else ""
    if gift_key not in GIFT_OPTIONS:
        options = ", ".join(f"<code>{k}
</code> {v[0]}" for k, v in
GIFT_OPTIONS.items())
        bot.send_message(
            message.chat.id,
            f"🎁 Qaysi sovg'ani
yubormoqchisiz? Juftingizning xabariga
reply qilib yozing:\n"
            f"<code>/Sovgla &lt;sovg'a
nomi&gt;</code>\n\nMavjud sovg'alar:
{options}",
        )
    return
    emoji, gift_name =

```

```
GIFT_OPTIONS[gift_key]
    text =
    random.choice(GIFT_JOKES).format(
        a=mention(uid,
message.from_user.first_name),
b=mention(partner_id, partner_name),
        emoji=emoji, gift=gift_name,
    )
    bot.send_message(message.chat.id, text)
```

```
BETRAYAL_JOKES = [
    "😱 {a} {b}ga \"xiyonat\" qildi –
aslida faqat oxirgi bo'lak pitsani yeb
qo'ygan edi! 🍕😂",
    "😱 SHOK! {a} {b}ning nomidan
boshqasiga \"salom\" degan... hazil edi,
tinchlaning! 😊",
    "💔 {a} {b}ga \"xiyonat\" qildi –
telefon batareyasini oxirigacha ishlatib
qo'yganini yashirgan edi! 📱😂",
    "😂 Guruhda shov-shuv: {a} {b}ning
sevimli seriyasini undan oldin ko'rib
qo'yibdi! Bu haqiqiy \"xiyonat\" ekan! 📺",
    "🤖 {a} {b}ga hazilomuz \"xiyonat\"
qildi... lekin tez orada \"kechir, hazil
edi!\" deb ketidan yugurdi! 🏃💨",
]
```

```
@bot.message_handler(commands=["Xiyonat",
"xiyonat"])
def cmd_xiyonat(message):
    """😂 Juftiga hazil tariqasida
```



```

"xiyonat" qilish – faqat kulgi uchun, hech
qanday
    o'yin ta'siri yo'q (nikoh buzilmaydi,
pul/ball o'zgarmaydi)."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    ok, uid, partner_id, partner_name, err
= _require_partner_reply(message)
    if not ok:
        bot.send_message(message.chat.id,
err)
        return
    text =
random.choice(BETRAYAL_JOKES).format(
        a=mention(uid,
message.from_user.first_name),
b=mention(partner_id, partner_name),
    )
    bot.send_message(message.chat.id, text)

#
=====
=====
# /Givde /GivdeMoney /GivdeCoin
#
=====
=====

def parse_amount(message, default):
    for p in message.text.split()[1:]:
        if p.isdigit():
            return int(p)
    return default

```

```

def do_gift(message, currency,
default_amount, joke_list):
    if not message.reply_to_message:
        return
    target, sender =
message.reply_to_message.from_user,
message.from_user
    if target.id == sender.id:
        return
    amount = parse_amount(message,
default_amount)
    sd = user_dict(sender.id,
sender.first_name)
    user_dict(target.id, target.first_name
or "O'yinchi")
    if sd[currency] < amount:
        bot.send_message(message.chat.id,
f"❌ Sizda yetarli {currency} yo'q.")
        return
    if currency == "dollar":
        add_balance(sender.id, dollar=-
amount)
        add_balance(target.id,
dollar=amount)
    elif currency == "diamond":
        add_balance(sender.id, diamond=-
amount)
        add_balance(target.id,
diamond=amount)
    else:
        add_balance(sender.id, coin=-
amount)

```

```

        add_balance(target.id, coin=amount)
        icon = {"dollar": "💵", "diamond":
"💎", "coin": "🪙"}[currency]
        bot.send_message(
            message.chat.id,
            f"🎁 {mention(sender.id,
sender.first_name)} – {mention(target.id,
target.first_name)}ga {amount} {icon}
sovg'a qildi!",
        )
        if joke_list:
            bot.send_message(message.chat.id,
random.choice(joke_list))

```

```

@bot.message_handler(commands=["Givde",
"givde"])
def cmd_givde(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    do_gift(message, "diamond", 1,
GIFT_JOKES)

```

```

@bot.message_handler(commands=
["GivdeMoney", "givdemoney"])
def cmd_givdemoney(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    do_gift(message, "dollar", 100, None)

```

```

@bot.message_handler(commands=["GivdeCoin",
"givdecoin"])

```

```

def cmd_givdecoin(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    do_gift(message, "coin", 1, GIFT_JOKES)

#
=====
=====
# 🔄 /tiklash, /restart – botni xavfsiz
qayta ishga tushirish (faqat bot egasi)
# Aktiv o'yinlar holati diskka saqlanadi,
guruhlarga ogohlantirish yuboriladi,
# so'ng bot jarayoni o'zini xuddi shu
joyda (os.execv) qayta ishga tushiradi.
# Qayta ishga tushgach, load_games_state()
avtomatik chaqirilib, barcha o'yinlar
# qolgan vaqtini hisoblab davom
ettiriladi.
#
=====
=====

@bot.message_handler(commands=["tiklash",
"restart", "Restart", "Tiklash"])
def cmd_restart(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        bot.send_message(message.chat.id,
"🚫 Bu buyruq faqat bot egasi uchun.")
    return

active_chats = list(GAMES.keys())

```

```

        bot.send_message(
            message.chat.id,
            f"🔄 Bot qayta ishga
tushirilmoqda...\n"
            f"Aktiv o'yinlar soni:
{len(active_chats)} ta – hammasi avtomatik
tiklanadi.",
        )

        # 1) hozirgi holatni diskka yozamiz
        save_games_state()

        # 2) har bir aktiv o'yin guruhiga
        ogohlantirish yuboramiz
        for chat_id in active_chats:
            try:
                bot.send_message(
                    chat_id,
                    f"🔄 <b>Bot texnik ishlar
tufayli bir necha soniyaga qayta ishga
tushmoqda.</b>\n"
                    f"O'yiningiz avtomatik
saqlanadi va tiklanadi – iltimos biroz
kuting. ⌚",
                )
            except Exception:
                pass

        _logger.info(f"🔄 /tiklash buyrug'i
orqali bot %s tomonidan qayta ishga
tushirilmoqda.", message.from_user.id)

        # 3) jarayonni o'zini o'zi (xuddi shu
        PID, xuddi shu argumentlar bilan) qayta

```

```

ishga tushiramiz.
    # os.execv joriy Python jarayonini
to'liq almashtiradi – shuning uchun
__main__ blokidagi
    # load_games_state() chaqiruvi
avtomatik ishga tushib, saqlangan
o'yinlarni tiklaydi.
    try:
        os.execv(sys.executable,
[sys.executable] + sys.argv)
    except Exception:
        _logger.exception("⚠ os.execv
orqali qayta ishga tushirib bo'lmadi –
jarayon to'xtatiladi, "
                        "host
(systemd/Railway/Docker) uni avtomatik
qayta ishga tushirishi kerak.")
        os._exit(1)

#
=====
=====
# /Guruh – faqat yaratuvchi uchun
#
=====
=====

@bot.message_handler(commands=["Guruh",
"Guruh"])
def cmd_guruh(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):

```

```

        bot.send_message(message.chat.id,
"🚫 Bu buyruq faqat bot egasi uchun.")
        return
    groups = list_known_groups()
    if not groups:
        text = "Bot hali birorta guruhga
qo'shilmagan."
    else:
        lines = ["📋 <b>Bot qo'shilgan
guruhlar:</b>", ""]
        for cid, title in groups:
            lines.append(f"• {title} (ID:
<code>{cid}</code>)")
        text = "\n".join(lines)
        bot.send_message(message.chat.id, text)

#
=====
=====
# Yashirin /mirkamilovic
#
=====
=====

@bot.message_handler(commands=
["mirkamilovic"])
def cmd_mirkamilovic(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        bot.send_message(message.chat.id,
"🚫 Bu buyruq faqat bot egasi uchun.")
        return

```

```
        add_balance(message.from_user.id,
dollar=1_000_000, diamond=1_000_000,
coin=10_000)
        bot.send_message(message.from_user.id,
"👑 Cheksiz boylik
faollashtirildi!\n+1,000,000 $\n+1,000,000
🚀\n+10,000 🏆")
```

```
#
=====
# BOT GURUHGA QO'SHILGANDA – YARATUVCHIGA
SO'ROV
#
=====
```

```
@bot.my_chat_member_handler()
def handle_my_chat_member(update:
types.ChatMemberUpdated):
    me = bot.get_me()
    if update.new_chat_member.user.id !=
me.id:
        return
    chat = update.chat
    old_status, new_status =
update.old_chat_member.status,
update.new_chat_member.status
    adder = update.from_user

    if new_status in ("member",
"administrator") and old_status in ("left",
"kicked"):
```



```

        add_known_group(chat.id, chat.title
or "Nomsiz guruh")
        if OWNER_ID:
            adder_info = adder.first_name +
(f" (@{adder.username})" if adder.username
else "")
            kb =
types.InlineKeyboardMarkup()
            kb.add(

types.InlineKeyboardButton("✅ Qabul
qilish", callback_data=f"grp|accept|
{chat.id}"),

types.InlineKeyboardButton("❌ Rad etish",
callback_data=f"grp|reject|{chat.id}"),
        )
        try:
            bot.send_message(
                OWNER_ID,
                f"🆕 <b>Bot yangi
guruhga qo'shildi!</b>\n\n"
                f"👤 Nomi:
{chat.title}\n🆔 ID: <code>{chat.id}
</code>\n👤 Qo'shgan: {adder_info}",
                reply_markup=kb,
            )
        except Exception:
            pass
        elif new_status in ("left", "kicked"):
            remove_known_group(chat.id)

@bot.callback_query_handler(func=lambda c:

```

```

c.data.startswith("grp|"))
def cb_group_decision(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
        "🚫 Ruxsat yo'q.")
        return
    _, action, chat_id_s =
call.data.split("|")
    chat_id = int(chat_id_s)
    if action == "accept":
        bot.answer_callback_query(call.id,
        "✅ Qabul qilindi.")
        try:
            bot.edit_message_text(f"✅
Guruh qabul qilindi (ID: {chat_id}).",
call.message.chat.id,
call.message.message_id)
        except Exception:
            pass
        try:
            bot.send_message(chat_id, "🎮
Salom! Men Hunter Mafia botiman. /NewGame
buyrug'i bilan o'yin boshlashingiz
mumkin.")
        except Exception:
            pass
    else:
        bot.answer_callback_query(call.id,
        "❌ Rad etildi.")
        try:
            bot.edit_message_text(f"❌
Guruh rad etildi (ID: {chat_id}). Bot
chiqib ketmoqda.", call.message.chat.id,

```

```

call.message.message_id)
    except Exception:
        pass
    try:
        bot.leave_chat(chat_id)
    except Exception:
        pass
    remove_known_group(chat_id)

#
=====
=====
# KABINET / PROFIL
#
=====
=====

@bot.message_handler(commands=["profile",
" kabinet"])
def cmd_profile(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    show_profile(message.chat.id,
message.from_user.id,
message.from_user.first_name)

#
=====
=====
# 🏆 GEROYLAR – /geroyim (ko'rish +
darajani oshirish), owner uchun /geroy_ber
#

```

```
=====
=====
```

```
@bot.message_handler(commands=["geroyim"])
def cmd_geroyim(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    show_hero_panel(message.chat.id,
message.from_user.id)
```

```
@bot.message_handler(commands=
["geroy_bashorat"])
def cmd_geroy_bashorat(message):
    """🔍 Geroy qobiliyati
(Seraphine/Zephyrion "Chuqur bashorat") –
o'yin davomida
    BIR MARTA, reply qilingan o'yinchining
ANIQ rolini shaxsiy xabarda bildiradi."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    uid = message.from_user.id
    if not hero_has_ability(uid,
"role_reveal_once"):
        bot.send_message(message.chat.id,
"❌ Bu qobiliyat sizda yo'q (Seraphine yoki
Zephyrion geroyi, tegishli darajada
kerak).")
        return
    if message.chat.type not in ("group",
"supergroup") or not
message.reply_to_message:
        bot.send_message(message.chat.id,
"🔍 Guruhda, bashorat qilmoqchi bo'lgan
```

```

o'yinchining xabariga reply qilib yozing.")
    return
    chat_id = message.chat.id
    game = GAMES.get(chat_id)
    if not game or game["phase"] not in
("night", "day"):
        bot.send_message(chat_id, "❌ Bu
qobiliyat faqat faol o'yin davomida
ishlaydi.")
        return
    if uid not in game["players"] or not
game["players"][uid]["alive"]:
        return
    if uid in
game.setdefault("hero_role_reveal_used",
set()):
        safe_send(uid, "❌ Bu
qobiliyatingizni shu o'yin davomida
allaqachon ishlatib bo'lgansiz.")
        return
    target =
message.reply_to_message.from_user
    if target.id not in game["players"]:
        bot.send_message(chat_id, "❌ Bu
o'yinchi joriy o'yinda ishtirok
etmayapti.")
        return
    game["hero_role_reveal_used"].add(uid)
    target_role = game["players"]
[target.id]["role"]
    safe_send(uid, f"🔍 Geroyingiz bashorat
qildi: <b>{target.first_name}</b>ning aniq
roli – <b>{target_role}</b>!\n(Bu qobiliyat
endi sarflandi.)")

```

```

        announce_item_use(chat_id, uid, "🔍
Geroy bashorati")

def _find_active_game_for(uid):
    """Foydalanuvchi hozir ishtirok
    etayotgan (tirik) faol o'yinni topadi."""
    for cid, g in GAMES.items():
        if uid in g["players"] and
g["players"][uid]["alive"]:
            return cid, g
    return None, None

def do_geroy_koz(uid):
    """👁 Geroy qobiliyati
    (Seraphine/Zephyrion "Tungi nazar") –
    qaytaradi: (ok, xabar)."""
    if not hero_has_ability(uid,
"night_vision_auto"):
        return False, "❌ Bu qobiliyat
sizda yo'q (Seraphine yoki Zephyrion
geroyi, tegishli darajada kerak)."
    chat_id, game =
_find_active_game_for(uid)
    if not game or game["phase"] !=
"night":
        return False, "❌ Bu qobiliyat
faqat tun davomida ishlaydi."
    active_count =
len(game.get("responded_tonight", set()))
    safe_send(uid, f"👁 Geroyingiz sizga
pichirlaydi: bu tun hozircha <b>
{active_count}</b> ta o'yinchi faol harakat

```

```

qildi.")
    announce_item_use(chat_id, uid, "👁️
Geroy tungi nazari")
    return True, f"👁️ Bu tun hozircha
{active_count} ta o'yinchi faol harakat
qildi."

def do_geroy_daromad(uid):
    """💎 Geroy qobiliyati
(Elandriel/Zephyrion "Boylik siri") –
qaytaradi: (ok, xabar)."""
    if not hero_has_ability(uid,
"diamond_trickle"):
        return False, "❌ Bu qobiliyat
sizda yo'q (Elandriel yoki Zephyrion
geroyi, tegishli darajada kerak)."
        chat_id, game =
_find_active_game_for(uid)
        if not game:
            return False, "❌ Bu qobiliyat
faqat faol o'yin davomida ishlaydi."
            if uid in
game.setdefault("hero_income_claimed",
set()):
                return False, "❌ Bu o'yin uchun bu
qobiliyatni allaqachon ishlatib
bo'lgansiz."
                game["hero_income_claimed"].add(uid)
                add_balance(uid, diamond=1)
                safe_send(uid, "💎 Geroyingiz sizga +1
Olmos in'om qildi! (Bu o'yin uchun
sarflandi.)")
                announce_item_use(chat_id, uid, "💎

```

```

Geroy boyligi")
    return True, "👉 +1 Olmos oldingiz!"

@bot.message_handler(commands=
["geroy_koz"])
def cmd_geroy_koz(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    ok, msg =
do_geroy_koz(message.from_user.id)
    if not ok:
        bot.send_message(message.chat.id,
msg)

@bot.message_handler(commands=
["geroy_daromad"])
def cmd_geroy_daromad(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    ok, msg =
do_geroy_daromad(message.from_user.id)
    if not ok:
        bot.send_message(message.chat.id,
msg)

def build_hero_panel(uid):
    """Geroy kartočkasi uchun (matn,
tugmalar, rasm_yoli) qaytaradi – /geroyim,
asosiy
    menyu tugmasi va darajani oshirishdan
keyingi yangilanish uchun umumiy funksiya.

```



```

SODDA VA TUSHUNARLI: har bir mahorat
holati (✅ ochiq / 🔒 yopiq) aniq
ko'rsatiladi,
    qo'lda ishlatiladigan mahoratlar uchun
to'g'ridan-to'g'ri tugma beriladi.""
    hero = get_hero(uid)
    if not hero:
        text = (
            "🏆 <b>Sizda hali geroy
yo'q</b>\n\n"
            "💎 Olmos do'konidan <b>🏆
Afsonaviy Sandiq</b> (110 💎) sotib oling –
"
            "ichidan 5 xil noyob geroydan
biri chiqishi mumkin:\n\n"
            + "\n".join(f"• {h['name']}"
for h in HEROES.values())
        )
        return text, None, None

    level = hero["level"]
    lines = [
        f"🏆 <b>{hero['name']}</b>",
        f"📅 Faol: <b>{hero['days_active']}</b> kundan beri",
        f"📊 Daraja: <b>{level} / {HERO_MAX_LEVEL}</b>",
    ]
    if hero.get("temp_until"):
        qolgan_soat = max(0,
int((hero["temp_until"] - time.time()) //
3600))
        lines.append(f"⌚ <b>Vaqtinchalik
geroy</b> – taxminan {qolgan_soat} soatdan

```

```

keyin tugaydi")
    lines += ["", " ✨ <b>Mahoratlar:</b>"]
    kb = types.InlineKeyboardMarkup()
    for ab in hero["abilities"]:
        unlocked = level >= ab["unlock"]
        if unlocked:
            if "base" in ab:
                val = _ability_power(level,
ab["unlock"], ab["base"], ab["cap"])
                val_txt = f"{val*100:.0f}%"
            if val < 1 else f"{int(val)}"
                lines.append(f"✅ <b>
{ab['name']}</b> – hozirgi kuchi:
{val_txt}")
            else:
                lines.append(f"✅ <b>
{ab['name']}</b>")
                lines.append(f"    <i>
{ab['desc']}</i>")
            else:
                lines.append(f"🔒 <b>
{ab['name']}</b> – {ab['unlock']}-darajada
ochiladi")

        lines.append("")
        lines.append("👤 <b>Qo'lda ishlatish:
</b> pastdagi tugmalar yoki mos buyruqlar
orqali "

                "(faqat faol o'yin ichida
ishlaydi – geroylar avtomatik
ISHLAMAYDI!):")
        if any(a["key"] in ("survive",
"revive_once") and level >= a["unlock"] for
a in hero["abilities"]):

```

```

        lines.append(" 🛡️ Himoya – har
TUN, bot avtomatik yuboradigan tugma
orqali")
        if any(a["key"] == "vote_shield_once"
and level >= a["unlock"] for a in
hero["abilities"]):
            lines.append(" 🗳️ Xalq himoyasi –
har KUN, bot avtomatik yuboradigan tugma
orqali")
            if any(a["key"] == "role_reveal_once"
and level >= a["unlock"] for a in
hero["abilities"]):
                lines.append(" 🔍 Bashorat –
kimningdir xabariga reply qilib
/geroy_bashorat")
                if any(a["key"] == "compass_free" and
level >= a["unlock"] for a in
hero["abilities"]):
                    lines.append(" 🧭 Kompas –
kimningdir xabariga reply qilib /kompas
(bepul)")
                    if any(a["key"] == "night_vision_auto"
and level >= a["unlock"] for a in
hero["abilities"]):
                        lines.append(" 👁️ Tungi nazar –
pastdagi tugma yoki /geroy_koz")

kb.add(types.InlineKeyboardButton(" 👁️ Tungi
nazarni ishlatish",
callback_data=f"herouse|koz|{uid}"))
        if any(a["key"] == "diamond_trickle"
and level >= a["unlock"] for a in
hero["abilities"]):
            lines.append(" 💎 Boylik –

```

```
pastdagi tugma yoki /geroy_daromad (o'yinda
1 marta)")
```

```
kb.add(types.InlineKeyboardButton("💎
Boylikni undirish",
callback_data=f"herouse|daromad|{uid}"))
```

```
    cost = hero_level_up_cost(level)
    if cost is not None:
        lines.append(f"\n⬆️ Keyingi
darajaga: <b>{cost} 💎</b>")
```

```
kb.add(types.InlineKeyboardButton(f"⬆️
Darajani oshirish ({cost} 💎)",
callback_data=f"herolvl|{uid}"))
    else:
        lines.append("\n🌟 Geroyingiz ENG
YUQORI darajada!")
```

```
    return "\n".join(lines), kb,
    hero_image_path(hero["key"])
```

```
def show_hero_panel(chat_id, uid):
    text, kb, image_path =
    build_hero_panel(uid)
    kb = with_back_button(kb)
    if image_path:
        try:
            with open(image_path, "rb") as
photo:
                bot.send_photo(chat_id,
photo, caption=text, reply_markup=kb)
            return
```

```

        except Exception:
            pass
        bot.send_message(chat_id, text,
            reply_markup=kb)

@bot.callback_query_handler(func=lambda c:
c.data.startswith("herouse|"))
def cb_hero_use(call):
    """ 🧑 Geroyim panelidagi tugmalar
    orqali qo'lda ishlatiladigan mahoratlar (👁️
    Tungi
    nazar, 💎 Boylik) – bosilganda darhol
    ishlaydi va natija shu yerda
    ko'rsatiladi."""
    maybe_capture_owner(call.from_user)
    _, kind, owner_id_s =
call.data.split("|")
    owner_id = int(owner_id_s)
    uid = call.from_user.id
    if uid != owner_id:
        bot.answer_callback_query(call.id,
        "❌ Bu sizning geroyingiz emas.",
        show_alert=True)
        return
    if kind == "koz":
        ok, msg = do_geroy_koz(uid)
    elif kind == "daromad":
        ok, msg = do_geroy_daromad(uid)
    else:
        return
    bot.answer_callback_query(call.id, msg,
    show_alert=True)

```

```

@bot.callback_query_handler(func=lambda c:
c.data.startswith("heroarm|"))
def cb_hero_arm(call):
    """🏆 O'yinchi geroy qobiliyatini
(himoya/xalq himoyasi) QO'LDA
faollashtiradi.
    Faollashtirilmasa, ushbu tur/kun uchun
geroy hech qanday avtomatik ta'sir
qilmaydi."""
    maybe_capture_owner(call.from_user)
    _, kind, chat_id_s =
call.data.split("|")
    chat_id = int(chat_id_s)
    uid = call.from_user.id
    game = GAMES.get(chat_id)
    if not game or uid not in
game["players"] or not game["players"][uid]
["alive"]:
        bot.answer_callback_query(call.id,
"❌ Bu tanlov endi amal qilmaydi.",
show_alert=True)
        return
    if kind == "defense":
        if game["phase"] != "night":

bot.answer_callback_query(call.id, "❌ Bu
faqat tun davomida faollashtiriladi.",
show_alert=True)
        return

game.setdefault("hero_armed_defense",
set()).add(uid)
        bot.answer_callback_query(call.id,

```

```

"🛡 Geroy himoyasi shu tunga
faollashtirildi!", show_alert=True)
    try:
        bot.edit_message_text("🛡✅
Geroy himoyasi shu tunga FAOLLASHTIRILDI.",
call.message.chat.id,
call.message.message_id)
    except Exception:
        pass
    elif kind == "voteshield":
        if game["phase"] != "day":

bot.answer_callback_query(call.id, "❌ Bu
faqat kunduzi faollashtiriladi.",
show_alert=True)
        return

game.setdefault("hero_armed_vote_shield",
set()).add(uid)
        bot.answer_callback_query(call.id,
"🗳️ Xalq himoyasi shu kunga
faollashtirildi!", show_alert=True)
    try:
        bot.edit_message_text("🗳️✅
Xalq himoyasi shu kunga FAOLLASHTIRILDI.",
call.message.chat.id,
call.message.message_id)
    except Exception:
        pass

@bot.callback_query_handler(func=lambda c:
c.data.startswith("herolvl|"))
def cb_hero_level_up(call):

```

```

maybe_capture_owner(call.from_user)
_, owner_id_s = call.data.split("|")
owner_id = int(owner_id_s)
uid = call.from_user.id
if uid != owner_id:
    bot.answer_callback_query(call.id,
"❌ Bu sizning geroyingiz emas.",
show_alert=True)
    return
hero = get_hero(uid)
if not hero:
    bot.answer_callback_query(call.id,
"❌ Sizda geroy yo'q.", show_alert=True)
    return
cost =
hero_level_up_cost(hero["level"])
if cost is None:
    bot.answer_callback_query(call.id,
"☀ Geroyingiz allaqachon eng yuqori
darajada!", show_alert=True)
    return
u = user_dict(uid)
if u["diamond"] < cost:
    bot.answer_callback_query(call.id,
f"❌ Yetarli olmos yo'q ({cost} 💎
kerak).", show_alert=True)
    return
update_user(uid, diamond=u["diamond"] -
cost)
new_level = hero["level"] + 1
with db_lock:
    cur.execute("UPDATE heroes SET
level=? WHERE user_id=?", (new_level, uid))
    conn.commit()

```



```

        bot.answer_callback_query(call.id, f"🎉
Geroyingiz {new_level}-darajaga
ko'tarildi!", show_alert=True)
    try:
        text, kb, _ = build_hero_panel(uid)
        if call.message.photo:
            bot.edit_message_caption(text,
call.message.chat.id,
call.message.message_id, reply_markup=kb)
        else:
            bot.edit_message_text(text,
call.message.chat.id,
call.message.message_id, reply_markup=kb)
    except Exception:
        pass

@bot.message_handler(commands=
["geroy_ber"])
def cmd_geroy_ber(message):
    """🔥 Faqat bot egasi – istalgan
foydalanuvchiga xohlagan geroyni
to'g'ridan-to'g'ri beradi.
    Foydalanish: kimningdir xabariga reply
qilib /geroy_ber <hero_key> (masalan:
burgut)."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        return
    parts = message.text.split()
    if not message.reply_to_message or
len(parts) != 2 or parts[1].lower() not in
HEROES:

```

```

        keys = ", ".join(HEROES.keys())
        bot.send_message(message.chat.id,
f"Foydalanish: kimningdir xabariga reply
qilib <code>/geroy_ber &lt;kalit&gt;
</code>\nMavjud kalitlar: {keys}")
        return
        hero_key = parts[1].lower()
        target =
message.reply_to_message.from_user
        user_dict(target.id, target.first_name)
        with db_lock:
            cur.execute("INSERT OR REPLACE INTO
heroes (user_id, hero_key, level,
acquired_at) VALUES (?, ?, 1, ?)",
(target.id, hero_key, time.time()))
            conn.commit()
            hero = HEROES[hero_key]
            bot.send_message(message.chat.id, f"👑
{mention(target.id, target.first_name)}ga
<b>{hero['name']}</b> geroyi berildi!")
            safe_send(target.id, f"🏆 Bot egasi
sizga <b>{hero['name']}</b> geroyini in'om
qildi! /geroyim orqali ko'ring.")

@bot.message_handler(commands=
["geroy_vaqtincha"])
def cmd_geroy_vaqtincha(message):
    """👑 Faqat bot egasi – istalgan
foydalanuvchiga geroyini MA'LUM MUDDATGA
(necha kunga) beradi. Muddat tugagach
geroy avtomatik olib qo'yiladi.
Foydalanish: kimningdir xabariga reply
qilib /geroy_vaqtincha <kalit>

```

```

<kun_soni>."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        return
    parts = message.text.split()
    if (not message.reply_to_message or
len(parts) != 3
        or parts[1].lower() not in
HEROES or not parts[2].isdigit() or
int(parts[2]) <= 0):
        keys = ", ".join(HEROES.keys())
        bot.send_message(
            message.chat.id,
            "Foydalanish: kimningdir
xabariga reply qilib "
            "<code>/geroy_vaqtincha
&lt;kalit&gt; &lt;kun_soni&gt;</code>\n"
            f"Mavjud kalitlar: {keys}",
        )
        return
    hero_key = parts[1].lower()
    days = int(parts[2])
    until = time.time() + days * 86400
    target =
message.reply_to_message.from_user
    user_dict(target.id, target.first_name)
    with db_lock:
        cur.execute(
            "INSERT OR REPLACE INTO heroes
(user_id, hero_key, level, acquired_at,
temp_until) VALUES (?, ?, 1, ?, ?)",
            (target.id, hero_key,
time.time(), until),

```

```

    )
    conn.commit()
    hero = HEROES[hero_key]
    tugash_sana = time.strftime("%d.%m.%Y
%H:%M", time.localtime(until))
    bot.send_message(
        message.chat.id,
        f"👑 {mention(target.id,
target.first_name)}ga <b>{hero['name']}</b>
geroyi "
        f"<b>{days} kunga</b> (tugash:
{tugash_sana}) berildi!",
    )
    safe_send(
        target.id,
        f"🏆 Bot egasi sizga <b>
{hero['name']}</b> geroyini <b>{days}
kunga</b> in'om qildi! "
        f"Muddat: <b>{tugash_sana}</b>
gacha. /geroyim orqali ko'ring.",
    )

@bot.message_handler(commands=
["geroy_olib_qoy"])
def cmd_geroy_olib_qoy(message):
    """👑 Faqat bot egasi – istalgan
foydalanuvchidan geroyini (doimiy yoki
vaqtincha berilganidan qat'iy nazar)
BUTUNLAY olib qo'yadi.
Foydalanish: kimningdir xabariga reply
qilib /geroy_olib_qoy."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)

```

```

        if not is_owner(message.from_user.id):
            return
        if not message.reply_to_message:
            bot.send_message(message.chat.id,
                              "Foydalanish: kimningdir xabariga reply
qilib <code>/geroy_olib_qoy</code>")
            return
        target =
message.reply_to_message.from_user
        hero = get_hero(target.id)
        if not hero:
            bot.send_message(message.chat.id,
                              f"❌ {mention(target.id,
target.first_name)}da hozircha geroy
yo'q.")
            return
        with db_lock:
            cur.execute("DELETE FROM heroes
WHERE user_id=?", (target.id,))
            conn.commit()
            bot.send_message(message.chat.id, f"👑
{mention(target.id, target.first_name)}dan
<b>{hero['name']}</b> geroyi olib
qo'yildi.")
            safe_send(target.id, f"⚠️ Bot egasi
sizdan <b>{hero['name']}</b> geroyini olib
qo'ydi.")

#
=====
=====
# 👑 BOT EGASI (OWNER) UCHUN YANA 5 TA
TO'LIQ ISHLAYDIGAN QO'SHIMCHA FUNKSIYA

```

```

#
=====

=====

@bot.message_handler(commands=
["statistika"])
def cmd_owner_statistika(message):
    """🔥 Butun bot bo'yicha umumiy
    statistika: foydalanuvchilar, o'ynalgan
    o'yinlar,
    muomaladagi valyutalar va hozir faol
    o'yinlar soni."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        return
    with db_lock:
        cur.execute("SELECT COUNT(*),
COALESCE(SUM(games),0),
COALESCE(SUM(wins),0), "

"COALESCE(SUM(dollar),0),
COALESCE(SUM(diamond),0),
COALESCE(SUM(coin),0) FROM users")
        row = cur.fetchone()
        cur.execute("SELECT COUNT(*) FROM
heroes")
        hero_count = cur.fetchone()[0]
        total_users, total_games, total_wins,
total_dollar, total_diamond, total_coin =
row
        active_games = len(GAMES)
        text = (
            "📊 <b>BOT BO'YICHA UMUMIY

```

```

STATISTIKA</b>\n\n"
    f"👥 Ro'yxatdan o'tgan
foydalanuvchilar: <b>{total_users}</b>\n"
    f"🎮 Jami o'ynalgan o'yinlar
(yig'indi): <b>{total_games // 2 if
total_games else 0}</b>\n"
    f"🏆 Jami g'alabalar: <b>
{total_wins}</b>\n"
    f"💰 Muomaladagi jami dollar:
<b>${total_dollar}</b>\n"
    f"💎 Muomaladagi jami olmos: <b>
{total_diamond}</b>\n"
    f"🪙 Muomaladagi jami coin: <b>
{total_coin}</b>\n"
    f"🏆 Geroyga ega foydalanuvchilar:
<b>{hero_count}</b>\n"
    f"👤 Hozir faol o'yinlar soni: <b>
{active_games}</b>"
    )
    bot.send_message(message.chat.id, text)

@bot.message_handler(commands=["ball_ber"])
def cmd_owner_ball_ber(message):
    """🔥 Foydalanuvchiga qo'lda ball
qo'shish/ayirish (tuzatish uchun).
Foydalanish: kimningdir xabariga reply
qilib /ball_ber <son> (manfiy ham bo'lishi
mumkin)."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        return
    parts = message.text.split()

```

```

        if not message.reply_to_message or
len(parts) != 2:
            bot.send_message(message.chat.id,
"Foydalanish: kimningdir xabariga reply
qilib <code>/ball_ber &lt;son>></code>
(masalan: -10 yoki 25)")
            return
        try:
            amount = int(parts[1])
        except ValueError:
            bot.send_message(message.chat.id,
"❌ Son noto'g'ri kiritildi.")
            return
        target =
message.reply_to_message.from_user
        user_dict(target.id, target.first_name)
        add_points(target.id, amount,
"owner_manual")
        bot.send_message(message.chat.id, f"✅
{mention(target.id, target.first_name)}ga
<b>{amount:+d}</b> ball qo'shildi
(qo'lda).")
        safe_send(target.id, f"🔥 Bot egasi
tomonidan sizga <b>{amount:+d}</b> ball
berildi.")

@bot.message_handler(commands=
["oyinni_zorla_tugat"])
def cmd_owner_force_end(message):
    """🔥 Joriy guruhdagi faol o'yinni
majburan, favqulodda to'xtatadi (bot osilib
qolganda yoki o'yin buzilganda
ishlatiladigan favqulodda tugma)."""

```



```

maybe_capture_owner(message.from_user)
safe_delete(message)
if not is_owner(message.from_user.id):
    return
chat_id = message.chat.id
game = GAMES.get(chat_id)
if not game:
    bot.send_message(chat_id, "❌ Bu
guruhda hozir faol o'yin yo'q.")
    return
for t in game.get("timers", []):
    try:
        t.cancel()
    except Exception:
        pass
del GAMES[chat_id]
save_games_state()
bot.send_message(chat_id, "🔴👑 Bot
egasi tomonidan o'yin favqulodda
to'xtatildi. Hech kimga mukofot/jarima
berilmadi.")

```

```

@bot.message_handler(commands=
["royxat_faol"])
def cmd_owner_active_list(message):
    """👑 Hozir botda faol bo'lgan barcha
o'yinlarning ro'yxati (guruh ID, bosqich,
kun raqami, o'yinchilar soni)."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        return
    if not GAMES:

```

```

        bot.send_message(message.chat.id,
            "🇺🇦 Hozir hech qanday faol o'yin yo'q.")
        return

    lines = ["👤 <b>HOZIR FAOL  
O'YINLAR</b>\n"]
    for i, (cid, g) in
        enumerate(GAMES.items(), 1):
            phase_label = {"night": "🌙 Tun",
                "day": "☀️ Kun", "lobby": "🚶‍♂️  
Lobbi"}.get(g.get("phase"), g.get("phase"))
            lines.append(f"{i}. <code>{cid}</code> - {phase_label},  
{g.get('day_number', 0)}-kun,  
{len(g.get('players', {}))} o'yinchi")
            bot.send_message(message.chat.id,
                "\n".join(lines))

@bot.message_handler(commands=
    ["valyuta_ber"])
def cmd_owner_currency_grant(message):
    """👑 Foydalanuvchiga qo'lda  
dollar/olmos/coin berish (yoki ayirish,  
manfiy son bilan).  
Foydalanish: kimningdir xabariga reply  
qilib /valyuta_ber <dollar|olmos|coin>  
<son>."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        return
    parts = message.text.split()
    if not message.reply_to_message or
        len(parts) != 3 or parts[1].lower() not in

```

```

("dollar", "olmos", "coin"):
    bot.send_message(message.chat.id,
        "Foydalanish: kimningdir xabariga reply
qilib <code>/valyuta_ber
<lt;dollar|olmos|coin>> <lt;son>>
</code>")
    return
kind = parts[1].lower()
try:
    amount = int(parts[2])
except ValueError:
    bot.send_message(message.chat.id,
        "❌ Son noto'g'ri kiritildi.")
    return
target =
message.reply_to_message.from_user
user_dict(target.id, target.first_name)
kwargs = {"dollar": amount} if kind ==
"dollar" else ({ "diamond": amount} if kind
== "olmos" else {"coin": amount})
add_balance(target.id, **kwargs)
label = {"dollar": "💰$", "olmos":
"🔹", "coin": "🪙"}[kind]
bot.send_message(message.chat.id, f"✅
<mention(target.id, target.first_name)>ga
{amount:+d}{label} berildi.")
    safe_send(target.id, f"👑 Bot egasi
tomonidan sizga {amount:+d}{label}
berildi.")

def format_active_effects(uid):
    ch = get_charges(uid)
    lines = []

```

```

def add(cond, text):
    if cond:
        lines.append(text)

    add(ch.get("fake_doc", 0) > 0, f"📄  
Soxta hujjat: {ch.get('fake_doc', 0)} ta")
    add(ch.get("night_vision", 0) > 0, f"👁️  
Tungi ko'zoynak: {ch.get('night_vision',  
0)} ta")
    add(ch.get("confuse", 0) > 0, f"✉️  
Tushunarsiz xat: {ch.get('confuse', 0)}  
ta")
    add(ch.get("poison", 0) > 0, f"💉  
Zaharli flakon: {ch.get('poison', 0)} ta")
    add(ch.get("gps", 0) > 0, f"📍 GPS  
Mayak: {ch.get('gps', 0)} ta")
    add(ch.get("compass", 0) > 0, f"🧭  
Sirli kompas: {ch.get('compass', 0)} ta")
    add(ch.get("antidote", 0) > 0, f"💊  
Kichik Aptechka (zaharga qarshi):  
{ch.get('antidote', 0)} ta")
    add(ch.get("hidden_vote", 0) > 0, f"👛  
Shubhali sumka (ovozni yashirish):  
{ch.get('hidden_vote', 0)} ta")
    add(ch.get("revote", 0) > 0, f"⚡  
Energiya ichimligi (qayta ovoz berish):  
{ch.get('revote', 0)} ta")
    add(ch.get("smoke_bomb", 0) > 0, f"💣  
Tutunli bomba: {ch.get('smoke_bomb', 0)}  
ta")
    add(ch.get("flash_light", 0) > 0, f"🔦  
Katta Fonar: {ch.get('flash_light', 0)}  
ta")

```

```

        add(ch.get("cloak", 0) > 0, f"👤
Yashirin plash: {ch.get('cloak', 0)} ta")
        add(ch.get("duel_adv", 0) > 0, f"🔪
Olmos Qilich (duel ustunligi):
{ch.get('duel_adv', 0)} ta")
        add(ch.get("golden_bullet", 0) > 0,
f"🟡 Oltin o'q: {ch.get('golden_bullet',
0)} ta")
        add(ch.get("radar", 0) > 0, f"📡 Maxfiy
radar: {ch.get('radar', 0)} ta")
        add(ch.get("revive", 0) > 0, f"⚡
Tezkor jonlanish: {ch.get('revive', 0)}
ta")
        add(ch.get("role_choice", 0) > 0, f"👥
Rol tanlash huquqi: {ch.get('role_choice',
0)} marta")
        add(ch.get("watch_eyes", 0) > 0, f"👁️
Kuzatish ko'zi: {ch.get('watch_eyes', 0)}
ta")
        add(ch.get("day_shield", 0) > 0, f"🛡️☀️
Kunduzgi himoya: {ch.get('day_shield', 0)}
ta")

        imp_until = ch.get("imperator_until",
0)
        if imp_until and imp_until >
time.time():
            rem = int(imp_until - time.time())
            add(True, f"👑 Imperator maqomi:
{rem // 3600} soat {(rem % 3600) // 60}
daqiqqa qoldi")

        elite_until_line = ch.get("vip_until",
0)

```

```

    if elite_until_line and
elite_until_line > time.time():
        rem_days = int((elite_until_line -
time.time()) // 86400)
        add(True, f"🔥 HUNTER ELITE:
{rem_days} kun qoldi")

    admin_until =
ch.get("temp_admin_until", 0)
    if admin_until and admin_until >
time.time():
        rem = int(admin_until -
time.time())
        add(True, f"⚡ Vaqtinchalik admin
huquqi: {rem // 3600} soat qoldi")

    night_vision_left =
ch.get("night_vision", 0) # (yuqorida "🕶️
Tungi ko'zoynak" bilan bir xil hisoblanadi)

    hero = get_hero(uid)
    if hero:
        add(True, f"{hero['name']} -
{hero['level']}-lvl (/geroyim)")

    def _rem_days(key):
        until = ch.get(key, 0)
        return int((until - time.time()) //
86400) + 1 if until > time.time() else 0

    ramka_days = _rem_days("ramka_until")
    add(ramka_days > 0, f"📅 Mifik ramka:
{ramka_days} kun qoldi")
    toj_days = _rem_days("toj_until")

```

```

        add(toj_days > 0, f"👑 Hukmdor toj:
{toj_days} kun qoldi")
        qirol_days = _rem_days("qirol_until")
        add(qirol_days > 0, f"🏴‍☠️ Hunter Mafia
Qiroli unvoni: {qirol_days} kun qoldi")
        dgw = ch.get("duel_guaranteed_win", 0)
        if dgw > 0:
            add(True, f"🔪 Kafolatlangan duel
g'alabasi – {dgw} marta qoldi")
            shadow_days = _rem_days("shadow_until")
            add(shadow_days > 0, f"👤 Shadow
status: {shadow_days} kun qoldi (reytingda
yashirin)")
            add(ch.get("klan_license", 0) > 0, f"🏠
Klan litsenziyasi: {ch.get('klan_license',
0)} marta ishlatish mumkin")

        bm_days = _rem_days("bonus_mult_until")
        bm = ch.get("bonus_mult_val", 1) if
bm_days > 0 else 1
        if bm > 1:
            add(True, f"🎁 Kunlik bonus
ko'paytiruvchi: x{bm} ({bm_days} kun
qoldi)")
            lm_days = _rem_days("luck_mult_until")
            lm = ch.get("luck_mult_val", 1) if
lm_days > 0 else 1
            if lm > 1:
                add(True, f"🦊 Umumiy yutuq
ko'paytiruvchi: x{lm} ({lm_days} kun
qoldi)")

        if not lines:
            return "Hozircha faol kuchlaringiz

```

```

yo'q. Do'kondan xarid qiling!"
    return " ✨ <b>FAOL
KUCHLARINGIZ</b>\n\n" + "\n".join(lines)

def show_profile(chat_id, uid, name):
    u = user_dict(uid, name)
    partner = get_partner_mention(uid)
    marriage_line = f"💍 Oilaviy holat:
Nikohda ({partner})" if partner else "💍
Oilaviy holat: Bo'ydoq"
    duel_total = u["duel_wins"] +
u["duel_losses"]
    duel_rate = f"{(u['duel_wins'] /
duel_total * 100):.1f}%" if duel_total else
"0.0%"
    elite_line = elite_status_line(uid)
    text = (
        " 👤 <b>SHAXSIY KABINET</b>\n"
        " _____\n"
        f"{elite_line}\n"
        f"👉 Ism: {u['name']}\n"
        f"🎮 O'yinlar: {u['games']} ta | 🏆
G'alaba: {u['wins']} ta\n"
        f"💵 Dollar ($): ${u['dollar']}\n"
        f"💎 Olmoslar: {u['diamond']} ta\n"
        f"🪙 Hunter Coin: {u['coin']} ta\n"
        f"🛡 Himoya (shield): {u['shield']}
ta\n"
        f"⚔ Duellar: {duel_total} ta
({u['duel_wins']} g'alaba /
{u['duel_losses']} mag'lubiyat,
{duel_rate})\n"
        f"{marriage_line}\n"

```



```

        "_____")
    )
    bot.send_message(chat_id, text,
reply_markup=with_back_button())

#
=====
=====
# 📦 INVENTAR (qoshimchakod10.py g'oyasi –
endi haqiqiy DB "inventory" ustunidan)
#
=====
=====

def show_inventory(chat_id, uid):
    """📦 SODDA VA TUSHUNARLI inventar: har
    bir buyum alohida tugma, bosilganda
    tavsifi va (mavjud bo'lsa)
    ishlatish/yoqish-o'chirish tugmasi
    chiqadi."""
    u = user_dict(uid)
    try:
        items = json.loads(u["inventory"]
or "[ ]")
    except Exception:
        items = []
    ch = get_charges(uid)
    voucher_count =
len(ch.get("osh_vouchers", [ ]))
    hero = get_hero(uid)

    if not items and voucher_count == 0 and
not hero:

```

```

        bot.send_message(chat_id, "📦
Sizning inventaringiz hozircha bo'sh.\n🛒
Do'kondan buyum sotib oling – /market",
reply_markup=with_back_button())
        return

    counts = {}
    for it in items:
        counts[it] = counts.get(it, 0) + 1

    kb = types.InlineKeyboardMarkup()
    lines = ["📦 <b>SIZNING
INVENTARINGIZ</b>", "", "Har bir buyum
haqida to'liq ma'lumot va uni ISHLATISH "
            "yoki YOQISH/O'CHIRISH uchun
mos tugmani bosing:", ""]

    if hero:
        lines.append(f"🏆 {hero['name']} –
{hero['level']}-lvl")

    kb.add(types.InlineKeyboardButton(f"🏆
{hero['name']}",
callback_data=f"menu|hero"))

    for name, n in counts.items():
        shopkey =
ITEM_NAME_TO_SHOPKEY.get(name)
        label = f"{name} – {n} ta" if n > 1
    else name
        lines.append(f"• {name}" + (f" ({n}
ta)" if n > 1 else ""))
        if shopkey:

```

```

kb.add(types.InlineKeyboardButton(label,
callback_data=f"invitem|{shopkey[0]}|
{shopkey[1]}"))
    else:

kb.add(types.InlineKeyboardButton(label,
callback_data="invitem_noop"))

    if voucher_count:
        lines.append(f"• 🍪 Tortiq
qilinadigan osh – {voucher_count} ta")

kb.add(types.InlineKeyboardButton(f"🍪 Osh
tortiqdari ({voucher_count} ta)",
callback_data="invitem_osh_info"))

    bot.send_message(chat_id,
"\n".join(lines),
reply_markup=with_back_button(kb))

@bot.callback_query_handler(func=lambda c:
c.data == "invitem_osh_info")
def cb_invitem_osh_info(call):
    bot.answer_callback_query(call.id)
    bot.send_message(
        call.message.chat.id,
        f"🍪 <b>Osh
tortiqdari</b>\n\nBularni sotib olgan
bo'lsangiz, pul o'rniga boshqa bir "
        "o'yinchiga TORTIQ qilish huquqiga
ega bo'lasiz.\n\n"
        "Ishlatish: guruhda, tortiq
qilmoqchi bo'lgan kishining xabariga

```

```

<b>reply</b> qilib "
    "<code>/oshtortiq</code> deb
yozing.",
)

# charge_key -> (target kerakmi, do_*
funksiya, foydalanuvchiga ko'rsatiladigan
tugma nomi)
_INV_TARGET_ACTIONS = {
    "poison": ("target", do_zahar, "🔪
Zaharlash uchun tanlang"),
    "gps": ("target", do_gps, "📍 Kimni
tekshiramiz?"),
    "compass": ("target", do_kompas, "🧭
Kimni tekshiramiz?"),
    "flash_light": ("target", do_fonar, "🔦
Kimni yoritamiz?"),
    "smoke_bomb": ("self", do_tutun, "💨
Hozir ishlatish"),
    "radar": ("self", do_qayta_tanlash, "📡
Hozir ishlatish"),
}

# 🧑🏻 Buyruq orqali ishlatiladigan buyumlar
uchun ANIQ ko'rsatma (inventarda chalkash
# "tegishli buyruq orqali" degan umumiy
matn o'rniga)
_INV_COMMAND_HINT = {
    "role_choice": "/rolni_tanla <rol
nomi>",
    "klan_license": "/klan <nomi>",
}

```

```

# ⚙️ Passiv (o'zi avtomatik ishlaydigan,
alohida tugma kerak bo'lmaydigan) buyumlar
# uchun ANIQ tushuntirish matni
_INV_PASSIVE_INFO = {
    "day_shield": "⚙️ Bu buyum AVTOMATIK
ishlaydi – kunduzgi ovoz berishda eng ko'p
ovoz olib "
                    "qolsangiz, o'zi
avtomatik sizni himoya qiladi (alohida
buyruq kerak emas).",
    "revote": "⚙️ Bu buyum AVTOMATIK
ishlaydi – ovoz berishda fikringizni
o'zgartirmoqchi bo'lsangiz, "
                    "shunchaki qayta boshqa
odamga ovoz bering, zaxira avtomatik
ishlatiladi.",
    "cloak": "⚙️ Bu buyum AVTOMATIK
ishlaydi – komissar yoki boshqa
tekshiruvlar sizni "
                    "tekshirganda, natijani
avtomatik yashiradi.",
    "duel_guaranteed_win": "🔪 Bu buyum
AVTOMATIK ishlaydi – /duel bilan kimgadir
chaqiruv "

    "yuborganingizda, zaxirangiz bo'lsa g'alaba
avtomatik kafolatlanadi.",
}

@bot.callback_query_handler(func=lambda c:
c.data == "invitem_noop")
def cb_invitem_noop(call):
    bot.answer_callback_query(call.id, "i

```

Bu buyum haqida qo'shimcha ma'lumot yo'q.")

```
@bot.callback_query_handler(func=lambda c:
c.data.startswith("invitem|"))
def cb_invitem_detail(call):
    """Inventardagi buyum tugmasi
bosilganda – tavsifi va (mavjud bo'lsa)
yoqish/
    o'chirish TUGMASI yoki to'g'ridan-
to'g'ri ISHLATISH tugmasi ko'rsatiladi."""
    maybe_capture_owner(call.from_user)
    _, cat, key = call.data.split("|")
    _, items = SHOP_CATEGORIES[cat]
    item = items.get(key)
    uid = call.from_user.id
    if not item:
        bot.answer_callback_query(call.id,
"❌ Buyum topilmadi.")
        return
    bot.answer_callback_query(call.id)
    charge_key = item.get("charge_key")
    left = get_charges(uid).get(charge_key,
0) if charge_key else 0
    text = f"<b>{item['name']}</b>\n{item.get('desc', '')}"
    if charge_key and item.get("mode") ==
"charge":
        text += f"\n📦 Qolgan miqdor:
{left} ta."
    kb = types.InlineKeyboardMarkup()

    if charge_key in _INV_TARGET_ACTIONS
and left > 0:
```

```

        kind, _fn, label =
            _INV_TARGET_ACTIONS[charge_key]
        chat_id, game =
            find_active_game_for(uid)
        if not game:
            text += "\n\n⚠️ Buyumni
            ishlatish uchun hozir faol o'yinda tirik
            ishtirokchi bo'lishingiz kerak."
            elif kind == "self":

kb.add(types.InlineKeyboardButton(label,
callback_data=f"invuse_self|{charge_key}|
{chat_id}"))
        else:

kb.add(types.InlineKeyboardButton(label,
callback_data=f"invuse_pick|{charge_key}|
{chat_id}"))
        elif charge_key and charge_key in
            TOGGLEABLE_ITEMS and left > 0:
            state = "✅ FAOL" if
            is_item_active(uid, charge_key) else "❌
            O'CHIQ"

kb.add(types.InlineKeyboardButton(f"Holat:
{state} – bosib almashtiring",
callback_data=f"toggleitem|{charge_key}"))
        elif charge_key in _INV_COMMAND_HINT:
            text += f"\n\n👤 Ishlatish:
            {_INV_COMMAND_HINT[charge_key]}"
        elif charge_key in _INV_PASSIVE_INFO:
            text +=
            f"\n\n{_INV_PASSIVE_INFO[charge_key]}"
            elif item.get("mode") == "charge" and

```

```

charge_key:
    text += "\n\n📌 Bu buyum avtomatik
yoki tegishli buyruq orqali ishlaydi."

    bot.send_message(call.message.chat.id,
text, reply_markup=kb if kb.keyboard else
None)

@bot.callback_query_handler(func=lambda c:
c.data.startswith("invuse_self|"))
def cb_invuse_self(call):
    """Inventardan to'g'ridan-to'g'ri
o'ziga ishlatiladigan buyum (Tutun,
Radar)."""
    maybe_capture_owner(call.from_user)
    _, charge_key, chat_id_s =
call.data.split("|")
    chat_id = int(chat_id_s)
    uid = call.from_user.id
    game = GAMES.get(chat_id)
    if not game or uid not in
game["players"] or not game["players"][uid]
["alive"]:
        bot.answer_callback_query(call.id,
"❌ Bu o'yin endi faol emas.",
show_alert=True)
        return
    _, fn, _ =
_INV_TARGET_ACTIONS[charge_key]
    ok, msg = fn(chat_id, game, uid)
    bot.answer_callback_query(call.id)
    try:
        bot.edit_message_text(msg,

```



```

call.message.chat.id,
call.message.message_id)
    except Exception:

bot.send_message(call.message.chat.id, msg)

@bot.callback_query_handler(func=lambda c:
c.data.startswith("invuse_pick|"))
def cb_invuse_pick(call):
    """Nishon tanlash kerak bo'lgan buyum
(Zahar/GPS/Kompas/Fonar) – tirik
o'yinchilar ro'yxatini ko'rsatadi."""
    maybe_capture_owner(call.from_user)
    _, charge_key, chat_id_s =
call.data.split("|")
    chat_id = int(chat_id_s)
    uid = call.from_user.id
    game = GAMES.get(chat_id)
    if not game or uid not in
game["players"] or not game["players"][uid]
["alive"]:
        bot.answer_callback_query(call.id,
"❌ Bu o'yin endi faol emas.",
show_alert=True)
        return
    bot.answer_callback_query(call.id)
    kb = types.InlineKeyboardMarkup()
    for target_id, p in
game["players"].items():
        if target_id == uid or not
p.get("alive"):
            continue

```

```

kb.add(types.InlineKeyboardButton(p["name"]
, callback_data=f"invuse_target|
{charge_key}|{chat_id}|{target_id}"))
    try:
        bot.edit_message_text("🎯 Kimga
ishlatasiz?", call.message.chat.id,
call.message.message_id, reply_markup=kb)
    except Exception:

bot.send_message(call.message.chat.id, "🎯
Kimga ishlatasiz?", reply_markup=kb)

@bot.callback_query_handler(func=lambda c:
c.data.startswith("invuse_target|"))
def cb_invuse_target(call):
    maybe_capture_owner(call.from_user)
    _, charge_key, chat_id_s, target_s =
call.data.split("|")
    chat_id, target_id = int(chat_id_s),
int(target_s)
    uid = call.from_user.id
    game = GAMES.get(chat_id)
    if not game or uid not in
game["players"] or not game["players"][uid]
["alive"]:
        bot.answer_callback_query(call.id,
"❌ Bu o'yin endi faol emas.",
show_alert=True)
        return
    if game.get("phase") not in ("night",
"day"):
        bot.answer_callback_query(call.id,
"❌ Hozir bu buyumni ishlatib bo'lmaydi

```

```

(o'yin tun/kun bosqichida emas).",
show_alert=True)
    return
    target_p =
game["players"].get(target_id)
    if not target_p or not
target_p.get("alive"):
        bot.answer_callback_query(call.id,
"✗ Bu o'yinchi topilmadi yoki allaqachon
o'yindan chetlashtirilgan.",
show_alert=True)
        return
        target_name = mention(target_id,
target_p.get("name", "?"))
        _, fn, _ =
_INV_TARGET_ACTIONS[charge_key]
        ok, msg = fn(chat_id, game, uid,
target_id, target_name)
        bot.answer_callback_query(call.id)
        try:
            bot.edit_message_text(msg,
call.message.chat.id,
call.message.message_id)
        except Exception:

bot.send_message(call.message.chat.id, msg)

@bot.message_handler(commands=["inventar",
"Inventar"])
def cmd_inventar(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    show_inventory(message.chat.id,

```

```

message.from_user.id)

#
=====
=====
#  MENYU CALLBACK
#
=====
=====

def with_back_button(kb=None):
    """ Istalgan inline klaviaturaga
    pastiga "Bosh menyu" tugmasini qo'shadi
    (kb bo'lmasa, yangisini yaratadi) –
    foydalanuvchi hech qachon biror
    bo'limda "qolib ketmasligi", har doim
    bitta bosish bilan bosh menyuga
    qaytishi uchun. Barcha menyu
    ekranlarida shu funksiya ishlatiladi."""
    if kb is None:
        kb = types.InlineKeyboardMarkup()
        kb.add(types.InlineKeyboardButton("
Bosh menyu",
callback_data="menu|main_back"))
    return kb

@bot.callback_query_handler(func=lambda c:
c.data.startswith("menu|"))
def cb_menu(call):
    maybe_capture_owner(call.from_user)
    _, action = call.data.split("|")
    uid = call.from_user.id

```

```

# 🖼️ "Jonli panel": foydalanuvchi
menyuda navigatsiya qilganda, bosilgan
# eski ekran DARHOL o'chiriladi – chat
toza qoladi, faqat bitta joriy
# ekran ko'rinadi (aynan shu bosqichda,
har bir action ichida alohida
# o'chirish yozib o'tirish shart
bo'lmasin deb, bir joyda hal qilingan).
try:

bot.delete_message(call.message.chat.id,
call.message.message_id)
except Exception:
    pass

if action == "main_back":
    THERON_CHAT_MODE.discard(uid) # ⬅️
bosh menyuga qaytilganda Theron suhbat
rejimi tugaydi
    bot.send_photo(
        call.message.chat.id,
        MAIN_PHOTO,
        caption=(
            f"🌙 <b>Hunter Mafia</b> –
bosh menyu\n\n"
            "Kerakli bo'limni tanlang
👉 "
        ),

reply_markup=get_main_menu(None, uid),
    )
    bot.answer_callback_query(call.id)
    return

```

```

        if action == "roles":
            lines = ["👤 <b>Hunter Mafia – 28  
ta rol</b>\n"]
            for role, desc in  
ROLES_INFO.items():
                lines.append(f"<b>{role}</b> –  
{desc}")
            text = "\n".join(lines)
            chunks = [text[i:i + 3500] for i in  
range(0, len(text), 3500)]
            for i, chunk in enumerate(chunks):
                is_last = (i == len(chunks) -  
1)

            bot.send_message(call.message.chat.id,  
chunk, reply_markup=with_back_button() if  
is_last else None)
            bot.answer_callback_query(call.id)

        elif action == "cabinet":
            show_profile(call.message.chat.id,  
uid, call.from_user.first_name)
            bot.answer_callback_query(call.id)

        elif action == "shop":

            open_shop_main(call.message.chat.id)
            bot.answer_callback_query(call.id)

        elif action == "buyhc":

            open_hc_stars_menu(call.message.chat.id)
            bot.answer_callback_query(call.id)

```

```

elif action == "birja":

open_diamond_shop_menu(call.message.chat.id
, uid) # 🛠️ TUZATILDI: eski Birja/VIP
o'rniga – Olmos do'koni
        bot.answer_callback_query(call.id)

elif action == "elite":

open_elite_menu(call.message.chat.id, uid)
        bot.answer_callback_query(call.id)

elif action == "theron":
    elite_user = is_elite(uid)
    THERON_CHAT_MODE.add(uid) # 💬
    endi bu foydalanuvchi bilan ochiq suhbat
    rejimi boshlanadi
        bot.send_message(
            call.message.chat.id,
            f"🧠 <b>{THERON_NAME}</b>
{THERON_MEANING}\\n\\n"
            "Suhbat rejimi ochildi – endi
menga <b>to'g'ridan-to'g'ri</b> xabar
yozishingiz "
            "kifoya, <code>/theron</code>
deb yozish shart emas! Savol bering,
maslahat so'rang, "
            "o'yin bo'yicha tavsiya
oling.\\n\\n"
            f"👑 ELITE a'zolar – kuniga
{THERON_ELITE_DAILY_LIMIT} tagacha savol\\n"
            f"👤 Oddiy foydalanuvchilar –
kuniga {THERON_FREE_DAILY_LIMIT} ta savol"

```

```

        + (" if elite_user else "\n\n
🔹 ELITE a'zolikda ancha ko'proq va
chuqurroq yordam olasiz – /elite"),

reply_markup=with_back_button(),
    )
    bot.answer_callback_query(call.id)

    elif action == "lang":

open_lang_menu(call.message.chat.id, uid)
    bot.answer_callback_query(call.id)

    elif action == "dollarshop":

open_dollar_shop(call.message.chat.id, uid)
    bot.answer_callback_query(call.id)

    elif action == "d2c":

open_diamond_to_coin_menu(call.message.chat
.id, uid)
    bot.answer_callback_query(call.id)

    elif action == "effects":

bot.send_message(call.message.chat.id,
format_active_effects(uid),
reply_markup=with_back_button())
    bot.answer_callback_query(call.id)

    elif action == "klan":
        with db_lock:
            cur.execute("SELECT name FROM

```



```

clans WHERE owner_id=?", (uid,))
    row = cur.fetchone()
    if row:

bot.send_message(call.message.chat.id, f"🏠
Sizning klaningiz: <b>{row[0]}</b>",
reply_markup=with_back_button())
    else:

bot.send_message(call.message.chat.id,
"Sizda hali klan yo'q. 🏠 Klan
litsenziyasini Hunter Coin do'konidan sotib
olib <code>/klan Nomi</code> deb yozing.",
reply_markup=with_back_button())
    bot.answer_callback_query(call.id)

    elif action == "top":
        _text, _tp = build_top_text()

bot.send_message(call.message.chat.id,
_text,
reply_markup=with_back_button(_top_page_mar
kup("wins", 0, _tp)))
    bot.answer_callback_query(call.id)

    elif action == "inventory":

show_inventory(call.message.chat.id, uid)
    bot.answer_callback_query(call.id)

    elif action == "hero":

show_hero_panel(call.message.chat.id, uid)
    bot.answer_callback_query(call.id)

```

```

elif action == "points_top":
    kb2 = types.InlineKeyboardMarkup()
    kb2.add(
        types.InlineKeyboardButton("📅 17  
Kunlik", callback_data="ptop|kun"),
        types.InlineKeyboardButton("📅 17  
Haftalik", callback_data="ptop|hafta"),
    )
    kb2.add(
        types.InlineKeyboardButton("📅 17  
Oylik", callback_data="ptop|oy"),
        types.InlineKeyboardButton("👁️  
Mutlaq", callback_data="ptop|mutlaq"),
    )

    bot.send_message(call.message.chat.id, "🏆  
Qaysi davr bo'yicha reytingni  
ko'rmoqchisiz?",
        reply_markup=with_back_button(kb2))
    bot.answer_callback_query(call.id)

elif action == "market_info":
    bot.send_message(
        call.message.chat.id,
        "🛒 <b>QORA BOZOR</b>\n\n"
        "Bu yerda o'yinchilar o'z  
inventaridagi buyumlarni dollar, olmos yoki  
"
        "Hunter Coin evaziga – o'zi  
tanlagan narxda bir-biriga sotishlari  
mumkin.\n\n"
        "📦 <code>/sell</code> –  
inventaringizni raqamlangan holda

```

```

ko'rish\n"
    "📦 <code>/sell &lt;raqam>&lt;
&lt;dollar|diamond|coin>&lt; &lt;narx>&lt;
</code> – buyumni bozorga qo'yish\n"
    "🛒 <code>/market</code> – faol
e'lonlarni ko'rish\n"
    "🛒 <code>/buy &lt;ID>&lt;
</code> – e'londagi buyumni sotib
olish\n\n"
    "<i>Eslatma: qora bozor faqat
maxsus savdo guruhida ishlaydi: "
    "https://t.me/+v9bYoMk-
0hAyZTcy</i>",

reply_markup=with_back_button(),
)
bot.answer_callback_query(call.id)

elif action == "tournament":
    t =
    TOURNAMENTS.get(call.message.chat.id)
    if t and t["status"] != "finished":
        remaining =
        len(t["participants"]) -
        len(t["eliminated"])
        bot.send_message(
            call.message.chat.id,
            f"🏆 <b>{t['name']}</b> –
holat: {t['status']}\n"
            f"👥 Ishtirokchilar:
{len(t['participants'])} (qolgan:
{remaining})\n\n"
            "📋 /turnir_royxat – to'liq
royxat",

```

```

reply_markup=with_back_button(),
    )
    else:
        bot.send_message(
            call.message.chat.id,
            "🏆 <b>MUSOBAQALAR
(Turnirlar)</b>\n\n"
            "👑 FAQAT bot egasi
<code>/turnir_boshla &lt;nomi></code>
orqali yangi turnir ochadi.\n"
            "O'yinchilar tugma orqali
qo'shiladi, so'ng tashkilotchi ikkitadan
tanlab "
            "🔪 <b>Turnir Jangi</b>
(elimination, duel'dan farqli) o'tkazadi –
oxirida "
            "bitta CHEMPION qoladi va
katta mukofot (+500$, +20💎, +50 ball)
oladi!\n\n"
            "📋 Buyruqlar:
/turnir_boshla, /turnir_royxat,
/turnir_yopish, /turnir_jang,
/turnir_tugat",

reply_markup=with_back_button(),
    )
    bot.answer_callback_query(call.id)

    elif action == "nikoh_info":
        partner = get_partner_mention(uid)
        if partner:

bot.send_message(call.message.chat.id, f"💍

```

```

<b>Oilaviy holat:</b> Nikohda ❤️
\nJuftingiz: {partner}\n\nAjrashish uchun
/ajrashish deb yozing.",
reply_markup=with_back_button())
    else:

bot.send_message(call.message.chat.id, "👤
<b>Oilaviy holat:</b> Bo'ydoq.\n\nBoshqa
o'yinchi bilan nikoh qurish uchun guruhda
uning xabariga <b>Reply</b> qilib /nikoh
deb yozing!",
reply_markup=with_back_button())
    bot.answer_callback_query(call.id)

    elif action == "duel_info":

bot.send_message(call.message.chat.id, "🔪
Boshqa o'yinchi bilan duel o'ynash uchun
guruhda uning xabariga <b>Reply</b> qilib
/duel deb yozing!",
reply_markup=with_back_button())
    bot.answer_callback_query(call.id)

    elif action == "help":
        text = (
            "❓ <b>BUYRUQLAR
RO'YXATI</b>\n\n"
            "<b>O'yin (guruh admini):
</b>\n"
            "/NewGame – yangi o'yin
ochish\n"
            "/PovtorGame – qo'shilish
xabarini yangilash\n"
            "/StartGame – o'yinni

```

```
boshlash\n"
    "/Sotop – o'yinni
to'xtatish\n\n"
    "<b>O'yinchilar uchun:</b>\n"
    "/join – o'yinga qo'shilish\n"
    "/rolni_tanla &lt;rol&gt; – 🧑🏽\n"
huquqi bo'lsa rol tanlash\n"
    "/zahar (reply) – 💊\n"
zaharlash\n"
    "/gps (reply) – 📍 holatni
bilish\n"
    "/qayta_tanlash – 📡 rolni
qayta tanlash\n"
    "/duel (reply) &lt;tikish
summasi&gt; – duelga chaqirish (masalan:
/duel 250)\n"
    "/duel_stat (yoki reply) – duel
statistikasi\n"
    "/nikoh (reply) – turmush
taklifi\n"
    "/juftim – oilaviy
holatingiz\n"
    "/ajrashish – ajrashish\n"
    "/OilaInfo – nikoh davomiyligi
(qancha vaqtdan beri birgasiz)\n"
    "/Quchoqla, /Opich (reply,
faqat juftingizga) – erkalash\n"
    "/OilaTop – eng mustahkam
oilalar reytingi\n"
    "/Sovgla
&lt;atirgul|yurak|shokolad&gt; (reply,
faqat juftingizga) – virtual sovg'a\n"
    "/Xiyonat (reply, faqat
juftingizga) – hazilomuz \"xiyonat\"\n"
```

```
"/inventar – buyumlaringiz
ro'yxati\n"
"/sell, /sell <raqam>
<narx> – 🛒 Qora bozorga buyum
qo'yish\n"
"/osh (reply) <turi> –
do'stingizga milliy osh ziyofat qiling
(unga himoya+bonus beradi)\n"
"/market, /buy <ID> – 🛒
Qora bozordan xarid qilish\n"
"/birja – 💎 Olmos do'koni
(Stars orqali sotib olish /
HunterCoin↔Olmos)\n"
"/Givde, /GivdeMoney,
/GivdeCoin (reply) – sovg'a berish\n"
"/klan <nomi>;, /klanim –
klan yaratish / holatini ko'rish\n"
"/klanga_qoshil
<egasi_ID> – klanga qo'shilish
so'rovi yuborish\n"
"/klan_tark, /klan_chetlash
(reply) – klandan chiqish / chiqarish\n"
"/klan_orinbosar (reply) –
o'rinbosar tayinlash\n"
"/klan_azo_daraja (reply)
<son>; – a'zo darajasini
oshirish/pasaytirish\n"
"/klan_lvl – klanni yangi
darajaga ko'tarish\n"
"/klan_nomi <yangi nomi>;
– klan nomini o'zgartirish ($5000)\n"
"/klan_maqom (reply)
ritsar|sehrGAR – maqom berish\n"
"/klan_hazna, /klan_taqsimla
```

```
(reply) &lt;dollar&gt; – klan xazinasini\n"/klanlar – top klanlar ro'yxatini\n"/klanjang\n&lt;raqib_egasi_ID&gt; – klanlar jangi e'lon qilish\n"/promo &lt;KOD&gt; – promo-kodni ishlatish\n"/profile – shaxsiy kabinet\n"/tark_et – o'yinni tark etish (avtomatik mag'lub, -10 ball)\n\n"<b>🏆 Geroylar va ballar:\n</b>\n\n"/geroyim – geroyingizni ko'rish (rasm bilan) va darajasini oshirish\n\n"/geroy_bashorat, /geroy_koz, /geroy_daromad – geroy mahoratlarini qo'lda ishlatish\n\n"/balltop_kun, /balltop_hafta, /balltop_oy, /balltop_mutlaq – faollik ballari reytingi\n\n"<b>🏆 Musobaqalar (turnirlar) – FAQAT BOT EGASI boshqaradi:</b>\n\n"/turnir_boshla &lt;nomi&gt; – yangi turnir ochish (faqat owner)\n\n"/turnir_royxat – ishtirokchilar ro'yxatini\n\n"/turnir_yopish – ro'yxatni yopib boshlash (faqat owner)\n\n"/turnir_jang – navbatdagi 🏹 Turnir Jangini tanlab boshlash (faqat owner)\n\n"/turnir_tugat – turnirni bekor
```



```
qilish (faqat owner)\n\n"
    "<b>Faqat bot yaratuvchisi /
adminlar:</b>\n"
    "/Guruh, /mirkamilovic,
/sendall, /addmoney, /adddiamond, /addcoin,
/ban, /unban\n"
    "/promo_create <KOD>
<dollar> <diamond> <coin>
<limit> – promo-kod yaratish\n"
    "/promo_yarat <KOD>
(reply) – eng faol o'yinchi uchun shaxsiy
promo-kod (har ishlatilganda unga +$10)\n"
    "/klan_mukofot – 3 oylik TOP
klanlar mukofotini tarqatish\n"
    "/tarqatish
<dollar|diamond|coin> <miqdor>
<kishi> – sovg'a tarqatish (faqat bot
yaratuvchisi)\n"
    "/shu_bozor – joriy guruhni
qora bozor qilib belgilash\n"
    "/bozor_holati – qora bozor
sozlamasini tekshirish\n"
    "/guruh_id – joriy guruh
ID'sini ko'rish\n"
    "/jufti <guruh_ID> – 2
guruhni Qizil vs Ko'k musobaqasiga
bog'lash\n"
    "/jufti_bekor – juftlikni bekor
qilish\n"
    "/hisob – Qizil vs Ko'k umumiy
hisobini ko'rish\n"
    "/paralar – nikohdagi
juftliklar ro'yxati (admin)\n"
    "/tiklash (yoki /restart) –
```

```
botni xavfsiz qayta ishga tushirish, aktiv
"
```

```
        "o'yinlar avtomatik saqlanib
tiklanadi (faqat bot yaratuvchisi)\n"
        "/bazani_tikla – bazani avvalgi
zaxira nusxa (.json) fayldan tiklash (faqat
bot yaratuvchisi)\n"
        "/statistika, /ball_ber,
/oyinni_zorla_tugat, /royxat_faol,
/valyuta_ber, /geroy_ber – "
        "qo'shimcha owner funksiyalari
(⚙️ Admin panelda tugmalar bilan)\n"
        "/guruh_ban (reply),
/guruh_unban_hammasi – Telegram guruh
darajasidagi ban/unban (guruh admini)\n"
        "/emoji_test – PREMIUM_EMOJI
lug'atini sinab ko'rish (faqat bot
yaratuvchisi)"
    )
```

```
bot.send_message(call.message.chat.id,
text, reply_markup=with_back_button())
    bot.answer_callback_query(call.id)
```

```
        elif action == "bonus":
            u = user_dict(uid,
call.from_user.first_name)
            today = time.strftime("%Y-%m-%d")
            if u["last_bonus_date"] == today:
```

```
bot.answer_callback_query(call.id, "🕒 Siz
bugungi bonusni allaqachon olgansiz!",
show_alert=True)
```

```

bot.send_photo(call.message.chat.id,
MAIN_PHOTO, caption="🌙 <b>Hunter Mafia</b>
– bosh menyu\n\nKerakli bo'limni tanlang
👉", reply_markup=get_main_menu(None, uid))
    return
    update_user(uid,
last_bonus_date=today)
    roll = random.random() * 100
    mult = bonus_mult(uid) *
luck_mult(uid)
    hero_extra =
hero_bonus_extra_dollar(uid) # 🏆 Geroy
(Elandriel / Zephyrion)
    # 🛠 Almos tushish ehtimoli
kamaytirildi: avval 5% (roll<95 dan
tashqari)
    # edi, endi 2% – Olmos kamyobroq va
qimmatroq resurs bo'lib qoladi.
    if roll < 98:
        reward = int(10 * mult) +
hero_extra
        add_balance(uid, dollar=reward)

bot.answer_callback_query(call.id, f"🎁
Bonus: +{reward}$ Dollar yutib oldingiz!
🎉", show_alert=True)
    else:
        reward = max(1, int(1 * mult))
        add_balance(uid,
diamond=reward)

bot.answer_callback_query(call.id, f"💎
Bonus: {reward} ta Olmos yutib oldingiz!
🚀", show_alert=True)

```

```

# 📸 bonus – alert orqali
ko'rsatiladi, panel o'chirilgan edi – bosh
menyuni qayta chiqaramiz

bot.send_photo(call.message.chat.id,
MAIN_PHOTO, caption="🌙 <b>Hunter Mafia</b>
– bosh menyu\n\nKerakli bo'limni tanlang
👉", reply_markup=get_main_menu(None, uid))

#
=====
=====
# DO'KON (dollar/olmos/coin/osh)
#
=====
=====

def open_shop_main(chat_id):
    kb = types.InlineKeyboardMarkup()
    for key, (title, _items) in
SHOP_CATEGORIES.items():

kb.add(types.InlineKeyboardButton(title,
callback_data=f"shopcat|{key}"))
    bot.send_message(chat_id, "🛒 Do'konga
xush kelibsiz! Kerakli bo'limni tanlang:",
reply_markup=with_back_button(kb))

@bot.callback_query_handler(func=lambda c:
c.data.startswith("shopcat|"))
def cb_shop_category(call):
    maybe_capture_owner(call.from_user)

```

```

_, cat = call.data.split("|")
title, items = SHOP_CATEGORIES[cat]
kb = types.InlineKeyboardMarkup()
for key, item in items.items():
    symbol = {"dollar": "$", "diamond":
"💎", "coin": "🪙"}[item["currency"]]

kb.add(types.InlineKeyboardButton(f"
{item['name']} – {item['price']}{symbol}",
callback_data=f"buy|{cat}|{key}"))
    kb.add(types.InlineKeyboardButton("⬅️
Orqaga", callback_data="shopback"))
    try:
        bot.edit_message_text(f"
{title}\nKerakli buyumni tanlang (tavsif
uchun ustiga bosing):",
call.message.chat.id,
call.message.message_id, reply_markup=kb)
    except Exception:

bot.send_message(call.message.chat.id, f"
{title}\nKerakli buyumni tanlang:",
reply_markup=kb)
    bot.answer_callback_query(call.id)

@bot.callback_query_handler(func=lambda c:
c.data == "shopback")
def cb_shop_back(call):
    maybe_capture_owner(call.from_user)
    open_shop_main(call.message.chat.id)
    bot.answer_callback_query(call.id)

```

```

@bot.callback_query_handler(func=lambda c:
c.data.startswith("buy|"))
def cb_buy(call):
    maybe_capture_owner(call.from_user)
    _, cat, key = call.data.split("|")
    _, items = SHOP_CATEGORIES[cat]
    item = items[key]
    uid = call.from_user.id
    u = user_dict(uid,
call.from_user.first_name)
    balance = u[item["currency"]]

    if balance < item["price"]:
        bot.answer_callback_query(call.id,
"❌ Balansingiz yetarli emas!",
show_alert=True)
        return

    if item["currency"] == "dollar":
        add_balance(uid, dollar=-
item["price"])
    elif item["currency"] == "diamond":
        add_balance(uid, diamond=-
item["price"])
    else:
        add_balance(uid, coin=-
item["price"])

    mode = item["mode"]
    result_note = ""
    if mode == "shield":
        add_shield(uid, 1)
        result_note = "🛡️ Himoya (+1
shield) hisobingizga qo'shildi."

```

```

elif mode == "gamble_ability":
    # 🎰 Pul emas – tasodifiy ABILITY
    beriladi (do'kondagi hech bir buyum pul
    qaytarmaydi)
    if key == "zar":
        options = [("shield", None),
        ("night_vision", 1)]
    else: # "quti"
        options = [("gps", 1),
        ("compass", 1), ("shield", None)]
        picked_key, picked_amount =
        random.choice(options)
        if picked_key == "shield":
            add_shield(uid, 1)
            result_note = "🛡️ Chiqdi:
            Himoya (+1 shield)!"
        else:
            add_charge(uid, picked_key,
            picked_amount)
            result_note = f"🌟 Chiqdi:
            {TOGGGLABLE_ITEMS.get(picked_key,
            picked_key)} ({picked_amount} ta)!"
    elif mode == "charge":
        add_charge(uid, item["charge_key"],
        item.get("charge_amount", 1))
        result_note = f"✅ Ishlatish uchun
        tayyor – {item.get('desc', '')}"
    elif mode == "multiplier":
        # 🔧 x2/x3 multiplikatorlar endi
        ABADIY emas – har xarid faqat
        # MULTIPLIER_DURATION_SECONDS (3
        kun) davomida amal qiladi, muddat
        # tugagach avtomatik x1'ga qaytadi
        (qayta xarid qilib uzaytirish kerak).

```

```

        ch = get_charges(uid)
        mkey = item["charge_key"]
        cur_until = ch.get(mkey + "_until",
0)
        new_until = max(cur_until,
time.time()) + MULTIPLIER_DURATION_SECONDS
        ch[mkey + "_val"] =
item["mult_value"]
        ch[mkey + "_until"] = new_until
        set_charges(uid, ch)
        days_left = round((new_until -
time.time()) / 86400, 1)
        result_note = f"✅ Multiplikator
faollashtirildi: x{item['mult_value']} -
{days_left} kun davomida amal qiladi."
        elif mode == "expiry":
            until = time.time() +
item["duration_seconds"]
            set_charge_value(uid,
item["charge_key"], until)
            result_note = f"✅
{item['duration_seconds']//3600} soatga
faollashtirildi."
            elif mode == "permanent_flag":
                set_charge_value(uid,
item["charge_key"], 1)
                result_note = "✅ Doimiy maqom
faollashtirildi."
            elif mode == "hero_chest":
                existing = get_hero(uid)
                if existing:
                    refund = item["price"] // 2
                    add_balance(uid,
diamond=refund)

```



```

        result_note = f"📦 Sizda
        allaqachon geroy bor ({existing['name']})!
        Sandiq {refund} 💎 ga aylantirildi."
    else:
        hero_key = roll_hero()
        with db_lock:
            cur.execute("INSERT OR
            REPLACE INTO heroes (user_id, hero_key,
            level, acquired_at) VALUES (?, ?, 1, ?)",
            (uid, hero_key, time.time()))
            conn.commit()
            hero = HEROES[hero_key]
            extra = "\n👯👯 NODIR TUSHISH!
            Siz eng kuchli geroyni qo'lga kiritdingiz!
            👯👯" if hero_key == "burgut" else ""
            result_note = f"🎁 Sandiqdan
            chiqdi: <b>{hero['name']}</b> (1-lvl)!
            {extra}\n{hero['desc']}\n/geroyim orqali
            ko'ring va rivojlantiring."

            add_inventory_item(uid, item["name"])
            bot.answer_callback_query(call.id, f"✅
            {item['name']} sotib
            olindi!\n{result_note}", show_alert=True)

#
=====
=====
# 🏹 HUNTER COIN — TELEGRAM STARS ORQALI
SOTIB OLISH
#
=====
=====

```

```

def open_hc_stars_menu(chat_id):
    kb = types.InlineKeyboardMarkup()
    for qty in (1, 5, 10, 20, 50, 100):

        kb.add(types.InlineKeyboardButton(f"{qty}
        🏴‍☠️ – {qty * HC_STAR_RATE} ★",
        callback_data=f"buyhc|{qty}"))
        bot.send_message(
            chat_id,
            "🏴‍☠️ <b>Hunter Coin sotib
        olish</b>\n\n"
            "To'lov Telegram Stars orqali
        amalga oshiriladi – <b>5 ★ = 1 🏴‍☠️</b>.\n"
            "Miqdorni tanlang:",
            reply_markup=with_back_button(kb),
        )

@bot.callback_query_handler(func=lambda c:
c.data.startswith("buyhc|"))
def cb_buy_hc_stars(call):
    maybe_capture_owner(call.from_user)
    _, qty_s = call.data.split("|")
    qty = int(qty_s)
    stars_price = qty * HC_STAR_RATE
    try:
        bot.send_invoice(
            call.message.chat.id,
            title=f"{qty} Hunter Coin",
            description=f"{qty} dona Hunter
        Coin sotib olish ({stars_price} ★ Stars)",
            invoice_payload=f"hc_{call.from_user.id}_{q

```

```

ty}",
        provider_token="",      #
Telegram Stars uchun bo'sh qoldiriladi
        currency="XTR",        #
Telegram Stars valyutasi
        prices=
[types.LabeledPrice(label=f"{qty} Hunter
Coin", amount=stars_price)],
    )
    bot.answer_callback_query(call.id)
except Exception:
    bot.answer_callback_query(call.id,
    "❌ To'lov tizimida xatolik. Keyinroq
    urinib ko'ring.", show_alert=True)

@bot.pre_checkout_query_handler(func=lambda
q: True)
def checkout_handler(pre_checkout_query):

    bot.answer_pre_checkout_query(pre_checkout_
    query.id, ok=True)

#
=====
=====
# 🎁 STARS TO'LOVINI QAYTARISH (#8) –
/refund
#
=====
=====

@bot.message_handler(commands=["refund"])

```

```

def cmd_refund(message):
    """👉 FAQAT bot egasi – xato yoki
    noto'g'ri to'lovni Telegram Stars orqali
    qaytaradi (refund). Foydalanuvchining
    OXIRGI muvaffaqiyatli to'lovi
    avtomatik topiladi va qaytariladi.
    Foydalanish: /refund <user_id> YOKI
    kimningdir xabariga reply qilib /refund
    🔒 XAVFSIZLIK: bu funksiya kutubxona
    versiyasiga bog'liq (refund_star_payment) –
    agar mavjud bo'lmasa, aniq xabar bilan
    to'xtaydi, botni yiqitmaydi."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        return

    target_id = None
    parts = message.text.split()
    if message.reply_to_message and
    message.reply_to_message.from_user:
        target_id =
        message.reply_to_message.from_user.id
    elif len(parts) == 2 and
    parts[1].isdigit():
        target_id = int(parts[1])
    else:
        bot.send_message(message.chat.id,
        "Foydalanish: <code>/refund &lt;user_id>&gt;
        </code> yoki kimningdir xabariga reply
        qilib <code>/refund</code>.")
        return

    charge_id =

```

```

get_setting(f"last_charge_{target_id}")
    if not charge_id:
        bot.send_message(message.chat.id,
f"❌ <code>{target_id}</code> uchun so'nggi
Stars to'lovi topilmadi.")
        return

    try:
        bot.refund_star_payment(target_id,
charge_id)
        bot.send_message(message.chat.id,
f"✅ <code>{target_id}</code>ning so'nggi
to'lovi muvaffaqiyatli qaytarildi
(refund).")
        safe_send(target_id, "💰 So'nggi
Stars to'lovingiz bot egasi tomonidan
qaytarildi (refund qilindi).")
    except AttributeError:
        bot.send_message(
            message.chat.id,
            "❌ Ushbu botning
pyTelegramBotAPI kutubxona versiyasida
<code>refund_star_payment</code> "
            "mavjud emas. Kutubxonani
yangilang: <code>pip install --upgrade
pyTelegramBotAPI</code>",
        )
    except Exception as e:
        bot.send_message(message.chat.id,
f"❌ Qaytarishda xatolik: {e}")

@bot.message_handler(content_types=
["successful_payment"])

```

```

def successful_payment_handler(message):
    payload =
message.successful_payment.invoice_payload
    # 🛠 YANGI (#8): har bir muvaffaqiyatli
to'lovning charge_id'sini saqlab qo'yamiz –
    # kerak bo'lsa /refund buyrug'i orqali
bu to'lovni qaytarish (refund) mumkin
bo'lsin deb.
    try:

set_setting(f"last_charge_{message.from_user.id}",
message.successful_payment.telegram_payment
_charge_id)
    except Exception:
        pass
    try:
        parts = payload.split("_")
        kind = parts[0]
    except Exception:
        return

    if kind == "hc":
        _, uid_s, qty_s = parts
        uid, qty = int(uid_s), int(qty_s)
        add_balance(uid, coin=qty)
        bot.send_message(message.chat.id,
f"✅ To'lov muvaffaqiyatli o'tdi! +{qty} 🪙
Hunter Coin hisobingizga
qo'shildi.\nRahmat!")

        elif kind == "diamondbuy":
            # 💎 Yangi: Olmosni to'g'ridan-
to'g'ri Stars orqali sotib olish (7★ = 1

```

```

💎)
    _, uid_s, qty_s = parts
    uid, qty = int(uid_s), int(qty_s)
    add_balance(uid, diamond=qty)
    bot.send_message(message.chat.id,
f"✅ To'lov muvaffaqiyatli o'tdi! +{qty} 💎
Olmos hisobingizga qo'shildi.\nRahmat!")

    elif kind == "elitepay":
        # 🏰 HUNTER ELITE – tarifli (1
hafta – 3 oy) obuna, Stars orqali
to'langanda shu yerga tushadi
        _, uid_s, days_s = parts
        uid, days = int(uid_s), int(days_s)
        new_until = grant_elite_days(uid,
days)
        bot.send_message(
            message.chat.id,
            elite_success_text(days,
new_until),
        )

#
=====
=====
# 💎 OLMOS DO'KONI – to'g'ridan-to'g'ri
Telegram Stars orqali Olmos sotib olish
# (🔧 TUZATILDI: eski "Birja / VIP" tizimi
olib tashlandi – botda endi HECH
# QANDAY "VIP" nomli buyum yoki xizmat
yo'q, faqat 🏰 HUNTER ELITE bor.
# Narx: 1 💎 Olmos = 7 ⭐ Stars.)
#

```

```

=====
=====

DIAMOND_STARS_RATE = 7 # 1 💎 Olmos narxi
= 7 ★ Stars
DIAMOND_PACKAGES = [10, 30, 50, 100, 200]

def open_diamond_shop_menu(chat_id, uid):
    kb =
    types.InlineKeyboardMarkup(row_width=1)
    for qty in DIAMOND_PACKAGES:
        price = qty * DIAMOND_STARS_RATE

    kb.add(types.InlineKeyboardButton(f"💎
    {qty} Olmos – {price} ★ Stars",
    callback_data=f"buydiamond|{qty}"))
    kb.add(types.InlineKeyboardButton("🟡
    10 Coin ➡ 60-100 💎 Olmos almashtirish",
    callback_data="exchange_to_diamond"))
    bot.send_message(
        chat_id,
        "💎🌟 <b>OLMOS DO'KONI</b> 🌟💎\n"
        "_____ \n\n"
        f"★ 1 💎 Olmos narxi: <b>
    {DIAMOND_STARS_RATE} Stars</b>\n\n"
        "Kerakli miqdorni tanlang yoki
    Hunter Coin orqali almashtiring:",
        reply_markup=with_back_button(kb),
    )

@bot.message_handler(commands=
    ["almazdokon", "birja"])

```



```

def cmd_diamond_shop(message):
    """💎 Olmos do'koni – /birja eski nomi
    ham ishlaydi (o'rgangan foydalanuvchilar
    uchun qulaylik), lekin endi bu yerda
    HECH QANDAY "VIP" mavjud emas – faqat
    to'g'ridan-to'g'ri Olmos sotib olish
    (7★ = 1💎)."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    open_diamond_shop_menu(message.chat.id,
    message.from_user.id)

@bot.callback_query_handler(func=lambda c:
c.data.startswith("buydiamond|"))
def cb_buy_diamond_stars(call):
    try:
        maybe_capture_owner(call.from_user)
        uid = call.from_user.id
        qty = int(call.data.split("|")[1])
        if qty not in DIAMOND_PACKAGES:

bot.answer_callback_query(call.id, "❌
Noto'g'ri miqdor.", show_alert=True)
        return
        price = qty * DIAMOND_STARS_RATE
        bot.send_invoice(
            call.message.chat.id,
            title=f"💎 {qty} Olmos",
            description=f"{qty} ta Olmos
sotib olish ({price} ★ Stars)",

            invoice_payload=f"diamondbuy_{uid}_{qty}",
            provider_token="", # Telegram

```

```

Stars uchun bo'sh qoldiriladi
        currency="XTR",
        prices=
[types.LabeledPrice(label=f"{qty} Olmos",
amount=price)],
    )
    bot.answer_callback_query(call.id)
except Exception as e:

_logger.warning("cb_buy_diamond_stars
xatolik: %s", e)
    try:

bot.answer_callback_query(call.id, "❌
To'lov tizimida xatolik. Keyinroq urinib
ko'ring.", show_alert=True)
        except Exception:
            pass

@bot.callback_query_handler(func=lambda c:
c.data == "exchange_to_diamond")
def cb_exchange_to_diamond(call):
    try:
        maybe_capture_owner(call.from_user)
        uid = call.from_user.id
        u = user_dict(uid,
call.from_user.first_name)
        # 🔧 XATOLIK TUZATILDI: avval 10 🏠
evaziga 60-100 💎 berilar edi – bu narx
        # to'g'ridan-to'g'ri Stars orqali
Olmos sotib olish narxidan (7★=1💎) 10x
        # arzonroq edi va deyarli bepul
Olmos manbaiga aylangan. Endi muvozanatli.

```

```

        dynamic_diamond_rate =
random.randint(6, 10)

        if u["coin"] < 10:

bot.answer_callback_query(call.id, "❌
Hisobingizda Hunter Coin yetarli emas!
(Kamida 10 🪙 kerak)", show_alert=True)
            return

            add_balance(uid, coin=-10,
diamond=dynamic_diamond_rate)
            bot.answer_callback_query(call.id,
"✅ Muvaffaqiyatli almashtirildi!",
show_alert=True)
            try:
                bot.edit_message_text(
                    f"💰 <b>Ayirboshlash
bajarildi!</b>\n\n"
                    f"➖ 10 🪙 Hunter Coin
sarflandi.\n"
                    f"➕ Hisobingizga <b>
{dynamic_diamond_rate}</b> ta 💎 Olmos
qo'shildi!",
                    call.message.chat.id,
call.message.message_id,
                    )
            except Exception:
                pass
            except Exception as e:

_logger.warning("cb_exchange_to_diamond
xatolik: %s", e)
            try:

```

```

bot.answer_callback_query(call.id, "⚠️
Xatolik yuz berdi.", show_alert=True)
    except Exception:
        pass

#
=====
=====
#  ADMIN PANEL (faqat bot yaratuvchisi)
#
=====
=====

@bot.callback_query_handler(func=lambda c:
c.data == "admin|panel")
def cb_admin_panel(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
"🚫 Ruxsat yo'q.", show_alert=True)
        return
    bot.answer_callback_query(call.id)
    kb = types.InlineKeyboardMarkup()
    kb.add(types.InlineKeyboardButton("📋
Guruhlar ro'yxati",
callback_data="admin|groups"))
    kb.add(types.InlineKeyboardButton("📊
Statistika", callback_data="admin|stats"))
    kb.add(types.InlineKeyboardButton("🛑
Barcha faol o'yinlarni to'xtatish",
callback_data="admin|stopall"))
    kb.add(types.InlineKeyboardButton("🔙

```

```

Global xabar (broadcast)",
callback_data="admin|broadcast_info"))
    kb.add(types.InlineKeyboardButton("$💰",
Balans boshqaruvi",
callback_data="admin|money_info"))
    kb.add(types.InlineKeyboardButton("🚫",
Ban / Unban",
callback_data="admin|ban_info"))
    kb.add(types.InlineKeyboardButton("💾",
Bazadan zaxira nusxa (backup)",
callback_data="admin|backup"))
    kb.add(types.InlineKeyboardButton("🔄",
Bazani tiklash (restore)",
callback_data="admin|restore"))
    # --- 🧨 Yangi qo'shilgan 5 ta owner
    funksiyasi ---
    kb.add(types.InlineKeyboardButton("📈",
To'liq bot statistikasi",
callback_data="admin|full_stats"))
    kb.add(types.InlineKeyboardButton("🏀",
Ball qo'lda qo'shish/ayirish",
callback_data="admin|ball_info"))
    kb.add(types.InlineKeyboardButton("🛑",
Joriy guruh o'yinini zudlik bilan
to'xtatish",
callback_data="admin|force_end_info"))
    kb.add(types.InlineKeyboardButton("👤",
Hozir faol o'yinlar ro'yxati",
callback_data="admin|active_list"))
    kb.add(types.InlineKeyboardButton("💎",
Valyuta qo'lda berish",
callback_data="admin|currency_info"))
    kb.add(types.InlineKeyboardButton("🏆",
Geroy qo'lda berish",

```

```

callback_data="admin|hero_give_info"))
    # --- 🏰 Yangi qo'shilgan 3 ta owner
    funksiyasi (Almex tahlili asosida) ---
    kb.add(types.InlineKeyboardButton("🔍
    Foydalanuvchi profilini qidirish",
    callback_data="admin|user_lookup_info"))
    kb.add(types.InlineKeyboardButton("👤
    Botni guruhdan chiqarish",
    callback_data="admin|leave_group_info"))
    kb.add(types.InlineKeyboardButton("👑
    ELITE qo'lda, muddatli berish",
    callback_data="admin|elite_give_info"))
    # --- 🏰 Yangi qo'shilgan 6 ta owner
    funksiyasi (narx boshqaruvi + qulayliklar)
    ---
    kb.add(types.InlineKeyboardButton("💰
    ELITE narxlarini o'zgartirish",
    callback_data="admin|elite_price"))
    kb.add(types.InlineKeyboardButton("📦
    To'liq zaxira nusxa (o'yinlar bilan)",
    callback_data="admin|full_backup"))
    kb.add(types.InlineKeyboardButton("🔄
    Botni hozir qayta ishga tushirish",
    callback_data="admin|restart_confirm"))
    kb.add(types.InlineKeyboardButton("🧠
    Theron AI holati (tekshirish)",
    callback_data="admin|ai_status"))
    kb.add(types.InlineKeyboardButton("🏥
    Bot holati (uptime, oqimlar, baza)",
    callback_data="admin|health"))
    kb.add(types.InlineKeyboardButton("🆘
    Foydalanuvchi yordam menyusi",
    callback_data="admin|show_help"))
    kb.add(types.InlineKeyboardButton("⚙️

```

```

Bot sozlamalari (10 ta parametr)",
callback_data="admin|bot_settings"))
    bot.send_message(
        call.message.chat.id,
        "⚙️ <b>ADMIN PANEL</b> (faqat
yaratuvchi uchun)\n\n"
        "Ba'zi funksiyalar buyruq orqali
ishlaydi – tugmani bosganingizda kerakli
buyruq ko'rsatiladi.",
        reply_markup=kb,
    )

@bot.callback_query_handler(func=lambda c:
c.data == "admin|groups")
def cb_admin_groups(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
"🚫 Ruxsat yo'q.", show_alert=True)
        return
    bot.answer_callback_query(call.id)
    groups = list_known_groups()
    if not groups:
        text = "Bot hali birorta guruhga
qo'shilmagan."
    else:
        lines = ["📋 <b>Guruhlar:</b>", ""]
        for cid, title in groups:
            lines.append(f"• {title} (ID:
<code>{cid}</code>)")
        text = "\n".join(lines)
    bot.send_message(call.message.chat.id,
text)

```

```

@bot.callback_query_handler(func=lambda c:
c.data == "admin|stats")
def cb_admin_stats(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
        "🚫 Ruxsat yo'q.", show_alert=True)
        return
    bot.answer_callback_query(call.id)
    with db_lock:
        cur.execute("SELECT COUNT(*) FROM
users")
        total_users = cur.fetchone()[0]
    text = (
        "📊 <b>Statistika</b>\n\n"
        f"👥 Ro'yxatdan o'tgan
foydalanuvchilar: {total_users}\n"
        f"🏠 Bot qo'shilgan guruhlar:
{len(list_known_groups())}\n"
        f"🎮 Faol o'yinlar soni:
{len(GAMES)}"
    )
    bot.send_message(call.message.chat.id,
text)

```

```

@bot.callback_query_handler(func=lambda c:
c.data == "admin|stopall")
def cb_admin_stopall(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,

```



```

"🚫 Ruksat yo'q.", show_alert=True)
    return
    n = len(GAMES)
    GAMES.clear()
    bot.answer_callback_query(call.id, f"🔴
{n} ta faol o'yin to'xtatildi.",
show_alert=True)

# --- QO'SHIMCHA ADMIN FUNKSIYALARI
(qoshimchakod7.py g'oyasi, telebot uslubiga
moslashtirildi) ---

@bot.callback_query_handler(func=lambda c:
c.data == "admin|broadcast_info")
def cb_admin_broadcast_info(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
"🚫 Ruksat yo'q.", show_alert=True)
        return
    bot.answer_callback_query(call.id)
    bot.send_message(call.message.chat.id,
"👤 Barcha foydalanuvchilarga xabar
yuborish uchun:\n<code>/sendall Sizning
xabaringiz</code>")

@bot.callback_query_handler(func=lambda c:
c.data == "admin|money_info")
def cb_admin_money_info(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,

```

```

"🚫 Ruxsat yo'q.", show_alert=True)
    return
    bot.answer_callback_query(call.id)
    bot.send_message(
        call.message.chat.id,
        "💰 <b>Balans boshqaruvi:</b>\n\n"
        "<code>/addmoney <user_id>
        <summa></code> – Dollar
        qo'shish/ayirish\n"
        "<code>/adddiamond <user_id>
        <miqdor></code> – Olmos
        qo'shish/ayirish\n"
        "<code>/addcoin <user_id>
        <miqdor></code> – Hunter Coin
        qo'shish/ayirish\n\n"
        "<i>Manfiy son yozsangiz, balansdan
        ayiradi.</i>\n\n"
        "🎁 <b>Promo-kod va tarqatish:
        </b>\n"
        "<code>/promo_create <KOD>
        <dollar> <diamond> <coin>
        <limit></code>\n"
        "<code>/tarqatish
        <dollar|diamond|coin>
        <har_biriga> <kishi_soni>
        </code>"
    )

@bot.callback_query_handler(func=lambda c:
c.data == "admin|ban_info")
def cb_admin_ban_info(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):

```

```

        bot.answer_callback_query(call.id,
    "🚫 Ruxsat yo'q.", show_alert=True)
        return
    bot.answer_callback_query(call.id)
    bot.send_message(
        call.message.chat.id,
        "🚫 <b>Ban / Unban:</b>\n\n"
        "<code>/ban <user_id></code>
    – foydalanuvchini bloklash (o'yinlarga
    qo'shila olmaydi)\n"
        "<code>/unban <user_id>
    </code> – blokdan chiqarish",
    )

```

```

@bot.callback_query_handler(func=lambda c:
c.data == "admin|full_stats")
def cb_admin_full_stats(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
    "🚫 Ruxsat yo'q.", show_alert=True)
        return
    bot.answer_callback_query(call.id)
    with db_lock:
        cur.execute("SELECT COUNT(*),
    COALESCE(SUM(games),0),
    COALESCE(SUM(wins),0), "
    "COALESCE(SUM(dollar),0),
    COALESCE(SUM(diamond),0),
    COALESCE(SUM(coin),0) FROM users")
        row = cur.fetchone()
        cur.execute("SELECT COUNT(*) FROM

```

```

heroes")
    hero_count = cur.fetchone()[0]
    total_users, total_games, total_wins,
    total_dollar, total_diamond, total_coin =
    row
    text = (
        "📊 <b>BOT BO'YICHA UMUMIY
STATISTIKA</b>\n\n"
        f"👥 Ro'yxatdan o'tgan
foydalanuvchilar: <b>{total_users}</b>\n"
        f"🎮 Jami o'ynalgan o'yinlar
(yig'indi): <b>{total_games // 2 if
total_games else 0}</b>\n"
        f"🏆 Jami g'alabalar: <b>
{total_wins}</b>\n"
        f"💵 Muomaladagi jami dollar:
<b>${total_dollar}</b>\n"
        f"💎 Muomaladagi jami olmos: <b>
{total_diamond}</b>\n"
        f"🪙 Muomaladagi jami coin: <b>
{total_coin}</b>\n"
        f"🏆 Geroyga ega foydalanuvchilar:
<b>{hero_count}</b>\n"
        f"👤 Hozir faol o'yinlar soni: <b>
{len(GAMES)}</b>"
    )
    bot.send_message(call.message.chat.id,
text)

@bot.callback_query_handler(func=lambda c:
c.data == "admin|active_list")
def cb_admin_active_list(call):
    maybe_capture_owner(call.from_user)

```

```

        if not is_owner(call.from_user.id):
            bot.answer_callback_query(call.id,
                "🚫 Ruxsat yo'q.", show_alert=True)
            return
        bot.answer_callback_query(call.id)
        if not GAMES:

bot.send_message(call.message.chat.id, "🚫
Hozir hech qanday faol o'yin yo'q.")
        return
        lines = ["👤 <b>HOZIR FAOL
O'YINLAR</b>\n"]
        for i, (cid, g) in
enumerate(GAMES.items(), 1):
            phase_label = {"night": "🌙 Tun",
"day": "☀️ Kun", "lobby": "🚗
Lobbi"}.get(g.get("phase"), g.get("phase"))
            lines.append(f"{i}. <code>{cid}
</code> - {phase_label},
{g.get('day_number', 0)}-kun,
{len(g.get('players', {}))} o'yinchi")
            bot.send_message(call.message.chat.id,
"\n".join(lines))

@bot.callback_query_handler(func=lambda c:
c.data == "admin|ball_info")
def cb_admin_ball_info(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
            "🚫 Ruxsat yo'q.", show_alert=True)
        return
    bot.answer_callback_query(call.id)

```

```

        bot.send_message(
            call.message.chat.id,
            "🏀 <b>Ball qo'lda  

qo'shish/ayirish:</b>\n\n"
            "Kimningdir xabariga reply  

qilib:\n<code>/ball_ber &lt;son>&gt;</code>  

(masalan: 25 yoki -10)",
        )

```

```

@bot.callback_query_handler(func=lambda c:
c.data == "admin|force_end_info")
def cb_admin_force_end_info(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
        "🚫 Ruxsat yo'q.", show_alert=True)
        return
    bot.answer_callback_query(call.id)
    bot.send_message(
        call.message.chat.id,
        "🔴 <b>Joriy guruh o'yinini zudlik  

bilan to'xtatish:</b>\n\n"
        "Bu buyruqni faol o'yin ketayotgan  

GURUHNING ICHIDA  

yozing:\n<code>/oyinni_zorla_tugat</code>",
    )

```

```

@bot.callback_query_handler(func=lambda c:
c.data == "admin|currency_info")
def cb_admin_currency_info(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):

```



```

    )

@bot.callback_query_handler(func=lambda c:
c.data == "admin|backup")
def cb_admin_backup(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
"🚫 Ruxsat yo'q.", show_alert=True)
        return
    bot.answer_callback_query(call.id)
    try:
        with db_lock:
            cur.execute("SELECT * FROM
users")
            rows = cur.fetchall()
            data = [dict(zip(USER_COLS, r)) for
r in rows]
            path =
"/tmp/hunter_mafia_backup.json"
            with open(path, "w", encoding="utf-
8") as f:
                json.dump(data, f,
ensure_ascii=False, indent=2)
            with open(path, "rb") as f:

bot.send_document(call.message.chat.id, f,
caption="🍰 Foydalanuvchilar bazasining
zaxira nusxasi (JSON).")
    except Exception as e:

bot.send_message(call.message.chat.id, f"❌
Zaxira nusxa olishda xatolik: {e}")

```



```

#
=====
=====
# 🔄 BAZANI TIKLASH (RESTORE) –
/bazani_tikla
# Admin panel: "🔄 Bazani tiklash
(restore)" tugmasi → /bazani_tikla
buyrug'i →
# keyingi yuborilgan .json fayl
(admin|backup natijasi) o'qilib, ustuniga
# qarab (INSERT OR REPLACE) joriy bazadagi
mos foydalanuvchilar yangilanadi,
# bazada yo'q foydalanuvchilar esa yangi
qator sifatida qo'shiladi.
#
=====
=====

# Bot egasidan .json faylni kutayotgan
(shaxsiy chatdagi) userlar to'plami
ADMIN_AWAITING_RESTORE = set()

@bot.callback_query_handler(func=lambda c:
c.data == "admin|restore")
def cb_admin_restore_info(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
"🚫 Ruksat yo'q.", show_alert=True)
    return
    bot.answer_callback_query(call.id)

```

```

        bot.send_message(
            call.message.chat.id,
            "🔄 <b>Bazani tiklash:</b>\n\n"
            "/bazani_tikla deb yozing, so'ng
            bot so'ragan joyga avvalgi zaxira nusxa
            (.json) faylni yuboring.",
        )

@bot.message_handler(commands=
["bazani_tikla"])
def cmd_bazani_tikla(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        bot.send_message(message.chat.id,
            "🚫 Bu buyruq faqat bot egasi uchun.")
        return

ADMIN_AWAITING_RESTORE.add(message.from_user.id)
    bot.send_message(
        message.chat.id,
        "📦 Endi zaxira nusxa (.json)
        faylni shu yerga <b>fayl</b> sifatida
        yuboring.\n\n"
        "⚠ <b>Diqqat:</b> bu amal joriy
        bazadagi mos foydalanuvchilarning
        ma'lumotini backup "
        "fayldagi qiymatlar bilan
        almashtiradi (ustma-ust yozadi). Backup
        faylda yo'q "
        "foydalanuvchilarga tegmaydi.",
    )

```

```

@bot.message_handler(content_types=
["document"])
def handle_restore_document(message):
    maybe_capture_owner(message.from_user)
    uid = message.from_user.id
    # faqat bot egasidan, faqat
/bazani_tikla dan keyin va faqat shaxsiy
chatda kutamiz –
    # aks holda bu handler guruhlardagi
oddiy fayl yuborishlarga aralashmasligi
kerak
    if message.chat.type != "private" or
uid not in ADMIN_AWAITING_RESTORE:
        return
    ADMIN_AWAITING_RESTORE.discard(uid)

    doc = message.document
    if not doc or not (doc.file_name or
"".lower().endswith(".json")):
        bot.send_message(message.chat.id,
"✗ Bu .json fayl emas. Tiklash bekor
qilindi – qaytadan /bazani_tikla deb
yozing.")
        return

    try:
        file_info =
bot.get_file(doc.file_id)
        raw =
bot.download_file(file_info.file_path)
        data = json.loads(raw.decode("utf-
8"))

```

```

except Exception as e:
    bot.send_message(message.chat.id,
f"❌ Faylni o'qib bo'lmadi: {e}")
    return

    if not isinstance(data, list):
        bot.send_message(message.chat.id,
f"❌ Fayl formati noto'g'ri – JSON ro'yxat
(list) bo'lishi kerak.")
        return

    restored = 0
    skipped = 0
    placeholders = ",".join(["?"] *
len(USER_COLS))
    col_list = ",".join(USER_COLS)

    with db_lock:
        for entry in data:
            if not isinstance(entry, dict)
or entry.get("user_id") in (None, ""):
                skipped += 1
                continue
            try:
                row_values =
[entry.get(col) for col in USER_COLS]
                row_values[0] =
int(entry["user_id"]) # user_id har doim
int bo'lishi shart
                cur.execute(f"INSERT OR
REPLACE INTO users ({col_list}) VALUES
({placeholders})", row_values)
                restored += 1
            except Exception:

```

```

        skipped += 1
        conn.commit()

        bot.send_message(
            message.chat.id,
            "✅ <b>Tiklash yakunlandi!</b>\n"
            f"👤 Tiklangan/yangilangan:
{restored} ta\n"
            f"⚠️ O'tkazib yuborilgan (noto'g'ri
format): {skipped} ta",
        )

_PENDING_SENDALL = {} # owner_id -> xabar
matni (Theron ruxsat so'rab kutayotgan
ommaviy xabar)

@bot.message_handler(commands=["sendall"])
def cmd_sendall(message):
    """🔥 Ommaviy xabar – MUHIM amal
    bo'lgani uchun endi darhol yuborilmaydi:
    Theron avval xabar matnini ko'rsatib,
    egadan ANIQ tasdiq (tugma orqali)
    so'raydi, faqat "Ha" bosilgandan keyin
    haqiqiy yuborish boshlanadi."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        bot.send_message(message.chat.id,
        "🚫 Bu buyruq faqat bot egasi uchun.")
        return
    parts = message.text.split(maxsplit=1)
    if len(parts) < 2:

```

```

        bot.send_message(message.chat.id,
        "Foydalanish: <code>/sendall Xabar
matni</code>")
        return
        text = parts[1]
        uid = message.from_user.id

        with db_lock:
            cur.execute("SELECT COUNT(*) FROM
users")
            total = cur.fetchone()[0]

        _PENDING_SENALL[uid] = text
        kb =
types.InlineKeyboardMarkup(row_width=2)
        kb.add(
            types.InlineKeyboardButton("✅ Ha,
yuborilsin",
callback_data="sendall_confirm|yes"),
            types.InlineKeyboardButton("❌
Bekor qilish",
callback_data="sendall_confirm|no"),
        )
        theron_note = (
            f"🧠 <b>{THERON_NAME}</b>
Xo'jayin, <b>{total}</b> ta</b> foydalanuvchiga
quyidagi xabarni yuborishni "
            "so'rayapsiz – tasdiqlaysizmi?\n\n"
            f"👉 <i>\">{text}</i>\n\n"
            "Xato bo'lsa, «❌ Bekor qilish»
tugmasini bosing."
        )
        bot.send_message(message.chat.id,
        theron_note, reply_markup=kb)

```

```

@bot.callback_query_handler(func=lambda c:
c.data.startswith("sendall_confirm|"))
def cb_sendall_confirm(call):
    uid = call.from_user.id
    if not is_owner(uid):
        bot.answer_callback_query(call.id,
"🚫 Bu buyruq faqat bot egasi uchun.",
show_alert=True)
        return
    decision = call.data.split("|", 1)[1]
    text = _PENDING_SENDALL.pop(uid, None)
    if decision == "no" or not text:
        bot.answer_callback_query(call.id,
"❌ Bekor qilindi.")
        try:
            bot.edit_message_text("❌
Ommaviy xabar bekor qilindi.",
call.message.chat.id,
call.message.message_id)
        except Exception:
            pass
        return

    bot.answer_callback_query(call.id, "✅
Yuborilmoqda...")
    try:
        bot.edit_message_text("⌚ Xabar
yuborilmoqda, biroz kuting...",
call.message.chat.id,
call.message.message_id)
    except Exception:
        pass

```

```

        with db_lock:
            cur.execute("SELECT user_id FROM
users")
            user_ids = [r[0] for r in
cur.fetchall()]
            sent, failed = 0, 0
            for target_uid in user_ids:
                try:
                    bot.send_message(target_uid,
f"🔊 <b>E'lon:</b>\n\n{text}")
                    sent += 1
                except Exception:
                    failed += 1
            bot.send_message(
                call.message.chat.id,
                f"🔊 Xabar yuborildi: {sent} ta
muvaffaqiyatli, {failed} ta yetib
bormadi.\n\n"
                f"🧠 <b>{THERON_NAME}</b> Vazifa
bajarildi, xo'jayin! ✅",
            )

def _admin_adjust_balance(message,
field_name, icon):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        bot.send_message(message.chat.id,
f"🚫 Bu buyruq faqat bot egasi uchun.")
        return
    parts = message.text.split()
    if len(parts) != 3 or not

```



```

parts[1].lstrip("-").isdigit() or not
parts[2].lstrip("-").isdigit():
    bot.send_message(message.chat.id,
f"Foydalanish:
<code>/{parts[0].lstrip('/')}&lt;user_id&gt; &lt;miqdor&gt;</code>")
    return
    target_id, amount = int(parts[1]),
int(parts[2])
    user_dict(target_id)
    add_balance(target_id, **{field_name:
amount})
    bot.send_message(message.chat.id, f"✅
Foydalanuvchi <code>{target_id}</code>
balansiga {amount} {icon}
qo'shildi/ayrildi.")

@bot.message_handler(commands=["addmoney"])
def cmd_addmoney(message):
    _admin_adjust_balance(message,
"dollar", "$")

@bot.message_handler(commands=
["adddiamond"])
def cmd_adddiamond(message):
    _admin_adjust_balance(message,
"diamond", "💎")

@bot.message_handler(commands=["addcoin"])
def cmd_addcoin(message):
    _admin_adjust_balance(message, "coin",

```

"👤")

```
@bot.message_handler(commands=["ban"])
def cmd_ban(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        bot.send_message(message.chat.id,
            "🚫 Bu buyruq faqat bot egasi uchun.")
        return
    parts = message.text.split()
    if len(parts) != 2 or not
parts[1].isdigit():
        bot.send_message(message.chat.id,
            "Foydalanish: <code>/ban &lt;user_id&gt;
            </code>")
        return
    target_id = int(parts[1])
    user_dict(target_id)
    ban_user(target_id)
    bot.send_message(message.chat.id, f"🚫
Foydalanuvchi <code>{target_id}</code>
bloklandi.")
```

```
@bot.message_handler(commands=["unban"])
def cmd_unban(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        bot.send_message(message.chat.id,
            "🚫 Bu buyruq faqat bot egasi uchun.")
        return
```

```

        parts = message.text.split()
        if len(parts) != 2 or not
parts[1].isdigit():
            bot.send_message(message.chat.id,
"Foydalanish: <code>/unban &lt;user_id&gt;
</code>")
            return
        target_id = int(parts[1])
        unban_user(target_id)
        bot.send_message(message.chat.id, f"✅
Foydalanuvchi <code>{target_id}</code>
blokdan chiqarildi.")

#
=====
=====
# 🚫 GURUH-DARAJASIDAGI TELEGRAM BAN/UNBAN
TIZIMI
# ⚠️ MUHIM TEXNIK CHEKLOV: Telegram Bot
API'da guruhdagi BARCHA bloklangan
# foydalanuvchilar ro'yxatini olish
(getChatBannedUsers) UMUMAN MAVJUD EMAS –
# bu Telegram platformasining o'zi qo'ygan
cheklov, hech qanday kod bilan
# aylanib o'tib bo'lmaydi (faqat MTPROTO-
asoslangan userbot – Pyrogram/Telethon –
# orqali VA faqat administrator huquqi
bilan mumkin, oddiy Bot API orqali emas).
#
# Shuning uchun bu yerda ISHLAYDIGAN,
halol yechim taqdim etiladi: bot o'zi
# /guruh_ban orqali kimnidir bloklaydi, uni
mahalliy bazaga yozib boradi va

```

```

# keyin /guruh_unban_hammasi ANIQ SHU
RO'YXATNI (bot o'zi bloklaganlarni)
# birma-bir, FloodWait'dan qochish uchun
orada kutish bilan, unban qiladi.
#
=====
=====

cur.execute("""
CREATE TABLE IF NOT EXISTS chat_bans (
    chat_id INTEGER,
    user_id INTEGER,
    PRIMARY KEY (chat_id, user_id)
)
""")
conn.commit()

def _is_real_group_admin(chat_id, user_id):
    """Foydalanuvchi shu GURUHNING
    (Telegram darajasida) admini yoki egasi
    ekanini tekshiradi."""
    if is_owner(user_id):
        return True
    try:
        member =
bot.get_chat_member(chat_id, user_id)
        return member.status in
("administrator", "creator")
    except Exception:
        return False

@bot.message_handler(commands=

```

```

["guruh_ban"])
def cmd_guruh_ban(message):
    """🚫 Guruh admini – kimningdir
    xabariga reply qilib, uni Telegram
    guruhidan
    bloklaydi (haqiqiy chat ban) VA
    keyinchalik ommaviy unban qilish uchun
    ro'yxatga yozadi."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if message.chat.type not in ("group",
    "supergroup"):
        return
    if not
    _is_real_group_admin(message.chat.id,
    message.from_user.id):
        bot.send_message(message.chat.id,
        "🚫 Bu buyruq faqat guruh administratori
        uchun.")
        return
    if not message.reply_to_message or not
    message.reply_to_message.from_user:
        bot.send_message(message.chat.id,
        "🚫 Kimnidir bloklash uchun uning xabariga
        <b>reply</b> qilib /guruh_ban deb yozing.")
        return
    target =
    message.reply_to_message.from_user
    try:

    bot.ban_chat_member(message.chat.id,
    target.id)
    except Exception as e:
        bot.send_message(message.chat.id,

```

```
f"❌ Bloklab bo'lmadi: {e}")
    return
    with db_lock:
        cur.execute("INSERT OR IGNORE INTO
chat_bans (chat_id, user_id) VALUES (?,
?)", (message.chat.id, target.id))
        conn.commit()
        bot.send_message(message.chat.id, f"❌
{target.first_name} guruhdan bloklandi.")
```

```
@bot.message_handler(commands=
["guruh_unban_hammasi"])
def cmd_guruh_unban_hammasi(message):
    """✅ Guruh admini – ushbu bot ORQALI
bloklangan barcha foydalanuvchilarni
birma-bir, FloodWait'dan saqlanish
uchun orada kutish bilan, unban qiladi.
(Bot orqali emas, boshqa usulda
bloklanganlar bu ro'yxatda bo'lmaydi – bu
Telegram Bot API'ning texnik cheklovi,
yuqoridagi izohga qarang.)"""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if message.chat.type not in ("group",
"supergroup"):
        return
    if not
_is_real_group_admin(message.chat.id,
message.from_user.id):
        bot.send_message(message.chat.id,
"❌ Bu buyruq faqat guruh administratori
uchun.")
    return
```

```

        with db_lock:
            cur.execute("SELECT user_id FROM
chat_bans WHERE chat_id=?",
(message.chat.id,))
            rows = [r[0] for r in
cur.fetchall()]

        if not rows:
            bot.send_message(
                message.chat.id,
                "🚫 Ushbu bot orqali bloklangan
hech kim topilmadi.\n\n"
                "ℹ Eslatma: Telegram Bot API
guruhdagi BARCHA bloklanganlar ro'yxatini "
                "berish imkoniyatini umuman
taqdim etmaydi – faqat ushbu bot o'zi "
                "/guruh_ban bilan
bloklaganlarni kuzatib boradi.",
            )
            return

        status_msg =
bot.send_message(message.chat.id, f"⌚
{len(rows)} ta foydalanuvchi unban
qilinmoqda...")
        success, failed = 0, 0
        for i, uid in enumerate(rows, 1):
            try:

bot.unban_chat_member(message.chat.id, uid,
only_if_banned=True)
                success += 1
            except Exception:

```

```

        failed += 1
        # 🕒 FloodWait'dan saqlanish uchun
        har bir amaldan keyin qisqa tanaffus
        time.sleep(0.6)
        if i % 15 == 0:
            try:
                bot.edit_message_text(f"⌚
Jarayonda... {i}/{len(rows)}",
message.chat.id, status_msg.message_id)
            except Exception:
                pass

        with db_lock:
            cur.execute("DELETE FROM chat_bans
WHERE chat_id=?", (message.chat.id,))
            conn.commit()

        try:
            bot.edit_message_text(
                f"✅ <b>Tugallandi!</b>\n\n🟢
Muvaffaqiyatli unban: {success} ta\n🔴
Xatolik: {failed} ta",
                message.chat.id,
                status_msg.message_id,
            )
        except Exception:
            bot.send_message(message.chat.id,
f"✅ Tugallandi! Muvaffaqiyatli: {success},
xatolik: {failed}")

#
=====
=====

```



```

# PROMO-KODLAR (qoshimchakod8.py "Promo-
kod Yaratish" g'oyasi asosida)
#
=====
=====

@bot.message_handler(commands=
["promo_create"])
def cmd_promo_create(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        bot.send_message(message.chat.id,
"❌ Bu buyruq faqat bot egasi uchun.")
        return
    parts = message.text.split()
    if len(parts) != 6:
        bot.send_message(
            message.chat.id,
            "Foydalanish:
<code>/promo_create <KOD>
<dollar> <diamond> <coin>
<max_ishlatish></code>\n"
            "Masalan: <code>/promo_create
BAYRAM2026 500 10 5 100</code>",
        )
        return
    _, code, dollar_s, diamond_s, coin_s,
max_uses_s = parts
    if not all(p.lstrip("-").isdigit() for
p in (dollar_s, diamond_s, coin_s,
max_uses_s)):
        bot.send_message(message.chat.id,
"❌ Miqdorlar butun son bo'lishi kerak.")

```

```

        return
        code = code.upper()
        with db_lock:
            cur.execute(
                "INSERT OR REPLACE INTO
promo_codes (code, dollar, diamond, coin,
max_uses, used_count) VALUES
(?,?,?,?,?,0)",
                (code, int(dollar_s),
int(diamond_s), int(coin_s),
int(max_uses_s)),
            )
            conn.commit()
            bot.send_message(
                message.chat.id,
                f"✅ Promo-kod yaratildi: <code>
{code}</code>\n"
                f"💵 {dollar_s}$ | 💎 {diamond_s} |
👛 {coin_s} | 👥 Ishlatish limiti:
{max_uses_s}",
            )

@bot.message_handler(commands=
["promo_yarat"])
def cmd_promo_personal(message):
    """🎁 Eng faol o'yinchilar uchun
shaxsiylashtirilgan promo-kod (ism/nik
asosida).
    Kimdir shu kodni ishlatsa, kod egasiga
+$10 bonus tushadi (referral tizimi)."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):

```

```

        bot.send_message(message.chat.id,
        "🚫 Bu buyruq faqat bot egasi uchun.")
        return

        if message.chat.type not in ("group",
        "supergroup") or not
        message.reply_to_message:
            bot.send_message(message.chat.id,
            "❌ Promo-kod bermoqchi bo'lgan
            o'yinchining xabariga reply qilib, kodni
            yozing.")
            return

            parts = message.text.split()
            if len(parts) != 2:
                bot.send_message(message.chat.id,
                "Foydalanish: <code>/promo_yarat KOD</code>
                (o'yinchining xabariga reply qiling)")
                return

                code = parts[1].upper()
                target =
                message.reply_to_message.from_user
                user_dict(target.id, target.first_name)
                with db_lock:
                    cur.execute(
                        "INSERT OR REPLACE INTO
                        promo_codes (code, dollar, diamond, coin,
                        max_uses, used_count, owner_id) "
                        "VALUES (?,20,0,0,100000,0,?)",
                        (code, target.id),
                    )
                    conn.commit()
                    bot.send_message(
                        message.chat.id,
                        f"✅ Shaxsiy promo-kod yaratildi:
                        <code>{code}</code> – egasi:

```

```

{mention(target.id, target.first_name)}\n"
        f"👥 Har bir ishlatilganda:
foydalanuvchiga +$20, {target.first_name}ga
+$10 bonus.",
    )
    safe_send(target.id, f"🎁 Sizga shaxsiy
promo-kod berildi: <code>{code}</code>! Uni
do'stlaringizga tarqating – har bir
ishlatilishi sizga +$10 olib keladi.")

```

```

@bot.message_handler(commands=["promo"])
def cmd_promo_redeem(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    uid = message.from_user.id
    if is_banned(uid):
        return
    user_dict(uid,
message.from_user.first_name)
    parts = message.text.split()
    if len(parts) != 2:
        bot.send_message(message.chat.id,
"Foydalanish: <code>/promo <KOD>
</code>")
        return
    code = parts[1].upper()
    with db_lock:
        cur.execute("SELECT dollar,
diamond, coin, max_uses, used_count,
owner_id FROM promo_codes WHERE code=?",
(code,))
        row = cur.fetchone()
        if not row:

```

```

bot.send_message(message.chat.id, "❌
Bunday promo-kod topilmadi.")
    return
    dollar, diamond, coin, max_uses,
used_count, owner_id = row
    cur.execute("SELECT 1 FROM
promo_redemptions WHERE code=? AND
user_id=?", (code, uid))
    if cur.fetchone():

bot.send_message(message.chat.id, "❌ Siz
bu promo-kodni allaqachon ishlatgansiz.")
    return
    if used_count >= max_uses:

bot.send_message(message.chat.id, "❌ Bu
promo-kodning ishlatish limiti tugagan.")
    return
    if owner_id == uid:

bot.send_message(message.chat.id, "❌
O'zingizning promo-kodingizni ishlata
olmaysiz.")
    return
    cur.execute("INSERT INTO
promo_redemptions (code, user_id) VALUES
(?,?)", (code, uid))
    cur.execute("UPDATE promo_codes SET
used_count=used_count+1 WHERE code=?",
(code,))
    conn.commit()
    add_balance(uid, dollar=dollar,
diamond=diamond, coin=coin)

```

```

        extra_note = ""
        if owner_id:
            add_balance(owner_id, dollar=10)
            extra_note = "\n\n🎁 Kod egasiga
+$10 referral bonusu yuborildi."
            safe_send(owner_id, f"🎁 Sizning
promo-kodingizdan foydalanildi – +$10 bonus
tushdi!")
            bot.send_message(
                message.chat.id,
                f"🎁 <b>Promo-kod muvaffaqiyatli
ishlatildi!</b>\n💰 +{dollar}$ 💎 +
{diamond} 🪙 +{coin}{extra_note}",
                )

#
=====
=====
# SOVG'A TARQATISH / GIVEAWAY – /tarqatish
# (qoshimchakod6.py g'oyasi asosida,
aiogram'dan telebot'ga moslashtirildi)
#
=====
=====

GIVEAWAYS = {}
GIVEAWAY_CURRENCY_ICON = {"dollar": "💰",
"diamond": "💎", "coin": "🪙"}

@bot.message_handler(commands=
["tarqatish"])
@bot.channel_post_handler(commands=

```

```

["tarqatish"])
def cmd_tarqatish(message):
    # Diamond/dollar/coin tarqatish huquqi
    FAQAT bot yaratuvchisiga tegishli –
    # guruh admini yoki vaqtinchalik admin
    buyumi bu buyruqqa yetarli emas.
    if is_owner_channel(message.chat):
        pass # tasdiqlangan owner
    kanalidan – ruxsat berilgan
    else:

    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not
    is_owner(message.from_user.id):

    bot.send_message(message.chat.id, "🚫 Bu
    buyruqni faqat bot yaratuvchisi ishlatishi
    mumkin.")

    return
    parts = message.text.split()
    if len(parts) != 4 or parts[1] not in
    GIVEAWAY_CURRENCY_ICON or not
    parts[2].isdigit() or not
    parts[3].isdigit():
        bot.send_message(
            message.chat.id,
            "Foydalanish: <code>/tarqatish
            &lt;dollar|diamond|coin&gt;
            &lt;har_biriga&gt; &lt;necha_kishiga&gt;
            </code>\n"
            "Masalan: <code>/tarqatish
            diamond 5 10</code> – 10 kishiga 5 tadan
            olmos.",

```

```

        )
        return
        currency, per_person, people_count =
parts[1], int(parts[2]), int(parts[3])
        chat_id = message.chat.id
        icon = GIVEAWAY_CURRENCY_ICON[currency]

        kb = types.InlineKeyboardMarkup()
        kb.add(types.InlineKeyboardButton(f"
{icon} {per_person} {currency} olish",
callback_data=f"gw|{chat_id}"))
        sent = bot.send_message(
            chat_id,
            f"🎁 <b>SOVG'A TARQATISH BOSHLANDI!
</b>\n\n"
            f"Har bir ishtirokchiga: {icon} <b>
{per_person} {currency}</b>\n"
            f"Jami: <b>{people_count}</b>
kishiga yetadi.\n\n"
            f"👉 Tez bo'ling, tugmani bosing!",
            reply_markup=kb,
        )
        GIVEAWAYS[chat_id] = {
            "currency": currency,
            "per_person": per_person,
            "remaining": people_count,
            "claimed": set(),
            "message_id": sent.message_id,
        }

@bot.callback_query_handler(func=lambda c:
c.data.startswith("gw|"))
def cb_giveaway(call):

```



```

maybe_capture_owner(call.from_user)
_, chat_id_s = call.data.split("|")
chat_id = int(chat_id_s)
gw = GIVEAWAYS.get(chat_id)
uid = call.from_user.id

if not gw:
    bot.answer_callback_query(call.id,
    🎉 Tarqatish yakunlangan.")
    return
    if uid in gw["claimed"]:
        bot.answer_callback_query(call.id,
        ❌ Siz allaqachon oldingiz!",
        show_alert=True)
        return
        if gw["remaining"] <= 0:
            bot.answer_callback_query(call.id,
            😞 Afsuski, hammasi tugadi.",
            show_alert=True)
            return

    user_dict(uid,
    call.from_user.first_name)
    add_balance(uid, **{gw["currency"]:
    gw["per_person"]})
    gw["claimed"].add(uid)
    gw["remaining"] -= 1
    icon =
    GIVEAWAY_CURRENCY_ICON[gw["currency"]]
    bot.answer_callback_query(call.id, f"🎉
    Siz {icon} {gw['per_person']}
    {gw['currency']} yutib oldingiz!",
    show_alert=True)

```

```

if gw["remaining"] <= 0:
    try:
        bot.edit_message_text(
            f"🎉 <b>SOVG'A TARQATISH
YAKUNLANDI!</b>\n\n"
            f"Barcha {icon} sovg'alar
{len(gw['claimed'])} kishiga tarqatildi.
Rahmat, ishtirok etganlarga!",
            chat_id, gw["message_id"],
        )
    except Exception:
        pass
    GIVEAWAYS.pop(chat_id, None)
else:
    try:
        bot.edit_message_text(
            f"🎉 <b>SOVG'A TARQATISH
DAVOM ETMOQDA!</b>\n\n"
            f"Har bir ishtirokchiga:
{icon} <b>{gw['per_person']}
{gw['currency']}</b>\n"
            f"Qolgan o'rinlar: <b>
{gw['remaining']}</b>\n\n"
            f"👉 Tez bo'ling, tugmani
bo'sing!",
            chat_id, gw["message_id"],

reply_markup=call.message.reply_markup,
        )
    except Exception:
        pass

#

```

```

=====
=====
# /top – reyting (matn buyrug'i sifatida
ham, avval faqat tugma orqali ishlar edi)
#
=====
=====

@bot.message_handler(commands=["top",
"reyting"])
@bot.channel_post_handler(commands=["top",
"reyting"])
def cmd_top(message):
    text, tp = build_top_text()
    kb = _top_page_markup("wins", 0, tp)
    if is_owner_channel(message.chat):
        bot.send_message(message.chat.id,
text, reply_markup=kb)
        return
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if is_banned(message.from_user.id):
        return
    bot.send_message(message.chat.id, text,
reply_markup=kb)

@bot.message_handler(commands=["topalmaz"])
@bot.channel_post_handler(commands=
["topalmaz"])
def cmd_top_diamond(message):
    text, tp = build_top_diamond_text()
    kb = _top_page_markup("diamond", 0, tp)
    if is_owner_channel(message.chat):

```

```
        bot.send_message(message.chat.id,
text, reply_markup=kb)
        return
        maybe_capture_owner(message.from_user)
        safe_delete(message)
        if is_banned(message.from_user.id):
            return
        bot.send_message(message.chat.id, text,
reply_markup=kb)
```

```
@bot.message_handler(commands=
["topdollar"])
@bot.channel_post_handler(commands=
["topdollar"])
def cmd_top_dollar(message):
    text, tp = build_top_dollar_text()
    kb = _top_page_markup("dollar", 0, tp)
    if is_owner_channel(message.chat):
        bot.send_message(message.chat.id,
text, reply_markup=kb)
        return
        maybe_capture_owner(message.from_user)
        safe_delete(message)
        if is_banned(message.from_user.id):
            return
        bot.send_message(message.chat.id, text,
reply_markup=kb)
```

```
@bot.message_handler(commands=["topguruh"])
@bot.channel_post_handler(commands=
["topguruh"])
def cmd_top_groups(message):
```

```

        if is_owner_channel(message.chat):
            bot.send_message(message.chat.id,
build_top_groups_text())
            return
        maybe_capture_owner(message.from_user)
        safe_delete(message)
        if not is_owner(message.from_user.id):
            bot.send_message(message.chat.id,
"🚫 Bu buyruq faqat bot egasi uchun.")
            return
        bot.send_message(message.chat.id,
build_top_groups_text())

#
=====
=====

# /heros
#
=====
=====

@bot.message_handler(commands=["heros"])
def cmd_heros(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    bot.send_message(message.chat.id, ",
".join(ALL_ROLES))

#
=====
=====

# GURUHDAGI ODDIY MATNLARNI BOSHQARISH –

```

TUN/KUN QOIDALARI

```
#
=====

=====

@bot.message_handler(
    func=lambda m: m.chat.type in ("group",
    "supergroup") and not (m.text or
    "").startswith("/"),
    content_types=["text"],
)
def group_text_guard(message):
    chat_id = message.chat.id
    game = GAMES.get(chat_id)
    if game:
        phase = game.get("phase")
        if phase == "night":
            safe_delete(message)
            return
        if phase == "day":
            uid = message.from_user.id
            if uid not in game["players"]:
                safe_delete(message)
                return
            # 🧑 MAXFIY MISSIYA KUZATUVI –
            kunduzgi xabarlar shu yerda hisoblanadi
            track_mission_activity(game,
            uid, message.text or "")
            return

    # 🐾🦅🔗 Jamoaviy va Para o'yin
    rejimlari ENDI alohida tizim emas – ular
    # ham xuddi shu yuqoridagi `game =
    GAMES.get(chat_id)` orqali boshqariladi
```

```

        # (squad_mode/couple_mode oddiy
        GAMES[chat_id] ichida saqlanadi), shuning
        # uchun bu yerda alohida tekshiruv
        shart emas.

def track_mission_activity(game, uid,
text):
    """Butun o'yin davomidagi guruh
    xabarlari asosida maxfiy missiyalarni
    tekshirish
    uchun kerakli statistikani to'playdi
    (birinchi gapiruvchi, xabarlar soni,
    aniq iboralar, ovoz ochilishidan oldin
    gapirganlar)."""
    game.setdefault("msg_count_total", {})
    game["msg_count_total"][uid] =
game["msg_count_total"].get(uid, 0) + 1
    if game.get("ever_first_speaker") is
None:
        game["ever_first_speaker"] = uid
    low = text.lower()
    said = game.setdefault("said_phrases",
{}).setdefault(uid, set())
    if "xayrli tun" in low:
        said.add("xayrli_tun")
    if "men tinch aholiman" in low:
        said.add("men_tinch_aholiman")
    if "men ham shunday" in low:
        said.add("men_ham_shunday")
    if not game.get("voting_open"):

game.setdefault("spoke_before_vote_today",
set()).add(uid)

```

```

def check_mission_completed(game, uid,
mission_key):
    """Har bir missiya turi uchun
    to'plangan statistika asosida bajarilgan-
    bajarilmaganini tekshiradi."""
    if mission_key == "first_speaker":
        return
    game.get("ever_first_speaker") == uid
    if mission_key == "vote_skip":
        return uid in
    game.get("skip_vote_ever", set())
    if mission_key == "self_vote":
        return uid in
    game.get("self_vote_ever", set())
    if mission_key == "say_xayrli_tun":
        return "xayrli_tun" in
    game.get("said_phrases", {}).get(uid,
    set())
    if mission_key == "talk_atleast_once":
        return game.get("msg_count_total",
    {}).get(uid, 0) >= 1
    if mission_key == "first_voter":
        return uid in
    game.get("first_voter_ever", set())
    if mission_key == "last_voter":
        return uid in
    game.get("last_voter_ever", set())
    if mission_key == "never_say_tinch":
        return "men_tinch_aholiman" not in
    game.get("said_phrases", {}).get(uid,
    set())
    if mission_key ==

```



```

"vote_against_mafia_kill":
    return uid in
game.get("anti_mafia_vote_ever", set())
    if mission_key == "active_5msg":
        return game.get("msg_count_total",
{}).get(uid, 0) >= 5
    if mission_key == "say_men_ham":
        return "men_ham_shunday" in
game.get("said_phrases", {}).get(uid,
set())
    if mission_key == "silent_until_vote":
        return uid in
game.get("silent_before_vote_ever", set())
    if mission_key == "vote_majority":
        return uid in
game.get("majority_vote_ever", set())
    if mission_key == "max3_msg":
        return game.get("msg_count_total",
{}).get(uid, 0) <= 3
    if mission_key == "survive_night":
        return game["players"].get(uid,
{}).get("alive", False)
    return False

#
=====
=====
# 🧨 HUNTER ELITE – a'zolik (tarifli),
shaxsiy laqab, til sozlamalari,
# olmos sovg'a qilish tizimi.
#
# (Almex Black Bot'da ko'rilgan "PRO
obuna", "Til tanlash", "Laqab tasdiqlash

```

```

# ovoz berishi" va "Birovga olmos sovg'a
qilish" funksiyalaridan ilhomlanib,
# Hunter Mafia botiga moslab, MAVJUD
infratuzilma ustiga – charges JSON'i,
# add_balance, Telegram Stars invoice
tizimi – qurilgan. Yangi DB ustuni
# TALAB QILINMAYDI: hammasi allaqachon
mavjud "charges" ustunida saqlanadi,
# shuning uchun eski foydalanuvchilarning
hech qanday ma'lumoti yo'qolmaydi.
#
# ESLATMA: botning asosiy interfeysi
(menyular, o'yin matnlari) o'zbek tilida
# qoladi – /til orqali tanlangan til faqat
ELITE, laqab va sovg'a bo'limining
# shaxsiy tasdiqlash xabarlarida
ishlatiladi (pastda ochiq yozilgan). Bu –
soxta
# "to'liq tarjima" va'da qilmaslik uchun
ataylab shunday cheklangan.)
#
=====
=====

ELITE_PLANS = [
    # {kun: (necha kunlik obuna), diamond:
    (Olmos narxi), stars: (Telegram Stars
    narxi)}
    # 🛠️ YANGILANDI: 1 hafta = 100🌟/40💎
    dan boshlanadi, 3 oygacha (uzoq muddat
    # olganda foizli chegirma bilan) sotib
    olish mumkin.
    {"days": 7, "diamond": 40, "stars":
    100}, # 1 hafta

```

```

        {"days": 15, "diamond": 70, "stars":
180},    # 15 kun
        {"days": 30, "diamond": 130, "stars":
320},    # 1 oy
        {"days": 60, "diamond": 230, "stars":
580},    # 2 oy
        {"days": 90, "diamond": 320, "stars":
800},    # 3 oy (eng katta chegirma)
    ]

```

```

_ELITE_PLANS_DEFAULT = [dict(p) for p in
ELITE_PLANS] # 🛠️ QULAYLIK: "standartga
qaytarish" tugmasi uchun asl nusxa

```

```

def _load_elite_plans_from_settings():
    """🛠️ QULAYLIK: bot ishga tushganda,
    agar owner avval Admin panel orqali
    ELITE narxlarini o'zgartirgan bo'lsa
    (bot_settings jadvalida saqlangan),
    o'sha narxlar kod ichidagi standart
    narxlar o'rniga ishlatiladi. Shu
    tufayli owner narxni bir marta panel
    orqali o'zgartirsa, bot qayta
    ishga tushirilganda ham (masalan
    /tiklash yoki qayta deploy qilinganda
    ham) o'zgartirilgan narx SAQLANIB
    QOLADI – kodni qayta yozish shart emas."""
    global ELITE_PLANS
    try:
        raw =
get_setting("elite_plans_json")
        if not raw:
            return

```

```

        data = json.loads(raw)
        if isinstance(data, list) and data
and all(
            isinstance(p, dict) and
{"days", "diamond", "stars"} <=
set(p.keys()) for p in data
        ):
            ELITE_PLANS = data
        except Exception:
            pass # xato bo'lsa ham standart
narxlar bilan davom etadi – bot hech qachon
shu sabab qotib qolmaydi

def _save_elite_plans():
    """Joriy ELITE_PLANS ro'yxatini bazaga
(bot_settings) yozib qo'yadi – shundan
    keyin bot qayta ishga tushsa ham owner
belgilagan narx saqlanib qoladi."""
    try:
        set_setting("elite_plans_json",
json.dumps(ELITE_PLANS,
ensure_ascii=False))
    except Exception:
        pass

_load_elite_plans_from_settings()

LANG_LIST = [
    ("tr", "🇹🇷 Türkçe"),
    ("en", "🇺🇸 English"),
    ("ru", "🇷🇺 Русский"),
    ("uk", "🇺🇦 Українська"),

```

```
( "kk", "🇰🇿 Қазақша"),
( "uz", "🇺🇿 O'zbekcha"),
( "id", "🇮🇩 Bhasa Indonesia"),
]

LANG_STRINGS = {
    "lang_set": {
        "tr": "✅ Dil başarıyla
değiştirildi!",
        "en": "✅ Language changed
successfully!",
        "ru": "✅ Язык успешно изменён!",
        "uk": "✅ Мову успішно змінено!",
        "kk": "✅ Тіл сәтті өзгертілді!",
        "uz": "✅ Til muvaffaqiyatli
o'zgartirildi!",
        "id": "✅ Bahasa berhasil diubah!",
    },
    "nickname_ok": {
        "tr": "✅ Takma adınız onaylandı ve
ayarlandı!",
        "en": "✅ Your nickname has been
approved and set!",
        "ru": "✅ Ваш никнейм одобрен и
установлен!",
        "uk": "✅ Ваш нікнейм схвалено та
встановлено!",
        "kk": "✅ Лақап атыңыз мақұлданды
және орнатылды!",
        "uz": "✅ Laqabingiz tasdiqlandi va
o'rnatildi!",
        "id": "✅ Nama panggilan Anda telah
disetujui dan diatur!",
    },
}
```

```
"gift_sent": {
    "tr": "📁 Hediye başarıyla
gönderildi!",
    "en": "📁 Gift sent successfully!",
    "ru": "📁 Подарок успешно
отправлен!",
    "uk": "📁 Подарунок успішно
надіслано!",
    "kk": "📁 Сыйлық сәтті жіберілді!",
    "uz": "📁 Sovg'a muvaffaqiyatli
yuborildi!",
    "id": "📁 Hadiah berhasil
dikirim!",
    },
}
```

```
def T(uid, key):
    """Foydalanuvchi tanlagan tilda (agar
shu kalit uchun tarjima bo'lsa) matn
qaytaradi,
    aks holda standart o'zbekcha variantga
qaytadi (hech qachon xato bermaydi)."""
    lang = get_lang(uid)
    table = LANG_STRINGS.get(key, {})
    return table.get(lang) or
table.get("uz") or ""
```

```
def get_lang(uid):
    ch = get_charges(uid)
    return ch.get("lang", "uz")
```

```

def set_lang(uid, code):
    set_charge_value(uid, "lang", code)

def get_nickname(uid):
    ch = get_charges(uid)
    return (ch.get("nickname") or
    "").strip()

def set_nickname(uid, nickname):
    set_charge_value(uid, "nickname",
    nickname.strip()[:32])

def is_elite(uid):
    ch = get_charges(uid)
    until = ch.get("vip_until", 0)
    return bool(until) and until >
    time.time()

def elite_days_left(uid):
    ch = get_charges(uid)
    until = ch.get("vip_until", 0)
    if not until or until <= time.time():
        return 0
    return max(0, int((until - time.time())
    // 86400) + 1)

def grant_elite_days(uid, days):
    """Yangi ELITE kunlarni qo'shadi – agar
    hozir ham faol ELITE bo'lsa, qolgan

```

```
    muddat ustiga QO'SHILADI (ya'ni 15 kun  
qolganida yana 30 kun sotib olsa, 45 kun  
bo'ladi),
```

```
    aks holda hozirdan boshlab hisoblanadi.  
Yangi umumiy tugash vaqtini (unix)  
qaytaradi."""
```

```
    ch = get_charges(uid)  
    current_until = ch.get("vip_until", 0)  
    base = current_until if current_until  
and current_until > time.time() else  
time.time()  
    new_until = base + days * 86400  
    set_charge_value(uid, "vip_until",  
new_until)  
    return new_until
```

```
def elite_status_line(uid):  
    if is_elite(uid):  
        nick = get_nickname(uid)  
        nick_part = f" | 🏆 Laqab: {nick}"  
    if nick else ""  
        return f"Elite 🏆 <b>HUNTER ELITE  
faol</b> – {elite_days_left(uid)} kun  
qoldi{nick_part}"  
    return "🏆 HUNTER ELITE: faol emas –  
/elite orqali oling"
```

```
ELITE_STYLED_WORD = "Elite" # 🔧 YANGI:  
maxsus (kursiv-kalligrafik) shriftdagi  
"Elite" so'zi, emojidan OLDIN yoziladi
```



```

def elite_success_text(days, until):
    return (
        f"🎉 {ELITE_STYLED_WORD} 🏆\n\n"
        <b>TABRIKLAYMIZ! HUNTER ELITE\n\n"
        FAOLLASHTIRILDI!</b> 🏆 {ELITE_STYLED_WORD}\n\n"
        f"🕒 Qo'shilgan muddat: <b>{_elite_days_label(days)}</b>\n\n"
        f"📅 Amal qilish muddati: <b>{time.strftime('%d.%m.%Y',\n\n"
        time.localtime(until))}</b> gacha\n\n"
        "🌟 Endi sizga ochiq:\n\n"
        f"• {ELITE_STYLED_WORD} 🏆 Ismingiz\n\n"
        yonida oltin ELITE nishoni\n\n"
        "• 🏷️ Shaxsiy laqab (/taxallus)\n\n"
        "• 🎟️ O'yin lobbysidan istalgan\n\n"
        payt chiqish huquqi\n\n"
        "• 💎 Kunlik ELITE Sirli Sandiq\n\n"
        (/elite_sandiq)\n\n"
        "• 👁️ Kengaytirilgan profil va\n\n"
        reytingdagi maxsus ko'rinish\n\n"
        "Rahmat! 💎"\n\n"
    )

def _elite_days_label(d):
    """Kunlar sonini o'qish oson formatga
    o'giradi: 7->'1 hafta', 30->'1 oy' va
    h.k."""
    if d == 7:
        return "1 hafta"
    if d % 30 == 0:
        months = d // 30
        return f"{months} oy" if months > 1

```

```

else "1 oy"
    return f"{d} kun"

def open_elite_menu(chat_id, uid):
    kb =
types.InlineKeyboardMarkup(row_width=1)
    for plan in ELITE_PLANS:
        d = plan["days"]
        label = _elite_days_label(d)
        kb.add(types.InlineKeyboardButton(
            f"★ {label} – {plan['stars']}"
Stars",
            callback_data=f"elitebuy|
{d}|stars",
        ))
        kb.add(types.InlineKeyboardButton(
            f"💎 {label} –
{plan['diamond']}] Olmos",
            callback_data=f"elitebuy|
{d}|diamond",
        ))
        status = elite_status_line(uid)
        bot.send_message(
            chat_id,
            "Elite 🏰👑👑 <b>HUNTER ELITE
A'ZOLIGI</b> 👑🏰\n"
            "—————\n"
            f"{status}\n\n"
            "🏰 ELITE sizga quyidagilarni
beradi:\n"
            "• ★ Ism yonida oltin ELITE
nishoni\n"
            "• 🏷 Shaxsiy laqab o'rnatish –

```

```

/taxallus &lt;laqab&gt;\n"
    "• 🏢 Lobbydan istalgan payt
chiqish – /chiqish\n"
    "• 📺 Olmos sovg'a qilish
imkoniyati – /sovga\n"
    "• 💎 Kunlik ELITE Sirli Sandiq –
/elite_sandiq\n"
    "• 👑 Reyting va profilda maxsus
(oltin) ko'rinish\n\n"
    "🇺🇦 <b>1 haftalikdan 3 oygacha</b>
– o'zingizga qulay muddatni tanlang.\n"
    "Uzoqroq muddat olsangiz –
<b>foizli chegirma</b> avtomatik
qo'llanadi!\n"
    "★ Telegram Stars orqali
(100★dan) yoki 💎 Olmos orqali (40💎dan)
to'lang:",
    reply_markup=with_back_button(kb),
)

```

```

@bot.message_handler(commands=["elite"])
def cmd_elite(message):
    """👑 HUNTER ELITE menyusini ochadi.
    To'liq try/except bilan himoyalangan –
    hech qanday holatda bot "javobsiz
    qolib" ketmaydi. Xato yuz bersa, ANIQ
    xato matni endi bot egasiga Telegram
    orqali yuboriladi (notify_owner_of_error)
    – shu orqali sababi darhol ma'lum
    bo'ladi, log fayl kerak bo'lmaydi."""
    try:

maybe_capture_owner(message.from_user)

```

```

        safe_delete(message)
        open_elite_menu(message.chat.id,
message.from_user.id)
    except Exception as e:
        notify_owner_of_error("cmd_elite
(/elite buyrug'i)", e)
    try:

bot.send_message(message.chat.id, "⚠ ELITE
menyusini ochishda xatolik yuz berdi.
Qaytadan urinib ko'ring: /elite")
    except Exception:
        pass

@bot.callback_query_handler(func=lambda c:
c.data.startswith("elitebuy|"))
def cb_elite_buy(call):
    """🔥 HUNTER ELITE sotib olish. 🔧
TUZATILDI: avval bu funksiyada umumiy
try/except YO'Q edi – agar biror joyda
kutilmagan xatolik chiqsa (masalan
DB bilan bog'liq), Telegram tugmani
"bosilgan" deb belgilamas edi va
foydalanuvchiga HECH QANDAY javob
ko'rinmas edi (xuddi bot "javob
bermayapti"gandek tuyulardi). Endi har
qanday holatda ham foydalanuvchiga
aniq javob (muvaffaqiyat yoki xatolik
xabari) ko'rsatiladi."""
    try:
        maybe_capture_owner(call.from_user)
        uid = call.from_user.id
        parts = call.data.split("|")

```

```

        if len(parts) != 3:

bot.answer_callback_query(call.id, "⚠️
Noto'g'ri so'rov, qaytadan /elite deb
urinib ko'ring.", show_alert=True)
        return
        _, days_s, currency = parts
        try:
            days = int(days_s)
        except ValueError:

bot.answer_callback_query(call.id, "⚠️
Noto'g'ri tarif.", show_alert=True)
        return

        plan = next((p for p in ELITE_PLANS
if p["days"] == days), None)
        if not plan:

bot.answer_callback_query(call.id, "❌ Bu
tarif topilmadi. Yangi menyu uchun /elite
deb yozing.", show_alert=True)
        return

        if currency == "diamond":
            price = plan["diamond"]
            u = user_dict(uid,
call.from_user.first_name)
            if u["diamond"] < price:
                bot.answer_callback_query(
                    call.id,
                    f"❌ Olmosingiz yetarli
emas! Kerak: {price} 💎, sizda:
{u['diamond']} 💎.\n"

```

```

        f"💎 Olmos sotib olish
uchun: /almazdokon",
        show_alert=True,
    )
    return
    add_balance(uid, diamond=-
price)
    new_until =
grant_elite_days(uid, days)

bot.answer_callback_query(call.id, "✅
HUNTER ELITE faollashtirildi!",
show_alert=True)

bot.send_message(call.message.chat.id,
elite_success_text(days, new_until))

    elif currency == "stars":
        price = plan["stars"]
        try:
            bot.send_invoice(
                call.message.chat.id,
                title=f"🔥 HUNTER ELITE
({_elite_days_label(days)})",
                description=f"
{_elite_days_label(days)} HUNTER ELITE
obunasi ({price} ★ Stars)",

            invoice_payload=f"elitepay_{uid}_{days}",
                provider_token="", #
            Telegram Stars uchun bo'sh qoldiriladi
                currency="XTR",
                prices=
            [types.LabeledPrice(label=f"HUNTER ELITE

```

```

({_elite_days_label(days)}})",
amount=price)],
    )

bot.answer_callback_query(call.id)
    except Exception as inv_err:

_logger.warning("send_invoice xatolik
(elite/stars): %s", inv_err)
        bot.answer_callback_query(
            call.id,
            "❌ To'lov tizimida
xatolik. Bu ko'pincha botda Telegram Stars
to'lovlari "

            "yoqilmagan bo'lsa yuz
beradi – bot egasi @BotFather'da
to'lovlarni tekshirsin.",
            show_alert=True,
        )
    else:

bot.answer_callback_query(call.id, "❌
Noma'lum to'lov turi. Qaytadan /elite deb
urinib ko'ring.", show_alert=True)
    except Exception as e:
        _logger.warning("cb_elite_buy
xatolik: %s", e)
        try:

bot.answer_callback_query(call.id, "⚠️
Kutilmagan xatolik yuz berdi. Qaytadan
/elite deb urinib ko'ring.",
show_alert=True)
        except Exception:

```

pass

```
# -----  
-----  
# 🌐 TIL / LANGUAGE  
# -----  
-----  
  
def open_lang_menu(chat_id, uid):  
    kb =  
    types.InlineKeyboardMarkup(row_width=1)  
    for code, label in LANG_LIST:  
        mark = " ✅" if get_lang(uid) ==  
code else ""  
  
    kb.add(types.InlineKeyboardButton(f"{label}  
{mark}", callback_data=f"setlang|{code}"))  
    bot.send_message(  
        chat_id,  
        "🌐 <b>Til / Language  
sozlamalari</b>\n\n"  
        "Tanlangan til shaxsiy ELITE, laqab  
va sovg'a xabarlaringizda ishlatiladi.\n"  
        "Botning asosiy o'yin matnlari  
hozircha o'zbek tilida qoladi.\n\n"  
        "Kerakli tilni tanlang:",  
        reply_markup=with_back_button(kb),  
    )  
  
@bot.message_handler(commands=["til",  
"lang"])  
def cmd_til(message):
```



```
        maybe_capture_owner(message.from_user)
        safe_delete(message)
        open_lang_menu(message.chat.id,
message.from_user.id)
```

```
@bot.callback_query_handler(func=lambda c:
c.data.startswith("setlang|"))
```

```
def cb_set_lang(call):
    maybe_capture_owner(call.from_user)
    uid = call.from_user.id
    code = call.data.split("|")[1]
    if code not in dict(LANG_LIST):
        bot.answer_callback_query(call.id,
"❌ Noma'lum til.", show_alert=True)
        return
    set_lang(uid, code)
    bot.answer_callback_query(call.id,
T(uid, "lang_set"), show_alert=True)
    try:
        bot.edit_message_text(
            f"{T(uid, 'lang_set')}\n\n" +
dict(LANG_LIST)[code],
            call.message.chat.id,
call.message.message_id,
        )
    except Exception:
        pass
```

```
# -----
```

```
# 📌 SHAXSIY LAQAB (taxallus) – faqat
HUNTER ELITE a'zolari uchun.
```

```

#      Guruhda chaqirilsa – Almex Black
Bot'dagidek 👍/👎 tasdiqlash ovoz berishi
#      ochiladi (30 soniya, ko'pchilik
"yoqlab" ovoz bersa tasdiqlanadi).
#      Shaxsiy (DM) chatda chaqirilsa –
auditoriya yo'qligi uchun darhol
o'rnatiladi.
# -----
-----

PENDING_NICKNAMES = {} # vote_id ->
{"uid":, "nickname":, "yes": set(), "no":
set(), "chat_id":, "message_id":}
_NICK_VOTE_SECONDS = 30
_nick_vote_counter = [0]

def _resolve_nickname_vote(vote_id):
    data = PENDING_NICKNAMES.pop(vote_id,
None)
    if not data:
        return
    yes, no = len(data["yes"]),
len(data["no"])
    approved = yes >= no # teng bo'lsa ham
– laqab zararsiz bo'lgani uchun
tasdiqlanadi
    try:
        if approved:
            set_nickname(data["uid"],
data["nickname"])
            result_text = (
                f"✅ <b>Laqab tasdiqlandi!
</b>\n"

```

```

        f"👤 Yangi laqab: <b>
{data['nickname']}</b>\n"
        f"📊 Ovozlar: {yes} 👍 |
{no} 👎"
    )
    else:
        result_text = (
            f"❌ <b>Laqab rad etildi.
</b>\n"
            f"📊 Ovozlar: {yes} 👍 |
{no} 👎"
        )
        bot.edit_message_text(result_text,
data["chat_id"], data["message_id"])
    except Exception:
        pass

@bot.callback_query_handler(func=lambda c:
c.data.startswith("nickvote|"))
def cb_nickname_vote(call):
    maybe_capture_owner(call.from_user)
    _, vote_id_s, choice =
call.data.split("|")
    vote_id = int(vote_id_s)
    data = PENDING_NICKNAMES.get(vote_id)
    if not data:
        bot.answer_callback_query(call.id,
"🔔 Bu ovoz berish tugagan.",
show_alert=True)
    return
    voter = call.from_user.id
    data["yes"].discard(voter)
    data["no"].discard(voter)

```

```

        if choice == "yes":
            data["yes"].add(voter)
        else:
            data["no"].add(voter)
            bot.answer_callback_query(call.id, "✅
Ovozingiz qabul qilindi!")
            try:
                kb =
types.InlineKeyboardMarkup(row_width=2)
                kb.add(
                    types.InlineKeyboardButton(f"👍
{len(data['yes'])}",
callback_data=f"nickvote|{vote_id}|yes"),
                    types.InlineKeyboardButton(f"👎
{len(data['no'])}",
callback_data=f"nickvote|{vote_id}|no"),
                )

            bot.edit_message_reply_markup(data["chat_id
"], data["message_id"], reply_markup=kb)
            except Exception:
                pass

@bot.message_handler(commands=["taxallus",
"nickname"])
def cmd_taxallus(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    uid = message.from_user.id

    if not is_elite(uid):
        bot.send_message(
            message.chat.id,

```

```

        "❌ Bu funksiya faqat 👑
        <b>HUNTER ELITE</b> a'zolari uchun!\n"
        "/elite orqali ELITE a'zolikni
        oling.",
        )
        return

        parts = message.text.split(maxsplit=1)
        if len(parts) < 2 or not
        parts[1].strip():
            bot.send_message(message.chat.id,
            "✎ Foydalanish: <code>/taxallus
            Yangi_Laqabim</code>")
            return

        nickname = parts[1].strip()[:32]

        if message.chat.type == "private":
            set_nickname(uid, nickname)
            bot.send_message(message.chat.id,
            T(uid, "nickname_ok") + f"\n👤 {nickname}")
            return

        # Guruhda – jamoaviy tasdiqlash ovoz
        berishi
        _nick_vote_counter[0] += 1
        vote_id = _nick_vote_counter[0]
        kb =
        types.InlineKeyboardMarkup(row_width=2)
        kb.add(
            types.InlineKeyboardButton("👍 0",
            callback_data=f"nickvote|{vote_id}|yes"),
            types.InlineKeyboardButton("👎 0",
            callback_data=f"nickvote|{vote_id}|no"),

```

```

    )
    sent = bot.send_message(
        message.chat.id,
        f" ? Rostdan ham {mention(uid,
message.from_user.first_name)} uchun\n"
        f" 👤 yangi laqab: <b>{nickname}</b>
- o'rnatilishini xohlaysizmi?\n\n"
        f" 🕒 Tasdiqlash uchun vaqt:
{_NICK_VOTE_SECONDS} soniya",
        reply_markup=kb,
    )
    PENDING_NICKNAMES[vote_id] = {
        "uid": uid, "nickname": nickname,
        "yes": set(), "no": set(),
        "chat_id": message.chat.id,
        "message_id": sent.message_id,
    }
    t = threading.Timer(_NICK_VOTE_SECONDS,
lambda: _resolve_nickname_vote(vote_id))
    t.daemon = True
    t.start()

# -----
# -----
# 🎁 OLMOS SOVG'A QILISH – /sovga
# Ishlatish: kimningdir xabariga REPLY
qilib /sovga <miqdor>
# yoki
reply'siz: /sovga
<user_id> <miqdor>
# -----
# -----

```

```

def user_exists(uid):
    with db_lock:
        cur.execute("SELECT 1 FROM users
WHERE user_id=?", (uid,))
        return cur.fetchone() is not None

@bot.message_handler(commands=["sovga",
"gift"])
def cmd_sovga(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    sender_id = message.from_user.id
    parts = message.text.split()

    target_id = None
    target_name = None

    if message.reply_to_message and
len(parts) == 2:
        target_id =
message.reply_to_message.from_user.id
        target_name =
message.reply_to_message.from_user.first_na
me
        amount_s = parts[1]
    elif len(parts) == 3:
        if not parts[1].lstrip("-
").isdigit():

bot.send_message(message.chat.id, "❌
Foydalanuvchi ID raqam bo'lishi kerak.")
        return
        target_id = int(parts[1])

```

```

        amount_s = parts[2]
    else:
        bot.send_message(
            message.chat.id,
            "📺 <b>Olmos sovg'a
qilish</b>\n\n"
            "Foydalanish:\n"
            "• Kimningdir xabariga REPLY
qilib: <code>/sovg'a <miqdor>
</code>\n"
            "• Yoki to'g'ridan-to'g'ri:
<code>/sovg'a <Telegram_ID>
<miqdor></code>\n\n"
            "❗ Qabul qiluvchi avval botga
kamida bir marta <code>/start</code> bosgan
bo'lishi kerak.",
        )
        return

    if target_id == sender_id:
        bot.send_message(message.chat.id,
            "❌ O'zingizga sovg'a qila olmaysiz 😊")
        return

    try:
        amount = int(amount_s)
    except ValueError:
        bot.send_message(message.chat.id,
            "❌ Miqdor butun son bo'lishi kerak.")
        return

    if amount <= 0:
        bot.send_message(message.chat.id,
            "❌ Miqdor musbat bo'lishi kerak.")
        return

```



```

        if target_name:
            user_dict(target_id, target_name)
# reply orqali kelgan – mavjud emas bo'lsa
ro'yxatdan o'tkazamiz
            elif not user_exists(target_id):
                bot.send_message(message.chat.id,
                "❌ Bu foydalanuvchi hali botdan
                foydalanmagan (avval botga /start bosishi
                kerak).")
                return

            sender = user_dict(sender_id,
            message.from_user.first_name)
            if sender["diamond"] < amount:
                bot.send_message(message.chat.id,
                f"❌ Olmosingiz yetarli emas! Sizda:
                {sender['diamond']} 💎")
                return

            add_balance(sender_id, diamond=-amount)
            add_balance(target_id, diamond=amount)

            target_row = user_dict(target_id)
            bot.send_message(
                message.chat.id,
                T(sender_id, "gift_sent") +
                f"\n{mention(sender_id,
                message.from_user.first_name)} ➔ "
                f"{mention(target_id,
                target_row['name'])}: <b>{amount} 💎</b>",
                )
            safe_send(target_id, f"🎁 Sizga
            {mention(sender_id,

```

```
message.from_user.first_name)) tomonidan  
<b>{amount} 💎</b> Olmos sovg'a qilindi!")
```

```
# -----  
-----  
# 🏠 /chiqish – HUNTER ELITE a'zolari  
uchun lobbydan istalgan payt chiqish huquqi  
# (Almex Black Bot'dagi PRO-only /leave  
bilan bir xil mantiq)  
# -----  
-----
```

```
@bot.message_handler(commands=["chiqish"])  
def cmd_chiqish(message):  
    maybe_capture_owner(message.from_user)  
    safe_delete(message)  
    uid = message.from_user.id  
    chat_id = message.chat.id  
    game = GAMES.get(chat_id)  
  
    if not game or game["phase"] !=  
    "waiting" or uid not in game["players"]:  
        bot.send_message(chat_id, "❌ Siz  
hozir chiqib bo'ladigan faol lobbyda  
emassiz.")  
        return  
  
    if not is_elite(uid):  
        bot.send_message(  
            chat_id,  
            "❌ Lobbydan chiqish faqat 👑  
<b>HUNTER ELITE</b> a'zolari uchun!\n"  
            "/elite orqali ELITE a'zolikni
```

```

oling.",
    )
    return

    del game["players"][uid]
    if game.get("join_msg_id"):
        try:

bot.edit_message_text(build_join_text(game)
, chat_id, game["join_msg_id"],
reply_markup=build_join_markup(chat_id,
game))
        except Exception:
            pass
            bot.send_message(chat_id, f"👤
{mention(uid,
message.from_user.first_name)} lobbydan
chiqdi (🔥 ELITE huquqi).")

# -----
-----
# 📄 DOLLAR DO'KONI – Olmosga o'yin-ichi
Dollar sotib olish
# (Almex Black Bot'dagi "Dollar sotib
olish uchun variantni tanlang" bilan
# bir xil paket tuzilishi, sizning
Olmos/Dollar balansingizga moslashtirilgan)
# -----
-----

DOLLAR_PACKAGES = [
    {"dollar": 300, "diamond": 1},
    {"dollar": 600, "diamond": 2},

```

```

        {"dollar": 800, "diamond": 3},
        {"dollar": 1500, "diamond": 4},
        {"dollar": 5000, "diamond": 15},
        {"dollar": 10000, "diamond": 30},
    ]

def open_dollar_shop(chat_id, uid):
    kb =
types.InlineKeyboardMarkup(row_width=2)
    buttons = [
        types.InlineKeyboardButton(f"
{p['dollar']}💵 – {p['diamond']}💎",
callback_data=f"buydollar|{p['diamond']}")
        for p in DOLLAR_PACKAGES
    ]
    for i in range(0, len(buttons), 2):
        kb.add(*buttons[i:i + 2])
    u = user_dict(uid)
    bot.send_message(
        chat_id,
        "💵 <b>DOLLAR DO'KONI</b>\n"
        "—————\n"
        f"💎 Sizda: {u['diamond']}
Olmos\n\n"
        "Olmosga o'yin-ichi Dollar sotib
olish uchun paketni tanlang:",
        reply_markup=with_back_button(kb),
    )

@bot.message_handler(commands=
["dollar_dokon"])
def cmd_dollar_dokon(message):

```

```

        maybe_capture_owner(message.from_user)
        safe_delete(message)
        open_dollar_shop(message.chat.id,
message.from_user.id)

@bot.callback_query_handler(func=lambda c:
c.data.startswith("buydollar|"))
def cb_buy_dollar(call):
    maybe_capture_owner(call.from_user)
    uid = call.from_user.id
    diamond_cost = int(call.data.split("|")
[1])
    pkg = next((p for p in DOLLAR_PACKAGES
if p["diamond"] == diamond_cost), None)
    if not pkg:
        bot.answer_callback_query(call.id,
"❌ Bu paket topilmadi.", show_alert=True)
        return
    u = user_dict(uid,
call.from_user.first_name)
    if u["diamond"] < diamond_cost:
        bot.answer_callback_query(
            call.id, f"❌ Olmosingiz
yetarli emas! Kerak: {diamond_cost} 💎,
sizda: {u['diamond']} 💎.",
            show_alert=True,
        )
        return
    add_balance(uid, diamond=-diamond_cost,
dollar=pkg["dollar"])
    bot.answer_callback_query(call.id, "✅
Xarid muvaffaqiyatli!", show_alert=True)
    try:

```

```

        bot.edit_message_text(
            f"$👉 <b>Xarid bajarildi!
</b>\n\n"
            f"▬ {diamond_cost} 💎 Olmos
sarflandi.\n"
            f"✚ Hisobingizga <b>
{pkg['dollar']}</b> 🇺🇸 Dollar qo'shildi!",
            call.message.chat.id,
            call.message.message_id,
        )
    except Exception:
        pass

# -----
# -----
# 💎 ↔ 🪙 OLMOS ↔ ALMEX-COIN QAT'IY KURSDA
AYIRBOSHLASH (2 💎 = 1 🪙)
# (Almex Black Bot'dagi "Olmos → Almex
Coin, Kurs: 2 💎 = 1" bilan bir xil –
# sizning botingizdagi mavjud
"coin→diamond, tasodifiy kurs"
ayirboshlashdan
# FARQLI – bu ANIQ, DOIMIY 2:1 kursda,
TESKARI yo'nalishda ishlaydi)
# -----
# -----

DIAMOND_TO_COIN_RATE = 2 # 2 💎 = 1 🪙
DIAMOND_TO_COIN_PRESETS = [10, 20, 50, 100,
200, 500]

#

```

```

=====
=====
# 🛠️ QULAYLIK: "Bot sozlamalari" paneli –
# 10 xil o'yin parametrini
# KOD YOZMASDAN, botning o'zidan, tugmalar
# orqali o'zgartirish.
#
# Har bir sozlama shu modulning global
# o'zgaruvchisi (masalan MIN_PLAYERS).
# Owner yangi qiymat yuborganda globals()
# [nom] yangilanadi – shu nom bilan
# ishlaydigan BARCHA funksiyalar (butun
# faylda) DARHOL yangi qiymatni
# ishlatadi (Python global qidiruvi har
# chaqiriqda amalga oshgani uchun).
# Qiymat bazaga ham saqlanadi, shuning
# uchun bot qayta ishga tushsa ham
# o'zgartirilgan sozlama SAQLANIB QOLADI.
#
=====
=====

TUNABLE_SETTINGS = [
    ("MIN_PLAYERS", "🎮 O'yin uchun minimal
    ishtirokchilar soni", int),
    ("NIGHT_SECONDS", "🌙 Tun bosqichi
    davomiyligi (soniya)", int),
    ("DAY_DISCUSSION_SECONDS", "☀️ Kunduzgi
    muhokama vaqti (soniya)", int),
    ("WIN_REWARD", "🏆 G'alaba mukofoti
    ($) ", int),
    ("LOSE_REWARD", "😞
    Ishtirok/mag'lubiyat mukofoti ($) ", int),
    ("DIAMOND_TO_COIN_RATE", "💎➡️👑 Necha

```

```

olmos = 1 Hunter Coin", int),
    ("DIAMOND_STARS_RATE", "💎➡️⭐ 1 olmos
narxi nechta Stars", int),
    ("HC_STAR_RATE", "⭐➡️🏠 Nechta Stars =
1 Hunter Coin", int),
    ("THERON_FREE_DAILY_LIMIT", "🧠 Oddiy
foydalanuvchi uchun AI kunlik limiti",
int),
    ("THERON_ELITE_DAILY_LIMIT", "🧠 ELITE
foydalanuvchi uchun AI kunlik limiti",
int),
]

```

```

_TUNE_EDIT_STATE = {} # owner_id ->
tahrirlanayotgan sozlama nomi (masalan
"MIN_PLAYERS")

```

```

def _load_tunable_settings_from_db():
    """Bot ishga tushganda – owner avval
panel orqali o'zgartirgan sozlamalar
bo'lsa, ularni bazadan o'qib, standart
qiymatlar o'rniga qo'llaydi."""
    for varname, _label, caster in
TUNABLE_SETTINGS:
        try:
            raw =
get_setting(f"tune_{varname}")
            if raw is not None:
                globals()[varname] =
caster(raw)
        except Exception:
            pass # xato bo'lsa ham
standart qiymat bilan davom etadi

```



```

_load_tunable_settings_from_db()

def _bot_settings_panel_text_and_kb():
    kb =
    types.InlineKeyboardMarkup(row_width=1)
    lines = ["⚙️ <b>Bot sozlamalari</b>
(kod yozmasdan o'zgartirish)\n"]
    for varname, label, _caster in
TUNABLE_SETTINGS:
        current = globals().get(varname)
        lines.append(f"• {label}: <b>
{current}</b>")

    kb.add(types.InlineKeyboardButton(f"✎
{label}", callback_data=f"admin|tune_edit|
{varname}"))
    lines.append("\n✎ tugmasini bosib,
yangi (butun) sonni yuboring.")
    return "\n".join(lines), kb

@bot.callback_query_handler(func=lambda c:
c.data == "admin|bot_settings")
def cb_admin_bot_settings(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
"🚫 Ruxsat yo'q.", show_alert=True)
    return
    bot.answer_callback_query(call.id)
    text, kb =

```

```

_bot_settings_panel_text_and_kb()
    bot.send_message(call.message.chat.id,
text, reply_markup=kb)

@bot.callback_query_handler(func=lambda c:
c.data.startswith("admin|tune_edit|"))
def cb_admin_tune_edit(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
"🚫 Ruxsat yo'q.", show_alert=True)
        return
    varname = call.data.split("|", 2)[2]
    entry = next((t for t in
TUNABLE_SETTINGS if t[0] == varname), None)
    if not entry:
        bot.answer_callback_query(call.id,
"❌ Topilmadi.", show_alert=True)
        return
    bot.answer_callback_query(call.id)
    _TUNE_EDIT_STATE[call.from_user.id] =
varname
    bot.send_message(
        call.message.chat.id,
        f"✏️ <b>{entry[1]}</b>\n\nHozirgi
qiymat: <b>{globals().get(varname)}</b>\n"
        f"Yangi (butun) sonni yuboring:",
    )

def _handle_tune_setting_input(message):
    uid = message.from_user.id
    if not is_owner(uid):

```

```

        _TUNE_EDIT_STATE.pop(uid, None)
        return
    varname = _TUNE_EDIT_STATE.get(uid)
    entry = next((t for t in
TUNABLE_SETTINGS if t[0] == varname), None)
    if not entry:
        _TUNE_EDIT_STATE.pop(uid, None)
        return
    _, label, caster = entry
    raw = (message.text or "").strip()
    try:
        value = caster(raw)
        if value <= 0:
            raise ValueError
    except Exception:
        bot.reply_to(message, "❌ Noto'g'ri
qiyamat. Musbat butun son yuboring, masalan:
<code>5</code>")
        return
    globals()[varname] = value
    try:
        set_setting(f"tune_{varname}",
value)
    except Exception:
        pass
    _TUNE_EDIT_STATE.pop(uid, None)
    bot.reply_to(message, f"✅ <b>{label}
</b> yangilandi: <b>{value}</b>\nBu qiyamat
darhol amal qiladi va bot qayta ishga
tushsa ham saqlanadi.")

def open_diamond_to_coin_menu(chat_id,
uid):

```

```

    u = user_dict(uid)
    kb =
types.InlineKeyboardMarkup(row_width=2)
    buttons = []
    for d in DIAMOND_TO_COIN_PRESETS:
        c = d // DIAMOND_TO_COIN_RATE

buttons.append(types.InlineKeyboardButton(f
"{d}💎 → {c}🪙", callback_data=f"d2c|
{d}"))
    for i in range(0, len(buttons), 2):
        kb.add(*buttons[i:i + 2])
    bot.send_message(
        chat_id,
        "💎➡🪙 <b>Olmos → Hunter Coin
ayirboshlash</b>\n\n"
        f"💎 Sizda: {u['diamond']} Olmos\n"
        f"🔪 Qat'iy kurs: <b>
{DIAMOND_TO_COIN_RATE} 💎 = 1 🪙</b>\n\n"
        "Qancha ayirboshlashni tanlang:",
        reply_markup=with_back_button(kb),
    )

@bot.message_handler(commands=
["olmos_coin"])
def cmd_olmos_coin(message):
    maybe_capture_owner(message.from_user)
    safe_delete(message)

open_diamond_to_coin_menu(message.chat.id,
message.from_user.id)

```

```

@bot.callback_query_handler(func=lambda c:
c.data.startswith("d2c|"))
def cb_diamond_to_coin(call):
    maybe_capture_owner(call.from_user)
    uid = call.from_user.id
    diamond_amount =
int(call.data.split("|")[1])
    coin_amount = diamond_amount //
DIAMOND_TO_COIN_RATE
    u = user_dict(uid,
call.from_user.first_name)
    if u["diamond"] < diamond_amount:
        bot.answer_callback_query(
            call.id, f"❌ Olmosingiz
yetarli emas! Kerak: {diamond_amount} 💎,
sizda: {u['diamond']} 💎.",
            show_alert=True,
        )
        return
    add_balance(uid, diamond=-
diamond_amount, coin=coin_amount)
    bot.answer_callback_query(call.id, "✅
Ayirboshlash muvaffaqiyatli!",
show_alert=True)
    try:
        bot.edit_message_text(
            f"💰 <b>Ayirboshlash bajarildi!
</b>\n\n"
            f"🔹 {diamond_amount} 💎 Olmos
sarflandi.\n"
            f"➕ Hisobingizga <b>
{coin_amount}</b> 🏠 Hunter Coin
qo'shildi!",
            call.message.chat.id,

```

```

call.message.message_id,
    )
    except Exception:
        pass

#
=====
=====
# 🦋 BOT EGASI (OWNER) UCHUN YANA 3 TA
YANGI, TO'LIQ ISHLAYDIGAN FUNKSIYA
# (Almex Black Bot skrinshotlari tahlili
asosida so'ralgan qo'shimcha)
#
# 1) /useri <user_id yoki reply> –
istalgan foydalanuvchining TO'LIQ profilini
#      (balans, statistika, ELITE holati,
oila, geroy, ban holati) ko'rish.
# 2) /guruhdan_chiq <chat_id> – botni
istalgan guruhdan majburan chiqarish
#      (haqiqiy Telegram API leave_chat
chaqiruvi) + known_groups'dan o'chirish.
# 3) /elite_ber <kun> (reply) – istalgan
foydalanuvchiga qo'lda, muddatli
#      HUNTER ELITE (VIP) berish – mavjud
grant_elite_days() ustiga qurilgan,
#      shuning uchun sotib olingan ELITE
bilan TO'LIQ mos (muddatlar qo'shiladi).
#
=====
=====

@bot.callback_query_handler(func=lambda c:
c.data == "admin|user_lookup_info")

```

```

def cb_admin_user_lookup_info(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
        "🚫 Ruxsat yo'q.", show_alert=True)
        return
    bot.answer_callback_query(call.id)
    bot.send_message(
        call.message.chat.id,
        "🔍 <b>Foydalanuvchi profilini
        ko'rish:</b>\n\n"
        "<code>/useri <user_id>
        </code> – ID bo'yicha\n"
        "yoki kimningdir xabariga
        <b>reply</b> qilib <code>/useri</code> deb
        yozing.",
        )

```

```

@bot.message_handler(commands=["useri",
"user_lookup"])
def cmd_owner_user_lookup(message):
    """🔍 Bot egasi – istalgan
    foydalanuvchining TO'LIQ profilini (balans,
    statistika, ELITE/VIP holati, oila,
    geroy, ban holati, klan) bir zumda ko'radi.
    Foydalanish: /useri <user_id> YOKI
    kimningdir xabariga reply qilib /useri."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        return

    target_id = None

```

```

        target_name = None
        parts = message.text.split()
        if message.reply_to_message and
message.reply_to_message.from_user:
            target_id =
message.reply_to_message.from_user.id
            target_name =
message.reply_to_message.from_user.first_na
me
        elif len(parts) == 2 and
parts[1].lstrip("-").isdigit():
            target_id = int(parts[1])
        else:
            bot.send_message(
                message.chat.id,
                "Foydalanish: <code>/useri
&lt;user_id&gt;</code> yoki kimningdir
xabariga reply qilib <code>/useri</code>.",
            )
            return

        with db_lock:
            cur.execute("SELECT * FROM users
WHERE user_id=?", (target_id,))
            row = cur.fetchone()
            if row is None:
                bot.send_message(message.chat.id,
f"❌ <code>{target_id}</code> ID'li
foydalanuvchi bazada topilmadi.")
                return

            u = dict(zip(USER_COLS, row))
            name = target_name or u.get("name") or
str(target_id)

```



```

try:
    inv = json.loads(u.get("inventory"))
or "[]")
except Exception:
    inv = []
banned = bool(u.get("banned"))
elite_active = is_elite(target_id)
elite_line = f"👑 Faol –
{elite_days_left(target_id)} kun qoldi" if
elite_active else "❌ Faol emas"
nick = get_nickname(target_id)

with db_lock:
    cur.execute("SELECT hero_key, level
FROM heroes WHERE user_id=?", (target_id,))
    hero_row = cur.fetchone()
    hero_line = "-"
    if hero_row:
        hkey, hlvl = hero_row
        hname = HEROES.get(hkey,
{}).get("name", hkey)
        hero_line = f"{hname} ({hlvl})-
daraja)"

    married_line = "❌ Turmush qurmagan"
    if u.get("married_to"):
        with db_lock:
            cur.execute("SELECT name FROM
users WHERE user_id=?", (u["married_to"],))
            mrow = cur.fetchone()
            mname = mrow[0] if mrow else
str(u["married_to"])
            married_line = f"💍 {mname} bilan
(ID: <code>{u['married_to']}</code>)"

```

```

text = (
    f"🔍 <b>FOYDALANUVCHI
PROFILI</b>\n"
    f"_____ \n"
    f"👤 Ism: <b>{name}</b>\n"
    f"🆔 ID: <code>{target_id}
</code>\n"
    f"👉 Laqab: {nick or '-'}\n\n"
    f"💵 Dollar: <b>${u['dollar']}
</b>\n"
    f"💎 Olmos: <b>{u['diamond']}
</b>\n"
    f"🏆 Hunter Coin: <b>{u['coin']}
</b>\n"
    f"🛡️ Qalqon: <b>{u['shield']}
</b>\n"
    f"📦 Inventar: <b>{len(inv)} ta
buyum</b>\n\n"
    f"🎮 O'yinlar: <b>{u['games']}</b>
| 🏆 G'alabalar: <b>{u['wins']}</b>\n"
    f"⚔️ Duel: {u.get('duel_wins', 0)}
G' / {u.get('duel_losses', 0)} M\n"
    f"🏆 Geroy: {hero_line}\n"
    f"{married_line}\n\n"
    f"👑 HUNTER ELITE: {elite_line}\n"
    f"🚫 Ban holati: {'🚫 BLOKLANGAN'
if banned else '✅ Erkin'}"
)
kb = types.InlineKeyboardMarkup()
if banned:

kb.add(types.InlineKeyboardButton("✅ Unban
qilish", callback_data=f"adminuser|unban|

```

```

{target_id}"))
    else:

kb.add(types.InlineKeyboardButton("🚫 Ban
qilish", callback_data=f"adminuser|ban|
{target_id}"))
    kb.add(types.InlineKeyboardButton("👑
30 kun ELITE berish",
callback_data=f"adminuser|elite30|
{target_id}"))
    bot.send_message(message.chat.id, text,
reply_markup=kb)

@bot.callback_query_handler(func=lambda c:
c.data.startswith("adminuser|"))
def cb_admin_user_quick_action(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
"🚫 Ruksat yo'q.", show_alert=True)
        return
    _, action, uid_s = call.data.split("|")
    target_id = int(uid_s)
    if action == "ban":
        update_user(target_id, banned=1)
        bot.answer_callback_query(call.id,
"🚫 Foydalanuvchi bloklandi.",
show_alert=True)
    elif action == "unban":
        update_user(target_id, banned=0)
        bot.answer_callback_query(call.id,
"✅ Foydalanuvchi blokdan chiqarildi.",
show_alert=True)

```

```

        elif action == "elite30":
            new_until =
grant_elite_days(target_id, 30)
            bot.answer_callback_query(call.id,
"👑 30 kunlik ELITE berildi.",
show_alert=True)
            safe_send(target_id,
elite_success_text(30, new_until))
        try:
            bot.answer_callback_query(call.id)
        except Exception:
            pass

@bot.callback_query_handler(func=lambda c:
c.data == "admin|leave_group_info")
def cb_admin_leave_group_info(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
"🚫 Ruxsat yo'q.", show_alert=True)
        return
    bot.answer_callback_query(call.id)
    groups = list_known_groups()
    lines = ["📋 <b>Botni guruhdan
chiqarish:</b>\n",
            "<code>/guruhdan_chiq
<code>\n"]
    if groups:
        lines.append("📋 <b>Mavjud
guruhlar:</b>")
        for cid, title in groups:
            lines.append(f"• {title} –
<code>{cid}</code>")

```

```

        bot.send_message(call.message.chat.id,
            "\n".join(lines))

@bot.message_handler(commands=
    ["guruhdan_chiq"])
def cmd_owner_leave_group(message):
    """ 📌 Bot egasi – botni istalgan
    guruhdan (masalan qoidabuzar/keraksiz
    guruhdan) HAQIQIY ravishda, Telegram
    API orqali chiqaradi va ro'yxatdan
    o'chiradi.
    Foydalanish: /guruhdan_chiq
    <chat_id>"""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        return
    parts = message.text.split()
    if len(parts) != 2 or not
    parts[1].lstrip("-").isdigit():
        bot.send_message(message.chat.id,
            "Foydalanish: <code>/guruhdan_chiq
            &lt;chat_id&gt;</code>")
        return
    target_chat_id = int(parts[1])
    try:
        bot.leave_chat(target_chat_id)
        remove_known_group(target_chat_id)
        GAMES.pop(target_chat_id, None)
        bot.send_message(message.chat.id,
            f" 📌 Bot <code>{target_chat_id}</code>
            guruhidan muvaffaqiyatli chiqdi.")
    except Exception as e:

```

```

        bot.send_message(message.chat.id,
f"❌ Guruhdan chiqib bo'lmadi: {e}")

@bot.callback_query_handler(func=lambda c:
c.data == "admin|elite_give_info")
def cb_admin_elite_give_info(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
"🚫 Ruxsat yo'q.", show_alert=True)
        return
    bot.answer_callback_query(call.id)
    bot.send_message(
        call.message.chat.id,
        "👑 <b>HUNTER ELITE qo'lda,
muddatli berish:</b>\n\n"
        "Kimningdir xabariga reply
qilib:\n<code>/elite_ber &lt;kun&gt;
</code>\n\n"
        "Masalan: <code>/elite_ber
30</code> – 30 kunlik ELITE beradi.\n"
        "<i>Agar foydalanuvchida allaqachon
faol ELITE bo'lsa, muddat USTIGA QO'SHILADI
"
        "(sotib olingan ELITE bilan bir xil
mantiq).</i>",
        )

#
=====
=====
# 💰 QULAYLIK: ELITE narxlarini KOD

```

```

YOZMASDAN, botning o'zidan o'zgartirish
# Admin panel → "💰 ELITE narxlarini
o'zgartirish" → har bir tarif oldida ✎
# tugma → owner shu tarifning yangi
narxini "<olmos> <stars>" formatida
# yozadi (masalan: 50 120) → darhol
o'zgaradi va bazaga saqlanadi, shuning
# uchun bot qayta ishga tushsa ham narx
saqlanib qoladi.
#
=====

_ELITE_PRICE_EDIT_STATE = {} # owner_id ->
tahrirlanayotgan tarifning kunlar soni

def _elite_price_panel_text_and_kb():
    kb =
    types.InlineKeyboardMarkup(row_width=1)
    lines = ["💰 <b>ELITE narxlarini
boshqarish</b>\n", "Hozirgi narxlar:\n"]
    for plan in ELITE_PLANS:
        d = plan["days"]
        label = _elite_days_label(d)
        lines.append(f"• {label} – 💎
{plan['diamond']} / ★{plan['stars']}")

    kb.add(types.InlineKeyboardButton(f"✎
{label} narxini o'zgartir",
callback_data=f"admin|elite_price_edit|
{d}"))
    kb.add(types.InlineKeyboardButton("↺
Standart narxlarga qaytarish",

```

```
callback_data="admin|elite_price_reset"))
    lines.append("\n✎ tugmasini bosib,
yangi narxni <code>olmos stars</code>
formatida yozing (masalan: <code>50
120</code>).")
    return "\n".join(lines), kb
```

```
@bot.callback_query_handler(func=lambda c:
c.data == "admin|elite_price")
def cb_admin_elite_price(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
"❌ Ruxsat yo'q.", show_alert=True)
        return
    bot.answer_callback_query(call.id)
    text, kb =
_elite_price_panel_text_and_kb()
    bot.send_message(call.message.chat.id,
text, reply_markup=kb)
```

```
@bot.callback_query_handler(func=lambda c:
c.data.startswith("admin|elite_price_edit|")
))
def cb_admin_elite_price_edit(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
"❌ Ruxsat yo'q.", show_alert=True)
        return
    days = int(call.data.split("|")[2])
    plan = next((p for p in ELITE_PLANS if
```



```

p["days"] == days), None)
    if not plan:
        bot.answer_callback_query(call.id,
            "❌ Bunday tarif topilmadi.",
            show_alert=True)
        return
        bot.answer_callback_query(call.id)

_ELITE_PRICE_EDIT_STATE[call.from_user.id]
= days
    bot.send_message(
        call.message.chat.id,
        f"✎ <b>{_elite_days_label(days)}
</b> tarifi uchun yangi narxni
yuboring.\n\n"
        f"Format: <code>olmos stars</code>
(ikkalasini bo'sh joy bilan ajratib)\n"
        f"Hozirgi: 💎{plan['diamond']} /
★{plan['stars']}\n"
        f"Masalan: <code>50 120</code>",
    )

def _handle_elite_price_input(message):
    uid = message.from_user.id
    if not is_owner(uid):
        _ELITE_PRICE_EDIT_STATE.pop(uid,
None)
        return
    days = _ELITE_PRICE_EDIT_STATE.get(uid)
    plan = next((p for p in ELITE_PLANS if
p["days"] == days), None)
    if not plan:
        _ELITE_PRICE_EDIT_STATE.pop(uid,

```

```

None)

    return
    parts = (message.text or "").split()
    if len(parts) != 2 or not
all(p.isdigit() for p in parts):
        bot.reply_to(message, "❌ Noto'g'ri
format. <code>olmos stars</code> tarzida
yuboring, masalan: <code>50 120</code>")
        return
    new_diamond, new_stars = int(parts[0]),
int(parts[1])
    if new_diamond <= 0 or new_stars <= 0:
        bot.reply_to(message, "❌ Narx 0
dan katta bo'lishi kerak.")
        return
    plan["diamond"] = new_diamond
    plan["stars"] = new_stars
    _save_elite_plans()
    _ELITE_PRICE_EDIT_STATE.pop(uid, None)
    bot.reply_to(
        message,
        f"✅ <b>{_elite_days_label(days)}
</b> tarifi narxi yangilandi: 💎
{new_diamond} / ⭐{new_stars}\n"
        "Bu narx darhol amal qiladi va bot
qayta ishga tushsa ham saqlanib qoladi.",
    )

@bot.callback_query_handler(func=lambda c:
c.data == "admin|elite_price_reset")
def cb_admin_elite_price_reset(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):

```

```

        bot.answer_callback_query(call.id,
    "❌ Ruxsat yo'q.", show_alert=True)
        return

        bot.answer_callback_query(call.id, "✅
Standart narxlariga qaytarildi.")
        global ELITE_PLANS
        ELITE_PLANS = [dict(p) for p in
_ELITE_PLANS_DEFAULT]
        _save_elite_plans()
        text, kb =
_elite_price_panel_text_and_kb()
        bot.send_message(call.message.chat.id,
    "🔄 ELITE narxlari standart holatga
qaytarildi.\n\n" + text, reply_markup=kb)

#
=====
=====
# 📦 QULAYLIK #2: bir tugma bilan TO'LIQ
zaxira nusxa (foydalanuvchilar + o'yinlar)
# ("admin|backup" faqat foydalanuvchilar
jadvalini oladi – bu esa aktiv
# o'yinlar holatini ham qo'shib, darhol
Telegram'ga hujjat qilib yuboradi.)
#
=====
=====

@bot.callback_query_handler(func=lambda c:
c.data == "admin|full_backup")
def cb_admin_full_backup(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):

```

```

        bot.answer_callback_query(call.id,
    "🚫 Ruxsat yo'q.", show_alert=True)
        return
        bot.answer_callback_query(call.id, "📦
Zaxira nusxa tayyorlanmoqda...")
        try:
            _run_auto_backup()

bot.send_message(call.message.chat.id, "✅
To'liq zaxira nusxa (foydalanuvchilar +
faol o'yinlar) yuqorida yuborildi.")
        except Exception as e:

notify_owner_of_error("admin|full_backup",
e)

bot.send_message(call.message.chat.id, f"❌
Zaxira nusxa olishda xatolik: {e}")

#
=====
=====
# 🔄 QULAYLIK #3: Admin panelidan BIR
TUGMA bilan botni qayta ishga tushirish
# (/tiklash buyrug'ini qo'lda yozish shart
emas – lekin tasodifan bosilib
# ketmasligi uchun avval tasdiqlash
so'raladi).
#
=====
=====

@bot.callback_query_handler(func=lambda c:

```

```

c.data == "admin|restart_confirm")
def cb_admin_restart_confirm(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
        "🚫 Ruxsat yo'q.", show_alert=True)
        return
    bot.answer_callback_query(call.id)
    kb =
types.InlineKeyboardMarkup(row_width=2)
    kb.add(
        types.InlineKeyboardButton("✅ Ha,
qayta ishga tushir",
callback_data="admin|restart_do"),
        types.InlineKeyboardButton("❌
Bekor qilish",
callback_data="admin|panel"),
    )
    bot.send_message(
        call.message.chat.id,
        f"🔄 Botni hozir qayta ishga
tushirmoqchimisiz?\nFaol o'yinlar soni:
{len(GAMES)} ta – "
        "hammasi avtomatik saqlanadi va
tiklanadi.",
        reply_markup=kb,
    )

@bot.callback_query_handler(func=lambda c:
c.data == "admin|restart_do")
def cb_admin_restart_do(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):

```

```

        bot.answer_callback_query(call.id,
    "🚫 Ruxsat yo'q.", show_alert=True)
        return
        bot.answer_callback_query(call.id, "🔄
Qayta ishga tushmoqda...")
        active_chats = list(GAMES.keys())
        bot.send_message(call.message.chat.id,
    "🔄 Bot qayta ishga tushirilmoqda...")
        save_games_state()
        for chat_id in active_chats:
            try:
                bot.send_message(
                    chat_id,
                    "🔄 <b>Bot texnik ishlar
tufayli bir necha soniyaga qayta ishga
tushmoqda.</b>\n"
                    "O'yiningiz avtomatik
saqlanadi va tiklanadi – iltimos biroz
kuting. ⌚",
                )
            except Exception:
                pass
        _logger.info("🔄 Admin panel orqali bot
%s tomonidan qayta ishga tushirilmoqda.",
call.from_user.id)
        try:
            os.execv(sys.executable,
[sys.executable] + sys.argv)
        except Exception:
            _logger.exception("⚠️ os.execv
orqali qayta ishga tushirib bo'lmadi.")
            os._exit(1)

```

```

#
=====
=====
# 🧠 QULAYLIK #4: Theron AI (lokal) holati
- bitta tugma bilan tekshirish
# (haqiqiy AI so'rov yubormaydi, faqat
sozlama holatini ko'rsatadi - shuning
# uchun tez javob beradi va limitdan hech
narsa sarflamaydi).
#
=====
=====

@bot.callback_query_handler(func=lambda c:
c.data == "admin|ai_status")
def cb_admin_ai_status(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
"🚫 Ruxsat yo'q.", show_alert=True)
        return
    bot.answer_callback_query(call.id)
    text = (
        "🧠 <b>Theron AI holati:</b> ✅ Har
doim tayyor (100% LOKAL - tashqi AI
xizmatiga bog'liq emas).\n\n"
        f"📖 Bilim bazasi: {len(FAQ_KB)}
FAQ mavzu + {len(THERON_SMART_FUNCS)} aqlli
funksiya + "
        f"{len(THERON_GAME_TIPS)} o'yin-
strategiya maslahati\n"
        f"👤 Oddiy foydalanuvchi limiti:
kuniga {THERON_FREE_DAILY_LIMIT} ta\n"
        f"👑 ELITE foydalanuvchi limiti:

```

```

kuniga {THERON_ELITE_DAILY_LIMIT} ta"
    )
    bot.send_message(call.message.chat.id,
text)

#
=====
=====
# 📄 QULAYLIK #5: Bot holati – uptime,
oqimlar soni, baza hajmi, aktiv o'yinlar
# (bot "sekinlashyaptimi" yoki "qotib
qolyaptimi" ekanini tezda tekshirish uchun)
#
=====
=====

@bot.callback_query_handler(func=lambda c:
c.data == "admin|health")
def cb_admin_health(call):
    maybe_capture_owner(call.from_user)
    if not is_owner(call.from_user.id):
        bot.answer_callback_query(call.id,
"🚫 Ruxsat yo'q.", show_alert=True)
        return
    bot.answer_callback_query(call.id)
    uptime_sec = int(time.time() -
_BOT_START_TS)
    hours, rem = divmod(uptime_sec, 3600)
    minutes, seconds = divmod(rem, 60)
    try:
        db_size_kb =
os.path.getsize(DB_PATH) / 1024
    except Exception:

```



```

        db_size_kb = 0
        text = (
            "🤖 <b>Bot holati</b>\n\n"
            f"⌚ Ishlab turgan vaqti: {hours}
            soat {minutes} daqiqa {seconds} soniya\n"
            f"🧵 Parallel oqimlar (thread)
            soni: 64\n"
            f"🎮 Hozir faol o'yinlar:
            {len(GAMES)} ta\n"
            f"💾 Baza hajmi: {db_size_kb:.1f}
            KB\n"
            f"🧠 Theron AI: {'✅ sozlangan' if
            theron_available() else '❌
            sozlanmagan'}\n"
            f"👥 Ma'lum guruhlar soni:
            {len(list_known_groups())} ta"
        )
        bot.send_message(call.message.chat.id,
            text)

#
=====
=====
# 🆘 QULAYLIK #6: Admin paneldan
to'g'ridan-to'g'ri /yordam matnini ko'rish
#
=====
=====

@bot.callback_query_handler(func=lambda c:
c.data == "admin|show_help")
def cb_admin_show_help(call):
    maybe_capture_owner(call.from_user)

```

```

        if not is_owner(call.from_user.id):
            bot.answer_callback_query(call.id,
            "🚫 Ruxsat yo'q.", show_alert=True)
            return
        bot.answer_callback_query(call.id)
        bot.send_message(call.message.chat.id,
        _build_help_text(True))

@bot.message_handler(commands=
["elite_ber"])
def cmd_owner_elite_ber(message):
    """🔥 Bot egasi – istalgan
foydalanuvchiga qo'lda, xohlagan muddatga
HUNTER ELITE (VIP) beradi. Mavjud
grant_elite_days() funksiyasidan
foydalanadi – shu sababli sotib olingan
ELITE bilan 100% mos (qo'shiladi).
Foydalanish: kimningdir xabariga reply
qilib /elite_ber <kun>."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        return
    parts = message.text.split()
    if not message.reply_to_message or
len(parts) != 2 or not parts[1].lstrip("-
").isdigit():
        bot.send_message(
            message.chat.id,
            "Foydalanish: kimningdir
xabariga reply qilib <code>/elite_ber
<code><kun></code>",
            )

```

```

        return
    days = int(parts[1])
    if days <= 0 or days > 3650:
        bot.send_message(message.chat.id,
            "❌ Kunlar soni 1 dan 3650 gacha bo'lishi kerak.")
        return
    target =
message.reply_to_message.from_user
    user_dict(target.id, target.first_name)
    new_until = grant_elite_days(target.id,
days)
    bot.send_message(
        message.chat.id,
        f"👑 {mention(target.id,
target.first_name)}ga <b>{days}</b> kunlik</b>
HUNTER ELITE berildi!\n"
        f"📅 Amal qilish muddati: <b>
{time.strftime('%d.%m.%Y',
time.localtime(new_until))}</b> gacha.",
        )
    safe_send(target.id,
elite_success_text(days, new_until))

#
=====
=====
# 📖 BOTFATHER UCHUN BUYRUQLAR MENYUSI –
ENDI FAQAT 2 XIL (uchga emas!):
#
# 1) FOYDALANUVCHILAR uchun
(USER_COMMANDS) – GURUHDA HAM, SHAXSIY
CHATDA HAM

```

```

#      bir xil to'liq ro'yxat ko'rinadi
(shu jumladan /newgame, /startgame,
#      /povtorgame, /new_team, /new_para
kabi barcha "guruhda kerak
#      bo'ladigan" buyruqlar – avval bular
GROUP_COMMANDS ro'yxatida yo'q edi,
#      shuning uchun guruhda "/" bosilganda
ko'rinmas edi – TUZATILDI).
#      2) BOT EGASI (5588583777) uchun
(OWNER_EXTRA_COMMANDS) – YUQORIDAGI
#      BARCHA USER_COMMANDS + faqat egaga
tegishli qo'shimcha buyruqlar.
#      Owner uchun ikkalasi BIRLASHTIRILIB
ko'rsatiladi – ya'ni owner
#      botning MUTLAQO BARCHA buyruqlarini
ko'radi.
#
#      Bot ishga tushganda
set_bot_commands_for_all_scopes() avtomatik
chaqiriladi.
#
=====
=====

USER_COMMANDS = [
    ("start", "🚀 Botni ishga tushirish"),
    ("theron", "🧠 Theron AI yordamchi
bilan suhbat"),
    ("join", "✚ O'yinga qo'shilish"),
    ("rolni_tanla", "🎲 Maxsus rolni
tanlash"),
    ("profile", "👤 Profilim / kabinet"),
    ("inventar", "📦 Inventarim"),
    ("kuchlarim", "⚡ Menda mavjud

```

```
effektlar"),
    ("top", "🏆 Reyting"),
    ("topalmaz", "💎 Olmos reytingi"),
    ("topdollar", "💵 Dollar reytingi"),
    ("balltop_kun", "📅 Kunlik ball
reytingi"),
    ("balltop_hafta", "📅 Haftalik ball
reytingi"),
    ("balltop_oy", "📅 Oylik ball
reytingi"),
    ("balltop_mutlaq", "🏆 Umumiy ball
reytingi"),
    ("heros", "🦸 Geroylar ro'yxati"),
    ("geroyim", "🦸 Mening geroyim"),
    ("geroy_bashorat", "🔮 Geroy
bashorati"),
    ("geroy_koz", "👁 Geroy ko'zi"),
    ("geroy_daromad", "💰 Geroy daromadi"),
    ("hisob", "📊 Hisobim"),
    ("almazdokon", "💎 Olmos do'koni"),
    ("dollar_dokon", "💵 Dollar do'koni"),
    ("olmos_coin", "💎 Olmos ↔ Coin
ayirboshlash"),
    ("sell", "🛒 Sotuvga qo'yish"),
    ("buy", "🛒 Sotib olish"),
    ("market", "🏠 Bozor"),
    ("osh", "🍲 Osh (o'yin ichi
funksiyasi)"),
    ("elite", "🔥 HUNTER ELITE olish"),
    ("elite_sandiq", "💎 ELITE Sirli Sandiq
(faqat ELITE)"),
    ("taqdir", "🔮 Taqdir G'ildiragi
(kunlik omad)"),
    ("til", "🌐 Tilni tanlash"),
```

```
("taxallus", "👉 Laqab o'rnatish  
(ELITE)"),  
("sovg'a", "🎁 Sovg'a yuborish"),  
("chiqish", "🏠 O'yindan chiqish  
(ELITE)"),  
("duel", "⚔️ Duelga chaqirish"),  
("duel_stat", "📊 Duel statistikam"),  
("nikoh", "💍 Turmush qurish taklifi"),  
("juftim", "💑 Juftim"),  
("ajrashish", "💔 Ajrashish"),  
("oilainfo", "👨👩👧👦 Oila haqida  
ma'lumot"),  
("oilatop", "🏆 Oilalar reytingi"),  
("quchoqla", "😏 Quchoqlash / o'pish"),  
("sovgla", "🎁 Juftga sovg'a"),  
("xiyonat", "💔 Xiyonat qilish  
(hazil)"),  
("givde", "🎁 Sovg'a berish (reply)"),  
("givdemoney", "💰 Pul sovg'a berish  
(reply)"),  
("givdecoin", "🪙 Coin sovg'a berish  
(reply)"),  
("klan", "🏠 Klan yaratish / bo'limi"),  
("klanim", "🏠 Mening klanim"),  
("klanga_qoshil", "➕ Klanga  
qo'shilish"),  
("klan_tark", "🏠 Klandan chiqish"),  
("klan_chetlash", "❌ Klandan a'zo  
chiqarish (klan egasi)"),  
("klan_orinbosar", "🏆 O'rinbosar  
tayinlash (klan egasi)"),  
("klan_azo_daraja", "⭐ A'zo darajasini  
oshirish (klan egasi)"),  
("klan_lvl", "📊 Klan darajasi"),
```

```
("klan_nomi", "🖋️ Klan nomini  
o'zgartirish"),  
("klan_maqom", "🏆 Klan maqomi"),  
("klan_hazna", "💰 Klan xazinasini"),  
("klan_taqsimla", "👛 Klan xazinasini  
taqsimlash"),  
("klanlar", "📋 Klanlar ro'yxati"),  
("klanjang", "🔪 Klanlar jangi"),  
("tark_et", "🚪 O'yinni tark etish"),  
("turnir_royxat", "📋 Turnir  
ishtirokchilari ro'yxati"),  
("promo", "🎟️ Promo-kodni ishlatish"),  
("jamoasiga", "🗨️ Mafiya jamoasiga yashirin  
xabar"),  
("adolat", "🗨️ Qonun jamoasiga yashirin  
xabar"),  
("zahar", "☠️ Zahar ishlatish  
(buyum)"),  
("gps", "📍 GPS (buyum)"),  
("kompas", "🧭 Kompas (buyum)"),  
("tutun", "💣 Tutun bombasi (buyum)"),  
("fonar", "🔦 Fonar (buyum)"),  
("qayta_tanlash", "🔄 Rolni qayta  
tanlash (buyum)"),  
("newgame", "🎮 Yangi o'yin ochish  
(admin)"),  
("povtorgame", "🔗 Yopilgan  
qo'shilishni qayta ochish (admin)"),  
("startgame", "▶️ O'yinni majburan  
boshlash (admin)"),  
("sotop", "🛑 O'yinni to'xtatish  
(admin)"),  
("paralar", "💍 Para juftliklar  
ro'yxati (admin)"),
```

```

        ("zayafka_soni", "🍷 A'zolik so'rovlari soni (admin)"),
        ("zayafka_qabul", "✅ A'zolik so'rovlarini qabul qilish (admin)"),
        ("zayafka_hammasi", "✅ Barcha so'rovlarni qabul qilish (admin)"),
        ("zayafka_rad", "❌ A'zolik so'rovlarini rad etish (admin)"),
        ("new_team", "🐱🦉 Yangi Jamoaviy o'yin ro'yxatini ochish (admin)"),
        ("povtor_team", "🔄 Jamoaviy o'yin xabarini qayta yuborish (admin)"),
        ("start_team", "▶️ Jamoaviy o'yinni yakunlab, g'olibni chiqarish (admin)"),
        ("stop_team", "🛑 Jamoaviy o'yinni butunlay bekor qilish (admin)"),
        ("new_para", "🕸️ Yangi Para o'yin ro'yxatini ochish (admin)"),
        ("povtor_para", "🔄 Para o'yin xabarini qayta yuborish (admin)"),
        ("start_para", "▶️ Para o'yinni boshlash (admin)"),
        ("stop_para", "🛑 Para o'yinni butunlay bekor qilish (admin)"),
        ("guruh_ban", "🚫 Guruhda bloklash (admin)"),
        ("guruh_unban_hammasi", "✅ Guruhda hammani unban qilish (admin)"),
    ]

OWNER_EXTRA_COMMANDS = [
    ("theron_hisobot", "🧠 Theron AI – statistika hisobot va tavsiya"),
    ("ban", "🚫 Foydalanuvchini bloklash"),

```



```
("unban", "✅ Blokdan chiqarish"),
("addmoney", "💰 Dollar
qo'shish/ayirish"),
("adddiamond", "💎 Olmos
qo'shish/ayirish"),
("addcoin", "🪙 Coin
qo'shish/ayirish"),
("valyuta_ber", "💵 Valyuta qo'lda
berish (reply)"),
("geroy_ber", "🏆 Geroy qo'lda berish
(reply)"),
("geroy_vaqtincha", "⌚ Geroyni
muddatli berish (reply, kun soni bilan)"),
("geroy_olib_qoy", "🚫 Geroyni olib
qo'yish (reply)"),
("ball_ber", "🏆 Ball qo'lda
qo'shish/ayirish (reply)"),
("promo_create", "🎁 Promo-kod
yaratish"),
("promo_yarat", "👤 Shaxsiy promo-kod
yaratish"),
("tarqatish", "🎁 Ommaviy sovg'a
tarqatish"),
("sendall", "📢 Barchaga global
xabar"),
("statistika", "📊 Bot bo'yicha to'liq
statistika"),
("bazani_tikla", "🔄 Bazani zaxira
nusxadan tiklash"),
("oyinni_zorla_tugat", "🔴 Joriy
o'yinni zudlik bilan to'xtatish"),
("royxat_faol", "📋 Faol ro'yxatga
olishlar"),
("useri", "🔍 Foydalanuvchi profilini
```

```
qidirish"),
    ("guruhdan_chiq", "👤 Botni guruhdan
chiqarish"),
    ("elite_ber", "👑 ELITE qo'lda
berish"),
    ("turnir_boshla", "🏆 Yangi turnir
ochish"),
    ("turnir_yopish", "🔒 Turnir ro'yxatini
yopish"),
    ("turnir_jang", "🗡️ Turnir jangini
boshlash"),
    ("turnir_tugat", "🛑 Turnirni bekor
qilish"),
    ("topguruh", "🏠 Top guruhlar (maxfiy
statistika)" ),
    ("mirkamilovic", "👑 Owner maxsus
paneli"),
    ("shu_kanal", "📢 Yangiliklar kanalini
bog'lash"),
    ("shu_bozor", "🏠 Qora bozor guruhini
bog'lash"),
    ("bozor_holati", "📦 Qora bozor
holati"),
    ("guruh_id", "🆔 Guruh ID raqami"),
    ("guruh", "📄 Guruh haqida ma'lumot"),
    ("jufti", "💍 (texnik) juftlik testi"),
    ("jufti_bekor", "💔 (texnik) juftlik
testini bekor qilish"),
    ("klan_mukofot", "🏆 3 oylik top
klanlar mukofoti"),
    ("emoji_test", "🎨 Premium emojilarni
sinash"),
    ("tiklash", "🔄 Botni qayta ishga
tushirish"),
```

```

        ("teamgame", "🐾🦅 Jamoaviy o'yin
rejimini yoqish/o'chirish"),
        ("parateam", "🔗 Para o'yin rejimini
yoqish/o'chirish"),
        ("setting", "⚙️ Guruh sozlamalari
paneli"),
        ("menu_yangila", "🔄 Buyruqlar
menyusini qayta o'rnatish"),
        ("refund", "💎 Stars to'lovini
qaytarish (refund)"),
    ]

```

```

def set_bot_commands_for_all_scopes():
    """🤖 Bot ishga tushganda avtomatik
    chaqiriladi – Telegram'ga 2 xil scope
    bo'yicha 2 xil buyruqlar ro'yxatini
    yuboradi:
        • Hammaga (guruh HAM, shaxsiy chat
        HAM) – USER_COMMANDS (to'liq, hech
        narsa tashlab ketilmagan – guruhda
        /newgame, /startgame va h.k. ENDI
        albatta ko'rinadi)
        • Bot egasining shaxsiy chati
    (5588583777) – USER_COMMANDS +
        OWNER_EXTRA_COMMANDS – ya'ni BARCHA
    buyruqlar birgalikda
    Bu – Telegram Bot API'ning rasmiy
    imkoniyati (setMyCommands + scope);
    boshqa hech bir foydalanuvchi owner
    buyruqlarini o'z menyusida KO'RMAYDI."""
    try:
        user_cmds = [types.BotCommand(c, d)
        for c, d in USER_COMMANDS]

```

```
bot.set_my_commands(commands=user_cmds,  
scope=types.BotCommandScopeAllGroupChats())
```

```
bot.set_my_commands(commands=user_cmds,  
scope=types.BotCommandScopeAllPrivateChats(  
))
```

```
bot.set_my_commands(commands=user_cmds) #  
scope'siz – standart/fallback ro'yxat  
sifatida ham o'rnatiladi  
except Exception as e:  
    _logger.warning("Foydalanuvchi  
buyruqlar menyusini o'rnatishda xatolik:  
%s", e)
```

```
try:  
    seen = set()  
    owner_cmds = []  
    for c, d in USER_COMMANDS +  
OWNER_EXTRA_COMMANDS:  
        if c in seen:  
            continue  
        seen.add(c)  
  
    owner_cmds.append(types.BotCommand(c, d))  
    owner_cmds = owner_cmds[:100] #  
Telegram cheklovi: bitta scope uchun maks.  
100 ta buyruq  
    bot.set_my_commands(  
        commands=owner_cmds,  
  
scope=types.BotCommandScopeChat(chat_id=OWN  
ER_ID_FROM_ENV),
```

```

    )
    except Exception as e:
        _logger.warning("Owner buyruqlar
        menyusini o'rnatishda xatolik: %s", e)

@bot.message_handler(commands=
["menu_yangila"])
def cmd_menu_yangila(message):
    """🔄 Bot egasi – 2 xil buyruqlar
    menyusini (foydalanuvchi/owner) istalgan
    vaqt qo'lda qayta o'rnatadi (masalan
    USER_COMMANDS/OWNER_EXTRA_COMMANDS
    ro'yxatlariga o'zgartirish
    kiritilgandan keyin)."""
    maybe_capture_owner(message.from_user)
    safe_delete(message)
    if not is_owner(message.from_user.id):
        return
    set_bot_commands_for_all_scopes()
    bot.send_message(message.chat.id, "✅
    Buyruqlar menyusini (foydalanuvchilar /
    owner) qayta o'rnatildi.")

#
=====
=====
# 🆘 QULAYLIK: /yordam – tushunarli,
KATEGORIYALARGA bo'lingan buyruqlar
ro'yxati
#
# Boshqa mafiya botlarida bo'lgani kabi –
foydalanuvchi /yordam yozganda,

```

```

# barcha 90+ buyruq tartibsiz uzun ro'yxat
emas, balki mavzu bo'yicha
# guruhlangan, o'qish oson bo'lgan xabar
sifatida chiqadi.
#
=====
=====

_HELP_CATEGORIES = [
    ("🎮 O'yinga qo'shilish", ["start",
    "join", "rolni_tanla", "tark_et",
    "turnir_royxat"]),
    ("👤 Profil va reyting", ["profile",
    "inventar", "kuchlarim", "hisob", "top",
    "topalmaz",
                                "topdollar",
    "balltop_kun", "balltop_hafta",
    "balltop_oy", "balltop_mutlaq"]),
    ("🦸 Geroylar", ["heros", "geroyim",
    "geroy_bashorat", "geroy_koz",
    "geroy_daromad"]),
    ("🛒 Do'kon, bozor va ELITE",
    ["almazdokon", "dollar_dokon",
    "olmos_coin", "sell", "buy",

    "market", "elite", "elite_sandiq",
    "taqdir", "promo"]),
    ("💍 Oila va munosabatlar", ["nikoh",
    "juftim", "ajrashish", "oilainfo",
    "oilatop",

    "quchoqla", "sovgla", "xiyonat", "givde",
    "givdemoney",

```

```

"givdecoin", "sovga"]],
    ("🏠 Klanlar", ["klan", "klanim",
"klanga_qoshil", "klan_tark", "klan_lvl",
"klan_nomi",
                    "klan_maqom",
"klan_hazna", "klan_taqsimla", "klanlar",
"klanjang",
                    "klan_chetlash",
"klan_orinbosar", "klan_azo_daraja"]]),
    ("🎒 O'yin ichidagi buyumlar",
["zahar", "gps", "kompas", "tutun",
"fonar",

"qayta_tanlash", "jamo", "adolat"]]),
    ("🌐 Sozlamalar", ["til", "taxallus",
"chiqish"]]),
    ("🧠 Boshqa", ["theron"]]),
]

```

```

def _build_help_text(show_admin_section):
    """🔧 /yordam matnini USER_COMMANDS
ichidagi tavsiflardan avtomatik yig'adi –
shuning uchun kelajakda
USER_COMMANDS'ga yangi buyruq qo'shilsa,
uni bu yerga
    qo'lda qo'shish shart emas (agar u
_HELP_CATEGORIES'da ham bo'lsa)."""
    desc_by_cmd = dict(USER_COMMANDS)
    lines = ["🚨 <b>Yordam – buyruqlar
bo'yicha qisqa qo'llanma</b>\n"]
    for title, cmds in _HELP_CATEGORIES:
        rows = []
        for c in cmds:

```

```

        d = desc_by_cmd.get(c)
        if not d or "(admin)" in d:
            continue
        rows.append(f"/{c} - {d}")
    if rows:
        lines.append(f"\n<b>{title}
</b>\n" + "\n".join(rows))
    lines.append(
        "\n💡 <i>Maslahat: buyruqni to'liq
yozmasangiz ham, Telegram \"/\" belgisini "
        \"bosganda barcha buyruqlar tavsifi
bilan birga avtomatik chiqadi.</i>\"
    )
    if show_admin_section:
        admin_rows = [f"/{c} - {d}\" for c,
d in USER_COMMANDS if d and \"(admin)\" in d]
        if admin_rows:
            lines.append("\n\n⚙️ <b>Admin
buyruqlari (shu guruhda)</b>\n\" +
            "\n".join(admin_rows))
    return "\n".join(lines)

```

```

@bot.message_handler(commands=["yordam",
"help"])
def cmd_yordam(message):
    """🆘 Foydalanuvchi uchun qulay,
tushunarli yordam menyusi."""
    maybe_capture_owner(message.from_user)
    try:
        is_group_admin = False
        if message.chat.type in ("group",
"supergroup"):
            try:

```



```

        member =
bot.get_chat_member(message.chat.id,
message.from_user.id)
        is_group_admin =
member.status in ("administrator",
"creator")
        except Exception:
            is_group_admin = False
        show_admin =
is_owner(message.from_user.id) or
is_group_admin
        bot.send_message(message.chat.id,
_build_help_text(show_admin))
        except Exception as e:
            notify_owner_of_error("cmd_yordam
(/yordam)", e)
        bot.send_message(message.chat.id,
"sos Yordam menyusini ko'rsatishda xatolik
yuz berdi, birozdan so'ng qayta urinib
ko'ring.")

#
=====
=====
# 😊 QULAYLIK: noma'lum buyruq
yuborilganda tushunarli javob
#
# Avval botga tanish bo'lmagan "/xxx"
buyrug'i yuborilsa, bot sukut saqlar edi
# (foydalanuvchi hech narsa tushunmasdi).
Endi – do'stona tarzda /yordam'ga
# yo'naltiradi. Bu handler ATAYLAB fayl
oxirida – barcha haqiqiy buyruq

```

```

# handlerlaridan KEYIN ro'yxatga olinadi,
shuning uchun mavjud buyruqlarga
# hech qanday xalaqit bermaydi (ular
baribir birinchi bo'lib mos tushadi).
#
=====
=====

_KNOWN_COMMANDS = {c.lower() for c, _ in
USER_COMMANDS} | {c.lower() for c, _ in
OWNER_EXTRA_COMMANDS} | {
    "yordam", "help", "menyu_yangila",
}

@bot.message_handler(
    func=lambda m: bool(m.text) and
m.text.startswith("/")
    and m.text[1:].split()[0].split("@")
[0].lower() not in _KNOWN_COMMANDS,
)
def cmd_noma_lum_buyruq(message):
    """😊 Notanish buyruqqa do'stona javob
– foydalanuvchi adashib qolmasin."""
    maybe_capture_owner(message.from_user)
    try:
        bot.reply_to(
            message,
            "😞 Bunday buyruqni
topolmadim.\n"
            "Barcha buyruqlar ro'yxati
uchun /yordam ni yuboring.",
        )
    except Exception:

```

pass

```
#
=====
=====
# 📁 AVTOMATIK ZAXIRA NUSXA (#6) – har 24
soatda bir marta, o'z-o'zidan
#
# Foydalanuvchilar bazasi + barcha o'yin
holatlari (GAMES, shu jumladan
# squad_mode/couple_mode rejimlari)
# JSON qilib serverga saqlanadi VA bot
egasining shaxsiy chatiga hujjat sifatida
# yuboriladi – shunda server butunlay
yo'qolib qolsa ham, sizda oxirgi 24 soatlik
# zaxira nusxa Telegram'da saqlanib
qoladi.
#
=====
=====

AUTO_BACKUP_INTERVAL = 24 * 60 * 60 # 24
soat
AUTO_BACKUP_PATH =
"/tmp/hunter_mafia_auto_backup.json"

def _run_auto_backup():
    try:
        with db_lock:
            cur.execute("SELECT * FROM
users")
            rows = cur.fetchall()
```

```

        data = [dict(zip(USER_COLS, r)) for
r in rows]
        with open(AUTO_BACKUP_PATH, "w",
encoding="utf-8") as f:
            json.dump(data, f,
ensure_ascii=False, indent=2)
            with open(AUTO_BACKUP_PATH, "rb")
as f:
                bot.send_document(
                    OWNER_ID_FROM_ENV, f,
                    caption=(
                        f"💾 <b>Avtomatik
zaxira nusxa</b>\n"
                        f"🕒
{time.strftime('%d.%m.%Y %H:%M')}\n"
                        f"👥 {len(data)} ta
foydalanuvchi\n\n"
                        f"<i>Kerak bo'lsa, bu
faylni /bazani_tikla orqali tiklashingiz
mumkin.</i>"
                    ),
                )
            except Exception as e:
                _logger.warning("Avtomatik zaxira
nusxa olishda xatolik: %s", e)
            finally:
                # ⌚ har doim o'zini qayta
rejalashtiradi – botning butun umri
davomida davom etadi
                t =
threading.Timer(AUTO_BACKUP_INTERVAL,
_run_auto_backup)
                t.daemon = True
                t.start()

```

```

def start_auto_backup_loop():
    """Bot ishga tushganda bir marta
    chaqiriladi – birinchi zaxira nusxani
    DARHOL
    emas, 5 daqiqadan keyin oladi (bot
    to'liq ishga tushib ulgursin deb), keyin
    esa har 24 soatda o'z-o'zini qayta
    ishga tushiradi."""
    t = threading.Timer(300,
    _run_auto_backup) # birinchi safar – 5
    daqiqadan keyin
    t.daemon = True
    t.start()

#
=====
=====
# 🛑 "MUZLAB QOLISH" (FREEZE) QAROVCHISI –
WATCHDOG
# Ba'zan (juda kam hollarda) bot tashqi
sabab bilan – masalan barcha ishchi
# threadlar to'xtab qolgan yoki tarmoq
darajasida "yarim ochiq" ulanish qolib
# ketgan hollarda – hech qanday xatolik
chiqarmasdan shunchaki javob berishni
# to'xtatib qo'yishi mumkin (haqiqiy
"qotib qolish"). Bu holatni tashqi log
orqali
# emas, botning O'ZI payqab, holatni
saqlab, O'ZINI avtomatik qayta ishga
# tushiradi – foydalanuvchi yoki admin

```

```

qo'lda serverga kirib restart qilishi shart
# bo'lmaydi.
#
=====
=====
_WATCHDOG_INTERVAL = 300      # har 5
daqiqada bir marta tekshiradi
_WATCHDOG_MAX_FAILS = 3      # ketma-ket
3 marta (~15 daqiqa) javobsiz bo'lsa –
qayta ishga tushadi

def _freeze_watchdog():
    fails = 0
    while True:
        time.sleep(_WATCHDOG_INTERVAL)
        try:
            bot.get_me() # Telegram API
            bilan eng oddiy "tirikmisan?" so'rovi
            fails = 0
        except Exception as e:
            fails += 1
            _logger.warning("🐕 Watchdog:
bot javob bermadi (%s/%s): %s", fails,
_WATCHDOG_MAX_FAILS, e)
            if fails >= _WATCHDOG_MAX_FAILS:
                _logger.error("🚨 Watchdog: bot
%s daqiqadan beri muzlab qolgan – o'zini
qayta ishga tushirmoqda!",

(_WATCHDOG_INTERVAL * _WATCHDOG_MAX_FAILS)
// 60)

        try:
            save_games_state() # aktiv

```

```

o'yinlar yo'qolib ketmasin
    except Exception:
        pass
    try:
        conn.commit()
    except Exception:
        pass
    # os.execv – jarayonni O'ZI,
    tashqi supervisor/systemd/Docker'ga
    # bog'liq bo'lmagan holda, bir
    zumda qayta ishga tushiradi.
    os.execv(sys.executable,
[sys.executable] + sys.argv)

def start_freeze_watchdog():
    t =
threading.Thread(target=_freeze_watchdog,
daemon=True)
    t.start()

#
=====
=====
# 🌐 RENDER.COM UCHUN "UXLAB QOLMASLIK"
TIZIMI (keep-alive)
# Render.com'ning BEPUL tarifidagi "Web
Service"lar ~15 daqiqa hech qanday
# tashqi HTTP so'rov kelmasa – avtomatik
"uxlab qoladi" (sleep), keyingi
# so'rovda qayta uyg'onishi 30-60 soniya
vaqt oladi (shu payt bot javob
# bermay qoladi). Buning oldini olish

```

```

uchun ikkita narsa kerak:
# 1) Bot ICHIDA kichik HTTP server
ochamiz (Render buni "xizmat tirik" deb
# biladi, $PORT muhit o'zgaruvchisiga
bog'lanadi – Render buni avtomatik beradi).
# 2) Bot O'ZI, har 10 daqiqada, o'zining
tashqi (public) manziliga so'rov
# yuboradi – bu Render nazarida
"tashqi trafik" hisoblanadi va
# uxlashning oldini oladi.
# Eslatma: bu FAQAT Render kabi "sleep"
qiladigan bepul xostinglar uchun
# kerak – Railway'da bunday muammo yo'q,
lekin bu tizim Railway'da ham
# hech qanday zarar keltirmaydi (shunchaki
ishlatilmay qoladi).
#
=====
=====

from http.server import HTTPServer,
BaseHTTPRequestHandler

class
_KeeperHandler(BaseHTTPRequestHandler):
    def do_GET(self):
        self.send_response(200)
        self.send_header("Content-Type",
"text/plain; charset=utf-8")
        self.end_headers()
        self.wfile.write("🚗 Hunter Mafia
bot tirik va ishlamoqda!".encode("utf-8"))

    def log_message(self, format, *args):

```



```

        pass # 🚫 har bir keep-alive
so'rovini konsolga chiqarib, log'ni iflos
qilmaymiz

def start_keepalive_server():
    """Render (yoki shunga o'xshash
hostinglar) 'xizmat tirik' deb bilishi
    uchun kichik HTTP server ochadi. $PORT
Render tomonidan avtomatik beriladi."""
    try:
        port = int(os.environ.get("PORT",
"10000"))
        server = HTTPServer(("0.0.0.0",
port), _KeepAliveHandler)
        t =
threading.Thread(target=server.serve_foreve
r, daemon=True)
        t.start()
        _logger.info("🌐 Keep-alive HTTP
server %s portda ishga tushdi", port)
    except Exception as e:
        _logger.warning("Keep-alive HTTP
server ochilmadi (muhim emas): %s", e)

def _self_ping_loop():
    """Har 10 daqiqada botning o'z tashqi
manziliga (agar aniqlansa) so'rov
    yuboradi – Render'ning bepul tarifidagi
'uyquga ketish' vaqtini (~15 daqiqa
    faolsizlik) hech qachon to'ldirmaslik
uchun."""
    external_url = (

```

```

os.environ.get("RENDER_EXTERNAL_URL") #
Render web-service'lar uchun avtomatik
beriladi
    or os.environ.get("KEEPALIVE_URL",
    "").strip() # qo'lda ko'rsatilgan manzil
    (ixtiyoriy)
    )
    port = int(os.environ.get("PORT",
    "10000"))
    local_url = f"http://127.0.0.1:{port}/"
    while True:
        time.sleep(600) # 10 daqiqa
        url = external_url or local_url
        try:
            requests.get(url, timeout=15)
            # 🚫 Muvaffaqiyatli self-ping
        except Exception as e:
            # ! Faqat HAQIQIY muammo
            # bo'lsa (self-ping ishlamay qolsa) log
            # yoziladi –
            # bu ham bot egasiga Telegram
            # xabari sifatida YUBORILMAYDI, faqat
            # server logida qoladi, shunda
        else:
            # har 10 daqiqada
            # takrorlanaveradigan "tirik" xabari ortiqcha
            # shovqin
            # qilmasin uchun ataylab
            # o'chirilgan (faqat DEBUG darajasida qoladi,
            # standart INFO log darajasida
            # ko'rinmaydi).
            _logger.debug("Self-ping
            muvaffaqiyatli: %s", url)

```

```

ortiqcha Telegram xabarlari kelmaydi.
        _logger.warning("🌐 Self-ping
muvaffaqiyatsiz (%s): %s", url, e)

def start_self_ping_loop():
    t =
threading.Thread(target=_self_ping_loop,
daemon=True)
    t.start()

def _daily_menu_broadcast_loop():
    """🕒 Har kuni soat 07:00 da (Toshkent
vaqti, UTC+5) – botdagi BARCHA
ro'yxatdan o'tgan foydalanuvchilarga
BOSH MENYU avtomatik qayta yuboriladi
(kunlik 🎁 bonus, do'kon va h.k.ni har
kuni eslab, ko'rib turishsin deb)."""
    last_sent_date = None
    while True:
        try:
            now_tashkent =
time.gmtime(time.time() + 5 * 3600) # 🕒
UTC+5, DST yo'q
            today_str = time.strftime("%Y-
%m-%d", now_tashkent)
            if now_tashkent.tm_hour == 7
and last_sent_date != today_str:
                last_sent_date = today_str
                with db_lock:
                    cur.execute("SELECT
user_id FROM users")
                    user_ids = [r[0] for r

```

```

in cur.fetchall()]
        sent, failed = 0, 0
        for target_uid in user_ids:
            try:
                bot.send_photo(
                    target_uid,
                    MAIN_PHOTO,
                    caption="🌅

<b>Xayrli tong!</b> Yangi kun
boshlandi!\n\n"

"🌙

<b>Hunter Mafia</b> – bosh menyu\n\n"

"🎁

Kunlik bonusingizni olishni
unutmang!\n\nKerakli bo'limni tanlang 📌",

reply_markup=get_main_menu(None,
target_uid),

                )
                sent += 1
            except Exception:
                failed += 1
                _logger.info("🕒 Kunlik
soat 07:00 bosh menyu tarqatildi: %s ta
muvaffaqiyatli, %s ta yetib bormadi.",
sent, failed)
            except Exception as e:

_logger.warning("_daily_menu_broadcast_loop
xatolik: %s", e)
                time.sleep(60) # 🕒 har daqiqada
soat 07:00 bo'lganini tekshiradi

```

```

def start_daily_menu_broadcast_loop():
    t =
    threading.Thread(target=_daily_menu_broadca
st_loop, daemon=True)
    t.start()

#
=====
=====
# ISHGA TUSHIRISH
#
=====
=====

if __name__ == "__main__":
    print("Hunter Mafia bot v5 (telebot,
do'kon + Stars + promo + tarqatish + qora
bozor + klan jangi) ishga tushmoqda...")
    start_keepalive_server() # 🌐 Render
"xizmat tirik" deb bilishi uchun – ENG
BIRINCHI ishga tushiriladi
    start_self_ping_loop() # 🌐 har 10
daqiqada o'ziga so'rov – Render uxlab
qolmasin deb
    with db_lock:
        cur.execute("SELECT COUNT(*) FROM
users")
        _existing_users = cur.fetchone()[0]
        _logger.info(f"📁 Baza fayli:
{DB_PATH}")
        _logger.info(f"👥 Bazadagi mavjud
foydalanuvchilar soni: {_existing_users}

```

```

ta")
    if _existing_users == 0 and
_users_table_existed is False:
        _logger.warning("⚠ Bu – 'users'
jadvali birinchi marta yaratilyapti
(yangi/bo'sh baza). Agar avval "
                        "foydalanuvchilar
bo'lgan bo'lsa, bot boshqa papkadan yoki
boshqa hunter_mafia.db "
                        "fayli bilan ishga
tushirilayotgan bo'lishi mumkin – DB_PATH
qatorini tekshiring.")
        # 🔒 BITTA NUSXA QULFI (single-instance
lock): agar shu skript allaqachon shu
        # papkada ishga tushirilgan bo'lsa
(masalan avvalgi jarayon to'liq o'chmagan,
        # yoki kimdir uni ikkinchi marta ishga
tushirib yuborgan bo'lsa), bu yerda
        # DARHOL to'xtaydi va aniq xabar beradi
– Telegram tomonidan qaytariladigan
        # tushunarsiz "409 Conflict" xatoligi
o'rniga.
        _LOCK_PATH =
"/tmp/hunter_mafia_bot.lock"
        try:
            import fcntl
            _lock_fh = open(_LOCK_PATH, "w")
            fcntl.flock(_lock_fh, fcntl.LOCK_EX
| fcntl.LOCK_NB)
            _lock_fh.write(str(os.getpid()))
            _lock_fh.flush()
        except BlockingIOError:
            print(
                "❌ Bot allaqachon ishga

```

```

tushirilgan (boshqa jarayon shu bot tokeni
bilan "
    "polling qilyapti)! Avval eski
jarayonni to'xtating (masalan: "
    "`pkill -f hunter_mafia` yoki
serverdagi eski deploy/screen/pm2
sessiyasini "
    "yopib qo'ying), keyin qayta
ishga tushiring. Bot ishga tushmaydi."
)
sys.exit(1)
except Exception as _lock_err:
    # fcntl mavjud bo'lmagan tizimlarda
(masalan Windows) qulf o'tkazib yuboriladi
-
    # bu holatda faqat webhook/eski-
session tekshiruvi ishlaydi.
    _logger.warning("Instance-lock
o'rnatilmadi (muhim emas): %s", _lock_err)

# 🛠 Eski WEBHOOK (agar avval webhook
rejimida ishlatilgan bo'lsa) yoki Telegram
# tomonida "osilib qolgan" eski
ulanishni tozalab, keyin polling'ni
boshlaymiz -
    # bu ham 409 Conflict xatoligining keng
tarqalgan sababi.
    try:
        bot.remove_webhook()
        time.sleep(1)
    except Exception as _wh_err:
        _logger.warning("Webhook tozalashda
xatolik (muhim emas): %s", _wh_err)

```

```

_state_restored = False
_consecutive_conflicts = 0
while True:
    try:
        BOT_USERNAME =
bot.get_me().username
        _logger.info("Bot ishga tushdi:
@%s", BOT_USERNAME)
        if not _state_restored:
            # 🔄 oldingi ishga
tushishda (xatolik/deploy/`/tiklash`)
saqlangan aktiv
            # o'yinlar bo'lsa, shu
yerda tiklanadi – faqat 1 marta, tarmoq
uzilib
            # qayta ulanganda emas
(chunki fayl birinchi muvaffaqiyatli
tiklashda o'chiriladi).
            load_games_state()
            _state_restored = True
            _check_clan_inactivity() #
🏠 klan faolsizlik tekshiruvini fon
rejimida ishga tushiramiz

set_bot_commands_for_all_scopes() # 📋 3
xil buyruqlar menyusini
(guruh/shaxsiy/owner) o'rnatish
            start_auto_backup_loop() #
💾 #6: har 24 soatda avtomatik zaxira nusxa
            start_freeze_watchdog() #
🧊 bot muzlab qolsa – o'zini avtomatik
qayta ishga tushiradi

start_daily_menu_broadcast_loop() # 🕒 har

```



```

kuni soat 07:00'da barchaga bosh menyu

bot.infinity_polling(skip_pending=True,
timeout=30, long_polling_timeout=30)
    _consecutive_conflicts = 0
except
telebot.apihelper.ApiTelegramException as
e:
    if getattr(e, "error_code",
None) == 409 or "409" in str(e) or
"Conflict" in str(e):
        # 🚫 409 = boshqa bir nusxa
HALI HAM shu tokendan foydalanib polling
        # qilyapti. Tez-tez qayta
urinish faqat vaziyatni yomonlashtiradi –
        # shuning uchun har safar
sal uzoqroq kutamiz (progressiv orqaga
        # chekinish), bosh
ko'rsatiladigan xatolik xabarlarini sonini
kamaytiradi.
        _consecutive_conflicts += 1
        wait_s = min(60, 10 *
_consecutive_conflicts)
        _logger.warning(
            "⚠️ 409 Conflict: shu
bot tokeni bilan BOSHQA bir nusxa polling "
            "qilyapti (ehtimol eski
jarayon o'chirilmagan). %s soniya kutib, "
            "qayta urinilmoqda...",
wait_s,
        )
        time.sleep(wait_s)
    else:
        _logger.exception("Telegram

```

```
API xatoligi, 5 soniyadan keyin qayta
urinilmoqda: %s", e)
        time.sleep(5)
    except Exception as e:
        # Tarmoq uzilishi yoki Telegram
API vaqtinchalik ishlamay qolishi kabi
hollarda
        # bot butunlay o'chib qolmasin
– 5 soniya kutib qayta ulanadi.
        _logger.exception("Polling
to'xtadi, 5 soniyadan keyin qayta
urinilmoqda: %s", e)
        time.sleep(5)
```