



Blog / [Solana Hello World \(Installation and Troubleshooting\)](#)

Solana Hello World (Installation and Troubleshooting)



Hello World

 **RareSk**

This is a Solana hello world tutorial. We will walk you through the steps to install Solana and troubleshoot issues that may arise.

If you encounter an issue, please check the Troubleshooting section at the end of this article.

Install Rust

Skip this if you already have Rust installed.

```
# install rust
curl --proto '=https' --tlsv1.2 -sSf https://sh.rustup.rs | sh
```

[Copy](#)

Install Yarn

You will need this to run the unit tests. Skip this if you already have yarn installed.

```
# install yarn -- assumes node js is installed
corepack enable # corepack comes with node js
```

[Copy](#)

Install the Solana cli and Anchor

```
# install solana
curl --proto '=https' --tlsv1.2 -sSfL https://solana-
install.solana.workers.dev | bash
```

[Copy](#)

Install Anchor

```
# install anchor
cargo install --git https://github.com/solana-foundation/anchor avm -
-force
avm install latest
avm use latest
```

[Copy](#)

Testing the installation

Initialize and build an Anchor Program (for hello world)

Mac users: we recommend calling your program `day_1` instead of `day1` because Anchor seems to silently insert underscores on Mac machines sometimes.

```
anchor init day1 # use day_1 if you have a mac
cd day1
anchor build
```

[Copy](#)

Depending on your machine and internet connection, this step may take a while. This is also where you are likely to run into installation problems, so please see the troubleshooting section if necessary.

```
solana config set --url localhost
```

Run the test validator node

Run the following command in a new shell, not in the Anchor project. But do not close the shell where you ran `anchor build`. This is running a local (test) Solana node instance on your machine:

```
# shell 2
```

Copy

```
solana-test-validator
```

Ensure the program_id is synced with the Anchor key

Go back to the shell with the Anchor project and run the following command:

```
# shell 1
```

Copy

```
anchor keys sync
```



```
# shell 1
```

Copy

```
anchor test --skip-local-validator
```

The command above runs the test for our program. If you have not already created a test wallet, Anchor will give you instructions for how to do so. We do not provide those instructions here because it will be dependent on your OS and file structure. You may also need to airdrop yourself some local Sol by running `solana airdrop 100 {YOUR_WALLET_ADDRESS}` in the terminal. You can get your wallet address by running `solana address` in the command line.

The expected output is as follows:

```
day_1
Your transaction signature 3bJH3A41cFYdry2JcrAm7QkJcXHEQHE2JY2iwWZcVCixzKgwz5LzotvgXzUzqCje2aFasZ6kqr7RBd6
eMoXweFCf
  ✓ Is initialized! (212ms)

1 passing (214ms)

🌟 Done in 2.97s.
```

Hello World

Now let's make our program output "Hello, world!". Add the following line marked with `****NEW LINE HERE****` to `programs/day_1/src/lib.rs`.

```
use anchor_lang::prelude::*;
```

[Courses](#) ▾[Blog](#)[Testimonials](#)[Web3 Jobs](#)[Pricing](#)[Copy](#)[Apply Now](#)

```
declare_id!("...");
```

```
#[program]
```

```
pub mod day_1 {
```

```
    use super::*;
```

```
    pub fn initialize(ctx: Context<Initialize>) → Result<()> {
```

```
        msg!("Hello, world!"); // **** NEW LINE HERE ****
```

```
        Ok(())
```

```
    }
```

```
}
```

```
#[derive(Accounts)]
```

```
pub struct Initialize {}
```

Before running the test again, kill the local validator process and restart it with:

```
solana-test-validator --reset
```

[Copy](#)

On This Page

[Installation steps](#)[Testing the installation](#)

Run the test again

```
anchor test --skip-local-validator
```

[Copy](#)

Hello World

RareSkills

Realtime Solana logs

Questions and Answers

Troubleshooting

Learn more with RareSkills

Find the log file by running

ls .anchor/program-logs/

Courses

Blog

Testimonials

Web3 Jobs

Pricing



Apply Now

Open that file to see the logged "Hello world"

```
(base) → day_1 git:(main) ✗ cat .anchor/program-logs/D9Bks8Miko6tT7XRnM5Kocd3vY6PvSXT6phFunu5ZKjh.day_1.log
Streaming transaction logs mentioning D9Bks8Miko6tT7XRnM5Kocd3vY6PvSXT6phFunu5ZKjh. Confirmed commitment
Transaction executed in slot 1182:
  Signature: 2Pv7HbJHTy6KLSjzQ4JZNr7eXSXzKmN1gen4LSvh1UTt6DMwMV4EHrq4jc2n2bXVCrHoYoU9tNfeVQaRQZjdkgnF
  Status: Ok
  Log Messages:
    Program D9Bks8Miko6tT7XRnM5Kocd3vY6PvSXT6phFunu5ZKjh invoke [1]
    Program log: Instruction: Initialize
    Program log: Hello, world!
  Program D9Bks8Miko6tT7XRnM5Kocd3vY6PvSXT6phFunu5ZKjh consumed 385 of 200000 compute units
  Program D9Bks8Miko6tT7XRnM5Kocd3vY6PvSXT6phFunu5ZKjh success
```

Realtime Solana logs

Alternatively, you can view the logs as they happen by opening a third shell and running:

```
# shell 3
```

```
solana logs
```

Copy

Now run the test again, and you should see the same message in the terminal where you ran `solana logs`.

Questions and Answers

In Rust, the exclamation point indicates that these are macros. We will revisit macros in a later tutorial.

Do I need an initialize function?

No, that was autogenerated by the Anchor framework. You could name it whatever you like.

There is nothing special about the name `initialize` in this context, and so we can change the name to whatever we like. This is unlike some other keywords and languages, like how `main` is a special name in some languages, or how `constructor` is a special name in Solidity.

Exercise: Try renaming `initialize` in `programs/day_1/src/lib.rs` and `initialize` in `tests/day_1.ts` to become `initialize2` and run the test again. See the change marked in the **orange circles** below.

```
use anchor_lang::prelude::*;
declare_id!("Fg6PaFpoGXkYsidMpWTK6N2Be27FefcYkg476zPFsLnS");

#[program]
pub mod day_1 {
    use super::*;

    pub fn initialize2(tx: Context<Initialize>) -> Result<> {
        Ok(())
    }
}

#[derive(Accounts)]
pub struct Initialize {}

-

import * as anchor from "@project-serum/anchor";
import { Program } from "@project-serum/anchor";
import { Day1 } from "../target/types/day_1";

describe("day_1", () => {
    // Configure the client to use the local cluster.
    anchor.setProvider(anchor.AnchorProvider.env());

    const program = anchor.workspace.Day1 as Program<Day1>;

    it("Is initialized!", async () => {
        // Add your test here.
        const tx = await program.methods.initialize2().rpc();
        console.log("Your transaction signature", tx);
    });
});
```



Why do we run the test with `--skip-local-validator`?

When the tests run against a node, we will be able to query the node for state changes. If you are not able to get the node to run, it is okay to run `anchor test` without the `--skip-local-validator` flag. However, you will have a harder time developing and testing, so we recommend getting the local validator to work.

Troubleshooting

Solana is a rapidly developing software, and you may run into installation issues. We've documented the ones you are most likely to encounter the following sections.

Our tutorial series was written with the following versions:

- Anchor = version 0.29.0
- Solana = version 1.16.25
- Rustc = 1.77.0-nightly

You can change the Anchor version by running:

```
avm install 0.29.0
avm use 0.29.0
```

[Copy](#)

error: package solana-program v1.18.0 cannot be built

```
error: package `solana-program v1.18.0` cannot be built because it
requires rustc 1.72.0 or newer, while the currently active rustc version
```

[Copy](#)

Check the version of Solana you are running using `solana --version`. Then plug that version into the `ver` above. An example resolution is shown below:

```
(base) ➔ wat git:(main) ✖ anchor build
error: package `solana-program v1.18.0` cannot be built because it requires rustc 1.72.0 or newer, while the currently active rustc
version is 1.68.0-dev
Either upgrade to rustc 1.72.0 or newer, or use
cargo update -p solana-program@1.18.0 --precise ver
where `ver` is the latest version of `solana-program` supporting rustc 1.68.0-dev
(base) ➔ wat git:(main) ✖ solana --version
solana-cli 1.16.25 (src:8dd7d060; feat:2294205250, client:SolanaLabs)
(base) ➔ wat git:(main) ✖ cargo update -p solana-program@1.18.0 --precise 1.16.25
warning: virtual workspace defaulting to `resolver = "1"` despite one or more workspace members being on edition 2021 which implies
`resolver = "2"``
```

error[E0658]: use of unstable library feature 'build_hasher_simple_hash_one'

If you get the following error:

```
error[E0658]: use of unstable library feature
'build_hasher_simple_hash_one'
→ src/random_state.rs:463:5
|
463 | / fn hash_one<T: Hash>(&self, x: T) → u64 {
464 | | RandomState::hash_one(self, x)
465 | | }
| |_____^
|
= note: see issue #86161 https://github.com/rust-lang/rust/issues/86161
for more information
```

[Copy](#)

Run the following command: `cargo update -p ahash@0.8.7 --precise 0.8.6`.

Credit: <https://solana.stackexchange.com/questions/8800/cant-build-hello-world>

Error: Deploying program failed: Error processing Instruction 1: custom program error: 0x1

```
Error: Deploying program failed: Error processing Instruction 1: custom
program error: 0x1
There was a problem deploying: Output { status:
ExitStatus(unix_wait_status(256)), stdout: "", stderr: "" }.
```

Copy

If you get this error, your keys are not synced. Run `anchor keys sync`.

Error: failed to send transaction: Transaction simulation failed: Attempt to load a program that does not exist

Your keys are not synced. Run `anchor keys sync`.

Error: Your configured rpc port: 8899 is already in use

You ran `anchor test` without `--skip-local-validator` while the validator is running in the background. Either turn off the validator and run `anchor test` or run `anchor test --skip-local-validator` with the validator running. Skip local validator

Error: Account J7t...zjK has insufficient funds for spend

Run the command below to airdrop 100 SOL to your development address:

```
solana airdrop 100 J7t...zjK
```

[Copy](#)

Error: RPC request error: cluster version query failed

```
Error: RPC request error: cluster version query failed: error sending
request for url (http://localhost:8899/): error trying to connect: tcp
connect error: Connection refused (os error 61)
There was a problem deploying: Output { status:
ExitStatus(unix_wait_status(256)), stdout: "", stderr: "" }.
```

[Copy](#)

This means the `solana-test-validator` is not running in the background. Run `solana-test-validator` in another shell.

thread 'main' panicked at 'called Option::unwrap() on a None value'

```
thread 'main' panicked at 'called `Option::unwrap()` on a `None` value',
/Users/username/.cargo/git/checkouts/anchor-
50c4b9c8b5e0501f/347c225/lang/syn/src/idl/file.rs:214:73
```

[Copy](#)

It's likely you didn't run `anchor build` yet.

I'm using Mac and I get Error: failed to start validator: Failed to create ledger at test-ledger: blockstore error

Follow the instructions in this [Stack Exchange thread](#).

I don't have corepack on my Mac despite having node.js

Run the following commands:

```
brew install corepack  
brew link --overwrite corepack
```

Copy

Credit: <https://stackoverflow.com/questions/70082424/command-not-found-corepack-when-installing-yarn-on-node-v17-0-1>

error: not a directory:

```
BPF SDK: /Users/rareskills/.local/share/solana/install/releases/stable-  
43daa37937907c10099e30af10a5a0b43e2dd2fe/solana-release/bin/sdk/bpf  
cargo-build-bpf child: rustup toolchain list -v  
cargo-build-bpf child: rustup toolchain link bpf
```

Copy

```
/Users/rarekills/.local/share/solana/install/releases/stable-43daa37937907c10099e30af10a5a0b43e2dd2fe/solana-release/bin/sdk/bpf/dependencies/bpf-tools/rust
error: not a directory:
```



clear the cache: run `rm -rf ~/.cache/solana/*`.

Error: target/idl/day_1.json doesn't exist. Did you run anchor build?

Create a new project and name it day_1 instead of day1. Anchor seems to silently insert underscores on some machines.

Learn more with RareSkills

This tutorial is the first in our free [Solana Course](#).

Originally Published February, 08, 2024

RareSkills Looking For An Audit? RareSkills Leverage our extensive network of top security specialists. Get A Quote	YieldNest CoursesBlogTestimonialsWeb3 JobsPricing Senior Smart Contract Engineer Join YieldNest as a Senior Smart Contract Engineer to architect and deploy... Apply Now	Foreverlong Backend Engineer Join us as a Full Stack Developer to architect and ship a... Apply Now	MONAD Senior Engineer looking for a Senior Frontend Engineer who lives and breathes interface quality... Apply Now
---	--	---	--

Join Our Newsletter

Occasional updates straight to your inbox. No spam.

Your email address

Subscribe



The Web3 education platform trusted by industry-leading developers and auditors.



- Blog

Testimonials

Web3 Jobs
- Learn Solidity

60 Days of Solana

ZK Book
- Events

Contact

