

Codexa initialization portability

PR summary • tracked wiring stays clean across linked worktrees

Project	codexa
Checkout	isolated Codexa task worktree
Branch	codex/backend/codexa-20260719-codexa-portable-tracked-init
Base	main at adc1e65
Subject	fix(init): keep tracked wiring clean across worktrees

Problem

codexa `init` embedded an absolute checkout path in generated `.codex/config.toml`, `.codex/hooks.json`, and `.mcp.json` wiring. When a team intentionally tracked those files, initializing a linked worktree rewrote them for the new path and made a freshly created worktree appear dirty. The index report could therefore say the tree was clean immediately before bootstrap changed tracked files.

Resolution

- Tracked wiring omits the checkout argument and resolves the active Git root at process startup; untracked host-local wiring keeps its explicit absolute path.
- Codex lifecycle commands resolve from their session cwd, while Claude MCP launches honor its validated `CLAUDE_PROJECT_DIR` contract.
- Linked worktrees retain a stable MCP server name derived from the shared Git directory, and Claude-only tracked wiring preserves its existing name and core/full tool profile.
- Requested `.mcp.json` content is parsed before any other wiring changes, so a malformed shared config cannot leave initialization half-applied.
- Generated text is written only when bytes change, including repeated `--no-hooks` initialization with remaining team-owned hooks.

Source Commits

- 1062fa8 — fix(init): keep tracked wiring portable across worktrees
- e70a8a0 — fix(cli): honor Claude project roots
- e814b14 — fix(init): preserve Claude-only wiring
- fa83ee9 — fix(init): avoid stable hook rewrites

Verification

- `npm run check` passed: source/release/privacy gates, 28 Claude command smokes, 89 Claude hook smokes, and 905 Vitest tests passed with 1 intentional skip.
- Focused initialization, hook, and MCP suites passed: 62 of 62 tests.
- A real linked-worktree smoke migrated tracked wiring once, committed it, then reran initialization and lifecycle commands from a nested directory with a clean Git status before and after.
- The shared worktree-helper self-test passed after adding the board prose synchronization regression.
- Two independent adversarial confirmation reviews of `origin/main...HEAD` reported no actionable findings; one explicitly checked bloat, idempotence, and partial-write behavior.

Operational Notes

Existing repositories that track absolute Codexa wiring require one intentional migration commit. After that commit, future linked-worktree initialization is byte-stable and Git-clean. Repositories with untracked wiring retain their prior host-local behavior and explicit checkout path.

The host workspace's companion board helper was corrected and regression-tested separately so changing its default repository also refreshes stale default/focus prose. That host-local helper is not part of this repository diff.

Rollback is a normal revert of the four source commits. That restores the old absolute-path behavior and therefore also restores the linked-worktree dirtying failure for tracked wiring.