



WEX OTR Card Management Web Service

Reference

July 2024 – Version 12.0

Disclaimer

Although the information contained herein has been carefully verified, Electronic Funds Source LLC (EFS) assumes no responsibility for errors that might appear in this document or for damage to property or persons resulting from improper use of the software. EFS reserves the right to change the contents and form of this document, as well as the features and specifications of its products, at any time without notice. The information in this publication does not represent a commitment on the part of EFS.

This document contains proprietary information that is protected by copyright. All rights are reserved. No part of this document may be photocopied, reproduced, or translated into another language without the prior written consent of EFS.

Contact Information

Electronic Funds Source LLC
1104 Country Hills Drive
Suite 600
Ogden, UT 84403

Toll-Free Support: 1-888-824-7378

Trademarks

All trademarks appearing in this document, whether or not bearing the trademark symbol, are the property of their respective owners.

Electronic Funds SourceSM is a service mark of Electronic Funds Source LLC.

Copyright

© 2017 Electronic Funds Source LLC

Contents

Card Management Web Service Overview	8
Accessing EFS Web Services	8
New Soap Web Services	8
Old Soap Web Services	8
Security Updates	9
Authentication.....	9
Timestamps	10
Tips on Using Web Service Methods.....	11
Using Web Service Methods.....	11
Datetime Format:	11
Pulling Transactional Data	11
Requests for longer periods may time out (the server stores 15 minutes of data in memory)..	11
Pull a maximum of 7 days of data at once.....	11
Excessive polling may lead to account suspension by WEX IT.....	11
Implement a daily check to ensure all transactions from the previous day are received.	11
Use transaction IDs (unique identifiers) for verification.....	11
Parent/Child Methods	11
Description of Each Web Service Method (alphabetical).....	12
Add Location Group Locations	12
Cancel Pending Transfer	13
Create and Submit Order.....	14
Create Info Limit Card	16
Create Location Group.....	17
Create New Policy.....	18
Create New Site Policy	19
Create Order.....	20
Create SmartPay Scheduled Transfer	22
Create SmartPay Transfer Account	24
Delete Info Limit Card	25
Delete Order.....	26
Delete Override.....	27
Delete SmartPay Scheduled Transfer	28
Delete SmartPay Transfer Account	29
Do SmartPay ACH Transfer.....	30
Does Card Position	31
Find Orders.....	32
Get Allowed Order Types.....	34
Get Card.....	35
Get Card Version 2	38

Get Card by Driver ID	41
Get Card Descriptions	42
Get Card Refreshing Limits	43
Get Card Summaries.....	44
Get Card Summaries V2	45
Get Cards With No Driver ID	46
Get Carrier Info	47
Get Cash History	48
Get Child Transactions	50
Get Child Transactions New (Preferred)	51
Get Child Transaction Rejects.....	52
Get Contracts	53
Get Credit Limits	54
Get Current Cash All Amounts	55
Get Current Cash Amounts.....	56
Get Current Payroll Cash Amounts	57
Get Geographic Price Locations	58
Get Interstate Price Locations	59
Get Last Mileage	60
Get Location Group Descriptions.....	61
Get Location Group Locations.....	62
Get Location Group Rule	63
Get Location Groups	64
Get Mobile Roles	65
Get Money Code.....	66
Get Money Code V2	67
Get Money Code By ID.....	69
Get Money Code Use	71
Get Money Code Use V2	73
Get Money Codes	74
Get Money Codes V2	75
Get One Carrier Child Transaction	76
Get Order.....	77
Get Order Cards	78
Get Order Choices	79
Get Order Styles.....	80
Get Order Types.....	81

Get Payroll Cash History	82
Get Payroll Cash History for all cards.....	83
Get Policy.....	84
Get Policy Descriptions	86
Get Policy Refreshing Limits	87
Get Product Groups.....	88
Get Products.....	89
Get Prompt Types.....	90
Get Registered Checks	91
Get Site Policy Descriptions	93
Get SmartPay Driver	94
Get SmartPay Scheduled Transfers.....	95
Get SmartPay Transfer Accounts.....	96
Get Transaction Locations	97
Get Transaction Locations for Card	99
Get Transaction Locations for Policy	101
Get Transactions	103
Get Transactions Extended	104
Get Transactions Extended Locations.....	105
Get Transactions Preferred	106
Get Transactions Rejects	107
Issue Money Code	109
Issue Money Code with Prompts	110
Issue New Payroll Card	111
Issue New Personalized Payroll Card.....	112
IVR Login	113
Load Cash [by card number]	114
Load Cash Version 2	115
Load Cash by Driver ID	116
Load Cash by Driver ID Version 2	117
Login	118
Logout.....	119
Managed Fuel Action	120
Managed Fuel Action by Driver	121
Money Code Summary	122
Override Last Mileage	123
Pull Carrier Gets Discount Data.....	124

Register Card Position	125
Register Check	126
Reissue Damaged Card	127
Remove Card	128
Remove Location Group	129
Remove Location Group Locations.....	130
Replace Lost or Stolen Card	131
Search Location.....	132
Server Time.....	133
Set Card	134
Set Card Version 2	137
Set Card PIN	140
Set Card Refreshing Limits.....	141
Set Carrier Discount.....	142
Set Location Group Locations	143
Set Location Group Rule	144
Set Moneycode Bill On Issue.....	145
Set Policy	146
Set Policy Refreshing Limits.....	148
Set Site Policy.....	149
Set SmartPay Driver.....	150
Set SmartPay Transfer Account.....	151
Sign Up Scale	152
SmartPay Transfer History	153
Stop Order	154
Submit Order.....	155
Transaction Summary.....	156
Transfer Card	157
Update Order	158
Update Order Cards	159
Validate Card	160
Verify SmartPay Transfer.....	161
Verify User	162
Void Money Code.....	163
Appendix A. Reference Tables	164
Code Tables.....	164
Auto Roll Map	164
Category Codes	164

Chain Id's	166
Country Codes	167
Discount Types.....	167
Fuel Types.....	168
Info IDs	168
Limit IDs.....	169
Location Amenities	171
Tax IDs	172
Transaction Types	173
Transaction Metas.....	173
WSLineTaxes.....	176
WSMoneyCode	177
WSMoneyCodeHistRec	178
WSMoneyCodeHistRecV2.....	179
WSMoneyCodeHistUse	180
WSTransaction	181
WSTransactionExt	184
WSTransactionExtv2	187
WSTransactionInfo	190
WSMetadata.....	191
WSTransactionLocation.....	192
WSTransactionLineItem	193
Overrides	194
Location Types	195
Shipping Methods	197
Card Order Property Keys.....	198
Update History	200

Card Management Web Service Overview

Customers and vendors can use the EFS LLC Card Management Web Service to integrate real-time with the EFS LLC card, money code, and transaction system.

Features:

- Integrate with EFS cards, money codes, and transactions.
- Real-time access to data

Accessing EFS Web Services

New Soap Web Services

The web services are implemented as soap web services.

The wsdl for the QA/test web service can be found at:

<https://ws.partner.efslc.com/axis2/services/CardManagementWS?wsdl>

The wsdl for the production web service can be found at:

<https://ws.efslc.com/axis2/services/CardManagementWS?wsdl>

The endpoint URLs for each environment are as follows:

<https://ws.partner.efslc.com/axis2/services/CardManagementWS/>

<https://ws.efslc.com/axis2/services/CardManagementWS/>

Client Code Generation: Many tools are available to generate and test client code in various languages (e.g., SoapUI).

Old Soap Web Services

The web services are implemented as soap web services.

The wsdl for the QA/test web service can be found at:

<https://test.efslc.com/richapp/Wsdl.action?wsdl=/axis2/services/CardManagementWS>

The wsdl for the production web service can be found at:

<https://ws.efslc.com/richapp/Wsdl.action?wsdl=/axis2/services/CardManagementWS>

The endpoint URLs for each environment are as follows:

<https://test.efslc.com/axis2/services/CardManagementWS/>

<https://ws.efslc.com/axis2/services/CardManagementWS/>

Security Updates

- **SSL/TLS Versions:** EFS LLC uses TLS for secure communication. Clients **must support TLS 1.2 or higher**.
- **Certificate Rotation:** We regularly rotate certificates without prior notice. Clients must be able to handle this by updating their trusted key stores to support new certificates and revocations.
- **Certificate Pinning:** **Do not pin** to specific certificates. Support industry-standard Certificate Authorities (CAs) and update trusted key stores regularly.
- **Certificate Revocation:** Clients must support certificate revocation to ensure communication with valid servers.

Authentication

- This web service uses custom login/logout methods instead of standard HTTP authentication.
- Login returns a token (clientId) used for subsequent calls.
- Logout invalidates the token. Re-login is required for further use.

Error Handling

- Unsuccessful calls return a SoapFault.
- Successful calls may or may not return a specific response ("no news is good news").
- Common error messages:
 - InvalidClientId: Expired token. Re-login required.
 - InvalidParameterNameID: Incorrect parameter value. Correct and retry.
 - NotAllowed: Access blocked by firewall. Contact your account manager.
- Method-specific errors are documented in the "Error Messages" section.

API Error Handling Best Practices:

This document outlines best practices for handling various API errors:

Types of Errors

- **Transient Faults:** Network or server issues (e.g., timeouts, connection issues). Retry after a brief wait.
- **Timeouts:** Server response delays. Retry after a reasonable wait.
- **Client Errors:** Invalid requests (e.g., missing data, incorrect format). Fix and resend.
- **Server Errors:** Internal server issues. It may require support team intervention. Retry after a longer wait.
- **Application Errors:** Business logic or data validation errors. Fix the request and resend.

Determining Retriable Errors

Use HTTP status codes and error messages.



- 4xx errors (except 429) are client errors (not retrievable).
- 429 (Rate Limit Exceeded): Retry after a waiting period.
- 5xx errors are server errors (potentially retrievable).

Choosing a Retry Strategy

- Exponential Back-off: Increase wait time between retries exponentially (e.g., 1s, 2s, 4s).
- Incremental Intervals: Increase wait time by a fixed amount between retries (e.g., 1s, 2s, 3s).
- Exponential Back-off with Jitter: Combine exponential back-off with random wait time to avoid synchronized retries.

Avoiding Common Pitfalls

- Don't retry immediately to prevent overloading the service.
- Set a limit on retries and implement a fallback mechanism.

HTTP Cookies

Clients should support HTTP cookies for secure and efficient communication:

- **Industry-Standard Cookie Handling:** Adhere to RFC 6265 for cookie creation, management, and expiration.
- **Cookie Jars for Session Isolation:** Implement cookie jars to isolate sessions for each customer/user. This allows network security appliances to manage sessions anonymously. Network security appliances may block all sessions if they cannot isolate abusive users.

Timestamps

All of our servers are central time. Some soap proxy generators are not very good at dealing with timestamps so the web service developer should be careful to note that they are dealing with timestamps correctly.

Tips on Using Web Service Methods

Using Web Service Methods

- **Login**- Obtain a clientId for authentication
- 1. **Session Management**- Client IDs expire daily (around 3:00 AM CT).
 - Use try/catch blocks to handle expired sessions and retry with a new login.
 - Don't use infinite loops for retries in case of network errors.

Datetime Format:

ISO 8601 format (yyyy-mm-ddThh:mm:ss-[zz:zz](#)) is used for datetime fields (e.g., 2017-10-25T23:30:59-06:00).

ISO format is used for datetime fields:

yyyy-mm-ddThh:mm:ss-[zz:zz](#)

Where [-zz:zz](#) is the optional timezone

Pulling Transactional Data

EFS recommends pulling data every 1-15 minutes for optimal performance.

Requests for longer periods may time out (the server stores 15 minutes of data in memory).

Pull a maximum of 7 days of data at once.

Excessive polling may lead to account suspension by WEX IT.

Implement a daily check to ensure all transactions from the previous day are received.

Use transaction IDs (unique identifiers) for verification.

Parent/Child Methods

Most parent/child methods are available through the EFS LLC Carrier Group Parent/Child WS (refer to its documentation).

Card Management WS provides only these related methods:

Get Child Transaction Rejects

Get Child Transactions

Get One Carrier Child Transaction

Description of Each Web Service Method (alphabetical)

Add Location Group Locations

Adds locations to an existing location group on the carrier.

addLocGrpLocs

Input

clientId	string (32)	The client ID from the login response
groupId	Int	The group Id created in the method add location groups.
loc	Array	An array of 1 to many location ids. Make sure you use valid 6 digit EFS LLC location ids in your input for a valid result.

Output

If the request was successful then the call will just return a result set with no return values. If there was an error a fault will be returned.

Error Messages

- A fault string or flying j exception error.

Cancel Pending Transfer

Cancels a pending SmartFunds ACH or wire transfer.

cancelPendingTransfer

Input

clientId	string (32)	The client ID from the login response
ppdDetailId	string (30)	The ID of the transfer that is being cancelled

Output

If the request was successful then the call will just return a result set with no return values. If there was an error a fault will be returned.

Error Messages

- A fault error or flying j exception error may be returned.
- InvalidppdDetailId = invalid payment ID.

Create and Submit Order

This method allows the system to create card orders for EFS LLC cards.

createAndSubmitOrder

Input

clientId	string (32)	The client ID from the login response
policyNumber	int(3)	The policy # for the cards being ordered on. Policy #1 is the most commonly used policy but you can use any policy that you have set-up on the carrier.
orderType		Please talk to your EFS rep for the orderType
cardStyle	Int	Please talk to your EFS rep for cardStyle **ccb_style_options for Order Type and Card Style combos
orderQty	Int	The number of cards being ordered
embossedName	string (25)	The embossed name on the card – reminder only certain # of characters will fit on the front of the card. If you have a custom card style, test to see how many characters will print.
shipToFirst	string(30)	Ship to contact first name
shipToLast	string(30)	Ship to contact last name
shipToAddress1	string(30)	Ship to address line 1
shipToAddress2	string(30)	Ship to address line 2
shipToCity	string(30)	Ship to city
shipToState	string(2)	State or Provincial abbreviation
shipToZip	String(10)	The ship to zip or postal code
shipToCountry	string(3)	Shipping country code – USA or CAN
shippingMethod	Int	See the shipping method index . NOTE: There may be fees associated with certain shipping methods.
rushProcessing	char(1)	Y – Rush N – Standard NOTE: there may be fees associated with rush orders.
cardCarrier	char(1)	Y – Yes indicates the card will come with a card carrier (MasterCard) N – No indicates the cards will not come with card carriers.
Props		See the array of Properties . The EFS LLC implementation/integration team will need to provide the list of property values.
Cards	Array	The array of cards being created. Idx starts at 0 for the first card in the order and up to the order quantity.
Props	Array	The props for the individual cards.

Output

cardOrderID	long	The card order ID created by the system for the card order.
RequestStatus	object	If there is an error, the error code and description

Error Messages

- A fault error, flying j exception error or error with an error # and description.

Create Info Limit Card

Creates a virtual card with limits that can be tied to a driver's card with a trip number. When a driver is linked to a trip card, purchases will pull from that virtual card.

createInfoLimitCard

Input

clientId	string (32)	The client ID from the login response
policyNumber		Policy number to assign trip card
infolId		The prompt ID (TRIP)
reportValue		Trip number

Output

cardNumber		Info limit card number
------------	--	------------------------

Error Messages

- A fault error, a flying j exception error or an error returned with an error # and description.

Create Location Group

Creates a new location group for the customer. Once you create a location group, you can add locations to the group. Then the location group can be added to a policy or card.

The location group related operations are: getLocationGroupDescriptions, createLocGrp, removeLocGrp, getLocGrpRule, setLocGrpRule, getLocGrpLocs, setLocGrpLocs, addLocGrpLocs, removeLocGrpLocs.

createLocGrp

Input

clientId	string (32)	The client ID from the login response
name		Name of the location group
ruleBased	true/false	There are 2 types of groups, rule based and non-rule based (or explicit). Rule-based groups consist of area/location type pairs. • The area can be empty, a country (USA or CAN), or the abbreviation for a US or Canadian state or province. • The location type can be empty or any of the valid location types. The rules when set will be a pipe-delimited list of comma delimited pairs, e.g.: CAN, AK,FJ

Output

Result	Int	The location group # generated by the system. Record this to use in the other location group methods for later use.
--------	-----	---

Error Messages

- Invalid string – the system will let you know if you enter an invalid clientId, name or ruleBased value.

Create New Policy

Creates a new policy for a customer. Policies group cards together.

createNewPolicy

Input

clientId	string (32)	The client ID from the login response
----------	-------------	---------------------------------------

Output

result	int (3)	The new Policy # created, 1-499 are valid values.
--------	---------	---

Error Messages

- A fault error, flying j exception error or an error with an error # and description.

Create New Site Policy

Creates a new site policy record. This has a limit of 100 total site policies. Site policies will fall within the range of 500 to 599.

createNewSitePolicy

Input

clientId	string (32)	The client ID from the login response
Description	string(30)	The site policy description

Output

description	string(30)	The site policy description
policy	Int	The site policy # created

Error Messages

- A fault string or flying J exception error.

Create Order

Creates a new order for cards. You then have to submit the order whereas if you use the create and submit order method that will do both in one.

createOrder

Input

clientId	string (32)	The client ID from the login response
newOrderData		
policyNumber	Int(3)	The policy # for the card order.
orderType	int	1 = New card order 2 = Replacement - lost or stolen 3 = Renew expired 4 = Replace damaged (Not available) 5 = New personal card (Not available) 6 = New spouse card (Not available)
cardStyle	Int	See the card style index
orderQty	Int	The number of cards being ordered
embossedName	string (25)	The embossed name on the card – reminder only certain # of characters will fit on the front of the card. If you have a custom card style, test to see how many characters will print.
shipToFirst	string(30)	Ship to contact first name
shipToLast	string(30)	Ship to contact last name
shipToAddress1	string(30)	Ship to address line 1
shipToAddress2	string(30)	Ship to address line 2
shipToCity	string(30)	Ship to city
shipToState	string(2)	State or Provincial abbreviation
shipToZip	String(10)	The ship to zip or postal code
shipToCountry	string(3)	Shipping country code – USA or CAN
shippingMethod	Int	See the shipping method index. NOTE: There may be fees associated with certain shipping methods.
rushProcessing	char(1)	Y – Rush N – Standard NOTE: there may be fees associated with rush orders.
cardCarrier	char(1)	Y – Yes indicates the card will come with a card carrier (MasterCard) N – No indicates the cards will not come with card carriers.
Props		See the array of Props
Cards	Array	The array of cards being created. Idx starts at 0 for the first card in the order and up to the order quantity.

Props	Array	The props for the individual cards.
-------	-------	-------------------------------------

Output

cardOrderID	long	The card order ID created by the system for the card order.
RequestStatus	object	If there is an error, the error code and description

Error Messages

- A fault error, flying j exception error or an error with an error # and description.

Create SmartPay Scheduled Transfer

SmartFunds card: creates a scheduled ACH or wire transfer.

createSmartPayScheduledTransfer

Input

clientId	string (32)	The client ID from the login response
TransferDefinition array	1 to many	
transferAccountId	int (30)	Unique ID for the transfer account
scheduleType	string(2)	The schedule type. TRANSFER_ON_LOAD is Transfer On Load DAILY – Daily Transfer DAY_OF_MONTH – Transfers on specified day(s) of the month DAY_OF_WEEK – Transfers on the day of the week. *for transfers that are not Transfer On Load, funds will only transfer if available or up to the amount available. For example if the system sets up \$100 but only \$50 is available \$50 will transfer.
scheduleValue	int (2)	For TRANSFER_ON_LOAD, leave blank. For DAILY, leave blank For DAY_OF_MONTH, it is binary using the days of the month, You must pass a minimum of 28 zeroes/ones (you can't use the 30th or 31st due to February) - turning to 1 the day or days you want to turn on. For example 000100000000000000000000000000 would be the 4th of the month 100000000000000000000000000000 would be the 1st of the month For DAY_OF_WEEK, pass 7 zeroes/ones turning on the days you want, Sunday is not allowed but must be populated. The first digit is for Monday, etc. For example: 1000000 - Monday 0100000 – Tuesday 1010100 – Mon/Wed/Fri
transferType	string (1)	FIXED_AMOUNT for Fixed Amount PERCENTAGE is for Percentage
transferValue	decimal (9,2)	The transfer value For the percentages, it's 1 for 100%, 0.50 for 50%, etc. For the FIXED_AMOUNT, it's a dollar amount like 100 for \$100
emailNotification	string (1)	1 = yes, 0 = no

Output

transferId	string (30)	The scheduled transfer ID
------------	-------------	---------------------------

Error Messages

- InvalidtransferAccountId = invalid transfer account

Create SmartPay Transfer Account

Creates SmartFunds scheduled ACH or wire transfers.

createSmartPayTransferAccount

Input

clientId	string (32)	The client ID from the login response
Account array	1 to many	
cardNumber	string (25)	The card number.
bankName	string (50)	The bank name.
routingNumber	int (9)	The bank routing ID.
accountNumber	string (17)	The bank account #.
accountOwnerName	string (25)	The bank owner.
accountType	int (2)	28 PRENOTE PAYMENT CHECKING 38 PRENOTE PAYMENT SAVINGS 22 AUTOMATED PAYMENT CHECKING 32 AUTOMATED PAYMENT SAVINGS
accountNickname	string (50)	Account nickname.

Output

A successful response

```
example : <soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <soapenv:Body>
    <ns5: createSmartPayTransferAccountResponse xmlns:ns5="http://com.tch.cards.service"/>
  </soapenv:Body>
</soapenv:Envelope>
```

Error Messages

- A fault error, flying j exception error or error with error # and error description.

Delete Info Limit Card

Deletes the info limit card from the system. Creating a new card in the cards table and it adds a specific prompt that the system is looking for at the end of the card #. For example, you can have a trip # and policy assigned to the card. Then you assign the prompt to a physical card.

deleteInfoLimitCard

Input

clientId	string (32)	The client ID from the login response
policyNumber	Int(3)	Policy number to assign trip card
infold	Char(4)	The prompt ID (TRIP) – see the list of valid prompts
reportValue	Char(24)	Trip number

Output

Empty response means the deletion was successful.

Error Messages

- A fault string or flying j exception.

Delete Order

This method will delete a card order if you no longer need the cards ordered. As long as the cards have not been shipped, it will stop the cards from going out.

deleteOrder

Input

clientId	string (32)	The client ID from the login response
orderId	Long	The card order id that you want to delete.

Output

SUCCESS		A successful response indicates the order was deleted.
---------	--	--

Error Messages

- ERROR – delete order failed.

Delete Override

Deletes an override from a card.

deleteOverride

Input

clientId	string (32)	The client ID from the login response
cardNumber	string (25)	The card # that the system is removing the override from

Output

If the delete override was successful, the call will just return with no return values. If there was an error, a fault will be returned.

Error Messages

A fault error, flying j exception error or an error with error # and description.

Delete SmartPay Scheduled Transfer

Deletes a scheduled transfer set-up on a SmartFunds card.

deleteSmartPayScheduledTransfer

Input

clientId	string (32)	The client ID returned in the login response
transferId	string (30)	The transfer ID belonging to the scheduled transfer being deleted.

Output

Successful response or error.

Error Messages

A fault error, flying j exception error or an error with error # and description.

Delete SmartPay Transfer Account

Deletes a bank account set-up for ACH transfers on a SmartFunds cards.

deleteSmartPayTransferAccount

Input

clientId	string (32)	The client ID returned in the login response
accountId	string (30)	The account ID belonging to the bank account being cancelled.

Output

Successful response or error.

Error Messages

A fault error, flying j exception error or an error with error # and description.

Do SmartPay ACH Transfer

Performs a SmartFunds ACH transfer.

doSmartPayAchTransfer

Input

clientId	string (32)	The client ID returned in the login response
transfer array		1 to many
transferAccountId	string (30)	The account transfer ID created for the account.
cardNumber	string max(25)	The card #
amount	decimal (11,2)	Transfer amount, please see account manager or implementation manager for max load amount on the SmartFunds contract.
refNumber	string (30)	A reference ID to be associated with the ACH transfer.

Output

Successful response or error.

Error Messages

A fault error, flying j exception error or an error with error # and description.

Does Card Position

This is related to customers that use the EFS LLC SecureFuel product. This method will return if the customer uses secure fuel. If has secure fuel rules of 1 or 2 and a member type of customer, this will return true.

doesCardPosition

Input

clientId	string (32)	The client ID returned in the login response
----------	-------------	--

Output

doesCardPosition	Boolean	true/false
------------------	---------	------------

Error Messages

A fault error, flying j exception error or an error with error # and description.

Find Orders

This is a method that allows you to search card orders under your customer.

findOrders

Input

clientId	string (32)	The client ID from the login response
Filter		Optional search options – fill out 1 to many
startDate	datetime	The starting date/time for the search.
endDate	datetime	The ending date/time for the search.
embossedName	string(30)	The embossed name on the card.
shipToFirst	string(30)	The shipping contact first name.
shipToLast	string(30)	The shipping contact last name.
shipToCity	string(30)	The shipping contact city.
shipToState	string(2)	The shipping contact state/provincial abbreviation.
shipToZip	string(10)	The shipping contact zip or postal code.
shipToCountry	string(3)	Shipping country code – USA or CAN

Output

1 to many order summaries will be returned. If there are no card orders that match it will return an empty element.

orderId	long	The order id.
createDate	datetime	The create date/time.
orderStatus	string(1)	E F I N T W Y b
statusMsg	string	Order status message.
embossedName	string (25)	The embossed name on the card.
orderQty	int	The card order quantity.
orderType	int(1)	1 = New card order 2 = Replacement - lost or stolen 3 = Renew expired 4 = Replace damaged (Not available) 5 = New personal card (Not available) 6 = New spouse card (Not available)

PolicyNumber	int(3)	The policy # from the card order.
cardStyle	int	The card style from the card order.
rushProcessing	Char(1)	Y – Rush order No – Standard shipping NOTE: Charges may apply to rush orders This can be null.
shipToFirst	string(30)	The shipping contact first name.
shipToLast	string(30)	The shipping contact last name.
shipToAddress1	string(30)	The shipping contact address 1.
shipToAddress2	string(30)	The shipping contact address 2.
shipToCity	string(30)	The shipping contact city.
shipToState	string(2)	The shipping contact state or provincial abbreviation.
shipToZip	string(10)	The shipping contact zip or postal code.
shipToCountry	string(3)	The shipping contact county (USA or CAN)

Error Messages

- A fault error, flying j exception or error with an error # code and description.

Get Allowed Order Types

Finds out the allowed card order types for the customer's Carrier ID/Customer # for each policy. Multiple types are allowed for the policy.

getAllowedOrderTypes

Input

clientId	string (32)	The client ID from the login response
----------	-------------	---------------------------------------

Output

If there is nothing found, this is an empty result list.

orderType	int	Order type #
orderDesc	string (30)	The order type description
defCardStyle	int	Card style #. Contact your account manager or implementation representative for a valid list of card styles.
defCardStyleDesc	string (30)	Card style description
defPolicy	numeric (3)	The policy #

Error Messages

- A fault error, flying j exception or error with error # code and description.

Get Card

Gets card information about a card, including the header info, prompt infos, limits, location groups, locations, and time restrictions.

getCard

Input

clientId	string (32)	Required. From the login response
cardNumber	string (25)	Required. The card number the system is requesting info on

Output

Header		
companyXRef	string (15)	The company Xref populated for the card.
handEnter	string (7)	ALLOW, DISALLOW or POLICY
infoSource	string (7)	Indicates if the Prompt Infos are at the Card, Policy, or Both levels. Valid values are Policy, Card, or Both.
limitSource	string (7)	Policy, Card, or Both
locationOverride	boolean (1)	0 = no override, 1 = override
locationSource	string (7)	Policy, Card, or Both
overrideAllLocations	true/false	True or false
originalStatus	string (8)	Active, Inactive, Deleted – will often be returned as nil such as: <originalStatus xsi:nil="1" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
payrollStatus	string (8)	Active, Inactive, Follows
override	boolean (1)	0 = false, 1 = true
policyNumber	int (3)	The policy # the card belongs to, 1-99 are valid.
status	string (8)	Active, Inactive, Hold, Deleted
timeSource	string (7)	Policy, Card, or Both
lastUsedDate	datetime	The last used date/time on the card.
lastTransaction	string (10)	The authorization # for the last transaction on the card.
payrollUse	string (1)	The payroll use value, P - payroll B - Both payroll and normal N - Normal Y - Debit L - Debit with Limits
payrollAtm	string (8)	Disallow or allow SmartFunds from the ATM
payrollChk	string (8)	Disallow or allow registered checks from SmartFunds
payrollAch	string (8)	Disallow or allow ACH from SmartFunds.
payrollWire	string (8)	Disallow or allow Wires from SmartFunds.

payrollDebit	string (8)	Disallow or allow use of SmartFunds on the debit network (Maestro, etc.)
Infos Object		A list of prompts assigned to the card. Only prompts assigned at the CARD level are returned, POLICY prompts are not returned even if the card source is set to "BOTH." There can be zero to many infos returned per card.
infoId	string (4)	The info ID for the prompt item. See Info IDs for the valid infos.
lengthCheck	true/false	Indicates if length check is on or off for a prompt.
matchValue	string (24)	If a prompt is Exact Match this is the value. For example, this is the Driver ID #, Unit #, etc. Do not send more than 24 characters in this field.
maximum	numeric (10)	The maximum value. Only checked if lengthCheck is true.
Minimum	numeric (10)	The minimum value. Only checked if lengthCheck is true.
reportValue	string (24)	If a prompt is Report Only this is the report value. For example, this is the Driver ID #, Unit #, etc., that will be reported.
validationType	string (13)	The validation type for the prompt. ALPHABETIC, ALPHA_NUMERIC, NUMERIC, REPORT_ONLY, EXACT_MATCH, ACCRUAL_CHECK & DYNAMIC are the valid options. NOTE: Use EXACT_MATCH to prompt and validate at the pump, use REPORT_ONLY for reporting prompts only. These are most commonly used at the card level. DYNAMIC can only be used with CNTN, PPIN and DRID
value	String	For the accrual check method for odometer or hubometer, this is the accrual value. For all other info ids/validation type combos just leave as <value/> or <value>0</value>
Limits Object		A list of limits assigned to the card. Only limits assigned at the CARD level are returned, POLICY limits are not returned even if the card source is set to "BOTH." There can be zero to many limits returned per card.
hours	int (3)	The hours the limit is good for before resetting.
limit	numeric (4)	The limit value, which will be gallons for fuel or DEF dispensed and dollar amounts in all other cases. For example if the limit is ULSD and this value is 300 that will be 300 gallons. This will be a value from 0 to 9999.
limitId	string	The limit ID for the limit value. See Limit IDs for values.
minHours	int (3)	Minimum hours between using the limit between uses.
Location Groups Object		A list of location groups assigned to the card if the customer participates in using location groups. There can be zero to many location groups.
locationGroups	int (10)	The location group.
Locations Object		A list of locations that this card is BLOCKED from using. Only add to this list if you want to block the card from going to the locations listed. There can be zero to many locations.
locations	int (7)	The location ID for the location being blocked.

Time Restrictions Object		A list of time restrictions that are applicable for the card. Only card level time restrictions are returned even if the time source is BOTH or POLICY. There can be zero to many time restrictions.
beginTime	datetime	Begin time for the time restriction. The year, month, day portions will show 1970-01-01, only the time values are applicable.
day	int (1)	The day being restricted. 1 = Sunday, 2 = Monday, 3 = Tuesday, 4 = Wednesday, 5 = Thursday, 6 = Friday, 7 = Saturday
endTime	datetime	The end time for the time restriction. The year, month, day portions will show 1970-01-01, only the time values are applicable.

NOTE: If the system is going to display card information to the user such as info prompts, limits, etc., call [Get Policy](#) to get the policy level info to combine with the card information to show. If the card source is BOTH, the system should display both card and policy info to the user. Card level always trumps policy.

Get Card Version 2

Gets card information about a card, including the header info, prompt infos, limits, location groups, locations, and time restrictions. This is an updated version that will return refreshing limits that are at the card level, the old version doesn't return that value.

getCardv2

Input

clientId	string (32)	Required. From the login response
cardNumber	string (25)	Required. The card number the system is requesting info on

Output

Header		
companyXRef	string (15)	The company Xref populated for the card.
handEnter	string (7)	ALLOW, DISALLOW or POLICY
infoSource	string (7)	Indicates if the Prompt Infos are at the Card, Policy, or Both levels. Valid values are Policy, Card, or Both.
limitSource	string (7)	Policy, Card, or Both
locationOverride	boolean (1)	0 = no override, 1 = override
locationSource	string (7)	Policy, Card, or Both
overrideAllLocations	true/false	True or false
originalStatus	string (8)	Active, Inactive, Deleted – will often be returned as nil such as: <originalStatus xsi:nil="1" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
payrollStatus	string (8)	Active, Inactive, Follows
override	boolean (1)	0 = false, 1 = true
policyNumber	int (3)	The policy # the card belongs to, 1-99 are valid.
status	string (8)	Active, Inactive, Hold, Deleted
timeSource	string (7)	Policy, Card, or Both
lastUsedDate	datetime	The last used date/time on the card.
lastTransaction	string (10)	The authorization # for the last transaction on the card.
payrollUse	string (1)	The payroll use value, P - payroll B - Both payroll and normal N - Normal Y - Debit L - Debit with Limits
payrollAtm	string (8)	Disallow or allow SmartFunds from the ATM
payrollChk	string (8)	Disallow or allow registered checks from SmartFunds
payrollAch	string (8)	Disallow or allow ACH from SmartFunds.

payrollWire	string (8)	Disallow or allow Wires from SmartFunds.
payrollDebit	string (8)	Disallow or allow use of SmartFunds on the debit network (Maestro, etc.)
Infos Object		A list of prompts assigned to the card. Only prompts assigned at the CARD level are returned, POLICY prompts are not returned even if the card source is set to "BOTH." There can be zero to many infos returned per card.
infolD	string (4)	The info ID for the prompt item. See Info IDs for the valid infos.
lengthCheck	true/false	Indicates if length check is on or off for a prompt.
matchValue	string (24)	If a prompt is Exact Match this is the value. For example, this is the Driver ID #, Unit #, etc. Do not send more than 24 characters in this field.
maximum	numeric (10)	The maximum value. Only checked if lengthCheck is true.
Minimum	numeric (10)	The minimum value. Only checked if lengthCheck is true.
reportValue	string (24)	If a prompt is Report Only this is the report value. For example, this is the Driver ID #, Unit #, etc., that will be reported.
validationType	string (13)	The validation type for the prompt. ALPHABETIC, ALPHA_NUMERIC, NUMERIC, REPORT_ONLY, EXACT_MATCH, ACCRUAL_CHECK & DYNAMIC are the valid options. NOTE: Use EXACT_MATCH to prompt and validate at the pump, use REPORT_ONLY for reporting prompts only. These are most commonly used at the card level. DYNAMIC can only be used with CNTN, PPIN and DRID
value	String	For the accrual check method for odometer or hubometer, this is the accrual value. For all other info ids/validation type combos just leave as <value/> or <value>0</value>
Limits Object		A list of limits assigned to the card. Only limits assigned at the CARD level are returned, POLICY limits are not returned even if the card source is set to "BOTH." There can be zero to many limits returned per card.
hours	int (3)	The hours the limit is good for before resetting.
limit	numeric (4)	The limit value, which will be gallons for fuel or DEF dispensed and dollar amounts in all other cases. For example if the limit is ULSD and this value is 300 that will be 300 gallons. This will be a value from 0 to 9999.
limitId	string	The limit ID for the limit value. See Limit IDs for values.
minHours	int (3)	Minimum hours between using the limit between uses.
autoRollMap	int (3)	If limit is auto roll the auto roll map.
autoRollMax	int (4)	Max value for the auto roll limit. Max 9999. Please set this to 0 if you don't want a maximum daily limit.
Location Groups Object		A list of location groups assigned to the card if the customer participates in using location groups. There can be zero to many location groups.

locationGroups	int (10)	The location group.
Locations Object		A list of locations that this card is BLOCKED from using. Only add to this list if you want to block the card from going to the locations listed. There can be zero to many locations.
locations	int (7)	The location ID for the location being blocked.
Time Restrictions Object		A list of time restrictions that are applicable for the card. Only card level time restrictions are returned even if the time source is BOTH or POLICY. There can be zero to many time restrictions.
beginTime	datetime	Begin time for the time restriction. The year, month, day portions will show 1970-01-01, only the time values are applicable.
day	int (1)	The day being restricted. 1 = Sunday, 2 = Monday, 3 = Tuesday, 4 = Wednesday, 5 = Thursday, 6 = Friday, 7 = Saturday
endTime	datetime	The end time for the time restriction. The year, month, day portions will show 1970-01-01, only the time values are applicable.

NOTE: If the system is going to display card information to the user such as info prompts, limits, etc., call [Get Policy](#) to get the policy level info to combine with the card information to show. If the card source is BOTH, the system should display both card and policy info to the user. Card level always trumps policy.

Get Card by Driver ID

Gets card information about a card by the Driver ID assigned to the card, including the header info, prompt infos, limit infos, location groups, locations, and time restrictions.

getCardByDriverId

Input

clientId	string (32)	From the login response
driverId	string (24)	The driver ID # the customer is requesting card info for.

Output

This is the same output as the [Get Card](#) output.

NOTE: If the system is going to display card information to the user such as info prompts, limits, etc., call [Get Policy](#) to get the policy level info to combine with the card information to show. If the card source is BOTH, the system should display both card and policy info to the user. Card level always trumps policy.

Error Messages

- A fault error, flying j exception or error # code and description.

Get Card Descriptions

Returns a set of cards created since a certain date.

getCardDescriptions

Input

clientId	string (32)	From the login response
createdSince	datetime	The date from which the system is requesting card descriptions.

Output

Array containing:

cardNumber	string (25)	The card #.
companyXRef	string (15)	The company xref on the card.

Error Messages

- A fault error, flying j exception or error # code and description.

Get Card Refreshing Limits

This method will return the refreshing/velocity limits associated with a card – primarily used for MasterCard's but it could sometimes be used on fleet cards.

getCardRefreshingLimits

Input

clientId	string (32)	The client ID from the login response
cardNumber	string(19)	The card #

Output

It will return the refreshing limit for a card – the limit

dayCntLimit	int	The daily # of transactions allowed.
dayAmtLimit	Int	The daily amount limit in dollars.
weekCntlimit	Int	The weekly # of transactions allowed.
weekAmtLimit	Int	The weekly amount allowed.
monCntlimit	Int	The monthly # of transactions allowed.
monAmtLimit	int	The monthly amount limit.

Error Messages

- The system will return an error with an error #.

Get Card Summaries

Returns a list of cards and card data, you can limit the search by type, search parameters, pay use fields, or get all card details.

getCardSummaries

Input

clientId	string (32)	From the login response
request array		Optional search features
type	string (4)	Search Type: NUMBER, XREF, UNIT, DRIVERID, DRIVERNAME, POLICY, GPSID, VIN, STATUS
searchParam	string	A card search parameter of search type fields example- Status: A (Active) H (Hold) U (Fraud) I (Inactive)
payrUse	string (1)	1.The payroll use flag: B, P or N (P= Payroll Only, B= Both payroll and company, N = Company side only,

Output

Array containing:

cardNumber	string (25)	The card #.
policyNumber	int (3)	The policy # the card belongs to, 1-99 are valid.
companyXref	string (15)	The company Xref populated for the card.
unitNumber	string(24)	The unit # assigned to the card, if applicable.
driverId	string (24)	The Driver ID assigned to the card, if applicable.
driverName	string (24)	The Driver Name assigned to the card, if applicable.
override	boolean (1)	indicates if a card has an override, 0 = false and 1 = true.
beingOverridden	true/false	indicates if a card is overridden or not.
status	string (8)	The status of the card
payrollStatus	string (8)	The payroll status of the card, if the cards is SmartFunds or Universal this applies. Active, Inactive, & Follows are valid values. Follows means the status follows the card status.
Gpsid	string (10)	The GPS ID for Secure Fuel cards.
Vin	string (17)	The VIN assigned to the card, again for Secure Fuel uses.
Zid	string (17)	The ZID for the card, for secure fuel.
Infosrc	string (7)	Indicates if the Prompt Infos are at the Card, Policy, or Both levels. Valid values are POLICY, CARD or BOTH.
policySubfleet	string (24)	The Subfleet ID info assigned to the policy the card belongs to.
cardSubfleet	string (24)	The Subfleet ID info assigned to the card.

Error Messages

- A fault error, flying j exception or error # code and description.

Get Card Summaries V2

Returns a list of cards and card data, you can limit the search by type, search parameters, pay use fields, or get all card details. Multiple search types and parameters are supported in a single search

getCardSummariesV2

Input

clientId	string (32)	From the login response
request		Optional search features
payrUse	string (1)	1.The payroll use flag: B, P or N (P= Payroll Only, B= Both payroll and company, N = Company side only,
request array		
type	string (4)	Search Type: NUMBER, XREF, UNIT, DRIVERID, DRIVERNAME, POLICY, GPSID, VIN, STATUS
searchParam	string	A card search parameter of search type fields example- Status: A (Active) H (Hold) U (Fraud) I (Inactive)

Output

Array containing:

cardNumber	string (25)	The card #.
policyNumber	int (3)	The policy # the card belongs to, 1-99 are valid.
companyXref	string (15)	The company Xref populated for the card.
unitNumber	string(24)	The unit # assigned to the card, if applicable.
driverId	string (24)	The Driver ID assigned to the card, if applicable.
driverName	string (24)	The Driver Name assigned to the card, if applicable.
override	boolean (1)	indicates if a card has an override, 0 = false and 1 = true.
beingOverridden	true/false	indicates if a card is overridden or not.
status	string (8)	The status of the card
payrollStatus	string (8)	The payroll status of the card, if the cards is SmartFunds or Universal this applies. Active, Inactive, & Follows are valid values. Follows means the status follows the card status.
Gpsid	string (10)	The GPS ID for Secure Fuel cards.
Vin	string (17)	The VIN assigned to the card, again for Secure Fuel uses.
Zid	string (17)	The ZID for the card, for secure fuel.
Infosrc	string (7)	Indicates if the Prompt Infos are at the Card, Policy, or Both levels. Valid values are POLICY, CARD or BOTH.
policySubfleet	string (24)	The Subfleet ID info assigned to the policy the card belongs to.
cardSubfleet	string (24)	The Subfleet ID info assigned to the card.

Get Cards With No Driver ID

Returns all cards that are not on deleted status that don't have a driver ID assigned to the card. This can be handy for finding cards available to be assigned to new drivers.

getCardsWithNoDriverId

Input

clientId	string (32)	The client ID from the login response
cardType	string 32	P - payroll B - Both payroll and normal N - Normal Y - Debit L - Debit with Limits, if you only have one card type you can leave this field blank and it will pull in all cards with no driver Id

Output

Array containing the list of unassigned cards.

value	string (25)	The card #(s)
-------	-------------	---------------

Error Messages

- A fault error, flying j exception or error # code and description.

Get Carrier Info

Returns main information about a customer.

getCarrierInfo

Input

clientId	string (32)	The client ID returned in the login response.
----------	-------------	---

Output

name	string (2590)	The carrier name assigned in the EFS LLC system.
carrierId	int (7)	The carrier ID assigned to the customer by EFS LLC.
locationGroups	true/false	This field indicates if the carrier ID uses location groups for fuel networks or not.

Error Messages

- A fault error, flying j exception or error # code and description.

Get Cash History

Returns cash advance history for a card and date range.

getCashHistory

Input

clientId	string (32)	The client ID returned in the login response.
cardNumber	string (25)	The card number the system is requesting cash history for.
begDate	datetime	The begin date/time for the cash history request.
endDate	datetime	The end date/time for the cash history request.

Output

Value array

amount	decimal (11,2)	The amount.
cardNumber	string (25)	The card number.
cashId	string (4)	The ID associated with the activity. BBAL = beginning balance, LOAD = cash load, RMVE = cash removal. NOTE actual cashings are not reported, just the beginning balance and loads/removals to the cash balance done by actual users. Other Cash Id's listed below
date	datetime	The date/time of the transaction.
name	string (24)	The eManager user behind the activity, if applicable
refNumber	string (30)	The reference ID associated with the cash activity.
transactionId	int (10)	A transaction ID associated with an activity, usually 0.

Additional Cash Id's

BBAL - beginning balance

CLRF - Cash Ld/Rmv Fees

CRED - This usually means credit applied

Card - The usually means balance due to Card Transfer

DATD - ATM Denial fee

DATW - ATM Withdrawl fee

DCGL - Card Load fee

DLRF - Cash Ld/Rmv Fee as well

DREC - Regular Check fee

DTCU - EFS Network Use fee

LOAD - load to the card

RMVE -remove funds

WDRW - withdrawal

Error Messages

- InvalidLoginException = password is incorrect.
- InvalidAccountException = bad user.
- AccountLockedException = the account has been locked because of too many invalid logins.
- A fault error, flying j exception or error # code and description may be returned.

Get Child Transactions

Retrieves transactions for a child carrier belonging to a parent.

getChildTransactions

Input

parentClientId	string (32)	The client ID returned from the login request. Use a login from a Parent customer.
begDate	datetime	The start date/time the system is requesting transactions for.
endDate	datetime	The end date/time the system is requesting transactions for.

Output

Array of child transactions

Error Messages

- A fault error, flying j exception or error # code and description.

Get Child Transactions New (Preferred)

Retrieves transactions for a child carrier belonging to a parent.

getChildTransactionsNew

Input

parentClientId	string (32)	The client ID returned from the login request. Use a login from a Parent customer.
begDate	datetime	The start date/time the system is requesting transactions for.
endDate	datetime	The end date/time the system is requesting transactions for.

Output

Array of child transactions

Error Messages

- A fault error, flying j exception or error # code and description.

Get Child Transaction Rejects

Returns rejected transactions for all child carriers associated to the parent. This can be narrowed by date.

getChildTranRejects

Input

clientId	string (32)	The client ID from the login response
startdate	datetime	The start date.
endDate	datetime	The end date.

Output

There will be zero to many rejects.

carrierID	int(7)	The child carrier id for the reject
Trandate	Datetime	The date/time of the reject
cardNum	string(19)	The card number.
invoice	string(12)	The invoice # from the merchant location.
locId	int(7)	The merchant's EFS LLC location id.
locName	varchar(2605)	The location name.
locCity	string(30)	The location city.
locState	string(2)	The location state or provincial abbreviation.
errorCode	int	The error code #.
errorDesc	char(100)	The error description.

Error Messages

- A fault error, flying j exception or error # code and description.

Get Contracts

Retrieves the contracts that belong to a customer and the information related to those contracts.

getContracts

Input

clientId	string (32)	The client ID returned from the login request.
----------	-------------	--

Output

Array of contracts:

checkFee	decimal (9,2)	The check fee on the contract.
contractId	int (20)	The contract ID assigned by EFS LLC.
country	string (1)	The contract's country, "U" for USA/USD and "C" for Canadian/CAD. The currency is tied to the country.
currency	string (3)	The currency: USD, CAD. This may be empty, it's best to use the country.
description	string (20)	The issuer description assigned by EFS LLC.
issuerId	int (7)	The EFS LLC issuer ID for the contract.
limitMethod	int (2)	The credit limit method used by EFS LLC for the contract. 1 = Overall Credit 2 = Daily Limit 3 = Overall Credit + Daily Limit 52 = Parent/Child
masterContract	true/false	An indicator if the contract is a master contract or not. If a customer has a master contract then other contracts roll up to the master for credit reasons.
status	string (8)	The status of the contract. Active, Inactive, & Closed are valid values. Active is the only status that indicates a contract can be used.

Error Messages

- A fault error, flying j exception or error # code and description.

Get Credit Limits

Retrieves information related to a specific contract including available balance information.

getCreditLimits

Input

clientId	string (32)	The client ID returned from the login request.
contractId	int (20)	The contract ID the system is requesting information on.

Output

contractStatus	string (8)	The status of the contract, Active, Inactive, & Closed are valid values. Active is the only status that can indicate a contract can be used.
transLimit	decimal (12,2)	The maximum transaction allowed on the contract.
origLimit	decimal (12,2)	The credit limit on the contract.
creditAvailable	decimal (12,2)	Available credit limit.
dailyLimit	decimal (12,2)	If applicable, the daily limit applied to the contract's credit. This is an overall daily limit.
dailyAvailable	decimal (12,2)	The amount available on the daily limit.
totalAvailable	decimal (12,2)	The overall total available limit.
maxMoneyCode	decimal (12,2)	The maximum money code allowed on the contract.
uom	string (3)	The unit of measure: USD/gallons or CAD/litres.

Error Messages

- InvalidLoginException = password is incorrect.
- InvalidAccountException = bad user.
- AccountLockedException = the account has been locked because of too many invalid logins.
- A fault error or flying j exception error may be returned.

Get Current Cash All Amounts

Returns the current cash amounts available for a list of card numbers (one to many).

getCurrentCashAllAmounts

Input

clientId	string (32)	The client ID returned from the login response.
array of card #s		You can send one to many cardNumbers, e.g., <pre><cardNumbers> <!--Zero or more repetitions:--> <value>7083051317437000016</value> <value>7083051317437000024</value> <value>7083051317437000032</value> </cardNumbers></pre>
cardNumber	string (25)	The card #

Output

The array of cash results returns the cash info for the cards requested.

cardNumber	string (25)	The card #.
oneTimeCash	decimal (12,2)	The one time cash balance on the card.
recurringCash	decimal (12,2)	The recurring cash limit on the card.
contractLimit	decimal (12,2)	The maximum cash advance allowed by the contract.
cashAvailable	decimal (12,2)	The available cash balance on the card. This is computed based on the One Time Cash Balance + Recurring Cash Limit, compare that to the contract limit and the lowest value is available.

Error Messages

- InvalidLoginException = password is incorrect.
- Invalid Card # = bad card # passed in the request.
- A fault or flying j exception error.

Get Current Cash Amounts

Returns the current cash available for a list of card numbers (one to many).

getCurrentCashAmounts

Input

clientId	string (32)	The client ID returned from the login response.
Card # array		1 to many card #s

Output

Array of card balances, returned in the same order as the cards were submitted.

Error Messages

- InvalidLoginException = password is incorrect.
- InvalidCard# = invalid card # submitted.
- A fault error or flying j exception.

Get Current Payroll Cash Amounts

Returns the SmartFunds balances for a list of card numbers (one to many).

getCurrentPayrollCashAmounts

Input

clientId	string (32)	The client ID returned from the login response.
Card # array	1 to many card #s	

Output

Array of card SmartFunds balances, returned in the same order as the cards were submitted.

Error Messages

A fault error or flying j exception.

Get Geographic Price Locations

Returns geographic location info with last price within a range specified in the request.

getGeoPriceLocations

Input

clientId	string (32)	The client ID returned from the login response.
cardNumber	string (25)	The card #.
latitude	float (10,6)	The latitude, can be signed.
longitude	float (10,6)	The longitude, can be signed.
searchRange	int (3)	The search range radius for finding locations.
taxFlag	boolean (1)	The tax flag, true or false (1 or 0). Indicates whether or not taxes are included in the price.

Output

Array of locations:

locId	int (7)	The location ID assigned by EFS LLC to the location.
name	string (45)	The location's name.
addr1	string (30)	The address 1 line of the location.
addr2	string (30)	The address 2 line of the location, if applicable.
city	string (30)	The location's city.
state	string (2)	The location's state/province.
zip	string (10)	The location's zip/postal code.
country	string (3)	The location's country, for example USA, CAN.
phone	string (11)	The locations phone #, formatted 999-999-9999.
Continued on next page....		
chainId	int (10)	A list of chain ID's .
latitude	float (10,6)	The latitude, can be signed.
longitude	float (10,6)	The longitude, can be signed.
price	decimal (4,3)	The most recent PPU, if available.
amenities		A list of Location Amenities , if available.

Error Messages

A fault error or flying j exception.

Get Interstate Price Locations

Returns the location info with last price for interstates specified in a request.

getInterstatePriceLocations

Input

clientId	string (32)	The client ID returned from the login response.
cardNumber	string (25)	The card #.
interstates	string (254)	The interstate(s) requesting info, comma separated.
states	string (254)	The state/province abbreviations, separated by commas.
taxFlag	boolean (1)	The tax flag, true or false (1 or 0). Indicates whether or not taxes are included in the price.

Output

Array of locations:

locId	int (7)	The location ID assigned by EFS LLC to the location.
name	string (45)	The location's name.
addr1	string (30)	The address 1 line of the location.
addr2	string (30)	The address 2 line of the location, if applicable.
city	string (30)	The location's city.
state	string (2)	The location's state/province.
zip	string (10)	The location's zip/postal code.
country	string (3)	The location's country, for example USA, CAN.
phone	string (11)	The locations phone #, formatted 999-999-9999
Continued on next page		
chainId	int (10)	A list of chain ID's
latitude	float (10,6)	The latitude, can be signed.
longitude	float (10,6)	The longitude, can be signed.
price	decimal (4,3)	The most recent PPU, if available.
amenities		A list of Location Amenities , if available.

Error Messages

A fault error or flying j exception.

Get Last Mileage

Returns the last mileage for a unit.

getLastMileage

Input

clientId	string (32)	The client ID returned in the login response.
Search Array, 1 to many		
unit	string (24)	The unit #.
code	string (4)	Odometer (ODRD) or Hubometer (HBRD).

Output

Array of mileage readings.

Error Messages

A fault error or flying j exception.

Get Location Group Descriptions

This will return the location group ids available for your customer.

getLocationGroupDescriptions

Input

clientId	string (32)	The client ID from the login response
----------	-------------	---------------------------------------

Output

GroupId	Int	The group ID
Name	string(32)	The group name or description
ruleBased	True/false	If the group is rule based (true) or not (false)
editable	True/false	True/False – you can modify location groups that your customer created but the default EFS LLC groups are not editable by outside users.

Error Messages

A fault or flying j exception error.

Get Location Group Locations

This method will return the location ids associated with a certain location group.

getLocGrpLocs

Input

clientId	string (32)	The client ID from the login response
groupId	Int	The group id that the system is looking up.

Output

Array		An array of the location ids in the group.
-------	--	--

Error Messages

- A fault string or flying j exception error.

Get Location Group Rule

This method will return the rules associated to a location group.

getLocGrpRule

Input

clientId	string (32)	The client ID from the login response
groupID	Int	The group id you are checking the rules for

Output

results	string	The pipe/comma delimited list of rules associated with the group
---------	--------	--

Error Messages

A fault or flying j exception error.

Get Location Groups

Returns valid location groups for a card or policy. Location groups are created by EFS LLC on behalf of the customer but the customer can retrieve location groups.

getLocationGroups

Input

clientId	string (32)	The client ID returned in the login response.
cardNum	string (25)	The card number.
policyNum	int (3)	The policy #. The system can pass the card # and/or the policy #.

Output

Array of location groups:

grpId	int (10)	The ID assigned to the location group.
name	string (5)	The name of the location group.
carrierId	int (7)	The carrier ID for the location group. If 0 the location group can be used by all carriers.

Error Messages

A fault or flying j exception error.

Get Mobile Roles

Returns valid mobile roles for specific applications.

getMobileRoles

Input

clientId	string (32)	The client ID returned in the login response.
application	string (10)	The mobile application.

Output

List of mobile roles.

Error Messages

A fault or flying j exception error.

Get Money Code

Returns information related to a specific money code belonging to the customer.

getMoneyCode

Input

clientId	string	Required. Token returned from login
alphaCode	string	Required. EFS ID for the money code.

Output

activeDate	datetime	
alphaCode	String (6)	
amount	decimal(9,2)	
code	serial	
codeType	string	char(10), for example E_MANAGER for all web service or web generated codes.
contractId	int (20)	
feeType	Boolean	shows whether fees were deducted from the amount or not. False = not deducted True = fees are deducted
firstUse	dateTime	
Id	Int(20)	Money code ID
issuedTo	string	
notes	string	
numUses	string	
payee	string	
status		
uses	Object array	If this is a code that has been used multiple times you will see all the uses in this field. You will see amount, check number and the time it was used
voidDate	dateTime	
voided	Boolean	example true or false
who	String	

Error Messages

A fault or flying j exception error.

Get Money Code V2

Returns information related to a specific money code belonging to the customer.

getMoneyCodeV2

Input

clientId	string	Required. Token returned from login
alphaCode	string	Required. EFS ID for the money code.

Output

activeDate	datetime	
alphaCode	String (6)	
amount	decimal(9,2)	
code	serial	
codeType	string	char(10), for example E_MANAGER for all web service or web generated codes.
contractId	int (20)	
feeType	Boolean	shows whether fees were deducted from the amount or not. False = not deducted True = fees are deducted
firstUse	dateTime	
Id	Int(20)	Money code ID
issuedTo	string	
notes	string	
numUses	string	
payee	string	
status		
uses	Object array	If this is a code that has been used multiple times you will see all the uses in this field. You will see amount, check number and the time it was used
voidDate	dateTime	
voided	Boolean	example true or false
who	String	
Prompt	N/A	Array of Prompt Values
infoType	string (4)	The info ID for the prompt item. See Info IDs for the valid infos.
infoValue	string (24)	This is the info/prompt value. For example, this is the Driver ID #, Unit #, etc., that will be reported.

Error Messages

A fault or flying j exception error.

Get Money Code By ID

Returns information related to a specific money code. This call will also return the location information from where the check was cashed

getMoneyCodeById

Input

clientId	string	Required. Token returned from login
codeId	string	Required. EFS ID for the money code.

Output

activeDate	datetime	
amount	decimal(9,2)	
AmountUsed	decimal(9,2)	
code	serial	
codeType	string	char(10), for example E_MANAGER for all web service or web generated codes.
contractId	int (20)	
Created	dateTime	
deductFees	boolean	shows whether fees were deducted from the amount or not. False = not deducted True = fees are deducted
feeAmount	decimal(9,2)	
feeType	Boolean	shows whether fees were deducted from the amount or not. False = not deducted True = fees are deducted
firstUse	string	
Id	Int(20)	Money code ID
issuedTo	string	
Notes	string	
numUses	Int(20)	
payee	string	
status	string	
uses	Object array	If this is a code that has been used multiple times you will see all the uses in this field. You will see amount, check number, the date/time it was used, location name, city, state and phone number
voidDate	dateTime	
voided	Boolean	example true or false

who	Boolean	
-----	---------	--

Error Messages

A fault or flying j exception error.

Get Money Code Use

Returns money code uses for a certain date range.

getMoneyCodeUse

Input

clientId	string (32)	The client ID returned in the login response.
contractId	int (20)	The contract ID the system is requesting money code use information for.
masterContractId	int (20)	The master contract ID, set to -1 if there is no master contract.
begDate	datetime	The beginning date/time the system is requesting information for.
endDate	datetime	The end date/time the system is requesting information for.

Output

Array of money codes, zero to many: [WSMoneyCodeHistRec](#)

Error Messages

A fault or flying j exception error.

Get Money Code Use V2

Returns money code uses for a certain date range.

getMoneyCodeUseV2

Input

clientId	string (32)	The client ID returned in the login response.
contractId	int (20)	The contract ID the system is requesting money code use information for.
masterContractId	int (20)	The master contract ID, set to -1 if there is no master contract.
begDate	datetime	The beginning date/time the system is requesting information for.
endDate	datetime	The end date/time the system is requesting information for.

Output

Array of money codes, zero to many: [WSMoneyCodeHistRecV2](#)

Error Messages

A fault or flying j exception error.

Get Money Codes

Returns information on a money code.

getMoneyCodes

Input

clientId	string (32)	Required. Token returned from login
begDate	datetime	The begin date/time for the request
endDate	datetime	The end date/time for the request

Output

Array of money codes, zero to many: [WSMoneyCodeHistRec](#)

Error Messages

A fault or flying j exception error.

Get Money Codes V2

Returns information on a money code.

getMoneyCodesV2

Input

clientId	string (32)	Required. Token returned from login
begDate	datetime	The begin date/time for the request
endDate	datetime	The end date/time for the request

Output

Array of money codes, zero to many: [WSMoneyCodeHistRecV2](#)

Error Messages

A fault or flying j exception error.

Get One Carrier Child Transaction

Allows a parent carrier to get all of the transactions belonging to one child carrier of the parent.

getOneCarrierChildTransaction

Input

parentClientId	string (32)	The client ID returned in the login response.
childCarrierId	int (7)	The child carrier ID the Parent is requesting transactions for.
begDate	datetime	The beginning date/time the system is requesting information for.
endDate	datetime	The end date/time the system is requesting information for.

Output

Array of zero to many.

Error Messages

A fault or flying j exception error.

Get Order

This method will return details on a card order.

getOrder

Input

clientId	string (32)	The client ID from the login response
orderId	long	The card order id from the card order.

Output

orderId	long	The card order id.
policyNumber	int(3)	The policy # for the card order.
orderType	Int	The order type from the card order.
cardStyle	Int	The card style from the
props	object	An array of the property objects for the order.

Error Messages

A fault or flying j exception error.

Get Order Cards

This method will return the order information for a specific card order line list.

getOrderCards

Input

clientId	string (32)	The client ID from the login response
orderId	long	The card order id
cardSelections	string	It's a comma separated ID list of card order line numbers.

Output

orderId	long	The card order id.
policyNumber	int(3)	The policy # for the card order.
orderType	int	The order type from the card order.
cardStyle	int	The card style from the card order.
props	object	An array of the property objects for the order.

Error Messages

A fault or flying j exception error.

Get Order Choices

This returns the card order choices for some input parameters.

getOrderChoices

Input

clientId	string (32)	The client ID from the login response
policyNumber	int(3)	The policy # for the card order choices
orderType	Int(1)	See the order type list
cardStyle	int	See the card style list
localeCode	string	This is the locale of the order, example en_US, en_CA, or fr_CA.
requiredOnly	Boolean	True/False or 1/0

Output

This is an array of 0 to many

propRequired	string	A list of the required properties for card orders.
cardScope	Boolean	The card scope.
unique	Boolean	The unique indicator.
priorPost	string	The prior/post indicator.
validationType	string	The validation type.
Code/desc array		An object of code/descriptions

Error Messages

A fault or flying j exception error.

Get Order Styles

This will return the order styles for a customer, policy and order type combination.

getOrderStyles

Input

clientId	string (32)	The client ID from the login response
policyNumber	int(3)	The policy #
orderType	int	Please see the order type list.

Output

This will return 0 to many

cardStyle	int	The card style.
Description	string	The description of the card style.

Error Messages

A fault or flying j exception error.

Get Order Types

This web service method will return a list of order types/descriptions allowed for a certain policy #.

getOrderTypes

Input

clientId	string (32)	The client ID from the login response
policyNumber	Int(3)	The policy #

Output

An array of zero to many.

orderType	In	The order type.
description	String(30)	The order type description.

Error Messages

A fault or flying j exception error.

Get Payroll Cash History

Allows a customer to get the SmartFunds history for a card and date range.

getPayrollCashHistory

Input

clientId	string (32)	The client ID returned in the login response.
cardNum	string (25)	The card number.
begDate	datetime	The beginning date/time the system is requesting information for.
endDate	datetime	The end date/time the system is requesting information for.

Output

Array of payroll history records.

Error Messages

A fault or flying j exception error.

Get Payroll Cash History for all cards

Allows a customer to get the SmartFunds history for all the cards on the account for a certain date range.

getPayrollCashHistoryV2

Input

clientId	string (32)	The client ID returned in the login response.
cardNum	string (25)	The card number for a specific card or ALL for all cards
begDate	datetime	The beginning date/time the system is requesting information for.
endDate	datetime	The end date/time the system is requesting information for.
CardStatus	String	The Status of the cards. 1. A = Active 2. I = Inactive 3. H = Hold 4. D = Deleted All 5. ALL for all card statuses

Output

Array of payroll history records.

Error Messages

Invalid date/time

Invalid Client ID

Invalid Card Status

Begin Date and End Date cannot be more than a week apart

Get Policy

Returns information related to one policy, including the header info, limits, location groups, locations, and time restrictions.

getPolicy

Input

clientId	string (32)	Returned from the Login response
policyNumber	int (3)	The policy # the system or user is inquiring upon.

Output

The information related to the policy will be returned.

<header> section		Main info on policy.
contractId	int (20)	The Contract ID assigned to the Policy. This is the main billing contract ID assigned to the customer by EFS LLC's financial system. Note that transactions for SmartFunds or falling under specific site policies may hit a different contract based on set-up.
description	string (30)	The description/name assigned to the policy.
handEnter	true/false	Indicates if Hand Entry is allowed at the policy level or not.
payrollContractId	int (20)	If the customer has SmartFunds, the contract ID for SmartFunds else 0.
payrollAtm	true/false	Indicates if SmartFunds can be drawn at the ATM for the policy.
payrollChk	true/false	Indicates if SmartFunds can be drawn via registered check.
payrollAch	true/false	Indicates if SmartFunds ACH transfer is allowed for the Policy.
payrollWire	true/false	Indicates if SmartFunds wire transfer is allowed for the policy.
payrollDebit	true/false	Indicates if SmartFunds can be drawn by using the card in the Debit network.
<infos> section		Prompts on the policy. This is an array of zero to many. Each info returned has:
infolId	string (4)	Identifies the info type
lengthCheck	true/false	Indicates if there is a length check on the prompt.
matchValue	string (24)	If prompt is exact match the match value assigned.
maximum	int (20)	Max length.
minimum	int (20)	Min length.
reportValue	string (24)	If prompt is report only the report value.
validationType	string (13)	The validation type for the prompt. ALPHABETIC, ALPHA_NUMERIC, NUMERIC, REPORT_ONLY, EXACT_MATCH, & ACCRUAL_CHECK are the valid options. NOTE: Use EXACT_MATCH to prompt and validate at the pump, use REPORT_ONLY for reporting prompts only. These are most commonly used at the card level.

value	int(24)	Value
<limits> section		Limits on the policy. This is an array of zero to many. Each info returned has:
hours	int (3)	Hours between use
limit	int (4)	Limit value
limitId	string (4)	Limit ID from EFS LLC
minHours	int (20)	Minimum hours between using the limit
autoRollMap	int (3)	If limit is auto roll the auto roll map
autoRollMax	int (4)	Max value for the auto roll limit.
locationGroups	int (10)	If using locationGroups, the locationGroups you want to assign. Zero to many can be sent over.
locations	int (7)	Zero to many. The locationId that the customer wants to block from their fuel network. The customer should send one row per location being blocked.
Time restrictions	array	Holds any time restrictions set-up on the policy.
beginTime	datetime	Begin time for the time restriction. The year, month, day portions will show 1970-01-01, only the time values are applicable.
day	int (1)	The day being restricted. 1 = Sunday, 2 = Monday, 3 = Tuesday, 4 = Wednesday, 5 = Thursday, 6 = Friday, 7 = Saturday
endTime	datetime	The end time for the time restriction. The year, month, day portions will show 1970-01-01, only the time values are applicable.

Error Messages

A fault or flying j exception error.

Get Policy Descriptions

Returns the policy #s and descriptions for all policies belonging to the customer.

getPolicyDescriptions

Input

clientId	string (32)	Returned from the Login response
----------	-------------	----------------------------------

Output

Array of policy descriptions.

contractId	int (20)	The contract ID assigned to the policy.
description	string (30)	The policy name/description.
policyNumber	int (3)	The policy #.

Error Messages

A fault or flying j exception error.

Get Policy Refreshing Limits

This method will return the refreshing limits for a specific policy.

getPolicyRefreshingLimits

Input

clientId	string (32)	The client ID from the login response
policyNumber	Int(3)	The policy # you are checking the refreshing limits on.

Output

It will return the refreshing limit for a card – the limit

dayCntLimit	int	The daily # of transactions allowed.
dayAmtLimit	Int	The daily amount limit in dollars.
weekCntlimit	Int	The weekly # of transactions allowed.
weekAmtLimit	Int	The weekly amount allowed.
monCntlimit	Int	The monthly # of transactions allowed.
monAmtLimit	int	The monthly amount limit.

Error Messages

A fault or flying j exception error.

Get Product Groups

Returns all valid limit product groups.

getProductGroups

Input

clientId	string (32)	Returned from the Login response
----------	-------------	----------------------------------

Output

Array of product groups available for cards and policies.

description	string (30)	The product description.
groupId	string (4)	The product group ID. See Limit IDs for valid values.
groupNumber	int (4)	The group #.
isFuel	true/false	Indicates if the product is a fuel product or not.

Error Messages

A fault or flying j exception error.

Get Products

Returns all valid limit products.

getProducts

Input

clientId	string (32)	Returned from the Login response
----------	-------------	----------------------------------

Output

Array of products.

code	string (4)	The product code ID.
description	string (30)	The product description.
fuelType	int (50)	The fuel type. 0 for non-fuel products.
fuelUse	int (1)	The fuel use. 1 for Tractor, 2 for Reefer, 0 for N/A.
group	string (4)	The group ID.
phraseId	int (4)	The phrase ID used for translation purposes.
shellCIProduct	N/A	Used for Shell Oil only
shellFuelType	N/A	Used for Shell Oil only
shellPriceGroup	N/A	Used for Shell Oil only

Error Messages

A fault or flying j exception error.

Get Prompt Types

Returns all valid prompt codes allowed.

getPromptTypes

Input

clientId	string	Returned from the Login response
----------	--------	----------------------------------

Output

List of available info prompt ids. See [Info IDs](#) for valid values.

Error Messages

A fault or flying j exception error.

Get Registered Checks

A web service method that allows customers to retrieve registered check data for their cleared, un cleared and all checks

getRegisteredChecks

Input

clientId	string (32)	The client ID returned in the login response.
begDate	dateTime	The card number. Required. Start date for search. GMT Time format, i.e., YYYY-MM-DDThh:mm:ss.ccc-hh:mm, where the – hh:mm is the GMT offset for the time zone
endDate	dateTime	Required. End date for search.
checkStatus	String	UNCLEARED – returns uncleared checks only ,ALL – returns all checks, CLEARED– returns cleared checks only

Output

Array of location groups:

amount	Decimal(12,2)	The check amount.
checkNumber	String	The check #
clearedDate	DateTime	The cleared date for cleared checks.
codeCard	Int	The code or card # registered on the check – this will be a card # for SmartFunds cards that register checks.
contractID	Int	The contract ID.
createDate	dateTime	The date/time the check was registered
locationCity	String	The location city
locationID	Int	The location ID registered to, often this will be 60000 the register check default location.
locationName	String	The location name.
locationState	String(2)	The location state/province.
payee	String	The payee name.
reauthLocation	Int	The reauthorized location id, if applicable.
voided	true/false	A flag indicating if the check was voided or not.
referenceID	string	the reference ID from the cash advance table, this is optional. reference_num is the field *this could be from cash_adv table or payr_cash_adv table
confirmationID	string	ID from the cash advance table, this is optionalcash_adv_Id is the field *this could be from cash_adv table or payr_cash_adv table

Error Messages

Session Timeout – Client ID is expired

Invalid Check Status
invalid date format

Get Site Policy Descriptions

This method returns a list of site policy #s and their descriptions and values for a customer.

getSitePolicyDescriptions

Input

clientId	string (32)	The client ID from the login response
----------	-------------	---------------------------------------

Output

An array of zero to many.

sitePolicy	int (3)	The site policy #.
siteDescription	string(30)	The site policy description.
sitePolicyPolicy array		An array of policies the site policy is assigned to – can be zero to many.
contractId	Int (20)	The contract id of the policy.
Description	string	The description of the policy – it could be null.
policyNumber	int(3)	The policy # that the site policy is assigned to.

Error Messages

A fault or flying j exception error.

Get SmartPay Driver

Returns the SmartFunds driver information for a card. All SmartFunds cards are required to have a driver information record set-up.

getSmartPayDriver

Input

clientId	string (32)	Returned from the Login response
cardNum	string (25)	The card #.

Output

cardNumber	string (25)	The card #.
firstName	string (30)	The cardholder's first name.
lastName	string (30)	The cardholder's last name.
address	string (30)	The cardholder's address.
city	string (30)	The cardholder's city.
state	string (2)	The cardholder's state/provincial abbreviation.
postalCode	string (10)	The cardholder's zip or postal code.
country	string (2)	US or CN
dob	datetime	Date of birth, the time values are zeroed out.
last4ss	int (4)	The last 4 of the social security or tax identification.
email	string (50)	Email address.
phone	string (12)	Phone #, 999-999-9999 format.

Error Messages

A fault or flying j exception error.

Get SmartPay Scheduled Transfers

Returns the SmartFunds scheduled transfers for a card.

getSmartPayScheduledTransfers

Input

clientId	string (32)	Returned from the Login response
cardNum	string (25)	The card #.

Output

Array of SmartPay scheduled transfers

transferId	string (30)	The scheduled transfer ID.
transferAccountId	int (30)	Unique ID for the transfer account.
scheduleType	string(2)	The schedule type. DD = DAILY, MD = DAY OF MONTH, TL = TRANSFER ON LOAD, WD = DAY OF WEEK are valid values.
scheduleValue	int (2)	The scheduled value, corresponding to the schedule type chosen.
transferType	string (1)	F = Fixed Amount, P = Percentage
transferValue	decimal (9,2)	the Transfer Value.
emailNotification	string (1)	Y = yes, N = No.

Error Messages

A fault or flying j exception error.

Get SmartPay Transfer Accounts

Returns SmartFunds transfer accounts that are set-up for a card.

getSmartPayTransferAccounts

Input

clientId	string (32)	Returned from the Login response
cardNum	string (25)	The card #.

Output

Array of SmartPay transfer accounts.

transferAccountId	string (30)	Transfer acct ID.
cardNumber	string (25)	The card number.
bankName	string (50)	The bank name.
routingNumber	int (9)	The bank routing ID.
accountNumber	string (17)	The bank account #.
accountOwnerName	string (24)	The bank owner.
accountType	int (1)	28 PRENOTE PAYMENT CHECKING 38 PRENOTE PAYMENT SAVINGS 22 AUTOMATED PAYMENT CHECKING 32 AUTOMATED PAYMENT SAVINGS
accountNickname	string (50)	Account nickname.

Error Messages

A fault or flying j exception error.

Get Transaction Locations

Returns information about transaction locations, from one to many.

getTransLocations

Input

clientId	string (32)	Returned from the Login response
locationIds	array	1 to many
locationId	int (7)	

Output

Array of locations:

address1	string (30)	The address line 1 for the location.
address2	string (30)	The address line 2 for the location.
apartmentNumber		Optional
businessType		Optional
businessUnit		Optional
chainId	int (10)	The Chain ID assigned. See the full list of Chain ID's
city	string (40)	The location city.
country	string (3)	The location country, USA, CAN, MXN for example.
dataSource	string	The data source for the location, if applicable.
entity	string (3)	The taxing entity assigned to the location.
gstTaxId	string (20)	The Canadian Goods & Services Tax (GST) Tax Registration ID for the location, applicable to some Canadian locations only.
id	string (7)	The location ID assigned to the location by EFS LLC.
latitude	float (10,6)	The latitude of the location, if assigned.
longitude	float (10,6)	The longitude of the location, if assigned.
name	string (45)	The location name.
opisId	string (15)	The OPIS ID assigned to the location, used for re-pricing purposes in some cases.
pemexId	string (20)	The Pemex ID for a location (Mexican Pemex).
phone	string (12)	The phone #, formatted 999-999-9999.
pricesUpdated		Typically set to: <pricesUpdated xsi:nil="1" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
qstTaxId	string (20)	The Canadian Quebec Sales Tax (QST) Tax Registration ID for the location, applicable to some Canadian locations only.

rfcNumber	int (10)	The rfc number is blank. Typically, e.g.: <rfcNumber> </rfcNumber>.
site	string	The site. Typically set to: <site xsi:nil="1" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
state	string (2)	The location's state/provincial abbreviation.
status	string (1)	A = Active, H = hold online, still can transaction, any other values indicate the site is not open for transacting.
streetNumber	string (50)	The street #.
supplier	string (10)	The supplier ID for the location assigned by EFS for settlement purposes.
supplierLocCode	string (10)	The location # assigned by the supplier, if applicable.
zip	string (10)	The zip or postal code.
zone	string (10)	The location's zone.
zoneName	string (45)	The zone name.

Error Messages

A fault or flying j exception error.

Get Transaction Locations for Card

Returns information about transaction locations where the specified card # may fuel.

getTransLocationsForCard

For tips on getting transaction data, refer to [Pulling Transactional Data](#).

Input

clientId	string (32)	Returned from the Login response
cardNum	string (25)	Card #.

Output

Array of locations:

address1	string (30)	The address line 1 for the location.
address2	string (30)	The address line 2 for the location.
apartmentNumber		Optional
businessType		Optional
businessUnit		Optional
chainId	int (10)	The Chain ID assigned.
city	string (40)	The location city.
country	string (3)	The location country, USA, CAN, MXN for example.
dataSource	string	The data source for the location, if applicable.
entity	string (3)	The taxing entity assigned to the location.
gstTaxId	string (20)	The Canadian Goods & Services Tax (GST) Tax Registration ID for the location, applicable to some Canadian locations only.
id	string (7)	The location ID assigned to the location by EFS LLC.
latitude	float (10,6)	The latitude of the location, if assigned.
longitude	float (10,6)	The longitude of the location, if assigned.
name	string (45)	The location name.
opisId	string (15)	The OPIS ID assigned to the location, used for re-pricing purposes in some cases.
pemexId	string (20)	The Pemex ID for a location (Mexican Pemex).
phone	string (12)	The phone #, formatted 999-999-9999.
pricesUpdated		Typically set to: <pricesUpdated xsi:nil="1" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
qstTaxId	string (20)	The Canadian Quebec Sales Tax (QST) Tax Registration ID for the location, applicable to some Canadian locations only.

rfcNumber	int (10)	The rfc number is blank. Typically, e.g.: <rfcNumber> </rfcNumber>.
site	string	The site. Typically set to: <site xsi:nil="1" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
state	string (2)	The location's state/provincial abbreviation.
status	string (1)	A = Active, H = hold online, still can transaction, any other values indicate the site is not open for transacting.
streetNumber	string (50)	The street #.
supplier	string (10)	The supplier ID for the location assigned by EFS for settlement purposes.
supplierLocCode	string (10)	The location # assigned by the supplier, if applicable.
zip	string (10)	The zip or postal code.
zone	string (10)	The location's zone.
zoneName	string (45)	The zone name.

Error Messages

A fault or flying j exception error.

Get Transaction Locations for Policy

Returns information about transaction locations for a specific policy #.

getTransLocationsForPolicy

For tips on getting transaction data, refer to [Pulling Transactional Data](#).

Input

clientId	string (32)	Returned from the Login response
policyNum	int (3)	The policy #

Output

Array of locations:

address1	string (30)	The address line 1 for the location.
address2	string (30)	The address line 2 for the location.
apartmentNumber		Optional
businessType		Optional
businessUnit		Optional
chainId	int (10)	The Chain ID assigned.
city	string (40)	The location city.
country	string (3)	The location country, USA, CAN, MXN for example.
dataSource	string	The data source for the location, if applicable.
entity	string (3)	The taxing entity assigned to the location.
gstTaxId	string (20)	The Canadian Goods & Services Tax (GST) Tax Registration ID for the location, applicable to some Canadian locations only.
id	string (7)	The location ID assigned to the location by EFS LLC.
latitude	float (10,6)	The latitude of the location, if assigned.
longitude	float (10,6)	The longitude of the location, if assigned.
name	string (45)	The location name.
opisId	string (15)	The OPIS ID assigned to the location, used for re-pricing purposes in some cases.
pemexId	string (20)	The Pemex ID for a location (Mexican Pemex).
phone	string (12)	The phone #, formatted 999-999-9999.
pricesUpdated		Typically set to: <pricesUpdated xsi:nil="1" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
qstTaxId	string (20)	The Canadian Quebec Sales Tax (QST) Tax Registration ID for the location, applicable to some Canadian locations only.

rfcNumber	int (10)	The rfc number is blank. Typically, e.g.: <rfcNumber> </rfcNumber>.
site	string	The site. Typically set to: <site xsi:nil="1" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
state	string (2)	The location's state/provincial abbreviation.
status	string (1)	A = Active, H = hold online, still can transaction, any other values indicate the site is not open for transacting.
streetNumber	string (50)	The street #.
supplier	string (10)	The supplier ID for the location assigned by EFS for settlement purposes.
supplierLocCode	string (10)	The location # assigned by the supplier, if applicable.
zip	string (10)	The zip or postal code.
zone	string (10)	The location's zone.
zoneName	string (45)	The zone name.

Error Messages

A fault or flying j exception error.

Get Transactions

Returns transactions for a period.

getTransactions

For tips on getting transaction data, refer to [Pulling Transactional Data](#).

Input

clientId	string (32)	Required. Token returned from login
begDate	dateTime	Required. Start date for search. GMT Time format, i.e., YYYY-MM-DDThh:mm:ss.ccc-hh:mm, where the -hh:mm is the GMT offset for the time zone.
endDate	dateTime	Required. End date for search.

Output

Array of [WSTransaction](#)

Error Messages

A fault or flying j exception error.

Get Transactions Extended

Returns extended transaction information (including tax info) for a period.

getTransactionsExt

For tips on getting transaction data, refer to [Pulling Transactional Data](#).

Input

clientId	string (32)	Required. Token returned from login
begDate	dateTime	Required. Start date for search. GMT Time format, i.e., YYYY-MM-DDThh:mm:ss.ccc-hh:mm, where the -hh:mm is the GMT offset for the time zone.
endDate	dateTime	Required. End date for search.

Output

Array of [WSTransactionExtendedv2](#)

Error Messages

A fault or flying j exception error.

Get Transactions Extended Locations

Returns card transactional data for a specified period.

getTransExtLoc

- EFS recommends that customers pull transaction data every 1-15 minutes. Requests for longer periods take more time to load and can increase timeouts, since our servers store 15 minutes of transactions in memory. So, for example, polling for 11 minutes worth of data every 10 minutes is much more efficient than polling two or three times a day.
- Do not pull more than three months of data at one time.
- It is good practice to put in a daily check to make sure the end system has received all fuel card transactions for the previous day. The system could do a one-time run after midnight for the previous day and make sure all transaction IDs are inputted. Transaction IDs are unique #s for each transaction.

Input

clientId	string (32)	Required. Token returned from login
begDate	dateTime	Required. Start date for search. GMT Time format, i.e., YYYY-MM-DDThh:mm:ss.ccc-hh:mm, where the -hh:mm is the GMT offset for the time zone.
endDate	dateTime	Required. End date for search.

Output

Array of [WSTransactionExt](#), with the additional fields listed below

chainId	numeric (10)	From the location.chain_id field. See list of Chain ID's
locationName	string (50)	Location name
locationstate	string (2)	Location state/province abbreviation
originalTransId	string (20)	If a transaction is a credit transaction, populate the transaction ID that was credited in this field.

Error Messages

A fault or flying j exception error.

Get Transactions Preferred

Returns transactions for a period.

getMcTransExtLocV2

*Note: The **preferred version** for getting transactions, which should be used for all new development.*

For tips on getting transaction data, refer to [Pulling Transactional Data](#).

Input

clientId	string (32)	Required. Token returned from login
begDate	dateTime	Required. Start date for search. GMT Time format, i.e., YYYY-MM-DDThh:mm:ss.ccc-hh:mm, where the -hh:mm is the GMT offset for the time zone.
endDate	dateTime	Required. End date for search.

Output

Array of [WSTransactionExtendedv2](#)

Error Messages

A fault or flying j exception error.

Get Transactions Rejects

Returns rejected transactions. This can be narrowed to a specific card, merchant location, or invoice or pulled for an entire customer.

getTranRejects

- EFS recommends that customers pull transaction data every 1-15 minutes. Requests for longer periods take more time to load and can increase timeouts, since our servers store 15 minutes of transactions in memory. So, for example, polling for 11 minutes worth of data every 10 minutes is much more efficient than polling two or three times a day.
- For tips on getting transaction data, refer to [Pulling Transactional Data](#).

Input

clientId	string (32)	Required. Token returned from login
startDate	dateTime	Required. Start date for search. GMT Time format, i.e. YYYY-MM-DDThh:mm:ss.ccc-hh:mm, where the -hh:mm is the GMT offset for the time zone.
endDate	dateTime	Required. End date for search.
cardNum	string (25)	The EFS LLC card # the system is adding cash to or removing cash from.
invoice	string (15)	Invoice reference on the customer receipt. Use this only if the system is looking for a reject for a specific receipt else leave null.
locationId	int (7)	EFS LLC Location ID. Use this only if the system is looking for rejects for a specific location ID.

Output

Array of Transaction Rejects. There can be zero to many rejects based on the input. Each reject contains:

tranDate	dateTime	The reject date/time, Central Time zone.
cardNum	string (25)	The EFS LLC card # the system is adding cash to or removing cash from.
invoice	string (15)	Invoice reference on the customer receipt. Use this only if the system is looking for a reject for a specific receipt else leave null.
locId	int (7)	EFS LLC Location ID. Use this only if the system is looking for rejects for a specific location ID.
locName	string (45)	The location's name.
locCity	string (30)	The location's city.
locState	string (2)	The location's state/provincial abbreviation.
errorCode	int (4)	The EFS LLC error code # for the reject.
errorDesc	string (100)	The error message for the reject.
unit	string (24)	The unit # on the reject.

Error Messages

A fault or flying j exception error.

Issue Money Code

Creates money codes or EFS LLC checks.

issueMoneyCode

Input

All fields required.

clientId	string (32)	Client ID returned in the login response.
contractId	int (20)	EFS contract ID
masterContractId	int (20)	This is only used by specific customers, all others should set it to -1.
amount	decimal	Amount of the money code, e.g., 100.00 is \$100.00.
feeType	boolean (1)	Sets whether fees are deducted from the amount or not. If not, set to 0, else if fees are deducted, set to 1.
issuedTo	string (30)	Who the money code is issued to
notes	string (30)	Notes section for the code
currency	string (3)	USD or CAD

Output

[WSMoneyCode](#) object

Error Messages

- Amount larger than user maximum = Amount is more than the money code limit on the contract.
- Too many codes issued by user = User has reached max money codes issued per day/week.
- A fault error or flying j exception error.

Issue Money Code with Prompts

Creates money codes or EFS LLC checks with prompt values for reporting purposes only.

issueMoneyCodePrompts

Input

All fields required.

clientId	string (32)	Client ID returned in the login response.
contractId	int (20)	EFS contract ID
masterContractId	int (20)	This is only used by specific customers, all others should set it to -1.
amount	decimal	Amount of the money code, e.g., 100.00 is \$100.00.
feeType	boolean (1)	Sets whether fees are deducted from the amount or not. If not, set to 0, else if fees are deducted, set to 1.
issuedTo	string (30)	Who the money code is issued to
notes	string (30)	Notes section for the code
currency	string (3)	USD or CAD
Prompt	N/A	Array of Prompt Values
infoType	string (4)	The info ID for the prompt item. See Info IDs for the valid infos.
infoValue	string (24)	This is the info/prompt value. For example, this is the Driver ID #, Unit #, etc., that will be reported.

Output

[WSMoneyCode](#) object

Error Messages

- Amount larger than user maximum = Amount is more than the money code limit on the contract.
- Too many codes issued by user = User has reached max money codes issued per day/week.
- A fault error or flying j exception error.

Issue New Payroll Card

Makes a new instant issue card for the carrier/clientId.

issueNewPayrollCard

Input

clientId	string (32)	The client ID from the login response
Data		
shipToFirst	string(30)	Shipping contact first name.
shipToLast	string(30)	Shipping contact last name.
shipToAddress1	string(30)	Shipping contact address line 1.
shipToAddress2	string(30)	Shipping contact address line 2.
shipToCity	string(30)	Shipping contact city.
shipToState	string(2)	Shipping contact state/provincial abbreviation.
shipToZip	string(10)	Shipping contact zip or postal code.
shipToCountry	string(3)	Shipping contact country USA or CAN.
shippingMethod	int	The shipping method.
rushProcessing	Char(1)	Y – Rush order No – Standard shipping NOTE: Charges may apply to rush orders

Output

orderId	Long	The order id for the card order.
requestStatus	String	Indicates SUCCESS or ERROR.

Error Messages

A fault or flying j exception error.

Issue New Personalized Payroll Card

This method is used to issue a personalized payroll card.

issueNewPersonalizedPayrollCard

Input

clientId	string (32)	The client ID from the login response
Data		
embossedName	string (25)	The embossed name on the card – reminder only certain # of characters will fit on the front of the card. If you have a custom card style, test to see how many characters will print.
shipToFirst	string(30)	The shipping contact first name.
shipToLast	string(30)	The shipping contact last name.
shipToAddress1	string(30)	The shipping contact address 1 line.
shipToAddress2	string(30)	The shipping contact address 2 line.
shipToCity	string(30)	The shipping contact city.
shipToState	string(2)	The shipping contact state or provincial code.
shipToZip	string(10)	The shipping contact zip or postal code.
shipToCountry	string(3)	The shipping contact country USA or CAN.
shippingMethod	int	The shipping method.
rushProcessing	Char(1)	Y – Rush order No – Standard shipping NOTE: Charges may apply to rush orders

Output

orderId	Long	The order id for the card order.
requestStatus	String	Indicates SUCCESS or ERROR.

Error Messages

A fault or flying j exception error.

IVR Login

Validates Interactive Voice Response (IVR) logins for the Automated Phone System.

ivrLogin

Input

clientId	string (32)	Client ID returned in the login response.
passwd	string (30)	The password.
userId	string (15)	The IVR user ID.

Output

Successful or rejected login response.

Error Messages

A fault or flying j exception error.

Load Cash [by card number]

Loads one-time or SmartFunds cash to a card. This is coming soon in release 11.5 from EFS.

loadCash

Input

clientId	string (32)	The clientId from the Login response.
cardNumber	string (25)	The EFS LLC card # the system is adding cash to or removing cash from.
amount	decimal (12,2)	Amount of the cash advance, this can be negative. If this is a removal, put a negative sign in front of the amount (i.e., -50.00 is to remove \$50, etc.)
refNumber	string (24)	Optional. a reference # for the cash advance, for example this can be an order # or settlement ID.
payroll	boolean (1)	Set to 1 or true to load to SmartFunds or set to 0 or false to load to the one-time cash side of the card.

Output

A successful load cash response

example : <soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">

<soapenv:Body>

<ns5:loadCashResponse xmlns:ns5="http://com.tch.cards.service"/>

</soapenv:Body>

</soapenv:Envelope>

or a decline with error text.

Error Messages

- Invalid Card #
- Amount too high for user.
- Attempting to remove too much from a card (more than the balance).
- A fault or flying j exception error may be returned.

Load Cash Version 2

Loads one-time or SmartFunds cash to a card. If your account is flagged (request made by your Account Manager) you can put a duplicate check mechanism in to avoid duplicate loads

loadCashV2

Input

clientId	string (32)	The clientId from the Login response.
cardNumber	string (25)	The EFS LLC card # the system is adding cash to or removing cash from.
amount	decimal (12,2)	Amount of the cash advance, this can be negative. If this is a removal, put a negative sign in front of the amount (i.e., -50.00 is to remove \$50, etc.)
refNumber	string (24)	Optional. a reference # for the cash advance, for example this can be an order # or settlement ID.
payroll	boolean (1)	Set to 1 to load to SmartFunds or set to 0 to load to the one-time cash side of the card.

Output

A successful load cash response

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <soapenv:Body>
    <ns5:loadCashV2Response xmlns:ns5="http://com.tch.cards.service">
      <result>
        <confirmationNumber>19267432</confirmationNumber>
      </result>
    </ns5:loadCashV2Response>
  </soapenv:Body>
</soapenv:Envelope>>
```

Error Messages

- Invalid Card #
- Amount too high for user.
- Attempting to remove too much from a card (more than the balance).
- A fault or flying j exception error may be returned.
- Duplicate Advance, see confirmation #
- Duplicate Pending Advance, see confirmation #

(Internal Wex note: insert into member_meta (member_meta_id,member_id, mm_key, mm_value) VALUES (0,106651, 'CASHDUPCHK','D3');

example .. of mm_value MX -- X number of months DX -- X number of Days YX

Note: Max Month check is 1

Load Cash by Driver ID

Loads one-time or SmartFunds cash to a card by using the Driver ID.

loadCashDriverId

Input

clientId	string (32)	The clientId from the Login response.
driverId	string (24)	The EFS LLC driver ID the system is adding cash to or removing cash from.
amount	decimal (12,2)	Amount of the cash advance, this can be negative. If this is a removal, put a negative sign in front of the amount (i.e. -50.00 is to remove \$50, etc.)
refNumber	string (24)	Optional. A reference # for the cash advance, for example this can be an order # or settlement ID.
payroll	boolean	Set to 1 to load to SmartFunds or default set to 0 to load to the one-time cash side of the card.

Output

A successful load cash response

```
example : <soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <soapenv:Body>
    <ns5:loadCashResponse xmlns:ns5="http://com.tch.cards.service"/>
  </soapenv:Body>
</soapenv:Envelope>
```

or a decline with error text.

NOTE: if using this method, it is important that the Driver IDs assigned to the card are always unique and that the same Driver ID is not assigned to multiple cards. If multiple cards have the same Driver ID the system will not be able to load cash to the Driver ID's card.

Error Messages

- Invalid Card #
- Amount too high for user.
- Attempting to remove too much from a card (more than the balance).
- A fault string or flying j exception error may be returned.

Load Cash by Driver ID Version 2

Loads one-time or SmartFunds cash to a card. If your account is flagged (request made by your Account Manager) you can put a duplicate check mechanism in to avoid duplicate loads

loadCashDriverIdV2

Input

clientId	string (32)	The clientId from the Login response.
driverId	string (24)	The EFS LLC driver ID the system is adding cash to or removing cash from.
amount	decimal (12,2)	Amount of the cash advance, this can be negative. If this is a removal, put a negative sign in front of the amount (i.e. -50.00 is to remove \$50, etc.)
refNumber	string (24)	Optional. A reference # for the cash advance, for example this can be an order # or settlement ID.
payroll	boolean	Set to 1 to load to SmartFunds or default set to 0 to load to the one-time cash side of the card.

Output

A successful load cash response

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <soapenv:Body>
    <ns5:loadCashV2Response xmlns:ns5="http://com.tch.cards.service">
      <result>
        <confirmationNumber>19267432</confirmationNumber>
      </result>
    </ns5:loadCashV2Response>
  </soapenv:Body>
</soapenv:Envelope>>
```

Error Messages

- Invalid Card #
- Amount too high for user.
- Attempting to remove too much from a card (more than the balance).
- A fault or flying j exception error may be returned.
- Duplicate Advance, see confirmation #
- Duplicate Pending Advance, see confirmation #

(Internal Wex note: insert into member_meta (member_meta_id,member_id, mm_key, mm_value) VALUES (0,106651, 'CASHDUPCHK','D3');

example .. of mm_value MX -- X number of months DX -- X number of Days YX

Note: Max Month check is 1

Login

Login to the web service; returns a client ID that is used in all other methods as a form of authentication.

login

Input

user	string (25)	The user
password	string (30)	The password of the user.

Output

Result

clientId	string (32)	The clientId that will be used in all future method calls if they require a clientId.
----------	-------------	---

Error Messages

- InvalidLoginException = password is incorrect.
- InvalidAccountException = bad user.
- AccountLockedException = the account has been locked because of too many invalid logins.
- A fault or flying j exception error may be returned.

Logout

Logout.

logout

Input

clientId	string (32)	The client ID being logged out
----------	-------------	--------------------------------

Output

If the logout was successful, the call will just return with no return values. If there was an error, a fault will be returned.

Error Messages

A fault or flying j exception error.

Managed Fuel Action

Locks a card down to a route determined by a fuel optimization system.

managedFuelAction

Input

clientId	string (32)	The client ID returned in the login response.
Array of managed fuel requests:		
tripNumber	string (24)	The trip # for the order.
tripSeq	int (2)	The sequence of the fuel stop in the optimization request.
cardNumber	string (25)	The card #.
cardNumber2	string (25)	The card # 2, if this is team driver.
locationId	int(7)	The location ID.
fuelType	string (10)	The fuel type, if locking down to one fuel type.
fuelUse		1 Tractor or 2 Reefer
qtyAllowed		The maximum quantity allowed at the stop.
effDt	datetime	The effective date/time for the fuel stop.
expDt	datetime	The expiration date/time for the fuel stop.
action		The managed fuel action value.

Output

Successful response or a decline fuel action response.

Error Messages

A fault or flying j exception error.

Managed Fuel Action by Driver

Locks a card down to a route determined by a fuel optimization system using the Driver ID assigned to the card.

managedFuelAction

Input

clientId	string (32)	The client ID returned in the login response.
Array of managed fuel requests:		
tripNumber	string (24)	The trip # for the order.
tripSeq	int (2)	The sequence of the fuel stop in the optimization request.
driverId	string (24)	The Driver ID 1.
driverId	string (24)	The card # 2, if this is team driver.
locationId	int(7)	The location ID.
fuelType	string (10)	The fuel type, if locking down to one fuel type.
fuelUse		1 Tractor or 2 Reefer
qtyAllowed		The maximum quantity allowed at the stop.
effDt	datetime	The effective date/time for the fuel stop.
expDt	datetime	The expiration date/time for the fuel stop.
action		The managed fuel action value.

Output

Successful response or a decline fuel action response.

NOTE: if using this method, make sure to only have 1 card at a time assigned to any given Driver ID value, else the system will error on any attempts to load a fuel action for a Driver ID.

Error Messages

A fault or flying j exception error.

Money Code Summary

Returns the summary money code usage for a customer for a given period, including the count, total amount issued, and total used.

moneyCodeSummary

Input

clientId	string (25)	Client ID returned in the login response.
begDate	datetime	The beginning date/time the system is requesting money code information for.
endDate	datetime	The end date/time the system is requesting money code summary information for.

Output

mcCount	int (10)	Total # of money codes issued in the period.
mcTotal	decimal (12,2)	The total amount of money codes issued.
mcUsedTotal	decimal (12,2)	The total amount of money codes cashed in the period.

Error Messages

A fault or flying j exception error may be returned.

Override Last Mileage

Overrides the odometer for a unit.

overrideLastMileage

Input

clientId	string (32)	The client ID returned in the login response.
unit	string (24)	The unit #.
code	string (4)	The code, Odometer (ODRD) or Hubometer (HBRD).
mileage	numeric	The mileage that you want to use

Output

Successful response indicating odometer or hubometer was updated else decline error.

Error Messages

A fault or flying j exception error may be returned.

Pull Carrier Gets Discount Data

This pulls child carriers for a given parent id. You need the get a client id from the login WS.

pullCarrierGetsDiscountData

Input

clientId	string (32)	The client ID from the login response
lookupValue	string	This is either a child carrier id (child carrier) or All (leaving it empty I treat it as an All).

Output

An array of zero to many.

carrier	int(7)	The carrier ID
getsDiscount	Boolean	Y – yes carrier gets discount N – Carrier doesn't get the discount
carrierName	String(30)	The child carrier name.
modifiedDate	Datetime	The date/time the discount was last modified.

Error Messages

- A fault string or an error with a message.

Register Card Position

Registers the position of a card (latitude/longitude).

registerCardPosition

Input

clientId	string (32)	The client ID returned in the login response.
cardNum	string (25)	The card #.
latitude	float (10,6)	The latitude.
longitude	float (10,6)	The longitude.
source	string (24)	The data source.

Output

Successful response indicating card position was registered else a decline with an error string.

Error Messages

A fault or flying j exception error may be returned.

Register Check

Registers a check from one-time or SmartFunds cash on the card.

registerCheck

Input

clientId	string (32)	The client ID returned in the login response.
Array of registered check authorizations.		
cardNumber	string (25)	The card # the check is being registered from.
checkNumber	string (10)	The check # being registered.
dollarAmount	decimal (12,2)	The amount of the check.
fromUniversal	boolean (1)	If this check is from SmartFunds set to 1; else 0.

Output

Successful check registration(s) or decline with error text.

Error Messages

A fault or flying j exception error may be returned.

Reissue Damaged Card

Reissues a damaged payroll card (card type 5.5).

reissueDamagedCard

Input

clientId	string (32)	The client ID from the login response
data- an array of 1 to many		
cardNumber	Int(19)	The card #.
shipToFirst	String(30)	
shipToLast	String(30)	
shipToAddress1	String(30)	
shipToAddress2	String(30)	
shipToCity	String(30)	
shipToState	String(2)	
shipToZip	String(10)	
shipToCountry		
shippingMethod	int	
rushProcessing	Char(1)	Y – Rush order No – Standard shipping NOTE: Charges may apply to rush orders
reason	string	

Output

orderId	long	The card order id.
responseStatus	String	Shows the status of SUCCESS or ERROR

Error Messages

A fault or flying j exception error may be returned.

Remove Card

Removes a card.

removeCard

Input

clientId	string (32)	The client ID returned in the login response.
cardNumber	string (25)	The card #.

Output

Successful card number removal/deletion or decline with error response.

NOTE: This deletes the card within the EFS LLC system so only use this method if the user truly wants to delete the card.

Error Messages

A fault or flying j exception error may be returned.

Remove Location Group

This method will remove a location group from a customer.

removeLocGrp

Input

clientId	string (32)	The client ID from the login response
groupId	Int	The location group.

Output

Blank response is a success		
-----------------------------	--	--

Error Messages

- A fault string or flying j exception error may be returned.

Remove Location Group Locations

This method will remove location ids from a location group – for example if you want to remove a location from a fuel network.

removeLocGrpLocs

Input

clientId	string (32)	The client ID from the login response
groupId	int	
Locs	array	An array of 1 to many location ids. The location ids should be 6 digit EFS LLC location ids that are valid in the system.

Output

Blank response is a success		
-----------------------------	--	--

Error Messages

- A fault string or flying j exception error may be returned.

Replace Lost or Stolen Card

This is a web service method to replace a lost or stolen card.

replaceLostOrStolenCard

Input

clientId	string (32)	The client ID from the login response
data- an array of 1 to many		
cardNumber	Int(19)	The card #.
shipToFirst	String(30)	
shipToLast	String(30)	
shipToAddress1	String(30)	
shipToAddress2	String(30)	
shipToCity	String(30)	
shipToState	String(2)	
shipToZip	String(10)	
shipToCountry		
shippingMethod	int	
rushProcessing	Char(1)	Y – Rush order No – Standard shipping NOTE: Charges may apply to rush orders
reason	string	

Output

orderId	long	The card order id.
responseStatus	String	Shows the status of SUCCESS or ERROR

Error Messages

- A fault string or flying j exception error may be returned.

Search Location

Retrieves location information, by a specific location ID, state/province, city, name, country or location chain.

searchLocation

Note the system needs to select 1 to many items to search, not all are required.

Input

clientId	string (32)	Client ID returned in the login response.
locId	int (7)	If searching a specific location set else don't set.
state	string (2)	The state/provincial abbreviation.
city	string (30)	The city name.
name	string (45)	The location name. Note this is a "like" search.
country	string (3)	The country code, set to USA, CAN or MXN.
chainId	int (10)	The location's chain ID .

Output

An array of matching locations:

locId	int (7)	The EFS LLC Location ID for the location.
state	string(2)	The State or Provincial abbreviation.
city	string (30)	The city.
name	string (45)	The location name.
country	string (3)	The location country, CAN, USA, MXN for example.
chainId	int (7)	The chain the location belongs to, 0 is used for any locations not assigned to chains. List of Chain ID's
addr1	string (30)	The address line 1 for the location.
addr2	string (30)	The second address line for the location.
phone	string (12)	The phone # for the location, formatted 999-999-9999.

Error Messages

- InvalidLoginException = password is incorrect.
- A fault or flying j exception error may be returned.

Server Time

Returns the current server time (Central Time zone based).

serverTime

Input

clientId	string (32)	Client ID returned in the login response.
----------	-------------	---

Output

serverTime	datetime	The server time for EFS LLC, based on the Central Time zone.
------------	----------	--

Error Messages

- A fault string or flying j exception error may be returned.

Set Card

Updates card information.

Note: Make sure you echo back all fields from the getCard response, changing the applicable fields. Only remove fields or blank them out if you intend to remove them. This method does not assume that only changed values are being changed and other values remain the same. For example, if the system gets an <infos> record for Driver ID in the getCard response, if the system drops that <infos> record in the setCard, the card will no longer have a Driver ID assigned.

setCard

Input

clientId	string (32)	Client ID from the login response.
cardNumber	string (25)	The card number the system is updating.
Header		
companyXRef	string (15)	The company Xref populated for the card.
handEnter	string (7)	ALLOW, DISALLOW or POLICY
infoSource	string (7)	Indicates if the Prompt Infos are at the Card, Policy, or Both levels. Valid values are POLICY, CARD or BOTH.
limitSource	string (7)	POLICY, CARD or BOTH.
locationOverride	boolean (1)	0 = no override, 1 = override Please see the OVERRIDE appendix to see additional details about overrides.
locationSource	string (7)	POLICY, CARD or BOTH
overrideAllLocations	true/false	
originalStatus	string (8)	Active, Inactive, Deleted
payrollStatus	string (8)	Active, Inactive, Follows
override	boolean (1)	0 = false, 1 = true
policyNumber	int (3)	The policy # the card belongs to, 1-99 are valid.
status	string (7)	Active, Inactive, Hold, Deleted
timeSource	string (7)	POLICY, CARD, or BOTH
lastUsedDate	datetime	The last used date/time on the card.
lastTransaction	string (10)	The authorization # for the last transaction on the card.
payrollUse	string (1)	The payroll use value, P - payroll B - Both payroll and normal N - Normal Y - Debit L - Debit with Limits
payrollAtm	string (8)	DISALLOW or ALLOW SmartFunds from the ATM
payrollChk	string (8)	DISALLOW or ALLOW registered checks from SmartFunds

payrollAch	string (8)	DISALLOW or ALLOW ACH from SmartFunds.
payrollWire	string (8)	DISALLOW or ALLOW Wires from SmartFunds.
payrollDebit	string (8)	DISALLOW or ALLOW use of SmartFunds on the debit network (Maestro, etc.)
Infos Object		A list of prompts assigned to the card. Only prompts assigned at the CARD level are set here, POLICY level values are set via setPolicy.
infold	string (4)	The info ID for the prompt item. See Info IDs for the valid infos.
lengthCheck	true/false	Indicates if length check is on or off for a prompt.
matchValue	string (24)	If a prompt is Exact Match this is the value. For example, this is the Driver ID #, Unit #, etc. Do not send more than 24 characters in this field.
maximum	numeric (10)	The maximum value. Only checked if lengthCheck is true.
minimum	numeric (10)	The minimum value. Only checked if lengthCheck is true.
reportValue	string (24)	If a prompt is Report Only this is the report value. For example, this is the Driver ID #, Unit #, etc., that will be reported.
validationType	string (13)	The validation type for the prompt. ALPHABETIC, ALPHA_NUMERIC, NUMERIC, REPORT_ONLY, EXACT_MATCH, ACCRUAL_CHECK & DYNAMIC are the valid options. NOTE: Use EXACT_MATCH to prompt and validate at the pump, use REPORT_ONLY for reporting prompts only. These are most commonly used at the card level. DYNAMIC can only be used with CNTN, PPIN and DRID
value	String	For the accrual check method for odometer or hubometer, this is the accrual value. For all other info ids/validation type combos just leave as <value/> or <value>0</value>
Limits Object		A list of limits assigned to the card. Only limits assigned at the CARD level are set here, POLICY level values are set via setPolicy.
hours	int (3)	The hours the limit is good for before resetting.
limit	numeric (4)	The limit value, which will be Gallons for Fuel or DEF dispensed and dollar amounts in all other cases. For example if the limit is ULSD and this value is 300 that will be 300 gallons. This will be a value from 0 to 9999.
limitId	string	The limit ID for the limit value. See Limit IDs for values.
minHours	int (3)	Minimum hours between using the limit between uses.
Location Groups Object		A list of location groups assigned to the card if the customer participates in using location groups. There can be zero to many location groups.
locationGroups	int (10)	The location group.
Locations Object		A list of locations that this card is BLOCKED from using. Only add to this list if you want to block the card from going to the locations listed. There can be zero to many locations.

locations	int (7)	The location ID for the location being blocked.
Time Restrictions Object		A list of time restrictions that are applicable for the card. Only card level values are set here, policy level values are set via setPolicy.
beginTime	datetime	Begin time for the time restriction. The year, month, day portions will show 1970-01-01, only the time values are applicable.
day	int (1)	The day being restricted. 1 = Sunday, 2 = Monday, 3 = Tuesday, 4 = Wednesday, 5 = Thursday, 6 = Friday, 7 = Saturday
endTime	datetime	The end time for the time restriction. The year, month, day portions will show 1970-01-01, only the time values are applicable.

Output

A successful response or a decline error with text.

Error Messages

- A fault string or flying j exception error may be returned.

Set Card Version 2

Updates card information. This version allows users to set refreshing limits via the auto roll fields at the card level, where the original version did not that functionality.

Note: Make sure you echo back all fields from the getCard response, changing the applicable fields. Only remove fields or blank them out if you intend to remove them. This method does not assume that only changed values are being changed and other values remain the same. For example, if the system gets an <infos> record for Driver ID in the getCard response, if the system drops that <infos> record in the setCard, the card will no longer have a Driver ID assigned.

setCardV2

Input

clientId	string (32)	Client ID from the login response.
cardNumber	string (25)	The card number the system is updating.
Header		
companyXRef	string (15)	The company Xref populated for the card.
handEnter	string (7)	ALLOW, DISALLOW or POLICY
infoSource	string (7)	Indicates if the Prompt Infos are at the Card, Policy, or Both levels. Valid values are POLICY, CARD or BOTH.
limitSource	string (7)	POLICY, CARD or BOTH.
locationOverride	boolean (1)	0 = no override, 1 = override Please see the OVERRIDE appendix to see additional details about overrides.
locationSource	string (7)	POLICY, CARD or BOTH
overrideAllLocations	true/false	
originalStatus	string (8)	Active, Inactive, Deleted
payrollStatus	string (8)	Active, Inactive, Follows
override	boolean (1)	0 = false, 1 = true
policyNumber	int (3)	The policy # the card belongs to, 1-99 are valid.
status	string (7)	Active, Inactive, Hold, Deleted
timeSource	string (7)	POLICY, CARD, or BOTH
lastUsedDate	datetime	The last used date/time on the card.
lastTransaction	string (10)	The authorization # for the last transaction on the card.
payrollUse	string (1)	The payroll use value, P - payroll B - Both payroll and normal N - Normal Y - Debit L - Debit with Limits
payrollAtm	string (8)	DISALLOW or ALLOW SmartFunds from the ATM

payrollChk	string (8)	DISALLOW or ALLOW registered checks from SmartFunds
payrollAch	string (8)	DISALLOW or ALLOW ACH from SmartFunds.
payrollWire	string (8)	DISALLOW or ALLOW Wires from SmartFunds.
payrollDebit	string (8)	DISALLOW or ALLOW use of SmartFunds on the debit network (Maestro, etc.)
Infos Object		A list of prompts assigned to the card. Only prompts assigned at the CARD level are set here, POLICY level values are set via setPolicy.
infolD	string (4)	The info ID for the prompt item. See Info IDs for the valid infos.
lengthCheck	true/false	Indicates if length check is on or off for a prompt.
matchValue	string (24)	If a prompt is Exact Match this is the value. For example, this is the Driver ID #, Unit #, etc. Do not send more than 24 characters in this field.
maximum	numeric (10)	The maximum value. Only checked if lengthCheck is true.
Minimum	numeric (10)	The minimum value. Only checked if lengthCheck is true.
reportValue	string (24)	If a prompt is Report Only this is the report value. For example, this is the Driver ID #, Unit #, etc., that will be reported.
validationType	string (13)	The validation type for the prompt. ALPHABETIC, ALPHA_NUMERIC, NUMERIC, REPORT_ONLY, EXACT_MATCH, ACCRUAL_CHECK & DYNAMIC are the valid options. NOTE: Use EXACT_MATCH to prompt and validate at the pump, use REPORT_ONLY for reporting prompts only. These are most commonly used at the card level. DYNAMIC can only be used with CNTN, PPIN and DRID
value	String	For the accrual check method for odometer or hubometer, this is the accrual value. For all other info ids/validation type combos just leave as <value/> or <value>0</value>
Limits Object		A list of limits assigned to the card. Only limits assigned at the CARD level are set here, POLICY level values are set via setPolicy.
hours	int (3)	The hours the limit is good for before resetting.
limit	numeric (4)	The limit value, which will be Gallons for Fuel or DEF dispensed and dollar amounts in all other cases. For example if the limit is ULSD and this value is 300 that will be 300 gallons. This will be a value from 0 to 9999.
limitId	string	The limit ID for the limit value. See Limit IDs for values.
minHours	int (3)	Minimum hours between using the limit between uses.
autoRollMap	int (3)	If limit is auto roll the auto roll map.
autoRollMax	int (4)	Max value for the auto roll limit. Max 9999. Please set this to 0 if you don't want a maximum daily limit.
Location Groups Object		A list of location groups assigned to the card if the customer participates in using location groups. There can be zero to many location groups.

locationGroups	int (10)	The location group.
Locations Object		A list of locations that this card is BLOCKED from using. Only add to this list if you want to block the card from going to the locations listed. There can be zero to many locations.
locations	int (7)	The location ID for the location being blocked.
Time Restrictions Object		A list of time restrictions that are applicable for the card. Only card level values are set here, policy level values are set via setPolicy.
beginTime	datetime	Begin time for the time restriction. The year, month, day portions will show 1970-01-01, only the time values are applicable.
day	int (1)	The day being restricted. 1 = Sunday, 2 = Monday, 3 = Tuesday, 4 = Wednesday, 5 = Thursday, 6 = Friday, 7 = Saturday
endTime	datetime	The end time for the time restriction. The year, month, day portions will show 1970-01-01, only the time values are applicable.

Output

A successful response or a decline error with text.

Error Messages

- A fault string or flying j exception error may be returned.

Set Card PIN

This is the web service method to reset the Card ATM/IVR PIN.

setCardPin

Input

clientId	string (32)	The client ID from the login response
cardNum	string (25)	The card #
newPin	num (4)	The new 4-digit PIN. This cannot be the last 4 digits of the card.

Output

Result	String	The PIN # that you requested.
--------	--------	-------------------------------

Error Messages

- Result -1 indicates an error.
- A fault or flying j exception error may be returned.

Set Card Refreshing Limits

This web service method is used to set the refreshing/velocity limits on a card. Primarily

setCardRefreshingLimits

Input

clientId	string (32)	The client ID from the login response
cardNumber	int(19)	The card # being updated.
refreshingLimitSource	string	D - Policy, C - Card, or B - Both
dayCntLimit	int	The daily # of transactions allowed.
dayAmtLimit	Int	The daily amount limit in dollars.
weekCntlimit	Int	The weekly # of transactions allowed.
weekAmtLimit	Int	The weekly amount allowed.
monCntlimit	Int	The monthly # of transactions allowed.
monAmtLimit	int	The monthly amount limit.

Output

requestStatus	String	This will indicate a success or an error.
---------------	--------	---

Error Messages

- A fault string or flying j exception error may be returned.

Set Carrier Discount

This method indicates if a child carrier id gets the discounts or not from the parent.

setCarrierDiscount

Input

clientId	string (32)	The client ID from the login response
carrierDiscount array – 1 to many		
carrier	Int(7)	The child carrier id
getsDiscount	String	Y – yes the child carrier gets the discount N – no the child carrier doesn't get the discount

Output

Result	String	SUCCESS or ERROR
--------	--------	------------------

Error Messages

- A fault string or flying j exception error may be returned.

Set Location Group Locations

This method adds location groups to the location group created in the add location group method and will override any existing location ids that were in the location group (so add location groups locations adds to a list but this method replaces the list with the new values). You can add 1 to many location ids in one request.

setLocGrpLocs

Input

clientId	string (32)	The client ID from the login response
groupId	Int	The group Id created in the method add location groups.
Loc	Array	An array of 1 to many location ids. Make sure you use valid 6 digit EFS LLC location ids in your input for a valid result.

Output

A positive result string with no error		
--	--	--

Error Messages

- This method returns a fault string if there is an error and will return a flying j exception error in some cases.

Set Location Group Rule

This method is used to set location group rules for locations that are rule based. Rule-based groups consist of area/location type pairs.

- The area can be empty, a country (USA or CAN), or the abbreviation for a US or Canadian state or province.
- The location type can be empty or any of the valid location types.

The rules when set will be a pipe-delimited list of comma delimited pairs, e.g.:

CAN,|AK,FJ

Try not to add contradictory rules – the authorization process may not be able to handle a transaction if you set up something that is illogical.

The only way to delete a rule is to remove the location group (delete it) and then you can add a new one with new rules.

setLocGrpRule

Input

clientId	string (32)	The client ID from the login response
groupId	int	The location group being edited.
rule	string	The rule for the location group. Valid location types are listed here .

Output

Status 200 success -		
----------------------	--	--

Error Messages

- A fault string or flying j exception error may be returned.

Set Moneycode Bill On Issue

Switches a contract's money code bill on issue flag from Yes (bill on issue) to No (bill on use).

setMcodeBillOnIssue

Input

clientId	string (32)	The client ID from the login response
contractID	int (20)	The contract ID being updated
ynFlag	string (1)	Y or N for how you want to change the setting

Output

Success response indicates a good request, else an error or soap fault indicates an issue with the request.

Error Messages

- A fault string or flying j exception error may be returned.

Set Policy

Updates a policy. Updates to the policy will impact all cards under the policy, especially if the card infos, limits, locations, and/or time restrictions are set to Both or Policy.

setPolicy

Input

clientId	string	Returned from the Login response
policyNumber	int (3)	The policy # the system or user is inquiring upon. The information related to the policy will be returned.
<header> section		Main info on policy.
contractId	int (20)	The Contract ID assigned to the Policy. This is the main billing contract ID assigned to the customer by EFS LLC's financial system. Note that transactions for SmartFunds or falling under specific site policies may hit a different contract based on set-up.
description	string (30)	The description/name assigned to the policy.
handEnter	true/false	Indicates if Hand Entry is allowed at the policy level or not.
payrollContractId	int (20)	If the customer has SmartFunds, the contract ID for SmartFunds else 0.
payrollAtm	true/false	Indicates if SmartFunds can be drawn at the ATM for the policy.
payrollChk	true/false	Indicates if SmartFunds can be drawn via registered check.
payrollAch	true/false	Indicates if SmartFunds ACH transfer is allowed for the Policy.
payrollWire	true/false	Indicates if SmartFunds wire transfer is allowed for the policy.
payrollDebit	true/false	Indicates if SmartFunds can be drawn by using the card in the Debit network.
<infos> section		Prompts on the policy. This is an array of zero to many. Each info returned has:
infoId	string (4)	identifies the info type
lengthCheck	true/false	indicates if there is a length check on the prompt.
matchValue	string (24)	If prompt is exact match, the exact match value is assigned.
maximum	int (20)	Max length.
minimum	int (20)	Min length.
reportValue	string (24)	If prompt is report only, the report value is assigned.
validationType	string (13)	The validation type for the prompt. ALPHABETIC, ALPHA_NUMERIC, NUMERIC, REPORT_ONLY, EXACT_MATCH, & ACCRUAL_CHECK are the valid options. Note: Use EXACT_MATCH to prompt and validate at the pump, use REPORT_ONLY for reporting prompts only. These are most commonly used at the card level.
value	int(24)	Value

<limits> section		Limits on the policy. This is an array of zero to many. Each info returned has:
hours	int (3)	Hours between use
limit	int (4)	Limit value
limitId	string (4)	Limit ID from EFS LLC
minHours	int (20)	Minimum hours between using the limit
autoRollMap	int (3)	If limit is auto roll the auto roll map
autoRollMax	int (4)	Max value for the auto roll limit.
locationGroups	int (10)	If using locationGroups, the locationGroups you want to assign. Zero to many can be sent over.
locations	int (7)	Zero to many. The locationId that the customer wants to block from their fuel network. The customer should send one row per location being blocked.
Time restrictions	array	This would hold any time restrictions set up on the policy.
beginTime	datetime	Begin time for the time restriction. The year, month, day portions will show 1970-01-01, only the time values are applicable.
day	int (1)	The day being restricted. 1 = Sunday, 2 = Monday, 3 = Tuesday, 4 = Wednesday, 5 = Thursday, 6 = Friday, 7 = Saturday
endTime	datetime	The end time for the time restriction. The year, month, day portions will show 1970-01-01, only the time values are applicable.

Output

A successful response or a decline error with text.

Error Messages

- A fault string or flying j exception error may be returned.

Set Policy Refreshing Limits

This method will set the refreshing limits on a policy. Please note when you update these limits it will impact all cards under the policy where the card's refreshing limit source is pointed to the policy.

setPolicyRefreshingLimits

Input

clientId	string (32)	The client ID from the login response
policyNumber	Int(3)	The policy #.
dayCntLimit	int	The daily # of transactions allowed.
dayAmtLimit	Int	The daily amount limit in dollars.
weekCntLimit	Int	The weekly # of transactions allowed.
weekAmtLimit	Int	The weekly amount allowed.
monCntLimit	Int	The monthly # of transactions allowed.
monAmtLimit	int	The monthly amount limit.

Output

requestStatus	String	This will indicate a success or an error.
---------------	--------	---

Error Messages

- A fault string or flying j exception error may be returned.

Set Site Policy

This method assigns site policy to a policy.

setSitePolicy

Input

clientId	string (32)	The client ID from the login response
policyNum	int(3)	Site policy number. This has a limit of 100 total policies. Ipolicy >= 501 and ipolicy <= 599
addRemoveall	string	ADD -add the site policy to the policy REMOVE – remove the site policy from the policy ALL – this will assign the site policies to all policies, so be careful.
Policies – an array of 1 to many policies.		This allows you to add 1 or more policies to a site policy.

Output

An array of 1 to many

policies	Int(3)	An array of the site policies added.
----------	--------	--------------------------------------

Error Messages

- A fault string or flying j exception error may be returned.

Set SmartPay Driver

Updates a SmartFunds driver.

setSmartPayDriver

Input

clientId	string (32)	The client ID returned in the login response.
SmartPay Driver array		
cardNumber	string (25)	The card #.
firstName	string (30)	The cardholder's first name.
lastName	string (30)	The cardholder's last name.
address	string (30)	The cardholder's address.
city	string (30)	The cardholder's city.
state	string (2)	The cardholder's state/provincial abbreviation.
postalCode	string (10)	The cardholder's zip or postal code.
country	string (2)	US or CN
dob	datetime	Date of birth, the time values are zeroed out.
last4ss	int (4)	The last 4 of the social security or tax identification.
email	string (50)	Email address.
phone	string (12)	Phone #, 999-999-9999 format.

Output

A successful response or a decline error with text.

Error Messages

- A fault string or flying j exception error may be returned.

Set SmartPay Transfer Account

Updates a SmartFunds bank account set-up for a card.

setSmartPayTransferAccount

Input

clientId	string (32)	The client ID returned in the login response.
SmartPay Transfer Account array		
transferAccountId	string (30)	The transfer account ID being updated.
cardNumber	string (25)	The card number.
bankName	string (50)	The bank name.
routingNumber	int (9)	The bank routing ID.
accountNumber	string (17)	The bank account #.
accountOwnerName	string (24)	The bank owner.
accountType	int (1)	28 PRENOTE PAYMENT CHECKING 38 PRENOTE PAYMENT SAVINGS 22 AUTOMATED PAYMENT CHECKING 32 AUTOMATED PAYMENT SAVINGS
accountNickname	string (50)	Account nickname.
effectiveDate	datetime	Effective date/time.
batchHeaderId	string (10)	The batch header ID.
createdBy	string (15)	Created by user.
verifyDate	datetime	The verify date/time.
verifyAmountOne	decimal (12,2)	The verification amount 1 for the prenote.
verifyAmountTwo	decimal (12,2)	The verification amount 2 for the prenote.
verifyTryCount	int (1)	The verification try count, 0-9.
expireDate	datetime	The expiration date/time.

Output

A successful response or a decline error with text.

Error Messages

- A fault string or flying j exception error may be returned.

Sign Up Scale

This is used by CAT Scale application to sign the card and driver up for scale services.

signUpScale

Input

cardNumber	string(19)	The card #.
driverID	char(24)	The driver id.

Output

result	String(30)	The name of the account.
carrierID	Int(7)	The carrier ID the card is associated with.

Error Messages

- A fault string or flying j exception error may be returned.

SmartPay Transfer History

Retrieves SmartFunds transfers for a card.

smartPayTransferHistory

Input

clientId	string (32)	Client Id returned from the login.
cardNumber	string (25)	The card number.
count	int (3)	The # of transfers requested.

Output

An array of SmartPay transfers for the card.

Error Messages

- A fault string or flying j exception error may be returned.

Stop Order

This is used to stop/cancel a card order.

stopOrder

Input

clientId	string (32)	The client ID from the login response
orderId	long	The order id being stopped

Output

Request	String	This indicates if it was a success or error.
---------	--------	--

Error Messages

- An unable to submit order error.

Submit Order

This is used to submit a card order that was created under create order – we recommend that you always use the create and submit that allows you to do this all at once.

submitOrder

Input

clientId	string (32)	The client ID from the login response
orderId	long	The order id being stopped

Output

Request	String	This indicates if it was a success or error.
---------	--------	--

Error Messages

- A fault error, a flying j excpetion error or an error message that the order was failed to be submitted.

Transaction Summary

Summarizes fuel transaction information for a customer for a time period, including the count and total amount.

transSummary

Input

clientId	string (32)	Client Id returned from the login.
begDate	datetime	Beginning date/time.
endDate	datetime	Ending date/time.

Output

tranCount	int (20)	The # of transactions during the period.
tranTotal	decimal (12,12)	The total amount of transactions during the period.

Error Messages

- A fault string or flying j exception error may be returned.

Transfer Card

Transfers card information from one card to another, including any one-time or SmartFunds balances.

transferCard

Input

clientId	string (32)	Client Id returned from the login.
fromCard	string (25)	The card number data is being transferred from.
toCard	string (25)	The card # data is being transferred to.

Output

A successful response indicating the card data was transferred or a decline with text.

Error Messages

- A fault string or flying j exception error may be returned.

Update Order

This method is used to update a card order properties for orders that have not been shipped. This updates the properties at the order level, use the update order cards for individual card properties.

updateOrder

Input

clientId	string (32)	The client ID from the login response
orderId	Long	The card order being modified.
Props	Array	The prop from the card order.

Output

request	String	The web service request status of SUCCESS or ERROR.
---------	--------	---

Error Messages

- A fault string or flying j exception error may be returned.

Update Order Cards

This web service method is used to update properties for the individual cards within a card order.

updateOrderCards

Input

clientId	string (32)	The client ID from the login response
orderId	Long	The card order being modified.
Idx from Cards	Array	The array of cards being created. Idx starts at 0 for the first card in the order and it goes up to the order quantity.
Props	Array	The props for the individual cards.

Output

request	String	The web service request status of SUCCESS or ERROR.
---------	--------	---

Error Messages

- A fault string or flying j exception error may be returned.

Validate Card

Validates card, PIN, and driver ID information, primarily used for SmartFunds or ATM cards.

validCard

Input

cardNumber	string (25)	The card #
pin	int (4)	The pin #.
driverId	string (24)	The driver ID assigned.

Output

Successful validation or error response with text.

Error Messages

- A fault string or flying j exception error may be returned.

Verify SmartPay Transfer

Verifies SmartFunds transfers when a prenote is done for a SmartFunds bank account.

verifySmartPayTransfer

Input

clientId	string (32)	The client ID.
Array of Smartpay amounts to verify		
transferAccountId	string (30)	The transfer account ID.
verifyAmt1	decimal (12,2)	The transfer amount 1.
verifyAmt2	decimal (12,2)	The transfer amount 2.

Output

Successful validation or error response with text.

Error Messages

- A fault string or flying j exception error may be returned.

Verify User

This method is used internally by EFS, so do not use.

Void Money Code

voids out money codes that were issued in error or are no longer needed.

voidMoneyCode

Input

clientId	string	Required. Token returned from login
moneyCode	string	Required. EFS money code #.

Output

A successful void response or an error.

Error Messages

- A fault string or flying j exception error may be returned.

Appendix A. Reference Tables

Code Tables

Auto Roll Map

Description	Auto Rolls Value
Daily	127
Sunday	1
Monday	2
Tues	4
Wed	8
Thurs	16
Fri	32
Sat	64
Sun/Mon	3
Sun/Mon/Tues	7
Sun/Mon/Tues/Wed	15
Sun/Mon/Tues/Wed/Thurs	31
Sun/Mon/Tues/Wed/Thurs/Fri	63
Sun/Tues/Wed/Thurs/Fri/Sat	125
Sun/Tues/Wed/Thurs/Fri	61
Sun/Tues/Wed/Thurs	29
Sun/Tues/Wed	13
Sun/Tues	5
Sun/Wed/Thurs/Fri/Sat	121
Sun/Wed/Thurs/Fri	57
Sun/Wed/Thurs	25
Sun/Wed	9
Sun/Thurs/Fri/Sat	113
Sun/Thurs/Fri	49
Sun/Thurs	17
Sun/Fri/Sat	97
Sun/Fri	33
Mon/Tues/Wed/Thurs/Fri/Sat	126
Mon/Tues/Wed/Thurs/Fri	62
Mon/Tues/Wed/Thurs	30
Mon/Tues/Wed	14
Mon/Tues	6
Tues/Wed/Thurs/Fri/Sat	124
Tues/Wed/Thurs/Fri	60

Category Codes

ADD	ADDITIVES
AGFL	AG FUEL
AGCD	AGRICULTURAL CAR DIESEL



FARM	AGRICULTURAL FUEL
TOLL	AMBASSADOR BRIDGE TOLL
ANFR	ANTI-FREEZE
AVGS	AVIATION GAS
BDSL	BIO DIESEL
BDSR	BIO DIESEL REEFER
BPRP	BOTTLED PROPANE
BRAK	BRAKES AND WHEELS
CDSL	CAR DIESEL
CADV	CASH ADVANCE
CLTH	CLOTHING
CNG	COMPRESSED NATURAL GAS
DELI	DELI FOODS
DSL1	DIESEL #1
DEF	DIESEL EXHAUST FLUID CONTAINER
DEFD	DIESEL EXHAUST FLUID DISPENSED
ELEC	ELECTRONICS
EUPR	ETHANOL UNLEADED PREMIUM
ETAX	EXEMPT TAX AMOUNT
EVCH	ELECTRIC CHARGING
FAX	FAX
WIFI	FLEET WIFI BILLING
FUEL	FUEL
FURN	FURNACE OIL
GASO	GASOHOL
GROC	GROCERIES
HARD	HARDWARE
HPRO	HEATING PROPANE
IDLE	IDLEAIR
IDS2	INDUSTRIAL DIESEL #2
IPRO	INDUSTRIAL PROPANE
KERO	KEROSENE
LABR	LABOR
LNG	LIQUID NATURAL GAS
LMPR	LUMPER FEE
MDSL	MARKED DIESEL
MRFR	MARKED RFR
MULD	MARKED ULTRA LOW DIESEL
MERC	MERCHANDISE
NGAS	NATURAL GAS
OIL	OIL
OILC	OIL CHANGE
SPLT	OTHER METHOD OF PAYMENT
PNT	PAINT
PARK	PARKING
PHON	PHONE TIME
PROP	PROPANE
RECP	RECAP
LCNG	RECOVERED LNG

RFR	REEFER
RFR1	REEFER #1
ULSR	REEFER ULTRA LOW SULFUR
RFND	REFUND
REST	RESTAURANT
STAX	SALES TAX
SCLE	SCALES
COUP	SHELL COUPON
DISC	SHELL COUPON
SHWR	SHOWER
ATMD	STAR NETWORK DENIAL
ATMB	STAR NETWORK INQUIRY
MGAS	TAX EXEMPT GAS
TCHN	TIRE CHAINS
TIRE	TIRES
SCAN	TONS IMAGING
TRAL	TRAILER
TRPP	TRIP PERMIT
PART	TRUCK PARTS
REPR	TRUCK REPAIR
WASH	TRUCK/CAR WASH
ULSD	ULTRA LOW SULFUR DIESEL
UNCL	UNLEADED CARD LOCK GAS
UNPL	UNLEADED PLUS
UNPR	UNLEADED PREMIUM
UNRG	UNLEADED REGULAR
UREA	DIESEL EXHAUST FLUID CONTAINER
WWFL	WINDSHIELD WASHER FLUID

Chain Id's

0	Independents/Other
1	Pilot FJ
2	Loves
3	TA/Petro
4	Sapp Brothers
5	Wilco
6	Speedway/SuperAmerica
7	Quick Trip
8	Kangaroo/Pantry
9	Petro-Canada
10	Imperial Oil/Esso
11	Kwik Trip
12	Quick Fuel
13	Ambest
14	Cat Scales
15	Exxon Mobile US OTR Network

16	Quarles
17	Maverik
18	Irving 24
19	Road Ranger
20	NFN Retail
21	NFN Cardlock
101	WEX NAF
201	Retail Ultramar
202	Retail Chevron
203	Retail Pioneer
204	Retail Couche-Tard
205	Retail FasGas
206	Retail Race Trac
211	Cardlock Chevron
212	Cardlock Columbia Fuels
213	Cardlock Bluewave
214	Cardlock Pipeline
215	Cardlock Ultramar

****Notes**

- Values can be added to this list in the future.
 - Based on the card type/BIN you use, not all chain ids may apply but this is a full list.
- (Check with your Account manager/customer service if you have questions)

Country Codes

67	C	Canada
77	M	Mexico
85	U	United States

Discount Types

67	C	Better of cost-plus or retail
68	D	Cents off retail (discount) retail minus
78	N	No deal
80	P	Better of fixed price and cents off retail
87	W	Better of retail or weekly fixed price
98	b	Better of cost plus and retail minus

99	c	Straight cost-plus
119	w	Straight weekly fixed price

Fuel Types

Fuel types are based on the merchant partner. These are standard for EFS LLC protocol. Other protocols will use different fuel types.

1	Diesel #1	
2	Diesel #2	
4	Unleaded Regular Gasoline	
8	Unleaded Midgrade Gasoline	
16	Unleaded Premium Gasoline	
32	Propane	
128	Marked/Dyed Diesel	
256	Bio Diesel	
512	Car Diesel	
1024	Agricultural Fuel	
2048	Gasohol	
4096	Natural Gas	
8192	Ultra Low Sulfur Diesel	ULSD
16384	Aviation Fuel	
65536	Unleaded Card Lock Gasoline	
2097152	Furnace Oil	
8388608	Compressed Natural Gas	CNG
16777216	Liquid Natural Gas	LNG

Info IDs

BDAY	Birthday
BLID	Billing ID
CNTN	Control Number
CRDR	Card Description
DLIC	Driver's License #
DLST	Driver's License State
DRID	Driver ID
EXPT	Expense Type

FSTI	First Initial
GLCD	GL Code
HBRD	Hubometer
HRRD	Reefer Hour Reading
LCST	License State
LICN	License #
LSTN	Last Name
NAME	Driver Name
ODRD	Odometer
OINV	Original Invoice
PONB	Purchase Order #
PPIN	Personal Identifier
RTMP	Reefer Temperature
SSUB	Sub Fleet Identifier
TLOC	Terminal Location
TRIP	Trip #
TRLR	Trailer #
UNIT	Unit #

Limit IDs

ADD	Additives
AMDS	Aviation Merchandise
ANFR	Anti-Freeze
AVGS	Aviation Gas
BDSL	BioDiesel
BRAK	Brakes and Wheels
CADV	Cash Advance
CLTH	Clothing
CNG	Compressed Natural Gas
COUP	Coupon
DEF	Diesel Exhaust Fluid Bulk
DEFC	Diesel Exhaust Fluid Container
DELI	Restaurant/Deli
DSL	Diesel
DSLM	Mexico Diesel

ELEC	Electronics
EVCH	Electric Charging
FAX	Faxdefc
FURN	Furnace Oil
GAS	Gasoline
GASM	Mexico Gas Magna
GASP	Premium Gas Mexico
GROC	C-Store/Groceries
HARD	Hardware/Accessories
IDLE	IdleAire
JET	Jet Fuel
KERO	Kerosene
LABR	Labor
LMPR	Lumper
LNG	Liquid Natural Gas
MDSL	Marked/Tax Exempt Diesel
MERC	Miscellaneous Merchandise
MGAS	Marked/Tax Exempt Gas
MRFR	Marked Reefer
NGAS	Natural Gas
OIL	Oil
OILC	Oil Change
PART	Parts
PHON	Phone Time
PNT	Paint
PROP	Propane
RECP	Recap
REPR	Repair Service
REST	Restaurant
RFND	Refund
RFR	Reefer
RFRM	Thermo
SCAN	Tons Imaging
SCLE	Weigh Scale
SHWR	Shower
SPLT	Split/Other Method of Payment

STAX	Sales Tax
TIRE	Tires/Tire Repairs
TOLL	Ambassador Bridge Toll
TRAL	Trailer
TRPP	Trip Permit
ULSD	Ultra Low Sulfur Diesel
WASH	Car Wash
WIFI	Fleet WiFi Billing
WWFL	Windshield Washer Fluid

Location Amenities

1	Paved
2	Overnight
3	Lighted
4	All Hours
5	Showers
6	Lounge
7	Restaurant
8	Restaurant Nearby
9	Deli
10	Convenience Store/C-Store
11	Motel
12	Motel Nearby
13	Laundry
14	ATM
15	Scales
16	Lubes & Oil
17	Lubes Nearby
18	Repairs
19	Repairs Nearby
20	Wash
21	MDSL
22	BDSL
23	LSD
24	ULSD

25	Gas
26	MGas
27	Air Hose
28	Towing
29	Stand Alone (Cardlock)
30	Phones
31	Fast Food
32	Propane
33	Restroom
34	Parts and Tires
35	Fax
36	Cash
37	Diesel Exhaust Fluid (DEF)
38	Diesel Exhaust Fluid Containers (DEFC)

Tax IDs

CAP	Competitive Advantage Program (Saskatchewan)
FED	Federal Fuel Tax
FET	Federal Excise Tax
FNT	First Nations Tax
GST	Goods & Services Tax
GWT	Ground Water Tax
HST	Harmonized Sales Tax
MEX10	IVA-Fuel tax 10
MEX15	IVA-Fuel tax 15
MEXC	IVA-Customer Fee Tax
MEXS	IVA-Supplier Fee Tax
PFT	Provincial Fuel Tax
PST	Provincial Sales Tax
QST	Quebec Sales Tax
SFTAX	State Fuel Tax
VTT	Victoria and Vancouver Transit Tax, sometimes known as "UTT"

Transaction Types

1	Standard Fuel Card Transaction
2	Check Advance Transaction
3	Terminal Transaction
4	Direct Billed Fuel Card Transaction
5	Express Fuel Card Transaction
6	Pilot Flying J Fleet Sales Web Transaction
7	Star ATM transactions
8	Phone Card Transaction
9	WiFi Transaction
10	e-fund ATM transactions
11	ATM Denial/Rejection
12	ACH Transfer
13	ACH Transfer Credit
14	Star Debit Card Transactions
15	E-fund Debit Transactions
16	Cash Advance Load & Removes
63	Override Transaction

***** Any of these listed with a negative sign in front (-1, -2, -14 etc.) are transactions that have been credited and/or voided

Transaction Metas

Trans Meta Type ID	Trans Meta Description
BatchType	Batch Process Name
BatchFileName	Batch Transaction Input File Name
AuxPosType	Auxilliary POS Device Type
CSDE	Card Side
ZconGpsid	ZCON Zonar Unit GPS id
LocAddress	Location Address
LocCity	Location City
LocState	Location State
LocTerminalId	Location Terminal ID
FLTC	Vehicle Fault Codes
FLVL	Current Fuel Level
LANE	ZCON Lane Number
LAT	Vehicle GPS Latitude

Trans Meta Type ID	Trans Meta Description
LONG	Vehicle GPS Longitude
ZIDL	ZCON Idle Time
ENOD	Engine Odometer
CGFeeTierRebateType	Carrier Group Fee Tier Rebate Type
CPOL	Card Policy
LocName	Location Name
LocZip	Location ZipCode
LocPhone	Location Phone Number
TCHEK_SITE_NUM	T-Chek site number
IMPERIAL_SITE_NUM	Imperial Oil site number
IOL_BATCH_NUM	Imperial Oil batch number
IOL_BATCH_SEQ_NUM	Imperial Oil batch sequence number
IOL_SAF	Imperial Oil store and forward
MARKED_FUEL_CERT	Marked fuel certificate
IOL_MISSING_CERT	Imperial Oil missing marked fuel cert
IMPERIAL SITE_NUM	Imperial Site ID
RF_TAG_TYPE	RF tag type
RF_TAG_ID	RF tag ID
CDAS	Fedex Ground CDAS Number
IOL_FLEET_NUM	IOL 3rd party fleet number
IOL_3P_AUTH_NUM	IOL 3rd party auth number
MASTER_CONTRACT_ID	Master contract ID
FRAUD_SCR	Fraud Score
LOC_CITY	Location City
LOC_NAME	Location Name
LOC_STATE	Location State
MC_ACCEPT	Mcfleet Acceptor ID
MC_MCC	Mcfleet MCC
MC_MSG_NUM	Mcfleet Message Number
MC_TRNTYPE	Mcfleet Transaction Type
AUTH_LOGFILE	Front end Auth logfile
SB_DATE	Silver Bullet Date
STANDIN_FILE	Standin File Name
SUPP_FEE_CARR	Carrier fee paid by Supplier
AMT_CARR_FEE_PD	Carrier fee paid by Supplier
CGTierRebateAmt	Carrier Group Parent Tier Rebate Amount
S_FEE_PARENT_ID	Parent Contract for revenue sharing
ExtendedTermsFee	Extended Terms Fee
InNetworkFee	In Network Fee
MiscCarrAdderFee	Misc. Carrier Adder Fee
OutofNetworkFee	Out Of Network Fee
S_FEE_EFS_SET_PRIMARY	EFS Fixed Split Revenue

Trans Meta Type ID	Trans Meta Description
S_FEE_PARENT_SET_PRIMARY	Parent Fixed Split Revenue
S_FEE_EFS_PCT_PRIMARY	EFS Percetage Split Revenue
S_FEE_PARENT_PCT_PRIMARY	Parent Percentage Split Revenue
S_PRICING_TIER_ID	Tier ID used for pricing deal

WSLineTaxes

Note: the amounts for line item taxes are in the currency of the merchant location.

taxDescription	varchar(2610)	The Tax Description for the tax. This is sometimes the same as the Tax Code.
grossNetFlag	string (1)	N indicates tax net of discount, G indicates gross tax pre-discount.
amount	decimal (9,2)	The tax amount, in the merchant's currency.
taxClass	string(1)	The tax class ID. Typically set to xsi:nil="1" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
deferralDate	date/time	The tax deferral date if applicable, it is typically null such as <deferralDate xsi:nil="1" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
taxCode	string (3)	The Tax Code ID. (see Tax Code IDs).
exemptFlag	string (1)	Y indicates the tax is exempt for this customer, N indicates the tax is not exempt for this customer.
pstExemptAdjust	decimal (9,2)	The PST Exempt adjustment amount for PST exempt transactions.
gstExemptAdjust	decimal (9,2)	The GST Exempt adjustment amount for GST exempt transactions.

WSMoneyCode

code	string	The value that will be written on the money code check
id	int	Unique EFS identifier for each money code.

WSMoneyCodeHistRec

activated	datetime	
alphaCode	String (6)	
amount	decimal(9,2)	
amountUsed	decimal(9,2)	
code	serial	
codeType	string	char(10), for example E_MANAGER for all web service or web generated codes.
contractId	int (20)	
Created	dateTime	
deductFees	boolean	shows whether fees were deducted from the amount or not. False = not deducted True = fees are deducted
feeAmount	decimal(9,2)	
feeType	boolean	shows whether fees were deducted from the amount or not. False = not deducted True = fees are deducted
firstUse	dateTime	
Id	Int(20)	Money code ID
issuedTo	string	
notes	string	
numUses	string	
payee	string	
Status		
voidDate	dateTime	
voided	Boolean	
who	String	

WSMoneyCodeHistRecV2

activated	datetime	
alphaCode	String(6)	
amount	decimal(9,2)	
amountUsed	decimal(9,2)	
code	serial	
codeType	string	char(10), for example E_MANAGER for all web service or web generated codes.
contractId	int (20)	
Created	dateTime	
deductFees	boolean	shows whether fees were deducted from the amount or not. False = not deducted True = fees are deducted
feeAmount	decimal(9,2)	
feeType	boolean	shows whether fees were deducted from the amount or not. False = not deducted True = fees are deducted
firstUse	dateTime	
Id	Int(20)	Money code ID
issuedTo	string	
notes	string	
numUses	string	
payee	string	
Status		
voidDate	dateTime	
voided	Boolean	
who	String	
infoType	string (4)	The info ID for the prompt item. See Info IDs for the valid infos.
infoValue	string (24)	This is the info/prompt value. For example, this is the Driver ID #, Unit #, etc., that will be reported.

WSMoneyCodeHistUse

amount	Decimal(9,2)	Dollar amount of the transaction
checkNumber	int	Check number used for code
time	datetime	The date/time of transaction

WSTransaction

ARBatchNumber	int (20)	N/A to the customer.
CPNRDeliveryTP	string	N/A, will be <CPNRDeliveryTP/>.
MCMultiCurrency	true/false	N/A
OPDataSource	string (20)	N/A, typically <OPDataSource/>.
POSDate	dateTime	Date of transaction as reported by POS
accountType	N/A	Will return null such as <accountType/>
arNumber	char(20)	Typically this is a number but may start with a "C"
authCode	char(10)	POS authorization code
billingCountry	int (3)	Carrier's location country (see Country Codes)
billingCurrency	string	The currency for the contract. This is often null, such as <billingCurrency xsi:nil="1" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/> but may be set to US, USD, CN, CAD.
cardNumber	string (20)	Credit card number used
carrierFee	decimal (max 99.99)	Carrier fee in billing currency
carrierId	int (7)	EFS ID assigned to the customer
companyXRef	char (24)	The company xref on the card.
contractId	int (20)	EFS contract ID. Specific to the policies.
conversionRate	decimal (8,4)	Transaction currency conversion rate. If there is no conversion, this is set to 1.0.
country	int	Country where location happened (see Country Codes)
discAmount	decimal (8,2)	Transaction discount total amount
discType	int	Type of the discount (see Discount Types)
fundedTotal	decimal (8,2)	Amount that was billed to the carrier in the locations currency. This does not include carrier fee.
handEntered	true/false	Indicates if the card was hand entered or swiped.
inAddress	N/A	Will be <inAddress/>.
infos		Array of WSTransactionInfo
invoice	char (12)	Invoice reference on the customer receipt (invoice number may be appended with DB for Direct Bill or split funding transaction. Example: <invoice>0362580656DB</invoice>)
issuerDeal	N/A	Will be 0.0
issuerFee	N/A	Will be 0.0
issuerId	int (7)	EFS internal ID assigned to issuer of card
language	int (1)	Language of the card. 0 = English, 1 = French.
lineItems		Array of WSTransactionLineItem

locationChainId	Int(10)	The location Chain ID
locationName	String	The location name.
locationAddress	String	The location address.
locationCountry	int	Country where transaction took place (see Country Codes)
locationCurrency	string	USD (US dollars) or CAD (Canadian dollars)
locationId	int	EFS LLC Location ID.
locationState	String(2)	The location state or provincial abbreviation.
locationZip	String	The location zip or postal code, 5 digits in the USA but in Canada a string.
locationLatitude	String	The location latitude.
locationLongitude	String	The location longitude.
locationCountry	int	Country where transaction took place (see Country Codes)
locationCurrency	string	USD (US dollars) or CAD (Canadian dollars)
locationId	int	EFS LLC Location ID.
messageDLVD	N/A	Will be <messageDLVD/>.
netTotal	decimal (8,2)	Obsolete, same as pref total.
nonAreaFee	(8,2)	Out of area fee for cards with specific defined area
override	true/false	Indicates if the transaction occurred while the card was in override mode.
postDiscTax	decimal (8,2)	Tax applied pre discount
preDiscTax	decimal (8,2)	Tax applied post discount
prefTotal	decimal (8,2)	Funded total in currency of contract
reportedCarrier	dateTime	Date and time transaction was reported back to the customer if they are AS400 customers.
settleAmount	decimal (8,2)	Amount settled with the POS
settleId	int (7)	EFS settlement ID for suppliers. May be set to zero.
splitBilling	true/false	If true pref total is in locations currency
statementId	int (20)	Statement ID if available.
supplierId	int (7)	EFS supplier ID assigned to the merchant.
suprFee	decimal (8,2)	N/A to the customer this is the supplier fee. May be zeroes.
taxExemptAmount	decimal (8,2)	Amount of pref total that is tax exempt, typically this is only applicable for Canadian customers with special tax exemptions.
terminalId	string	N/A, will be <terminalId/>
terminalType	string	N/A, will be <terminalType/>
transReported	dateTime	Date the transaction was reported.
transactionDate	dateTime	Date and time of transaction
transactionId	int (40)	EFS transaction ID. This is unique for each transaction.

transactionType	int	Type of transaction (see Transaction Types)
-----------------	-----	--

WSTransactionExt

ARBatchNumber	int (20)	N/A to the customer, it's the AR batch number the transaction is part of.
CPNRDeliveryTP	string	N/A, will be <CPNRDeliveryTP/>.
MCMultiCurrency	true/false	This indicates if the transaction is MC Multi Currency, true or false. This is typically false.
OPDataSource	string (20)	N/A, typically <OPDataSource/>.
POSDate	dateTime	The date/time of the transaction as reported by the merchant Point of Sale. This is not always populated as it depends on the merchant partner and whether or not they send in date/time.
accountType	N/A	Not applicable and will be set to null similar to: <accountType/>
arNumber	char(20)	The EFS LLC AR # assigned to the Contract ID the transaction processed under. Each policy is assigned to a Primary Contract ID that is used for billing purposes, and that will be reported here. If SmartFunds are in use (for payroll, settlement, or advances) then there can be a SmartFunds contract associated with the Policy and that AR # will be populated for SmartFunds transactions.
authCode	char(10)	The Point of Sale Authorization Code provided by EFS LLC to the merchant partner for the sale.
billingCountry	int (3)	The customer's location country (see Country Codes)
billingCurrency	string	The currency for the contract, this indicates the currency the transaction will be billed in. This is often null such as <billingCurrency – string – xsi:nil="1" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/> but may be set to US, USD, CN, CAD.
cardNumber	string (20)	The credit card number used on the transaction.
carrierFee	decimal (max 99.99)	The customer fee charged on the transaction. Please note if there are data capture fees for the transaction they will not be included in these fees but will be reported on the customer statement from EFS LLC.
carrierId	int (7)	The Customer # assigned to the customer by EFS LLC. A single web service user can only access 1 customer at a time, although in certain cases customers may have more than 1 carrier based on set-up need. If that is the case, then set-up a user for each carrier to pull transactions.
companyXRef	char (24)	The company cross reference value assigned to the card. Each card can have 1 company cross reference assigned at a time, but it is an optional field.
contractId	int (20)	The EFS LLC contract ID assigned to the transaction for billing purposes (this is related to the AR Number).

conversionRate	decimal (8,4)	Transaction currency conversion rate applicable to the transaction. If there is no conversion rate applicable, for example if both the merchant and billing currency are USD, then this is set to 1.0.
country	int (3)	Country where location happened (see Country Codes)
discAmount	decimal (8,2)	The discount amount for the transaction. As a standard rule, this is the difference between the Retail Total Amount (retail PPU * quantity for line items) and the Discounted Total Amount (discount PPU * quantity for line items)
discType	int	The type of the discount applied to the transaction (see Discount Types)
fundedTotal	decimal (8,2)	The total amount of the transaction, in merchant currency. This is less the discount but does not include any customer fees.
handEntered	true/false	Indicates if the card was hand entered or swiped to be processed. Typically cards are swiped but there are cases where a card number may be manually entered.
inAddress	N/A	The field will be <inAddress/>
infos		The array of Information (prompted for or report only) for the transaction. There can be zero to many records (see WSTransactionInfo).
invoice	char (12)	The merchant invoice reference # for the transaction, many times this matches the merchant receipt number.
issuerDeal	N/A	Set to \$0.0.
issuerFee	N/A	Set to \$0.0.
issuerId	int (7)	The EFS LLC internal ID assigned to the card issuer, typically N/A to customers or software vendors.
language	int (1)	The language of the card. 0 = English, 1 = French.
lineItems		Array of WSTransactionLineItem . There will be 1 to many line items per transaction, which represents a product purchased. STAX or sales tax can also be a line item, but other taxes are reported in the taxes..
locationCountry	int (3)	The country where transaction took place (see Country Codes)
locationCurrency	string (3)	The location currency, USD (US dollars), CAD (Canadian dollars), or MXN for Mexican pesos.
locationId	int (7)	EFS LLC Location ID assigned to the merchant. Please note all ATM transactions will have the same Location ID and all MasterCard transactions will have the same Location ID.
messageDLVD	string (10)	This is N/A will be <messageDLVD/>.
netTotal	decimal (8,2)	Obsolete, same as pref total. Please use pref total.
nonAreaFee	decimal (8,2)	The out of area fee for cards with specific defined area.
override	true/false	This indicates if the transaction occurred while the card was in override mode or not.
postDiscTax	decimal (8,2)	The tax applied post-discount or "net" tax.

preDiscTax	decimal (8,2)	The tax applied pre-discount or “gross” tax.
prefTotal	decimal (8,2)	The funded total of the transaction in the customer’s billing currency, less the discount but not inclusive of the customer fee.
reportedCarrier	dateTime	The date and time the transaction was reported back to the customer if the customer uses an AS/400 system. This is typically not used for web service customers.
settleAmount	decimal (8,2)	The amount settled to the merchant for the transaction. This is N/A to the customer.
settleId	int (7)	EFS LLC settlement ID assigned the merchant supplier. This may be set to zeroes if settlement is not applicable. This is N/A to the customer.
splitBilling	true/false	If this is set to True, the pref total is in the merchant’s currency.
statementId	int (20)	The EFS LLC statement ID for the transaction, if available. This may be zeroes or N/A if the transaction has not yet been included on a statement.
supplierId	int (7)	EFS LLC supplier ID assigned to the merchant for settlement. This is not applicable to the customer.
suprFee	decimal (8,2)	N/A to the customer, this is the supplier fee. This may be set to zeroes.
taxExemptAmount	decimal (8,2)	The amount of pref total that is tax exempt, typically this is only applicable for Canadian customers with special tax exemptions, for example government entities that may be GST/HST/FNT exempt in Canada.
terminalId	string	N/A, will be <terminalId/>
terminalType	string	N/A, will be <terminalType/>
transReported	dateTime	The date the transaction was reported.
transactionDate	dateTime	The date and time of transaction.
transactionId	int (40)	EFS LLC transaction ID. This is unique for each transaction and can be used as the unique identifier for the transaction.
transactionType	int	Type of transaction (see Transaction Types)
lineTaxes		An array of Line Taxes (see WSLineTaxes)
metadata		An array of Meta Data (see WSMetaData)

WSTransactionExtv2

ARBatchNumber	int (20)	N/A to the customer, it's the AR batch number the transaction is part of.
CPNRDeliveryTP	string	N/A, will be <CPNRDeliveryTP/>.
MCMultiCurrency	true/false	This indicates if the transaction is MC Multi Currency, true or false. This is typically false.
OPDataSource	string (20)	N/A, typically <OPDataSource/>.
POSDate	dateTime	The date/time of the transaction as reported by the merchant Point of Sale. This is not always populated as it depends on the merchant partner and whether or not they send in date/time.
accountType	N/A	Not applicable and will be set to null similar to: <accountType/>
arNumber	char(20)	The EFS LLC AR # assigned to the Contract ID the transaction processed under. Each policy is assigned to a Primary Contract ID that is used for billing purposes, and that will be reported here. If SmartFunds are in use (for payroll, settlement, or advances) then there can be a SmartFunds contract associated with the Policy and that AR # will be populated for SmartFunds transactions.
authCode	char(10)	The Point of Sale Authorization Code provided by EFS LLC to the merchant partner for the sale.
billingCountry	int (3)	The customer's location country (see Country Codes)
billingCurrency	string	The currency for the contract, this indicates the currency the transaction will be billed in. This is often null such as <billingCurrency – string – xsi:nil="1" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/> but may be set to US, USD, CN, CAD.
cardNumber	string (20)	The credit card number used on the transaction.
carrierFee	decimal (max 99.99)	The customer fee charged on the transaction. Please note if there are data capture fees for the transaction they will be included in these fees as well.
carrierId	int (7)	The Customer # assigned to the customer by EFS LLC. A single web service user can only access 1 customer at a time, although in certain cases customers may have more than 1 carrier based on set-up need. If that is the case, then set-up a user for each carrier to pull transactions.
companyXRef	char (24)	The company cross reference value assigned to the card. Each card can have 1 company cross reference assigned at a time, but it is an optional field.
contractId	int (20)	The EFS LLC contract ID assigned to the transaction for billing purposes (this is related to the AR Number).
conversionRate	decimal (8,4)	Transaction currency conversion rate applicable to the transaction. If there is no conversion rate applicable, for example if both the merchant and billing currency are USD, then this is set to 1.0.

country	int (3)	Country where location happened (see Country Codes)
discAmount	decimal (8,2)	The discount amount for the transaction. As a standard rule, this is the difference between the Retail Total Amount (retail PPU * quantity for line items) and the Discounted Total Amount (discount PPU * quantity for line items)
discType	int	The type of the discount applied to the transaction (see Discount Types)
fundedTotal	decimal (8,2)	The total amount of the transaction, in merchant currency. This is less the discount but does not include any customer fees.
handEntered	true/false	Indicates if the card was hand entered or swiped to be processed. Typically cards are swiped but there are cases where a card number may be manually entered.
inAddress	N/A	The field will be <inAddress/>
infos		The array of Information (prompted for or report only) for the transaction. There can be zero to many records (see WSTransactionInfo).
invoice	char (12)	The merchant invoice reference # for the transaction, many times this matches the merchant receipt number.
issuerDeal	N/A	Set to \$0.0.
issuerFee	N/A	Set to \$0.0.
issuerId	int (7)	The EFS LLC internal ID assigned to the card issuer, typically N/A to customers or software vendors.
language	int (1)	The language of the card. 0 = English, 1 = French.
lineItems		Array of WSTransactionLineItem . There will be 1 to many line items per transaction, which represents a product purchased. STAX or sales tax can also be a line item, but other taxes are reported in the taxes..
locationAddress	String	The location address
locationCountry	int (3)	The country where transaction took place (see Country Codes)
locationCurrency	string (3)	The location currency, USD (US dollars), CAD (Canadian dollars), or MXN for Mexican pesos.
locationId	int (7)	EFS LLC Location ID assigned to the merchant. Please note all ATM transactions will have the same Location ID and all MasterCard transactions will have the same Location ID.
locationLatitude	String	The latitude of the location. Please note this will be zero if not available (for example in the ATM or MasterCard network). *Note: If you find issues with latitude/longitude please report to your EFS account manager.
locationLongitude	String	The latitude of the location. Please note this will be zero if not available (for example in the ATM or MasterCard network). *Note: If you find issues with latitude/longitude please report to your EFS account manager.
locationPostalCode	String(10)	The postal code/zip code for the location, if available.

messageDLVD	string (10)	This is N/A will be <messageDLVD/>.
netTotal	decimal (8,2)	Obsolete, same as pref total. Please use pref total.
nonAreaFee	decimal (8,2)	The out of area fee for cards with specific defined area.
override	true/false	This indicates if the transaction occurred while the card was in override mode or not.
postDiscTax	decimal (8,2)	The tax applied post-discount or "net" tax.
preDiscTax	decimal (8,2)	The tax applied pre-discount or "gross" tax.
prefTotal	decimal (8,2)	The funded total of the transaction in the customer's billing currency, less the discount but not inclusive of the customer fee.
reportedCarrier	dateTime	The date and time the transaction was reported back to the customer if the customer uses an AS/400 system. This is typically not used for web service customers.
settleAmount	decimal (8,2)	The amount settled to the merchant for the transaction. This is N/A to the customer.
settleId	int (7)	EFS LLC settlement ID assigned the merchant supplier. This may be set to zeroes if settlement is not applicable. This is N/A to the customer.
splitBilling	true/false	If this is set to True, the pref total is in the merchant's currency.
statementId	int (20)	The EFS LLC statement ID for the transaction, if available. This may be zeroes or N/A if the transaction has not yet been included on a statement.
supplierId	int (7)	EFS LLC supplier ID assigned to the merchant for settlement. This is not applicable to the customer.
suprFee	decimal (8,2)	N/A to the customer, this is the supplier fee. This may be set to zeroes.
taxExemptAmount	decimal (8,2)	The amount of pref total that is tax exempt, typically this is only applicable for Canadian customers with special tax exemptions, for example government entities that may be GST/HST/FNT exempt in Canada.
terminalId	string	N/A, will be <terminalId/>
terminalType	string	N/A, will be <terminalType/>
transReported	dateTime	The date the transaction was reported.
transactionDate	dateTime	The date and time of transaction.
transactionId	int (40)	EFS LLC transaction ID. This is unique for each transaction and can be used as the unique identifier for the transaction.
transactionType	int	Type of transaction (see Transaction Types)
lineTaxes		An array of Line Taxes (see WSLineTaxes)
metadata		An array of Meta Data (see WSMetaData)

WSTransactionInfo

type	string	Type of info (see Info IDs)
value	string	Value at time of transaction

WSMetadata

typeId	String(30	The trans meta type id. See list here .
metaData	string	The trans meta data
description	String(255)	The description of what the trans meta is.

WSTransactionLocation

locationCity	String (2590)	Location city
locationState	String (2)	Location state

WSTransactionLineItem

Note: the amounts and quantities for line items are in the currency and units of measure of the location where the purchase occurred.

amount	decimal (8,2)	The transaction amount.
billingFlag	int (1)	N/A, This field will be set to 0.
category	string	Product category (see Category Codes)
cmptAmount	decimal (8,2)	N/A, set to \$0.0.
cmptPPU	decimal (8,3)	N/A, set to \$0.0.
discAmount	decimal (8,2)	The discount amount for this line item.
fuelType	int	The type of fuel or will be 0 for non-fuel products (see Fuel Types)
groupCategory	string	Product group category (see Category Codes)
groupNumber	int (7)	N/A to the customer, it's a number assigned by EFS LLC to the product group category.
issuerDeal	decimal (8,2)	N/A will be set to \$0.0.
issuerDealPPU	decimal (8,3)	N/A will be set to \$0.0
lineNumber	int (20)	The transaction line #, for each transaction there can be 1 to many product lines and this corresponds to the line # for the product.
number	int (10)	N/A to the customer, it is an EFS LLC product category group #.
ppu	decimal (8,3)	The Discounted PPU for the product. This will be zeroes if PPU is not applicable (cash advances and such).
prodCD	string	N/A, will often be <prodCD xsi:nil="1" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>.
quantity	decimal (8,3)	The quantity purchased, based on the merchant's unit of measure. This is set to 1 where it is not applicable (cash advances and such).
retailPPU	decimal (8,3)	The Retail PPU for the product. This will be zeroes if PPU is not applicable (cash advances and such).
serviceType	int (1)	N/A anymore, will be 1 for self service or could be zeroes.
useType	int (1)	The fuel use type. 0 = non-fuel 1 = fuel 2 = reefer products

Overrides

This section is to help describe how to do various card overrides.

Override All Locations

- Do a getCard
- Then call setCard and echo back your data from the getCard response
- Update the following fields:
 - overrideAllLocations to True
 - override will be set from 1 to 9, 1 meaning 1 time override 9 meaning 9 times

Override Single Location ID

- Do a getCard
- Then call setCard and echo back your data from the getCard response
- Update the following fields:
 - locationOverride will be set to the 6 digit EFS LLC Location Id that you want to open the card up to. Make sure that this is a valid location id.
 - overrideAllLocations set to False
 - override will be set from 1 to 9, 1 meaning 1 time override 9 meaning 9 times

Override Product Limits

- Do a getCard
- Then call setCard and echo back your data from the getCard response except remove the limits
- Update the following fields:
 - overrideAllLocations set to True
 - override will be set from 1 to 9, 1 meaning 1 time override 9 meaning 9 times
 - Add back the limits array with the products and limits that you want for the override. For example if you want to allow ULSD for 1000 gallons, you would put
 - <limits>
 <hours>1</hours>
 <limit>1000</limit>
 <limitId>ULSD</limitId>
 <minHours>0</minHours>

Override Refreshing Limits

This override requires several web service calls.

- Do a getCard
- Then call setCard and echo back your data from the getCard response.
- Update the following fields:
 - overrideAllLocations set to True
 - override will be set from 1 to 9, 1 meaning 1 time override 9 meaning 9 times
- Then call the setCardRefreshingLimits method using a cardNumber that is the card # plus the word OVER, for example 708305123456789111 the OVER card will be 708305123456789111OVER.
- Set the limits to the override values.

Location Types

Location Type
AFL
BULK
CAFE
CAFL
CARE
COMP
CS
DAFL
ESSO
FJ
FJSH
FJW
FXG
GG
IDLE
IOL
ITMS
IVCL
IVRL
IVRT
LVS
MCLO
MISC
MOBL
MORT
PACP
PDCA
PLT
PTFR
PTOW
SHAF
SHCL
SHRL
SHRT
SHUS
STOR
SUN
TAFR
TAOW

Location Type
TERM
TONS
WIFI
WILC
YF

Shipping Methods

Shipping Method ID	Description
1	Standard Shipping
2	Ground Shipping
3	Overnight Shipping
4	Rush Overnight Shipping
5	Regular Mail
6	Registered Mail
7	Carrier
8	Expedited Shipping for Naivgator
42	Overnight FedEx for GE
44	PUROLATOR OVERNIGHT
45	Expedited Shipping
50	UPS Standard
51	UPS Overnight
60	USPS Standard
61	USPS Overnight
70	USPS Regular Mail
71	UPS Rush Next Day Air Early AM
72	UPS Next Day Air
73	UPS Next Day Air Saver
74	UPS 2nd Day Air AM
75	UPS 2nd Day Air
76	UPS 3 Day Select
77	UPS Ground
78	UPS Worldwide Saver
79	UPS Worldwide Express
80	FedEx Rush Priority Overnight
81	FedEx Standard Overnight
82	FedEx 2 Day AM
83	FedEx 2 Day
84	FedEx Express Saver
85	FedEx Ground
86	FedEx International Priority

Card Order Property Keys

Properties Key
billingMethodId
createChildCarriers
doNotShipCards
defaultPolicy
cardPressId
promptCode
localeCode
welcomeKits
mcTranTypes
defCardStatus
infosrc
lmtsrc
timesrc
locsrc
velsrc
ccbNumberingId
ccbExpireTypeId
ccbExpireMonths
envelopes
checks
sleeves
shipToPhone
shipToEmail
mrsrc
payrMrsrc
mipPaymentSrc
payrAmt
payrChk
payrWire
payrDebit
mcProduct
dayCntLimit
weekCntLimit
monCntLimit
dayAmtLimit
weekAmtLimit
monAmtLimit
defCardStatus
ccbExpireTypeId

Properties Key
created
templateName
langCode
handEnter
payrUse
contractId

Update History

Author	Date	Update
Jayme Larsen & Jessie Halter	12/12/2018	Added new methods
Jayme Montgomery, Jessie Halter, & Judy Haynes	4/17/2018	Added new methods. Verified all methods and parameters. Applied new format to the document.
Jessie Halter	4/17/2015	Added Get Cards With No Driver ID method.
Marisa Beasley & Jessie Halter	10/1/2014	Created document.