

Lab: Objects & Composition

Problems for in-class lab for the ["JavaScript Advanced" course @ SoftUni](https://judge.softuni.bg/Contests/2758/Objects-and-Composition-Lab). Submit your solutions in the SoftUni judge system at <https://judge.softuni.bg/Contests/2758/Objects-and-Composition-Lab>.

1. City Record

You will receive a city's **name** (string), **population** (number), and **treasury** (number) as arguments, which you will need to set as **properties** of an **object** and **return** it.

Examples

Input	Output
'Tortuga', 7000, 15000	{ name: 'Tortuga', population: 7000, treasury: 15000 }
'Santo Domingo', 12000, 23500	{ name: 'Santo Domingo', population: 12000, treasury: 23500 }

2. Town Population

You have been tasked to create a registry for different **towns** and their **population**.

Input

The **input** comes as array of strings. Each element will contain data for a town and its population in the following format: "{townName} <-> {townPopulation}"

If you receive the same town twice, **you should add** the **given population** to the **current one**.

Output

As **output**, you must print all the towns and their population.

Examples

Input	Output
['Sofia <-> 1200000', 'Montana <-> 20000', 'New York <-> 10000000', 'Washington <-> 2345000', 'Las Vegas <-> 1000000']	Sofia : 1200000 Montana : 20000 New York : 10000000 Washington : 2345000 Las Vegas : 1000000
['Istanbul <-> 100000', 'Honk Kong <-> 2100004', 'Jerusalem <-> 2352344', 'Mexico City <-> 23401925', 'Istanbul <-> 1000']	Istanbul : 101000 Honk Kong : 2100004 Jerusalem : 2352344 Mexico City : 23401925

3. City Taxes

This task is an extension of Problem 1, you may use your solution from that task as a base.

You will receive a city's **name** (string), **population** (number), and **treasury** (number) as arguments, which you will need to set as **properties** of an **object** and **return** it. In addition to the input parameters, the object must have a property **taxRate** with an initial value of **10**, and three **methods** for managing the city:

- **collectTaxes()** - Increase **treasury** by **population * taxRate**
- **applyGrowth(percentage)** - Increase population by **given percentage**
- **applyRecession(percentage)** - Decrease treasury by **given percentage**

Round down the values after each calculation.

Input

Your solution will receive three **valid** parameters. The methods that expect parameters will be tested with valid input.

Output

Return an **object** as described above. The methods of the object modify the object and don't return anything.

Input	Output
<pre>const city = cityTaxes('Tortuga', 7000, 15000); console.log(city);</pre>	<pre>{ name: 'Tortuga', population: 7000, treasury: 15000, taxRate: 10, collectTaxes: [Function: collectTaxes], applyGrowth: [Function: applyGrowth], applyRecession: [Function: applyRecession] }</pre>
Testing with code	
Input	Output
<pre>const city = cityTaxes('Tortuga', 7000, 15000); city.collectTaxes(); console.log(city.treasury); city.applyGrowth(5); console.log(city.population);</pre>	<pre>85000 7350</pre>

4. Object Factory

Create a function that can compose objects by copying functions from a given library of functions. You will receive **two parameters** – a **library** of functions as an associative array (object) and an **array of orders**, represented as objects. You must **return** a new array – the fulfilled orders.

The **first parameter** will be an object where each property is a **function**. You will use this **library of functions** to compose new objects.

The **second parameter** is an **array of orders**. Each order is an **object** with the following shape:

```
{
  template: [Object],
  parts: string[]
}
```

A **template** is an object that must be **copied**. The **parts array** contains the names of **required functions** as **strings**.

You must **create and return a new array**, by fulfilling all orders from the **orders array**. To fulfill an order, create a copy of the object's template and then add to it all functions, listed in the **parts array** of the order, by taking them from the **function library** (the first parameter to your solution).

Input

You will receive two parameters:

- **library** – an object
- **orders** – an array of objects

Output

Your solution must **return an array** of objects.

Example

Input
<pre>const library = { print: function () { console.log(`\${this.name} is printing a page`); }, scan: function () { console.log(`\${this.name} is scanning a document`); }, play: function (artist, track) { console.log(`\${this.name} is playing '\${track}' by \${artist}`); }, }; const orders = [{ template: { name: 'ACME Printer'}, parts: ['print'] }, { template: { name: 'Initech Scanner'}, parts: ['scan'] }, { template: { name: 'ComTron Copier'}, parts: ['scan', 'print'] }, { template: { name: 'BoomBox Stereo'}, parts: ['play'] }];</pre>

```
const products = factory(library, orders);
console.log(products);
```

Output

```
[
  {
    name: 'ACME Printer',
    print: [Function: print]
  },
  {
    name: 'Initech Scanner',
    scan: [Function: scan]
  },
  {
    name: 'ComTron Copier',
    scan: [Function: scan],
    print: [Function: print]
  },
  {
    name: 'BoomBox Stereo',
    play: [Function: play]
  }
]
```

5. Assembly Line

Create a function that **returns** a **library of decorator functions**. They can be used to **compose** different functionality in a **car object** that they receive as an argument.

Your solution must **return an object**, containing **three decorator functions**:

hasClima – compose air conditioning controls into the passed-in object. This function takes an **object as a parameter** and adds to it the following properties:

- **temp** – **number** with default value **21**;
- **tempSettings** – **number** with default value **21**;
- **adjustTemp** – **function** which takes **no arguments**. If **temp** is less than **tempSettings**, this function adds 1 to **temp**. If **temp** is more than **tempSettings**, it decreases **temp** by 1. If **temp** and **tempSettings** are equal, the function does nothing.

hasAudio – compose audio player functionality into the passed-in object. This function takes an **object as a parameter** and adds to it the following properties:

- **currentTrack** – **object** with properties **name** (string) and **artist** (string). The default value is **null**;
- **nowPlaying** – **function**, which **prints** on the console the text:
`Now playing '\${currentTrack.name}' by \${currentTrack.artist}` , where **name** and **artist** are properties of the **currentTrack** object. If **currentTrack** is **null**, this function does nothing.

hasParktronic – compose parking aid functionality into the passed in object. This function takes an **object as a parameter** and adds to it the following properties:

- **checkDistance** – **function**, which takes a **single argument distance** (number) and **prints** a message on the console, depending on its value:

```

distance < 0.1 – "Beep! Beep! Beep!"
0.1 <= distance < 0.25 – "Beep! Beep!"
0.25 <= distance < 0.5 – "Beep!"

```

In any other case, print an **empty string**.

Input

Your **solution** will receive **no arguments**. All the methods in the returned library must take an **object as an argument**. Any methods that you compose into this object must meet the input requirements listed in the description above.

Output

Your **solution** must **return an object** containing the **three decorators** described above.

Example

Setup	
<pre> const assemblyLine = createAssemblyLine(); const myCar = { make: 'Toyota', model: 'Avensis' }; </pre>	
Input	Output
<pre> assemblyLine.hasClima(myCar); console.log(myCar.temp); myCar.tempSettings = 18; myCar.adjustTemp(); console.log(myCar.temp); </pre>	<pre> 21 20 </pre>
Input	Output
<pre> assemblyLine.hasAudio(myCar); myCar.currentTrack = { name: 'Never Gonna Give You Up', artist: 'Rick Astley' }; myCar.nowPlaying(); </pre>	<pre> Now playing 'Never Gonna Give You Up' by Rick Astley </pre>
Input	Output
<pre> assemblyLine.hasParktronic(myCar); myCar.checkDistance(0.4); myCar.checkDistance(0.2); </pre>	<pre> Beep! Beep! Beep! </pre>
Input	Output
<pre> console.log(myCar); </pre>	<pre> { make: 'Toyota', model: 'Avensis', temp: 20, tempSettings: 18, adjustTemp: [Function], currentTrack: { name: 'Never Gonna Give You Up', artist: 'Rick Astley' }, } </pre>

```
nowPlaying: [Function],
checkDistance: [Function]
}
```

6. From JSON to HTML Table

You're tasked with creating an HTML table of students and their scores. You will receive a single string representing an **array of objects**, the **table's headings** should be equal to the **object's keys**, while **each object's values** should be a **new entry** in the table. Any **text values** in an object should be **escaped**, to avoid introducing dangerous code into the HTML.

Input

The **input** comes with a **single string argument** (the array of objects).

Output

The **output** should be printed on the console – for each **entry row** in the input print the **object representing it**.

Note:

Objects' **keys** will always be the **same**. Check more information for the **HTML Entity** [here](#).

HTML

You are provided with an HTML file to test your table in the browser.

index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>FromJSONToHTMLTable</title>
  <style>
    table,th{
      border: groove;
      border-collapse: collapse;
    }
    td{
      border: 1px solid black;
    }
    td,th{
      padding: 5px;
    }
  </style>
</head>
<body>
  <div id="wrapper">
  </div>
  <script>
    function fromJSONToHTMLTable(input){
      //Write your code here
    }
    window.onload = function(){
      let container = document.getElementById('wrapper');
      container.innerHTML =
fromJSONToHTMLTable([' [{"Name": "Stamat", "Price": 5.5}, {"Name": "Rumen", "Price": 6} ] ']);
    };
  </script>
</body>
</html>
```

Examples

Input	Output
<pre>`[{"Name":"Stamat", "Score":5.5}, {"Name":"Rumen", "Score":6}]`</pre>	<pre><table> <tr><th>Name</th><th>Score</th></tr> <tr><td>Stamat</td><td>5.5</td></tr> <tr><td>Rumen</td><td>6</td></tr> </table></pre>
<pre>`[{"Name":"Pesho", "Score":4, "Grade":8}, {"Name":"Gosho", "Score":5, "Grade":8}, {"Name":"Angel", "Score":5.50, "Grade":10}]`</pre>	<pre><table> <tr><th>Name</th><th>Score</th><th>Grade</th></tr> <tr><td>Pesho</td><td>4</td><td>8</td></tr> <tr><td>Gosho</td><td>5</td><td>8</td></tr> <tr><td>Angel</td><td>5.5</td><td>10</td></tr> </table></pre>