

# Getting Started

## Contents

- Installation
- First KivyMD application
- And the equivalent with *Kivy*
- To left - *Kivy*, to right - *KivyMD*
- And the equivalent with *KivyMD*
- *KivyMD*
- *Kivy*

In order to start using *KivyMD*, you must first [install the Kivy framework](#) on your computer. Once you have installed *Kivy*, you can install *KivyMD*.

### Warning

*KivyMD* depends on *Kivy*! Therefore, before using *KivyMD*, first [learn how to work with Kivy](#).

## Installation

```
pip install kivymd
```

Command above will install latest release version of KivyMD from [PyPI](#). If you want to install development version from [master](#) branch, you should specify link to zip archive:

```
pip install  kivymd/KivyMD
```

 [latest](#) ▼

**Note**

Replace *master.zip* with *<commit hash>.zip* (eg *51b8ef0.zip*) to download KivyMD from specific commit.

Also you can install manually from sources. Just clone the project and run pip:

```
git clone https://github.com/kivymd/KivyMD.git --depth 1
cd KivyMD
pip install .
```

**Note**

If you don't need full commit history (about 320 MiB), you can use a shallow clone (*git clone https://github.com/kivymd/KivyMD.git --depth 1*) to save time. If you need full commit history, then remove *--depth 1*.

## First KivyMD application

```
from kivymd.app import MDApp
from kivymd.ui.label import MDLabel

class MainApp(MDApp):
    def build(self):
        return MDLabel(text="Hello, World", halign="center")

MainApp().run()
```

## And the equivalent with *Kivy*

```
from kivy.app import App
from kivy.ui.label import Label

class MainApp(App):
    def build(self):
        return Label(text="Hello, World")

MainApp().run()
```

 [latest](#) ▼

## To left - *Kivy*, to right - *KivyMD*



At first glance, the *KivyMD* example contains more code... However, the following example already demonstrates how difficult it is to create a custom button in *Kivy*:

```

from kivy.app import App
from kivy.metrics import dp
from kivy.uix.behaviors import TouchRippleBehavior
from kivy.uix.button import Button
from kivy.lang import Builder
from kivy.utils import get_color_from_hex

KV = """
#:import get_color_from_hex kivy.utils.get_color_from_hex

<RectangleFlatButton>:
    ripple_color: 0, 0, 0, .2
    background_color: 0, 0, 0, 0
    color: root.primary_color

    canvas.before:
        Color:
            rgba: root.primary_color
        Line:
            width: 1
            rectangle: (self.x, self.y, self.width, self.height)

Screen:
    canvas:
        Color:
            rgba: get_color_from_hex("#0F0F0F")
        Rectangle:
            pos: self.pos
            size: self.size
"""

class RectangleFlatButton(TouchRippleBehavior, Button):
    primary_color = get_color_from_hex("#EB8933")

    def on_touch_down(self, touch):
        collide_point = self.collide_point(touch.x, touch.y)
        if collide_point:
            touch.grab(self)
            self.ripple_show(touch)
            return True
        return False

    def on_touch_up(self, touch):
        if touch.grab_current is self:
            touch.ungrab(self)
            self.ripple_fade()
            return True
        return False

class MainApp(App):
    def build(self):
        screen = Builder.load_string(KV)
        screen.add_widget(
            RectangleFlatButton(
                text="Hello, World",
                pos_hint={"center_x": 0.5, "center_y": 0.5},

```

```

        size_hint=(None, None),
        size=(dp(110), dp(35)),
        ripple_color=(0.8, 0.8, 0.8, 0.5),
    )
)
return screen

```

```
MainApp().run()
```

## And the equivalent with *KivyMD*

```

from kivymd.app import MDApp
from kivymd.uix.screen import MDScreen
from kivymd.uix.button import MDBButton, MDBButtonText

class MainApp(MDApp):
    def build(self):
        self.theme_cls.theme_style = "Dark"
        self.theme_cls.primary_palette = "Orange"

        return (
            MDScreen(
                MDBButton(
                    MDBButtonText(
                        text="Hello, World",
                    ),
                    pos_hint={"center_x": 0.5, "center_y": 0.5},
                )
            )
        )

MainApp().run()

```

## *KivyMD*



