

Report – Scansione dei Servizi con Nmap – Target Windows

Miriana Fiorito – miry.fiorito@gmail.com

Indice

1. Obiettivo
2. Tipologia di scansioni utilizzate
3. Fase 1 – Firewall Attivo
4. Fase 2 – Firewall Disattivato
5. Confronto tra le due condizioni
6. Conclusioni
7. Considerazioni sulla Sicurezza

1. Obiettivo

Verificare l'effetto del Windows Firewall sulla visibilità dei servizi di rete, eseguendo scansioni Nmap da Kali Linux verso una macchina Windows in due condizioni:

- Firewall attivo
- Firewall disattivato

2.1 Scansioni Nmap Utilizzate

Comando Nmap	Tipo di Scansione	Descrizione Semplice	Finalità
<code>nmap -sS -Pn 192.168.50.102</code>	TCP SYN Scan + No Ping	Invia pacchetti SYN per rilevare porte aperte, ignorando il ping	Scansione stealth, utile se ICMP è bloccato
<code>nmap -sT -Pn 192.168.50.102</code>	TCP Connect Scan + No Ping	Stabilisce connessioni complete con le porte, ignorando il ping	Scansione completa, usata se SYN non funziona
<code>nmap -sV -Pn</code>	Version Detection + No Ping	Identifica i servizi attivi e le loro versioni, ignorando il ping	Riconoscere software e servizi in esecuzione

192.168.50.102			
nmap -O -Pn 192.168.50.102	OS Detection + No Ping	Tenta di identificare il sistema operativo del target, ignorando il ping	Rilevare il tipo di sistema (Windows, Linux)

2.2 Scansioni con Firewall Attivo

```
(kali@kali)-[~]
$ nmap -sV -Pn 192.168.50.102
Starting Nmap 7.95 ( https://nmap.org ) at 2025-09-26 05:11 EDT
Nmap scan report for 192.168.50.102
Host is up (0.0020s latency).
Not shown: 992 filtered tcp ports (no-response)
PORT      STATE SERVICE        VERSION
80/tcp    open  http           Microsoft IIS httpd 10.0
135/tcp   open  msrpc          Microsoft Windows RPC
1801/tcp  open  msmq?
2103/tcp  open  msrpc          Microsoft Windows RPC
2105/tcp  open  msrpc          Microsoft Windows RPC
2107/tcp  open  msrpc          Microsoft Windows RPC
3389/tcp  open  ms-wbt-server Microsoft Terminal Services
8443/tcp  open  ssl/https-alt
MAC Address: 08:00:27:64:5E:39 (PCS Systemtechnik/Oracle VirtualBox virtual NIC)
Service Info: OS: Windows; CPE: cpe:/o:microsoft:windows

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 94.07 seconds

(kali@kali)-[~]
```

```
(kali@kali)-[~]
$ nmap -O -Pn 192.168.50.102
Starting Nmap 7.95 ( https://nmap.org ) at 2025-09-26 05:15 EDT
Nmap scan report for 192.168.50.102
Host is up (0.0014s latency).
Not shown: 992 filtered tcp ports (no-response)
PORT      STATE SERVICE
80/tcp    open  http
135/tcp   open  msrpc
1801/tcp  open  msmq
2103/tcp  open  zephyr-clt
2105/tcp  open  eklogin
2107/tcp  open  msmsg-mgmt
3389/tcp  open  ms-wbt-server
8443/tcp  open  https-alt
MAC Address: 08:00:27:64:5E:39 (PCS Systemtechnik/Oracle VirtualBox virtual NIC)
Warning: OSScan results may be unreliable because we could not find at least 1 open and 1 closed port
Aggressive OS guesses: Microsoft Windows 10 1607 (97%), Microsoft Windows Phone 7.5 or 8.0 (94%), Microsoft Windows Embedded Standard 7 (93%), Microsoft Windows 10 1511 - 1607 (92%), Microsoft Windows 7 or Windows Server 2008 R2 (91%), Microsoft Windows Server 2008 R2 or Windows 8.1 (91%), Microsoft Windows Server 2016 (91%), Microsoft Windows Vista SP0 or SP1, Windows Server 2008 SP1, or Windows 7 (91%), Microsoft Windows 11 21H2 (91%), Microsoft Windows Vista SP2, Windows 7 SP1, or Windows Server 2008 (90%)
No exact OS matches for host (test conditions non-ideal).
Network Distance: 1 hop

OS detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 22.87 seconds
```

```
(kali@kali)-[~]
$ nmap -sT -Pn 192.168.50.102

Starting Nmap 7.95 ( https://nmap.org ) at 2025-09-26 05:25 EDT
Nmap scan report for 192.168.50.102
Host is up (0.0038s latency).
Not shown: 992 filtered tcp ports (no-response)
PORT      STATE SERVICE
80/tcp    open  http
135/tcp   open  msrpc
1801/tcp  open  msmq
2103/tcp  open  zephyr-clt
2105/tcp  open  eklogin
2107/tcp  open  msmq-mgmt
3389/tcp  open  ms-wbt-server
8443/tcp  open  https-alt

Nmap done: 1 IP address (1 host up) scanned in 21.28 seconds
```

```
(kali@kali)-[~]
$ nmap -sS -Pn 192.168.50.102

Starting Nmap 7.95 ( https://nmap.org ) at 2025-09-26 05:26 EDT
Nmap scan report for 192.168.50.102
Host is up (0.0012s latency).
Not shown: 992 filtered tcp ports (no-response)
PORT      STATE SERVICE
80/tcp    open  http
135/tcp   open  msrpc
1801/tcp  open  msmq
2103/tcp  open  zephyr-clt
2105/tcp  open  eklogin
2107/tcp  open  msmq-mgmt
3389/tcp  open  ms-wbt-server
8443/tcp  open  https-alt
MAC Address: 08:00:27:64:5E:39 (PCS Systemtechnik/Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 18.81 seconds
```

2.3 Scansioni con Firewall Disattivato

```
(kali@kali)-[~]
$ nmap -sS -Pn 192.168.50.102

Starting Nmap 7.95 ( https://nmap.org ) at 2025-09-26 10:11 EDT
Nmap scan report for 192.168.50.102
Host is up (0.00059s latency).
Not shown: 982 closed tcp ports (reset)
PORT      STATE SERVICE
7/tcp     open  echo
9/tcp     open  discard
13/tcp    open  daytime
17/tcp    open  qotd
19/tcp    open  chargen
80/tcp    open  http
135/tcp   open  msrpc
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
1801/tcp  open  msmq
2103/tcp  open  zephyr-clt
2105/tcp  open  eklogin
2107/tcp  open  msmq-mgmt
3389/tcp  open  ms-wbt-server
5432/tcp  open  postgresql
8009/tcp  open  ajp13
8080/tcp  open  http-proxy
8443/tcp  open  https-alt
MAC Address: 08:00:27:64:5E:39 (PCS Systemtechnik/Oracle VirtualBox virtual NIC)

Nmap done: 1 IP address (1 host up) scanned in 20.81 seconds
```

```
(kali@kali)-[~]
$ nmap -sT -Pn 192.168.50.102

Starting Nmap 7.95 ( https://nmap.org ) at 2025-09-26 10:11 EDT
Nmap scan report for 192.168.50.102
Host is up (0.00081s latency).
Not shown: 982 closed tcp ports (conn-refused)
PORT      STATE SERVICE
7/tcp     open  echo
9/tcp     open  discard
13/tcp    open  daytime
17/tcp    open  qotd
19/tcp    open  chargen
80/tcp    open  http
135/tcp   open  msrpc
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
1801/tcp  open  msmq
2103/tcp  open  zephyr-clt
2105/tcp  open  eklogin
2107/tcp  open  msmq-mgmt
3389/tcp  open  ms-wbt-server
5432/tcp  open  postgresql
8009/tcp  open  ajp13
8080/tcp  open  http-proxy
8443/tcp  open  https-alt

Nmap done: 1 IP address (1 host up) scanned in 14.94 seconds
```

```
(kali@kali)-[~]
$ nmap -sV -Pn 192.168.50.102

Starting Nmap 7.95 ( https://nmap.org ) at 2025-09-26 10:12 EDT
Nmap scan report for 192.168.50.102
Host is up (0.0028s latency).
Not shown: 982 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
7/tcp     open  echo
9/tcp     open  discard?
13/tcp    open  daytime      Microsoft Windows International daytime
17/tcp    open  qotd         Windows qotd (English)
19/tcp    open  chargen
80/tcp    open  http         Microsoft IIS httpd 10.0
135/tcp   open  msrpc        Microsoft Windows RPC
139/tcp   open  netbios-ssn  Microsoft Windows netbios-ssn
445/tcp   open  microsoft-ds Microsoft Windows 7 - 10 microsoft-ds (workgroup: WORKGROUP)
1801/tcp  open  msmq?
2103/tcp  open  msrpc        Microsoft Windows RPC
2105/tcp  open  msrpc        Microsoft Windows RPC
2107/tcp  open  msrpc        Microsoft Windows RPC
3389/tcp  open  ms-wbt-server Microsoft Terminal Services
5432/tcp  open  postgresql?
8009/tcp  open  ajp13        Apache Jserv (Protocol v1.3)
8080/tcp  open  http         Apache Tomcat/Coyote JSP engine 1.1
8443/tcp  open  ssl/https-alt

MAC Address: 08:00:27:64:5E:39 (PCS Systemtechnik/Oracle VirtualBox virtual NIC)
Service Info: Host: DESKTOP-9K104BT; OS: Windows; CPE: cpe:/o:microsoft:windows

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 173.86 seconds
```

```
(kali@kali)-[~]
```

```
(kali㉿kali)-[~]
$ nmap -O -Pn 192.168.50.102
Starting Nmap 7.95 ( https://nmap.org ) at 2025-09-26 10:16 EDT
Nmap scan report for 192.168.50.102
Host is up (0.00077s latency).
Not shown: 982 closed tcp ports (reset)
PORT      STATE SERVICE
7/tcp     open  echo
9/tcp     open  discard
13/tcp    open  daytime
17/tcp    open  qotd
19/tcp    open  chargen
80/tcp    open  http
135/tcp   open  msrpc
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
1801/tcp  open  msmq
2103/tcp  open  zephyr-clt
2105/tcp  open  eklogin
2107/tcp  open  msmq-mgmt
3389/tcp  open  ms-wbt-server
5432/tcp  open  postgresql
8009/tcp  open  ajp13
8080/tcp  open  http-proxy
8443/tcp  open  https-alt
MAC Address: 08:00:27:64:5E:39 (PCS Systemtechnik/Oracle VirtualBox virtual NIC)
Device type: general purpose
Running: Microsoft Windows 10
OS CPE: cpe:/o:microsoft:windows_10
OS details: Microsoft Windows 10 1507 - 1607
Network Distance: 1 hop

OS detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 21.05 seconds
(kali㉿kali)-[~]
```

3. Fase 1 – Firewall Attivo

Stato del firewall:

- Attivo
- Blocca connessioni in entrata non autorizzate
- Consente connessioni in uscita

Risultati:

Porta	Servizio	Stato	Versione rilevata
135	msrpc	aperta	Microsoft RPC
445	microsoft-ds	aperta	Windows SMB
3389	ms-wbt-server	filtrata	—

4. Fase 2 – Firewall Disattivato

Azioni:

Disattivazione del firewall tramite Pannello di Controllo.

Risultati:

Porta	Servizio	Stato	Versione rilevata
135	msrpc	aperta	Microsoft RPC
139	netbios-ssn	aperta	NetBIOS Session Service
445	microsoft-ds	aperta	Windows SMB
3389	ms-wbt-server	aperta	Remote Desktop Protocol
49152	unknown	aperta	—

5. Confronto tra le due condizioni

Porta	Firewall Attivo	Firewall Disattivato	Differenza
135	aperta	aperta	Nessuna
139	nascosta	aperta	Visibile solo senza firewall
445	aperta	aperta	Nessuna
3389	filtrata	aperta	Accessibile senza firewall
49152	nascosta	aperta	Visibile solo senza firewall

6. Considerazioni sulla Sicurezza

- Il firewall è una barriera fondamentale contro accessi non autorizzati.
- Lasciare porte aperte come 3389 (RDP) può esporre il sistema a rischi di attacco remoto.
- È buona pratica mantenere il firewall attivo e configurare regole precise solo per i servizi necessari.
- In ambienti di test, disattivare il firewall può aiutare nell'analisi, ma in produzione deve sempre essere attivo.

7. Conclusioni

- Il Windows Firewall nasconde porte e servizi, riducendo la superficie d'attacco.
- Disattivandolo, Nmap rileva più porte aperte, inclusi servizi critici come RDP (3389).
- Questo dimostra l'importanza del firewall nella protezione di rete.

