

Built In Functions

<u>abs()</u>	Returns the absolute value of a number
<u>all()</u>	Returns True if all items in an iterable object are true
<u>any()</u>	Returns True if any item in an iterable object is true
<u>bool()</u>	Returns the boolean value of the specified object
<u>dict()</u>	Returns a dictionary (Array)
<u>enumerate()</u>	Takes a collection (e.g. a tuple) and returns it as an enumerate object
<u>filter()</u>	Use a filter function to exclude items in an iterable object
<u>float()</u>	Returns a floating point number
<u>format()</u>	Formats a specified value
<u>input()</u>	Allowing user input
<u>int()</u>	Returns an integer number
<u>iter()</u>	Returns an iterator object
<u>len()</u>	Returns the length of an object
<u>list()</u>	Returns a list
<u>map()</u>	Returns the specified iterator with the specified function applied to each item
<u>min()</u>	Returns the smallest item in an iterable
<u>next()</u>	Returns the next item in an iterable
<u>open()</u>	Opens a file and returns a file object
<u>pow()</u>	Returns the value of x to the power of y
<u>print()</u>	Prints to the standard output device
<u>range()</u>	Returns a sequence of numbers, starting from 0 and increments by 1 (by default)
<u>reversed()</u>	Returns a reversed iterator
<u>round()</u>	Rounds a numbers
<u>set()</u>	Returns a new set object
<u>sorted()</u>	Returns a sorted list
<u>str()</u>	Returns a string object
<u>sum()</u>	Sums the items of an iterator
<u>tuple()</u>	Returns a tuple

type()	Returns the type of an object
zip()	Returns an iterator, from two or more iterators

String Functions

capitalize()	Converts the first character to upper case
casefold()	Converts string into lower case
count()	Returns the number of times a specified value occurs in a string
endswith()	Returns true if the string ends with the specified value
find()	Searches the string for a specified value and returns the position of where it was found
format()	Formats specified values in a string
index()	Searches the string for a specified value and returns the position of where it was found
isalnum()	Returns True if all characters in the string are alphanumeric
isalpha()	Returns True if all characters in the string are in the alphabet
isdigit()	Returns True if all characters in the string are digits
islower()	Returns True if all characters in the string are lower case
isnumeric()	Returns True if all characters in the string are numeric
isupper()	Returns True if all characters in the string are upper case
join()	Converts the elements of an iterable into a string
lower()	Converts a string into lower case
replace()	Returns a string where a specified value is replaced with a specified value
split()	Splits the string at the specified separator, and returns a list
splitlines()	Splits the string at line breaks and returns a list
startswith()	Returns true if the string starts with the specified value
strip()	Returns a trimmed version of the string
swapcase()	Swaps cases, lower case becomes upper case and vice versa
title()	Converts the first character of each word to upper case
upper()	Converts a string into upper case

List Functions

append()	Adds an element at the end of the list
clear()	Removes all the elements from the list
copy()	Returns a copy of the list
count()	Returns the number of elements with the specified value
extend()	Add the elements of a list (or any iterable), to the end of the current list
index()	Returns the index of the first element with the specified value
insert()	Adds an element at the specified position
pop()	Removes the element at the specified position
remove()	Removes the first item with the specified value
reverse()	Reverses the order of the list
sort()	Sorts the list

Dictionary Functions

clear()	Removes all the elements from the dictionary
copy()	Returns a copy of the dictionary
get()	Returns the value of the specified key
items()	Returns a list containing a tuple for each key value pair
keys()	Returns a list containing the dictionary's keys
pop()	Removes the element with the specified key
popitem()	Removes the last inserted key-value pair
setdefault()	Returns the value of the specified key. If the key does not exist: insert the key, with the specified value
update()	Updates the dictionary with the specified key-value pairs
values()	Returns a list of all the values in the dictionary

Tuple Functions

count()	Returns the number of times a specified value occurs in a tuple
index()	Searches the tuple for a specified value and returns the position of where it was found