

MID-POINT LINE ALGORITHM (contd*)

LECTURE 4

Equation of a line:

Implicit form $\left\{ \begin{array}{l} y = mx + c \dots\dots (i) \end{array} \right.$, where $m = \frac{dy}{dx}$

↓

$\Rightarrow y = \frac{dy}{dx} \cdot x + c \dots\dots$ (multiply both sides with dx)

$\Rightarrow dx \cdot y = dy \cdot x + dx \cdot c \dots\dots$ (take $dx \cdot y$ to the right hand side)

$\Rightarrow \underbrace{dy \cdot x}_{\downarrow} - \underbrace{dx \cdot y}_{\downarrow} + \underbrace{dx \cdot c}_{\downarrow} = 0 \dots\dots$


Explicit form $\left\{ \right.$

$Ax + By + C = 0 \dots\dots (ii)$

(replace,
✓ $dy = A$
✓ $-dx = B$
✓ $dx \cdot c = C$)


case 1

case 2



if we plug in the coordinates of M into the eqn of the line, the resulting value of the function will be (+ve)

$f(m) = +ve$




if we plug in the coordinates of M into the eqn of the line, the resulting value of the function will be (-ve)

$f'(m') = -ve$

ସୂଚକ ଲିନି ଫିଗର ଅନୁସାରେ ଅଙ୍କିତ ହେଉ।


Bresenham's



we will be considering the rate of change (in the deviation from the midpoint)

(ii) to further locate the pixels in the path.

Designing the Algo for Zone 0.



(deviation at m_1 , solving for ΔE)

$$\text{at } m_1, \longrightarrow A(x+1) + B(y+1/2) + C = d_1$$

$$\text{at } m, \longrightarrow A(x+1) + B(y+1/2) + C = d$$

$$\lim_{\Delta x \rightarrow 0} (A(x+1) + B(y+1/2) + C) - (A(x) + B(y+1/2) + C) = d_1 - d \approx \Delta E$$

$$\therefore A = \Delta E$$

$$\text{meaning, } \Delta E = dy$$

(i)

the rate of change of pixel for a horizontal movement.

(deviation at m_2 , solving for ΔNE)

$$\text{at } m_2 \rightarrow A(x+2) + B(y+3/2) + C = d_2$$

$$\text{at } m \rightarrow A(x+1) + B(y+1/2) + C = d$$

$$A + B + 0 = d_2 - d = \Delta NE$$

$$\therefore \Delta NE = A + B$$

$$\Delta NE = dy - dx$$

ii

the rate of change in pixel for a corner movement.

we still need to solve for the initial deviation / d_{init} at m , for starting points (x_0, y_0)

$$\text{at } m, A(x_0+1) + B(y_0+1/2) + C = d_{init}$$

$$\Rightarrow Ax_0 + By_0 + C + A + B/2 = d_{init}$$


$$\Rightarrow d_{init} = A + B/2$$

since (x_0, y_0) is a coordinate from the line $Ax_0 + By_0 + C = 0$

$$\Rightarrow d_{init} = dy - dx/2$$

iii

Ø Now, we need figure out if we'll move to $\Delta E / \Delta NE$ based on the polarity of the value for d_{init} :



Ø for ΔNE , where line goes over midpoint.

$$d_{init} = dy - \frac{dx}{2} = 0.8 - \frac{1}{2} = 0.3 (+ve)$$

Ø for ΔE , where line goes below midpoint.

$$d_{init} = 0.3 - \frac{1}{2} = -0.2 (-ve)$$

*

∴ We can conclude that for a +ve value for d the movement will be ΔNE ,

AND,

for a -ve value for d the movement will be ΔE .

Pseudo Code (MPL Zone 0):

drawline (x_0, y_0, x_1, y_1) {

$$dy = y_1 - y_0$$

$$dx = x_1 - x_0$$

$$d = 2dy - dx$$

// $d = d_{init}$.

$$\Delta E = 2dy$$

// since we multiply 2 with d to avoid fraction

$$\Delta NE = 2(dy - dx)$$

// we need to multiply

ΔE & ΔNE with 2 as well.

$$x = x_0$$

$$y = y_0$$

draw(x, y);

while ($x \leq x_2$) {

if ($d \leq 0$) {

// for ΔE movement only x increases.

$x++$

$$d += \Delta E$$

// add ΔE to current value of d

} else {

// for ΔNE movement x, y both increase by 1.

$x++$

$y++$

$$d += \Delta NE$$

// add ΔNE to current value of d .

}

draw(x, y)

}

}

Q1)

Draw $(30, 50)$ to $(40, 54)$ using MPL

$\Delta y = 4$, $\Delta x = 10$

$d = \Delta y - \Delta x / 2 = 2(\Delta y) - \Delta x = 8 - 10 = -2$

use this to avoid fraction.

$\Delta E = 2 \cdot \Delta y = +8$

$\Delta NE = 2(\Delta y - \Delta x) = 2(4 - 10) = -12$

x	y	d	$\Delta E / \Delta NE$	(PIXEL)
30	50	-2	ΔE	$(30, 50)$
31	50	6	ΔNE	$(31, 50)$
32	51	-6	ΔE	$(32, 51)$
33	51	2	ΔNE	$(33, 51)$
34	52	-10	ΔE	$(34, 52)$
35	52	-2	ΔE	$(35, 52)$
36	52	6	ΔNE	$(36, 52)$
37	53	-6	ΔE	$(37, 53)$
38	53	2	ΔNE	$(38, 53)$
39	54	-10	ΔE	$(39, 54)$
40	54	-2	ΔE	$(40, 54)$

$\Delta NE \rightarrow x+, y+$

$\Delta E \rightarrow x+, y-$

init

init

done


$x_b - y_b = \text{init} \therefore$

Home Assignment Design for Zone 1 & Zone 5

Zone 1



$m_1(x+\frac{1}{2}, y+2)$ $m_2(x+\frac{3}{2}, y+2)$



$\Delta N \rightarrow x=x$
 $y=y+1$
 $\Delta NE \rightarrow x=x+1$
 $y=y+1$

ΔN

at m_1
at m

$$A(x+\frac{1}{2}) + B(y+2) + C = d_1$$

$$\hookrightarrow A(x+\frac{1}{2}) + B(y+1) + C = d$$

$$0 + B + 0 = \Delta N$$

$\therefore \Delta N = -dx$ \rightarrow we'll use $[-2dx]$

ΔNE

at m_2
at m

$$A(x+\frac{3}{2}) + B(y+2) + C = d_2$$

$$\hookrightarrow A(x+\frac{1}{2}) + B(y+1) + C = d$$

$$A + B = \Delta NE$$

$\therefore \Delta NE = dy - dx$ \rightarrow we'll use $[2(dy - dx)]$

d_{init}

at m
 (x_0, y_0)

$$A(x_0 + \frac{1}{2}) + B(y_0 + 1) + C = d_{init}$$

$$A/\frac{1}{2} + B = d_{init}$$

$\therefore d_{init} = dy/\frac{1}{2} - dx$ \rightarrow we'll use $[dy - 2dx]$