

Product Specification



Vinyl Glove Powdered (Blue)
Brand: Elite Super Touch



If you would like samples or have any questions about our vinyl gloves,
please email michelle@finetouch.co.nz or call us on 0800 82 82 82

Product Features

- Non sterile, ambidextrous, single use
- 3.0 mil glove – provides tactile sensitivity
- Smooth surface - provides tactile sensitivity
- Beaded cuff – glove less likely to break while donning
- Latex free – for those who are allergic or sensitive to latex protein
- Powdered – for easy donning
- Blue colour – ideal where colour identification is required
- 100 gloves per box, 10 boxes per carton
- Sizes: Small, Medium, Large, XLarge
- Product Codes: C-GVBS (carton - small)
 - C-GVBM (carton - medium)
 - C-GVBL (carton - large)
 - C-GVBXL (carton - xlarge)

Quality Assurance

- ISO 9001 : 2008 certified by China Quality Management Centre
- CE Mark: Directive 89/686/EEC certified by SGS (Taiwan)
- FDA Title 21 (21CFR 177.2600): Indirect food additive regulations

Product Specification



Vinyl Glove Powdered (Blue)
Brand: Elite Super Touch

Physical Properties

Compliance Standards:

ASTM D3578: Standard Specification for Rubber Examination Gloves

ASTM D5250: Standard Specification for PVC Gloves for Medical Application

EN455 Parts 1 & 2: Medical Gloves for Single Use. Requirements and Testing

EN ISO 10993: Biological Evaluation of Medical Devices

Dimensions

Size	Palm Width (mm)	Length (mm)
Small	85 ± 2	Min 230
Medium	95 ± 2	Min 230
Large	105 ± 2	Min 230
XLarge	115 ± 2	Min 230

Thickness

Point of Thickness Measurement	Single Wall (mm)
Cuff	Min 0.06
Palm	Min 0.08
Finger	Min 0.08

Physical Properties

Criteria	Before Ageing	After Ageing
Tensile Strength (MPa)	Min 9	Min 9
Elongation (%)	Min 300	Min 300

Powder Residue: Max 100 mg/pc

Pre Shipment

Inspection Criteria	Inspection Level	AQL
Dimensions	S2	4.0
Physical Properties	S2	4.0
Barrier Integrity	G1	1.5
Visual Inspection for Defects	G1	2.5