

# SUN-AVOIDANCE SLEW PLANNING ALGORITHM WITH POINTING AND ACTUATOR CONSTRAINTS

Mohammad Ayoubi\* and Junette Hsin†

A sun avoidance slew maneuver is described in this paper. The algorithm finds the angular velocity, angular acceleration, and quaternion profiles needed to avoid the sun vector that lies near the plane of a sensor's FOV onboard a spacecraft.

## INTRODUCTION

Large-angle slew maneuvers are required during any Earth-pointing or interplanetary missions. In many space missions, and for safety consideration, a sensitive payload such as imaging camera or telescope needs to be retargeted while avoiding sun vector or other bright objects in the sky. The attitude reorientation problem in the presence of attitude constrained zones has been studied in the last three decades. McInnes<sup>1</sup> addressed this problem via using an artificial potential function. He proposed a guidance law which is entirely analytical and suitable for onboard implementation. However, he uses Euler angles which are singular for large slew angles. A geometric approach was proposed by Spindle,<sup>2</sup> Hablani,<sup>3</sup> and Biggs and Colley<sup>4</sup> where a feasible attitude maneuver, or a guidance law, is precomputed based on the attitude-avoidance-zone constraints. Another approach for addressing this problem is using randomized algorithms.<sup>5</sup> However, depends on the number of constraints and initial and final attitudes, this approach is computationally expensive and not suitable for onboard implementation. Another approach for solving the time optimal reorientation maneuver subject to boundaries and path constraints is proposed by Spiller et al.<sup>6</sup> They used the particle swarm optimization (PSO) technique to find a sub-optimal solution with keep-out constraints. Another approach is to cast the problem as a convex optimization problem and use a semi-definite programming (SDP) or quadratically constrained quadratic programming (QCQP) to solve them. See for instance Kim and Mesbahi,<sup>7</sup> Kim et al.,<sup>8</sup> Sun and Dai,<sup>9</sup> and Lee and Mesbahi<sup>10</sup> Recently, Ramos and Schaub<sup>11</sup> proposed a method based on the Lyapunov stability theorem and logarithmic barrier potential function to derive a steering law for attitude control of a spacecraft subject to conically constrained inclusion and exclusion regions. They also considered the control-torque constraint in their algorithm. In this paper, we present a novel geometric approach for large-angle slew planning with pointing and actuator constraints. We assume spacecraft has a single light-sensitive payload with control-torque and angular momentum constraints. Furthermore, we assume the initial and final attitudes, instrument boresight vector, and sun vector are known. Then we derive the desired quaternions, angular velocity, and angular acceleration based on the Pontryagin's minimum principle (PMP) for this maneuver. The proposed algorithm in this paper is intuitive, deterministic, easy to implement, and includes the control-torque and angular momentum constraints. The

---

\*Title, department, affiliation, postal address.

†Title, department, affiliation, postal address.

main drawback of the proposed algorithm is its limitation for a single payload, single-constraint region. A Monte Carlo simulation is performed to show the viability of the proposed algorithm with control-torque and angular momentum constraints.

### Problem Justification

Given:  ${}^N\hat{P}_i, {}^N\hat{P}_f, {}^N\hat{S}, {}^G\hat{P}, \epsilon_p, {}^Nq^G, {}^N\omega^G(t_i)$ , and  ${}^N\omega^G(t_f)$ .

Find:

1. A sequence of slew maneuvers to avoid sun vector.
2. the commanded angular velocity, angular acceleration, and quaternion profiles.




Figure 1. The spacecraft is not drawn to scale.

Nomenclature:

- $G$  frame: Unit sphere attached to the gyrostat.
- $N$ : frame: The Newtonian frame fixed in the inertial space.
- ${}_G\hat{P}$ : Unit vector along the bore sight of payload in the  $G$  frame.
- ${}_N\hat{P}_i$ : Unit vector of the initial point in the  $G$  frame.
- ${}_N\hat{P}_f$ : Unit vector of the final point in the  $G$  frame.
- ${}_N\hat{S}$ : Unit vector of the sun vector in the  $N$  frame.
- $\epsilon_p$ : Payload half-cone angle.

## Literature surveyed

This is the literature surveyed.

## Contribution of work

This is the contribution of work.

## ALGORITHM DESCRIPTION

### Slew Maneuver

*Check the Sun Vector Intrusion*

1. Check the angular separation between the sun vector,  $\hat{S}$ , and the  $\hat{P}_i - \hat{P}_f$  plane.

$$\alpha = \frac{\pi}{2} - \cos^{-1}(\hat{S} \cdot \hat{e}) \quad (1)$$

where the eigenaxis is determined by

$$\hat{e} = \frac{\hat{P}_i \times \hat{P}_f}{|\hat{P}_i \times \hat{P}_f|} \quad (2)$$

2. IF  $|\alpha| < \epsilon_p$ , THEN determine the projection of the sun vector into the  $\hat{P}_i - \hat{P}_f$  plane.

$$\vec{S}_{||} = \hat{S} \cos \alpha \quad (3)$$



*Slew Maneuvers*


1. The 1<sup>st</sup> slew around the eigenaxis,  $\hat{e}$ , through angle:

$$\phi_1 = \begin{cases} \cos^{-1}(\hat{P} \cdot \hat{G} \hat{S}_{||}) - \epsilon_p & \text{when } \cos^{-1}(\hat{P} \cdot \hat{G} \hat{S}_{||}) - \epsilon_p \leq \pi \\ \cos^{-1}(\hat{P} \cdot \hat{G} \hat{S}_{||}) - \epsilon_p - 2\pi & \text{when } \cos^{-1}(\hat{P} \cdot \hat{G} \hat{S}_{||}) - \epsilon_p > \pi \end{cases} \quad (4)$$


2. The 2<sup>nd</sup> slew around the unit sun vector,  $\hat{S}$ , via  $\phi_2$ .

(a) when  $\alpha \neq 0$






(b) when  $\alpha = 0$



3. The 3<sup>rd</sup> slew about the  $\hat{e}$  through angle:

$$\phi_3 = \begin{cases} \cos^{-1}({}_G\hat{P}_f \cdot \hat{P}_2) & \text{when } {}_G\hat{P}_f \cdot \hat{P}_2 \geq 0 \\ \cos^{-1}({}_G\hat{P}_f \cdot \hat{P}_2) - 2\pi & \text{when } {}_G\hat{P}_f \cdot \hat{P}_2 < 0 \end{cases} \quad (5)$$



4. The final slew is about the instrument boresight axis to go to the final attitude.

## Summary of Algorithm

1. Slew around the eigenaxis,  $\hat{e}$ , through angle:

$$\phi_1 = \begin{cases} \cos^{-1}(\hat{P} \cdot_G \hat{S}_{||}) - \epsilon_p & \text{when } \cos^{-1}(\hat{P} \cdot_G \hat{S}_{||}) - \epsilon_p \leq \pi \\ \cos^{-1}(\hat{P} \cdot_G \hat{S}_{||}) - \epsilon_p - 2\pi & \text{when } \cos^{-1}(\hat{P} \cdot_G \hat{S}_{||}) - \epsilon_p > \pi \end{cases} \quad (6)$$


2. Slew around the  $\hat{S}$  via:

$$\phi_2 = \begin{cases} 2 \tan^{-1}\left(\frac{\epsilon_p}{\sin \alpha}\right) & \text{when } \alpha \neq 0 \\ \pi & \text{when } \alpha = 0 \end{cases} \quad (7)$$

3. Slew about the  $\hat{e}$  through angle:

$$\phi_3 = \begin{cases} \cos^{-1}({}_G \hat{P}_f \cdot \hat{P}_2) & \text{when } {}_G \hat{P}_f \cdot \hat{P}_2 \geq 0 \\ \cos^{-1}({}_G \hat{P}_f \cdot \hat{P}_2) - 2\pi & \text{when } {}_G \hat{P}_f \cdot \hat{P}_2 < 0 \end{cases} \quad (8)$$

4. Perform the final rotation,  $\phi_4$ , about the instrument boresight axis to adjust the attitude.



## STEERING LAWS

### Case 1: Single-Axis, Agile Slew Maneuver with Velocity and Acceleration Constraints.


*Problem Statement* Consider the motion of a [rigid](#) spacecraft around a given inertially-fixed axis,  ${}_G \hat{e} = [e_x, e_y, e_z]^T$ . The problem of minimum-time slew maneuver around the  $\hat{e}$  axis can be formulated as

$$\underset{u}{\text{Minimize}} J[x(\cdot), u(\cdot), t_f] = \int_{t_0}^{t_f} dt, \quad (9)$$

subject to the following dynamic constraint

$$\Sigma : \begin{cases} \dot{x}_1 = x_2, \\ \dot{x}_2 = M/I_{\hat{e}}^{G/G^*} = u, \end{cases} \quad (10)$$

where  $x_1 \triangleq \phi$  and  $x_2 = \dot{\phi}$ .



*Velocity and Acceleration Constraints* The boundary conditions are

$$BCs : \begin{cases} \phi(t_0) = 0, \phi(t_f) = \phi_f, \\ \dot{\phi}(t_0) = \dot{\phi}_0, \dot{\phi}(t_f) = \dot{\phi}_f, \end{cases} \quad (11)$$

and velocity (state) and acceleration (control) constraints are

$$C_1 : \begin{cases} |x_2 = \dot{\phi}| \leq \dot{\phi}_{max}, \\ |u = \ddot{\phi}| \leq \ddot{\phi}_{max}, \end{cases} \quad (12)$$

in which

$$\dot{\phi}_{max} = [I^{w/w^*}]^{-1} [{}^N H^{G/G^*} - (I^{G/G^*} + I^{w/w^*}) {}^N \omega^G] / (e_x + e_y + e_z), \quad (13)$$

and

$$\ddot{\phi}_{max} = {}_B \hat{e}^T {}_B M_{max} / I_{\hat{e}}^{G/G^*}, \quad (14)$$

where  ${}^N H^{G/G^*}$  is the total angular momentum of the gyrostatt with respect to its center of mass,  $G^*$ , in the  $N$ -frame.  $I^{G/G^*}$  and  $I^{w/w^*}$  represent the inertia dyadic of the gyrostatt and reaction wheel with respect to their center of masses, respectively.  ${}_B M_{max}$  is the maximum generated torque along the body-axes in the body frame.

**Find:**  $\phi(t)$ ,  $\dot{\phi}(t)$ , and  $\ddot{\phi}(t)$ .

## Steering Profiles

- Angular acceleration profile (bang-off-bang):

$$\ddot{\phi}(t) = u = \begin{cases} \ddot{\phi}_{max} & \text{when } t_0 \leq t \leq t_1, \\ 0 & \text{when } t_1 \leq t \leq t_2, \\ -\ddot{\phi}_{max} & \text{when } t_2 \leq t \leq t_f. \end{cases} \quad (15)$$

- Angular velocity profile:

$$\dot{\phi}(t) = \begin{cases} \dot{\phi}_0 + \ddot{\phi}_{max}(t - t_0) & \text{when } t_0 \leq t \leq t_1, \\ \dot{\phi}_{max} & \text{when } t_1 \leq t \leq t_2, \\ \dot{\phi}_{max} - \ddot{\phi}_{max}(t - t_2) & \text{when } t_2 \leq t \leq t_f. \end{cases} \quad (16)$$

- Angular position profile:

$$\phi(t) = \begin{cases} \dot{\phi}_0(t - t_0) + \frac{1}{2}\ddot{\phi}_{max}(t - t_0)^2 & \text{when } t_0 \leq t \leq t_1, \\ \phi(t_1) + \dot{\phi}_{max}(t - t_1) & \text{when } t_1 \leq t \leq t_2, \\ \phi(t_2) + \dot{\phi}_{max}(t - t_2) - \frac{1}{2}\ddot{\phi}_{max}(t - t_2)^2 & \text{when } t_2 \leq t \leq t_f. \end{cases} \quad (17)$$

- Using the conditions,  $\dot{\phi}(t_1) = \dot{\phi}_{max}$ ,  $\dot{\phi}(t_f) = \dot{\phi}_f$ ,  $\phi(t_f) = \phi_f$ , we can determine switching times  $t_1$ ,  $t_2$ , and final time  $t_f$  as:

$$t_1 = t_0 + \frac{\dot{\phi}_{max} - \dot{\phi}_0}{\ddot{\phi}_{max}}, \quad (18)$$

$$t_2 = t_1 + \frac{1}{\dot{\phi}_{max}} \left[ \phi_f - \dot{\phi}_0(t_1 - t_0) - \frac{1}{2}\ddot{\phi}_{max}(t_1 - t_0)^2 - \frac{\dot{\phi}_{max}(\dot{\phi}_{max} - \dot{\phi}_f)}{\ddot{\phi}_{max}} + \frac{(\dot{\phi}_{max} - \dot{\phi}_f)^2}{2\ddot{\phi}_{max}} \right], \quad (19)$$

and

$$t_f = t_1 + \frac{1}{\dot{\phi}_{max}} \left[ \phi_f - \dot{\phi}_0(t_1 - t_0) - \frac{1}{2}\ddot{\phi}_{max}(t_1 - t_0)^2 + \frac{(\dot{\phi}_{max} - \dot{\phi}_f)^2}{2\ddot{\phi}_{max}} \right]. \quad (20)$$

- Steering profiles:

$${}^N q^D(t) = [e_x \sin \frac{\phi(t)}{2}, e_y \sin \frac{\phi(t)}{2}, e_z \sin \frac{\phi(t)}{2}, \cos \frac{\phi(t)}{2}]^T \quad (21)$$

$${}^N_G \omega^D(t) = \dot{\phi}(t) {}_G \hat{e} \quad (22)$$

$${}^N_G \alpha^D(t) = \ddot{\phi}(t) {}_G \hat{e} \quad (23)$$



## Case 2: Single-Axis, Agile Slew Maneuver with Acceleration Constraint


*Problem Statement* Consider the optimal control problem described by Eqs.(9), (10), (11), and subject to control constraint

$$C_2 : |u = \ddot{\phi}| \leq \ddot{\phi}_{max}. \quad (24)$$

**Find:**  $\phi(t)$ ,  $\dot{\phi}(t)$ , and  $\ddot{\phi}(t)$ .

- Angular acceleration about the  $\hat{e}$  axis:

$$\ddot{\phi}(t) = \ddot{\phi}_{max}\mathbb{U}(t_0) - 2\ddot{\phi}_{max}\mathbb{U}(t - t_1) \quad (25)$$



where the switching and the final times are given by

$$t_1 = t_0 - \frac{\dot{\phi}_0}{\ddot{\phi}_{max}} + \frac{\sqrt{\ddot{\phi}_{max}^2(2\ddot{\phi}_{max}\phi_f + \dot{\phi}_f^2 + \dot{\phi}_0^2)}}{\sqrt{2}\ddot{\phi}_{max}^2} \quad (26)$$

and

$$t_f = t_0 - \frac{\dot{\phi}_f + \dot{\phi}_0}{\ddot{\phi}_{max}} + \frac{\sqrt{2}\sqrt{\ddot{\phi}_{max}^2(2\ddot{\phi}_{max}\phi_f + \dot{\phi}_{ef}^2 + \dot{\phi}_0^2)}}{\ddot{\phi}_{max}^2} \quad (27)$$

- Angular velocity about the  $\hat{e}$  axis:

$$\dot{\phi}(t) = \dot{\phi}_0 + \ddot{\phi}_{max}(t - t_0)\mathbb{U}(t_0) - 2\ddot{\phi}_{max}(t - t_1)\mathbb{U}(t - t_1) \quad (28)$$

- Angular position about the  $\hat{e}$  axis:

$$\begin{aligned} \phi(t) = & \dot{\phi}_0(t - t_0) + \ddot{\phi}_{max}\frac{(t - t_0)^2}{2}\mathbb{U}(t_0) \\ & - 2\ddot{\phi}_{max}\frac{(t - t_1)^2}{2}\mathbb{U}(t - t_1) \end{aligned} \quad (29)$$

*The First Slew Maneuver: A single-axis nonrest-to-rest maneuver around the  $\hat{e}$*

- The BCs:

$$\dot{\phi}(t_0) = \dot{\phi}_0, \phi(t_0) = 0, \dot{\phi}(t_{f1}) = 0, \phi(t_{f1}) = \phi_1. \quad (30)$$

The switching time,  $t_{11}$ , and minimum-time,  $t_{f1}$ , are

$$t_{11} = t_0 - \frac{\dot{\phi}_0}{\ddot{\phi}_{max}} + \frac{\sqrt{\ddot{\phi}_{max}^2(2\ddot{\phi}_{max}\phi_1 + \dot{\phi}_0^2)}}{\sqrt{2}\ddot{\phi}_{max}^2} \quad (31)$$

$$t_{f1} = t_0 - \frac{\dot{\phi}_0}{\ddot{\phi}_{max}} + \frac{\sqrt{2\ddot{\phi}_{max}^2(2\ddot{\phi}_{max}\phi_1 + \dot{\phi}_0^2)}}{\ddot{\phi}_{max}^2} \quad (32)$$

The  $\ddot{\phi}(t)$ ,  $\dot{\phi}(t)$ , and  $\phi(t)$ , can be found by substituting the boundary conditions given by (30) and  $t_{11}$  and  $t_{f1}$  in to Eqs. (25), (28), and (29), respectively.

*The Second Slew Maneuver: A rest-to-rest maneuver around the sun vector*

- The BCs:

$$\dot{\phi}(t_0) = 0, \phi(t_0) = 0, \dot{\phi}(t_{f2}) = 0, \phi(t_{f2}) = \phi_2. \quad (33)$$

The switching time,  $t_{12}$ , and the minimum-time,  $t_{f2}$ , are

$$t_{12} = t_0 - \frac{\sqrt{\phi_2}}{\ddot{\phi}_{max}} \quad (34)$$

$$t_{f2} = t_0 - \frac{2\sqrt{\phi_2}}{\ddot{\phi}_{max}} \quad (35)$$

The  $\ddot{\phi}(t)$ ,  $\dot{\phi}(t)$ , and  $\phi(t)$ , can be found by substituting the boundary conditions given by (33) and  $t_{12}$  and  $t_{f2}$  in to Eqs. (25), (28), and (29), respectively.

*The Third Slew Maneuver: A single-axis rest-to-nonrest maneuver around the  $\hat{e}$*

- The BCs:

$$\dot{\phi}(t_0) = 0, \phi(t_0) = 0, \dot{\phi}(t_{f3}) = \dot{\phi}_f, \phi(t_{f3}) = \phi_3. \quad (36)$$

The switching time,  $t_{13}$ , and the minimum-time,  $t_{f3}$ , are

$$t_{13} = t_0 + \frac{\sqrt{\ddot{\phi}_{max}^2(2\ddot{\phi}_{max}\phi_3 + \dot{\phi}_f^2)}}{\sqrt{2}\ddot{\phi}_{max}^2} \quad (37)$$

$$t_{f3} = t_0 - \frac{\dot{\phi}_f}{\ddot{\phi}_{max}} + \frac{\sqrt{2\ddot{\phi}_{max}^2(2\ddot{\phi}_{max}\phi_3 + \dot{\phi}_f^2)}}{\ddot{\phi}_{max}^2} \quad (38)$$

The  $\ddot{\phi}(t)$ ,  $\dot{\phi}(t)$ , and  $\phi(t)$ , can be found by substituting the boundary conditions given by (36) and  $t_{13}$  and  $t_{f3}$  in to Eqs. (25), (28), and (29), respectively.

## NUMERICAL SIMULATION

## CONCLUSION

## ACKNOWLEDGMENT

## APPENDIX: TITLE HERE

## Miscellaneous Physical Dimensions

## REFERENCES

- [1] C. R. McInnes, "Large angle slew maneuvers with autonomous sun vector avoidance," *Journal of Guidance Control Dynamics*, Vol. 17, 06 1994, pp. 875–877, 10.2514/3.21283.
- [2] K. Spindler, "New Methods in On-Board Attitude Control (AAS 98-308)," Vol. 100, 01 1998.
- [3] H. B. Hablani, "Attitude commands avoiding bright objects and maintaining communication with ground station," *Advances in the Astronautical Sciences*, 1998, 10.2514/2.4469.
- [4] J. D. Biggs and L. Colley, "Geometric Attitude Motion Planning for Spacecraft with Pointing and Actuator Constraints," *Journal of Guidance, Control, and Dynamics*, 2016, 10.2514/1.G001514.
- [5] E. Frazzoli, M. A. Dahleh, E. Feron, R. P. Kornfeld, and R. P. Kornfeld, "A Randomized Attitude Slew Planning Algorithm for Autonomous Spacecraft," *In AIAA Guidance, Navigation, and Control Conference*, 2001.
- [6] D. Spiller, L. Ansalone, and F. Curti, "Particle Swarm Optimization for Time-Optimal Spacecraft Reorientation with Keep-Out Cones," *Journal of Guidance, Control, and Dynamics*, 2016, 10.2514/1.G001228.
- [7] Y. Kim and M. Mesbahi, "Quadratically constrained attitude control via semidefinite programming," *IEEE Transactions on Automatic Control*, 2004, 10.1109/TAC.2004.825959.
- [8] Y. Kim, M. Mesbahi, G. Singh, and F. Y. Hadaegh, "On the convex parameterization of constrained spacecraft reorientation," *IEEE Transactions on Aerospace and Electronic Systems*, 2010, 10.1109/TAES.2010.5545176.
- [9] C. Sun and R. Dai, "Spacecraft Attitude Control under Constrained Zones via Quadratically Constrained Quadratic Programming," 2015, 10.2514/6.2015-2010.
- [10] U. Lee and M. Mesbahi, "Quaternion based optimal spacecraft reorientation under complex attitude constrained zones," *Advances in the Astronautical Sciences*, 2014.
- [11] M. Diaz Ramos and H. Schaub, "Kinematic Steering Law for Conically Constrained Torque-Limited Spacecraft Attitude Control," *Journal of Guidance, Control, and Dynamics*, Vol. 41, jul 2018, pp. 1990–2001, 10.2514/1.G002873.