V1.0
Otro texto

Clase 25/03/2026

Buscar para la próxima clase
1. Clave normal
2. Candidata
3. Superclave
4. Clave principal
5. Dependencia funcional

---

functional dependencies:

Definition

It's a generalization of the idea of a key for a relation

Más formalmente: Una dependencia funcional en una relacion R es una proposición de la forma

"Si dos tuplas R son iguales atributo a atributo (tienen los mismos valores en cada componente para cada atributo $A_1, A_2, ..., A_n$, entonces deben de *agree* en otra lista de atributo $B_1, B_2, ..., B_m$"

Debemos ver que con los atributos podemos obtener uno y solo uno de cada una de todas las instancia si seguimos con los mismos atributos para obtener tal.

$$A_1 A_2 \to B_1$$

Quiere decir que todas las instancias de $A_1 A_2$, entonces B_1 debería de tener un único avlor posible

Superkey

A set of attributes that contains a key is called a **superkey**, short for *"superset of a key"*.

Clave candidata

Es una superclave minimal.

Clave Primaria

Es una clave candidata elegida por el diseñador para identificar la celda

Key

An set of attributes it's a key $K \Leftrightarrow K$ functionally determines all other attributes in the table. If you K I can identify the entire tuple

Closure Functional Dependency

It's given some root in a graph. Compute all the dependencys. Then repeat until there's no node added. It's the union of all the nodes in the graph.

Trivial dependencies

$$A_1 \to A_1$$

Transitive rule

$$A_1 \to B_1 \wedge B_1 \to C_1 \Rightarrow A_1 \to C_1$$

Augmentation

$$A_1, ...A_n \rightarrow B_1, ..., B_m \Rightarrow A_1, ...A_n C_1 ..., C_k \rightarrow B_1, ..., B_m C_1 ..., C_k$$

Projecting a Set of Functional Dependencies.

Given

1. A relation R
2. A second relation R_1 (by proyection $R_1 = \pi_{\{L\}}(R)$)
3. Set of functional dependencies that hold in R
4. Compute the closre

Algorithm

For every possible subset of attributes X that exists in your new table S:

1. **Compute the Closure** (X^+)
2. **Intersect with the New Table**: Find the intersection of that closure with the attributes in your new table S. $Y = X^+ \cap S$
3. **Form the New Dependency**: For every attribute A in Y, if A is not already in X, then $X \rightarrow A$ is a functional dependency that holds in the new table.
4. **Simplify**

Avoid redundancy: Normal forms

We want to avoid anomalies in the DDBB because:

- Redundancy: Information repeated. It could cost or be extremaly giant a database if it's not designed correctly
- Update anomalies: we could change the content in one tuple and no in another and it could lead to inconsisteny
- Deletion anomalies: Set of vales becomes empty we could lose Information

Descomposition

Descomposition of a relation R into S and T without redundancy

1. $\{A_i, A_2, ..., A_n\} = \{B_1, B_2, ..., B_m\} \cup \{C_1, C_2, ..., C_k\}$
2. $S = \pi_{\{B_1, B_2, ..., B_m\}}(R)$
3. $T = \pi_{\{C_1, C_2, ..., C_k\}}(R)$

Boyce-Codd Normal form

A relation R is in BCNF $\Leftrightarrow$ whenever there is a nontrivial FD $A_1 A_2 ... A_n \rightarrow B_1 B_2 ... B_m$ for R, it is the case that $\{A_1, A_2, ..., A_n\}$ is a superkey for R.

"Equivalent the left side of every nontrivial FD must contain a key"

Descomposition into BCNF

1. Check whether R is in BCNF. If so, nothing more needs to be done. Return $\{R\}$ as the answer
2. If there are BCNF violations, let one be $X \rightarrow Y$. Use Algorithm 3.7 to compute X^+. Choose $R_1 = R^+$ as one relation schema and let R_2 have attributes X and those attributes of R that are not in X^+.
3. Use Algorithm 3.12 to compute the sets of FD's for R_1 and R_2, let these be S_1 and S_2, respectively
4. Descompose R_1 and R_2 again and again until they are BCNF

- Algorithm 3.7: Closure test

- Algorithm 3.12: Projecting a Set of Functional

Consequences of Descomposition

1. Elimination of anomalies
2. Recoverability of Information
3. Preservation

Formas normales

Una Forma Normal (FN) es un conjunto de reglas o "estándares de calidad" que aplicamos al diseño de una base de datos para asegurar que esté organizada de la manera más eficiente posible.

1st Normal Form

- **Unique Identifies**: we can identify each tuple by some set of components.
- **Atomic values**: components represent unique things. Not many
- Each **column name** must be **unique**
- There must be **no repeating groups**

2nd Normal Form

All data should depend on the whole primary key

3rd Normal Form

The primary key must define all Non Key columns and Non-Key columns must not depend on any other non-key

Formalmente

Whenever $A_1A_2...A_n \rightarrow B_1B_2...B_m$ is a nontrivial FD, either $\{A_1A_2...A_n\}$ is a superkey, or those of $B_1B_2...B_m$ that are not among the $A's$, are each a member of some key (not necessarily the same key).

BCNF

Arriba

Diferencia entre BCNF y 3NF

Es que permite dependencias funcionales hacia claves candidatas (primitivas)

Ejemplo: médico, paciente, especialidad

MVD (Multivalued dependency)

It's is a statement about some rela⊠tion R that when you fix the values for one set of attributes, then the values in certain other attributes are independent of the values of all the other attributes in the relation

$A_1, A_2, ...A_n \twoheadrightarrow B_1, B_2, ...B_m$

For each pair of tuples t and u of relation R that agree on all the $A's$, we can find in R some tuple v that agrees:

1. With both t and u on the $A's$,
2. With t on the $B's$, and
3. With u on all attributes of R that axe not among the $A's$ or $B's$.

Clase 01/04/2026

Estudiar:
- API Rest
- Modelo Relacional
- Algebra Relacional
- Operaciones
- Propiedades de las operaciones

Data model
it's a notation for describing data or Information Consist in
- structure of the data
- Operations on the data: queries and modifications on the database
- Constrains on the data: make the data has some meaning, knowing something that it's represents

important data models
- relation model:
- Semi-structured data model: XML

Relation model
Based on tables (relations). It's as it was an array of C struct, but they are not stored as them Operations: table oriented. know something about all of things in a table Constraints: doens't allow in some components some values

semi Semi-structured
it's a tree of graphs. Represent data hierachically nested tagged elements.

operations: follow paths in a tree

Constraints:
- data type of values associated with a tag.
- which data could be nested to a given tag.

Other data models
Object orintation models

. values can have structure
- Relations can have associated methods

Comparisons between data models
we want it to be fast. in that case, we preffered relational model

Relational Model
Represent data using relations: two-dimensions table

Attributes
Names of columns in a relation. They appear at the top of a table. Describes meaning of the column below.

Schemas

Name of a relation and the set of attributes. Attributes in a schema it's a set. But to talk about relations we need some standard, so we treat it like lists.

why? I don't see the benefits

Tuples

Rows of a relation. Tuples has one ***component*** for each attribute of the relation

Domains

each component should be atomic → must be of some type. Cannot be a record structure like array, set, etc.

The order in which we mention the attributes it's irrelevant.

Relation instances

a database changes over time. It has added, updated or deleted tuples. And, rarely the schema could change. An instence it's in some time the version of the database.

keys of relations

Set of attributes forms a key ⇔ we do not allow two tuple in the relation in all the attributes of the key.

Defining relation schema in SQL

SQl consists in: Data Definition and Data manipulation (for queries)

There are three kinds of relations:

- Stored relations (tables). The ones we use commonly.
- Views: relations defined by a computation. They are constructed when needed.
- Temporary tables: constructed by SQL language processor when it performs its job executing queries and data modifications

```
CREATE TABLE name (
  attribute_name   type
);
```

Data types

- STRING
  - CHAR: fixed length string
  - VARCHAR: fixed length string up to n characters.

Difference it's just implementation dependent

- Bit strings
  - BIT: bit strings of length n
  - BIT VARYING (n): bit strings of length up to n
- Boolean:
  - BOOLEAN: can take
    - True
    - False
    - Unknown
- INT / INTEGER: number

- SHORTINT

Difference its implementation dependent

- DATE
- TIME
- FLOAT / REAL
- DOUBLE (more precission)
- DECIMAL: decimal number that takes up to n decimal digits

Modifying relation schema

```
DROP TABLE table_name
```

ALTER TABLE

Has two options:

- ADD
- DROP

```
ALTER TABLE table_name option attribute
```

Default Values

When creating `DEFAULT value`

Declaring keys

- PRIMARY KEY
- UNIQUE: if the key consists in more than one attribute

Algebraic Query language

It's useful because it's less powerfull than common languages

What's an algebra?

operator and atomic operands

relation algebra: atomic operands are

- variables
- constants

Operators

- Set operations:
  - union
  - intersection
  - Difference
- Selection of some tuples
- Proyection of some columns
- Operations to combine two relations
  - Cartesian Product
  - Joins
- Renaming of attributes. Doesn't affect tuples, but to a schema

Set operations
union $R \cup S$ Intersection $R \cap S$ Difference $R - S$

1. R and S must have schemas with identical set of attributes. And types (domains) for each attribute must have the same in R and s
2. Colums R and S must be ordered before, so the order is same for both relations

Proyection
Produce from a relation R a new relation that has only some of R's columns

Selection
Produces a new relation with a subset of R's tuples. the tuples are those who satisfy some condition C.

Cartesian Product
Makes the cartesian product. Everyone meets everyone (talking about tuples)

Natural Joins
Given two relations we don't want all combinations, only pair tuples that match in some way $R \bowtie S$. We join them by the attributes that are common to each one. All rows generated are called: *joined tuples*

If there are multiple rows that have the same values in both, it gives all combinations taking all the rows

Theta Joins
it's less restrictive than natural joins, giving us actually a way to take the tuples that we want.

1. Take the cartesian product
2. Select from the product only those tuples that satisfy the condition C

Combining Operations to Form Queries
Put the result of some operation to another operation.

Renaming attributes
To make it easier in some queries it's useful to change the name of the attributes

Relationships Among Operations

$$R \cap S = R - (R - S)$$

$$R \bowtie_C S = \sigma_C(R \times S)$$

The natural join of R and S can be expressed by starting with the product $R \times S$. We then apply the selection operator with a condition C of the form

$$R.A_1 = S.A_1 \quad \text{AND} \quad R.A_2 = S.A_2 \quad \text{AND} \quad \ldots \quad \text{AND} \quad R.A_n = S.A_n$$

$R \bowtie S = \pi_L(\sigma_C(R \times S))$

Constraints on Relations
restrict the data that may be stored in a database

Relational Algebra as a Constraint Language
- $R = \emptyset$: There are no tuple in the result of R

- $R \subseteq$ Every tuple in R must be also in S

Referential Integrity Constraints
A value appearing in one context also appears in another, related context

$\pi_A(R) \subseteq \pi_B(S)$ (some attribute A and B)

Key Constraints
If an attribute (like name) is a Key, then every name must be unique. This implies that if two rows have the same name, they must be the exact same row (i.e., they must have the same address).

Using the notation above, it's possible to define precisely the constraints for keys.

1. Self-Product
2. Filter for Violations: Use Selection (σ)
3. the result of this search must be the Empty Set ($\emptyset$).

$$\sigma_{\text{MS1.name} = \text{MS2.name} \wedge \text{MS1.address} \neq \text{MS2.address}}(\text{MS1} \times \text{MS2}) = \emptyset$$

Clase 15/04/2026

Aprender sobre:
1. ACID
2. Transacciones

Además, voy a leer el capítulo 4 para ir adelantando

Las bases de datos están en casi todos los sitios web.

El poder viene de DBMS (database managment system)

They are useful for: creating and managing large amounts of data efficiently and allowing it to persist over long periods of time,

The Evolution of Database System s

DBMS expected to:
1. Allow users to create new databases and specify their schemas, using data-definition language
2. Give users the ability to query the data (question about data) and modify data, using data-manipulation language.
3. Support the storage of very large amounts of data over a large period of time
4. Enable durability, recovery of database in face of failure, erros of many kind or intentional misuse

+Control access to data from many users at once, without allowing unex pected interactions among users (isolation) and without actions on the data to be performed partially but not completely (atomicity)

Early Database Management Systems

First commertial DBMS
1. Late 1960´s. Evolved from file systems. Do not guarantee that data cannot be lost if it's not backed up
2. Do not support data-manipulation language.
3. Used in:
   1. Banking systems
   2. Airline reservation systems
   3.

Relational Database Systems

Paper of Codd proposed:

Database systems should present the user with a view of data organized as tables called relations

- Programmers should not be concerned for the way the data is stored

Smaller and Smaller Systems

Apparition of XML
Large collections of small documents can serve as a database, and the methods of querying and manipulating them are different

Bigger and Bigger Systems
Need to store more and more information. Pentabytes of information. Example: google, satelites information, Peer-to-peer file-sharing systems

Information integration
Many distributed information to tell the same thing:

Solution:
1. creation of data warehouses, where information from many legacy databases is copied periodically, with the appropriate translation, to a central database.
2. Middleware: sup⊠port an integrated model of the data of the various databases, while translating between this model and the actual models used by each databas

Overview of a Database Management System
two distinct sources of commands to the DBMS:

1. Conventional users and application programs that ask for data or modify data.
2. A database administrator: a person or persons responsible for the structure or schema of the database.

DDL (Data Definition Language)
schema-altering data-definition language (DDL) commands are parsed by a DDL processor and passed to the execution engine, which then goes through the index/file/record manager to alter the metadata, that is, the schema information for the database

Answering the Query
query parsed and compiled by: ***query compiler***

To perform to answer the query is passed to the ***execution engine*** This ***requests*** small pieces of data ***to: resource manager***. This knows about: data files, format and size of records and index files.

Request passed to: ***buffer manager***. Bring appropriate portions of data where it is kept permanently

Transaction Processing
Queries and DML actions grouped into ***transacitons***:

Units that must be ***executed atomically*** and in ***isolation*** Durable:
1. concurrency-control manager or scheduler: ensures atomicity and isolation.
2. logging and recovery manager, responsible for the durability of transactions.

Storage and Buffer Management
Data in: ***secondary storage***. Usually, it control storage on the disk directly.
1. The storage manager keeps track of the location of files on the disk and obtains the block or blocks containing a file on request from
2. The buffer manager is responsible for partitioning the available main memory into buffers.

Information that may be needed.
1. Data: contents of database itself
2. metadata: database schema. Describes schema
3. Log records: information about recent changes.
4. Statistics: information gathered and stored by DBMS
5. Indexes: data structures to access efficiently to the memory.

Transaction Processing

transaction manager therefore accepts transaction commands from an application. Tells when transactions begin and end

Transaction processor steps:

1. Logging: assure durability: writes the log in buffers and negotiates with the buffer manager to make sure that buffers are written to disk
2. Concurrency control: the scheduler (concurrency-control manager) must assure that the individual actions of multiple transactions are executed in such an order that the net effect is the same as if the transactions had in fact executed in their entirety, one-at-a-time
3. Deadlock resolution:The transaction manager has the responsibility to intervene and cancel ("roll back" or "abort") one or more transactions to let the others proceed.

ACID:

1. Atomicity: all-or-nothing execution of transaction
2. Consistency: consistency constraints, or expectations about relationships among data elements
3. isolation: each transaction must appear to be executed as if no other transaction is executing at the same time
4. Durability: the effect on the database of a transaction must never be lost, once the transaction has completed

The Query Processor

1. The query compiler: translates the query into an internal form called a query plan.
    1. Query parser: tree structure from the textual form of the query.
    2. Query preprocessor: semantic checks on the query and performing some tree transformations
    3. Query optimizer: transforms the initial query plan into the best available sequence of operations on the actual data.
2. Execution engine: executing each of the steps in the chosen query plan

End of Chapter 1

Concurrency Control (Chapter 18)

Must preserve consitency. Timing of individual steps must be regulated: ***scheduler***. Process of assuring transacitons preserve consistency when executed simultaneously: ***concurrency-control***



In most cases, the scheduler will execute write and reads directly. But, some situations: delay request or even abort the request.

To assure transactions preserve correctness of the database state: ***serializability*** and stronger: ***conflict-serializability*** .

locking, timestamping, and validation

Serial and Serializable Schedules

"correctness principle": every transaction, if executed in isolation (without any other transactions running concurrently), will transform any consistent state to another consistent state

Schedules

It's is a sequence of the important actions taken by one or more transactions. Place: main memory, not disk.

Database element read by multiple queris

T_1	T_2
READ(A,t)	READ(A,s)
t := t+100	s := s*2
WRITE(A,t)	WRITE(A,s)
READ(B,t)	READ(B,s)
t := t+100	s := s*2
WRITE(B,t)	WRITE(B,s)

Clase 22/04/2026

Buscar para la próxima clase
1. Transaction manager
2. Scheduler
3. Data manager
   1. Recovery manager
   2. Cache manager

Cap. 17, 18

Issues to address:
1. Data must be protected in the face of a system failure
2. Data must not be corrupted simply because several error-free queries or database modifications are being done at once.

Technique for resilience:
1. log
   1. Records securely history of database changes
   2. Undo/redo actions

Things that could go wrong

Failure modes

Erroneous data entry
Write constraints and triggers that detect data beliveed to be erroneous

Media fialures
Local failure of disk (only some bits). Detected by parity checks

Head crashes, all disk unreadable
1. RAID shcemes. Lost disk may be restored
2. Mantian an archive. Copy of database, distributed among several sites

Catastrophic failure
Media holding database completely destroyed
1. explossions

Solutions: archiving and redundant

System failure
System failures are problems that cause the state of a transaction to be lost

typical erros:
1. Power loss
2. Software erros

Solution. logs all database changes in separte nonvolatile log and redundancy of that info.

more about transactions
The transaction is the unit of execution of database operations.

Begins with: as soon opreatins on database are executed and end with “COMMIT” or “ROLLBACK”

Must:
1. atomically: all or nothing

Transaction manager job. transactions are executed correctly.
1. issuing signas to log manager. necessay information in the form of “log records” can be stored on the log.

Assuring that concurrently executing transactiosn do not interfere with each other in ways that introduce errors

he log manager maintains the log. It must deal with the buffer manager, since space for the log initially appears in main-memory buffers, and at certain times these buffers must be copied to disk

Correct Execution of Transactions
Database compose of “elements”: value that can be accessed or modified by transactions

Usually are one or more of:
1. Relations
2. Disk blocks or pages
3. Individuals tuples or objects

Database State: value for each of its elements.

The **Correctness Principle**: If a transaction executes in the absence of any other transactions or system errors, and it starts with the database in a consistent state, then the database is also in a consistent state when the transaction ends.

1. Transaction atomic
2. Execute simultaneously precaution

Operations of transactions
There address spaces that interact in important way
1. Space of disk blocks holding database elements
2. Virutal or main memory managed by buffer manager
3. Local address space of transaction

Read database element:
1. Brought to main memory buffer/s. Content of buffer can be read by transaction into its own address space

Writing:
1. Created the new value in its own space.
2. Value copied to appropiate buffer

Buffer may or not be copied to disk immediately. That’s responsability of buffer manager.

Primitives:
1. INPUT(X): copy disk block containing database element X to memory buffer
2. READ(x,t) copy database element X to transaction local variable t.
3. WRITE(X, t): copy value of local variable t to database element X in memory buffer
4. OUTPUT(X): copy block containingX from its buffer to disk

constraints
1. Databse element no larger than single block.
2. READ and WRITE issued by transactions

3. OUTPUT and INPUT issued by buffer manager

Undo logging

log is a file of log records, each telling something about what some transaction has done

Undoing the effects of transactions that may not have completed before the crash

Log Records

Log as file opened for appending only.

log manager job of recording in the log each important event.

Logs:

1. <START >: transaction T has begun.
2. <COMMIT>: Transaction T has completed successfully and will make no

more changes to database elements. All changes should appear on disk, but we cannot be sure when we sure it that it's already there.

1. <ABORT>: Transaciton T could not complete successfully
2. <T, X, v>: transaction T has changed database element X and its former value was v.

Undo-Logging Rules

1. If transaction T modifies database element X , then the log record of the form < T ,X ,v> must be written to disk before the new value of X is written to disk.
2. If a transaction commits, then its COMMIT log record must be written to

disk only after all database elements changed by the transaction have been written to disk, but as soon thereafter as possible

And summarizing the rules before: transactions materal must be written to disk in following order:

- The log records indicating changed database elements. (each element individdually)
- The changed database elements themselves. (each element individdually)
- The COMMIT log record.

The essential pol⊠icy for undo logging is that we don't write the <COMMIT T> record until the OUTPUT actions for T are completed.

If there's start and not commit log. Transaction must be undone. We don't know when or what was stored.