

Contents

1 Basic	1
1.1 <code>/.vimrc</code>	1
1.2 default code	1
1.3 debug list	1
2 Geometry	1
2.1 2D Point Template	1
2.2 外心 Circumcentre	1
2.3 Convex Hull	1
2.4 半平面交	1
2.5 圓交	2
2.6 線段交	2
2.7 Smallest Covering Circle	2
3 Mathematics	2
3.1 $ax+by=gcd(a,b)$	2
3.2 BigInt	2
3.3 FFT	3
3.4 FWHT	4
3.5 GaussElimination	4
3.6 Inverse	4
3.7 LinearPrime	4
3.8 Pollard's rho	4
3.9 數論基本工具	4
3.10 Mobius	5
3.11 Simplex	5
3.12 SG	6
3.13 Theorem	6
4 Graph	6
4.1 BCC	6
4.2 Dijkstra	7
4.3 Theorem - Domination	7
4.4 Strongly Connected Component (SCC)	7
4.5 Dominator Tree	7
4.6 Manhattan MST	8
4.7 Hungarian	9
4.8 KM	9
4.9 Theorem - Matching	10
4.10 Maximum General Matching	10
4.11 Minimum General Weighted Matching	10
4.12 Maximum Clique	11
4.13 Steiner Tree	11
4.14 最小平均環	11
4.15 Schreier Sims	12
4.16 Tarjan	12
4.17 2-SAT	13
5 Data Structure	13
5.1 Sparse Table	13
5.2 Segment Tree	13
6 String	14
6.1 KMP	14
7 Dark Code	14
7.1 輸入優化	14
7.2 PBDS	14
8 Search	14
8.1 LIS	14
8.2 Merge sort	15
9 Others	15
9.1 數位統計	15
9.2 1D/1D dp 優化	15
9.3 Theorem - DP optimization	15
9.4 Mo's algorithm	16
10 Persistence	16

1 Basic

1.1 `/.vimrc`

```
set nu ai si cin ts=4 sw=4 sts=4 expandtab

nmap #2 :! gedit %<.in %<*.in &<CR>
nmap #4 :! date > %<.pt; cat -n % > %<.pt; lpr %<.pt <
CR>
nmap #9 :! clear ; g++ -std=c++11 -O2 -D AC -o %<.out %
; for i in %<*.in; do echo $i; ./%<.out < $i; echo
""; done <CR>
```

```
nmap #0 :! clear ; g++ -std=c++11 -O2 -D AC -o %<.out %
; ./%<.out <CR>
nmap <C-I> :! read -p "CASE:" CASE; gedit %<_CASE.in <
CR>
```

1.2 default code

```
#include <bits/stdc++.h>
using namespace std;

int main(){
#ifdef AC
    freopen("", "r", stdin);
#endif
    ios_base::sync_with_stdio(0);
    cin.tie(false);
}
```

1.3 debug list

模板要記得 init
priority_queue 要清空
把邊界條件都加入測資
邊界條件 (過程溢位, 題目數據範圍), 會不會爆 long long
是否讀錯題目, 想不到時可以自己讀一次題目
環狀 or 凸包問題一定要每種都算 n 次
比較容易有問題的地方換人寫
注意公式有沒有推錯或抄錯
精度誤差 $\sqrt{\text{大的東西}} + \text{EPS}$
測試 %lld or %I64d
喇分 random_shuffle 隨機演算法
用 long long int 記得要算 MLE

2 Geometry

2.1 2D Point Template

```
typedef double Double;
struct Point {
    Double x, y;

    bool operator < (const Point &b) const {
        //return tie(x, y) < tie(b.x, b.y);
        //return atan2(y, x) < atan2(b.y, b.x);
        assert(0 && "choose compare");
    }
    Point operator + (const Point &b) const {
        return (Point){x+b.x, y+b.y};
    }
    Point operator - (const Point &b) const {
        return (Point){x-b.x, y-b.y};
    }
    Point operator * (const Double &d) const {
        return Point(d*x, d*y);
    }
    Double operator * (const Point &b) const {
        return x*b.x + y*b.y;
    }
    Double operator % (const Point &b) const {
        return x*b.y - y*b.x;
    }
    friend Double abs2(const Point &p) {
        return p.x*p.x + p.y*p.y;
    }
    friend Double abs(const Point &p) {
        return sqrt(abs2(p));
    }
};
typedef Point Vector;
```

```
struct Line{
    Point P; Vector v;
    bool operator < (const Line &b)const{
        return atan2(v.y,v.x) < atan2(b.v.y,b.v.x);
    }
};
```

2.2 外心 Circumcentre

```
#include "2Dpoint.cpp"

Point circumcentre(Point &p0, Point &p1, Point &p2){
    Point a = p1-p0;
    Point b = p2-p0;
    Double c1 = abs2(a)*0.5;
    Double c2 = abs2(b)*0.5;
    Double d = a % b;
    Double x = p0.x + ( c1*b.y - c2*a.y ) / d;
    Double y = p0.y + ( c2*a.x - c1*b.x ) / d;
    return {x,y};
}
```

2.3 Convex Hull

```
#include "2Dpoint.cpp"

// return H, 第一個點會在 H 出現兩次
void ConvexHull(vector<Point> &P, vector<Point> &H){
    int n = P.size(), m=0;
    sort(P.begin(),P.end());
    H.clear();

    for (int i=0; i<n; i++){
        while (m>=2 && (P[i]-H[m-2]) % (H[m-1]-H[m-2])
            <0)H.pop_back(), m--;
        H.push_back(P[i]), m++;
    }

    for (int i=n-2; i>=0; i--){
        while (m>=2 && (P[i]-H[m-2]) % (H[m-1]-H[m-2])
            <0)H.pop_back(), m--;
        H.push_back(P[i]), m++;
    }
}
```

2.4 半平面交

```
bool OnLeft(const Line& L,const Point& p){
    return Cross(L.v,p-L.P)>0;
}

Point GetIntersection(Line a,Line b){
    Vector u = a.P-b.P;
    Double t = Cross(b.v,u)/Cross(a.v,b.v);
    return a.P + a.v*t;
}

int HalfplaneIntersection(Line* L,int n,Point* poly){
    sort(L,L+n);

    int first,last;
    Point *p = new Point[n];
    Line *q = new Line[n];
    q[first=last=0] = L[0];
    for(int i=1;i<n;i++){
        while(first < last && !OnLeft(L[i],p[last-1])) last
            --;
        while(first < last && !OnLeft(L[i],p[first])) first
            ++;
        q[++last]=L[i];
        if(fabs(Cross(q[last].v,q[last-1].v))<EPS){
            last--;
        }
    }
}
```

```
if(OnLeft(q[last],L[i].P)) q[last]=L[i];
}
if(first < last) p[last-1]=GetIntersection(q[last-1],q[last]);
}
while(first<last && !OnLeft(q[first],p[last-1])) last
    --;
if(last-first<=1) return 0;
p[last]=GetIntersection(q[last],q[first]);

int m=0;
for(int i=first;i<=last;i++) poly[m++]=p[i];
return m;
}
```

2.5 圓交

```
vector<Double> interCircle(Double o1, Double r1, Double
    o2, Double r2) {
    Double d2 = abs2(o1 - o2);
    Double d = sqrt(d2);
    if (d < fabs(r1-r2) || r1+r2 < d) return {};
    Double u = 0.5*(o1+o2) + ((r2*r2-r1*r1)/(2.0*d2))*(o1
        -o2);
    Double A = sqrt((r1+r2+d) * (r1-r2+d) * (r1+r2-d) *
        (-r1+r2+d));
    Double v = A / (2.0*d2) * Double(o1.S-o2.S, -o1.F+o2.
        F);
    return {u+v, u-v};
}
```

2.6 線段交

```
Point interPnt(Point p1, Point p2, Point q1, Point q2,
    bool &res){
    Double f1 = cross(p2, q1, p1);
    Double f2 = -cross(p2, q2, p1);
    Double f = (f1 + f2);

    if(fabs(f) < EPS) {
        res = false;
        return {};
    }

    res = true;
    return (f2 / f) * q1 + (f1 / f) * q2;
}
```

2.7 Smallest Covering Circle

```
#include "circumcentre.cpp"
pair<Point,Double> SmallestCircle(int n, Point _p[]){
    Point *p = new Point[n];
    memcpy(p,_p,sizeof(Point)*n);
    random_shuffle(p,p+n);

    Double r2=0;
    Point cen;
    for (int i=0; i<n; i++){
        if ( abs2(cen-p[i]) <= r2)continue;
        cen = p[i], r2=0;
        for (int j=0; j<i; j++){
            if ( abs2(cen-p[j]) <= r2)continue;
            cen = (p[i]+p[j])*0.5;
            r2 = abs2(cen-p[i]);
            for (int k=0; k<j; k++){
                if ( abs2(cen-p[k]) <= r2)continue;
                cen = circumcentre(p[i],p[j],p[k]);
                r2 = abs2(cen-p[k]);
            }
        }
    }
}
```

```

}

delete[] p;
return {cen,r2};
}
// auto res = SmallestCircle(,);

```

3 Mathematics

3.1 $ax+by=\gcd(a,b)$

```

typedef pair<int, int> pii;
pii extgcd(int a, int b){
    if(b == 0) return make_pair(1, 0);
    else{
        int p = a / b;
        pii q = extgcd(b, a % b);
        return make_pair(q.second, q.first - q.second * p);
    }
}

```

3.2 BigInt

```

struct BigInt{
    static const int LEN = 60;
    static const int BIGMOD = 10000;
    int s;
    int vl, v[LEN];
    // vector<int> v;
    BigInt() : s(1) { vl = 0; }
    BigInt(long long a) {
        s = 1; vl = 0;
        if (a < 0) { s = -1; a = -a; }
        while (a) {
            push_back(a % BIGMOD);
            a /= BIGMOD;
        }
    }
    BigInt(string str) {
        s = 1; vl = 0;
        int stPos = 0, num = 0;
        if (!str.empty() && str[0] == '-') {
            stPos = 1;
            s = -1;
        }
        for (int i=SZ(str)-1, q=1; i>=stPos; i--) {
            num += (str[i] - '0') * q;
            if ((q *= 10) >= BIGMOD) {
                push_back(num);
                num = 0; q = 1;
            }
        }
        if (num) push_back(num);
    }
    int len() const { return vl; /* return SZ(v); */ }
    bool empty() const { return len() == 0; }
    void push_back(int x) { v[vl++] = x; /* v.PB(x); */ }
    void pop_back() { vl--; /* v.pop_back(); */ }
    int back() const { return v[vl-1]; /* return v.back()
        ; */ }
    void n() { while (!empty() && !back()) pop_back(); }
    void resize(int nl) {
        vl = nl; fill(v, v+vl, 0);
        // v.resize(nl); // fill(ALL(v), 0);
    }
    void print() const {
        if (empty()) { putchar('0'); return; }
        if (s == -1) putchar('-');
        printf("%d", back());
        for (int i=len()-2; i>=0; i--) printf("%.4d",v[i]);
    }
}

```

```

friend std::ostream& operator << (std::ostream& out,
    const BigInt &a) {
    if (a.empty()) { out << "0"; return out; }
    if (a.s == -1) out << "-";
    out << a.back();
    for (int i=a.len()-2; i>=0; i--) {
        char str[10];
        snprintf(str, 5, "%.4d", a.v[i]);
        out << str;
    }
    return out;
}

int cp3(const BigInt &b) const {
    if (s != b.s) return s > b.s ? 1 : -1;
    if (s == -1) return -(*this).cp3(-b);
    if (len() != b.len()) return len()>b.len()?1:-1;
    for (int i=len()-1; i>=0; i--)
        if (v[i]!=b.v[i]) return v[i]>b.v[i]?1:-1;
    return 0;
}

bool operator < (const BigInt &b) const { return cp3(b)
    ==-1; }
bool operator <= (const BigInt &b) const { return cp3(b)
    >=0; }
bool operator >= (const BigInt &b) const { return cp3(b)
    >=0; }
bool operator == (const BigInt &b) const { return cp3(b)
    ==0; }
bool operator != (const BigInt &b) const { return cp3(b)
    !=0; }
bool operator > (const BigInt &b) const { return cp3(b)
    ==1; }

BigInt operator - () const {
    BigInt r = (*this);
    r.s = -r.s;
    return r;
}

BigInt operator + (const BigInt &b) const {
    if (s == -1) return -(*this)+(-b);
    if (b.s == -1) return (*this)-(-b);
    BigInt r;
    int nl = max(len(), b.len());
    r.resize(nl + 1);
    for (int i=0; i<nl; i++) {
        if (i < len()) r.v[i] += v[i];
        if (i < b.len()) r.v[i] += b.v[i];
        if (r.v[i] >= BIGMOD) {
            r.v[i+1] += r.v[i] / BIGMOD;
            r.v[i] %= BIGMOD;
        }
    }
    r.n();
    return r;
}

BigInt operator - (const BigInt &b) const {
    if (s == -1) return -(*this)-(-b);
    if (b.s == -1) return (*this)+(-b);
    if ((*this) < b) return -(b-(*this));
    BigInt r;
    r.resize(len());
    for (int i=0; i<len(); i++) {
        r.v[i] += v[i];
        if (i < b.len()) r.v[i] -= b.v[i];
        if (r.v[i] < 0) {
            r.v[i] += BIGMOD;
            r.v[i+1]--;
        }
    }
    r.n();
    return r;
}

BigInt operator * (const BigInt &b) {
    BigInt r;
    r.resize(len() + b.len() + 1);
    r.s = s * b.s;
    for (int i=0; i<len(); i++) {
        for (int j=0; j<b.len(); j++) {

```

```

        r.v[i+j] += v[i] * b.v[j];
        if(r.v[i+j] >= BIGMOD) {
            r.v[i+j+1] += r.v[i+j] / BIGMOD;
            r.v[i+j] %= BIGMOD;
        }
    }
}
r.n();
return r;
}
Bigint operator / (const Bigint &b) {
    Bigint r;
    r.resize(max(1, len()-b.len()+1));
    int oriS = s;
    Bigint b2 = b; // b2 = abs(b)
    s = b2.s = r.s = 1;
    for (int i=r.len()-1; i>=0; i--) {
        int d=0, u=BIGMOD-1;
        while(d<u) {
            int m = (d+u+1)>>1;
            r.v[i] = m;
            if((r*b2) > (*this)) u = m-1;
            else d = m;
        }
        r.v[i] = d;
    }
    s = oriS;
    r.s = s * b.s;
    r.n();
    return r;
}
Bigint operator % (const Bigint &b) {
    return (*this)-(*this)/b*b;
}
};

```

3.3 FFT

```

const double pi = atan(1.0)*4;
struct Complex {
    double x,y;
    Complex(double _x=0,double _y=0)
        :x(_x),y(_y) {}
    Complex operator + (Complex &tt) { return Complex(x
        +tt.x,y+tt.y); }
    Complex operator - (Complex &tt) { return Complex(x
        -tt.x,y-tt.y); }
    Complex operator * (Complex &tt) { return Complex(x
        *tt.x-y*tt.y,x*tt.y+y*tt.x); }
};
void fft(Complex *a, int n, int rev) {
    // n是大于等于相乘的两个数组长度的2的幂次
    // 从0开始表示长度，对a进行操作
    // rev==1进行DFT，== -1进行IDFT
    for (int i = 1, j = 0; i < n; ++ i) {
        for (int k = n>>1; k > (j^=k); k >>= 1);
        if (i<j) std::swap(a[i],a[j]);
    }
    for (int m = 2; m <= n; m <= 1) {
        Complex wm(cos(2*pi*rev/m),sin(2*pi*rev/m));
        for (int i = 0; i < n; i += m) {
            Complex w(1.0,0.0);
            for (int j = i; j < i+m/2; ++ j) {
                Complex t = w*a[j+m/2];
                a[j+m/2] = a[j] - t;
                a[j] = a[j] + t;
                w = w * wm;
            }
        }
    }
    if (rev== -1) {
        for (int i = 0; i < n; ++ i) a[i].x /= n,a[i].y
            /= n;
    }
}

```

3.4 FWHT

```

// FWHT template

const int MAXN = 1<<20;

void FWHT(int a[], int l=0, int r=MAXN-1){
    if (l==r)return;

    int mid = (l+r)>>1+1, n = r-l+1;
    FWHT(a,l,mid-1);
    FWHT(a,mid,r);

    for (int i=0; i<(n>>1); i++){
        int a1=a[l+i], a2=a[mid+i];
        a[l+i] = a1+a2;
        a[mid+i] = a1-a2;
    }
}

```

3.5 GaussElimination

```

// by bcw_codebook

const int MAXN = 300;
const double EPS = 1e-8;

int n;
double A[MAXN][MAXN];

void Gauss() {
    for(int i = 0; i < n; i++) {
        bool ok = 0;
        for(int j = i; j < n; j++) {
            if(fabs(A[j][i]) > EPS) {
                swap(A[j], A[i]);
                ok = 1;
                break;
            }
        }
        if(!ok) continue;

        double fs = A[i][i];
        for(int j = i+1; j < n; j++) {
            double r = A[j][i] / fs;
            for(int k = i; k < n; k++) {
                A[j][k] -= A[i][k] * r;
            }
        }
    }
}

```

3.6 Inverse

```

int inverse[100000];
void invTable(int b, int p) {
    inverse[1] = 1;
    for( int i = 2; i <= b; i++ ) {
        inverse[i] = (long long)inverse[p%i] * (p-p/i) % p;
    }
}

int inv(int b, int p) {
    return b == 1 ? 1 : ((long long)inv(p % b, p) * (p-p/
        b) % p);
}

```

3.7 LinearPrime

```

const int MAXP = 100; //max prime
vector<int> P; // primes
void build_prime(){
    static bitset<MAXP> ok;
    int np=0;
    for (int i=2; i<MAXP; i++){
        if (ok[i]==0)P.push_back(i), np++;
        for (int j=0; j<np && i*P[j]<MAXP; j++){
            ok[ i*P[j] ] = 1;
            if ( i%P[j]==0 )break;
        }
    }
}

```

3.8 Pollard' s rho

```

// from PEC
// does not work when n is prime
Int f(Int x, Int mod){
    return add(mul(x, x, mod), 1, mod);
}
Int pollard_rho(Int n) {
    if ( !(n & 1) ) return 2;
    while (true) {
        Int y = 2, x = rand()%(n-1) + 1, res = 1;
        for ( int sz = 2 ; res == 1 ; sz *= 2 ) {
            for ( int i = 0 ; i < sz && res <= 1 ; i++) {
                x = f(x, n);
                res = __gcd(abs(x-y), n);
            }
            y = x;
        }
        if ( res != 0 && res != n ) return res;
    }
}

```

3.9 數論基本工具

```

Int POW(Int a, Int n, Int mod){
    Int re=1;
    while (n>0){
        if (n&1LL) re = re*a%mod;
        a = a*a%mod;
        n>>=1;
    }
    return re;
}

Int C(Int n, Int m){
    if (m<0 || m>n)return 0;
    return J[n] * inv(J[m]*J[n-m]%MOD) %MOD;
}

```

3.10 Mobius

```

void mobius() {
    fill(isPrime, isPrime + MAXN, 1);
    mu[1] = 1, num = 0;
    for (int i = 2; i < MAXN; ++i) {
        if (isPrime[i]) primes[num++] = i, mu[i] = -1;
        static int d;
        for (int j = 0; j < num && (d = i * primes[j])
            < MAXN; ++j) {
            isPrime[d] = false;
            if (i % primes[j] == 0) {
                mu[d] = 0; break;
            } else mu[d] = -mu[i];
        }
    }
}

```

3.11 Simplex

```

// Two-phase simplex algorithm for solving linear
// programs of the form
//
//      maximize      c^T x
//      subject to    Ax <= b
//                   x >= 0
//
// INPUT: A -- an m x n matrix
//        b -- an m-dimensional vector
//        c -- an n-dimensional vector
//        x -- a vector where the optimal solution will
//              be stored
//
// OUTPUT: value of the optimal solution (infinity if
//         unbounded
//         above, nan if infeasible)
//
// To use this code, create an LPSolver object with A,
// b, and c as
// arguments. Then, call Solve(x).

#include <iostream>
#include <iomanip>
#include <vector>
#include <cmath>
#include <limits>

using namespace std;

typedef long double DOUBLE;
typedef vector<DOUBLE> VD;
typedef vector<VD> VVD;
typedef vector<int> VI;

const DOUBLE EPS = 1e-9;

struct LPSolver {
    int m, n;
    VI B, N;
    VVD D;

    LPSolver(const VVD &A, const VD &b, const VD &c) :
        m(b.size()), n(c.size()), N(n + 1), B(m), D(m + 2,
            VD(n + 2)) {
        for (int i = 0; i < m; i++) for (int j = 0; j < n;
            j++) D[i][j] = A[i][j];
        for (int i = 0; i < m; i++) { B[i] = n + i; D[i][n]
            = -1; D[i][n + 1] = b[i]; }
        for (int j = 0; j < n; j++) { N[j] = j; D[m][j] = -
            c[j]; }
        N[n] = -1; D[m + 1][n] = 1;
    }

    void Pivot(int r, int s) {
        double inv = 1.0 / D[r][s];
        for (int i = 0; i < m + 2; i++) if (i != r)
            for (int j = 0; j < n + 2; j++) if (j != s)
                D[i][j] -= D[r][j] * D[i][s] * inv;
        for (int j = 0; j < n + 2; j++) if (j != s) D[r][j]
            *= inv;
        for (int i = 0; i < m + 2; i++) if (i != r) D[i][s]
            *= -inv;
        D[r][s] = inv;
        swap(B[r], N[s]);
    }

    bool Simplex(int phase) {
        int x = phase == 1 ? m + 1 : m;
        while (true) {
            int s = -1;
            for (int j = 0; j <= n; j++) {
                if (phase == 2 && N[j] == -1) continue;
                if (s == -1 || D[x][j] < D[x][s] || D[x][j] ==
                    D[x][s] && N[j] < N[s]) s = j;
            }

```

```

    }
    if (D[x][s] > -EPS) return true;
    int r = -1;
    for (int i = 0; i < m; i++) {
        if (D[i][s] < EPS) continue;
        if (r == -1 || D[i][n + 1] / D[i][s] < D[r][n + 1] / D[r][s] ||
            (D[i][n + 1] / D[i][s]) == (D[r][n + 1] / D[r][s]) && B[i] < B[r]) r = i;
    }
    if (r == -1) return false;
    Pivot(r, s);
}

DOUBLE Solve(VD &x) {
    int r = 0;
    for (int i = 1; i < m; i++) if (D[i][n + 1] < D[r][n + 1]) r = i;
    if (D[r][n + 1] < -EPS) {
        Pivot(r, n);
        if (!Simplex(1) || D[m + 1][n + 1] < -EPS) return
            -numeric_limits<DOUBLE>::infinity();
        for (int i = 0; i < m; i++) if (B[i] == -1) {
            int s = -1;
            for (int j = 0; j <= n; j++)
                if (s == -1 || D[i][j] < D[i][s] || D[i][j] == D[i][s] && N[j] < N[s]) s = j;
            Pivot(i, s);
        }
    }
    if (!Simplex(2)) return numeric_limits<DOUBLE>::infinity();
    x = VD(n);
    for (int i = 0; i < m; i++) if (B[i] < n) x[B[i]] = D[i][n + 1];
    return D[m][n + 1];
}

int main() {
    const int m = 4;
    const int n = 3;
    DOUBLE _A[m][n] = {
        { 6, -1, 0 },
        { -1, -5, 0 },
        { 1, 5, 1 },
        { -1, -5, -1 }
    };
    DOUBLE _b[m] = { 10, -4, 5, -5 };
    DOUBLE _c[n] = { 1, -1, 0 };

    VVD A(m);
    VD b(_b, _b + m);
    VD c(_c, _c + n);
    for (int i = 0; i < m; i++) A[i] = VD(_A[i], _A[i] + n);

    LPSolver solver(A, b, c);
    VD x;
    DOUBLE value = solver.Solve(x);

    cerr << "VALUE: " << value << endl; // VALUE: 1.29032
    cerr << "SOLUTION:"; // SOLUTION: 1.74194 0.451613 1
    for (size_t i = 0; i < x.size(); i++) cerr << " " << x[i];
    cerr << endl;
    return 0;
}

```

3.12 SG

Anti Nim (取走最後一個石子者敗)

先手必勝 if and only if

1. 「所有」堆的石子數都為 1 且遊戲的 SG 值為 0。
2. 「有些」堆的石子數大於 1 且遊戲的 SG 值不為 0。

Anti-SG (決策集合為空的遊戲者贏)

定義 SG 值為 0 時，遊戲結束，

則先手必勝 if and only if

1. 遊戲中沒有單一遊戲的 SG 函數大於 1 且遊戲的 SG 函數為 0。
2. 遊戲中某個單一遊戲的 SG 函數大於 1 且遊戲的 SG 函數不為 0。

Sprague-Grundy

1. 雙人、回合制
2. 資訊完全公開
3. 無隨機因素
4. 可在有限步內結束
5. 沒有和局
6. 雙方可採取的行動相同

SG(S) 的值為 0：後手(P)必勝

不為 0：先手(N)必勝

```

int mex(set S){
    // find the min number >= 0 that not in the S
    // e.g. S = {0, 1, 3, 4} mex(S) = 2
}

```

```

state = []
int SG(A) {
    if (A not in state) {
        S = sub_states(A)
        if( len(S) > 1 ) state[A] = reduce(operator.xor, [
            SG(B) for B in S])
        else state[A] = mex(set(SG(B) for B in next_states(
            A)))
    }
    return state[A]
}

```

3.13 Theorem

```

/*
Lucas's Theorem
For non-negative integer n,m and prime P,
C(m,n) mod P = C(m/M,n/M) * C(m%M,n%M) mod P
= mult_i ( C(m_i,n_i) )
where m_i is the i-th digit of m in base P.

```

Pick's Theorem
 $A = i + b/2 - 1$

Kirchhoff's theorem
 $A_{\{ii\}} = \deg(i), A_{\{ij\}} = (i,j) \setminus \text{in } E ? -1 : 0$
Deleting any one row, one column, and cal the det(A)

Nth Catalan recursive function:
 $C_0 = 1, C_{n+1} = C_n * 2(2n + 1)/(n+2)$

Mobius Formula
 $u(n) = 1$, if $n = 1$
 $(-1)^m$, 若 n 無平方數因數，且 $n = p_1 * p_2 * p_3 * \dots * p_k$
 0 , 若 n 有大於 1 的平方數因數

- Property

1. (積性函數) $u(a)u(b) = u(ab)$
2. $\sum_{d|n} u(d) = [n == 1]$

Mobius Inversion Formula

```

if      f(n) =  $\sum_{d|n} g(d)$ 
then    g(n) =  $\sum_{d|n} u(n/d)f(d)$ 
         =  $\sum_{d|n} u(d)f(n/d)$ 
- Application
the number/power of gcd(i, j) = k
- Trick
分塊,  $O(\sqrt{n})$ 

```

Chinese Remainder Theorem (m_i 兩兩互質)

```

x = a_1 (mod m_1)
x = a_2 (mod m_2)
....
x = a_i (mod m_i)

```

construct a solution:

```

Let M = m_1 * m_2 * m_3 * ... * m_n
Let M_i = M / m_i

```

```

t_i = 1 / M_i
t_i * M_i = 1 (mod m_i)

```

```

solution x = a_1 * t_1 * M_1 + a_2 * t_2 * M_2 + ...
            + a_n * t_n * M_n + k * M
= k*M +  $\sum a_i * t_i * M_i$ , k is positive integer.

```

```

under mod M, there is one solution  $x = \sum a_i * t_i * M_i$ 

```

Burnside's lemma

$|G| * |X/G| = \sum (|X^g|)$ where g in G

總方法數：每一種旋轉下不動點的個數總和 除以 旋轉的方法數

*/

4 Graph

4.1 BCC

邊雙連通

任意兩點間至少有兩條不重疊的路徑連接，找法：

1. 標記出所有的橋
2. 對全圖進行 DFS，不走橋，每一次 DFS 就是一個新的邊雙連通

// from BCW

```

struct BccEdge {
    static const int MXN = 100005;
    struct Edge { int v, eid; };
    int n, m, step, par[MXN], dfn[MXN], low[MXN];
    vector<Edge> E[MXN];
    DisjointSet djs;
    void init(int _n) {
        n = _n; m = 0;
        for (int i=0; i<n; i++) E[i].clear();
        djs.init(n);
    }
    void add_edge(int u, int v) {
        E[u].PB({v, m});
        E[v].PB({u, m});
        m++;
    }
    void DFS(int u, int f, int f_eid) {
        par[u] = f;
        dfn[u] = low[u] = step++;
        for (auto it:E[u]) {
            if (it.eid == f_eid) continue;
            int v = it.v;
            if (dfn[v] == -1) {
                DFS(v, u, it.eid);

```

```

                low[u] = min(low[u], low[v]);
            } else {
                low[u] = min(low[u], dfn[v]);
            }
        }
    }
    void solve() {
        step = 0;
        memset(dfn, -1, sizeof(int)*n);
        for (int i=0; i<n; i++) {
            if (dfn[i] == -1) DFS(i, i, -1);
        }
        djs.init(n);
        for (int i=0; i<n; i++) {
            if (low[i] < dfn[i]) djs.uni(i, par[i]);
        }
    }
}graph;

```

4.2 Dijkstra

```

typedef struct Edge{
    int v; long long len;
    bool operator > (const Edge &b)const { return len>b
        .len; }
} State;

const long long INF = 1LL<<60;

void Dijkstra(int n, vector<Edge> G[], long long d[],
    int s, int t=-1){
    static priority_queue<State, vector<State>, greater
        <State> > pq;
    while ( pq.size() )pq.pop();
    for (int i=1; i<=n; i++)d[i]=INF;
    d[s]=0; pq.push( (State){s,d[s]} );
    while ( pq.size() ){
        auto x = pq.top(); pq.pop();
        int u = x.v;
        if (d[u]<x.len)continue;
        if (u==t)return;
        for (auto &e:G[u]){
            if (d[e.v] > d[u]+e.len){
                d[e.v] = d[u]+e.len;
                pq.push( (State) {e.v,d[e.v]} );
            }
        }
    }
}

```

4.3 Theorm - Domination

Maximum Independent Set

General: [NPC] maximum clique of complement of G

Tree: [P] Greedy

Bipartite Graph: [P] Maximum Cardinality Bipartite Matching

Minimum Dominating Set

General: [NPC]

Tree: [P] DP

Bipartite Graph: [NPC]

Minimum Vertex Cover

General: [NPC] (?)maximum clique of complement of G

Tree: [P] Greedy, from leaf to root

Bipartite Graph: [P] Maximum Cardinality Bipartite Matching

Minimum Edge Cover

General: [P] V - Maximum Matching

Bipartite Graph: [P] Greedy, strategy: cover small degree node first.

(Min/Max)Weighted: [P]: Minimum/Minimum Weight Matching

4.4 Strongly Connected Component(SCC)

4.5 DominatorTree

```
// PEC VER

// idom[n] is the unique node that strictly dominates n
// but does
// not strictly dominate any other node that strictly
// dominates n.
// idom[n] = 0 if n is entry or the entry cannot reach
// n.
struct DominatorTree{
    static const int MAXN = 200010;
    int n,s;
    vector<int> g[MAXN],pred[MAXN];
    vector<int> cov[MAXN];
    int dfn[MAXN],nfd[MAXN],ts;
    int par[MAXN];
    int sdom[MAXN],idom[MAXN];
    int mom[MAXN],mn[MAXN];

    inline bool cmp(int u,int v) { return dfn[u] < dfn[v]
        ]; }

    int eval(int u) {
        if(mom[u] == u) return u;
        int res = eval(mom[u]);
        if(cmp(sdom[mn[mom[u]]],sdom[mn[u]]))
            mn[u] = mn[mom[u]];
        return mom[u] = res;
    }

    void init(int _n, int _s) {
        n = _n;
        s = _s;
        REP1(i,1,n) {
            g[i].clear();
            pred[i].clear();
            idom[i] = 0;
        }
    }

    void add_edge(int u, int v) {
        g[u].push_back(v);
        pred[v].push_back(u);
    }

    void DFS(int u) {
        ts++;
        dfn[u] = ts;
        nfd[ts] = u;
        for(int v:g[u]) if(dfn[v] == 0) {
            par[v] = u;
            DFS(v);
        }
    }

    void build() {
        ts = 0;
        REP1(i,1,n) {
            dfn[i] = nfd[i] = 0;
            cov[i].clear();
            mom[i] = mn[i] = sdom[i] = i;
        }
        DFS(s);
        for (int i=ts; i>=2; i--) {
            int u = nfd[i];
            if(u == 0) continue;
            for(int v:pred[u]) if(dfn[v]) {
                eval(v);
                if(cmp(sdom[mn[v]],sdom[u])) sdom[u] = sdom[mn[v]];
            }
            cov[sdom[u]].push_back(u);
            mom[u] = par[u];
            for(int w:cov[par[u]]) {
                eval(w);
                if(cmp(sdom[mn[w]],par[u])) idom[w] = mn[w];
                else idom[w] = par[u];
            }
        }
    }
};
```

```
    }
    cov[par[u]].clear();
    }
    REP1(i,2,ts) {
        int u = nfd[i];
        if(u == 0) continue;
        if(idom[u] != sdom[u]) idom[u] = idom[idom[u]];
    }
    }
}dom;

#define MXN 100005
#define PB push_back
#define FZ(s) memset(s,0,sizeof(s))

struct Scc{
    int n, nScc, vst[MXN], bln[MXN];
    vector<int> E[MXN], rE[MXN], vec;
    void init(int _n){
        n = _n;
        for (int i=0; i<MXN; i++){
            E[i].clear();
            rE[i].clear();
        }
    }
    void add_edge(int u, int v){
        E[u].PB(v);
        rE[v].PB(u);
    }
    void DFS(int u){
        vst[u]=1;
        for (auto v : E[u])
            if (!vst[v]) DFS(v);
        vec.PB(u);
    }
    void rDFS(int u){
        vst[u] = 1;
        bln[u] = nScc;
        for (auto v : rE[u])
            if (!vst[v]) rDFS(v);
    }
    void solve(){
        nScc = 0;
        vec.clear();
        FZ(vst);
        for (int i=0; i<n; i++)
            if (!vst[i]) DFS(i);
        reverse(vec.begin(),vec.end());
        FZ(vst);
        for (auto v : vec){
            if (!vst[v]){
                rDFS(v);
                nScc++;
            }
        }
    }
};
```

4.6 Manhattan MST

```
#include <bits/stdc++.h>
using namespace std;

const int MAXN = 100005;
const int OFFSET = 2000; // y-x may < 0, offset it, if
// y-x too large, please write a unique function
const int INF = 0xFFFFFFFF;
int n;
int x[MAXN], y[MAXN], p[MAXN];

typedef pair<int, int> pii;
pii bit[MAXN]; // [ val, pos ]

struct P {
    int x, y, id;
```



```

    bool operator<(const P&b ) const {
        if ( x == b.x ) return y > b.y;
        else return x > b.x;
    }
};
vector<P> op;

struct E {
    int x, y, cost;
    bool operator<(const E&b ) const {
        return cost < b.cost;
    }
};
vector<E> edges;

int find(int x) {
    return p[x] == x ? x : p[x] = find(p[x]);
}

void update(int i, int v, int p) {
    while ( i ) {
        if ( bit[i].first > v ) bit[i] = {v, p};
        i -= i & (-i);
    }
}

pii query(int i) {
    pii res = {INF, INF};
    while ( i < MAXN ) {
        if ( bit[i].first < res.first ) res = {bit[i].first, bit[i].second};
        i += i & (-i);
    }
    return res;
}

void input() {
    cin >> n;
    for ( int i = 0 ; i < n ; i++ ) cin >> x[i] >> y[i]
        ], op.push_back((P) {x[i], y[i], i});
}

void mst() {
    for ( int i = 0 ; i < MAXN ; i++ ) p[i] = i;
    int res = 0;
    sort(edges.begin(), edges.end());
    for ( auto e : edges ) {
        int x = find(e.x), y = find(e.y);
        if ( x != y ) {
            p[x] = y;
            res += e.cost;
        }
    }
    cout << res << endl;
}

void construct() {
    sort(op.begin(), op.end());
    for ( int i = 0 ; i < n ; i++ ) {
        pii q = query(op[i].y - op[i].x + OFFSET);
        update(op[i].y - op[i].x + OFFSET, op[i].x + op[i].y, op[i].id);
        if ( q.first == INF ) continue;
        edges.push_back((E) {op[i].id, q.second, abs(x[op[i].id]-x[q.second]) + abs(y[op[i].id]-y[q.second]) });
    }
}

void solve() {
    // [45 ~ 90 deg]
    for ( int i = 0 ; i < MAXN ; i++ ) bit[i] = {INF, INF};
    construct();

    // [0 ~ 45 deg]

```

```

    for ( int i = 0 ; i < MAXN ; i++ ) bit[i] = {INF, INF};
    for ( int i = 0 ; i < n ; i++ ) swap(op[i].x, op[i].y);
    construct();
    for ( int i = 0 ; i < n ; i++ ) swap(op[i].x, op[i].y);

    // [-90 ~ -45 deg]
    for ( int i = 0 ; i < MAXN ; i++ ) bit[i] = {INF, INF};
    for ( int i = 0 ; i < n ; i++ ) op[i].y *= -1;
    construct();

    // [-45 ~ 0 deg]
    for ( int i = 0 ; i < MAXN ; i++ ) bit[i] = {INF, INF};
    for ( int i = 0 ; i < n ; i++ ) swap(op[i].x, op[i].y);
    construct();

    // mst
    mst();
}

int main () {
    input();
    solve();
    return 0;
}

```

4.7 Hungarian

// Maximum Cardinality Bipartite Matching

```

struct Graph {
    static const int MAXN = 5005;
    vector<int> G[MAXN];
    int n;
    int match[MAXN]; // Matching Result
    int vis[MAXN];

    void init(int _n) {
        n = _n;
        for ( int i = 0 ; i < n ; i++ ) G[i].clear();
    }

    bool dfs(int u) {
        for ( auto v:G[u] ) {
            if (!vis[v]) {
                vis[v] = true;
                if (match[v] == -1 || dfs(match[v])) {
                    match[v] = u;
                    match[u] = v;
                    return true;
                }
            }
        }
        return false;
    }

    int solve() {
        int res = 0;
        memset(match, -1, sizeof(match));
        for (int i = 0; i < n; i++) {
            if (match[i] == -1) {
                memset(vis, 0, sizeof(vis));
                if (dfs(i)) res += 1;
            }
        }
        return res;
    }
} graph;

```

4.8 KM

Detect non-perfect-matching:

1. set all `edge[i][j]` as INF
2. if `solve() >= INF`, it is not perfectmatching.

```
-----
// Maximum Weight Perfect Bipartite Matching
// allow negative weight!
```

```
typedef long long Int;
struct KM {
    static const int MAXN = 1050;
    static const int INF = 1LL<<60;
    int n, match[MAXN], vx[MAXN], vy[MAXN];
    Int edge[MAXN][MAXN], lx[MAXN], ly[MAXN], slack[
        MAXN];
    void init(int _n){
        n = _n;
        for ( int i = 0 ; i < n ; i++ )
            for ( int j = 0 ; j < n ; j++ )
                edge[i][j] = 0;
    }
    void add_edge(int x, int y, Int w){
        edge[x][y] = w;
    }
    bool DFS(int x){
        vx[x] = 1;
        for ( int y = 0 ; y < n ; y++ ) {
            if ( vy[y] ) continue;
            if ( lx[x] + ly[y] > edge[x][y] ) {
                slack[y] = min(slack[y], lx[x] + ly[y]
                    - edge[x][y]);
            } else {
                vy[y] = 1;
                if ( match[y] == -1 || DFS(match[y]) ){
                    match[y] = x;
                    return true;
                }
            }
        }
        return false;
    }
    Int solve() {
        fill(match, match + n, -1);
        fill(lx, lx + n, -INF);
        fill(ly, ly + n, 0);
        for ( int i = 0 ; i < n ; i++ )
            for ( int j = 0 ; j < n ; j++ )
                lx[i] = max(lx[i], edge[i][j]);
        for ( int i = 0 ; i < n ; i++ ) {
            fill(slack, slack + n, INF);
            while (true){
                fill(vx, vx + n, 0);
                fill(vy, vy + n, 0);
                if ( DFS(i) ) break;
                Int d = INF;
                for ( int j = 0 ; j < n ; j++ )
                    if ( !vy[j] ) d = min(d, slack[j]);
                for ( int j = 0 ; j < n ; j++ ) {
                    if ( vx[j] ) lx[j] -= d;
                    if ( vy[j] ) ly[j] += d;
                    else slack[j] -= d;
                }
            }
        }
        Int res = 0;
        for ( int i = 0 ; i < n ; i++ ) {
            res += edge[ match[i] ][i];
        }
        return res;
    }
} graph;
```

4.9 Theorm - Matching

最大匹配 + 最小邊覆蓋 = V
 最大獨立集 + 最小點覆蓋 = V
 最大匹配 = 最小點覆蓋
 最小路徑覆蓋數 = V - 最大匹配數

4.10 Maximum General Matching

```
// Maximum Cardinality Matching

struct Graph {
    vector<int> G[MAXN];
    int pa[MAXN], match[MAXN], st[MAXN], S[MAXN], vis[
        MAXN];
    int t, n;

    void init(int _n) {
        n = _n;
        for ( int i = 1 ; i <= n ; i++ ) G[i].clear();
    }
    void add_edge(int u, int v) {
        G[u].push_back(v);
        G[v].push_back(u);
    }
    int lca(int u, int v){
        for ( ++t ; ; swap(u, v) ) {
            if ( u == 0 ) continue;
            if ( vis[u] == t ) return u;
            vis[u] = t;
            u = st[ pa[ match[u] ] ];
        }
    }
    void flower(int u, int v, int l, queue<int> &q) {
        while ( st[u] != 1 ) {
            pa[u] = v;
            if ( S[ v = match[u] ] == 1 ) {
                q.push(v);
                S[v] = 0;
            }
            st[u] = st[v] = 1;
            u = pa[v];
        }
    }
    bool bfs(int u){
        for ( int i = 1 ; i <= n ; i++ ) st[i] = i;
        memset(S, -1, sizeof(S));
        queue<int> q;
        q.push(u);
        S[u] = 0;
        while ( !q.empty() ) {
            u = q.front(); q.pop();
            for ( int i = 0 ; i < (int)G[u].size(); i++ ) {
                int v = G[u][i];
                if ( S[v] == -1 ) {
                    pa[v] = u;
                    S[v] = 1;
                    if ( !match[v] ) {
                        for ( int lst ; u ; v = lst, u = pa[v] ) {
                            lst = match[u];
                            match[u] = v;
                            match[v] = u;
                        }
                        return 1;
                    }
                    q.push(match[v]);
                    S[ match[v] ] = 0;
                } else if ( !S[v] && st[v] != st[u] ) {
                    int l = lca(st[v], st[u]);
                    flower(v, u, l, q);
                    flower(u, v, l, q);
                }
            }
        }
        return 0;
    }
    int solve(){
```

```

memset(pa, 0, sizeof(pa));
memset(match, 0, sizeof(match));
int ans = 0;
for ( int i = 1 ; i <= n ; i++ )
    if ( !match[i] && bfs(i) ) ans++;
return ans;
}
} graph;

```

4.11 Minimum General Weighted Matching

```

// Minimum Weight Perfect Matching (Perfect Match)

struct Graph {
    static const int MAXN = 105;
    int n, e[MAXN][MAXN];
    int match[MAXN], d[MAXN], onstk[MAXN];
    vector<int> stk;
    void init(int _n) {
        n = _n;
        for( int i = 0 ; i < n ; i ++ )
            for( int j = 0 ; j < n ; j ++ )
                e[i][j] = 0;
    }
    void add_edge(int u, int v, int w) {
        e[u][v] = e[v][u] = w;
    }
    bool SPFA(int u){
        if (onstk[u]) return true;
        stk.push_back(u);
        onstk[u] = 1;
        for ( int v = 0 ; v < n ; v++ ) {
            if ( u != v && match[u] != v && !onstk[v] )
            {
                int m = match[v];
                if ( d[m] > d[u] - e[v][m] + e[u][v] )
                {
                    d[m] = d[u] - e[v][m] + e[u][v];
                    onstk[v] = 1;
                    stk.push_back(v);
                    if ( SPFA(m) ) return true;
                    stk.pop_back();
                    onstk[v] = 0;
                }
            }
        }
        onstk[u] = 0;
        stk.pop_back();
        return false;
    }
    int solve() {
        for ( int i = 0 ; i < n ; i += 2 ) {
            match[i] = i+1;
            match[i+1] = i;
        }
        while (true){
            int found = 0;
            for ( int i = 0 ; i < n ; i++ )
                onstk[ i ] = d[ i ] = 0;
            for ( int i = 0 ; i < n ; i++ ) {
                stk.clear();
                if ( !onstk[i] && SPFA(i) ) {
                    found = 1;
                    while ( stk.size() >= 2 ) {
                        int u = stk.back(); stk.pop_back();
                        int v = stk.back(); stk.pop_back();
                        match[u] = v;
                        match[v] = u;
                    }
                }
            }
            if (!found) break;
        }
        int ret = 0;
    }
};

```

```

for ( int i = 0 ; i < n ; i++ )
    ret += e[i][match[i]];
ret /= 2;
return ret;
}
} graph;

```

4.12 Maximum Clique

```

const int MAXN = 105;
int best;
int m, n;
int num[MAXN];
// int x[MAXN];
int path[MAXN];
int g[MAXN][MAXN];

bool dfs( int *adj, int total, int cnt ){
    int i, j, k;
    int t[MAXN];
    if( total == 0 ){
        if( best < cnt ){
            // for( i = 0; i < cnt; i++) path[i] = x[i];
            best = cnt; return true;
        }
        return false;
    }
    for( i = 0; i < total; i++){
        if( cnt+(total-i) <= best ) return false;
        if( cnt+num[adj[i]] <= best ) return false;
        // x[cnt] = adj[i];
        for( k = 0, j = i+1; j < total; j++ )
            if( g[ adj[i] ][ adj[j] ] )
                t[ k++ ] = adj[j];
        if( dfs( t, k, cnt+1 ) ) return true;
    }
    return false;
}

int MaximumClique(){
    int i, j, k;
    int adj[MAXN];
    if( n <= 0 ) return 0;
    best = 0;
    for( i = n-1; i >= 0; i-- ){
        // x[0] = i;
        for( k = 0, j = i+1; j < n; j++ )
            if( g[i][j] ) adj[k++] = j;
        dfs( adj, k, 1 );
        num[i] = best;
    }
    return best;
}

```

4.13 Steiner Tree

```

// Minimum Steiner Tree
// O(V 3^T + V^2 2^T)
struct SteinerTree{
#define V 33
#define T 8
#define INF 1023456789
    int n, dst[V][V], dp[1 << T][V], tdst[V];
    void init( int _n ){
        n = _n;
        for( int i = 0 ; i < n ; i ++ ){
            for( int j = 0 ; j < n ; j ++ )
                dst[ i ][ j ] = INF;
            dst[ i ][ i ] = 0;
        }
    }
    void add_edge( int ui , int vi , int wi ){
        dst[ ui ][ vi ] = min( dst[ ui ][ vi ] , wi );
        dst[ vi ][ ui ] = min( dst[ vi ][ ui ] , wi );
    }
};

```

```

}
void shortest_path(){
    for( int k = 0 ; k < n ; k ++ )
        for( int i = 0 ; i < n ; i ++ )
            for( int j = 0 ; j < n ; j ++ )
                dst[ i ][ j ] = min( dst[ i ][ j ],
                                    dst[ i ][ k ] + dst[ k ][ j ] );
}
int solve( const vector<int>& ter ){
    int t = (int)ter.size();
    for( int i = 0 ; i < ( 1 << t ) ; i ++ )
        for( int j = 0 ; j < n ; j ++ )
            dp[ i ][ j ] = INF;
    for( int i = 0 ; i < n ; i ++ )
        dp[ 0 ][ i ] = 0;
    for( int msk = 1 ; msk < ( 1 << t ) ; msk ++ ){
        if( msk == ( msk & (-msk) ) ){
            int who = __lg( msk );
            for( int i = 0 ; i < n ; i ++ )
                dp[ msk ][ i ] = dst[ ter[ who ] ][ i ];
            continue;
        }
        for( int i = 0 ; i < n ; i ++ )
            for( int submsk = ( msk - 1 ) & msk ; submsk ;
                submsk = ( submsk - 1 ) & msk )
                dp[ msk ][ i ] = min( dp[ msk ][ i ],
                                      dp[ submsk ][ i ] +
                                      dp[ msk ^ submsk ][ i ] );
        for( int i = 0 ; i < n ; i ++ ){
            tdst[ i ] = INF;
            for( int j = 0 ; j < n ; j ++ )
                tdst[ i ] = min( tdst[ i ],
                                dp[ msk ][ j ] + dst[ j ][ i ] );
        }
        for( int i = 0 ; i < n ; i ++ )
            dp[ msk ][ i ] = tdst[ i ];
    }
    int ans = INF;
    for( int i = 0 ; i < n ; i ++ )
        ans = min( ans , dp[ ( 1 << t ) - 1 ][ i ] );
    return ans;
}
} solver;

```

4.14 最小平均環

```

// from BCW

/* minimum mean cycle */
const int MAXE = 1805;
const int MAXN = 35;
const double inf = 1029384756;
const double eps = 1e-6;
struct Edge {
    int v,u;
    double c;
};
int n,m,prv[MAXN][MAXN], prve[MAXN][MAXN], vst[MAXN];
Edge e[MAXE];
vector<int> edgeID, cycle, rho;
double d[MAXN][MAXN];
inline void bellman_ford() {
    for(int i=0; i<n; i++) d[0][i]=0;
    for(int i=0; i<n; i++) {
        fill(d[i+1], d[i+1]+n, inf);
        for(int j=0; j<m; j++) {
            int v = e[j].v, u = e[j].u;
            if(d[i][v]<inf && d[i+1][u]>d[i][v]+e[j].c) {
                d[i+1][u] = d[i][v]+e[j].c;
                prv[i+1][u] = v;
                prve[i+1][u] = j;
            }
        }
    }
}
double karp_mmc() {

```

```

// returns inf if no cycle, mmc otherwise
double mmc=inf;
int st = -1;
bellman_ford();
for(int i=0; i<n; i++) {
    double avg=-inf;
    for(int k=0; k<n; k++) {
        if(d[n][i]<inf-eps) avg=max(avg,(d[n][i]-d[k][i])/(n-k));
        else avg=max(avg,inf);
    }
    if (avg < mmc) tie(mmc, st) = tie(avg, i);
}
for(int i=0; i<n; i++) vst[i] = 0;
edgeID.clear(); cycle.clear(); rho.clear();
for( int i=n; !vst[st]; st=prv[i--][st] ) {
    vst[st]++;
    edgeID.PB(prve[i][st]);
    rho.PB(st);
}
while (vst[st] != 2) {
    int v = rho.back(); rho.pop_back();
    cycle.PB(v);
    vst[v]++;
}
reverse(ALL(edgeID));
edgeID.resize(SZ(cycle));
return mmc;
}

```

4.15 SchreierSims

```

// time: O(n^2 lg^3 |G| + t n lg |G|)
// mem : O(n^2 lg |G| + tn)
// t : number of generator
namespace SchreierSimsAlgorithm{
    typedef vector<int> Permu;
    Permu inv( const Permu& p ){
        Permu ret( p.size() );
        for( int i = 0; i < (int)p.size(); i ++ )
            ret[ p[ i ] ] = i;
        return ret;
    }
    Permu operator*( const Permu& a, const Permu& b ){
        Permu ret( a.size() );
        for( int i = 0 ; i < (int)a.size(); i ++ )
            ret[ i ] = b[ a[ i ] ];
        return ret;
    }
    typedef vector<Permu> Bucket;
    typedef vector<int> Table;
    typedef pair<int,int> pii;
    int n, m;
    vector<Bucket> bkts, bktsInv;
    vector<Table> lookup;
    int fastFilter( const Permu &g, bool addToG = 1 ){
        n = bkts.size();
        Permu p;
        for( int i = 0 ; i < n ; i ++ ){
            int res = lookup[ i ][ p[ i ] ];
            if( res == -1 ){
                if( addToG ){
                    bkts[ i ].push_back( p );
                    bktsInv[ i ].push_back( inv( p ) );
                    lookup[ i ][ p[ i ] ] = (int)bkts[i].size()-1;
                }
                return i;
            }
            p = p * bktsInv[i][res];
        }
        return -1;
    }
    long long calcTotalSize(){
        long long ret = 1;
        for( int i = 0 ; i < n ; i ++ )
            ret *= bkts[i].size();
    }
}

```

```

    return ret;
}
bool inGroup( const Permu &g ){
    return fastFilter( g, false ) == -1;
}
void solve( const Bucket &gen, int _n ){
    n = _n, m = gen.size(); // m perm[0..n-1]s
    //clear all
    bkts.clear();
    bktsInv.clear();
    lookup.clear();
}
for(int i = 0 ; i < n ; i ++ ){
    lookup[i].resize(n);
    fill(lookup[i].begin(), lookup[i].end(), -1);
}
Permu id( n );
for(int i = 0 ; i < n ; i ++ ) id[i] = i;
for(int i = 0 ; i < n ; i ++ ){
    bkts[i].push_back(id);
    bktsInv[i].push_back(id);
    lookup[i][i] = 0;
}
for(int i = 0 ; i < m ; i ++ )
    fastFilter( gen[i] );
queue< pair<pii,pii> > toUpd;
for(int i = 0; i < n; i ++ )
    for(int j = i; j < n; j ++ )
        for(int k = 0; k < (int)bkts[i].size(); k ++ )
            for(int l = 0; l < (int)bkts[j].size(); l ++ )
                toUpd.push( {pii(i,k), pii(j,l)} );
while( !toUpd.empty() ){
    pii a = toUpd.front().first;
    pii b = toUpd.front().second;
    toUpd.pop();
    int res = fastFilter(bkts[a.first][a.second] *
                        bkts[b.first][b.second]);
    if(res == -1) continue;
    pii newPair(res, (int)bkts[res].size() - 1);
    for(int i = 0; i < n; i ++ )
        for(int j = 0; j < (int)bkts[i].size(); ++j){
            if(i <= res)
                toUpd.push(make_pair(pii(i , j), newPair));
            if(res <= i)
                toUpd.push(make_pair(newPair, pii(i, j)));
        }
}
}
}
}

```

4.16 Tarjan

割點

點 u 為割點 if and only if 滿足 1. or 2.

1. u 為樹根，且 u 有多於一個子樹。
2. u 不為樹根，且滿足存在 (u,v) 為樹枝邊（或稱父子邊，即 u 為 v 在搜索樹中的父親），使得 $DFN(u) \leq Low(v)$ 。

橋

一條無向邊 (u,v) 是橋 if and only if (u,v) 為樹枝邊，且滿足 $DFN(u) < Low(v)$ 。

// 0 base

```

struct TarjanSCC{
    static const int MAXN = 1000006;
    int n, dfn[MAXN], low[MAXN], scc[MAXN], scn, count;
    vector<int> G[MAXN];
    stack<int> stk;
    bool ins[MAXN];

    void tarjan(int u){
        dfn[u] = low[u] = ++count;
        stk.push(u);

```

```

        ins[u] = true;
        for(auto v:G[u]){
            if(!dfn[v]){
                tarjan(v);
                low[u] = min(low[u], low[v]);
            }else if(ins[v]){
                low[u] = min(low[u], dfn[v]);
            }
        }
        if(dfn[u] == low[u]){
            int v;
            do {
                v = stk.top();
                stk.pop();
                scc[v] = scn;
                ins[v] = false;
            } while(v != u);
            scn++;
        }
    }
}

void getSCC(){
    memset(dfn,0,sizeof(dfn));
    memset(low,0,sizeof(low));
    memset(ins,0,sizeof(ins));
    memset(scc,0,sizeof(scc));
    count = scn = 0;
    for(int i = 0 ; i < n ; i ++ ){
        if(!dfn[i]) tarjan(i);
    }
}
}SCC;

```

4.17 2-SAT

const int MAXN = 2020;

```

struct TwoSAT{
    static const int MAXv = 2*MAXN;
    vector<int> GO[MAXv],BK[MAXv],stk;
    bool vis[MAXv];
    int SC[MAXv];

    void imply(int u,int v){ // u imply v
        GO[u].push_back(v);
        BK[v].push_back(u);
    }
    int dfs(int u,vector<int>*G,int sc){
        vis[u]=1, SC[u]=sc;
        for (int v:G[u])if (!vis[v])
            dfs(v,G,sc);
        if (G==GO)stk.push_back(u);
    }
    int scc(int n=MAXv){
        memset(vis,0,sizeof(vis));
        for (int i=0; i<n; i++)if (!vis[i])
            dfs(i,GO,-1);
        memset(vis,0,sizeof(vis));
        int sc=0;
        while (!stk.empty()){
            if (!vis[stk.back()])
                dfs(stk.back(),BK,sc++);
            stk.pop_back();
        }
    }
}SAT;

int main(){
    SAT.scc(2*n);
    bool ok=1;
    for (int i=0; i<n; i++){
        if (SAT.SC[2*i]==SAT.SC[2*i+1])ok=0;
    }
}

```

```

    if (ok){
        for (int i=0; i<n; i++){
            if (SAT.SC[2*i]>SAT.SC[2*i+1]){
                cout << i << endl;
            }
        }
    }
    else puts("NO");
}

```

5 Data Structure

5.1 Sparse Table

```

const int MAXN = 200005;
const int lgN = 20;

struct SP{ //sparse table
    int Sp[MAXN][lgN];
    function<int(int,int)> opt;
    void build(int n, int *a){ // 0 base
        for (int i=0 ;i<n; i++) Sp[i][0]=a[i];

        for (int h=1; h<lgN; h++){
            int len = 1<<(h-1), i=0;
            for (; i+len<n; i++)
                Sp[i][h] = opt( Sp[i][h-1] , Sp[i+len][h-1] );
            for (; i<n; i++)
                Sp[i][h] = Sp[i][h-1];
        }
    }
    int query(int l, int r){
        int h = __lg(r-l+1);
        int len = 1<<h;
        return opt( Sp[l][h] , Sp[r-len+1][h] );
    }
};

```

5.2 Segment Tree

```

int n,m,i,a,b,c;
int ans[MAXN<<2],add[MAXN<<2],inp[MAXN<<2];

inline int ls(const int&p){
    return p<<1;
}

inline int rs(const int&p){
    return p<<1|1;
}

inline int Max(const int&x,const int&y){
    return x>y?x:y;
}

inline void push_up(const int&p,const int&tag){
    ans[p]=Max(ans[ls(p)],ans[rs(p)])+tag;
}

void build(const int l=1,const int r=n,const int p=1){
    if(l==r){
        get(ans[p]);
        inp[l]=ans[p];
        return;
    }
    int mid=(l+r)>>1;
    build(l, mid, ls(p));
    build(mid+1,r,rs(p));
    push_up(p,0);
}

```

```

inline void update(const int&x,const int&y,const int&k,
    const int&l=1,const int&r=n,const int&p=1){
    if(l>=x&&r<=y){
        add[p]+=k;
        ans[p]+=k;
        return;
    }
    int mid=(l+r)>>1;
    if(x<=mid){
        update(x,y,k,l, mid, ls(p));
    }
    if(y>mid){
        update(x,y,k,mid+1,r,rs(p));
    }
    push_up(p,add[p]);
}

inline int query(const int &x,const int &y,const int &
    tag=0,const int &l=1,const int &r=n,const int &p=1)
{
    if(l>=x&&r<=y){
        return ans[p]+tag;
    }
    int mx=-1;
    int mid=(l+r)>>1;
    if(x<=mid){
        mx=Max(mx,query(x,y,tag+add[p],l, mid, ls(p)));
    }
    if(y>mid){
        mx=Max(mx,query(x,y,tag+add[p],mid+1,r,rs(p)));
    }
    return mx;
}

```

6 String

6.1 KMP

```

template<typename T>
void build_KMP(int n, T *s, int *f){ // 1 base
    f[0]=-1, f[1]=0;
    for (int i=2; i<=n; i++){
        int w = f[i-1];
        while (w>=0 && s[w+1]!=s[i])w = f[w];
        f[i]=w+1;
    }
}

template<typename T>
int KMP(int n, T *a, int m, T *b){
    build_KMP(m,b,f);
    int ans=0;

    for (int i=1, w=0; i<=n; i++){
        while ( w>=0 && b[w+1]!=a[i] )w = f[w];
        w++;
        if (w==m){
            ans++;
            w=f[w];
        }
    }
    return ans;
}

```

7 Dark Code

7.1 輸入優化

```

#include <stdio.h>

char getc(){

```

```

static const int bufsize = 1<<16;
static char B[bufsize], *S=B, *T=B;
return (S==T&&(T=(S=B)+fread(B,1,bufsize,stdin),S==T)
?0:*S++);
}

template <class T>
bool input(T& a){
    a=(T)0;
    register char p;
    while ((p = getc()) < '-')
        if (p==0 || p==EOF) return false;
    if (p == '-')
        while ((p = getc()) >= '0') a = a*10 - (p^'0');
    else {
        a = p ^ '0';
        while ((p = getc()) >= '0') a = a*10 + (p^'0');
    }
    return true;
}

template <class T, class... U>
bool input(T& a, U&... b){
    if (!input(a)) return false;
    return input(b...);
}

```

7.2 PBDS

```

#include<ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
#include <ext/pb_ds/detail/standard_policies.hpp>
typedef tree<int,null_type,less<int>,rb_tree_tag,
    tree_order_statistics_node_update> ordered_set;

```

8 Search

8.1 LIS

```

int LIS(vector<int>& s)
{
    if (s.size() == 0) return 0;

    vector<int> v;
    v.push_back(s[0]);

    for (int i = 1; i < s.size(); ++i)
    {
        int n = s[i];

        if (n > v.back())
            v.push_back(n);
        else
            *lower_bound(v.begin(), v.end(), n) = n;
    }

    return v.size();
}

```

8.2 Merge sort

```

void merge(int *vec, int start, int end)
{
    if (start >= end) return;
    int mid = start + ((end - start) >> 1);
    merge(vec, start, mid);
    merge(vec, mid + 1, end);
    for (int i = start; i <= mid; i++)
    {

```

```

//ans += distance(lower_bound(vec + mid + 1,
    vec + end + 1, vec[i] + lower),
    //
        upper_bound(vec + mid + 1,
            vec + end + 1, vec[i] + upper));
//Do some cool stuffs
}
inplace_merge(vec + start, vec + mid + 1, vec + end
    + 1);
}

```

9 Others

9.1 數位統計

```

int dfs(int pos, int state1, int state2 ....., bool
    limit, bool zero) {
    if ( pos == -1 ) return 是否符合條件;
    int &ret = dp[pos][state1][state2][....];
    if ( ret != -1 && !limit ) return ret;
    int ans = 0;
    int upper = limit ? digit[pos] : 9;
    for ( int i = 0 ; i <= upper ; i++ ) {
        ans += dfs(pos - 1, new_state1, new_state2,
            limit & ( i == upper), ( i == 0 ) && zero);
    }
    if ( !limit ) ret = ans;
    return ans;
}

int solve(int n) {
    int it = 0;
    for ( ; n ; n /= 10 ) digit[it++] = n % 10;
    return dfs(it - 1, 0, 0, 1, 1);
}

```

9.2 1D/1D dp 優化

```

#include<bits/stdc++.h>

int t, n, L;
int p;
char s[MAXN][35];
ll sum[MAXN] = {0};
long double dp[MAXN] = {0};
int prevd[MAXN] = {0};

long double pw(long double a, int n) {
    if ( n == 1 ) return a;
    long double b = pw(a, n/2);
    if ( n & 1 ) return b*b*a;
    else return b*b;
}

long double f(int i, int j) {
    // cout << (sum[i] - sum[j]+i-j-1-L) << endl;
    return pw(abs(sum[i] - sum[j]+i-j-1-L), p) + dp[j];
}

struct INV {
    int L, R, pos;
};
INV stk[MAXN*10];
int top = 1, bot = 1;
void update(int i) {
    while ( top > bot && i < stk[top].L && f(stk[top].L,
        i) < f(stk[top].L, stk[top].pos) ) {
        stk[top - 1].R = stk[top].R;
        top--;
    }
    int lo = stk[top].L, hi = stk[top].R, mid, pos =
        stk[top].pos;
    //if ( i >= lo ) lo = i + 1;
    while ( lo != hi ) {
        mid = lo + (hi - lo) / 2;

```



```

    if ( f(mid, i) < f(mid, pos) ) hi = mid;
    else lo = mid + 1;
}
if ( hi < stk[top].R ) {
    stk[top + 1] = (INV) { hi, stk[top].R, i };
    stk[top++].R = hi;
}
}

int main() {
    cin >> t;
    while ( t-- ) {
        cin >> n >> L >> p;
        dp[0] = sum[0] = 0;
        for ( int i = 1 ; i <= n ; i++ ) {
            cin >> s[i];
            sum[i] = sum[i-1] + strlen(s[i]);
            dp[i] = numeric_limits<long double>::max();
        }
        stk[top] = (INV) {1, n + 1, 0};
        for ( int i = 1 ; i <= n ; i++ ) {
            if ( i >= stk[bot].R ) bot++;
            dp[i] = f(i, stk[bot].pos);
            update(i);
            // cout << (ll) f(i, stk[bot].pos) << endl;
        }
        if ( dp[n] > 1e18 ) {
            cout << "Too hard to arrange" << endl;
        } else {
            vector<PI> as;
            cout << (ll)dp[n] << endl;
        }
    }
    return 0;
}

```

```

int l = 0, r = 0, nowAns = 0, BLOCK_SIZE, n, m;
int ans[];
struct QUE{
    int l, r, id;
    friend bool operator < (QUE a, QUE b){
        if(a.l / BLOCK_SIZE != b.l / BLOCK_SIZE)
            return a.l / BLOCK_SIZE < b.l / BLOCK_SIZE;
        return a.r < b.r;
    }
}qurys[];

inline void move(int pos, int sign) {
    // update nowAns
}

void solve() {
    BLOCK_SIZE = int(ceil(pow(n, 0.5)));
    sort(qurys, qurys + m);
    for (int i = 0; i < m; ++i) {
        const QUE &q = qurys[i];
        while (l > q.l) move(--l, 1);
        while (r < q.r) move(r++, 1);
        while (l < q.l) move(l++, -1);
        while (r > q.r) move(--r, -1);
        ans[q.id] = nowAns;
    }
}

```

10 Persistence

9.3 Theorm - DP optimization

Monotonicity & 1D/1D DP & 2D/1D DP

Definition xD/yD

1D/1D $DP[j] = \min(0 \leq i < j) \{ DP[i] + w(i, j) \}$; $DP[0] = k$
 2D/1D $DP[i][j] = \min(i < k \leq j) \{ DP[i][k-1] + DP[k][j] \}$
 $+ w(i, j)$; $DP[i][i] = 0$

Monotonicity

	c	d
a	w(a, c)	w(a, d)
b	w(b, c)	w(b, d)

Monge Condition

Concave (凹四邊形不等式): $w(a, c) + w(b, d) \geq w(a, d) + w(b, c)$

Convex (凸四邊形不等式): $w(a, c) + w(b, d) \leq w(a, d) + w(b, c)$

Totally Monotone

Concave (凹單調): $w(a, c) \leq w(b, d) \rightarrow w(a, d) \leq w(b, c)$

Convex (凸單調): $w(a, c) \geq w(b, d) \rightarrow w(a, d) \geq w(b, c)$

1D/1D DP $O(n^2) \rightarrow O(n \lg n)$

****CONSIDER THE TRANSITION POINT****

Solve 1D/1D Concave by Stack

Solve 1D/1D Convex by Deque

2D/1D Convex DP (Totally Monotone) $O(n^3) \rightarrow O(n^2)$

$h(i, j-1) \leq h(i, j) \leq h(i+1, j)$

9.4 Mo' s algorithm