Doc Number: 161310G00000-00	Doc Version: 008	Date: 03-Nov-2026

Super Mushshak Automatic Flight Test

Prepar3D v5 | Rahwali Airfield (OPRW) | Automatic Testing Mode

Super Mushshak Logger - ver. 1.0

Super Mushshak Airborne Automatic Testing Suite

Flight Test File: Super_Mushak_auto_takeoff_data_2026-11-03_09-31-14.csv

ONLINE, AUTOMATIC


Test Date: 03-Nov-2026 Test Time: 09:31:14


Initial Test Conditions


Validation	Sim	
***** Weight and Balance *****		
844.3	844.3	Gross Wt (kg)
105.2	105.2	Total Fuel Quantity (kg)
0.00	0.00	CG Pos in X Axis (mm)
0.00	0.00	CG Pos in Y Axis (mm)
***** Control Parameters *****		
-2.82	-2.77	Pitch Control Position (raw)
-1.55	-1.92	Roll Control Position (raw)
0.00	0.00	Rudder Pedal Position (raw)
100.0	100.0	Throttle Position (%)
-0.17	-1.28	Pitch Force: Applied/Virtual (N)
-0.04	-0.12	Roll Force: Applied/Virtual (N)
0.00	-0.00	Yaw Force: Applied/Virtual (N)
***** Environment Parameters *****		
1013	1013	Baro Press (hPa)
10.9	10.9	OAT (deg C)
325.0	324.9	Wind Dir (mag,deg)
7.80	7.80	Wind Spd (kt)
***** Engine Parameters (Piston Engine) *****		
2700	2701	Engine Speed (RPM)
100.0	100.0	Throttle Position (%)
0.00	0.00	Fuel Flow (pph)
590.2	590.0	Exhaust Gas Temp (deg C)

Validation	Sim	
***** Flight Parameters *****		
111.0	111.0	Indicated Airspeed (kt)
114.0	114.1	Ground Speed (kt)
0.18	0.18	Mach Number (-)
2851	2851	Pressure Alt (ft)
2106	2106	Radar Alt (ft)
750.0	750.0	Height of Terrain (ft)
-629.3	-616.4	Vertical Velocity (ft/min)
-1.11	-1.19	Pitch Angle (deg)
-4.44	-4.45	Bank Angle (deg)
40.7	40.7	Heading (deg)
1.57	1.57	Aircraft Angle of Attack (deg)
-0.33	-0.36	Sideslip Angle (deg)
44.9	42.8	Track Angle (deg)
0.49	0.46	Roll Rate (deg/s)
-2.19	-2.21	Pitch Rate (deg/s)
-1.05	-1.06	Yaw Rate (deg/s)
1.10	1.15	X Body Acceleration (g)
-0.19	-0.27	Y Body Acceleration (g)
0.76	0.61	Z Body Acceleration (g)


1st Quadrant Combined Group 1 (Airspeed, Climb, Altitude)











1st Quadrant Combined Group 2 (Pitch, Bank, Yaw, Heading)
















1st Quadrant Combined Group 3 (Propeller, Engine, Throttle)








t Combined Group 4 (Position + Manual Applied Force vs Inverted Automatic V
Manual Test (Reference)
Automatic Test (Sim)
Joystick Pitch Position (mm)
Time (s)
Manual Applied Force (Reference)
Automatic Virtual Force (Sim)
Pitch: Manual Applied Force vs Automatic Virtual Force (inverted) (N)
Time (s)
Manual Test (Reference)
Automatic Test (Sim)
Joystick Roll Position (mm)
Time (s)
Manual Applied Force (Reference)
Automatic Virtual Force (Sim)
Roll: Manual Applied Force vs Automatic Virtual Force (inverted) (N)
Time (s)


mbined Group 5 (Rudder Position + Manual Applied Force vs Inverted Automat
Manual Test (Reference)
Automatic Test (Sim)
Rudder Pedal Position (mm)
0.04
0.02
0.00
−0.02
−0.04
0
5
10
15
20
25
30
35
40
45
50
55
60
65
70
75
Time (s)
Manual Applied Force (Reference)
Automatic Virtual Force (Sim)
Yaw: Manual Applied Force vs Automatic Virtual Force (inverted) (N)
0.04
0.02
0.00
−0.02
−0.04
0
5
10
15
20
25
30
35
40
45
50
55
60
65
70
75
Time (s)