Doc Number: 161310G00000-00	Doc Version: 008	Date: 30-Oct-2026

Super Mushshak Automatic Flight Test

Prepar3D v5 | Rahwali Airfield (OPRW) | Automatic Testing Mode

Super Mushshak Logger - ver. 1.0

Super Mushshak Airborne Automatic Testing Suite

Flight Test File: Super_Mushak_auto_takeoff_data_2026-10-30_14-27-31.csv


ONLINE, AUTOMATIC

Test Date: 30-Oct-2026 Test Time: 14:27:31


Initial Test Conditions


Validation	Sim	
***** Weight and Balance *****		
851.4	848.4	Gross Wt (kg)
112.2	109.3	Total Fuel Quantity (kg)
0.00	0.00	CG Pos in X Axis (mm)
0.00	0.00	CG Pos in Y Axis (mm)
***** Control Parameters *****		
-3.90	-6.43	Pitch Control Position (raw)
-6.06	-3.43	Roll Control Position (raw)
0.00	0.00	Rudder Pedal Position (raw)
80.0	80.0	Throttle Position (%)
-0.04	0.05	Pitch Stick Force (N)
0.00	0.01	Roll Stick Force (N)
0.00	0.00	Rudder Pedal Force (N)
***** Environment Parameters *****		
1013	1013	Baro Press (hPa)
11.4	13.8	OAT (deg C)
323.1	343.2	Wind Dir (mag,deg)
7.10	3.80	Wind Spd (kt)
***** Engine Parameters (Piston Engine) *****		
2698	2698	Engine Speed (RPM)
80.0	80.0	Throttle Position (%)
0.00	0.00	Fuel Flow (pph)
548.1	592.4	Exhaust Gas Temp (deg C)


Validation	Sim	
***** Flight Parameters *****		
80.0	80.0	Indicated Airspeed (kt)
83.5	81.5	Ground Speed (kt)
0.18	0.16	Mach Number (-)
3000	1366	Pressure Alt (ft)
2255	620.7	Radar Alt (ft)
750.0	750.0	Height of Terrain (ft)
7658	1480	Vertical Velocity (ft/min)
0.00	0.00	Pitch Angle (deg)
-0.00	-0.00	Bank Angle (deg)
48.4	48.4	Heading (deg)
1.10	1.50	Aircraft Angle of Attack (deg)
-1.12	-1.44	Sideslip Angle (deg)
0.07	300.6	Track Angle (deg)
0.00	0.00	Roll Rate (deg/s)
0.00	0.00	Pitch Rate (deg/s)
0.00	0.00	Yaw Rate (deg/s)
-0.75	-0.57	X Body Acceleration (g)
0.88	0.72	Y Body Acceleration (g)
-24.6	-1.15	Z Body Acceleration (g)



1st Quadrant Combined Group 1 (Airspeed, Climb, Altitude)
Indicated Airspeed (kts)
Manual Test (Reference)
Automatic Test (Sim)
POH Speed (80 kt)
Tolerance (±3 kt)
Time (s)
Rate of Climb/Descent (fpm)
Manual Test (Reference)
Automatic Test (Sim)
POH ROC (820 fpm)
Tolerance (±100 fpm)
Time (s)
Indicated Altitude (ft)
Manual Test (Reference)
Automatic Test (Sim)
Tolerance (-1000 ft)
Time (seconds)


1st Quadrant Combined Group 2 (Pitch, Bank, Yaw, Heading)
















1st Quadrant Combined Group 3 (Propeller, Engine, Throttle)








t Combined Group 4 (Position + Manual Applied Force vs Inverted Automatic V
Manual Test (Reference)
Automatic Test (Sim)
Joystick Pitch Position (mm)
Time (s)
Pitch: Manual Applied Force vs Automatic Virtual Force (inverted) (N)
Joystick Roll Position (mm)
Roll: Manual Applied Force vs Automatic Virtual Force (inverted) (N)


mbined Group 5 (Rudder Position + Manual Applied Force vs Inverted Automat
Manual Test (Reference)
Automatic Test (Sim)
Rudder Pedal Position (mm)
0.04
0.02
0.00
−0.02
−0.04
0
5
10
15
20
25
30
35
40
45
50
55
60
65
70
75
Time (s)
Manual Test (Reference)
Automatic Test (Sim)
Yaw: Manual Applied Force vs Automatic Virtual Force (inverted) (N)
0.04
0.02
0.00
−0.02
−0.04
0
5
10
15
20
25
30
35
40
45
50
55
60
65
70
75
Time (s)