

```

from sklearn.datasets import load_iris
iris = load_iris()
import numpy as np
import matplotlib.pyplot as plt
from sklearn.tree import DecisionTreeClassifier

n_classes = 3
plot_colors = "ryb"
plot_step = 0.02


for pairidx, pair in enumerate([[0, 1], [0, 2], [0, 3], [1, 2], [1, 3], [2, 3]]):
    X = iris.data[:, pair]
    y = iris.target
    clf = DecisionTreeClassifier().fit(X, y)
    plt.subplot(2, 3, pairidx + 1)
    x_min, x_max = X[:, 0].min() - 1, X[:, 0].max() + 1
    y_min, y_max = X[:, 1].min() - 1, X[:, 1].max() + 1
    xx, yy = np.meshgrid(
        np.arange(x_min, x_max, plot_step), np.arange(y_min, y_max, plot_step)
    )
    plt.tight_layout(h_pad=0.5, w_pad=0.5, pad=2.5)
    Z = clf.predict(np.c_[xx.ravel(), yy.ravel()])
    Z = Z.reshape(xx.shape)
    cs = plt.contourf(xx, yy, Z, cmap=plt.cm.RdYlBu)
    plt.xlabel(iris.feature_names[pair[0]])
    plt.ylabel(iris.feature_names[pair[1]])
    for i, color in zip(range(n_classes), plot_colors):
        idx = np.where(y == i)
        plt.scatter(
            X[idx, 0],
            X[idx, 1], c=color,
            label=iris.target_names[i], edgecolor="black",
            s=15)

plt.suptitle("Decision surface of decision trees trained on pairs of features")
plt.legend(loc="lower right", borderpad=0, handletextpad=0)
plt.axis("tight")

plt.figure()
clf = DecisionTreeClassifier().fit(iris.data, iris.target)
from sklearn.tree import plot_tree
plot_tree(clf, filled=True)
plt.title("Decision tree trained on all the iris features")
plt.show()

```

Decision surface of decision trees trained on pairs of features



Decision tree trained on all the iris features

