

Week-13-Passing Arrays and Strings to Functions: Attempt review | REC-CIS - Google Chrome

Not securehttp://www.rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=160363&cmid=406

REC-CIS

GE23131-Programming Using C-2024

Quiz navigation

1

2

3

Show one page at a time

Finish review

Status	Finished
Started	Tuesday, 14 January 2025, 12:11 PM
Completed	Tuesday, 14 January 2025, 12:19 PM
Duration	7 mins 42 secs

Question 1

Correct

Flag question

Given an array of numbers, find the index of the smallest array element (the pivot), for which the sums of all elements to the left and to the right are equal. The array may not be reordered.

Example

arr=[1,2,3,4,6]

- the sum of the first three elements, $1+2+3=6$. The value of the last element is 6.
- Using zero based indexing, arr[3]=4 is the pivot between the two subarrays.
- The index of the pivot is 3.

Function Description

Complete the function balancedSum in the editor below.

Type here to search

29°C13:5114-01-2025ENG

1

1

1



1

-

Week-13-Passing Arrays and Strings to Functions: Attempt review | REC-CIS - Google Chrome

Not secure http://www.rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=160363&cmid=406

REC-CIS

STDIN Function Parameters

4 → arr[] size n = 4

1 → arr = [1, 2, 3, 3]

2

3

3

Sample Output 0

2

Explanation 0

- The sum of the first two elements, $1+2=3$. The value of the last element is 3.
- Using zero based indexing, $arr[2]=3$ is the pivot between the two subarrays.
- The index of the pivot is 2.

Sample Case 1

Sample Input 1

STDIN Function Parameters

Type here to search

13:51
14-01-2025

REC-CIS

```

3  → arr[] size n = 3
1  → arr = [1, 2, 1]
2
1

```

Sample Output 1

1

Explanation 1

- The first and last elements are equal to 1.
- Using zero based indexing, arr[1]=2 is the pivot between the two subarrays.
- The index of the pivot is 1.

Answer: (penalty regime: 0 %)

Reset answer

```

1  /*
2  * Complete the 'balancedSum' function below.
3  *
4  * The function is expected to return an INTEGER.
5  * The function accepts INTEGER_ARRAY arr as parameter.
6  */

```

REC-CIS

```

6  */
7
8  int balancedSum(int n, int* a)
9  {int l=0,t=0;
10 for(int i=0;i<n;i++){
11     t+=a[i];
12 }
13 }
14 for(int i=0;i<n;i++){
15     t-=a[i];
16     if(l==t)
17         return i;
18     l+=a[i];
19 }
20 return 1;
21 }
22 }
23

```

	Test	Expected	Got	
✓	int arr[] = {1,2,3,3}; printf("%d", balancedSum(4, arr))	2	2	✓

Passed all tests! ✓

Question 2

Correct

Flag question

Calculate the sum of an array of integers.

Week-13-Passing Arrays and Strings to Functions: Attempt review | REC-CIS - Google Chrome

Not secure http://www.rajalakshmicolleges.org/moodle/mod/quiz/review.php?attempt=160363&cmid=406

REC-CIS

The sum is $3 + 13 + 4 + 11 + 9 = 40$.

Function Description

Complete the function arraySum in the editor below.

arraySum has the following parameter(s):

int numbers[n]: an array of integers

Returns

int: integer sum of the numbers array

Constraints

$1 \leq n \leq 10^4$
 $1 \leq \text{numbers}[i] \leq 10^4$

Input Format for Custom Testing

Input from stdin will be processed as follows and passed to the function.

The first line contains an integer n, the size of the array numbers.

Windows taskbar: Type here to search, 29°C, 13:52, 14-01-2025

1

1



1

1

REC-CIS

Sample Input 1

STDIN Function

2 → numbers[] size n = 2

12 → numbers = [12, 12]

12

Sample Output 1

24

Explanation 1

12 + 12 = 24.

Answer: (penalty regime: 0 %)

Reset answer

```
1  /*
2  * Complete the 'arraySum' function below.
3  *
4  * The function is expected to return an INTEGER.
5  * The function accepts INTEGER_ARRAY numbers as parameter.
6  */
```


REC-CIS

```

7
8 int arraySum(int n, int *a)
9 {
10     int s=0;
11     for(int i=0;i<n;i++){
12         s+=a[i];
13     }
14     return s;
15 }
16
17

```

	Test	Expected	Got	
✓	int arr[] = {1,2,3,4,5}; printf("%d", arraySum(5, arr))	15	15	✓

Passed all tests! ✓

Question 3

Correct

Flag question

Given an array of n integers. rearrange them so that the sum of the absolute differences of all adjacent elements is minimized. Then, compute the sum of those absolute differences. Example $n = 5$ arr = [1, 3, 3, 2, 4] If the list is rearranged as arr' = [1, 2, 3, 3, 4], the absolute differences are $|1 - 2| = 1$, $|2 - 3| = 1$, $|3 - 3| = 0$, $|3 - 4| = 1$. The sum of those differences is $1 + 1 + 0 + 1 = 3$. Function Description Complete the function minDiff in the editor below. minDiff has the following parameter: arr: an integer array Returns: int: the sum of the absolute differences of adjacent elements Constraints $2 \leq n \leq 105$ $0 \leq arr[i] \leq 109$, where $0 \leq i < n$ Input Format For Custom Testing The

absolute differences of adjacent elements Constraints $2 \leq n \leq 105$ $0 \leq arr[i] \leq 109$, where $0 \leq i < n$ Input Format For Custom Testing The first line of input contains an integer, n , the size of arr . Each of the following n lines contains an integer that describes $arr[i]$ (where $0 \leq i < n$). Sample Case 0 Sample Input For Custom Testing STDIN Function ----- 5 $\rightarrow arr[]$ size $n = 5$ 5 $\rightarrow arr[] = [5, 1, 3, 7, 3]$ 1 3 7 3 Sample Output 6 Explanation $n = 5$ $arr = [5, 1, 3, 7, 3]$ If arr is rearranged as $arr' = [1, 3, 3, 5, 7]$, the differences are minimized. The final answer is $|1 - 3| + |3 - 3| + |3 - 5| + |5 - 7| = 6$. Sample Case 1 Sample Input For Custom Testing STDIN Function ----- 2 $\rightarrow arr[]$ size $n = 2$ 3 $\rightarrow arr[] = [3, 2]$ 2 Sample Output 1 Explanation $n = 2$ $arr = [3, 2]$ There is no need to rearrange because there are only two elements. The final answer is $|3 - 2| = 1$.

Answer: (penalty regime: 0 %)

Reset answer

```
1  /*
2  * Complete the 'minDiff' function below.
3  *
4  * The function is expected to return an INTEGER.
5  * The function accepts INTEGER_ARRAY arr as parameter.
6  */
7
8  int minDiff(int n, int* a)
9  {
10     int s=0;
11     for(int i=0;i<n;i++){
12         for(int j=0;j<n;j++){
13             if(a[i]<a[j]){
14                 int temp=a[i];
15                 a[i]=a[j];
16                 a[j]=temp;
17             }
18         }
19     }
20     for(int i=0;i<n-1;i++){
21         s+=abs(a[i]-a[i+1]);
22     }
23     return s;
24 }
```



REC-CIS

```

10 int s=0;
11 for(int i=0;i<n;i++){
12     for(int j=0;j<n;j++){
13         if(a[i]<a[j]){
14             int temp=a[i];
15             a[i]=a[j];
16             a[j]=temp;
17         }
18     }
19 }
20 for(int i=0;i<n-1;i++){
21     s+=abs(a[i]-a[i+1]);
22 }
23 return s;
24 }
25 }
26 }
27 }
    
```

	Test	Expected	Got	
✓	int arr[] = {5, 1, 3, 7, 3}; printf("%d", minDiff(5, arr))	6	6	✓

Passed all tests! ✓

Finish review