OneCompiler Upg AI C++ Run Save L

Main.cpp

```cpp
#include <iostream>
#include <string>
using namespace std;

int main()
{
    int destination;
    char travel_class;
    double baggage, base_fare , multiplier = 1, free_bag
    double extra_charge = 0, total = 0, tax = 0, final_t
    string dest_name, class_name;
    cout << "ENTER DESTINATION (1 Dubai, 2 London, 3 New
    cin >> destination;
    cout << "ENTER CLASS (E, B, F)" << endl;
    cin >> travel_class;
    cout << "ENTER BAGGAGE WEIGHT (kg)" << endl;
    cin >> baggage;
    switch (destination)
    {
        case 1:
            dest_name = "Dubai"; base_fare = 60000; brea
        case 2:
            dest_name = "London"; base_fare = 150000; br
        case 3:
            dest_name = "New York"; base_fare = 200000;
```

Console I/O AI Agent

```
ENTER DESTINATION (1 Dubai, 2 London, 3 New York, 4 Istanbul)
4
ENTER CLASS (E, B, F)
F
ENTER BAGGAGE WEIGHT (kg)
40
DESTINATION: Istanbul
CLASS: First
TICKET FARE: 315000
EXTRA BAGGAGE CHARGE: 0
TAX: 37800
FINAL FARE: 352800
```

Ready Terminal Light Wiki Internet