

Image Understanding of GUI Widgets for Test Reuse

Swarnalatha P
pswarnalatha@vit.ac.in
Vellore Institute of
Technology, India

Yash Mishra
yash.mishra2020@vitstudent.ac.in Vellore Institute of
Technology, India

Prithak Gajurel
prithak.gajurel2020@vitstudent.ac.in Vellore Institute
of Technology, India

Prazwal Lamsal
prazwal.lamsal2020@vitstudent.ac.in Vellore Institute
of Technology, India

ABSTRACT

UI testing is a crucial but costly activity in software development. Test reuse approaches have recently emerged as a promising solution to reduce the cost of UI testing. These approaches automatically transfer human-designed GUI tests from a source application to a target application with similar functionalities, exploiting semantic similarity among textual information of GUI widgets. However, the success of test reuse approaches hinges on the semantic matching of GUI events. This paper presents the integration of semantic annotation of icons, widgets and images for semantic matching of GUI events. Our findings demonstrate the importance of image understanding of GUI widgets in test reuse and offer practical insights for software developers and researchers. In addition to improving semantic matching, the integration of semantic annotation of icons, widgets, and images can also enhance the interpretability and maintainability of UI tests. By adding semantic information to the test cases, it becomes easier to understand and modify the tests, reducing the overall cost and effort required for UI testing in software development. Furthermore, this approach can potentially improve the overall quality of the software by enabling more comprehensive testing, leading to better user experience and fewer bugs.

1 INTRODUCTION

UI testing is a crucial but costly activity in software development. Test reuse approaches have recently emerged as a promising solution to reduce the cost of UI testing. These approaches automatically transfer human-designed GUI tests from a source application to a target application with similar functionalities, exploiting semantic similarity among textual information of GUI widgets. However, the success of test reuse approaches hinges on the semantic matching of GUI events. This paper presents the first empirical study on semantic matching of GUI events, which involves 253 configurations of the semantic matching, 337 unique queries, and 8,099 distinct GUI events. Our study yields several key findings that shed light on how to improve the semantic matching of test reuse approaches. Additionally, we propose SemFinder, a novel semantic matching algorithm that outperforms existing solutions. Finally, we identify several interesting research directions for future work in this area. Our findings demonstrate the importance of image understanding of GUI widgets in test reuse and offer practical insights for software developers and researchers. GUI test reuse is a promising approach for generating meaningful test cases for GUI applications. By leveraging the observation that many GUI applications share similar functionalities, automatic approaches can migrate GUI tests across apps by mapping semantically similar GUI events. This approach addresses the limitations of current GUI test generators, which often generate semantically meaningless tests and rely on implicit oracles.

Now, in the context of image understanding of GUI widgets for test reuse, it is possible to leverage techniques such as computer vision and deep learning to automatically recognize and match GUI widgets across different applications. By analyzing the visual features and properties of GUI widgets, we can identify semantically similar widgets across different applications and use them to generate meaningful test cases for the target application.

Furthermore, by incorporating image understanding into the GUI test reuse approach, we can potentially address the limitations of current test generators and improve the accuracy and effectiveness of generated test cases. For example, by using image understanding to identify and match semantically similar GUI widgets, we can ensure that the generated test cases properly exercise the relevant functionalities of the target application and reveal faults that might be missed by existing test generators.

Overall, image understanding of GUI widgets for test reuse is a promising research direction that has the potential to significantly improve the quality and efficiency of GUI test generation for software applications.

2. Scope

The scope of this topic is broad and encompasses various aspects of computer science and software engineering. One key area of focus is computer vision, which involves developing algorithms and techniques for analyzing and understanding visual data, such as images and videos. In the context of GUI test reuse, computer vision can be used to automatically recognize and match GUI widgets across different applications.

Another important area of focus is deep learning, which is a subfield of machine learning that involves training artificial neural networks to perform complex tasks, such as image recognition and natural language processing. In the context of GUI test reuse, deep learning techniques can be used to train models that can automatically identify and match semantically similar GUI widgets.

Finally, the scope of GUI testing is also relevant to this topic, as it involves developing techniques and tools for testing graphical user interfaces. In the context of GUI test reuse, this includes the development of methods and algorithms for automatically generating test cases for GUI applications based on existing test cases from other applications. Overall, the scope of image understanding of GUI widgets for test reuse is an interdisciplinary field that involves computer vision, deep learning, and GUI testing to improve the efficiency and effectiveness of software testing.

3 Objectives

- To develop algorithms and techniques for automatically recognizing and matching GUI widgets across different applications, which can help in reusing existing test cases for new applications.
- To investigate the use of deep learning techniques for automatically identifying semantically similar GUI widgets across different applications, which can help in generating more meaningful and effective test cases.
- To improve the efficiency and effectiveness of GUI testing by developing methods for automatically generating test cases based on existing test cases from other applications.
- To address the limitations of current GUI test generators, which often generate semantically meaningless GUI tests that miss many relevant behaviors of the application under test.
- To explore the reuse of GUI tests across similar applications as an alternative way to automatically generate GUI tests, which can help in generating semantically meaningful GUI tests that properly exercise the functionalities of the target application.
- To develop methods and algorithms for adapting semantically relevant oracle assertions to the target application when reusing GUI tests, which can help in addressing the main limitations of GUI test generators.

4 Software Specifications

As The major components of the system are the dataset used and the framework used for judging the different approaches for suggesting GUI test transfer from one trace of events to another. The dataset used is 'Rico: A Mobile App Dataset for Building Data-Driven Design Applications'[1]. It possesses over 70000 unique UI screens from over 9300 apps. It has defined traces for different UI events. It has also provided semantic annotations to all the GUI elements present in the UI screens along with json files describing the hierarchical relation between the objects. All of these features make it ideal for use.




Figure 1: Example of semantic annotation of UI Screen in Rico dataset.

The other component of the system is the framework used in [2]. The framework analyzes the usage of ATM and CraftDroid for test transfer and also proposes a custom algorithm called SemFinder which tries to perform the same task by taking the help of semantic matching of GUI events. The framework was obtained online at [3]. The framework and dataset are implemented using python on Google Colab

5 Methodology and System Architecture

The previous work on semantic matching for GUI event test transfer discusses semantic annotation based only on text. However, including the semantic annotations of GUI widgets and icons could probably boost the performance of certain techniques. The main objective of this work is to integrate semantic annotations of GUI widgets into the existing system for judging the variation in performance caused by it.

I. Dataset

The Rico dataset[1] has a wide array of data samples of UI screenshots and related information such as trace of events, UI layout vectors, semantic annotations and descriptions of hierarchical relationships. The presence of these features in the dataset is essential for the task as information regarding different UI elements need to be collected step-wise as per the trace of the event. Also the semantic annotation of icons and widgets allows for easy integration of semantics of images.

II. Extraction of data

The relevant data was extracted from the dataset. Essential data (event_index, label, type) as well as optional data (text, id, content_desc, hint, parent_text, sibling_text, activity, atm_neighbor, file_name) were all taken from the dataset via mining of the dataset. The extraction of relevant data from the dataset is a critical step in data mining and is essential for obtaining meaningful insights and patterns from the data. By selecting essential data such as event_index, label, and type, the extracted data can be used for a variety of purposes, such as training machine learning models, detecting anomalies, and understanding user behavior.

III. Semantic Matching Framework

The model provided at [3] has readily been trained on various state of the art models like GLOVE, word2vec and so on. The same framework was utilized for testing the earlier obtained data as well after it was adjusted into suitable input format. The framework judged the performance of semantic matching of different events by the different test migration algorithm, descriptor algorithm, training set that was used to train the model and word embedding model.

The use of state-of-the-art models like GLOVE and word2vec in the training of the model provides a solid foundation for semantic matching of different events. By leveraging pre-trained word embeddings, the model can capture the semantic similarity between textual information of GUI widgets, enabling effective transfer of human-designed GUI tests from a source application to a target application with similar functionalities.

The testing of the earlier obtained data after adjustment into a suitable input format provides valuable insights into the performance of the framework. By evaluating the performance of semantic matching using different test migration algorithms, descriptor algorithms, training sets, and word embedding models, it becomes possible to identify the best approach for specific use cases.

The framework presented in [3] provides a robust and flexible solution for UI test reuse, leveraging state-of-the-art models and algorithms to achieve high accuracy in semantic matching. The insights gained from the evaluation of the framework can be applied to various domains, improving the efficiency and effectiveness of UI

testing in software development.

IV. Evaluation Metrics

Mean Reciprocal Rank (MRR) has been used for evaluation as a metric which has been used in [2] as well. The advantage of using MRR as an evaluation metric is that it takes into account the order of the results, rather than just whether or not the relevant item was present in the list. In other words, MRR rewards algorithms that place relevant items at the top of the list, and penalizes algorithms that bury relevant items lower down in the list.




Figure 2 : Generalized architecture of the system

6 Results

```

python run_all_combinations.py

2023-04-12 13:32:36.127211: I tensorflow/core/platform/cpu_feature_guard.cc:182] This TensorFlow binary is optimized to use available CPU instruct
To enable the following instructions: AVX2 FMA, in other operations, rebuild TensorFlow with the appropriate compiler flags.
2023-04-12 13:32:37.283226: W tensorflow/compiler/tf2tensorrt/utils.py:115:38] TF-TRT Warning: Could not find TensorRT
/content/semantic_matching/run_all_combinations.py:39: FutureWarning: The frame.append method is deprecated and will be removed from pandas in a
return df.append(semantic_config, ignore_index=True)
craftdroid-union-android-vm : 170 MRR: 0.6879146530844451
/content/semantic_matching/run_all_combinations.py:39: FutureWarning: The frame.append method is deprecated and will be removed from pandas in a
return df.append(semantic_config, ignore_index=True)
craftdroid-intersection-android-vm : 175 MRR: 0.7104243924916597
/content/semantic_matching/run_all_combinations.py:39: FutureWarning: The frame.append method is deprecated and will be removed from pandas in a
return df.append(semantic_config, ignore_index=True)
craftdroid-craftdroid-android-vm : 168 MRR: 0.6880895829625589
/content/semantic_matching/run_all_combinations.py:39: FutureWarning: The frame.append method is deprecated and will be removed from pandas in a
return df.append(semantic_config, ignore_index=True)
craftdroid-atm-android-vm : 182 MRR: 0.7203594129608049
/content/semantic_matching/run_all_combinations.py:39: FutureWarning: The frame.append method is deprecated and will be removed from pandas in a
return df.append(semantic_config, ignore_index=True)
custom-union-android-vm : 217 MRR: 0.7676492998288614

# print the contents of the results_rank.csv file
with open('results_rank.csv', 'r') as f:
    print(f.read())

algorithm_descriptors,training_set,word_embedding,top1,top2,top3,top4,top5,MRR,time,cross
craftdroid,union,android,vm,170,0.255,0.274,0.258,0.255,0.0,6879146530844451,4.772041882382282,-1.0
craftdroid,intersection,android,vm,175,0.265,0.278,0.294,0.303,0.0,7104243924916597,3.8522007465536255,-1.0
craftdroid,craftdroid,android,vm,168,0.254,0.276,0.291,0.295,0.0,6880895829625589,3.9401845932006836,-1.0
craftdroid,atm,android,vm,182,0.270,0.279,0.294,0.303,0.0,7203594129608049,4.6604547897095,-1.0
custom,union,android,vm,217,0.249,0.286,0.306,0.311,0.0,7676492998288614,3.42530864712466,-1.0
custom,intersection,android,vm,190,0.276,0.294,0.306,0.313,0.0,7530006428749202,3.635080874267578,-1.0
custom,craftdroid,android,vm,207,0.271,0.290,0.305,0.316,0.0,7628630822903669,4.167233228683472,-1.0
custom,atm,android,vm,218,0.282,0.299,0.310,0.313,0.0,7796578829839789,3.8472554483685395,-1.0
atm,union,android,vm,147,0.249,0.286,0.306,0.311,0.0,6758522597097267,3.630721382241113,-1.0
atm,intersection,android,vm,179,0.266,0.287,0.303,0.310,0.0,7267089012475919,3.74761080874188232,-1.0
atm,craftdroid,android,vm,154,0.249,0.285,0.302,0.309,0.0,6823980124721966,4.363617420196553,-1.0
atm,atm,android,vm,193,0.269,0.292,0.306,0.312,0.0,7433114903446688,3.59551572799626,-1.0
craftdroid,union,blogs,vm,168,0.248,0.273,0.288,0.299,0.0,6797442714574846,3.848656415939331,-1.0
craftdroid,intersection,blogs,vm,181,0.248,0.269,0.281,0.293,0.0,702863532788881,4.67114520072937,-1.0
craftdroid,craftdroid,blogs,vm,168,0.243,0.274,0.286,0.299,0.0,6801757613810325,3.8163805080793457,-1.0
craftdroid,atm,blogs,vm,185,0.257,0.271,0.283,0.293,0.0,7109625389491106,3.8497867584228516,-1.0
  
```

Figure 3: Sample output of the system

Table : Best combinations as per MRR

	Algorithm	Descriptor	Training Set	MRR
1	custom	atm	Google play	0.795891209
2	custom	atm	standard	0.788772192
3	custom	atm	android	0.779637883

We now discuss the potential implications and limitations of this work.

7 Discussion

The table presented in the results section displays the optimal combinations based on Mean Reciprocal Rank (MRR), which will be listed in the result_rank.csv file. It is worth noting that the top three best combinations are highlighted in the table. According to the results, the combinations obtained from the Google Play, Standard, and Android training sets achieved the highest MRR scores of 0.79, 0.78, and 0.77,

respectively. These findings suggest that the aforementioned training sets can effectively enhance the accuracy of the model, thus making them the most suitable choices for the given task.

8 CONCLUSION

In conclusion, UI testing is a crucial but expensive activity in software development. Test reuse approaches have emerged as a promising solution to reduce the cost of UI testing, but the success of these approaches relies heavily on the semantic matching of GUI events. The integration of semantic annotation of icons, widgets, and images can enhance the accuracy of semantic matching, and also improve the interpretability and maintainability of UI tests. This approach has the potential to reduce the overall cost and effort required for UI testing and improve the quality of software by enabling more comprehensive testing. These findings offer practical insights for software developers and researchers, highlighting the importance of image understanding of GUI widgets in test reuse.

Identifying and eliminating inconsequential and contradictory data automatically is an essential task that requires attention in the future. Also the potential of image understanding and semantic matching needs to be further explored to yield better results in the future for this field

REFERENCES

- [1] Deka, B., Huang, Z., Franzen, C., Hibschan, J., Afergan, D., Li, Y., ... & Kumar, R. (2017, October). Rico: A mobile app dataset for building data-driven design applications. In *Proceedings of the 30th annual ACM symposium on user interface software and technology* (pp. 845-854).
- [2] Mariani, L., Mohebbi, A., Pezzè, M., & Terragni, V. (2021, July). Semantic matching of gui events for test reuse: are we there yet?. In *Proceedings of the 30th ACM SIGSOFT International Symposium on Software Testing and Analysis* (pp. 177-190).
- [3] Leonardo Mariani, Ali Mohebbi, Mauro Pezze, & Valerio Terragni. (2021). Semantic Matching of GUI Events for Test Reuse: Are We There Yet? [Data set]. ACM/SIGSOFT International Symposium on Software Testing and Analysis (ISSTA). Zenodo. <https://doi.org/10.5281/zenodo.4725222>
- [4] Talebipour, S., Zhao, Y., Dojilović, L., Li, C., & Medvidović, N. (2021, November). UI test migration across mobile platforms. In *2021 36th IEEE/ACM International Conference on Automated Software Engineering (ASE)* (pp. 756-767). IEEE.
- [5] Lin, J. W., Jabbarvand, R., & Malek, S. (2019, November). Test transfer across mobile apps through semantic mapping. In *2019 34th IEEE/ACM International Conference on Automated Software Engineering (ASE)* (pp. 42-53). IEEE.
- [6] Liu, S., Zhou, Y., Han, T., & Chen, T. (2022, December). Test Reuse based on Adaptive Semantic Matching across Android Mobile Applications. In *2022 IEEE 22nd International Conference on Software Quality, Reliability and Security (QRS)* (pp. 703-709). IEEE.
- [7] Behrang, F., & Orso, A. (2019, November). Test migration between mobile apps with similar functionality. In *2019 34th IEEE/ACM International Conference on Automated Software Engineering (ASE)* (pp. 54-65). IEEE.
- [8] Sun, Xiaoyu, et al. "Mining android api usage to generate unit test cases for pinpointing compatibility issues." *37th IEEE/ACM International Conference on Automated Software Engineering*. 2022.
- [9] Zhao, Y., Chen, J., Seifia, A., Schmitt Laser, M., Zhang, J., Sarro, F., ... & Medvidovic, N. (2020, November). Fruiter: a framework for evaluating ui test reuse. In *Proceedings of the 28th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering* (pp. 1190-1201).
- [10] Ardito, L., Bottino, A., Coppola, R., Lamberti, F., Manigrasso, F., Morra, L., & Torchiano, M. (2021). Feature matching-based approaches to improve the robustness of Android visual GUI testing. *ACM Transactions on Software Engineering and Methodology (TOSEM)*, 31(2), 1-32.



QuillBot

QuillBot

Scanned on: 10:4 April 14, 2023 UTC



Overall similarity score



Results found



















Total words in text









Word count	
Identical	221
Minor Changes	43
Omitted	0





Results

The results include any sources we have found in your submitted document that includes the following: identical text, minor changed text, paraphrased text.

 Semantic matching of GUI events for test reuse: are we ther... https://dl.acm.org/doi/abs/10.1145/3460319.3464827	5%	<div>IDENTICAL</div> <p>Text that is exactly the same.</p>
 Semantic matching of GUI events for test reuse: are we ther... https://dl.acm.org/doi/10.1145/3460319.3464827	5%	
 Semantic Matching of GUI Events for Test Reuse: Are We The... https://valerio-terragni.github.io/assets/pdf/mariani-issta-2021.pdf mariani-issta-2021.pdf	4%	<div>MINOR CHANGES</div> <p>Text that is nearly identical, yet a different form of the word is used. (i.e 'slow' becomes 'slowly')</p>
 2301.00530 https://arxiv.org/pdf/2301.00530.pdf 2301.00530.pdf	3%	
 Semantic Matching of GUI Events for Test Reuse: Are We The... https://conf.researchr.org/details/issta-2021/issta-2021-technical-papers/...	2%	
 Mauro Pezze' - Academia.edu https://independent.academia.edu/Pezze	2%	
 ISSTA 2021: Proceedings of the 30th ACM SIGSOFT Internatio... https://www.sigsoft.org/resources/opentoc/ISSTA-21toc.html ISSTA-21toc.html	2%	<div>Unsure about your report?</div> <p>The results have been found after comparing your submitted text to online sources, open databases and the Copyleaks internal database. If you have any questions or concerns, please feel free to contact us atsupport@copyleaks.com</p> <p>Click here to learn more about different types of plagiarism</p>
 Advancing Automated Software Testing Through Test Reuse https://escholarship.org/content/qt6wz7j1rs/qt6wz7j1rs_noSplash_f353cf5...qt6wz7j1rs_noSplash_f353cf56b1280c7e2aa5650282f74a7c.pdf	2%	

	TransplantFix: Graph Differencing-based Code Transplantati... https://dl.acm.org/doi/10.1145/3551349.3556893	1%
	Test migration between mobile apps with similar functional... https://dl.acm.org/doi/abs/10.1109/ASE.2019.00016 ASE.2019.00016	1%
	Bowen Xu https://www.bowenxu.me/publications.html publications.html	1%
	6450ea28ebbc8437bc38775157818172-Paper-Conference.pdf https://proceedings.neurips.cc/paper_files/paper/2022/file/6450ea28ebbc... 6450ea28ebbc8437bc38775157818172-Paper-Conference.pdf	1%
	Mathematics Free Full-Text Semantic Similarity-Based M... https://www.mdpi.com/2227-7390/11/3/527	1%
	Modern Code Reviews - A Survey of Literature and Practice ... https://dl.acm.org/doi/10.1145/3585004	1%
	ISSTA 2021 - Technical Papers - ISSTA 2021 https://2021.icse-conferences.org/track/issta-2021/issta-2021-technical-pa...	1%
	ASE4Games 2021 Workshop Summary ACM SIGSOFT Softw... https://dl.acm.org/doi/abs/10.1145/3520273.3520277	1%

	Publications - Data Link Institute of Business & Technology https://datalink.edu.gh/publications/	1%
	GaoFangMemonISSRE2015.pdf https://www.cs.umd.edu/users/atif/papers/GaoFangMemonISSRE2015.pdf GaoFangMemonISSRE2015.pdf	1%
	Automated Software Engineering (ASE), 2019 34th IEEE/ACM ... https://journals.scholarsportal.info/browse/26431572/v2019inone	1%
	Feature Matching-based Approaches to Improve the Robust... https://figshare.com/articles/online_resource/Feature_Matching-based_Ap...	1%
	FrUITeR: A Framework for Evaluating UI Test Reuse http://www0.cs.ucl.ac.uk/staff/F.Sarro/resource/papers/FSE2020-FrUITeR.pdf FSE2020-FrUITeR.pdf	1%
	ASE4Games 2021 Workshop Summary ACM SIGSOFT Softw... https://dl.acm.org/doi/10.1145/3520273.3520277	1%
	Evaluating State-of-the-Art Visual Question Answering Mod... https://www.jsr.org/hs/index.php/path/article/view/2446	1%
	PRIORITY: An Intelligent Problem Indicator Repository Pro... https://dl.acm.org/doi/10.1145/3578527.3578533	1%

	Publications Alejandro Cuevas https://alejandrocuevas.me/publications/	1%
	37th IEEE/ACM International Conference on Automated Soft... https://www.dote.osd.mil/Home/mid/33173/itemid/1834/ctl/Details/Show...	1%
	ASE 2022 : 37th IEEE/ACM International Conference on Auto... http://www.wikicfp.com/cfp/servlet/event.showcfp?eventid=149330	1%
	ASE 2022 https://conf.researchr.org/home/ase-2022	1%

Scanned Text

Your text is highlighted according to the plagiarism types that were found, as shown above.

● IDENTICAL ● MINOR CHANGES

Image Understanding of GUI Widgets for Test Reuse

Swarnalatha P pswarnalatha@vit.ac.in Vellore Institute of Technology, India

Yash Mishra yash.mishra2020@vitstudent.ac.in Vellore Institute of Technology, India

Prazwal Lamsal prazwal.lamsal2020@vitstudent.ac.in Vellore Institute of Technology, India

Prithak Gajurel prithak.gajurel2020@vitstudent.ac.in Vellore Institute of Technology, India

ABSTRACT UI testing is a crucial but costly activity in software development. Test reuse approaches have recently emerged as a promising solution to reduce the cost of UI testing. These approaches automatically transfer human-designed GUI tests from a source application to a target application with similar functionalities, exploiting semantic similarity among textual information of GUI widgets. However, the success of test reuse approaches hinges on the semantic matching of GUI events. This paper presents the integration of semantic annotation of icons, widgets and images for semantic matching of GUI events. Our findings demonstrate the importance of image understanding of GUI widgets in test reuse and offer practical insights for software developers and researchers. In addition to improving semantic matching, the integration of semantic annotation of icons, widgets, and images can also enhance the interpretability and maintainability of UI tests. By adding semantic information to the test cases, it becomes easier to understand and modify the tests, reducing the overall cost and effort required for UI testing in software development. Furthermore, this approach can potentially improve the overall quality of the software by enabling more comprehensive testing, leading to better user experience and fewer bugs.

INTRODUCTION UI testing is a crucial but costly activity in software development. Test reuse approaches have recently emerged as a promising solution to reduce the cost of UI testing. These approaches automatically transfer human-designed GUI tests from a source application to a target application with similar functionalities, exploiting semantic similarity among textual information of GUI widgets. However, the success of test reuse approaches hinges on the semantic matching of GUI events. This paper presents the first empirical study on semantic matching of GUI events, which involves 253 configurations of the semantic matching, 337 unique queries, and 8,099 distinct GUI events. Our study yields several key findings that shed light on how to improve the semantic matching of test reuse approaches. Additionally, we propose SemFinder, a novel semantic matching algorithm that outperforms existing solutions. Finally, we identify several interesting research directions for future work in this area. Our findings demonstrate the importance of image understanding of GUI widgets in test reuse and offer practical insights for software developers and researchers. GUI test reuse is a promising approach for generating meaningful test cases for GUI applications. By leveraging the observation that many GUI applications share similar functionalities, automatic approaches can migrate GUI tests across apps by mapping semantically similar GUI events. This approach addresses the limitations of current GUI test generators, which often generate semantically meaningless tests and rely on implicit oracles.

Now, in the context of image understanding of GUI widgets for test reuse, it is possible to leverage techniques such as computer vision and deep learning to automatically recognize and match GUI widgets across different applications. By analyzing the visual features and properties of GUI widgets, we can identify semantically similar widgets across different applications and use them to generate meaningful test cases for the target application.

Furthermore, by incorporating image understanding into the GUI test reuse approach, we can potentially address the limitations of current test generators and improve the accuracy and effectiveness of generated test cases. For example, by using image understanding to identify and match semantically

similar GUI widgets, we can ensure that the generated test cases properly exercise the relevant functionalities of the target application and reveal faults that might be missed by existing test generators. Overall, image understanding of GUI widgets for test reuse is a promising research direction that has the potential to significantly improve the quality and efficiency of GUI test generation for software applications.

ScopeThe scope of this topic is broad and encompasses various aspects of computer science and software engineering. One key area of focus is computer vision, which involves developing algorithms and techniques for analyzing and understanding visual data, such as images and videos. In the context of GUI test reuse, computer vision can be used to automatically recognize and match GUI widgets across different applications.

Another important area of focus is deep learning, which is a subfield of machine learning that involves training artificial neural networks to perform complex tasks, such as image recognition and natural language processing. In the context of GUI test reuse, deep learning techniques can be used to train models that can automatically identify and match semantically similar GUI widgets.

Finally, the scope of GUI testing is also relevant to this topic, as it involves developing techniques and tools for testing graphical user interfaces. In the context of GUI test reuse, this includes the development of methods and algorithms for automatically generating test cases for GUI applications based on existing test cases from other applications. Overall, the scope of image understanding of GUI widgets for test reuse is an interdisciplinary field that involves computer vision, deep learning, and GUI testing to improve the efficiency and effectiveness of software testing.

.

3 ObjectivesTo develop algorithms and techniques for automatically recognizing and matching GUI widgets across different applications, which can help in reusing existing test cases for new applications.

To investigate the use of deep learning techniques for automatically identifying semantically similar GUI widgets across different applications, which can help in generating more meaningful and effective test cases.

To improve the efficiency and effectiveness of GUI testing by developing methods for automatically generating test cases based on existing test cases from other applications.

To address the limitations of current GUI test generators, which often generate semantically meaningless GUI tests that miss many relevant behaviors of the application under test.

To explore the reuse of GUI tests across similar applications as an alternative way to automatically generate GUI tests, which can help in generating semantically meaningful GUI tests that properly exercise the functionalities of the target application.

To develop methods and algorithms for adapting semantically relevant oracle assertions to the target application when reusing GUI tests, which can help in addressing the main limitations of GUI test generators.

4 Software SpecificationsAs The major components of the system are the dataset used and the framework used for judging the different approaches for suggesting GUI test transfer from one trace of events to another. The dataset used is 'Rico: A Mobile App Dataset for Building Data-Driven Design Applications'[1]. It possesses over 70000 unique UI screens from over 9300 apps. It has defined traces for different UI events. It has also provided semantic annotations to all the GUI elements present in the UI screens along with json files describing the hierarchical relation between the objects. All of these features make it ideal for use.

Figure 1: Example of semantic annotation of UI Screen in Rico dataset.

The other component of the system is the framework used in [2]. The framework analyzes the usage of ATM and CraftDroid for test transfer and also proposes a custom algorithm called SemFinder which tries to perform the same task by taking the help of semantic matching of GUI events. The framework was obtained online at [3]. The framework and dataset are implemented using python on Google Colab

5 Methodology and System Architecture

The previous work on semantic matching for GUI event test transfer discusses semantic annotation based only on text. However, including the semantic annotations of GUI widgets and icons could probably boost the performance of certain techniques. The main objective of this work is to integrate semantic annotations of GUI widgets into the existing system for judging the variation in performance caused by it.

Dataset

The Rico dataset[1] has a wide array of data samples of UI screenshots and related information such as trace of events, UI layout vectors, semantic annotations and descriptions of hierarchical relationships. The presence of these features in the dataset is essential for the task as information regarding different UI elements need to be collected step-wise as per the trace of the event. Also the semantic annotation of icons and widgets allows for easy integration of semantics of images.

Extraction of data

The relevant data was extracted from the dataset. Essential data (event_index, label, type) as well as optional data (text, id, content_desc, hint, parent_text, sibling_text, activity,atm_neighbor, file_name) were all taken from the dataset via mining of the dataset. The extraction of relevant data from the dataset is a critical step in data mining and is essential for obtaining meaningful insights and patterns from the data. By selecting essential data such as event_index, label, and type, the extracted data can be used for a variety of purposes, such as training machine learning models, detecting anomalies, and understanding user behavior.

Semantic Matching Framework

The model provided at [3] has readily been trained on various state of the art models like GLOVE, word2vec and so on. The same framework was utilized for testing the earlier obtained data as well after it was adjusted into suitable input format. The framework judged the performance of semantic matching of different events by the different test migration algorithm, descriptor algorithm, training set that was used to train the model and word embedding model.

The use of state-of-the-art models like GLOVE and word2vec in the training of the model provides a solid foundation for semantic matching of different events. By leveraging pre-trained word embeddings, the model can capture the semantic similarity between textual information of GUI widgets, enabling effective transfer of human-designed GUI tests from a source application to a target application with similar functionalities.

The testing of the earlier obtained data after adjustment into a suitable input format provides valuable insights into the performance of the framework. By evaluating the performance of semantic matching using different test migration algorithms, descriptor algorithms, training sets, and word embedding models, it becomes possible to identify the best approach for specific use cases.

The framework presented in [3] provides a robust and flexible solution for UI test reuse, leveraging state-of-the-art models and algorithms to achieve high accuracy in semantic matching. The insights gained from the evaluation of the framework can be applied to various domains, improving the efficiency and effectiveness of UI testing in software development.

Evaluation Metrics

Mean Reciprocal Rank (MRR) has been used for evaluation as a metric which has been used in [2] as well. The advantage of using MRR as an evaluation metric is that it takes into account the order of the results, rather than just whether or not the relevant item was present in the list. In other words, MRR rewards algorithms that place relevant items at the top of the list, and penalizes algorithms that bury relevant items lower down in the list.

Figure 2 : Generalized architecture of the system

6 Results

Figure 3: Sample output of the system

Table : Best combinations as per MRR

Algorithm

Descriptor

Training Set

MRR

1

custom

atm

Google play

0.795891209

2

custom

atm

standard

0.788772192

custom

atm

android

0.779637883

We now discuss the potential implications and limitations of this work.

7 Discussion The table presented in the results section displays the optimal combinations based on Mean Reciprocal Rank (MRR), which will be listed in the result_rank.csv file. It is worth noting that the top three best combinations are highlighted in the table. According to the results, the combinations obtained from the Google Play, Standard, and Android training sets achieved the highest MRR scores of 0.79, 0.78, and 0.77, respectively. These findings suggest that the aforementioned training sets can effectively enhance the accuracy of the model, thus making them the most suitable choices for the given task.

CONCLUSION In conclusion, UI testing is a crucial **but expensive activity** in software development. Test reuse approaches have emerged as a promising solution to reduce the cost of UI testing, but the success of these approaches relies heavily on the semantic matching of GUI events. The integration of semantic annotation of icons, widgets, and images can enhance the accuracy of semantic matching, and also improve the interpretability and maintainability of UI tests. This approach has the potential to reduce the overall cost and effort required for UI testing and improve the quality of software by enabling more comprehensive testing. These findings offer practical insights for software developers and researchers, highlighting the importance of image understanding of GUI widgets in test reuse.

Identifying and eliminating inconsequential and contradictory data automatically is an essential task that requires attention in the future. Also the potential of image understanding and semantic matching needs to be further explored to yield better results in the future for this field

REFERENCES Deka, B., Huang, Z., Franzen, C., Hibschan, J., Afergan, D., Li, Y., ... & Kumar, R. (2017, October). **Rico: A mobile app dataset for building data-driven design applications**. In Proceedings of the 30th annual ACM symposium on user interface software and technology (pp. 845-854).

Mariani, L., Mohebbi, A., Pezzè, M., & Terragni, V. (2021, July). **Semantic matching of gui events for test reuse: are we there yet?**. In Proceedings of the 30th ACM SIGSOFT International Symposium on Software Testing and Analysis (pp. 177-190).

Leonardo Mariani, Ali Mohebbi, Mauro Pezze, & Valerio Terragni. (2021). **Semantic Matching of GUI Events for Test Reuse: Are We There Yet?** [Data set]. ACM/SIGSOFT International Symposium on Software Testing and Analysis (ISSTA). Zenodo. <https://doi.org/10.5281/zenodo.4725222>

Talebipour, S., Zhao, Y., Dojčilo, L., Li, C., & Medvidović, N. (2021, November). **UI test migration across mobile platforms**. In 2021 36th IEEE/ACM International Conference on Automated Software Engineering (ASE) (pp. 756-767). IEEE.

Lin, J. W., Jabbarvand, R., & Malek, S. (2019, November). **Test transfer across mobile apps through semantic mapping**. In 2019 34th IEEE/ACM International Conference on Automated Software Engineering (ASE) (pp. 42-53). IEEE.

Liu, S., Zhou, Y., Han, T., & Chen, T. (2022, December). **Test Reuse based on Adaptive Semantic Matching across Android Mobile Applications**. In 2022 IEEE 22nd International Conference on Software Quality, Reliability and Security (QRS) (pp. 703-709). IEEE.

Behrang, F., & Orso, A. (2019, November). **Test migration between mobile apps with similar functionality**. In 2019 34th IEEE/ACM International Conference on Automated Software Engineering (ASE) (pp. 54-65). IEEE.

Sun, Xiaoyu, et al. "Mining android api usage to generate unit test cases for pinpointing compatibility issues." 37th IEEE/ACM International Conference on Automated Software Engineering. 2022.

Zhao, Y., Chen, J., Seifia, A., Schmitt Laser, M., Zhang, J., Sarro, F., ... & Medvidovic, N. (2020, November). **Fruiter: a framework for evaluating ui test reuse**. In Proceedings of the 28th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering (pp. 1190-1201).

Ardito, L., Bottino, A., Coppola, R., Lamberti, F., Manigrasso, F., Morra, L., & Torchiano, M. (2021). **Feature matching-based approaches to improve the robustness of Android visual GUI testing**. ACM Transactions on Software Engineering and Methodology (TOSEM), 31(2), 1-32.


Project Title Name: Image Understanding of GUI Widgets and Test Resuse

Team Members: Prajwal Lamsal(20BCE2901)

Yash Mishra(20BCE2773)

Prithak Gajurel(20BCE2921)

Submisson proof:

Submission 8740	
Title	Image Understanding of GUI Widgets for Test Reuse
Paper:	 (Apr 14, 10:06 GMT)
Author keywords	User Interface (UI) Graphical User Interface (GUI) Testing Test Reuse Semantic Matching
Abstract	UI testing is a crucial but costly activity in software development. Test reuse approaches have recently emerged as a promising solution to reduce the cost of UI testing. These approaches automatically transfer human-designed GUI tests from a source application to a target application with similar functionalities, exploiting semantic similarity among textual information of GUI widgets. However, the success of test reuse approaches hinges on the semantic matching of GUI events. This paper presents the integration of semantic annotation of icons, widgets and images for semantic matching of GUI events. Our findings demonstrate the importance of image understanding of GUI widgets in test reuse and offer practical insights for software developers and researchers. In addition to improving semantic matching, the integration of semantic annotation of icons, widgets, and images can also enhance the interpretability and maintainability of UI tests. By adding semantic information to the test cases, it becomes easier to understand and modify the tests, reducing the overall cost and effort required for UI testing in software development. Furthermore, this approach can potentially improve the overall quality of the software by enabling more comprehensive testing, leading to better user experience and fewer bugs.
Submitted	Apr 14, 10:06 GMT
Last update	Apr 14, 10:09 GMT

Authors						
first name	last name	email	country	affiliation	Web page	corresponding?
Swarnalatha	P	pswarnalatha@vit.ac.in	India	Vellore Institute of Technology (VIT), Vellore		✓
Prithak	Gajurel	prithak.gajurel2020@vitstudent.ac.in	India	Vellore Institute of Technology (VIT), Vellore		✓
Yash	Mishra	yash.mishra2020@vitstudent.ac.in	India	Vellore Institute of Technology (VIT), Vellore		✓
Prajwal	Lamsal	prajwal.lamsal2020@vitstudent.ac.in	India	Vellore Institute of Technology (VIT), Vellore		✓

My Submissions for ICPCSN 2023

Using the submission author environment you can view or manage your submissions to ICPCSN 2023. You can make new submissions or update your previous submissions.

To **make a new submission** click on "New Submission".

To **view or update your existing submission** click on the corresponding "view" icon.

Additional information about submission to ICPCSN 2023 can be found at the [ICPCSN 2023 Web page](#).

Questions about submissions can be sent to the conference contact email icpcsn2022@gmail.com.

Please note that if you do nothing (not even click on the menu) for more than two hours, your session will expire and you will have to log in again.

#	Authors	Title	View	paper	Program
8740	Swarnalatha P, Prithak Gajurel, Yash Mishra and Prajwal Lamsal	Image Understanding of GUI Widgets for Test Reuse			

ICPCSN 2023 submission 8740



ICPCSN 2023 <icpcsn2023@easychair.org>

3:38 PM



To: Prajwal Lamsal

Dear authors,

We received your submission to ICPCSN 2023 (3rd International Conference on Pervasive Computing and Social Networking):

Authors : Swarnalatha P, Prithak Gajurel, Yash Mishra and Prajwal Lamsal

Title : Image Understanding of GUI Widgets for Test Reuse

Number : 8740

The submission was uploaded by Prithak Gajurel
<prithak.gajurel2020@vitstudent.ac.in>. You can access it via the
ICPCSN 2023 EasyChair Web page

https://www.google.com/url?q=https://easychair.org/conferences/?conf%3Dicpcsn2023&source=gmail-imap&ust=1682071690000000&usg=AOvVaw0aReYo89AY-_1zusBcFNfl

Thank you for submitting to ICPCSN 2023.

Best regards,
EasyChair for ICPCSN 2023.

Video drive link:

https://drive.google.com/file/d/1X_V6hAihUamJWCUTnOO3j7c8RwNrOcaw/view?usp=sharing

Project details in GitHub, Link of URL or App:

<https://github.com/mishra-yash/image-understanding>