

AC-Powered Outdoor FAB (Fujitsu Access Business) Cabinet




PC01B-0040-A327


Cabinet Equipped with:

- 1 RU Eltek Valere rectifier shelf
- Heat exchanger
- GFCI convenience outlet
- VRLA battery support (heater pad optional)
- Accommodate up to
- Temperature-hardened 10/100/1000 Ethernet support (R8.1)
- Single door w/pivoting equipment frame
 - Full front and rear access
- Cabinet dimensions (H x W x D):
 - 39.8 x 25 x 20" (1011 x 635 x 508 mm)
- Cabinet weight:
 - 143 lb (65kg) installation weight
 - 322 lb (146 kg) loaded w/cards and batteries
- GR-487-CORE compliant:
 - -40 to +115 °F (-40 to +46 °C) with solar load
- H-frame or outdoor wall-mountable
 - Pad/pole mount options available (ordered separately)
- Power requirement: 120 VAC @ 15 amps


Isometric View





Equipment View




Internal View



Interior Frame Pivot Detail





**Conduit Locations
(Underside View)**



Cable Entrances

Cabinet Block Diagram



Optional Equipment

Part Number	Description	Ordering Notes
Rectifiers / Power		
PC15L-0001-C082#08	12 Amp Rectifier Modules (CLEI: PBP3A01AAA)	Two Required
PC660-0106-T002	Generator Cable	
Battery		
06-857-000	EnerSys® SBS B14F 62 Ah VRLA Battery	One Required
06-852-000	EnerSys® SBS B11F 92 Ah VRLA Battery String	One Required
PC21L-0001-T027#05	Battery Strap	
PC21L-0001-T024#03	Battery Heater Pad – Twist Lock	
Fiber		
PC15L-0001-C061#05	24 Pos Fiber Management Panel – SC adapter only	
PC15L-0001-C061#11	Mini Splice Tray, Mass Fusion	For 12 ribbon fiber
PC15L-0001-C061#12	Fiber Ribbon pigtail	12 fiber
PC15L-0001-C061#13	Fiber Bundle pigtail	12 fiber
PC15L-0001-C061#10	Mini Splice Tray, Heat Shrink	For 12 bundle fiber
Mounting Kit/ Equipment		
PC21L-0001-T024#02	Pad Mount Plinth with Template	
PC21L-0001-T027#04	Pole Mount Kit	