

# UCB Momentum Q-learning: Correcting the bias without forgetting

Pierre Ménard<sup>1</sup>, Omar Darwiche Domingues<sup>2,3</sup>, Xuedong Shang<sup>2,3</sup>, Michal Valko<sup>4</sup>

<sup>1</sup>OvGU <sup>2</sup>Inria <sup>3</sup>Université de Lille <sup>4</sup>DeepMind



# Markov Decision Process (MDP)

**Tabular, episodic MDP:**  $H$  horizon,  $S$  states,  $A$  actions.

**Learning in MDP:** at episode  $t$ , step  $h$

- state  $s_h^t$
- action  $a_h^t$
- next state  $s_{h+1}^t \sim p_h(\cdot | s_h^t, a_h^t)$
- reward  $r_h(s_h^t, a_h^t)$  (known)

**Bellman equation** policy  $\pi$

$$Q_h^\pi(s, a) = (r_h + p_h V_{h+1}^\pi)(s, a)$$

$$V_h^\pi(s) = Q_h^\pi(s, \pi_h(s))$$

$$V_{H+1}^\pi(s) = 0$$

where  $p_h f = \sum_{s'} p_h(s' | s, a) f(s')$

# Markov Decision Process (MDP)

**Tabular, episodic MDP:**  $H$  horizon,  $S$  states,  $A$  actions.

**Learning in MDP:** at episode  $t$ , step  $h$

- state  $s_h^t$
- action  $a_h^t$
- next state  $s_{h+1}^t \sim p_h(\cdot | s_h^t, a_h^t)$
- reward  $r_h(s_h^t, a_h^t)$  (known)

**Optimal Bellman equation**

$$Q_h^*(s, a) = (r_h + p_h V_{h+1}^*)(s, a)$$

$$V_h^*(s) = \max_a Q_h^*(s, a)$$

$$V_{H+1}^*(s) = 0$$

where  $p_h f = \sum_{s'} p_h(s' | s, a) f(s')$

**Regret** after  $T$  episodes:  $R^T = \sum_{t=1}^T V_1^*(s_1) - V_1^{\pi^t}(s_1)$

# Regret minimization

**Lower bound**  $\mathbb{E}[R^T] \geq \Omega(\sqrt{H^3 SAT})$  [?, ?]

**Typical regret bound**  $R^T \leq \tilde{O}(\sqrt{H^3 SAT} + \text{poly}(H)S^2A)$

→ optimal bound only for  $T \geq \text{poly}(H)S^2A$ , bad when  $S$  large, continuous...

→ non-trivial bound i.e.  $R^T \leq TH$ , for  $\text{poly}(H)S$  samples per state-actions

Algorithm	Upper bound
UCBVI [?]	$\tilde{O}(\sqrt{H^3 SAT} + H^3 S^2 A)$
UBEV [?]	$\tilde{O}(\sqrt{H^4 SAT} + H^2 S^3 A^2)$
EULER [?]	$\tilde{O}\left(\sqrt{H^3 SAT} + H^3 S^{3/2} A(\sqrt{S} + \sqrt{H})\right)$
OptQL [?] (Bernstein)	$\tilde{O}(\sqrt{H^4 SAT} + H^{9/2} S^{3/2} A^{3/2})$
UCB-Advantage [?]	$\tilde{O}(\sqrt{H^3 SAT} + H^{33/4} S^2 A^{3/2} T^{1/4})$

# Regret minimization

**Lower bound**  $\mathbb{E}[R^T] \geq \Omega(\sqrt{H^3 SAT})$  [?, ?]

**Wanted regret bound**  $R^T \leq \tilde{O}(\sqrt{H^3 SAT} + \text{poly}(H)SA)$

→ optimal bound only for  $T \geq \text{poly}(H)SA$

→ non-trivial bound i.e.  $R^T \leq TH$ , for  $\text{poly}(H)$  samples per state-actions

**Question:** Regret **first order optimal** (in  $T$ ) and at most **linear** in  $S$ ?

Algorithm	Upper bound
UCBVI [?]	$\tilde{O}(\sqrt{H^3 SAT} + H^3 S^2 A)$
UBEV [?]	$\tilde{O}(\sqrt{H^4 SAT} + H^2 S^3 A^2)$
EULER [?]	$\tilde{O}(\sqrt{H^3 SAT} + H^3 S^{3/2} A(\sqrt{S} + \sqrt{H}))$
OptQL [?] (Bernstein)	$\tilde{O}(\sqrt{H^4 SAT} + H^{9/2} S^{3/2} A^{3/2})$
UCB-Advantage [?]	$\tilde{O}(\sqrt{H^3 SAT} + H^{33/4} S^2 A^{3/2} T^{1/4})$

# Regret minimization

**Lower bound**  $\mathbb{E}[R^T] \geq \Omega(\sqrt{H^3 SAT})$  [?, ?]

**Wanted regret bound**  $R^T \leq \tilde{O}(\sqrt{H^3 SAT} + \text{poly}(H)SA)$

→ optimal bound only for  $T \geq \text{poly}(H)SA$

→ non-trivial bound i.e.  $R^T \leq TH$ , for  $\text{poly}(H)$  samples per state-actions

**Question:** Regret first order optimal (in  $T$ ) and at most linear in  $S$ ? Yes!

Algorithm	Upper bound
UCBVI [?]	$\tilde{O}(\sqrt{H^3 SAT} + H^3 S^2 A)$
UBEV [?]	$\tilde{O}(\sqrt{H^4 SAT} + H^2 S^3 A^2)$
EULER [?]	$\tilde{O}(\sqrt{H^3 SAT} + H^3 S^{3/2} A(\sqrt{S} + \sqrt{H}))$
OptQL [?] (Bernstein)	$\tilde{O}(\sqrt{H^4 SAT} + H^{9/2} S^{3/2} A^{3/2})$
UCB-Advantage [?]	$\tilde{O}(\sqrt{H^3 SAT} + H^{33/4} S^2 A^{3/2} T^{1/4})$
UCBMQ (this paper)	$\tilde{O}(\sqrt{H^3 SAT} + H^4 SA)$

# Algorithms

**Principle**  $a_h^n \in \operatorname{argmax}_a \bar{Q}_h^n(s, a)$ , act greedily with respect to upper confidence bound on the optimal Q-values  $Q^*$

If  $p_h$  is known: dynamic Q-value iteration

$$\bar{Q}_h^n(s, a) = (r_h + p_h \bar{V}_h^{n-1})(s, a) \quad \bar{V}_h^n(s) = \max_a \bar{Q}_h^n(s, a)$$

# Algorithms

**Principle**  $a_h^n \in \operatorname{argmax}_a \bar{Q}_h^n(s, a)$ , act greedily with respect to upper confidence bound on the optimal Q-values  $Q^*$

If  $p_h$  is known: dynamic Q-value iteration

$$\bar{Q}_h^n(s, a) = (r_h + p_h \bar{V}_h^{n-1})(s, a) \quad \bar{V}_h^n(s) = \max_a \bar{Q}_h^n(s, a)$$

If  $p_h$  unknown, approximate the expectation with samples: Q-learning

$$Q_h^n(s, a) = \alpha_n (r_h + p_h^n \bar{V}_h^{n-1})(s, a) + (1 - \alpha_n) Q_h^{n-1}(s, a)$$
$$\bar{Q}_h^n(s, a) = Q_h^n(s, a) + b_h^n(s, a) \quad \bar{V}_h^n(s) = \max_a \bar{Q}_h^n(s, a)$$

where the sample expectation  $(p_h^n f)(s, a) = f(s_{h+1}^n)$



# Algorithms

**Principle**  $a_h^n \in \operatorname{argmax}_a \bar{Q}_h^n(s, a)$ , act greedily with respect to upper confidence bound on the optimal Q-values  $Q^*$

If  $p_h$  is known: dynamic Q-value iteration

$$\bar{Q}_h^n(s, a) = (r_h + p_h \bar{V}_h^{n-1})(s, a) \quad \bar{V}_h^n(s) = \max_a \bar{Q}_h^n(s, a)$$

If  $p_h$  unknown, approximate the expectation with samples: Q-learning

$$Q_h^n(s, a) = \alpha_n (r_h + p_h^n \bar{V}_h^{n-1})(s, a) + (1 - \alpha_n) Q_h^{n-1}(s, a)$$
$$\bar{Q}_h^n(s, a) = Q_h^n(s, a) + b_h^n(s, a) \quad \bar{V}_h^n(s) = \max_a \bar{Q}_h^n(s, a)$$

where the sample expectation  $(p_h^n f)(s, a) = f(s_{h+1}^n)$

How to choose the learning rate  $\alpha_n$  and the bonus  $b_h^n$ ?

# Q-learning

learning rate  $\alpha_n \approx 1/n$ , unfolding the formula for  $Q_h^n$  + Hoeffding inequality

$$\begin{aligned} Q_h^n(s, a) &\approx r_h(s, a) + \frac{1}{n} \sum_{i=1}^n p_h^i \bar{V}_{h+1}^{i-1}(s, a) \\ &\approx r_h(s, a) + p_h \underbrace{\left( \frac{1}{n} \sum_{i=1}^n \bar{V}_{h+1}^{i-1} \right)}_{:= V_{h,s,a}^n \text{ bias-value function}}(s, a) \pm \underbrace{\sqrt{\frac{H^2}{n}}}_{\text{variance term} \rightarrow \text{bonus}} \end{aligned}$$

→ **no  $S$  to pay** for passing from sample average  $p_h^i$  to true transition  $p_h$

→ **uniform average** over the past targets  $\bar{V}_{h+1}^{i-1}$ : bound exponential in  $H$

# Q-learning

learning rate  $\alpha_n \approx H/n$  (OptQL [?])

$$\begin{aligned} Q_h^n(s, a) &\approx r_h(s, a) + \frac{H}{n} \sum_{i \geq n-H/n}^n p_h^i \bar{V}_{h+1}^{i-1}(s, a) \\ &\approx r_h(s, a) + p_h \underbrace{\left( \frac{H}{n} \sum_{i \geq n-H/n}^n \bar{V}_{h+1}^{i-1} \right)}_{:= V_{h,s,a}^n \text{ bias-value function}}(s, a) \pm \underbrace{\sqrt{\frac{H^3}{n}}}_{\text{variance term}}. \end{aligned}$$

→ keep only the last  $H/n$  fraction of the past targets: bound polynomial in  $H$

→ only  $n/H$  samples in the average: extra  $H$  in the bonus

# UCB Momentum Q-learning

**Idea** Add a (negative) momentum to correct the bias [?]

learning rate  $\alpha_n \approx 1/n$  and momentum rate  $\gamma_n \approx H/n$ : UCBMQ

$$Q_h^n(s, a) = \alpha_n(r_h + p_h^n \bar{V}_{h+1}^{n-1})(s, a) + (1 - \alpha_n)Q_h^{n-1}(s, a) \\ + \underbrace{\gamma_n p_h^n (\bar{V}_{h+1}^{n-1} - V_{h,s,a}^{n-1})(s, a)}_{\leq 0, \text{ momentum}}$$

where the bias-value function

$$V_{h,s,a}^n(s') = (\alpha_n + \gamma_n) \bar{V}_{h+1}^{n-1}(s') + (1 - \alpha_n - \gamma_n) V_{h,s,a}^{n-1}(s') \\ \approx \frac{H}{n} \sum_{i \geq n-n/H}^n \bar{V}_{h+1}^{i-1}(s')$$

# UCB Momentum Q-learning

$$\begin{aligned}
 Q_h^n(s, a) &\approx r_h(s, a) + \frac{1}{n} \sum_{i=1}^n p_h^i \left( (H+1) \bar{V}_{h+1}^{i-1} - V_{s,a,h}^{i-1} \right) (s, a) \\
 &\approx r_h(s, a) + p_h \underbrace{\left( \frac{H}{n} \sum_{i \geq n-n/H}^n \bar{V}_h^{i-1} \right)}_{\approx V_{h,s,a}^n \text{ bias-value function}} (s, a) \pm \underbrace{\sqrt{\frac{H^2}{n}}}_{\text{variance term}} \\
 &\quad \pm \underbrace{\sqrt{\frac{H^3}{n} \sum_{i=1}^n p_h (V_{h,s,a}^{n-1} - \bar{V}_h^{n-1})(s, a) \frac{1}{n}}}_{\text{momentum variance term}}.
 \end{aligned}$$

→ keep only the last  $H/n$  fraction of the past targets: bound polynomial in  $H$

→  $n$  samples to approximate the mean

→ still an extra  $H$  in the bonus → Bernstein inequality instead of Hoeffding

# UCBMQ algorithm

**Regret bound** w.h.p.

$$R^T \leq \tilde{\mathcal{O}}(\sqrt{H^3 SAT} + H^4 SA)$$

**Time complexity** per episode  
 $\mathcal{O}(HS)$








**Space complexity**  $\mathcal{O}(HS^2A)$  (bias  
value function per state-action)  
Model-free vs model-based?

## Open problem

- linear in  $S$  regret bound for model-based algorithms? (UCBVI  
 $\tilde{\mathcal{O}}(\sqrt{H^3 SAT} + H^3 S^2 A)$ )
- Algorithm with bound  $\tilde{\mathcal{O}}(\sqrt{H^3 SAT} + H^2 SA)$ ?
- With time complexity  $\mathcal{O}(H)$  per episode and space complexity  $\mathcal{O}(HSA)$ ?

Thank you!

# Bibliography I

-  Azar, M. G., Munos, R., Ghavamzadeh, M., and Kappen, H. J. (2011). [Speedy Q-learning](#). In [Advances in Neural Information Processing Systems 24 \(NIPS\)](#), pages 2411–2419.
-  Azar, M. G., Osband, I., and Munos, R. (2017). [Minimax regret bounds for reinforcement learning](#). In [Proceedings of the 34th International Conference on Machine Learning \(ICML\)](#), pages 405–433.
-  Dann, C., Lattimore, T., and Brunskill, E. (2017). [Unifying PAC and regret: Uniform PAC bounds for episodic reinforcement learning](#). In [Advances in Neural Information Processing Systems 30 \(NIPS\)](#), pages 5714–5724.
-  Domingues, O. D., Ménard, P., Kaufmann, E., and Valko, M. (2021). [Episodic reinforcement learning in finite MDPs: Minimax lower bounds revisited](#). In [Proceedings of the 32nd International Conference on Algorithmic Learning Theory \(ALT\)](#).
-  Jin, C., Allen-Zhu, Z., Bubeck, S., and Jordan, M. I. (2018). [Is Q-learning provably efficient?](#) In [Advances in Neural Information Processing Systems 31 \(NeurIPS\)](#), pages 4863–4873.
-  Zanette, A. and Brunskill, E. (2019). [Tighter problem-dependent regret bounds in reinforcement learning without domain knowledge using value function bounds](#). In [Proceedings of the 36th International Conference on Machine Learning \(ICML\)](#), pages 12676–12684.
-  Zhang, Z., Zhou, Y., and Ji, X. (2020). [Almost optimal model-free reinforcement learning via reference-advantage decomposition](#). [arXiv preprint arXiv:2004.10019](#).