



Cisco Packet Tracer

File Edit Options View Tools Extensions Window Help

Logical Physical x 100 y 115

PC0

Command Prompt

```
Cisco Packet Tracer PC Command Line 1.0
C:\>ping 192.168.0.2

Pinging 192.168.0.2 with 32 bytes of data:

Request timed out.
Reply from 192.168.0.2: bytes=32 time=1ms TTL=255
Reply from 192.168.0.2: bytes=32 time=1ms TTL=255
Reply from 192.168.0.2: bytes=32 time=1ms TTL=255

Ping statistics for 192.168.0.2:
    Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
    Approximate round trip times in milliseconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms
C:\>ping 192.168.0.3

Pinging 192.168.0.3 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 192.168.0.3:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),
C:\>
```

Time: 00:07:00

Realtime Simulation

Активация Windows
Чтобы активировать Windows, перейдите в раздел "Параметры".

Cisco Packet Tracer

File Edit Options View Tools Extensions Window Help

Logical Physical x 100 y 115

Switch0

IOS Command Line Interface

```
Switch0#
Switch0# configure terminal
Switch0(config)#
Switch0(config)# interface FastEthernet0/1
Switch0(config-if)# no shutdown
Switch0(config-if)#
Switch0#
Switch0# configure terminal
Switch0(config)#
Switch0(config)# interface FastEthernet0/2
Switch0(config-if)# no shutdown
Switch0(config-if)#
Switch0#
Switch0# configure terminal
Switch0(config)#
Switch0(config)# interface Vlan1
Switch0(config-if)# no shutdown
Switch0(config-if)#
Switch0#
Switch0# configure terminal
Switch0(config)#
Switch0(config)# ip address 192.168.0.2 255.255.255.0
Switch0(config-if)#
Switch0#
Switch0# configure terminal
Switch0(config)#
Switch0(config)# line vty 0 4
Switch0(config-line)# password 123
Switch0(config-line)# login
Switch0#
```

Time: 00:07:56

Realtime Simulation

Активация Windows
Чтобы активировать Windows, перейдите в раздел "Параметры".

