

**UnB**

MIT Digital Currency Initiative and the University of Brasilia presents

# Cryptocurrency Design and Engineering

Lecture 12: Scalability  
Taught by: Neha Narula  
October 21st, 2025  
MAS.S62

---

# First half of today

- Motivation: transaction throughput
- What is scalability?
- On-chain scaling and challenges
- Payment channels
- The Lightning Network

# Motivation: transaction throughput

System	Throughput
Bitcoin	7 txs/sec
Ethereum	15-30 txs/sec
Solana	3,200 txs/sec
PostgreSQL r5.4xlarge	5,700 txs/sec
Visa	24,000 txs/sec



[tokenterminal.com/explorer/projects/solana/metrics/transactions-per-second](https://tokenterminal.com/explorer/projects/solana/metrics/transactions-per-second)

[docs.aws.amazon.com/whitepapers/latest/optimizing-postgresql-on-ec2-using-ebs/postgresql-benchmark-observations-and-considerations.html](https://docs.aws.amazon.com/whitepapers/latest/optimizing-postgresql-on-ec2-using-ebs/postgresql-benchmark-observations-and-considerations.html)

# What is scalability?

- More transactions per second?
- Cheaper fees?
- Lower latency?
- All of the above?

Scalability is when you can add more resources to get more good work done



Every new node still  
has to do the same  
work (validating the  
chain), again

More resources  
don't lead to  
additional good work

# Ways to add more resources

- Vertical scaling
  - Get a more powerful computer
- Horizontal scaling
  - Add more {cores, computers} and parallelize the work

# Vertical scaling

- 4MB blocks every 10 minutes: hardcoded. Why? Could we just change these limits?
  - Block size wars
  - Ethereum: gas limit, 12 sec block time
- Tension with decentralization
  - More expensive to run a fully validating node
  - Longer to validate leads to more orphans which leads to mining centralization

Market incentives  
lecture on  
November 18<sup>th</sup>!

# Horizontal scaling techniques

- Sharding: not everyone validates everything
- Verifiable computation: prover / verifiers
- Batched verification: payment channels

# First half of today

- Motivation: transaction throughput
- What is scalability?
- On-chain scaling and challenges
- **Payment channels**
- The Lightning Network

# Payment channels: basic idea

- Alice repeatedly buys coffee from Bob, who runs a coffeeshop
- Alice can run up a bar tab
  - Alice deposits .005 BTC in the tab
  - Every day, Alice buys coffee
  - At the end of the month, settle the tab between Alice and Bob
- Collapses 30 payments ☐ 2 on-chain transactions!

# Channel setup

(1) Alice creates,  
shows to Bob

Funding tx

Alice txid:index (.005 BTC)	Alice & Bob .005
--------------------------------	---------------------

Refund tx

	Alice .005
Locktime: 1 month	



# Channel setup

(1) Alice creates,  
shows to Bob

Funding tx

Alice txid:index (.005 BTC)	Alice & Bob .005
--------------------------------	---------------------

Refund tx

Bob sig	Alice .005
Locktime: 1 month	

(2) Bob  
signs, Alice  
holds

# Channel setup

(1) Alice creates,  
shows to Bob

Funding tx

Alice txid:index (.005 BTC)	Alice & Bob .005
Alice sig	


(3) Alice signs and gets this  
confirmed on chain

Refund tx

Bob sig	Alice .005
Locktime: 1 month	

(2) Bob  
signs, Alice  
holds

# Many payments Alice --> Bob




## Refund tx 1

Funding tx	Alice .0049
	Bob .0001
Locktime: 29 days	


time




# Many payments Alice --> Bob




# Many payments Alice --> Bob



# Bob closes the payment channel



# Alice maliciously closes the channel



# Bidirectional channels

- Previous payment channels only allowed one-way payments (Alice to Bob)
- Can we do two-way?
  - Yes!
- Similar idea. Differences:
  - Both sides fund the channel
  - Revoke old states explicitly


# Bidirectional channel setup

## Funding tx

Alice txid:index (1 BTC)	Alice & Bob 2 BTC
Bob txid:index (1 BTC)	

## Alice's commitment tx

Bob sig	Bob 1 BTC
	Bob & <b>secret</b> OR Alice & 10 blocks 1 BTC



Bob has a  
mirror tx

# Updating balances

- Alice and Bob construct new commitment txs to reflect updated balances
- Each gives the other the secret (also called a revocation key) for the previous commitment tx
- If someone broadcasts an old commitment tx, the other party can take the revocation path and taking the entirety of the other output!


# Broadcasting a revoked state

Funding tx

Alice txid:index (1 BTC)	Alice & Bob 2 BTC
Bob txid:index (1 BTC)	

Alice's commitment tx

Bob sig	Bob 1 BTC
	Bob & secret OK Alice & 10 blocks 1 BTC



# Closing a channel


- Cooperative close
  - Both sign a transaction spending to the appropriate balances for each user
- Non-cooperative close
  - Online party broadcasts latest commitment tx
  - Waits for the delay to pass
  - (delay is a chance for other party to contest and take revocation path if this isn't actually the latest state)

# New role: watchtowers


- Users need to be very careful and monitor in case their counterparty broadcasts an old state
- Can outsource this job ☐ *watchtowers*
- Watchtowers stand at the ready to take action for the user, but can't spend anything

# Lightning Network

- Too much cost to open a channel with everyone I might want to pay
- Multihop payments: Send a payment *through* other users over multiple channels



# Challenge: make spends on multiple channels atomic



Alice pays 1 BTC to Bob iff Bob pays 1 BTC to Carol

Carol generates secret  $R$ , and shares  $H(R)$  with Alice

Idea: use HTLCs (Hash Timelock Contracts)

# Alice->Bob HTLC

Alice's channel  
balance with Bob

## Funding tx

Alice txid:index (2 BTC)	Alice 3 BTC
Bob txid:index (1 BTC)	

## Bob's commitment tx

Bob's channel  
balance with Alice

Amount Bob has to forward  
to Carol to claim this output  
(the HTLC)

Alice  
1 BTC

Alice & secret  
OR  
Bob & 10 blocks  
1 BTC


HTLC Bob & R  
OR  
Alice & height N  
1 BTC

# Bob->Carol HTLC

## Funding tx


Bob txid:index (3 BTC)	Bob & Carol 5 BTC
Carol txid:index (2 BTC)	

## Carol's commitment tx

Bob sig	Bob 2 BTC
	Bob & secret OR Carol & 10 blocks 2 BTC
	HTLC Carol & R OR Bob & height N 1 BTC

Remember, Carol knows  
R, so she can  
immediately claim this  
HTLC

# HTLC flow



1. Carol generates secret  $R$ ,  
and shares  $H(R)$  with Alice

## Real-Time Lightning Network Statistics

### Number of Nodes

12,661 ↑ +2.38%



### Number of Channels

43,961 ↑ +1.3%



### Network Capacity

4,100.33 BTC ↑ +3%  
\$441,458,781.29



### Node Countdown

987,342  
1.3%



### Nodes Observed

60,359 ↑ +1.07%



### New Nodes (24h)

9 ↓ -52.63%



### New Channels (24h)

235 ↑ +5.86%



### Channel Countdown

956,039  
4.4%



### Nodes with Public IP

11,054



### Updated Nodes (24h)

5,300



### Updated Channels (24h)

39,324



### Capacity Countdown

995,900  
0.41%



# Lightning pros/cons

## Pros

- Very good off-chain scalability
- Instant settlement
- Doesn't require privileged parties

## Cons

- Additional liveness requirement
- Liquidity management
- Limitations to scaling
- Network complexity
- UX complexity