



TECHNICAL DRAWING OF A MECHANICAL PART (CROSS-SECTION).

Dimensions:

- Top diameters: $\varnothing 23$, $\varnothing 15$
- Internal diameters: $\varnothing 39$ (CENTER OF R8), $\varnothing 59.8$, $(\varnothing 61.8)$, $\varnothing 66.4 \pm 0.3$, $(\varnothing 89)$, $\varnothing 90$
- Radii: $R4$, $R8$, $R2$
- Thicknesses/offsets: 4, 2.3, 7.5, 3.5
- Vertical dimension: 40

Notes:

- EMBOSS THE MANUFACTURER MARK AND DATE OF MANUFACTURE.
- EXAMPLE: MAY 2012: [Symbol]

Callouts:

- 1: Points to the top surface of the part.
- 2: Points to the top surface of the part.
- 3: Points to the bottom surface of the part.

STATIC SPRING RATE IN P DIRECTION KsP(N/mm)±15%	STATIC SPRING RATE IN Q DIRECTION (REF.) KsQ(N/mm)	MAX. SUPPORT LOAD IN P DIRECTION 1W(N)	ALLOWABLE LOAD IN P DIRECTION (N)
350	310	780	2720

1

GENERAL RUBBER TOLERANCES	
CLASS B	mm
3 OR LESS	± 0.3
OVER 3 TO 6	± 0.4
OVER 6 TO 10	± 0.5
OVER 10 TO 50	± 1.0
OVER 50 TO 120	± 1.4
OVER 120 TO 250	± 2.0
OVER 250 TO 315	± 2.5
OVER 315 TO 500	± 3.5
500 OR MORE	± 0.8%

~~* DIMENSIONAL TOLERANCES NOT SPECIFIED ON THIS DRAWING SHALL CONFORM TO SANKI STANDARD KSS11-3 AND 4.~~

THIRD	2	INNER SLEEVE	1	STKM12C	REM-90-2					
ANGLE	1	RUBBER	1	NR BASE	G1747K (T.P.Hs=47)	3	PLATE	1	SPHC-P	REM-90-3
PROJ.	NO.	DESCRIPTION	QTY	MATERIAL	REMARKS	NO.	DESCRIPTION	QTY	MATERIAL	REMARKS
<u>4</u>						 倉敷化工株式会社 INDUSTRIAL MACHINERY DIVISION				
<u>3</u>										
<u>2</u>										
<u>1</u>	DIMENSION CORRECTED			'15 10 2	KAGEYAMA	TOMIWA				
CODE	REVISION HISTORY / CHANGES			DATE	APPD	REV.				
APPROVED		CHECKED	DRAWN	DATE CREATED		SCALE	NAME	ENGINE MOUNT		
IZUMI		HASUI	OKAMOTO	YEAR MONTH DAY '12 5 7		1/1	PART NO.	RD158-42181		

INSTALLED CONDITION (EXAMPLE) (DEFLECTION DUE TO EQUIPMENT LOAD IS NOT CONSIDERED)

