


STATIC SPRING RATE IN P DIRECTION KsP(N/mm)±15%	STATIC SPRING RATE IN Q DIRECTION (REF.) KsQ(N/mm)	MAX. SUPPORT LOAD IN P DIRECTION 1W(N)	ALLOWABLE LOAD IN P DIRECTION (N)
350	310	780	2720

1

GENERAL RUBBER TOLERANCES	
CLASS B	mm
3 OR LESS	± 0.3
OVER 3 TO 6	± 0.4
OVER 6 TO 10	± 0.5
OVER 10 TO 50	± 1.0
OVER 50 TO 120	± 1.4
OVER 120 TO 250	± 2.0
OVER 250 TO 315	± 2.5
OVER 315 TO 500	± 3.5
500 OR MORE	± 0.8%

THIRD	2	INNER SLEEVE	1	STKM12C	REM-90-2					
ANGLE	1	RUBBER	1	NR BASE	G1747K (T.P.Hs=47)	3	PLATE	1	SPHC-P	REM-90-3
PROJ.	NO.	DESCRIPTION	QTY	MATERIAL	REMARKS	NO.	DESCRIPTION	QTY	MATERIAL	REMARKS
④						 倉敷化工株式会社 INDUSTRIAL MACHINERY DIVISION				
③										
②										
①	DIMENSION CORRECTED			'15 10 2	KAGEYAMA	TOMIWA				
CODE	REVISION HISTORY / CHANGES			DATE	APPD	REV.				
APPROVED	CHECKED	DRAWN	DATE CREATED	SCALE	NAME	ENGINE MOUNT				
IZUMI	HASUI	OKAMOTO	YEAR MONTH DAY '12 5 7	1 / 1		PART NO.	RD158-42181			

