

CONFIDENTIAL

MANUFACTURING DRAWING

INSTALLED CONDITION (DEFLECTION DUE TO EQUIPMENT LOAD IS NOT CONSIDERED)

IDENTIFICATION (EMBOSSSED)
PART NO. "V1311-42151"
SHALL BE EMBOSSSED.

EMBOSS THE MANUFACTURER MARK
AND DATE OF MANUFACTURE.

EXAMPLE: AUGUST 2014:  

STOPPER

STOPPE

M16

(MOUNTING HOLE DIAMETER)

SPECIFICATIONS

1. STATIC SPRING RATE

STATIC SPRING RATE IN P DIRECTION KsP(N/mm)±15%	STATIC SPRING RATE IN Q DIRECTION (REF.) KsQ(N/mm)	MEASUREMENT RANGE		1W (N)	PRELOAD (N)		TEST SPEED (mm/min)	
		P DIRECTION	Q DIRECTION		P DIRECTION	Q DIRECTION	P DIRECTION	Q DIRECTION
851	710	BETWEEN 676 AND 2028 N	BETWEEN 676 AND 1352 N	1352	5408	4056	10	10

MEASURE IN THE INSTALLED CONDITION. (A DISC-TYPE STOPPER IS ACCEPTABLE.)

2. RUBBER MATERIAL: HEAT-RESISTANT NR

3. SURFACE TREATMENT METAL PRETREATMENT: No. 21

METAL PART SURFACE TREATMENT: BLACK COATING (ACRYLIC WATER-BASED EMULSION PAINT / ASUKA KK)

FILM THICKNESS: 15 μm MIN. / ADHESION TO RUBBER IS ACCEPTABLE, EXCEPT INNER SURFACE OF INNER SLEEVE.

4. DURABILITY: NO HARMFUL DAMAGE AFTER THE FOLLOWING TEST.

DIRECTION	LOAD CONDITIONS	1W	NUMBER OF CYCLES	FREQUENCY	AMBIENT TEMPERATURE
P	1W±2.5W	SEE TABLE ABOVE	1x10 ⁶ CYCLES	2Hz	40°C
Q	±2.5W	SEE TABLE ABOVE	1x10 ⁶ CYCLES	2Hz	40°C

NOTES

- | | | |
|---|---------------|------|
| 1. THIS PART DIFFERS FROM V1411-4215A IN STATIC SPRING RATE AND RUBBER SHAPE. | | |
| 2. SURFACE A (ENTIRE SURFACE) IS A FASTENING SURFACE (SEE INSTALLATION DRAWING); NO RUBBER FLASH IS PERMITTED.
NO LOOSE RUBBER FLASH IS PERMITTED ON SURFACE B (ENTIRE CIRCUMFERENCE). | MASS | 0.5 |
| 3. PROTOTYPE PART NO.: V1311-4215B | RUBBER VOLUME | 23.2 |

MASS	0.51 kg
RUBBER VOLUME	232 cm ³

[illegible]

03141567