

Insert a stage

between 03 Symbolic encoding and 04 Drop detection

chain

Source

>

01 Baseline

>

02 Noise floor

>

03 Symbolic encoding

>

+ new stage

>

04 Drop detection

inserting makes 04 stale

03 outputs Encoding

→

new stage accepts Encoding → emits Encoding

→

04 requires Encoding

4 of 21 blocks fit

search blocks

all

preprocess

encode

detect

cluster

model

control

sort fits first

show incompatible

Fits here 4

Symbol smoothing

Encoding → Encoding

≈ 0.1 s

has null

fits here

Run-length collapse

Encoding → Encoding

≈ 0.2 s

has null

fits here

Alphabet remap

Encoding → Encoding

≈ 0.1 s

no null

fits here

Word filter

Encoding → Encoding

≈ 0.1 s

has null

fits here

Doesn't fit at this point 17 · reasons shown

Matrix profile

Signal → Scores

≈ 6.4 h*

has null

needs Signal · here: Encoding

Seeded search

Signal + exemplar → Scores

≈ 1.1 s

has null

needs exemplar

a Discovery mode · not a chain blo

Threshold to spans

Scores → SpanSet

≈ 0.1 s

no null

emits SpanSet · 04 needs Encoding

Gramian encoding

WindowSet → Encoding

≈ 3 min

no null

needs WindowSet · here: Encodi

Hierarchical cluster

WindowSet → Grouping

≈ 40 s

no null

needs WindowSet

Bandpass filter

Signal → Signal

≈ 0.1 s

has null

needs Signal · here: Encoding

Model stage

Model + WindowSet → Scores

≈ 2 min

no null

needs Model

needs WindowSet · here: Encoding

Surrogate generator

Signal → Signal

≈ 0.3 s

no null

needs Signal · here: Encoding

Run-length collapse

Encoding → Encoding



Collapses repeated letters into runs: DDDDSSUU → D×4 S×2 U×2.

defaults

minimum run

keep SAME runs

emit

2 segments

yes

run lengths + letters

est. cost

0.2 s

null

yes

side-inputs

none

04 goes stale · 00-03 stay cached

inserting at the end changes the terminal type