



Explore



Analyse



Discovery



Models



Review



Library



Jobs · 3



Settings

PROJECT · recorded with runs

Data

Datasets

Channels & events

Vocabulary

Analysis

Nulls

Analysis defaults

Compute & HPC

Blocks

Workspaces

Review queues

Models & registration

Library groupings

Files

Storage & backups

Export

Record

Audit log

About

PERSONAL · this browser

Interface

Display

Keyboard & behaviour

differs from default

Nulls

project · recorded with runs

Reset page to defaults

Every result carries a null. Method, count and seed travel into the recipe hash; whether a null runs is not a setting.

Null per analysis kind

always on

analysis kind	used in	method	draws	seed	shown as
Detection chains	Analyse · Discovery	circular shift	200	per recipe	null expects · × null
Seed search	Discovery	circular shift of the channel	200	per recipe	distances behind the histogram
Interrogation · distributions	Analyse	matched random windows	200	per recipe	null histogram · null β
Interrogation · intervals	Analyse	shuffled onsets	200	per recipe	null interval distribution
Training · baseline	Models	label shuffle · random forest	200	per job	null band · p
Training · full model	Models	label shuffle · full retrain	5	per job	shuffle dots
Library groupings	Library	bootstrap resample of members	100	per grouping	group stability

each method is chosen per kind because the thing that must be destroyed differs: timing for detection, labels for training, membership for groupings

Significance

significance level α	0.01	with 200 draws the smallest reportable p is 0.005
multiple channels	none	HoIm
correction when a result is tested per channel	Benjamini-Hochberg	
show × null beside counts		Discovery scoreboard, templates, run reports

Running nulls

reuse null draws while the recipe is unchanged		a changed parameter invalidates the cached draws
null draws count toward local limits		estimates include them, so a 200× null can route a stage to the cluster