

Learning Relation Entailment Graphs

CSE 515 Final Report

Mitchell Koch, Justin Huang

Friday, June 14, 2013

Abstract

Can learning relation entailment graphs based on WordNet or Bayes net structure learning improve relation query performance?

1 Introduction and Motivation

Open IE [3]

previous relation entailment work [2, 1], on work in relation extraction using matrix factorization [6],

as well as on related work in probabilistic modeling of relations between entities [8, 7].

Freebase using distant supervision as in [5]

1.1 Database Query Task

Given a query for relation R with arguments X and Y , we expand the query to include all entailing relations. Given an original query $R(X, Y)$, it is expanded to $R'(X, Y)$ for all R' such that there is an edge from R' to R in the entailment graph. This process is shown in Figure 1.




Figure 1: An example of a query being expanded.

2 Methods and Algorithms

2.1 Constraints on WordNet

WordNet [4] is a hand-crafted resource that distinguishes between different word senses, and provides synonyms and entailments between them. We denote a word net sense with a number where *#1* is the most common. For example *note#4* is the fourth most common sense of “note,” which means “to write down”. Each WordNet sense has its sense number, a count indicating how often that sense is used, and a probability, which is the count divided by the sum of counts for all senses of the same word.

The challenge in using WordNet for relation entailment is that we need to determine what sense to use. Given the verb “take,” is it *take#21* (take by force) or *take#2* (take time)?

We follow the following steps for our method.

1. Assume a string can be any WordNet sense (“take” = *take#1*, *take#2*, ..., *take#42*)
2. Attempt the database query task using all possible entailments.
3. Label results as correct/incorrect
4. Split results into train / test sets, gather features of the path taken through the entailment graph that connected the result to the query.
5. Train a model of the probability that the path is correct given features of the path using logistic regression.
6. Evaluate the model on the test set.

Our features for a path in the entailment graph are as follows.

1. Path length
2. Average sense number
3. Average WordNet probability
4. Maximum sense number
5. Minimum WordNet probability




Figure 2: Component of the WordNet entailment graph with the first sense of conquer, *conquer#1*. Boxes represent synonym sets, arrows represent entailments.




Figure 3: Example path in entailment graph

2.2 Bayesian Network Structure Learning

3 Experiments and Results

4 Discussion and Conclusion

References

- [1] J. Berant, I. Dagan, and J. Goldberger. Global learning of typed entailment rules. In *Proceedings of the 49th Annual Meeting of the Association for Computational Linguistics: Human Language Technologies - Volume 1*, HLT '11, pages 610–619, Stroudsburg, PA, USA, 2011. Association for Computational Linguistics.
- [2] J. Berant, I. Dagan, and J. Goldberger. Learning entailment relations by




Figure 4: Examples of possible network structures

global graph structure optimization. *Comput. Linguist.*, 38(1):73–111, Mar. 2012.

- [3] O. Etzioni, M. Banko, S. Soderland, and D. S. Weld. Open information extraction from the web. *Commun. ACM*, 51(12):68–74, Dec. 2008.
- [4] C. Fellbaum, editor. *WordNet: an electronic lexical database*. MIT Press, 1998.
- [5] R. Hoffmann, C. Zhang, X. Ling, L. S. Zettlemoyer, and D. S. Weld. Knowledge-based weak supervision for information extraction of overlapping relations. In *ACL*, pages 541–550, 2011.
- [6] S. Riedel, L. Yao, B. M. Marlin, and A. McCallum. Relation extraction with matrix factorization and universal schemas. In *Joint Human Language Technology Conference/Annual Meeting of the North American Chapter of the Association for Computational Linguistics (HLT-NAACL '13)*, June 2013.
- [7] B. Taskar, P. Abbeel, and D. Koller. Discriminative probabilistic models for relational data. In *Proceedings of the Eighteenth conference on Uncertainty in artificial intelligence*, UAI'02, pages 485–492, San Francisco, CA, USA, 2002. Morgan Kaufmann Publishers Inc.
- [8] B. Taskar, M. F. Wong, P. Abbeel, and D. Koller. Link prediction in relational data. In *NIPS*, 2003.