

# Support Vector Machines

Aarti Singh, HMW-Alexander

February 13, 2017

---

[Back to Index](#)

---

## Contents

<b>1 Support Vectors</b>	<b>1</b>
<b>2 Data is ont linearly separable</b>	<b>2</b>

## Resources

- [Lecture](#)
- 

Pick the one with largest **margin**.

Separate line: ( $\vec{w}$  is perpendicular to this line)

$$\vec{w}^T \vec{x} + b = 0$$

Margin:

$$\gamma = \frac{2a}{\|\vec{w}\|}$$

Confidence:

$$(\vec{w}^T \vec{x}_i + b)y_i$$

Object function of SVM:

$$\max_{\vec{w}, b} \gamma = \frac{2a}{\|\vec{w}\|}, \quad s.t. \quad (\vec{w}^T \vec{x}_i + b)y_i \geq a, \quad \forall i$$

or

$$\min_{\vec{w}} \vec{w}^T \vec{w}, \quad s.t. \quad (\vec{w}^T \vec{x}_i + b)y_i \geq 1, \quad \forall i$$

## 1 Support Vectors

Linear yperplane defined by "support vectors". Only need to store the support vectors to predict labels of new points.

## 2 Data is not linearly separable

Not quadratic programming:

$$\min_{\vec{w}} \vec{w}^T \vec{w} + C \#mistakes, \quad s.t. (\vec{w}^T \vec{x}_i + b)y_i \geq 1, \quad \forall i$$

$C$  is a tradeoff parameter.

Soft margin approach (QP):

$$\min_{\vec{w}} \vec{w}^T \vec{w} + C \sum_j \xi_j, \quad s.t. (\vec{w}^T \vec{x}_i + b)y_i \geq 1 - \xi_i \quad \forall i$$

- $\xi$ : slack variables = (1 if  $x_i$  misclassified)
- $C$ : tradeoff parameter (chosen by cross-validation)

Hinge loss:

$$\xi_i = (1 - (\vec{w}^T \vec{x}_i + b)y_i)_+$$

Regularized hinge loss:

$$\min_{\vec{w}, b} \vec{w}^T \vec{w} + C \sum_i (1 - (\vec{w}^T \vec{x}_i + b)y_i)_+$$