

PREFLIGHT.md — venue checklist + naming contract + failure playbook

Run **on arrival, before participants enter**. Two minutes when everything is healthy; the whole point is discovering when it isn't (C22: you find the missing dependency standing in a strange room — this list makes you find it *first*).

The 2-minute pre-flight

- [] Mage powered; `curl http://127.0.0.1:11434/api/tags` answers ****on the mage box**** (model present — pulled before travel, never at the venue).

- [] Carried naming layer up; the one good name resolves from a ****clean resolver*** (`ping <name>` in a fresh* shell — never a warm browser, C26) on **two different client machines** (one PC, one Mac if mixed).

- [] Raw-IP fallback answers something soft (the catch-all — C28), not a 502.
- [] Client-to-client reachability: one laptop pings another. If this fails, the venue has client/AP isolation → carried switch/AP or overlay; no LAN trick will help (playbook, CEREMONY.md §5).

- [] `node tools/check.mjs` green on the mage box (axioms → runs re-derive).
- [] `node tools/corpus_pack.mjs --verify` green (the chain is intact before the room watches it extend).

- [] Roster page empty and serving; consent registers printed/loadable (workshop/consent/).

Naming contract (carried, not negotiated per venue)

- ONE good name for this mage instance — chosen by the cohort, held by the holder, no canonical string (C24). Services are **paths** under it.
- Resolution comes from **our resolver**, deterministic and identical for every client (C25). Venue mDNS may work; it is never *load-bearing*.
- Never `.localhost` for a shared name (RFC 6761 forces it to loopback — C27). Plain TLD (`.mesh` and friends) per instance.
- DHCP: the mage box gets a static/reserved address the resolver leans on.

Failure playbook (what the room sees → the move)

the room sees	it is	the move
"can't find the server" on SOME laptops	mDNS intermittency (C26)	switch everyone to the carried name; verify from clean shells
name dead AND raw IP 502s	name-keyed vhost (C23)	catch-all front door; never one literal string
nothing reaches anything	client isolation	carried AP/switch; else the overlay/tunnel
worked at home, dead here	outsourced naming (C22)	this checklist, next time run FIRST
it loads in the browser but ping fails	warm cache lying (C26)	trust the clean resolver, not the browser

The meta-rule: a flaky pass is a fail. A name that resolves *sometimes* ships the failure to the exact moment the room is watching.