



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 1 OF 71

**CERTIFIED COMPANY BY THE AMERICAN SOCIETY
OF MECHANICAL ENGINEERS (ASME U STAMP)**



ISO 9001:2015 CERTIFIED COMPANY BY TUV NORD GERMANY



Plot No. E6, E-Block, Bhosari Industrial Area, Opposite NARI,
Bhosari, Pune – 411026, Maharashtra, INDIA.

**TECHNO-COMMERCIAL OFFER FOR
TURNKEY PLANT**

OFFER NO.	APSPL-ANP-1118-25-26-R2	OFFER DATE:	21-01-2026
PREPARED BY	MISS. ADITI M. WAGH	CONTACT PERSON:	
CLIENT:			



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 2 OF 71

To,

M/S.

Kind Attention:

Subject: Techno-Commercial Proposal for Turnkey Plant supply.

Dear Sir,

We are in receipt of your enquiry about Supply of Turnkey Plant supply. We are very much thankful to you for this valuable enquiry

Kindly find attached herewith detailed Techno-Commercial Proposal in line with enquiry documents provided to us and discussions with our technical team.

We hope that the offer is in line with your requirements and we look forward to receiving your valuable order.

Please feel free to contact Undersign and our team for any queries if any.

Best Regards,

FOR ACME PROCESS SYSTEMS PVT. LTD.

Aditi M. Wagh

Engineer – Projects

Contact- + 91 9545596802

Email- aditi.wagh@acmeprocess.net


**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 3 OF 71

A) SOLVENT STORAGE TANK SYSTEM
1. MAIN SOLVENT STORAGE TANKS-40KL
PROCESS DETAILS

Fluid	DMF, ACN
Fluid Sp. Gr.	~1.2
Fluid Viscosity (in cP)	~200
Design Temperature in (°C)	Ambient
Maximum Operating Temperature in (°C)	Ambient
Maximum Operating Pressure in (Kg/cm ²)	ATM
Design Pressure in (Kg/cm ²)	ATM
Hydro test Pressure (Kg/cm ²)	Full Of Water

MECHANICAL DETAILS

Design Code	API 650 (Along with PESO Norms)
Joint Efficiency (Shell/Head)	0.85/1.00
Radiography (Shell/Head)	Spot (10% + All T Joints)/Full
Corrosion Allowance in mm	NIL

WETTED PART MOC AND GRADE

Shell	SA 240 Gr 304
Top & Bottom Dish Head	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 above 150 NB SA 240 Gr 304
Nozzle Flanges	SORF Flange A182 Stainless Steel 304 L B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE

NON-WETTED PART MOC AND GRADE

Plate	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 SCH 40 and Above 150 NB SA 240 Gr 304
Nozzle Connections	SORF Flange A182 Stainless Steel 304 B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE

VESSEL DETAILS

Gross Capacity	50KL
----------------	------



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 4 OF 71

Working Capacity	40KL
Tank Diameter (in mm)	3500
Tank Height TL to TL (in mm)	4900
Tank Shell Shape/Orientation	Cylindrical/Vertical
Shell Thickness of Base Material	6 mm
Tank Top Dish End Type	Conical Dish Head
Top Dish End Thickness	6 mm
Tank Bottom Dish End Type	Flat Dish Head
Bottom Dish End Thickness	8 mm

ACCESSORIES

Support	Skirt
Lifting Lugs	2 No's/ SS 304
Earthing Clit	2 No's/ SS 304

SURFACE FINISH

Surface Finish Internal	180 Grit Matt finish
Surface Finish External	120 Grit Matt Finish
Quantity	02 Nos.

NOZZLE SCHEDULE

Nozzle	Description	Size, NB	Rating	Sch./Thk	Qty	Remark
MH	Manhole	600 NB	-	-	1	-
N1	Inlet	150 NB	#150	40	4	SORF
N2	Dip Pipe	80 NB	#150	40	1	SORF
N3	Vent	25 NB	#150	40	1	SORF
N4	Outlet	100 NB	#150	40	2	SORF
N5	LT	50 NB	#150	40	2	SORF
N6	Spare	100 NB	#150	40	3	SORF
N7	SG/LG	100 NB	#150	40	2	SORF

	ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)		
	TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY	ISSUE:	VERSION: 1
		DOCUMENT NO.	APSPL- 25-26-R0
		DATE :	21-01-2026
		PAGE NO.	PAGE 5 OF 71

A. VALVE

SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Manual Ball Valve	SS304	#150/800#	Factory Finish	Audco / L&T Valves
2.	Actuated Ball Valve	SS304	#150/800#	Factory Finish	Audco / L&T Valves
3.	Control Valve	SS304	#150/800#	Factory Finish	Siemens Sipart / Samson
4.	Non Return Valve	SS304	#150/800#	Factory Finish	L&T, Audco, KSB
5.	Pressure Reducing Valve	SS304	#150/800#	Factory Finish	Anderson Greenwood (Emerson)/LECO
6.	Breather Valve	SS304	#150/800#	Factory Finish	Nirmal
7.	Bag Filter	SS304	#150/800#	Factory Finish	3M or equivalent

B. INSTRUMENT

SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Level Transmitter	SS304	#150	Electropolishing/Matt	Vega/ E&H
2.	Level Gauge	SS304	#150	Electropolishing/Matt	Wika
3.	Pressure Indicator	SS304	#150	Electropolishing/Matt	E&H /Yokogawa
4.	Level Switch	SS304	#150	Electropolishing/Matt	Vega/ E&H
5.	Flow Switch	SS304	#150	Electropolishing/Matt	E&H
6.	Level Indicator	SS304	#150	Electropolishing/Matt	E&H

C. PUMP

SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Centrifugal Pump (For Transfer)	SS304	#150	Electropolishing/Matt	Alfa Laval/Fristam
2.	Centrifugal Pump (For Tanker Unloading)	SS304	#150	Electropolishing/Matt	Alfa Laval/Fristam

D. ACCESSORIES

SR. NO	ITEM	SIZE NB					MOC	QTY
1.	PIPE	15	25	40	50	80	SS304	AS PER P&ID
2.	FLANGES	15	25	40	50	80	SS304	
3.	GASKET	15	25	40	50	80	PTFE	
4.	NBW	15	25	40	50	80	Standard	

2. MAIN SOLVENT STORAGE TANKS-25KL

PROCESS DETAILS

Fluid	IPA, IPE
Fluid Sp. Gr.	1.2
Fluid Viscosity (in cP)	200
Design Temperature in (°C)	Ambient
Maximum Operating Temperature in (°C)	Ambient
Maximum Operating Pressure in (Kg/cm ²)	ATM
Design Pressure in (Kg/cm ²)	ATM
Hydro test Pressure (Kg/cm ²)	Full Of Water

MECHANICAL DETAILS

Design Code	API 650 (Along with PESO Norms)
Joint Efficiency (Shell/Head)	0.85/1.00
Radiography (Shell/Head)	Spot (10% + All T Joints)/Full
Corrosion Allowance in mm	NIL

WETTED PART MOC AND GRADE

Shell	SA 240 Gr 304
Top & Bottom Dish Head	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 above 150 NB SA 240 Gr 304
Nozzle Flanges	SORF Flange A182 Stainless Steel 304 B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE

NON-WETTED PART MOC AND GRADE

Plate	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 SCH 40 and Above 150 NB SA 240 Gr 304
Nozzle Connections	SORF Flange A182 Stainless Steel 304 B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE

VESSEL DETAILS

Gross Capacity	31KL
Working Capacity	25KL



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 7 OF 71

Tank Diameter (in mm)	3000
Tank Height TL to TL (in mm)	4200
Tank Shell Shape/Orientation	Cylindrical/Vertical
Shell Thickness of Base Material	6 mm
Tank Top Dish End Type	Conical Dish Head
Top Dish End Thickness	6 mm
Tank Bottom Dish End Type	Flat Dish Head
Bottom Dish End Thickness	8 mm

ACCESSORIES

Support	Skirt
Lifting Lugs	2 No's/ SS 304
Earthing Clit	2 No's/ SS 304

SURFACE FINISH

Surface Finish Internal	180 Grit Matt Finish
Surface Finish External	120 Grit Matt Finish
Quantity	02 Nos.

NOZZLE SCHEDULE

Nozzle	Description	Size, NB	Rating	Sch./Thk	Qty	Remark
MH	Manhole	600 NB	-	-	1	-
N1	Inlet	150 NB	#150	40	4	SORF
N2	Dip Pipe	50 NB	#150	40	1	SORF
N3	Vent	25 NB	#150	40	1	SORF
N4	Outlet	50 NB	#150	40	2	SORF
N5	LT	50 NB	#150	40	1	SORF
N6	Spare	100 NB	#150	40	2	SORF
N7	SG/LG	100 NB	#150	40	2	SORF

	ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)		
	TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY	ISSUE:	VERSION: 1
		DOCUMENT NO.	APSPL- 25-26-R0
		DATE :	21-01-2026
		PAGE NO.	PAGE 8 OF 71

A. VALVE					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Manual Ball Valve	SS304	#150/800#	Factory Finish	Audco / L&T Valves
2.	Actuated Ball Valve	SS304	#150/800#	Factory Finish	Audco / L&T Valves
3.	Control Valve	SS304	#150/800#	Factory Finish	Siemens Sipart / Samson
4.	Non Return Valve	SS304	#150/800#	Factory Finish	L&T, Audco, KSB
5.	Pressure Reducing Valve	SS304	#150/800#	Factory Finish	Anderson Greenwood (Emerson)/LECO
6.	Breather Valve	SS304	#150/800#	Factory Finish	Nirmal
7.	Bag Filter	SS304	#150/800#	Factory Finish	3M or equivalent

B. INSTRUMENT					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Level Transmitter	SS304	#150	Electropolishing/Matt	Vega/ E&H
2.	Level Gauge	SS304	#150	Electropolishing/Matt	Wika
3.	Pressure Indicator	SS304	#150	Electropolishing/Matt	E&H /Yokogawa
4.	Level Switch	SS304	#150	Electropolishing/Matt	Vega/ E&H
5.	Flow Switch	SS304	#150	Electropolishing/Matt	E&H
6.	Level Indicator	SS304	#150	Electropolishing/Matt	E&H

C. PUMP					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
3.	Centrifugal Pump (For Transfer)	SS304	#150	Electropolishing/Matt	Alfa Laval/Fristam
4.	Centrifugal Pump (For Tanker Unloading)	SS304	#150	Electropolishing/Matt	Alfa Laval/Fristam

D. ACCESSORIES								
Sr. No	Item	Size NB					MOC	Qty
1.	PIPE	15	25	40	50	80	SS304	AS PER P&ID
2.	FLANGES	15	25	40	50	80	SS304	
3.	GASKET	15	25	40	50	80	PTFE	
4.	NBW	15	25	40	50	80	Standard	

B) DAY STORAGE TANK SYSTEM

1. FRESH SOLVENT DAY TANK - 2KL

PROCESS DETAILS

Fluid	Solvent (ACN, DMF)
Fluid Sp. Gr.	~1.2
Fluid Viscosity (in cP)	~200
Design Temperature in (°C)	52
Maximum Operating Temperature in (°C)	10-40
Maximum Operating Pressure in (Kg/cm ²)	FV-3
Design Pressure in (Kg/cm ²)	3.9
Hydro test Pressure (Kg/cm ²)	5

MECHANICAL DETAILS

Design Code	ASME SECTION VIII DIV.1
Joint Efficiency (Shell/Head)	0.85/1.00
Radiography (Shell/Head)	Spot (10 % + T- Joints)/ Full
Corrosion Allowance in mm	NIL

WETTED PART MOC AND GRADE

Shell	SA 240 Gr 304
Top & Bottom Dish Head	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 above 150 NB SA 240 Gr 304
Nozzle Flanges	SORF Flange A182 Stainless Steel 304 B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE

NON-WETTED PART MOC AND GRADE

Plate	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 SCH 40 and Above 150 NB SA 240 Gr 304
Nozzle Connections	SORF Flange A182 Stainless Steel 304 B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE

VESSEL DETAILS

Gross Capacity	3.1 KL
----------------	--------



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 10 OF 71

Working Capacity	2 KL
Tank Diameter (in mm)	1000
Tank Height TL to TL (in mm)	1100
Tank Shell Shape/Orientation	Cylindrical/Vertical
Shell Thickness of Base Material	5 mm
Tank Top Dish End Type	10% Torrispherical Dish Head
Top Dish End Thickness	6 mm
Tank Bottom Dish End Type	10% Torrispherical Dish Head
Bottom Dish End Thickness	6 mm

ACCESSORIES


Lug Support	4 No's/ SS304
Lifting Lugs	2 No's/ SS304
Earthing Clit	2 No's/ SS304

SURFACE FINISH

Surface Finish Internal	180 Grit Matt Finish
Surface Finish External	120 Grit Matt Finish
Quantity	2 Nos.

NOZZLE SCHEDULE

Nozzle	Description	Size, NB	Rating	Sch./Thk	Qty	Remark
HH	Hand hole	250 NB	--	-	1	-
N1	Inlet	50 NB	#150	40	3	SORF
N2	Vent	25 NB	#150	40	1	SORF
N3	Outlet	50 NB	#150	40	3	SORF
N4	LT	25 NB	#150	40	1	SORF
N5	Spare	25 NB	#150	40	2	SORF
N6	SG/LG	25 NB	#150	40	2	SORF

 ACME PROCESS : PEOPLE : PLANET	ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)		
	TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY	ISSUE:	VERSION: 1
		DOCUMENT NO.	APSPL- 25-26-R0
		DATE :	21-01-2026
		PAGE NO.	PAGE 11 OF 71

A. VALVE					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Manual Ball Valve	SS304	#150/#800	Factory Finish	L&T, Audco
2.	Actuated Ball Valve	SS304	#150/#800	Factory Finish	L&T, Audco
3.	Control Valve	SS304	#150/#800	Factory Finish	Siemens Sipart / Samson
4.	Non Return Valve	SS304	#150/#800	Factory Finish	L&T, Audco, KSB
5.	Pressure Safety Valve	SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
6.	Pressure Reducing Valve	SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
7.	Needle Valve	SS304	#150/#800	Factory Finish	Aira/Hawa
8.	Bag Filter	SS304	#150/#800	Factory Finish	3M or equivalent

B. INSTRUMENT					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Level Transmitter	SS304	#150	Electropolishing/Matt	Vega/ E&H
2.	Level Gauge	SS304	#150	Electropolishing/Matt	Wika
3.	Pressure Indicator	SS304	#150	Electropolishing/Matt	E&H /Yokogawa
4.	Level Switch	SS304	#150	Electropolishing/Matt	Vega/ E&H
5.	Flow Switch	SS304	#150	Electropolishing/Matt	E&H
6.	Level Indicator	SS304	#150	Electropolishing/Matt	E&H

C. PUMP					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Centrifugal Pump	SS304	#150	Electropolishing/Matt	Alfa Laval/Fristam

D. ACCESSORIES								
Sr. No	Item	Size NB					MOC	Qty
1.	PIPE	15	25	40	50	80	SS304	AS PER P&ID
2.	FLANGES	15	25	40	50	80	SS304	
3.	GASKET	15	25	40	50	80	PTFE	
4.	NBW	15	25	40	50	80	Standard	

**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 12 OF 71

2. FRESH SOLVENT DAY TANK -1KL**PROCESS DETAILS**

Fluid	Solvent (IPA, IPE)
Fluid Sp. Gr.	~1.2
Fluid Viscosity (in cP)	~200
Design Temperature in (°C)	52
Maximum Operating Temperature in (°C)	10-40
Maximum Operating Pressure in (Kg/cm ²)	FV- 3
Design Pressure in (Kg/cm ²)	3.9
Hydro test Pressure (Kg/cm ²)	5

MECHANICAL DETAILS

Design Code	ASME SECTION VIII DIV.1
Joint Efficiency (Shell/Head)	0.85/1.00
Radiography (Shell/Head)	Spot (10% + All T-Joints)/Full
Corrosion Allowance in mm	NIL

WETTED PART MOC AND GRADE

Shell	SA 240 Gr 304
Top & Bottom Dish Head	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 SCH 40 and Above 150 NB SA 240 Gr 304
Nozzle Flanges	SORF Flange A182 Stainless Steel 304 B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE

NON-WETTED PART MOC AND GRADE

Plate	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 SCH 40 and Above 150 NB SA 240 Gr 304
Nozzle Connections	SORF Flange A182 Stainless Steel 304 B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE

VESSEL DETAILS

Gross Capacity	1.25 KL
Working Capacity	1 KL



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 13 OF 71

Tank Diameter (in mm)	1000
Tank Height TL to TL (in mm)	1500
Tank Shell Shape/Orientation	Cylindrical/Vertical
Shell Thickness of Base Material	5 mm
Tank Top Dish End Type	10% Torrispherical Dish Head
Top Dish End Thickness	5 mm
Tank Bottom Dish End Type	10% Torrispherical Dish Head
Bottom Dish End Thickness	5 mm

ACCESSORIES

Lug Support	4 No's/ SS 304
Lifting Lugs	2 No's/ SS 304
Earthing Clit	2 No's/ SS 304

SURFACE FINISH

Surface Finish Internal	180 Grit Matt Finish
Surface Finish External	120 Grit Matt Finish
Quantity	2 Nos.

NOZZLE SCHEDULE

Nozzle	Description	Size, NB	Rating	Sch./Thk	Qty	Remark
HH	Hand hole	150 NB	-	-	1	-
N1	Inlet	25 NB	#150	40	3	SORF
N2	Vent	25 NB	#150	40	1	SORF
N3	Outlet	25 NB	#150	40	1	SORF
N4	LT	25 NB	#150	40	1	SORF
N5	Spare	25 NB	#150	40	2	SORF
N6	SG/LG	25 NB	#150	40	4	SORF

	ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)		
	TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY	ISSUE:	VERSION: 1
		DOCUMENT NO.	APSPL- 25-26-R0
		DATE :	21-01-2026
		PAGE NO.	PAGE 14 OF 71

A. VALVE					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Manual Ball Valve	SS304	#150/#800	Factory Finish	L&T, Audco
2.	Actuated Ball Valve	SS304	#150/#800	Factory Finish	L&T, Audco
3.	Control Valve	SS304	#150/#800	Factory Finish	Siemens Sipart / Samson
4.	Non Return Valve	SS304	#150/#800	Factory Finish	L&T, Audco, KSB
5.	Pressure Safety Valve	SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
6.	Pressure Reducing Valve	SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
7.	Needle Valve	SS304	#150/#800	Factory Finish	Aira/Hawa
8.	Bag Filter	SS304	#150/#800	Factory Finish	3M or equivalent

B. INSTRUMENT					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
7.	Level Transmitter	SS304	#150	Electropolishing/Matt	Vega/ E&H
8.	Level Gauge	SS304	#150	Electropolishing/Matt	Wika
9.	Pressure Indicator	SS304	#150	Electropolishing/Matt	E&H /Yokogawa
10.	Level Switch	SS304	#150	Electropolishing/Matt	Vega/ E&H
11.	Flow Switch	SS304	#150	Electropolishing/Matt	E&H
12.	Level Indicator	SS304	#150	Electropolishing/Matt	E&H

C. PUMP					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Centrifugal Pump	SS304	#150	Electropolishing/Matt	Alfa Laval/Fristam

D. ACCESSORIES								
SR. NO	ITEM	SIZE NB					MOC	QTY
1.	PIPE	15	25	40	50	80	SS304	AS PER P&ID
2.	FLANGES	15	25	40	50	80	SS304	
3.	GASKET	15	25	40	50	80	PTFE	
4.	NBW	15	25	40	50	80	Standard	

3. FRESH SOLVENT DAY TANK -1KL

PROCESS DETAILS

Fluid	Solvent (MDC)
Fluid Sp. Gr.	~1.2
Fluid Viscosity (in cP)	~200
Design Temperature in (°C)	52
Maximum Operating Temperature in (°C)	10-40
Maximum Operating Pressure in (Kg/cm ²)	FV- 3
Design Pressure in (Kg/cm ²)	3.9
Hydro test Pressure (Kg/cm ²)	5

MECHANICAL DETAILS

Design Code	ASME SECTION VIII DIV.1
Joint Efficiency (Shell/Head)	0.85/1.00
Radiography (Shell/Head)	Spot (10% + All T-Joints)/Full
Corrosion Allowance in mm	NIL

WETTED PART MOC AND GRADE

Shell	SA 240 Gr 316L
Top & Bottom Dish Head	SA 240 Gr 316L
Nozzle Pipe	Up to 150 NB SA 312 Gr 316L above 150 NB SA 240 Gr 316L
Nozzle Flanges	SORF Flange A182 Stainless Steel 316 L B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8M and SA 194 Gr 8M
Gasket	PTFE

NON-WETTED PART MOC AND GRADE

Plate	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 SCH 40 and Above 150 NB SA 240 Gr 304
Nozzle Connections	SORF Flange A182 Stainless Steel 304 B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE

VESSEL DETAILS

Gross Capacity	1.25 KL
Working Capacity	1 KL



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 16 OF 71

Tank Diameter (in mm)	1000
Tank Height TL to TL (in mm)	1500
Tank Shell Shape/Orientation	Cylindrical/Vertical
Shell Thickness of Base Material	5 mm
Tank Top Dish End Type	10% Torrispherical Dish Head
Top Dish End Thickness	5 mm
Tank Bottom Dish End Type	10% Torrispherical Dish Head
Bottom Dish End Thickness	5 mm

ACCESSORIES

Lug Support	4 No's/ SS 304+SS316L
Lifting Lugs	2 No's/ SS 304
Earthing Clit	2 No's/ SS 304

SURFACE FINISH

Surface Finish Internal	180 Grit Matt Finish
Surface Finish External	120 Grit Matt Finish
Quantity	1 Nos.

NOZZLE SCHEDULE

Nozzle	Description	Size, NB	Rating	Sch./Thk	Qty	Remark
HH	Hand hole	150 NB	-	-	1	-
N1	Inlet	25 NB	#150	40	3	SORF
N2	Vent	25 NB	#150	40	1	SORF
N3	Outlet	25 NB	#150	40	1	SORF
N4	LT	25 NB	#150	40	1	SORF
N5	Spare	25 NB	#150	40	2	SORF
N6	SG/LG	25 NB	#150	40	4	SORF

 ACME PROCESS : PEOPLE : PLANET	ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)		
	TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY	ISSUE:	VERSION: 1
		DOCUMENT NO.	APSPL- 25-26-R0
		DATE :	21-01-2026
		PAGE NO.	PAGE 17 OF 71

E. VALVE					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
9.	Manual Ball Valve	SS316L/SS304	#150/#800	Factory Finish	L&T, Audco
10.	Actuated Ball Valve	SS316L/SS304	#150/#800	Factory Finish	L&T, Audco
11.	Control Valve	SS316L/SS304	#150/#800	Factory Finish	Siemens Sipart / Samson
12.	Non Return Valve	SS316L/SS304	#150/#800	Factory Finish	L&T, Audco, KSB
13.	Pressure Safety Valve	SS316L/SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
14.	Pressure Reducing Valve	SS316L/SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
15.	Needle Valve	SS316L/SS304	#150/#800	Factory Finish	Aira/Hawa
16.	Bag Filter	SS316L/SS304	#150/#800	Factory Finish	3M or equivalent

F. INSTRUMENT					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
13.	Level Transmitter	SS316	#150	Electropolishing/Matt	Vega/ E&H
14.	Level Gauge	SS316	#150	Electropolishing/Matt	Wika
15.	Pressure Indicator	SS316	#150	Electropolishing/Matt	E&H /Yokogawa
16.	Level Switch	SS316	#150	Electropolishing/Matt	Vega/ E&H
17.	Flow Switch	SS316	#150	Electropolishing/Matt	E&H
18.	Level Indicator	SS316	#150	Electropolishing/Matt	E&H

G. PUMP					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
2.	Centrifugal Pump	SS316	#150	Electropolishing/Matt	Alfa Laval/Fristam
3.	AODD Pump	SS316	#150	Electropolishing/Matt	Wilden, Aro

H. ACCESSORIES								
SR. NO	ITEM	SIZE NB					MOC	QTY
5.	PIPE	15	25	40	50	80	SS316/SS304	AS PER P&ID
6.	FLANGES	15	25	40	50	80	SS316/SS304	
7.	GASKET	15	25	40	50	80	SS316/SS304	
8.	NBW	15	25	40	50	80	SS316/SS304	


**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 18 OF 71

4. SPENT DAY TANK -2KL
PROCESS DETAILS

Fluid	Solvent (DMF, ACN)
Fluid Sp. Gr.	~1.2
Fluid Viscosity (in cP)	~200
Design Temperature in (°C)	52
Maximum Operating Temperature in (°C)	10-40
Maximum Operating Pressure in (Kg/cm ²)	FV - 3
Design Pressure in (Kg/cm ²)	3.9
Hydro test Pressure (Kg/cm ²)	5

MECHANICAL DETAILS

Design Code	ASME SECTION VIII DIV.1
Joint Efficiency (Shell/Head)	0.85/1.00
Radiography (Shell/Head)	Spot (10% +All T-Joints)/ Full
Corrosion Allowance in mm	NIL

WETTED PART MOC AND GRADE

Shell	SA 240 Gr 304
Top & Bottom Dish Head	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 above 150 NB SA 240 Gr 304
Nozzle Flanges	SORF Flange A182 Stainless Steel 304 B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE

NON-WETTED PART MOC AND GRADE

Plate	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 SCH 40 and Above 150 NB SA 240 Gr 304
Nozzle Connections	SORF Flange A182 Stainless Steel 304 B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE

VESSEL DETAILS

Gross Capacity	3.1 KL
----------------	--------



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 19 OF 71

Working Capacity	2 KL
Tank Diameter (in mm)	1300
Tank Height TL to TL (in mm)	1950
Tank Shell Shape/Orientation	Cylindrical/Vertical
Shell Thickness of Base Material	5 mm
Tank Top Dish End Type	10% Torrispherical Dish Head
Top Dish End Thickness	6 mm
Tank Bottom Dish End Type	10% Torrispherical Dish Head
Bottom Dish End Thickness	6 mm

ACCESSORIES

Lug Support	4 No's/ SS 304
Lifting Lugs	2 No's/ SS 304
Earthing Clit	2 No's/ SS 304

SURFACE FINISH

Surface Finish Internal	Electropolishing
Surface Finish External	Matt
Quantity	2 Nos.

NOZZLE SCHEDULE

Nozzle	Description	Size, NB	Rating	Sch./Thk	Qty	Remark
HH	Hand hole	250 NB	-	-	-	-
N1	Inlet	50 NB	#150	40	3	SORF
N2	Vent	25 NB	#150	40	1	SORF
N3	Outlet	50 NB	#150	40	1	SORF
N4	LT	25 NB	#150	40	1	SORF
N5	Spare	25 NB	#150	40	2	SORF
N6	SG/LG	25 NB	#150	40	2	SORF

	ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)			
	TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY		ISSUE:	VERSION: 1
			DOCUMENT NO.	APSPL- 25-26-R0
			DATE :	21-01-2026
			PAGE NO.	PAGE 20 OF 71

A. VALVE

SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Manual Ball Valve	SS304	#150/#800	Factory Finish	L&T, Audco
2.	Actuated Ball Valve	SS304	#150/#800	Factory Finish	L&T, Audco
3.	Control Valve	SS304	#150/#800	Factory Finish	Siemens Sipart / Samson
4.	Non Return Valve	SS304	#150/#800	Factory Finish	L&T, Audco, KSB
5.	Pressure Safety Valve	SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
6.	Pressure Reducing Valve	SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
7.	Needle Valve	SS304	#150/#800	Factory Finish	Aira/Hawa

B. INSTRUMENT

SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Level Transmitter	SS304	#150	Electropolishing/Matt	Vega/ E&H
2.	Level Gauge	SS304	#150	Electropolishing/Matt	Wika
3.	Pressure Indicator	SS304	#150	Electropolishing/Matt	E&H /Yokogawa
4.	Level Switch	SS304	#150	Electropolishing/Matt	Vega/ E&H
5.	Flow Switch	SS304	#150	Electropolishing/Matt	E&H
6.	Level Indicator	SS304	#150	Electropolishing/Matt	E&H

C. PUMP

Sr. No	Description	MOC	Rating	SURFACE FINISH	MAKE
1.	Centrifugal Pump	SS304	#150	Electropolishing/Matt	Alfa Laval/Fristam

D. ACCESSORIES

SR. NO	ITEM	SIZE NB					MOC	QTY
1.	PIPE	15	25	40	50	80	SS304	AS PER P&ID
2.	FLANGES	15	25	40	50	80	SS304	
3.	GASKET	15	25	40	50	80	PTFE	
4.	NBW	15	25	40	50	80	Standard	

5. SPENT DAY TANK -1KL

PROCESS DETAILS

Fluid	Solvent (IPA, RXN, DAC1, DAC2)
Fluid Sp. Gr.	~1.2
Fluid Viscosity (in cP)	~200
Design Temperature in (°C)	52
Maximum Operating Temperature in (°C)	10-40
Maximum Operating Pressure in (Kg/cm ²)	FV - 3
Design Pressure in (Kg/cm ²)	3.9
Hydro test Pressure (Kg/cm ²)	5

MECHANICAL DETAILS

Design Code	ASME SECTION VIII DIV.1
Joint Efficiency (Shell/Head)	0.85/1.00
Radiography (Shell/Head)	Spot (10% + All T-Joints)/Full
Corrosion Allowance in mm	NIL

WETTED PART MOC AND GRADE

Shell	SA 240 Gr 304
Top & Bottom Dish Head	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 above 150 NB SA 240 Gr 304
Nozzle Flanges	SORF Flange A182 Stainless Steel 304 B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE

NON-WETTED PART MOC AND GRADE

Plate	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 SCH 40 and Above 150 NB SA 240 Gr 304
Nozzle Connections	SORF Flange A182 Stainless Steel 304 B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE

VESSEL DETAILS

Gross Capacity	1.25 KL
Working Capacity	1 KL



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 22 OF 71

Tank Diameter (in mm)	1000
Tank Height TL to TL (in mm)	1500
Tank Shell Shape/Orientation	Cylindrical/Vertical
Shell Thickness of Base Material	5 mm
Tank Top Dish End Type	10% Torrispherical Dish Head
Top Dish End Thickness	5 mm
Tank Bottom Dish End Type	10% Torrispherical Dish Head
Bottom Dish End Thickness	5 mm

ACCESSORIES

Lug Support	4 No's/ SS 304
Lifting Lugs	2 No's/ SS 304
Earthing Clit	2 No's/ SS 304

SURFACE FINISH

Surface Finish Internal	180 Grit Matt finish
Surface Finish External	120 Grit Matt Finish
Quantity	4 Nos.

NOZZLE SCHEDULE

Nozzle	Description	Size, NB	Rating	Sch./Thk	Qty	Remark
HH	Hand hole	150 NB	-	-	1	-
N1	Inlet	25 NB	#150	40	2	SORF
N2	Vent	25 NB	#150	40	1	SORF
N3	Outlet	25 NB	#150	40	1	SORF
N4	LT	25 NB	#150	40	1	SORF
N5	Spare	25 NB	#150	40	2	SORF
N6	SG/LG	25 NB	#150	40	2	SORF

 ACME PROCESS : PEOPLE : PLANET	ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)			
	TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY		ISSUE:	VERSION: 1
			DOCUMENT NO.	APSPL- 25-26-R0
			DATE :	21-01-2026
			PAGE NO.	PAGE 23 OF 71

A. VALVE

SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Manual Ball Valve	SS304	#150/#800	Factory Finish	L&T, Audco
2.	Actuated Ball Valve	SS304	#150/#800	Factory Finish	L&T, Audco
3.	Control Valve	SS304	#150/#800	Factory Finish	Siemens Sipart / Samson
4.	Non Return Valve	SS304	#150/#800	Factory Finish	L&T, Audco, KSB
5.	Pressure Safety Valve	SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
6.	Pressure Reducing Valve	SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
7.	Needle Valve	SS304	#150/#800	Factory Finish	Aira/Hawa

B. INSTRUMENT

SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Level Transmitter	SS304	#150	Electropolishing/Matt	Vega/ E&H
2.	Level Gauge	SS304	#150	Electropolishing/Matt	Wika
3.	Pressure Indicator	SS304	#150	Electropolishing/Matt	E&H /Yokogawa
4.	Level Switch	SS304	#150	Electropolishing/Matt	Vega/ E&H
5.	Flow Switch	SS304	#150	Electropolishing/Matt	E&H
6.	Level Indicator	SS304	#150	Electropolishing/Matt	E&H

C. PUMP

SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Centrifugal Pump	SS304	#150	Electropolishing/Matt	Alfa Laval/Fristam

D. ACCESSORIES

SR. NO	ITEM	SIZE NB					MOC	QTY
1.	PIPE	15	25	40	50	80	SS304	AS PER P&ID
2.	FLANGES	15	25	40	50	80	SS304	
3.	GASKET	15	25	40	50	80	PTFE	
4.	NBW	15	25	40	50	80	Standard	


**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 24 OF 71

6. SPENT DAY TANK -1KL
PROCESS DETAILS

Fluid	Solvent (MDC)
Fluid Sp. Gr.	~1.2
Fluid Viscosity (in cP)	~200
Design Temperature in (°C)	52
Maximum Operating Temperature in (°C)	10-40
Maximum Operating Pressure in (Kg/cm ²)	FV - 3
Design Pressure in (Kg/cm ²)	3.9
Hydro test Pressure (Kg/cm ²)	5

MECHANICAL DETAILS

Design Code	ASME SECTION VIII DIV.1
Joint Efficiency (Shell/Head)	0.85/1.00
Radiography (Shell/Head)	Spot (10% + All T-Joints)/Full
Corrosion Allowance in mm	NIL

WETTED PART MOC AND GRADE

Shell	SA 240 Gr 316L
Top & Bottom Dish Head	SA 240 Gr 316L
Nozzle Pipe	Up to 150 NB SA 312 Gr 316L above 150 NB SA 240 Gr 316L
Nozzle Flanges	SORF Flange A182 Stainless Steel 316L B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8M and SA 194 Gr 8M
Gasket	PTFE

NON-WETTED PART MOC AND GRADE

Plate	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 SCH 40 and Above 150 NB SA 240 Gr 304
Nozzle Connections	SORF Flange A182 Stainless Steel 304 B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE

VESSEL DETAILS

Gross Capacity	1.25 KL
Working Capacity	1 KL



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 25 OF 71

Tank Diameter (in mm)	1000
Tank Height TL to TL (in mm)	1500
Tank Shell Shape/Orientation	Cylindrical/Vertical
Shell Thickness of Base Material	5 mm
Tank Top Dish End Type	10% Torrispherical Dish Head
Top Dish End Thickness	5 mm
Tank Bottom Dish End Type	10% Torrispherical Dish Head
Bottom Dish End Thickness	5 mm

ACCESSORIES

Lug Support	4 No's/ SS 304+SS316L
Lifting Lugs	2 No's/ SS 304
Earthing Clit	2 No's/ SS 304

SURFACE FINISH

Surface Finish Internal	180 Grit Matt finish
Surface Finish External	120 Grit Matt Finish
Quantity	1 Nos.

NOZZLE SCHEDULE

Nozzle	Description	Size, NB	Rating	Sch./Thk	Qty	Remark
HH	Hand hole	150 NB	-	-	1	-
N1	Inlet	25 NB	#150	40	2	SORF
N2	Vent	25 NB	#150	40	1	SORF
N3	Outlet	25 NB	#150	40	1	SORF
N4	LT	25 NB	#150	40	1	SORF
N5	Spare	25 NB	#150	40	2	SORF
N6	SG/LG	25 NB	#150	40	2	SORF

	ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)			
	TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY		ISSUE:	VERSION: 1
			DOCUMENT NO.	APSPL- 25-26-R0
			DATE :	21-01-2026
			PAGE NO.	PAGE 26 OF 71

E. VALVE					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
8.	Manual Ball Valve	SS316L/SS304	#150/#800	Factory Finish	L&T, Audco
9.	Actuated Ball Valve	SS316L/SS304	#150/#800	Factory Finish	L&T, Audco
10.	Control Valve	SS316L/SS304	#150/#800	Factory Finish	Siemens Sipart / Samson
11.	Non Return Valve	SS316L/SS304	#150/#800	Factory Finish	L&T, Audco, KSB
12.	Pressure Safety Valve	SS316L/SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
13.	Pressure Reducing Valve	SS316L/SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
14.	Needle Valve	SS316L/SS304	#150/#800	Factory Finish	Aira/Hawa

F. INSTRUMENT					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
7.	Level Transmitter	SS316	#150	Electropolishing/Matt	Vega/ E&H
8.	Level Gauge	SS316	#150	Electropolishing/Matt	Wika
9.	Pressure Indicator	SS316	#150	Electropolishing/Matt	E&H /Yokogawa
10.	Level Switch	SS316	#150	Electropolishing/Matt	Vega/ E&H
11.	Flow Switch	SS316	#150	Electropolishing/Matt	E&H
12.	Level Indicator	SS316	#150	Electropolishing/Matt	E&H

G. PUMP					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
2.	Centrifugal Pump	SS316	#150	Electropolishing/Matt	Alfa Laval/Fristam

H. ACCESSORIES								
SR. NO	ITEM	SIZE NB					MOC	QTY
5.	PIPE	15	25	40	50	80	SS316/SS304	AS PER P&ID
6.	FLANGES	15	25	40	50	80	SS316/SS304	
7.	GASKET	15	25	40	50	80	PTFE	
8.	NBW	15	25	40	50	80	Standard	


**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 27 OF 71

7. WASTE DAY TANK -1KL
PROCESS DETAILS

Fluid	Solvent
Fluid Sp. Gr.	~1.2
Fluid Viscosity (in cP)	~200
Design Temperature in (°C)	52
Maximum Operating Temperature in (°C)	10-40
Maximum Operating Pressure in (Kg/cm ²)	FV-3
Design Pressure in (Kg/cm ²)	3.9
Hydro test Pressure (Kg/cm ²)	5

MECHANICAL DETAILS

Design Code	ASME SECTION VIII DIV.1
Joint Efficiency (Shell/Head)	0.85/1.00
Radiography (Shell/Head)	Spot (10% + All T Joints)/Full
Corrosion Allowance in mm	NIL

WETTED PART MOC AND GRADE

Shell	SA 240 Gr 316L
Top & Bottom Dish Head	SA 240 Gr 316L
Nozzle Pipe	Up to 150 NB SA 312 Gr 316L above 150 NB SA 240 Gr 316L
Nozzle Flanges	SORF Flange A182 Stainless Steel 316L B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE

NON-WETTED PART MOC AND GRADE

Plate	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 SCH 40 and Above 150 NB SA 240 Gr 304
Nozzle Connections	SORF Flange A182 Stainless Steel 304 B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE

VESSEL DETAILS

Gross Capacity	1.25 KL
Working Capacity	1 KL



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 28 OF 71

Tank Diameter (in mm)	1000
Tank Height TL to TL (in mm)	1500
Tank Shell Shape/Orientation	Cylindrical/Vertical
Shell Thickness of Base Material	5 mm
Tank Top Dish End Type	10% Torrispherical Dish Head
Top Dish End Thickness	5 mm
Tank Bottom Dish End Type	10% Torrispherical Dish Head
Bottom Dish End Thickness	5 mm

ACCESSORIES


Lug Support	4 No's/ SS 304 +SS316L
Lifting Lugs	2 No's/ SS 304
Earthing Clit	2 No's/ SS 304

SURFACE FINISH

Surface Finish Internal	Acid Pickling & Passivation
Surface Finish External	Acid Pickling & Passivation
Quantity	2 Nos.

NOZZLE SCHEDULE

Nozzle	Description	Size, NB	Rating	Sch./Thk	Qty	Remark
HH	Hand hole	150 NB	-	-	1	-
N1	Inlet	25 NB	#150	40	3	SORF
N2	Vent	25 NB	#150	40	1	SORF
N3	Outlet	25 NB	#150	40	1	SORF
N4	LT	25 NB	#150	40	1	SORF
N5	Spare	25 NB	#150	40	2	SORF
N6	SG/LG	25 NB	#150	40	1	SORF

 ACME PROCESS : PEOPLE : PLANET	ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)		
	TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY	ISSUE:	VERSION: 1
		DOCUMENT NO.	APSPL- 25-26-R0
		DATE :	21-01-2026
		PAGE NO.	PAGE 29 OF 71

A. VALVE					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Manual Ball Valve	SS316L/SS304	#150/#800	Factory Finish	L&T, Audco
2.	Actuated Ball Valve	SS316L/SS304	#150/#800	Factory Finish	L&T, Audco
3.	Control Valve	SS316L/SS304	#150/#800	Factory Finish	Siemens Sipart / Samson
4.	Non Return Valve	SS316L/SS304	#150/#800	Factory Finish	L&T, Audco, KSB
5.	Pressure Safety Valve	SS316L/SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
6.	Pressure Reducing Valve	SS316L/SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
7.	Needle Valve	SS316L/SS304	#150/#800	Factory Finish	Aira/Hawa

B. INSTRUMENT					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Level Transmitter	SS316	#150	Electropolishing/Matt	Vega/ E&H
2.	Level Gauge	SS316	#150	Electropolishing/Matt	Wika
3.	Pressure Indicator	SS316	#150	Electropolishing/Matt	E&H /Yokogawa
4.	Level Switch	SS316	#150	Electropolishing/Matt	Vega/ E&H
5.	Flow Switch	SS316	#150	Electropolishing/Matt	E&H
6.	Level Indicator	SS316	#150	Electropolishing/Matt	E&H

C. PUMP					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
A.	Centrifugal Pump	SS316	#150	Electropolishing/Matt	Alfa Laval/Fristam

D. ACCESSORIES								
SR. NO	ITEM	SIZE NB					MOC	QTY
1.	PIPE	15	25	40	50	80	SS316/SS304	AS PER P&ID
2.	FLANGES	15	25	40	50	80	SS316/SS304	
3.	GASKET	15	25	40	50	80	PTFE	
4.	NBW	15	25	40	50	80	Standard	


**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 30 OF 71

1. DUMP TANK -2.5 KL
PROCESS DETAILS

Fluid	Dump & Seal Water
Fluid Sp. Gr.	~1.2
Fluid Viscosity (in cP)	~200
Design Temperature in (°C)	52
Maximum Operating Temperature in (°C)	10-40
Maximum Operating Pressure in (Kg/cm ²)	FV-3
Design Pressure in (Kg/cm ²)	3.9
Hydro test Pressure (Kg/cm ²)	5

MECHANICAL DETAILS

Design Code	ASME SECTION VIII DIV.1
Joint Efficiency (Shell/Head)	0.85/1.00
Radiography (Shell/Head)	Spot (10 % + All T Joints)/Full
Corrosion Allowance in mm	NIL

WETTED PART MOC AND GRADE

Shell	SA 240 Gr 304
Top & Bottom Dish Head	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 above 150 NB SA 240 Gr 304
Nozzle Flanges	SORF Flange A182 Stainless Steel 304 B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE

NON-WETTED PART MOC AND GRADE

Plate	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 SCH 40 and Above 150 NB SA 240 Gr 304
Nozzle Connections	SORF Flange A182 Stainless Steel 304 B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE

VESSEL DETAILS

Gross Capacity	3.1 KL
Working Capacity	2.5 KL



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 31 OF 71

Tank Diameter (in mm)	1400
Tank Height TL to TL (in mm)	1700
Tank Shell Shape/Orientation	Cylindrical/Vertical
Shell Thickness of Base Material	5 mm
Tank Top Dish End Type	10% Torrispherical Dish Head
Top Dish End Thickness	5 mm
Tank Bottom Dish End Type	10% Torrispherical Dish Head
Bottom Dish End Thickness	5 mm

ACCESSORIES

Lug Support	4 No's/ SS 304
Lifting Lugs	2 No's/ SS 304
Earthing Clit	2 No's/ SS 304

SURFACE FINISH

Surface Finish Internal	Acid Pickling & Passivation
Surface Finish External	Acid Pickling & Passivation
Quantity	2 Nos.

NOZZLE SCHEDULE

Nozzle	Description	Size, NB	Rating	Sch./Thk	Qty	Remark
HH	Hand hole	150 NB	-	-	1	-
N1	Inlet	25 NB	#150	40	3	SORF
N2	Vent	25 NB	#150	40	1	SORF
N3	Outlet	25 NB	#150	40	2	SORF
N4	LT	25 NB	#150	40	1	SORF
N5	Spare	25 NB	#150	40	2	SORF
N6	SG/LG	25 NB	#150	40	2	SORF

2. WATER SEAL TANK -500 L

PROCESS DETAILS

Fluid	Dump & Seal Water
Fluid Sp. Gr.	~1.2
Fluid Viscosity (in cP)	~200
Design Temperature in (°C)	52
Maximum Operating Temperature in (°C)	10-40
Maximum Operating Pressure in (Kg/cm ²)	FV-3
Design Pressure in (Kg/cm ²)	3.9
Hydro test Pressure (Kg/cm ²)	5

MECHANICAL DETAILS

Design Code	ASME SECTION VIII DIV.1
Joint Efficiency (Shell/Head)	0.85/1.00
Radiography (Shell/Head)	Spot (10 % + All T Joints)/Full
Corrosion Allowance in mm	NIL

WETTED PART MOC AND GRADE

Shell	SA 240 Gr 304
Top & Bottom Dish Head	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 above 150 NB SA 240 Gr 304
Nozzle Flanges	SORF Flange A182 Stainless Steel 304 B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE

NON-WETTED PART MOC AND GRADE

Plate	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 SCH 40 and Above 150 NB SA 240 Gr 304
Nozzle Connections	SORF Flange A182 Stainless Steel 304 B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE

VESSEL DETAILS

Gross Capacity	0.65 KL
Working Capacity	0.5 KL



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 33 OF 71

Tank Diameter (in mm)	800
Tank Height TL to TL (in mm)	1100
Tank Shell Shape/Orientation	Cylindrical/Vertical
Shell Thickness of Base Material	4 mm
Tank Top Dish End Type	10% Torrispherical Dish Head
Top Dish End Thickness	4 mm
Tank Bottom Dish End Type	10% Torrispherical Dish Head
Bottom Dish End Thickness	4 mm

ACCESSORIES

Lug Support	4 No's/ SS 304
Lifting Lugs	2 No's/ SS 304
Earthing Clit	2 No's/ SS 304

SURFACE FINISH

Surface Finish Internal	Electropolishing
Surface Finish External	Matt
Quantity	2 Nos.

NOZZLE SCHEDULE

Nozzle	Description	Size, NB	Rating	Sch./Thk	Qty	Remark
HH	Hand hole	150 NB	-	-	1	-
N1	Inlet	25 NB	#150	40	3	SORF
N2	Vent	25 NB	#150	40	1	SORF
N3	Outlet	25 NB	#150	40	2	SORF
N4	LT	25 NB	#150	40	1	SORF
N5	Spare	25 NB	#150	40	2	SORF
N6	SG/LG	25 NB	#150	40	2	SORF

	ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)			
	TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY		ISSUE:	VERSION: 1
			DOCUMENT NO.	APSPL- 25-26-R0
			DATE :	21-01-2026
			PAGE NO.	PAGE 34 OF 71

A. VALVE

SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Manual Ball Valve	SS304	#150/#800	Factory Finish	L&T, Audco
2.	Actuated Ball Valve	SS304	#150/#800	Factory Finish	L&T, Audco
3.	Control Valve	SS304	#150/#800	Factory Finish	Siemens Sipart / Samson
4.	Non Return Valve	SS304	#150/#800	Factory Finish	L&T, Audco, KSB
5.	Pressure Safety Valve	SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
6.	Pressure Reducing Valve	SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
7.	Needle Valve	SS304	#150/#800	Factory Finish	Aira/Hawa

B. INSTRUMENT

SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Level Transmitter	SS304	#150	Electropolishing/Matt	Vega/ E&H
2.	Level Gauge	SS304	#150	Electropolishing/Matt	Wika
3.	Pressure Indicator	SS304	#150	Electropolishing/Matt	E&H /Yokogawa
4.	Level Switch	SS304	#150	Electropolishing/Matt	Vega/ E&H
5.	Flow Switch	SS304	#150	Electropolishing/Matt	E&H
6.	Level Indicator	SS304	#150	Electropolishing/Matt	E&H

C. PUMP

SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Centrifugal Pump	SS304	#150	Electropolishing/Matt	Alfa Laval/Fristam

D. ACCESSORIES

SR. NO	ITEM	SIZE NB					MOC	QTY
1.	PIPE	15	25	40	50	80	SS304	AS PER P&ID
2.	FLANGES	15	25	40	50	80	SS304	
3.	GASKET	15	25	40	50	80	PTFE	
4.	NBW	15	25	40	50	80	Standard	

**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 35 OF 71

C) BUFFER & DISSOLUTION SYSTEM

A. BUFFER & DISSOLUTION TANK-2KL

PROCESS DETAILS

	Shell Side	Limpet side
Fluid	Solvent	Chilled Water/Hot Water
Fluid Sp. Gr.	~1.1	Client to confirm
Fluid Viscosity (in cP)	~100	Client to confirm
Design Temperature in (°C)	52	169
Maximum Operating Temperature in (°C)	10-40	130
Maximum Operating Pressure in (Kg/cm ²)	FV-3	3.5
Design Pressure in (Kg/cm ²)	3.9	4.5
Hydro test Pressure (Kg/cm ²)	5	5.8
Solid Particles	NA	

MECHANICAL DETAILS

Design Code	ASME SECTION VIII DIV.1 & ASME BPE
Joint Efficiency (Shell/Head)	0.85/1.00
Radiography (Shell/Head)	Spot (10 % + All T Joints)/ Full
Corrosion Allowance in mm	NIL

WETTED PART MOC AND GRADE

Shell	SA 240 Gr 316L
Top & Bottom Dish Head	SA 240 Gr 316L
Baffles Plate	SA 240 Gr 316L
Nozzle Pipe	Up to 150 NB SA 312 Gr 316L above 150 NB SA 240 Gr 316
Nozzle Flanges	SORF Flange A182 Stainless Steel 316 L B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8M and SA 194 Gr 8M
Gasket	PTFE

NON-WETTED PART MOC AND GRADE

Plate	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 SCH 40 and Above 150 NB SA 240 Gr 304
Nozzle Connections	SORF Flange A182 Stainless Steel 304 B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE


**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 36 OF 71

VESSEL DETAILS

Gross Capacity	3.1 KL
Working Capacity	2 KL
Tank Diameter (in mm)	1300
Tank Height TL to TL (in mm)	1950
Tank Shell Shape/Orientation	Cylindrical/Vertical
Shell Thickness of Base Material	5 mm
Tank Top Dish End Type	10% Torrispherical Dish Head
Top Dish End Thickness	6 mm
Tank Bottom Dish End Type	10% Torrispherical Dish Head
Bottom Dish End Thickness	6 mm

LIMPET DETAILS

Limpet OD (in mm)	73
Limpet Pitch (in mm)	100
Limpet Thickness (in mm)	3
No. of Turns	12 No's
MOC	SS304

INSULATION DETAILS

Insulation MOC	Rockwool + Puff
Insulation Thickness	40 mm + 50 mm
Cladding Thickness	3 mm
Cladding MOC	SS304

ACCESSORIES

Baffles	L- 1850 mm x W- 130 mm x Thk- 4 mm
Mounting	Platform (SS 304 dimple type)
Spray Ball	SS316L/2 Nos/Lechler Make
Lug Support	4 No's/ SS 304+SS316L
Lifting Lugs	2 No's/ SS 304
Earthing Clit	2 No's/ SS 304

SURFACE FINISH

Surface Finish Internal	240 Grit Mirror Finish + Electropolishing
Surface Finish External	120 Grit Matt Finish
Quantity	02 Nos.

**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 37 OF 71

NOZZLE SCHEDULE

Nozzle	Description	Size, NB	Rating	Sch./Thk	Qty	Remark
HH	Hand hole	350 NB	-	-	1	-
AG	Agitator	150 NB	-	-	1	PAD Type
N1	Inlet	50 NB	#150	40	4	SORF
N2	Dip Pipe	25 NB	#150	40	4	SORF
N3	Vent	25 NB	#150	40	1	SORF
N4	Limpet Inlet	25 NB	#150	40	1	SORF
N5	Limpet Outlet	25 NB	#150	40	1	SORF
N6	Outlet	50 NB	#150	40	8	SORF
N7	Thermo well	25 NB	#150	40	1	SORF
N8	Spare	25 NB	#150	40	3	SORF

MIXER SPECIFICATION

TOP ENTRY AGITATOR MAKE - ACME

Type	Top Entry
Mounting	Center
Mixer Model	AGIHM – 1.1
Motor	1.1 kW/4P/FLP/1415/50Hz/IE3/VFD SUIT/CGL MAKE
Gearbox	Inline Helical/ Bonfiglioli make
Gear Box Model	AS _30
Gear Box Reduction Ratio	RR -15.37
Type of Impeller	2 x PBT W/O Fins + 1 x Kicker
Impeller Qty. x type x Ø	2 x PBT W/O Fins of Ø 590 mm
Mixers speed	~ 92 rpm
Tip Speed	PBT W/O Fins – 2.8 m/sec
Shaft Ø	Solid Shaft of Ø 60 mm
Shaft Length	2350 mm
Shaft Sealing	Single Mechanical Seal of Hi-fab Make
Wetted Part MOC	SS316 L
Non-Wetted Part MOC	SS 304
Contact Part Surface Finish	Electropolishing
Qty	2 No's

 ACME PROCESS : PEOPLE : PLANET	ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)			
	TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY	ISSUE:	VERSION: 1	
		DOCUMENT NO.	APSPL- 25-26-R0	
		DATE :	21-01-2026	
		PAGE NO.	PAGE 38 OF 71	

A. VALVE-					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Manual Ball Valve	SS316L/SS304	#150/#80 0	Factory Finish	Crane Saunders/Stillon/Micro pneumatics
2.	Actuated Ball Valve	SS316L/SS304	#150/#80 0	Factory Finish	Crane Saunders/Stillon/Micro pneumatics
3.	Control Valve	SS316L/SS304	#150/#80 0	Factory Finish	Siemens Sipart / Samson
4.	Non Return Valve	SS316L/SS304	#150/#80 0	Factory Finish	Crane Saunders/Stillon/Micro pneumatics
5.	Pressure Safety Valve	SS316L/SS304	#150/#80 0	Factory Finish	Anderson Greenwood (Emerson)/LECO
6.	Pressure Reducing Valve	SS316L/SS304	#150/#80 0	Factory Finish	Anderson Greenwood (Emerson)/LECO
7.	Needle Valve	SS316L/SS304	#150/#80 0	Factory Finish	Aira/Hawa
8.	Rupture Disc	SS316L/SS304	#150/#80 0	Factory Finish	BS&B/Fike
9.	Bag Filter	SS316L/SS304	#150/#80 0	Factory Finish	3M or equivalent
10.	Flush Bottom Valve	SS316L/SS304	#150/#80 0	Factory Finish	ITT/Asco (Emerson)
11.	Sampling Valve	SS316L/SS304	#150/#80 0	Factory Finish	ITT/Asco (Emerson)

B. INSTRUMENT-					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Flow Indicator	SS316	#150	Electropolishing/Matt	Vega/ E&H
2.	Flow Switch	SS316	#150	Electropolishing/Matt	Vega/ E&H
3.	Level Gauge	SS316	#150	Electropolishing/Matt	Wika
4.	Pressure Indicator	SS316	#150	Electropolishing/Matt	Vega/ E&H
5.	Pressure Switch	SS316	#150	Electropolishing/Matt	Vega/ E&H
6.	Pressure Indicator Transmitter	SS316	#150	Electropolishing/Matt	Vega/ E&H
7.	Level Transmitter	SS316	#150	Electropolishing/Matt	Vega/ E&H
8.	Pressure Transmitter	SS316	#150	Electropolishing/Matt	E&H /Yokogawa
9.	Level Switch	SS316	#150	Electropolishing/Matt	Vega/ E&H
10.	Load Cell	SS316	#150	-	Mettler Toledo
11.	Flow Indicator	SS316	#150	Electropolishing/Matt	E&H
12.	Temperature Transmitter	SS316	#150	Electropolishing/Matt	E&H
13.	Rupture Disc with Indicator	SS316	#150	Electropolishing/Matt	Fainger/Nirmal



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 39 OF 71

C. PUMP-

SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Centrifugal Pump	SS316L	#150	Electropolishing/Matt	Alfa Laval/Fristam

D. ACCESSORIES-

SR. NO	ITEM	SIZE NB					MOC	QTY
1.	PIPE	15	25	40	50	80	SS316L	AS PER P&ID
2.	FLANGES	15	25	40	50	80	SS316L	
3.	GASKET	15	25	40	50	80	PTFE	
4.	NBW	15	25	40	50	80	Standard	



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 40 OF 71

D) DSP AREA-1

A. PROCESS TANK-2KL

PROCESS DETAILS

	Shell Side	Limpet side
Fluid	Solvent (DAC-1 & DAC-2)	Chilled Water/Hot Water
Fluid Sp. Gr.	~1.1	Client to confirm
Fluid Viscosity (in cP)	~100	Client to confirm
Design Temperature in (°C)	195	169
Maximum Operating Temperature in (°C)	150	130
Maximum Operating Pressure in (Kg/cm ²)	FV-3	3.5
Design Pressure in (Kg/cm ²)	3.9	4.5
Hydro test Pressure (Kg/cm ²)	5.5	5.8
Solid Particles	NA	

MECHANICAL DETAILS

Design Code	ASME SECTION VIII DIV.1 & ASME BPE
Joint Efficiency (Shell/Head)	0.85/1.00
Radiography (Shell/Head)	Spot (10% + All T Joints)/Full
Corrosion Allowance in mm	NIL

WETTED PART MOC AND GRADE

Shell	SA 240 Gr 316L
Top & Bottom Dish Head	SA 240 Gr 316L
Baffles Plate	SA 240 Gr 316L
Nozzle Pipe	Up to 150 NB SA 312 Gr 316L above 150 NB SA 240 Gr 316
Nozzle Flanges	SORF Flange A182 Stainless Steel 316 L B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8M and SA 194 Gr 8M
Gasket	PTFE

NON-WETTED PART MOC AND GRADE

Plate	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 SCH 40 and Above 150 NB SA 240 Gr 304
Nozzle Connections	SORF Flange A182 Stainless Steel 304 L B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE


**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 41 OF 71

VESSEL DETAILS

Gross Capacity	3.1 KL
Working Capacity	2 KL
Tank Diameter (in mm)	1300
Tank Height TL to TL (in mm)	1950
Tank Shell Shape/Orientation	Cylindrical/Vertical
Shell Thickness of Base Material	5 mm
Tank Top Dish End Type	10% Torrispherical Dish Head
Top Dish End Thickness	6 mm
Tank Bottom Dish End Type	10% Torrispherical Dish Head
Bottom Dish End Thickness	6 mm

LIMPET DETAILS

Limpet OD (in mm)	73
Limpet Pitch (in mm)	100
Limpet Thickness (in mm)	3
No. of Turns	12 No's
MOC	SS304

INSULATION DETAILS

Insulation MOC	Rockwool + Puff
Insulation Thickness	40 mm + 50 mm
Cladding Thickness	3 mm
Cladding MOC	SS304

ACCESSORIES

Baffles	L- 1850 mm x W- 130 mm x Thk- 4 mm
Mounting	Platform (SS304 Dimple type)
Spray Ball	SS316L/2 Nos/ Lechler Make
Lug Support	4 No's/ SS 304+SS316L
Lifting Lugs	2 No's/ SS 304
Earthing Clit	2 No's/ SS 304

SURFACE FINISH

Surface Finish Internal	240 Grit mirror finish + Electro polishing
Surface Finish External	120 Grit Matt Finish
Quantity	04 Nos.



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 42 OF 71

NOZZLE SCHEDULE

Nozzle	Description	Size, NB	Rating	Sch./Thk	Qty	Remark
HH	Hand hole	350 NB	-	-	1	-
AG	Agitator	150 NB	-	-	1	Pad Type
N1	Inlet	50	#150	40	10	Sanitary Ferrule
N2	Dip Pipe	25	#150	40	4	Sanitary Ferrule
N3	Vent	25	#150	40	1	Sanitary Ferrule
N4	Limpet Inlet	25 NB	#150	40	1	SORF
N5	Limpet Outlet	25 NB	#150	40	1	SORF
N6	Outlet	50	#150	40	8	Sanitary Ferrule
N7	Thermo well	25	#150	40	1	Sanitary Ferrule
N9	Spare	25	#150	40	3	Sanitary Ferrule

MIXER SPECIFICATION

TOP ENTRY AGITATOR MAKE - ACME

Type	Top Entry
Mounting	Center
Mixer Model	AGIHM – 1.1
Motor	1.1 kW/4P/FLP/1415/50Hz/IE3/VFD SUIT/CGL MAKE
Gearbox	Inline Helical/ Bonfiglioli make
Gear Box Model	AS _30
Gear Box Reduction Ratio	RR -15.37
Type of Impeller	2 x PBT W/O Fins + 1 x Kicker
Impeller Qty. x type x Ø	2 x PBT W/O Fins of Ø 590 mm
Mixers speed	~ 93 rpm
Tip Speed	PBT W/O Fins – 2.8 m/sec
Shaft Ø	Solid Shaft of Ø 60 mm
Shaft Length	2350 mm
Shaft Sealing	Single Mechanical Seal of Hi-fab Make
Wetted Part MOC	SS316L
Non-Wetted Part MOC	SS 304
Contact Part Surface Finish	Electropolishing
Qty	4 No's

	ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)			
	TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY		ISSUE:	VERSION: 1
			DOCUMENT NO.	APSPL- 25-26-R0
			DATE :	21-01-2026
			PAGE NO.	PAGE 43 OF 71

A. VALVE					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Manual Ball Valve	SS316L/SS304	#150/#800	Factory Finish	Crane Saunders/Stillon/Micro pneumatics
2.	Actuated Ball Valve	SS316L/SS304	#150/#800	Factory Finish	Crane Saunders/Stillon/Micro pneumatics
3.	Control Valve	SS316L/SS304	#150/#800	Factory Finish	Siemens Sipart / Samson
4.	Non Return Valve	SS316L/SS304	#150/#800	Factory Finish	Crane Saunders/Stillon/Micro pneumatics
5.	Pressure Safety Valve	SS316L/SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
6.	Pressure Reducing Valve	SS316L/SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
7.	Needle Valve	SS316L/SS304	#150/#800	Factory Finish	Aira/Hawa
8.	Rupture Disc	SS316L/SS304	#150/#800	Factory Finish	BS&B/Fike
9.	Bag Filter	SS316L/SS304	#150/#800	Factory Finish	3M or equivalent
10.	Flush Bottom Valve	SS316L/SS304	#150/#800	Factory Finish	ITT/Asco (Emerson)
11.	Sampling Bottom Valve	SS316L/SS304	#150/#800	Factory Finish	ITT/Asco (Emerson)

B. INSTRUMENT					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Flow Indicator	SS316	#150	Electropolishing/Matt	Vega/ E&H
2.	Flow Switch	SS316	#150	Electropolishing/Matt	Vega/ E&H
3.	Level Gauge	SS316	#150	Electropolishing/Matt	Wika
4.	Pressure Indicator	SS316	#150	Electropolishing/Matt	Vega/ E&H
5.	Pressure Switch	SS316	#150	Electropolishing/Matt	Vega/ E&H
6.	Pressure Indicator Transmitter	SS316	#150	Electropolishing/Matt	Vega/ E&H
7.	Level Transmitter	SS316	#150	Electropolishing/Matt	Vega/ E&H
8.	Pressure Transmitter	SS316	#150	Electropolishing/Matt	E&H /Yokogawa
9.	Level Switch	SS316	#150	Electropolishing/Matt	Vega/ E&H
10.	Load Cell	SS316	#150	-	Mettler Toledo
11.	Flow Indicator	SS316	#150	Electropolishing/Matt	E&H
12.	Temperature Transmitter	SS316	#150	Electropolishing/Matt	E&H
13.	Rupture Disc with Indicator	SS316	#150	Electropolishing/Matt	Fainger/Nirmal



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 44 OF 71

C. ACCESSORIES-

SR. NO	ITEM	SIZE MM					MOC	QTY
5.	TUBE	12.7	25.4	38.1	50.8	76.2	SS316L	AS PER P&ID
6.	FLANGES	12.7	25.4	38.1	50.8	76.2	SS316L	
7.	GASKET	12.7	25.4	38.1	50.8	76.2	PTFE	
8.	NBW	12.7	25.4	38.1	50.8	76.2	Standard	

D. CIP SKID FOR DAC-1

COMPONENTS	
CIP Vessel	1 KL (SS316L)
Dosing Tank	2 Nos of 50 L (SS316L)
Heat Exchanger	Shell & Tube Heat Exchanger (SS316L)
Pump	2 Nos Centrifugal Pump (SS316)
Valve	SS316L
Piping	SS316L
Instrumentation & Automation	Instrumentation along with Local control panel for Monitoring and Control

**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 45 OF 71

E) DSP AREA-2

A. PROCESS TANK-1KL

PROCESS DETAILS

	Shell Side	Limpet side
Fluid	Solvent (DAC-1 & DAC-2)	Chilled Water/Hot Water
Fluid Sp. Gr.	~1.1	Client to confirm
Fluid Viscosity (in cP)	~100	Client to confirm
Design Temperature in (°C)	195	169
Maximum Operating Temperature in (°C)	150	130
Maximum Operating Pressure in (Kg/cm ²)	FV-3	3.5
Design Pressure in (Kg/cm ²)	3.9	4.5
Hydro test Pressure (Kg/cm ²)	5	5.8
Solid Particles	NA	

MECHANICAL DETAILS

Design Code	ASME SECTION VIII DIV.1 & ASME BPE
Joint Efficiency (Shell/Head)	0.85/1.00
Radiography (Shell/Head)	Spot (10 % + All T Joints)/Full
Corrosion Allowance in mm	NIL

WETTED PART MOC AND GRADE

Shell	SA 240 Gr 316L
Top & Bottom Dish Head	SA 240 Gr 316L
Baffles Plate	SA 240 Gr 316L
Nozzle Pipe	Up to 150 NB SA 312 Gr 316L above 150 NB SA 240 Gr 316
Nozzle Flanges	SORF Flange A182 Stainless Steel 316 L B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8M and SA 194 Gr 8M
Gasket	PTFE

NON-WETTED PART MOC AND GRADE

Plate	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 SCH 40 and Above 150 NB SA 240 Gr 304
Nozzle Connections	SORF Flange A182 Stainless Steel 304 L B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE



**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 46 OF 71

VESSEL DETAILS

Gross Capacity	1.25 KL
Working Capacity	1 KL
Tank Diameter (in mm)	1000
Tank Height TL to TL (in mm)	1500
Tank Shell Shape/Orientation	Cylindrical/Vertical
Shell Thickness of Base Material	5 mm
Tank Top Dish End Type	10% Torrispherical Dish Head
Top Dish End Thickness	5 mm
Tank Bottom Dish End Type	10% Torrispherical Dish Head
Bottom Dish End Thickness	5 mm

LIMPET DETAILS

Limpet OD (in mm)	73
Limpet Pitch (in mm)	100
Limpet Thickness (in mm)	3
No. of Turns	12 No's
MOC	SS304

INSULATION DETAILS

Insulation MOC	Rockwool + Puff
Insulation Thickness	40 mm + 50 mm
Cladding Thickness	3 mm
Cladding MOC	SS304

ACCESSORIES

Baffles	L- 1400 mm x W- 100 mm x Thk- 4 mm
Mounting	Platform (SS304 Dimple type)
Spray Ball	SS316L/2 Nos/ Lechler Make
Lug Support	4 No's/ SS 304+SS316L
Lifting Lugs	2 No's/ SS 304
Earthing Clit	2 No's/ SS 304

SURFACE FINISH

Surface Finish Internal	240 Grit mirror finish + Electro polishing
Surface Finish External	120 Grit Matt Finish
Quantity	04 Nos.



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 47 OF 71

NOZZLE SCHEDULE

Nozzle	Description	Size, NB	Rating	Sch./Thk	Qty	Remark
HH	Hand hole	350 NB	-	-	1	-
AG	Agitator	150 NB	-	-	1	PAD Type
N1	Inlet	25	#150	40	10	Sanitary Ferrule
N2	Dip Pipe	25	#150	40	4	Sanitary Ferrule
N3	Vent	25	#150	40	1	Sanitary Ferrule
N4	Limpet Inlet	25 NB	#150	40	1	TC END
N5	Limpet Outlet	25 NB	#150	40	1	TC END
N6	Outlet	25	#150	40	8	Sanitary Ferrule
N7	Thermowell	25	#150	40	1	Sanitary Ferrule
N8	Spare	25	#150	40	3	Sanitary Ferrule
N9	SG/LG	25	#150	40	2	Sanitary Ferrule

MIXER SPECIFICATION

TOP ENTRY AGITATOR MAKE - ACME

Type	Top Entry
Mounting	Center
Mixer Model	AGIHM – 1.1
Motor	1.1 kW/4P/FLP/1415/50Hz/IE3/VFD SUIT/CGL MAKE
Gearbox	Inline Helical/ Bonfiglioli make
Gear Box Model	AS _30
Gear Box Reduction Ratio	RR -15.37
Type of Impeller	2 x PBT W/O Fins
Impeller Qty. x type x Ø	2 x PBT W/O Fins of Ø 450 mm
Mixers speed	~ 100 rpm
Tip Speed	PBT W/O Fins – 2.8 m/sec
Shaft Ø	Solid Shaft of Ø 50 mm
Shaft Length	1840 mm
Shaft Sealing	Single Mechanical Seal of Hi-fab Make
Wetted Part MOC	SS316 L
Non-Wetted Part MOC	SS 304
Contact Part Surface Finish	Electro Polishing
Qty	04 No's

	ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)			
	TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY	ISSUE:	VERSION: 1	
		DOCUMENT NO.	APSPL- 25-26-R0	
		DATE :	21-01-2026	
		PAGE NO.	PAGE 48 OF 71	

A. VALVE					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Manual Ball Valve	SS316L/SS304	#150/#800	Factory Finish	Crane Saunders/Stillon/Micro pneumatics
2.	Actuated Ball Valve	SS316L/SS304	#150/#800	Factory Finish	Crane Saunders/Stillon/Micro pneumatics
3.	Control Valve	SS316L/SS304	#150/#800	Factory Finish	Siemens Sipart / Samson
4.	Non Return Valve	SS316L/SS304	#150/#800	Factory Finish	Crane Saunders/Stillon/Micro pneumatics
5.	Pressure Safety Valve	SS316L/SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
6.	Pressure Reducing Valve	SS316L/SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
7.	Needle Valve	SS316L/SS304	#150/#800	Factory Finish	Aira/Hawa
8.	Rupture Disc	SS316L/SS304	#150/#800	Factory Finish	BS&B/Fike
9.	Bag Filter	SS316L/SS304	#150/#800	Factory Finish	3M or equivalent
10.	Flush Bottom Valve	SS316L/SS304	#150/#800	Factory Finish	ITT/Asco (Emerson)
11.	Sampling Bottom Valve	SS316L/SS304	#150/#800	Factory Finish	ITT/Asco (Emerson)

B. INSTRUMENT					
SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Flow Indicator	SS316	#150	Electropolishing/Matt	Vega/ E&H
2.	Flow Switch	SS316	#150	Electropolishing/Matt	Vega/ E&H
3.	Level Gauge	SS316	#150	Electropolishing/Matt	Wika
4.	Pressure Indicator	SS316	#150	Electropolishing/Matt	Vega/ E&H
5.	Pressure Switch	SS316	#150	Electropolishing/Matt	Vega/ E&H
6.	Pressure Indicator Transmitter	SS316	#150	Electropolishing/Matt	Vega/ E&H
7.	Level Transmitter	SS316	#150	Electropolishing/Matt	Vega/ E&H
8.	Pressure Transmitter	SS316	#150	Electropolishing/Matt	E&H /Yokogawa
9.	Level Switch	SS316	#150	Electropolishing/Matt	Vega/ E&H
10.	Load Cell	SS316	#150	-	Mettler Toledo
11.	Flow Indicator	SS316	#150	Electropolishing/Matt	E&H
12.	Temperature Transmitter	SS316	#150	Electropolishing/Matt	E&H
13.	Rupture Disc with Indicator	SS316	#150	Electropolishing/Matt	Fainger/Nirmal

**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 49 OF 71

C. ACCESSORIES-

SR. NO	ITEM	SIZE MM					MOC	QTY
1.	TUBE	12.7	25.4	38.1	50.8	76.2	SS316L	AS PER P&ID
2.	FLANGES	12.7	25.4	38.1	50.8	76.2	SS316L	
3.	GASKET	12.7	25.4	38.1	50.8	76.2	PTFE	
4.	NBW	12.7	25.4	38.1	50.8	76.2	Standard	

D. CIP SKID FOR DAC-2

COMPONENTS	
CIP Vessel	1 KL (SS316L)
Dosing Tank	2 Nos of 50 L (SS316L)
Heat Exchanger	Shell & Tube Heat Exchanger (SS316L)
Pump	2 Nos Centrifugal Pump (SS316)
Valve	SS316L
Piping	SS316L
Instrumentation & Automation	Instrumentation along with Local control panel for Monitoring and Control



**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 50 OF 71

F) RECEIVER TANK SYSTEM

A. RECEIVER TANK -300L

PROCESS DETAILS

Fluid	Solvent (DAC 1, DAC 2)
Fluid Sp. Gr.	~1.2
Fluid Viscosity (in cP)	~200
Design Temperature in (°C)	52
Maximum Operating Temperature in (°C)	10-40
Maximum Operating Pressure in (Kg/cm ²)	FV to 3
Design Pressure in (Kg/cm ²)	3.9
Hydro test Pressure (Kg/cm ²)	5

MECHANICAL DETAILS

Design Code	ASME SECTION VIII DIV.1
Joint Efficiency (Shell/Head)	0.85/1.00
Radiography (Shell/Head)	Spot (10% + All T Joints)/Full
Corrosion Allowance in mm	NIL

WETTED PART MOC AND GRADE

Shell	SA 240 Gr 316L
Top & Bottom Dish Head	SA 240 Gr 316L
Nozzle Pipe	Up to 150 NB SA 312 Gr 316L above 150 NB SA 240 Gr 316L
Nozzle Flanges	SORF Flange A182 Stainless Steel 316 L B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8M and SA 194 Gr 8M
Gasket	PTFE

NON-WETTED PART MOC AND GRADE

Plate	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 SCH 40 and Above 150 NB SA 240 Gr 304
Nozzle Connections	SORF Flange A182 Stainless Steel 304 B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8
Gasket	PTFE

VESSEL DETAILS

Gross Capacity	400 L
----------------	-------



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 51 OF 71

Working Capacity	300 L
Tank Diameter (in mm)	700
Tank Height TL to TL (in mm)	980
Tank Shell Shape/Orientation	Cylindrical/Vertical
Shell Thickness of Base Material	5 mm
Tank Top Dish End Type	10% Torrispherical Dish Head
Top Dish End Thickness	5 mm
Tank Bottom Dish End Type	10% Torrispherical Dish Head
Bottom Dish End Thickness	5 mm

ACCESSORIES

Lug Support	4 No's/ SS 304+SS316L
Lifting Lugs	2 No's/ SS 304
Earthing Clit	2 No's/ SS 304

SURFACE FINISH

Surface Finish Internal	240 Grit mirror finish + Electro polishing
Surface Finish External	120 Grit Matt Finish
Quantity	2 Nos.

NOZZLE SCHEDULE

Nozzle	Description	Size, NB	Rating	Sch./Thk	Qty	Remark
HH	Hand hole	100 NB	-	-	1	-
N1	Inlet	25 NB	#150	40	2	TC
N2	Vent	25 NB	#150	40	1	TC
N3	Outlet	25 NB	#150	40	1	TC
N4	LT	25 NB	#150	40	1	TC
N5	Spare	15 NB	#150	40	2	TC
N6	SG/LG	25 NB	#150	40	2	TC

**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 52 OF 71

A. VALVE

SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Manual Ball Valve	SS316L/SS304	#150/#800	Factory Finish	Crane Saunders/Stillon/Micropneumatics
2.	Actuated Ball Valve	SS316L/SS304	#150/#800	Factory Finish	Crane Saunders/Stillon/Micropneumatics
3.	Non Return Valve	SS316L/SS304	#150/#800	Factory Finish	Crane Saunders/Stillon/Micropneumatics
4.	Pressure Reducing Valve	SS316L/SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
5.	Needle Valve	SS316L/SS304	#150/#800	Factory Finish	Aira / Rotex Automation

B. INSTRUMENT

SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Level Transmitter	SS316	#150	Electropolishing/Matt	Vega/ E&H
2.	Pressure Transmitter	SS316	#150	Electropolishing/Matt	E&H /Yokogawa
3.	Level Switch	SS316	#150	Electropolishing/Matt	Vega/ E&H
4.	Flow Meter	SS316	#150	Electropolishing/Matt	E&H
5.	Temperature Transmitter	SS316	#150	Electropolishing/Matt	E&H

C. ACCESSORIES-

SR. NO	ITEM	SIZE MM					MOC	QTY
1.	PIPE	12.7	25.4	38.1	50.8	76.2	SS316L	AS PER P&ID
2.	FLANGES	12.7	25.4	38.1	50.8	76.2	SS316L	
3.	GASKET	12.7	25.4	38.1	50.8	76.2	PTFE	
4.	NBW	12.7	25.4	38.1	50.8	76.2	Standard	



**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 53 OF 71

G) RECEIVER TANK SYSTEM

A. LYO TANK -500L

PROCESS DETAILS

Fluid	Solvent (LYO 1, LYO 2)
Fluid Sp. Gr.	~1.2
Fluid Viscosity (in cP)	~200
Design Temperature in (°C)	52
Maximum Operating Temperature in (°C)	10-40
Maximum Operating Pressure in (Kg/cm ²)	FV to 3
Design Pressure in (Kg/cm ²)	3.9
Hydro test Pressure (Kg/cm ²)	5

MECHANICAL DETAILS

Design Code	ASME SECTION VIII DIV.1
Joint Efficiency (Shell/Head)	0.85/1.00
Radiography (Shell/Head)	Spot (10% + All T Joints)/Full
Corrosion Allowance in mm	NIL

WETTED PART MOC AND GRADE

Shell	SA 240 Gr 316L
Top & Bottom Dish Head	SA 240 Gr 316L
Nozzle Pipe	Up to 150 NB SA 312 Gr 316L above 150 NB SA 240 Gr 316L
Nozzle Flanges	SORF Flange A182 Stainless Steel 316 L B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8M and SA 194 Gr 8M
Gasket	PTFE

NON-WETTED PART MOC AND GRADE

Plate	SA 240 Gr 304
Nozzle Pipe	Up to 150 NB SA 312 Gr 304 SCH 40 and Above 150 NB SA 240 Gr 304
Nozzle Connections	SORF Flange A182 Stainless Steel 304 B16.5 150#
Nut + Bolt + Washers	SA 193 Gr B8 and SA 194 Gr 8



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 54 OF 71

Gasket	PTFE					
VESSEL DETAILS						
Gross Capacity	650 L					
Working Capacity	500 L					
Tank Diameter (in mm)	800					
Tank Height TL to TL (in mm)	1120					
Tank Shell Shape/Orientation	Cylindrical/Vertical					
Shell Thickness of Base Material	5 mm					
Tank Top Dish End Type	10% Torrispherical Dish Head					
Top Dish End Thickness	5 mm					
Tank Bottom Dish End Type	10% Torrispherical Dish Head					
Bottom Dish End Thickness	5 mm					
ACCESSORIES						
Lug Support	4 No's/ SS 304+SS316L					
Lifting Lugs	2 No's/ SS 304					
Earthing Clit	2 No's/ SS 304					
SURFACE FINISH						
Surface Finish Internal	240 Grit mirror finish + Electro polishing					
Surface Finish External	120 Grit Matt Finish					
Quantity	2 Nos.					
NOZZLE SCHEDULE						
Nozzle	Description	Size, NB	Rating	Sch./Thk	Qty	Remark
HH	Hand hole	100 NB	-	-	1	-
N1	Inlet	25 NB	#150	40	2	TC
N2	Vent	25 NB	#150	40	1	TC
N3	Outlet	25 NB	#150	40	1	TC
N4	LT	25 NB	#150	40	1	TC
N5	Spare	15 NB	#150	40	2	TC
N6	SG/LG	25 NB	#150	40	2	TC



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 55 OF 71

MIXER SPECIFICATION

TOP ENTRY AGITATOR MAKE - ACME

Type	Top Entry
Mounting	Center
Mixer Model	AGIHM – 1.1
Motor	1.1 kW/4P/FLP/1415/50Hz/IE3/VFD SUIT/CGL MAKE
Gearbox	Inline Helical/ Bonfiglioli make
Gear Box Model	AS _30
Gear Box Reduction Ratio	RR -15.37
Type of Impeller	2 x PBT W/O Fins
Impeller Qty. x type x Ø	2 x PBT W/O Fins of Ø 320 mm
Mixers speed	~ 92 rpm
Tip Speed	PBT W/O Fins – 2.8 m/sec
Shaft Ø	Solid Shaft of Ø 45 mm
Shaft Length	1300 mm
Shaft Sealing	Single Mechanical Seal of Hi-fab Make
Wetted Part MOC	SS316 L
Non-Wetted Part MOC	SS 304
Contact Part Surface Finish	Electro Polishing
Qty	02 No's



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 56 OF 71

A. VALVE

SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Manual Ball Valve	SS316L/SS304	#150/#800	Factory Finish	Crane Saunders/Stillon/Micropneumatics
2.	Actuated Ball Valve	SS316L/SS304	#150/#800	Factory Finish	Crane Saunders/Stillon/Micropneumatics
3.	Non Return Valve	SS316L/SS304	#150/#800	Factory Finish	Crane Saunders/Stillon/Micropneumatics
4.	Pressure Reducing Valve	SS316L/SS304	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
5.	Needle Valve	SS316L/SS304	#150/#800	Factory Finish	Aira / Rotex Automation

B. INSTRUMENT

SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Level Transmitter	SS316	#150	Electropolishing/Matt	Vega/ E&H
2.	Pressure Transmitter	SS316	#150	Electropolishing/Matt	E&H /Yokogawa
3.	Level Switch	SS316	#150	Electropolishing/Matt	Vega/ E&H
4.	Flow Meter	SS316	#150	Electropolishing/Matt	E&H
5.	Temperature Transmitter	SS316	#150	Electropolishing/Matt	E&H

C. ACCESSORIES-

SR. NO	ITEM	SIZE NB					MOC	QTY
1.	PIPE	12.7	25.4	38.1	50.8	76.2	SS316L	AS PER P&ID
2.	FLANGES	12.7	25.4	38.1	50.8	76.2	SS316L	
3.	GASKET	12.7	25.4	38.1	50.8	76.2	PTFE	
4.	NBW	12.7	25.4	38.1	50.8	76.2	Standard	

	ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)			
	TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY		ISSUE:	VERSION: 1
			DOCUMENT NO.	APSPL- 25-26-R0
			DATE :	21-01-2026
			PAGE NO.	PAGE 57 OF 71

E. ACCESSORIES FOR 400L GLR-

- PLATFORM AND ACCESSORIES FOR 400L GLR- 2 NOS

A. VALVE

SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Manual Ball Valve	SS304+PTFE	#150/#800	Factory Finish	Polyvalve/Resistotech/ Horizon
2.	Actuated Ball Valve	SS304+PTFE	#150/#800	Factory Finish	Polyvalve/Resistotech/ Horizon
3.	Control Valve	SS304+PTFE	#150/#800	Factory Finish	Siemens Sipart / Samson
4.	Non Return Valve	SS304+PTFE	#150/#800	Factory Finish	L&T, Audco, KSB
5.	Pressure Safety Valve	SS304+PTFE	#150/#800	Factory Finish	Fainger
6.	Pressure Reducing Valve	SS304+PTFE	#150/#800	Factory Finish	Anderson Greenwood (Emerson)/LECO
7.	Needle Valve	SS304+PTFE	#150/#800	Factory Finish	Reputed
8.	Rupture Disc	SS304+PTFE	#150/#800	Factory Finish	BS&B/Fike
9.	Bag Filter	SS304+PTFE	#150/#800	Factory Finish	3M or equivalent
10.	Flush Bottom Valve	SS304+PTFE	#150/#800	Factory Finish	Smita/Tecnik/Dembla
11.	Sampling Bottom Valve	SS304+PTFE	#150/#800	Factory Finish	Smita/Tecnik/Dembla

B. INSTRUMENT

SR. NO	DESCRIPTION	MOC	RATING	SURFACE FINISH	MAKE
1.	Flow Indicator	Hastelloy	#150	Electropolishing/Matt	Vega/ E&H
2.	Flow Switch	Hastelloy	#150	Electropolishing/Matt	Vega/ E&H
3.	Level Gauge	Hastelloy	#150	Electropolishing/Matt	Wika
4.	Pressure Indicator	Hastelloy	#150	Electropolishing/Matt	Vega/ E&H
5.	Pressure Switch	Hastelloy	#150	Electropolishing/Matt	Vega/ E&H
6.	Pressure Indicator Transmitter	Hastelloy	#150	Electropolishing/Matt	Vega/ E&H
7.	Level Transmitter	Hastelloy	#150	Electropolishing/Matt	Vega/ E&H
8.	Pressure Transmitter	Hastelloy	#150	Electropolishing/Matt	E&H /Yokogawa
9.	Level Switch	Hastelloy	#150	Electropolishing/Matt	Vega/ E&H
10.	Load Cell	Hastelloy	#150	-	Mettler Toledo
11.	Flow Indicator	Hastelloy	#150	Electropolishing/Matt	E&H
12.	Temperature Transmitter	Hastelloy	#150	Electropolishing/Matt	E&H
13.	Rupture Disc with Indicator	Hastelloy	#150	Electropolishing/Matt	Fainger/Nirmal



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 58 OF 71

C. ACCESSORIES-

SR. NO	ITEM	SIZE NB					MOC	QTY
5.	PIPE	15	25	40	50	80	SS304+PTFE	AS PER P&ID
6.	FLANGES	15	25	40	50	80	SS304+PTFE	
7.	GASKET	15	25	40	50	80	PTFE	
8.	NBW	15	25	40	50	80	Standard	

**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 59 OF 71

H) TANK SUMMARY-

SR. NO	AREA DETAILS	TANK CAPACITY	QTY	PUMP QTY
1.	MAIN STORAGE TANK	40KL	2 Nos	10 Nos
2.		25 KL	2 Nos	10 Nos
3.	FRESH SOLVENT DAY	2 KL	2 Nos	2 Nos
4.		1 KL	3 Nos	4 Nos
5.	SPENT DAY TANK	2 KL	2 Nos	2 Nos
6.		1 KL	5 Nos	5 Nos
7.	WASTE DAY TANK	1 KL	4 Nos	4 Nos
8.	PROCESS TANKS	2 KL	6 Nos	2 Nos
9.		1 KL	4 Nos	-
10.	RECEIVER TANK	300L	2 Nos	-
11.		500L	2 Nos	-
12.	CIP SKID-DAC-1 & DAC-2	1 KL	2 Nos	4 Nos
13.		50 L	4 Nos	-

I) SOLVENT PREFILTERS

SR. NO	PRODUCT DETAILS	REQUIRED RANGE/ DETAILS
1.	Description	Pre filter shall be provided for each solvent before use in process
2.	Quantity	02 no. each for DMF, ACN, IPA and IPE. MDC (1 working & 1 standby with bypass line)
3.	Rating	Prefilter: As per process activity
4.	Flowrate	Max 2000 LPH
5.	Pressuredrop	Clean: 0. 2 bar Maximum: Vendor to specify
6.	Type	Sintered SS 316 filter medium SS 316 filter housing
7.	End Connections	Flanged to ANSI 150# rating



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:

VERSION: 1

DOCUMENT NO.

APSPL- 25-26-R0

DATE :

21-01-2026

PAGE NO.

PAGE 60 OF 71

J) SOLVENT FINAL FILTERS

SR. NO	PRODUCT DETAILS	REQUIRED RANGE/ DETAILS
1.	Description	Final filter shall be provided for each solvent before use in process.
2.	Quantity	02 no. each for DMF, ACN, IPA, IPE and MDC. (1 working & 1 standby with bypass line)
3.	Rating	Final filter : As per process vendor to specify
4.	Flowrate	Max 2000 LPH
5.	Pressure drop	Clean: 0. 2 bar Maximum: Vendor to specify
6.	Type	Sintered SS 316 filter medium SS 316 filter housing
7.	End Connections	Flanged to ANSI 150# rating

 ACME PROCESS : PEOPLE : PLANET	ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)		
	TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY	ISSUE:	VERSION: 1
		DOCUMENT NO.	APSPL- 25-26-R0
		DATE :	21-01-2026
		PAGE NO.	PAGE 61 OF 71

K) AUTOMATION DETAILS

SR NO.	ITEM DESCRIPTIONS	MAKE	ITEM QTY	FDR QTY	TOTAL QTY	UOM
A	ENCLOSURE FOR PLC PANEL		1	1	1	Nos.
1	PLC PANEL Enclosure 2000(H)X1200(W)X800(D) Floor Mounted RAL-7035 Siemens Grey	Fabricated	2	1	1	Nos.
B	INCOMING SECTION		1	1	1	LOT
1	MCB 2P,63AMP,10kA	Siemens	1	1	1	Nos.
2	Power On/Off Sel. Sw.	Siemens	1	1	1	Nos.
3	Red Indication Lamp, 220VAC supply voltage-LED type	Teknic	1	1	1	Nos.
4	Green Indication Lamp, 24VDC supply voltage-LED type	Teknic	1	4	4	Nos.
5	Neutral Link	Std	1	1	1	Nos.
C	CONTROL SECTION		1	1	1	LOT
1	MCB 2P,25 Amp, 10kA	Siemens	1	1	1	Nos.
2	MCB 2P,20 Amp, 10kA	Siemens	1	2	2	Nos.
3	MCB 2P,16 Amp, 10kA	Siemens	1	2	2	Nos.
4	MCB 2P,10 Amp, 10kA	Siemens	1	2	2	Nos.
5	MCB 2P,6 Amp, 10kA	Siemens	1	2	2	Nos.
6	MCB 2P,2 Amp, 10kA	Siemens	1	6	6	Nos.
7	MCB 1P,4 Amp, 10kA	Siemens	1	2	2	Nos.
8	MCB 1P,2 Amp, 10kA	Siemens	1	10	10	Nos.
9	220Vac Control Distribution Bank R,N	Elmex	1	1	1	Nos.
10	24Vdc Control Distribution Bank 24V,0V	Elmex	1	1	1	Nos.
11	SMPS 20 Amp 24VDC	Meanwell	1	2	2	Nos.
12	SMPS 10 Amp 24VDC	Meanwell	1	2	2	Nos.
13	Redundancy Module 20 Amp	UL	1	1	1	Nos.
14	Redundancy Module 40 Amp	UL	1	1	1	Nos.
15	Utility Socket 5Amp	Anchor	1	1	1	Nos.
D	MAIN PLC SECTION-Redundant		1	1	1	LOT
1	SIMATIC S7-1500H, CPU 1517H System bundle consisting of 2 x CPU 1517H-4 PN, 4 sync modules up to 10 m 2 x sync lines 1 m without memory card	Siemens	1	1	1	Nos.
2	S7-1500, mounting rail 160 mm (6.3")	Siemens	2	1	2	Nos.

	ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)		
	TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY	ISSUE:	VERSION: 1
		DOCUMENT NO.	APSPL- 25-26-R0
		DATE :	21-01-2026
		PAGE NO.	PAGE 62 OF 71

3	SIMATIC S7, MEMORY CARD FOR S7-1X00 CPU, 3,3 V FLASH, 256 MBYTE	Siemens	2	1	2	Nos.
4	PS 25W 24VDC	Siemens	2	1	2	Nos.

E	RIO SECTION- 5 RIO Panel		1	1	1	LOT
1	ET 200SP, IM155-6PN/3 HF	Siemens	5	1	5	Nos.
2	ET 200SP, Bus adapter BA 2xRJ45 Siemens		10	1	10	Nos.
3	ET 200SP, AI 8XI 2-/4-Wire Basic	Siemens	27	1	27	Nos.
4	ET 200SP, AQ 4xU/I ST	Siemens	12	1	12	Nos.
5	ET 200SP, DI 16x 24V DC ST, PU 1	Siemens	63	1	63	Nos.
6	ET 200SP, DQ 16X24VDC/0.5A BA	Siemens	4	1	4	Nos.
7	ET 200SP, CM PTP, PU 1	Siemens	1	2	2	Nos.
8	Base unit Type A0, BU15-P16+A0+2D	Siemens	20	1	20	Nos.
9	Base unit Type A0, BU15-P16+A0+2B	Siemens	88	1	88	Nos.
F	PLC ACCESSORIES		1	1	1	LOT
1	SIMATIC NET, IE FC TP STANDARD CABLE, GP 2X2 (PROFINET TYP A)	Siemens	1	100	100	Mtr.
2	IE FC RJ45 Plug 180 (1 pack = 10 items)	Siemens	1	2	2	Nos.
G	ENGINEERING STATION- REDUNDANT		1	1	1	NOS.
1	Desktop Intel Xeon E-2224G Processor 3.5GHz 8M Cache,4C/4T,Turbo,71W,TPM, 16GB Ram, 1TB HDD RAID10. Windows Server 2019. 24 Inch Monitor	DELL	2	1	2	Nos.
2	Antivirus total Security-1 Yr/1 User	Quick-Heal	2	1	2	Nos.
3	Microsoft Office 2021 ProPlus	Microsoft	2	1	2	Nos.
4	Windows Server 2019 License	Microsoft	2	1	2	Nos.
5	SIMATIC WinCC System software V8.1 8192 Power Tags (RC 8192)	SIEMENS	2	1	2	Nos.
6	WinCC Server V8.1	SIEMENS	2	1	2	Nos.
7	SIMATIC WinCC V8.1 Archive 1500 archive variables (countable)	SIEMENS	2	1	2	Nos.
8	WinCC Redundancy V8.1	SIEMENS	2	1	2	Nos.
9	WinCC/Audit V8.1 Audit RT Server	SIEMENS	2	1	2	Nos.
10	WinCC/Audit V8.1 Audit RC	SIEMENS	2	1	2	Nos.
H	ETHERNET SWITCHES & NETWORK CABINET		1	1	1	NOS.
1	24 Port Managed Ethernet Switch	CISCO	3	1	3	Nos.

 ACME PROCESS : PEOPLE : PLANET	ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)		
	TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY	ISSUE:	VERSION: 1
		DOCUMENT NO.	APSPL- 25-26-R0
		DATE :	21-01-2026
		PAGE NO.	PAGE 63 OF 71

2	Floor/Wall Mount Rack 6U	Std.	1	1	1	Nos.
I	PRINTER A2/A4		1	1	1	NOS.
1	Printer A4 Laser Jet	HP	1	1	1	Nos.
J	HMI Stations		1	2	2	Nos.
1	VisuNet GXP RM/PC system (Visunet GXP Zone 1/21 Technology: Thin Client-based Remote Monitor Display: 21,5" (16:9), FullHD. Front glass & Touch: Anti-glare, 10 finger multi-touch. Front interface: 5x capacitive System front keys & Bluetooth Interface. Supply: 18-36 V DC (Input). Interfaces: 1x Ethernet Ex e, 1x USB Platform: Intel® Atom Elkhart Lake x6211E, 4 GB RAM, 64 GB storage, P+F RM Shell 6.x (based on Win 10 IoT LTS)	P&F	1	6	6	Nos.
2	FAB SUB HMI22" ENCL	P&F	1	6	6	Nos.
3	PEDESTAL STAND	P&F	1	6	6	Nos.
5	SIMATIC WinCC System software V8.1 WinCC RT Client	SIEMENS	6	1	6	Nos.

K	OTHER MATERIAL		1	1	1	LOT
1	Fan Filter	Rexnord	1	6	6	Nos.
2	Tube Light 5W	Philips	1	4	4	Nos.
3	Door limit Sw.	Kyce	1	24	24	Nos.
4	E.Stop	Teknic	1	1	1	Nos.
5	16 Sq.mm Power TB	Elmex	1	10	10	Nos.
6	6 Sq.mm Power TB	Elmex	1	15	15	Nos.
7	Earth TB	Elmex	1	5	5	Nos.
8	Spike Guard 32Amp	Elcom	1	1	1	Nos.
9	Fuse type Terminal 4 Sq. mm With Fuse.	Elmex	1	500	500	Nos.
10	Non Fuse type Terminals 4 Sq. mm	Elmex	1	500	500	Nos.
11	Grey Colour Control Cable 1.5 sq. mm FR	Polycab	1	1	1	Lot
12	Black Colour Control Cable 1.5 sq. mm FR	Polycab	1	1	1	Lot
13	Blue Colour Control Cable 0.75 Sq.mm FR	Polycab	1	1	1	Lot
14	White Colour Control Cable 0.75 Sq.mm FR	Polycab	1	1	1	Lot
15	Grey Colour Control Cable 0.75 Sq.mm FR	Polycab	1	1	1	Lot
16	Yellow Colour Control Cable 0.75 Sq.mm FR	Polycab	1	1	1	Lot
17	Lugs-2.5 Sq.mm Pin Type	Std.	1	1	1	Lot



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 64 OF 71

18	Lugs-1.5 Sq.mm Pin Type	Std.	1	1	1	Lot
19	Lugs-0.75 Sq.mm Pin Type	Std.	1	1	1	Lot
20	End Plate (2.5/6)	Elmex	1	1	1	Lot
21	End Clamp SCUN	Std.	1	1	1	Lot
22	Name Plates	Std.	1	1	1	Lot
23	Hardware	Std.	1	1	1	Lot
24	Cable Duct	Trinity	1	1	1	Lot
25	Spiral	Std.	1	1	1	Lot
26	Terminal Marker	Std.	1	1	1	Lot
27	Ferrule & Yellow Tape	Std.	1	1	1	Lot
28	Consumable accessories (Lock,lugs,gasket,nut bolt and others)	STD.	1	1	1	Nos.



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 65 OF 71

BATTERY LIMITS

DESCRIPTION	ACME SCOPE	CLIENT SCOPE
Equipment Design	ACME SCOPE	
Supply of Equipment's.	ACME SCOPE	
Supply of P&ID	CLIENT SCOPE	
Process Guarantee		CLIENT SCOPE
Mechanical Guarantee	ACME SCOPE	
IQ,OQ & DQ Documents	ACME SCOPE	
PQ		CLIENT SCOPE (Support by ACME)
Supply of Process Valves as per P&ID	ACME SCOPE	
Supply of Utility Valves as per P&ID	ACME SCOPE	
Supply of Instruments as per P&ID	ACME SCOPE	
Supply of Process Piping from Storage tank to Process Area & Inside skid	ACME SCOPE	
Supply of Utility Piping & Accessories till inside rooms manifold		CLIENT SCOPE
Supply of Utility Piping & Accessories from room Manifold to Equipment	ACME SCOPE	
Supply of Insulation to Utility Piping & Accessories till inside room manifold		CLIENT SCOPE
Supply of Insulation to Utility Piping & Accessories from room Manifold to Equipment	ACME SCOPE	
Supply of Electrical all types of cables and accessories for Valves, and Instruments etc..	ACME SCOPE	
Supply of Electrical all types of cables and accessories for Pumps & Agitator	ACME SCOPE	
Earth Pit		CLIENT SCOPE
Earthing Jumpers to all flanges	ACME SCOPE	
Electrical main incomer power supply cable, supply and termination.		CLIENT SCOPE
Supply of Main Cable Trays and Installation inside Process Rooms	ACME SCOPE	
Supply of Main Cable Trays and Installation outside Process Rooms		CLIENT SCOPE
Supply of interconnecting Cable and Installation inside Process Rooms	ACME SCOPE	
Supply of Manpower for wire laying and termination inside Process Rooms	ACME SCOPE	



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-COMMERCIAL OFFER FOR TURNKEY PLANT SUPPLY

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 66 OF 71

Supply of Junction Boxes	ACME SCOPE	
Supply of PLC PANEL	ACME SCOPE	
Supply of RIO Panel for Safe Area	ACME SCOPE	
Supply of Pneumatic Bank for Safe Area	ACME SCOPE	
Supply of HMI for FLP Area	ACME SCOPE	
SCADA System	ACME SCOPE	
License Software's as mentioned in offer	ACME SCOPE	
Supply of MCC Panel	ACME SCOPE	
PLC Programming	ACME SCOPE	
Development of, HMI Screens, Control Logic.	ACME SCOPE	
Functional Specification	ACME SCOPE	
Supply and Installation of Structure for DAC-1, 2 Process Skid and GLR Skids	ACME SCOPE	
All Civil Engineering work and Drawings		CLIENT SCOPE
All pit drains and trench covering		CLIENT SCOPE
Any ventilation and Air Conditioning arrangement		CLIENT SCOPE
Utility Supply and consumables for load trial in Facility		CLIENT SCOPE
Factory Acceptance Test	ACME SCOPE	
Storage of Equipment and Accessories		CLIENT SCOPE
Material Movement at Site		CLIENT SCOPE
Crane Supply for Installation, Erection and Commissioning of Equipment's	ACME SCOPE	
Manpower Supply for Equipment Erection and Piping Fabrication	ACME SCOPE	
Process Piping Fabrication & Installation as per P&ID	ACME SCOPE	
Pipe Rack Fabrication and Installation	ACME SCOPE	
Operational and Maintenance manual	ACME SCOPE	
Trial Run	ACME SCOPE	
Site Acceptance Test (Including water trials and process- demonstration of continuous plant with actual spent solvent)	ACME SCOPE	

**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 67 OF 71

GENERAL NOTES:

1. ID, Height, Imp. Ø, Shaft Length are in mm. speed is in RPM, viscosity in cps, Temp. It is °C, Pressure in Kg/cm².
2. We have Considered Flame proof Area for all the supply.
3. Standard followed for Storage Tank-API-650 (PESO Norms).
4. Standard Followed for All Day Tank- ASME SEC.VIII DIV-I
5. Standard Followed for Process Tanks- ASME SEC.VIII DIV-I & ASME BPE
6. We have Considered All pump, Piping, Instruments, and Valves as per the P&ID.
7. Compatibility of material of construction in contact with in-tank content is not a responsibility of Acme Process Systems.
8. All Gear boxes offered are of Inline Helical Type of Bonfiglioli Make.
9. All the equipment is considered as per the data shared by client.
10. Site operation guarantee for complete package will be 12 months from the date of installation or 18 months from the date of dispatch whichever is earlier.
11. All material test certificates will be provided. Third Party Inspection is in client scope.
12. Anything other than mentioned in the offer is excluded & inclusion of the same will lead to price implication.
13. Due to current situation of COVID-19 outbreak & Ukraine-Russia war, carriers and transport providers throughout the supply chain are cancelling and rescheduling services, schedules are continually being adjusted, and space capacity issues are arising. This instability may affect rates, operations, schedules and access to services globally. ACME is unable to guarantee freight levels and service schedules at this time.



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 68 OF 71

PRICE SUMMARY FOR TURNKEY PROJECT SUPPLY

SR NO	ITEM	QTY	TOTAL PRICE IN INR
1	STORAGE TANK FARM	1 SET	22,95,00,000.00
2	FRESH SOLVENT TANK		
3	DAY TANK		
4	WASTE TANK		
5	BUFFER & DISSOLUTION TANK		
6	DAC-1		
7	DAC-2		
8	GLR ACCESSORIES		
9	PUMP		
10	AUTOMATION		
11	PNEUMATIC BANK		
12	PLATFORM FOR PROCESS VESSEL		
13	PIPE SUPPORT		
14	INSULATION (Process vessel & utility)		
15	IQ,OQ,DQ		
16	SERVICES		
17	FAT, SAT COMMISSIONING		
GRAND TOTAL IN INR FOR EX-WORKS, PUNE			22,95,00,000.00
IN WORDS- TWENTY TWO CRORE NINETY FIVE LAKH INR ONLY			

**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 69 OF 71

TERMS AND CONDITIONS**1.DELIVERY**

- The delivery of the Equipment will be, Ex. work Pune 22 weeks after the date of drawing approval and receipt of advance. And Total project delivery including Erection & Commissioning is 30 Weeks from the date of drawing approval. Based on the advance receipt, date of receipt of Approvals for the Drawing & other necessary design related documents from the buyer. All quoted shipping schedules are approximate and will depend upon prompt receipt of any drawings and other information from buyer, necessary for the design and manufacture of the equipment by Seller. Delay in advance payment, return of drawing approval will extend shipping date. Seller shall not be liable for any penalty or liquidated damages for failure to meet shipping schedules, except in those cases specifically approved in writing by an officer of Seller. During inspection, if customer suggests modification, in this case Seller shall not be liable for any penalty or liquidated damages for failure to meet shipping schedules.
- Seller shall not be liable for any damage or extra costs because of any delay due to a cause beyond Seller's control, including, without limitation, any Act of God, act of Buyer, embargo or other government act, regulation or request, fire, war, riot, flood, accident, strike, jurisdictional dispute, slow down, delay in transportation, and inability to obtain necessary labor, materials or manufacturing facilities. In the event of any such delay, the date of delivery shall be extended for a period equal to the time lost by reason of the delay.

2.INSTALLATION & START-UP

- The Buyers should inform us well in advance about the readiness of the site including the layout, utility etc.
- If the site is not ready within 3 months from the date dispatch, the buyer is liable to clear up all the balance payment, which is against this activity. However, we will carry on with the installation & start up later when the site is ready within a period of one year.

3.WARRANTY:

- Seller warrants the equipment manufactured by Seller and not by others, to be free from defects in workmanship and material under normal use and service for a period of 12 months from the date of commissioning and 18 months from the date supply whichever is earlier. Use or service with corrosive or abrasive chemicals or material is not deemed normal. Components manufactured by others, including expendable items, are warranted only in accordance with the warranty, if any, and issued by such other original manufacturers.
- All the bought-out components are fully guaranteed back-to-back as per the terms and conditions of the manufacturer.
- Components subjected to wear-and-tear like gaskets, glass, gauges, knobs, wires, and probes, mechanical seals are not covered under guarantee.
- The transportation and other expenses for the replacement of parts will be borne by the client.
- Warranty clause will not be applicable unless all the payment as per the agreed terms has been made by the client.

**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 70 OF 71

4. PAYMENT TERMS & CONDITIONS

- **PRICE:** The Prices for Site.
- **PACKING & FORWARDING:** NIL
- **TAXES & DUTIES:** Taxes as Applicable at the Time of Dispatch.
- **PAYMENT TERMS:**

SUPPLY-

- 30% - Advance along with purchase order.
- 10% - Against drawing and engineering document approval.
- 40%- Against Material receipt at Site on Pro Rata Basis.
- 10%- Against Erection at site or within 60 days of date of supply whichever is earlier.
- 10%- Against Commissioning & Handover or within 90 days of date of supply whichever is earlier.

➤ INSURANCE: NIL.

In the event of any loss or damage/complaint for the insurance consignment, buyer must inform the nearest office of the insurance company (with copy to their Bombay Office) as soon as client is aware of the loss or damage. Buyers will have to comply with all the certificates from the carriers when cases arrived are in damaged conditions showing the damage sustained. If buyer is arranging full insurance, please send two copies of open policy with name and address of insurance company incorporating seller's interest clause.

➤ **ANY OTHER LOCAL TAXES:** Any other taxes applicable to local government at site like work taxes, ESIC or any other such taxes if required to be paid by buyer. Interest in Overdue Payment: We will charge 3 % per month or part thereof for the delayed payment.

5. CANCELLATION:

In case of order cancellation, the buyer will make the following payments:

- Within 30 days – 33%
- Within 60 days – 66%
- Within 90 days – 100%

6. CHANGES:

Seller reserves the right to change the details of construction if such changes are in the best interest of both parties. In the event Buyer requires a change in specifications after engineering has started, after materials have been ordered, or after production has started, an order modification will be required. The modification should address statement of work, price, delivery schedule, and any other affected terms of the order. A modification by the Buyer will only be accepted by an authorized agent of the Buyer and must be documented in writing.



**TECHNO-COMMERCIAL
OFFER FOR TURNKEY
PLANT SUPPLY**

ISSUE:	VERSION: 1
DOCUMENT NO.	APSPL- 25-26-R0
DATE :	21-01-2026
PAGE NO.	PAGE 71 OF 71

7. JURISDICTION:

All disputes are subjected to Pune court's jurisdiction only.

8. VALIDITY:

This Offer validity is 15 days from the date of this offer.