



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-
COMMERCIAL OFFER
FOR
REACTORS WITH
AGITATOR

ISSUE:

Version : 1

DOCUMENT NO.

APSPL/EEPL/925/25-26/R3

DATE :

06-10-2025

PAGE NO.

Page 1 of 8

**CERTIFIED COMPANY BY THE AMERICAN SOCIETY
OF MECHANICAL ENGINEERS (ASME U STAMP)**



ISO 9001:2015 CERTIFIED COMPANY BY TUV NORD GERMANY



Plot No. E6, E-Block, Bhosari Industrial Area, Opposite NARI,
Bhosari, Pune – 411026, Maharashtra, INDIA.

**TECHNO-COMMERCIAL OFFER FOR
REACTOR WITH AGITATOR**

OFFER NO.	APSPL/EEPL/925/25-26/R3	OFFER DATE :	06-10-2025
PREPARED BY	MS. AABHA KULKARNI	CONTACT PERSON:	
CLIENT :			



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

**TECHNO-
COMMERCIAL OFFER
FOR
REACTORS WITH
AGITATOR**

ISSUE:	Version : 1
DOCUMENT NO.	APSPL/EEPL/925/25-26/R3
DATE :	06-10-2025
PAGE NO.	Page 2 of 8

SUBJECT: TECHNO COMMERCIAL OFFER FOR REACTOR WITH AGITATOR

Dear Sir,

We thank you for your enquiry for subject equipment. Based on the data provided by you, we are pleased to submit our Techno Commercial offer for the same as below –

1) 10 KL REACTOR (SS316)

Tag No : V-9301A & V-9301B

Process & Mechanical Details

Vessel

Process fluid	Client to confirm
Operating Temperature in °C	40
Design Temperature in °C	-30 to 180
Operating Pressure in kg/cm ² g	ATM/FV
Design Pressure kg/cm ² g	FV/3.5
Hydrotest Pressure kg/cm ² g	4.55
Corrosion Allowance in mm	1
MOC	SS316
Joint Efficiency (Shell/Dish) %	0.85/1
Radiography (Shell/Head)	SPOT only for shell + Dish 100% & all T joints
Density kg/m ³	1500
Viscosity cP	4000
Design Code	ASME SEC. VIII DIV. 1

Vessel Details :

Gross Capacity	12.96 KL
Working Capacity	10 KL
Tank Shape	Cylindrical
Tank Orientation	Vertical
Shell Inside Diameter	2200 mm
Shell Height (TL-TL)	2850 mm
Top/Bottom End Type	Tori spherical
Thickness (Shell/Top/Bottom)	10 mm / 10 mm / 12 mm

Material of Construction	Shell	SA240Gr316
	Top/Bottom Dish End	SA240Gr316
	Baffles	SA240Gr316
	Limpet Coil	NA
	Nozzle Neck	SA312TP316,SMLS
	Nozzle Flanges	SA182F316
	Nozzle dip pipe	SA 312 TP 316, SEAMLESS



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-COMMERCIAL OFFER FOR REACTORS WITH AGITATOR

ISSUE:	Version : 1
DOCUMENT NO.	APSPL/EEPL/925/25-26/R3
DATE :	06-10-2025
PAGE NO.	Page 3 of 8

	Nozzle Gaskets	PTFE
	Bolts Nuts (External)	SA 193 Gr.B8 & SA 194 Gr.8
	Bolts Nuts (External)	SA 193 Gr.B8M & SA 194 Gr.8M
	Body Flange	NA
	Manhole	SA 240 Gr.316
	Lug support	IS 2062 Gr B
	Wing Nuts & Bolts	SS304
	RF PAD	SA 240 Gr.316
	Internals	SS316
	Lifting Lug	SA 240 Gr.304
	Earthing Boss	SA 479 Gr.304
	Insulation cladding	NA
	Insulation	NA
	Foundation Bolt	Commercial CS Bolts
	Gasket	PTFE
Manhole	450 NB_SS316 with Flanges SORF+BLRF	
LG/SG	150 NB_SS316 + SS304 Cover	
Nozzle schedule	MDS	
Supports	4 Nos x Lug Support	
Surface Finish	SS- Internal/External- 240 Grit /Pickling MS- Sand Blasting & Painting	
AGITATOR DETAILS		
Agitator Model	AGIHM-15	
Motor Rating & make	15 KW/20HP/1460/IP55/IE3/FLP/415V/4P/50Hz/VFD Suit/TEFC/T4/Flange Mounted/CGL Make	
Gearbox Model & Make	AS 80F/Bonfiglioli make	
Reduction Ratio	15.65:1	
Safety Factor	2.1	
Impeller Type	3 Nos PBT 6 Bladed	
Impeller Diameter	3 Nos PBT Ø 800 mm	
RPM	~93	
Tip Speed (m/s)	3.89	
Shaft Diameter	~Ø 70 mm solid shaft in SS316 with steady bearing	
Shaft Length	~ 4250 mm	
Shaft Sealing/ Make	Single Mechanical Seal of Hi-fab Make with Karlrez ‘O’ ring	
Rigid Coupling (Internal)	SS316 - ACME make	
Flexible Coupling (External)	CS/CI, Lovejoy Make	
Bearing Housing	MS Housing + Back to Back Tapered Rolling Bearing of SKF make	



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-COMMERCIAL OFFER FOR REACTORS WITH AGITATOR

ISSUE:	Version : 1
DOCUMENT NO.	APSPL/EEPL/925/25-26/R3
DATE :	06-10-2025
PAGE NO.	Page 4 of 8

Lantern Stool	2 Nos. in MS
MOC	Wetted parts – SS316 Non- wetted Parts – MS
Quantity	1 Nos

2) 10 KL REACTOR (SS304)

Tag No : V-9301A & V-9301B

Process & Mechanical Details	Vessel
Process fluid	Client to confirm
Operating Temperature in °C	40
Design Temperature in °C	-30 to 180
Operating Pressure in kg/cm ² g	ATM/FV
Design Pressure kg/cm ² g	FV/3.5
Hydrotest Pressure kg/cm ² g	4.55
Corrosion Allowance in mm	1
MOC	SS316
Joint Efficiency (Shell/Dish) %	0.85/1
Radiography (Shell/Head)	SPOT only for shell + Dish 100% & all T joints
Density kg/m ³	1500
Viscosity cP	4000
Design Code	ASME SEC. VIII DIV. 1

Vessel Details :

Gross Capacity	12.96 KL	
Working Capacity	10 KL	
Tank Shape	Cylindrical	
Tank Orientation	Vertical	
Shell Inside Diameter	2200 mm	
Shell Height (TL-TL)	2850 mm	
Top/Bottom End Type	Tori spherical	
Thickness (Shell/Top/Bottom)	10 mm / 10 mm (Nom)/ 12 mm (Nom)	
Material of Construction	Shell	SA240Gr304
	Top/Bottom Dish End	SA240Gr304
	Baffles	SA240Gr304
	Limpet Coil	NA
	Nozzle Neck	SA312TP304,SMLS
	Nozzle Flanges	SA182F304



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-COMMERCIAL OFFER FOR REACTORS WITH AGITATOR

ISSUE:	Version : 1
DOCUMENT NO.	APSPL/EEPL/925/25-26/R3
DATE :	06-10-2025
PAGE NO.	Page 5 of 8

	Nozzle dip pipe	SA 312 TP 304, SEAMLESS
	Nozzle Gaskets	PTFE
	Bolts Nuts (External)	SA 193 Gr.B8 & SA 194 Gr.8
	Bolts Nuts (External)	SA 193 Gr.B8M & SA 194 Gr.8M
	Body Flange	NA
	Manhole	SA 240 Gr.304
	Lug support	IS 2062 Gr B
	Wing Nuts & Bolts	SS304
	RF PAD	SA 240 Gr.304
	Internals	SS304
	Lifting Lug	SA 240 Gr.304
	Earthing Boss	SA 479 Gr.304
	Insulation cladding	NA
	Insulation	NA
	Foundation Bolt	Commercial CS Bolts
	Gasket	PTFE
Manhole	450 NB_SS304 with Flanges SORF+BLRF	
LG/SG	150 NB_SS304 Cover	
Nozzle schedule	MDS	
Supports	4 Nos x Lug Support	
Surface Finish	SS- Internal/External- 240 Grit /Pickling MS- Sand Blasting & Painting	
AGITATOR DETAILS		
Agitator Model	AGIHM-15	
Motor Rating & make	15 KW/20HP/1460/IP55/IE3/FLP/415V/4P/50Hz/VFD Suit/TEFC/T4/Flange Mounted/CGL Make	
Gearbox Model & Make	AS 80F/Bonfiglioli make	
Reduction Ratio	15.65:1	
Safety Factor	2.1	
Impeller Type	3 Nos PBT 6 Bladed	
Impeller Diameter	3 Nos PBT Ø 800 mm	
RPM	~93	
Tip Speed (m/s)	3.89	
Shaft Diameter	~Ø 70 mm solid shaft in SS316 with steady bearing	
Shaft Length	~ 4250 mm	
Shaft Sealing/ Make	Single Mechanical Seal of Hi-fab Make with Karlrez ‘O’ ring	
Rigid Coupling (Internal)	SS304 - ACME make	
Flexible Coupling (External)	CS/CI, Lovejoy Make	

**ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)****TECHNO-
COMMERCIAL OFFER
FOR
REACTORS WITH
AGITATOR**

ISSUE:	Version : 1
DOCUMENT NO.	APSPL/EEPL/925/25-26/R3
DATE :	06-10-2025
PAGE NO.	Page 6 of 8

Bearing Housing	MS Housing + Back to Back Tapered Rolling Bearing of SKF make
Lantern Stool	2 Nos. in MS
MOC	Wetted parts – SS304
	Non- wetted Parts – MS
Quantity	2 Nos

Revision History

Revision	Comments / Changes	Commented By	Submission Date
R0	As per enquiry and MDS		29-08-2025
R1	SS304 Cost shared for comparison		05-09-2025
R2	No regret Price		01-10-2025
R3	Rock bottom Price		06-10-2025



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO- COMMERCIAL OFFER FOR REACTORS WITH AGITATOR

ISSUE:	Version : 1
DOCUMENT NO.	APSPL/EEPL/925/25-26/R3
DATE :	06-10-2025
PAGE NO.	Page 7 of 8

GENERAL NOTES

A) AGITATOR:

-) All Dimensions are in mm unless specified.
-) Agitators are designed considering Top Entry Center mounting in the tank.
-) Offered motors are of IP55/FLP/450V/3PH/IIA & IIB/VFD suitable of CGL make
-) The Gearbox shall be of Inline Helical type of Bonfiglioli make.
-) **The shaft sealing considered as per request by client shall be of single Mechanical Seal type of Hi-fab make. ACME will not responsible in case of any damages for seal.**
-) Supply, Installation and termination of field wiring shall be in client scope.
-) Electric control panel will be client's scope.
-) ID, Height, Imp. Ø, Shaft Length for agitator are in mm. speed is in RPM, viscosity in cP, Temp. Is in °C.
-) First fill of Gearbox oil shall be offered by ACME

B) VESSEL:

-) The vessel shall be provided with all the nozzles mentioned in the datasheet.
-) Internal/External Surface finish of the reactor shall be acid Pickling & passivation.
-) The nozzles size/projection should be confirmed by Client before the order finalization. The orientation shall be finalized during drawing approval stage.
-) Compatibility of the MOC with in-tank contents of the reactor shall be in Client's Scope.
-) Above offer is as per the shared datasheet details by client.
-) **Process design guarantee will be in Client scope. Mechanical design guarantee in client's scope**
- Mechanical guarantee in ACME's scope.**
-) **Insulation if any will be in client's scope**
-) **Limpet is not considered in above offer**
-) All material test certificates shall be provided. The material shall be of Non-Chinese origin.
-) **Installation and commissioning in client's scope.**
-) **Supervision is not considered in above scope. If required will be on additional chargeable basis of Rs 10,000/- per man day.**
-) **Electric control panel in client's scope**
-) Third party inspection shall be in Client's scope.
-) The Company guarantees that the goods manufactured by it and delivered hereunder will be free of defects in material and workmanship for a period of Eighteen (18) months from the date of shipment or Twelve (12) months from the date of installation, whichever is earlier.
-) Any post order requirement or change in the design other than stated in the offer may lead to price implication.



ACME PROCESS SYSTEMS PVT LTD, PUNE (INDIA)

TECHNO-
COMMERCIAL OFFER
FOR
REACTORS WITH
AGITATOR

ISSUE:	Version : 1
DOCUMENT NO.	APSPL/EEPL/925/25-26/R3
DATE :	06-10-2025
PAGE NO.	Page 8 of 8

PRICE SUMMARY

SR. NO	ITEMS	MOC	PRICE EACH	QTY	TOTAL PRICE
01	V-9301A & V-9301B	SS316	₹ 24,20,000/-	02	₹ 48,40,000/-
TOTAL (FOR)					₹ 48,40,000/-
IN WORDS: RUPEES FOURTY EIGHT LAKHS FOURTY THOUSAND ONLY					

Commercial Terms

Price basis	: FOR, Pithampur
Packing & Forwarding	: Inclusive
Insurance & Freight	: Inclusive
Taxes & Duties	: 18% GST Extra at actual.
Delivery Time	: 12~14 Weeks from the date of drawing approval.
Payment Terms	: 35% advance, 55% against PI after material readiness, 10% against PBG for 12 months
Validity	: 10 Days.

We trust this is in line with your requirements. Should you require any further information then please feel free to contact us.

Thanks & regards,

AABHA KULKARNI

SR. ENGINEER – Application & Sales

E- Mail: aabha.kulkarni@acmeprocess.net

M.no: +91 9545526693

ACME PROCESS SYSTEM PVT. LTD