Does an Explanation Stability Score Notice Data Drift?

A Reproduction and Stress Test on Three Tabular Datasets

Mithil Nagabathula
University of East London
mithilnishu2000@gmail.com

October 2026

Abstract

Explanation Stability Scores combine several checks on SHAP and LIME explanations into one number and gate what explanations a production system may show. We reproduce one such score from an MSc dissertation [11] (ESS $= 0.4G + 0.4L + 0.2F$: global rank stability, local perturbation stability and SHAP–LIME agreement, gated at 0.75) and stress-test it on a recruitment dataset, Adult income and German credit. The reproduction holds (ESS $= 0.881$ on the original data), but four findings qualify it. (1) As specified, G compares a batch's feature ranking with itself and is exactly 1 at baseline, so 40% of the score carries no information until a reference is fixed. (2) Across 225 drifted batches with graded covariate shift, missingness and prior shift, the 0.75 gate never fired, even when balanced accuracy fell by 0.33; the lowest ESS observed was 0.763. Its components moved in opposite directions: under covariate shift L rose as G fell. (3) ESS did fall when the *model* was made unreliable with label noise or overfitting (to 0.684 and 0.715 in the worst case on two datasets), which suggests it measures model and explanation quality rather than data drift. (4) A calibrated variant with a held-out reference and a bootstrap threshold detected 56–95% of harmful batches but had false alarms, and a simple population stability index rule detected 78–95%. We conclude that an explanation stability score is a useful check on a model, not a drift monitor, and should sit beside input drift statistics rather than replace them. Code and results are released.

1 Introduction

Regulation increasingly expects automated decisions to come with explanations [2]. Post-hoc explainers such as SHAP [8, 9] and LIME [16] are the usual tools, but their outputs can be unstable [1, 3, 20], manipulable [18] and mutually inconsistent [7]. A natural engineering response is to measure explanation stability continuously and withhold or caveat explanations when it drops. The MSc dissertation we study [11] does this inside an MLOps pipeline [6, 17]: an Explanation Stability Score (ESS) gates whether a recruitment model shows full explanations (≥ 0.75), limited explanations with a warning (≥ 0.60) or a disclaimer only.

A gate is only useful if it fires when it should. This paper asks whether ESS responds to the conditions that make explanations untrustworthy in production: shifts in the input distribution [14, 15], missing data, changes in class balance, and an unreliable model. The author of this paper also wrote the dissertation; the purpose here is to test that work critically and report what holds and what does not. Contributions:

- a faithful, open reimplementation of ESS and a reproduction of the original result;
- a dose-response study over three datasets, three drift types and five intensities, with five seeds each;
- a positive control showing what ESS *does* respond to;
- a calibrated variant and a comparison with the population stability index (PSI), the standard input-drift statistic.

2 The score

For a model f, a batch X of d features and SHAP values ϕ:

Global rank stability G. Rank features by mean $|\phi|$ over X. With $r_X(j)$ the rank of feature j and $r_{\text{ref}}(j)$ its rank in a reference, $G = 1 - \frac{1}{d}\sum_j |r_X(j) - r_{\text{ref}}(j)|/(d-1)$.

Local stability L. For sampled rows x, add Gaussian noise of 5% of each numeric feature's standard deviation to get x'; $L = \text{mean}\max\big(0, 1 - \|\phi(x) - \phi(x')\|_1 / \|\phi(x)\|_1\big)$.

Fidelity F. For sampled rows, the overlap of the top-5 features by $|\phi|$ and by LIME weight, divided by 5.

$\text{ESS} = 0.4G + 0.4L + 0.2F$. In the dissertation's implementation the reference for G is the batch itself, so $G = 1$ whenever the score is computed on a single batch. In our drift experiments the reference is the undrifted monitoring batch, which is how a deployed monitor would have to use it. SHAP values come from CatBoost's exact TreeSHAP [13].

3 Experimental setup

Data. *Recruitment*: 8,995 candidate offers, 14 features, 81% joined [12]; gender is excluded from the features as in the dissertation. *Adult*: a 20,000-row sample of the census income data [5], 11 features, race and sex excluded. *German credit*: 1,000 applicants, 19 features, the combined sex/marital-status field excluded [4].

Model. CatBoost with class weighting, 500 iterations, depth 6, $\ell_2 = 3$, learning rate 0.05, as in the dissertation.

Protocol. For each dataset and seed (5 seeds), we split 70/30, train on the 70%, and split the 30% into a reference window and a monitoring window of up to 500 rows each. ESS uses 80 rows for L and 40 for F (LIME with 2,000 samples).

Drift. On the monitoring window we apply: *covariate shift* of the five most important numeric features by $\{0.25, 0.5, 1, 1.5, 2\}$ standard deviations (with 30% jitter); *missingness* at rates $\{0.1, \ldots, 0.8\}$ on the five most important features (imputed as in training); and *prior shift*, resampling to a positive-class share of $\{0.1, 0.3, 0.5, 0.9, 0.97\}$. This gives 15 drifted batches and one clean batch per seed, 240 batches in total. For each we record ESS and its parts, mean PSI across features, and the change in balanced accuracy and AUC.

4 Results

4.1 Reproduction

On the original recruitment split, ESS was 0.881 ($G = 1$, $L = 0.883$, $F = 0.636$), passing the full-explanation gate as reported. Table 1 gives cross-validated performance. CatBoost had lower accuracy than a random forest but higher balanced accuracy, the metric that matters with an 81/19 class split.

G is constant at baseline. Because the reference is the batch itself, $G = 1$ contributes a fixed 0.4 to every single-batch score. The informative range of ESS is therefore $[0.4, 1]$, and the 0.75 gate requires only $0.4L + 0.2F \geq 0.35$, which holds for any model whose local stability exceeds 0.875 regardless of fidelity.

Table 1: Predictive performance on the recruitment data, 25 runs (5 seeds × 5 folds), mean ± 95% CI. Both models use class weighting.

Model	Accuracy	Balanced acc.	Macro F1	Not-joined F1
CatBoost	0.723 ± 0.004	0.688 ± 0.005	0.637 ± 0.004	0.460 ± 0.006
Random Forest	0.793 ± 0.003	0.640 ± 0.004	0.646 ± 0.004	0.417 ± 0.007

Table 2: Sampling variability of ESS on an unchanged batch: 10 repetitions with different sampling seeds for each local (n_L) and LIME (n_F) sample size.

Dataset	n_L / n_F	ESS mean	ESS SD	L SD	F SD	Range
Recruitment	20 / 20	0.873	0.0200	0.0266	0.0544	0.058
Recruitment	80 / 40	0.874	0.0075	0.0126	0.0271	0.028
Recruitment	200 / 100	0.870	0.0054	0.0111	0.0159	0.017
Adult	20 / 20	0.913	0.0089	0.0132	0.0309	0.031
Adult	80 / 40	0.918	0.0037	0.0085	0.0169	0.011
Adult	200 / 100	0.917	0.0033	0.0063	0.0112	0.010
German credit	20 / 20	0.907	0.0119	0.0136	0.0387	0.039
German credit	80 / 40	0.907	0.0055	0.0082	0.0268	0.017
German credit	200 / 100	0.906	0.0024	0.0044	0.0112	0.008

4.2 Estimator variance

With the dissertation's sample sizes, ESS on an unchanged batch varied with the sampling seed by a standard deviation of 0.004–0.008 (Table 2), dominated by the LIME-based F. With 20 rows for each component the standard deviation rose to 0.009–0.020 and the range of ten repetitions reached 0.058 on the recruitment data, comparable to the effect of moderate drift below.

4.3 Dose-response under drift

Figure 1 shows ESS, its components and the change in balanced accuracy under each drift type. Table 3 gives the strongest level of each.

The gate never fired. Across all 225 drifted batches, no ESS fell below 0.75 (Table 4). The lowest values were 0.763 (recruitment, 80% missing), 0.818 (German credit) and 0.825 (Adult). The largest accuracy loss, a 0.33 drop in balanced accuracy on Adult under a 2 SD covariate shift, left ESS at 0.863.

Components cancel. Under covariate shift, G fell as expected, but L *rose*: on Adult from 0.945 to 0.978. Shifting features pushes rows into flat regions of the tree ensemble, where small perturbations change SHAP values less. The weighted sum hides the movement of G. Under missingness on the recruitment and German credit data, F fell most (from 0.63 to 0.42 and from 0.64 to 0.39), probably because SHAP attributes importance to imputed values that LIME's perturbations do not reproduce. Prior shift changed ESS by at most 0.06, and on the recruitment data by less than its own sampling noise.

Correlation with harm. ESS was positively correlated with the change in balanced accuracy (Spearman ρ 0.41–0.64), so it moves in the right direction, but too little to cross a fixed threshold. PSI correlated more strongly with harm on two of three datasets (0.87 and 0.57) and weakly on German credit (0.15), where shifting integer-coded features produces large PSI even when accuracy barely changes.




Figure 1: ESS (thick), G, L, F (mean ± SD over 5 seeds, left axis) and change in balanced accuracy (dashed, right axis) as drift intensity increases. The dotted line is the 0.75 gate.

4.4 Positive control

If ESS is insensitive to drift, does it respond to anything? Table 5 trains deliberately worse models: with 20% or 40% of training labels flipped, and with an overfit configuration (depth 10, almost no regularisation, 1,500 iterations), evaluated on the same clean audit batch. ESS fell as the model degraded in 11 of 12 degraded configurations, driven by both L and F. The combination of overfitting and 40% label noise took it to 0.684 on recruitment and 0.715 on Adult, the only conditions in this study that crossed the 0.75 gate; on German credit it reached 0.852, and overfitting alone left ESS unchanged (0.909 against 0.910). G between two training runs stayed between 0.90 and 0.96 throughout and did not separate good models from bad ones. ESS is therefore a signal about the *model*: whether its attributions are smooth and whether two explainers agree about it.

4.5 A calibrated variant

Two changes address the problems above: measure G against a held-out reference window rather than the batch itself, and set the threshold from a bootstrap null distribution of no-drift batches rather than at a fixed 0.75. We call this ESS* and alarm when it falls below the 5th percentile of 30 bootstrap batches. Under the null, G averaged 0.976–0.991, and the 5th-percentile thresholds

Table 3: ESS and its components at baseline and at the strongest level of each drift type (mean of 5 seeds). PSI is the mean population stability index across features.

Dataset	Condition	ESS	G	L	F	PSI	Δbal.acc.
Recruitment	No drift	0.880	1.000	0.886	0.629	0.00	–
	Covariate +2 SD	0.845	0.868	0.920	0.649	3.15	-0.103
	80% missing	0.795	0.864	0.914	0.421	5.33	-0.144
	Prior 97% positive	0.874	0.985	0.886	0.629	0.02	+0.009
Adult	No drift	0.911	1.000	0.945	0.666	0.00	–
	Covariate +2 SD	0.863	0.815	0.978	0.730	1.25	-0.330
	80% missing	0.846	0.833	0.964	0.638	4.80	-0.146
	Prior 97% positive	0.855	0.887	0.923	0.657	0.51	+0.002
German credit	No drift	0.908	1.000	0.949	0.640	0.00	–
	Covariate +2 SD	0.904	0.942	0.976	0.684	3.45	+0.007
	80% missing	0.824	0.898	0.968	0.386	3.55	-0.127
	Prior 97% positive	0.891	0.963	0.955	0.618	0.04	+0.055

Table 4: Does ESS track harm? Spearman correlation between each signal and the change in balanced accuracy over all drifted batches (75 per dataset), the share of drifted batches the dissertation's 0.75 gate would have restricted, and the lowest ESS observed.

Dataset	ρ(ESS, Δbal.acc.)	ρ(PSI, −Δbal.acc.)	Batches gated below 0.75	Min. ESS
Recruitment	0.64	0.87	0%	0.763
Adult	0.41	0.57	0%	0.825
German credit	0.44	0.15	0%	0.818

were 0.856 (recruitment), 0.906 (Adult) and 0.889 (German credit), all far above 0.75.

Table 6 compares detection of *harmful* drift, defined as a fall of at least two points in balanced accuracy. ESS* detected 65%, 95% and 56% of harmful batches where the original gate detected none. However, it raised alarms on 40% and 20% of clean batches on Adult and German credit, because the null was built from one seed's model and applied to models from other seeds. A PSI rule of thumb (mean PSI > 0.1) detected 78–95% of harmful batches.

5 Discussion

What ESS is good for. The positive control suggests a clear role: as a pre-deployment and retraining check that a model's explanations are smooth and corroborated. A model trained on noisy labels or overfit produced noticeably lower ESS on clean data.

What it is not good for. As a production drift gate, ESS with a fixed threshold did not fire under any drift we applied, including drift that cut balanced accuracy by a third. Explanation shift can be a sensitive drift signal [10], but a weighted sum of stability components dilutes it: a self-referenced G is constant, L can rise under shift, and the 0.75 threshold sits far below the null distribution.

Recommendations. (1) Compute G against a fixed reference window, or use a rank-similarity measure such as rank-biased overlap [19]. (2) Calibrate thresholds per model from a bootstrap null and report the false-alarm rate. (3) Monitor the components separately, since their movements cancel. (4) Pair any explanation score with input drift statistics such as PSI.

Limitations. Drift was synthetic and applied to the most important features, which is a favourable case for detection. Three tabular datasets and one model family were studied. The

Table 5: Positive control: models made less reliable by label noise or overfitting, evaluated on the same clean audit batch (mean of 3 seeds). G (retrain) compares global rankings between two training runs of the same configuration.

Dataset	Model	ESS	L	F	G (retrain)	Bal. acc.
Recruitment	regularised (default)	0.879	0.875	0.645	0.949	0.693
	label noise 20%	0.834	0.809	0.552	0.952	0.670
	label noise 40%	0.819	0.819	0.457	0.916	0.598
	overfit (depth 10, l2 0.01, 1500 it)	0.825	0.774	0.580	0.927	0.573
	overfit + label noise 40%	0.684	0.510	0.398	0.956	0.555
Adult	regularised (default)	0.919	0.955	0.685	0.921	0.835
	label noise 20%	0.901	0.927	0.650	0.927	0.818
	label noise 40%	0.874	0.911	0.550	0.927	0.779
	overfit (depth 10, l2 0.01, 1500 it)	0.870	0.882	0.585	0.939	0.777
	overfit + label noise 40%	0.715	0.554	0.467	0.958	0.608
German credit	regularised (default)	0.910	0.952	0.647	0.949	0.692
	label noise 20%	0.894	0.928	0.615	0.928	0.658
	label noise 40%	0.861	0.919	0.467	0.897	0.556
	overfit (depth 10, l2 0.01, 1500 it)	0.909	0.952	0.640	0.920	0.649
	overfit + label noise 40%	0.852	0.901	0.458	0.904	0.553

Table 6: Detection of harmful drift (balanced accuracy down by at least 2 points) by the original fixed gate, the calibrated ESS* (held-out reference, bootstrap 5th-percentile threshold) and a PSI rule of thumb. False alarms: share of clean batches flagged by ESS*. Harmful: number of harmful batches.

Dataset	Threshold	False alarms	ESS*	Gate 0.75	PSI>0.1	Harmful
Recruitment	0.856	0%	65%	0%	92%	48
Adult	0.906	40%	95%	0%	95%	44
German credit	0.889	20%	56%	0%	78%	36

bootstrap null used a single seed's model, which inflated false alarms. The recruitment data is a public dataset of uncertain provenance. Finally, the dissertation and this paper share an author; the code is released so that others can check both.

6 Conclusion

The Explanation Stability Score reproduced as reported and responded to unreliable models, but it did not notice data drift that substantially harmed accuracy. Explanation scores should be used to vet models, calibrated against a held-out reference if used for monitoring, and paired with conventional drift statistics.

Reproducibility. Code and result files will be released at
https://github.com/mithil2k2000-tech/ess-drift-study.

Use of AI tools. An AI assistant (Claude, Anthropic) helped write experiment code and draft text. The author designed the study questions, reviewed the code and results, and takes responsibility for the content.

References

[1] David Alvarez-Melis and Tommi S. Jaakkola. On the robustness of interpretability methods. *arXiv preprint arXiv:1806.08049*, 2018.

[2] European Parliament and Council of the European Union. Regulation (EU) 2024/1689 of the European Parliament and of the Council laying down harmonised rules on artificial intelligence (Artificial Intelligence Act). Official Journal of the European Union, L series, 2024.

[3] Amirata Ghorbani, Abubakar Abid, and James Zou. Interpretation of neural networks is fragile. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 3681–3688, 2019.

[4] Hans Hofmann. Statlog (German credit data). UCI Machine Learning Repository, 1994.

[5] Ron Kohavi. Scaling up the accuracy of naive-Bayes classifiers: A decision-tree hybrid. In *Proceedings of the Second International Conference on Knowledge Discovery and Data Mining*, pages 202–207, 1996.

[6] Dominik Kreuzberger, Niklas Kühl, and Sebastian Hirschl. Machine learning operations (MLOps): Overview, definition, and architecture. *IEEE Access*, 11:31866–31879, 2023.

[7] Satyapriya Krishna, Tessa Han, Alex Gu, Steven Wu, Shahin Jabbari, and Himabindu Lakkaraju. The disagreement problem in explainable machine learning: A practitioner's perspective. *arXiv preprint arXiv:2202.01602*, 2022.

[8] Scott M. Lundberg and Su-In Lee. A unified approach to interpreting model predictions. In *Advances in Neural Information Processing Systems*, volume 30, 2017.

[9] Scott M. Lundberg, Gabriel Erion, Hugh Chen, Alex DeGrave, Jordan M. Prutkin, Bala Nair, Ronit Katz, Jonathan Himmelfarb, Nisha Bansal, and Su-In Lee. From local explanations to global understanding with explainable AI for trees. *Nature Machine Intelligence*, 2(1): 56–67, 2020.

[10] Carlos Mougan, Klaus Broelemann, Gjergji Kasneci, Thanassis Tiropanis, and Steffen Staab. Explanation shift: Detecting distribution shifts on tabular data via the explanation space. *arXiv preprint arXiv:2210.12369*, 2022.

[11] Mithil Nagabathula. Operationalising explainable AI reliability in a cloud-native MLOps framework using an explanation stability score: A recruitment case study. MSc dissertation, University of East London, 2026.

[12] Devashish Patel. HR analytics: Candidate offer acceptance data. https://github.com/devashishpatel/HR-Analytics. Accessed October 2026.

[13] Liudmila Prokhorenkova, Gleb Gusev, Aleksandr Vorobev, Anna Veronika Dorogush, and Andrey Gulin. CatBoost: Unbiased boosting with categorical features. In *Advances in Neural Information Processing Systems*, volume 31, 2018.

[14] Joaquin Quiñonero-Candela, Masashi Sugiyama, Anton Schwaighofer, and Neil D. Lawrence, editors. *Dataset Shift in Machine Learning*. MIT Press, 2009.

[15] Stephan Rabanser, Stephan Günnemann, and Zachary C. Lipton. Failing loudly: An empirical study of methods for detecting dataset shift. In *Advances in Neural Information Processing Systems*, volume 32, 2019.

[16] Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. "why should I trust you?": Explaining the predictions of any classifier. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 1135–1144, 2016.

[17] D. Sculley, Gary Holt, Daniel Golovin, Eugene Davydov, Todd Phillips, Dietmar Ebner, Vinay Chaudhary, Michael Young, Jean-François Crespo, and Dan Dennison. Hidden technical debt in machine learning systems. In *Advances in Neural Information Processing Systems*, volume 28, 2015.

[18] Dylan Slack, Sophie Hilgard, Emily Jia, Sameer Singh, and Himabindu Lakkaraju. Fooling LIME and SHAP: Adversarial attacks on post hoc explanation methods. In *Proceedings of the AAAI/ACM Conference on AI, Ethics, and Society*, pages 180–186, 2020.

[19] William Webber, Alistair Moffat, and Justin Zobel. A similarity measure for indefinite rankings. *ACM Transactions on Information Systems*, 28(4):1–38, 2010.

[20] Chih-Kuan Yeh, Cheng-Yu Hsieh, Arun Sai Suggala, David I. Inouye, and Pradeep Ravikumar. On the (in)fidelity and sensitivity of explanations. In *Advances in Neural Information Processing Systems*, volume 32, 2019.