

WEEK 4 ASSIGNMENT

1. Which of the following best describes 'speedup' in parallel computing.

- A. The ratio of sequential execution time to parallel execution time
- B. The increase in power consumption
- C. The total number of processors used
- D. The reduction in clock speed

Answer: The ratio of sequential execution time to parallel execution time

2. What is 'Amdahl's Law'.

- A. A principle for optimizing cache usage
- B. A formula to predict the theoretical maximum speedup in parallel computing
- C. A method to increase memory bandwidth
- D. A technique for improving input/output operations

Answer: A formula to predict the theoretical maximum speedup in parallel computing

3. Which of the following is an example of embarrassingly parallel tasks.

- A. Tasks that require frequent synchronization
- B. Tasks that can be easily separated into independent parts
- C. Tasks that depend on the results of other tasks
- D. Tasks that involve continuous communication

Answer: Tasks that can be easily separated into independent parts

4. Which of the following is a challenge in parallel computing.

- A. Clock speed management
- B. Heat dissipation
- C. Load balancing
- D. Static memory allocation

Answer: Load balancing

5. What is a 'race condition' in the context of parallel computing.

- A. A situation where two or more processes compete for CPU time
- B. A condition where the behavior of a system depends on the timing of events
- C. A method for optimizing memory usage
- D. A technique for increasing processing speed

Answer: A condition where the behavior of a system depends on the timing of events

6. OpenMP is used for.

- A. Shared Memory Programming
- B. Distributed Memory Programming
- C. Both Distributed and Shared Memory Programming
- D. None of these

Answer: Shared Memory Programming

7. Which directive is used to parallelize a loop in OpenMP.

- A. `#pragma omp parallel`
- B. `#pragma omp loop`
- C. `#pragma omp parallel loop`
- D. `#pragma omp parallel for`

Answer: `#pragma omp parallel for`

8. In the OpenMP execution model, what does the term "fork" refer to.

- A. The point where the program starts
- B. The creation of a single thread
- C. The destruction of a team of threads
- D. The creation of multiple threads by a single thread

Answer: The creation of multiple threads by a single thread

9. Which of the following best describes the "join" phase in the OpenMP execution model.

- A. Threads are created and start executing
- B. Threads finish their execution and rejoin the master thread
- C. Threads are paused and waiting for synchronization
- D. Threads communicate with each other

Answer: Threads finish their execution and rejoin the master thread

10. Which function in OpenMP is used to get the unique ID of a thread.

- A. `omp_get_num_threads()`
- B. `omp_get_thread_num()`
- C. `omp_num_threads()`
- D. `omp_thread_num()`

Answer: `omp_get_thread_num()`

11. Which function is used to set the number of threads in OpenMP.

- A. `omp_get_num_threads()`
- B. `omp_get_thread_num()`
- C. `omp_num_threads()`
- D. `omp_set_num_threads()`

Answer: `omp_set_num_threads()`

12. Which function is used to get the total number of threads in OpenMP.

- A. `omp_get_num_threads()`
- B. `omp_get_thread_num()`
- C. `omp_num_threads()`
- D. `omp_set_num_threads()`

Answer: `omp_get_num_threads()`

13. What is the role of #pragma omp parallel sections in OpenMP.

- A. To create a critical section
- B. To parallelize individual sections of code
- C. To terminate a parallel region
- D. To synchronize all threads

Answer: To parallelize individual sections of code

14. Which environment variable is used to set the number of threads in an OpenMP program.

- A. OMP_NUM_THREADS
- B. OMP_SET_THREADS
- C. OMP_THREAD_COUNT
- D. OMP_THREADS

Answer: OMP_NUM_THREADS

15. How does OpenMP handle parallel regions in its execution model.

- A. By creating multiple parallel regions simultaneously
- B. By creating a single parallel region and executing it repeatedly
- C. By creating parallel regions dynamically as needed
- D. By creating parallel regions only at the beginning of the program

Answer: By creating parallel regions dynamically as needed