

Household LPG Cylinder Safety, Regulator & Leakage Guide

BANGLADESH LPG SAFETY & REGULATORY COMPLIANCE PLATFORM

CODE: AEL-SOP-CST-2024 | CATEGORY: CUSTOMER | ISSUED: May 2024

Kitchen Safety, Safe Regulator Connection, Leak Detection & Life-Saving Protocols

Statutory Reference: Department of Explosives (DoE) & Bangladesh Energy Regulatory Commission (BERC)

1. SAFE INSTALLATION & STORAGE IN HOUSEHOLD KITCHENS

- [*] Always keep LPG cylinders strictly upright on a firm, level floor in a ventilated area.
- [*] Never place cylinders inside enclosed, unventilated cabinets or below ground level.
- [*] Maintain at least 1 meter distance between the cylinder and your gas stove or electrical switches.
- [*] Use only certified low-pressure click-on regulators with undamaged O-ring rubber seals.

2. HOSE INSPECTION, REPLACEMENT & LEAK DETECTION

- [*] Use only certified reinforced rubber hoses (BDS 1499 standard); replace every 2 years.
- [*] Test connections regularly using soapy water sponge. NEVER use matchsticks or candles!
- [*] Look for bubbles on regulator neck or hose joints. If bubbles appear, turn off regulator.
- [*] Always turn off cylinder regulator knob at night or when leaving the house unattended.

3. CRITICAL EMERGENCY PROTOCOL IF YOU SMELL GAS

- [*] DO NOT touch any electric switch, refrigerator door, or mobile phone in the kitchen.
- [*] Immediately turn the cylinder regulator switch to OFF position.
- [*] Open all kitchen windows and doors wide to allow gas vapor to disperse naturally.
- [*] Evacuate family members calmly outside into fresh air and call Fire Service at 16137.

24/7 LPG EMERGENCY HOTLINES: Fire Service: 16137 | National Emergency: 999 | DoE Central: +880 2-9335445

This is an official technical compliance document published by AEL SafeLPG Bangladesh. Authorized users can verify this document online at lpgsafety.org.bd