

LPG Retail Dealer Storage & Cylinder Handling SOP

BANGLADESH LPG SAFETY & REGULATORY COMPLIANCE PLATFORM

CODE: AEL-SOP-DLR-2024 | CATEGORY: DEALER | ISSUED: May 2024

Warehouse Storage, Safe Stacking, Ventilation & Commercial Compliance Standards

Statutory Reference: Department of Explosives (DoE) & Bangladesh Energy Regulatory Commission (BERC)

1. RETAIL WAREHOUSE VENTILATION & STORAGE SPECIFICATIONS

- [*] Store cylinders strictly in well-ventilated, ground-floor non-combustible sheds.
- [*] Ensure natural cross-ventilation with louvered floor-level vents (LPG is heavier than air).
- [*] Stack empty or full cylinders strictly upright; maximum allowed stacking is 2 tiers.
- [*] Keep storage area strictly clear of flammable chemicals, stoves, or open flames.

2. RECEIVING, INSPECTION & HANDLING PROCEDURES

- [*] Inspect every inbound cylinder for intact seal, tare weight, and valve neck integrity.
- [*] Never drop, roll horizontally, or drag cylinders during loading or unloading.
- [*] Conduct mandatory soap-water leak testing on suspected valves before customer handover.
- [*] Quarantine and report damaged, dented, or overdue hydro-test cylinders immediately.

3. FIRE SAFETY GEAR & CONSUMER ADVISORY DUTIES

- [*] Deploy minimum two 9kg Dry Chemical Powder (DCP) extinguishers at warehouse entry.
- [*] Display emergency telephone numbers (Fire Service 16137) prominently on the wall.
- [*] Educate every purchaser on safe vertical cylinder transport and regulator snap-lock.

24/7 LPG EMERGENCY HOTLINES: Fire Service: 16137 | National Emergency: 999 | DoE Central: +880 2-9335445

This is an official technical compliance document published by AEL SafeLPG Bangladesh. Authorized users can verify the document's authenticity at [lpgsafety.org.bd](https://www.lpgsafety.org.bd).