

Bulk Road Tanker & Cylinder Transit Safety Code

BANGLADESH LPG SAFETY & REGULATORY COMPLIANCE PLATFORM

CODE: AEL-SOP-DST-2024 | CATEGORY: DISTRIBUTOR | ISSUED: May 2024

HAZMAT Transport Standards, Static Bonding, Speed Limits & Route Safety

Statutory Reference: Department of Explosives (DoE) & Bangladesh Energy Regulatory Commission (BERC)

1. ROAD TANKER SPECIFICATIONS & RIGID MECHANICAL FITNESS

- [*] Install certified spark arrestors on vehicle exhaust systems at all times.
- [*] Ensure static grounding bonding reel is firmly attached before hose connection.
- [*] Equip all tankers with rear-end crash bumper guards extending 150mm beyond tank rear.
- [*] Maintain digital GPS telemetry logging vehicle speed, route deviation, and braking.

2. CYLINDER CARRIER TRUCK SAFETY GUIDELINES

- [*] Transport cylinders exclusively in upright positions secured with heavy-duty lashings.
- [*] Ensure truck cargo floor is non-sparking (timber lined or rubber bonded).
- [*] Never transport passengers, matches, lighters, or loose steel tools in the cargo bed.
- [*] Strictly observe urban transit windows and avoid congested residential roads during rush hours.

3. ON-ROAD EMERGENCY INCIDENT RESPONSE PROTOCOLS

- [*] In case of breakdown or leak, immediately park in open area and place caution reflectors at 50m.
- [*] Stop engine immediately, disconnect battery master switch, and notify emergency hotline 16137.
- [*] Keep bystanders at minimum 100m upwind; never allow smoking or vehicle ignition nearby.

24/7 LPG EMERGENCY HOTLINES: Fire Service: 16137 | National Emergency: 999 | DoE Central: +880 2-9335445

This is an official technical compliance document published by AEL SafeLPG Bangladesh. Authorized users only. [Verify Online](#) | lpgsafety.org.bd