
CS5787: Exercises 1

FULL_CODE_FOLDER_URL

Mitchell Krieger
mak483

Meitong (Estelle) He
mh2585

1 Theory: Question 1 [12.5 pts]

- a) What is the input X ?
There are m samples in the batch with 10 features each so the input shape is $(m, 10)$
- b) What is the shape of the hidden layer's weight vector W_h , and the shape of its bias vector b_h ?
To transform an $(m, 10)$ input into a hidden layer of 50 neurons we need a shape W_h to have a shape of $(10, 50)$ so that we get a $(m, 50)$ result. After the weight matrix is applied, we then add the bias b_h to each row of W_h , which means that the result needs to be $(1, 50)$
- c) What is the shape of the output layer's weight vector W_o , and its bias vector b_o ?
 $W_h : (50, 3), b_h : (1, 3)$
- d) What is the shape of the network's output matrix Y ? $(m, 3)$
- e) Write an equation that computes the network's output matrix Y as a function of X , W_h , b_h , W_o , and b_o ?
$$Y = W_o a(W_h X + b_h) + b_o$$

Where a is the ReLU activation function, $a(x) = \max(0, x)$.

2 Theory: Question 2 [12.5 pts]

For the first layer there are $3 \times 3 \times 3$ parameters in each of the 100 kernels, and then we need bias parameters for each kernel as well. This totals $3 \times 3 \times 3 \times 100 + 100 = 2800$ parameters. In the second layer there are $3 \times 3 \times 100$ parameters in each of the 200 kernels, and then we need bias parameters for each kernel as well. This totals $3 \times 3 \times 100 \times 200 + 200 = 180200$. In the final layer there are $3 \times 3 \times 200$ parameters in each of the 200 kernels, and then we need bias parameters for each kernel as well. This totals $3 \times 3 \times 200 \times 400 + 400 = 720400$. Adding all the layers together we get $2800 + 180200 + 720400 = 903400$ total parameters.

3 Theory: Question 3 [25 pts]

TODO: Provide your answers to Question 3 here.

4 Practical [50 pts]

TODO: Provide a report detailing your experiments, results and discussion in this section.