MAS.S60

AI Agents for Cognitive Augmentation

Computer-Use Agents & Beyond

Yasith Samaradivakara
Graduate Student
Fluid Interfaces Group
MIT Media Lab

Week 4



Moral Agents (Brooke)



Ideation Map (David)

Spiralverse (Egemen)



Working Memory Environment (Hyung)



Lang Table (Jad)



10 BIT (Juan-Ruben)

Week 4



Work Attention (Leticia)



Computer Abuse (Lilith)



CLARA (Manasi)



Ludwig (Mateo)



Env for Explanations (Matti)

Our Cognitive Gardens (Raine)

Week 4



Paprika (Ray)

Liminal (Roma)



FireBench (Yanning)



Market Sims (Stacey)



OpenSim (Yue)

Robotic Memory (Yuxiang)

Course logistics

1. **Reflections on environments**
2. **Class survey and final project teams**
3. **Mid-semester project proposals (11/3)**





Show and tell



Show and tell

Zoom Meeting ID: 923 8867 7954

1. **The problem**
   What objectives is the environment trying to enable agents to complete?

2. **The environment**
   What are (S), (O), (A), the transition dynamics and task distribution?

3. **Live demo**

4. **What you learned**
   One interesting failure, limitation, or result from your environment build and testing.



MAS.S60

AI Agents for Cognitive Augmentation

Computer-Use Agents & Beyond

Yasith Samaradivakara
Graduate Student
Fluid Interfaces Group
MIT Media Lab

Device-Use Agents

What is a Device-Use Agent?


Observation
Snapshot from the environment
Screenshot
(visual state)
UI tree
(accessibility)
File system
(files, folders)
Device state
(orientation, sensors, status, etc.)
Environment
Computer, apps, websites, devices, physical world, etc.
Computer / Desktop
apps, websites, operating system
Mobile device
apps, settings, sensors
Human
Goal / Instruction
Natural language
AI Agent
Reason / Plan / Decide
Wearables
smartglasses, watches, rings, etc.
Physical devices
robots, lights, cameras, printers, IoT, etc.
Action
Change the environment
Click
(mouse)
Type
(keyboard)
Scroll
(navigation)
Run command
(apps, files, APIs)

Perception-Action for Browser



Human User vs Computer Software?

DOM vs Screenshots



DOM-based	Screenshot-based
Structured elements	Pixels and visual layout
Precise element targeting	Coordinate-based targeting
Best for standard HTML interfaces	Best for visual or canvas-heavy interfaces
Can miss visual details	Sensitive to layout changes

Find the mug with the blue floral pattern

Product A: White mug

Product B: Floral mug

Browser-Use



AI-native browser agent

https://github.com/browser-use/browser-use

Playwright

```python
from playwright.async_api import async_playwright

async def book_flight():
    async with async_playwright() as p:
        browser = await p.chromium.launch(headless=False)
        page = await browser.new_page()

        await page.goto("https://www.example-airline.com")
        await page.get_by_label("From").fill("New York (NYC)")
        await page.get_by_label("To").fill("Boston (BOS)")
        await page.get_by_label("Depart").fill("Oct 25, 2026")
        await page.get_by_role("button", name="Search Flights").click()

        await page.get_by_text("$129").click()
        await page.get_by_role("button", name="Continue to Checkout").click()
        await browser.close()
```

Automation API

- Faster, Lower-Cost
- When steps are clear and simple
- Ideal for testing
- Full control



MCP (Accessibility Snapshots)

Chrome DevTools Protocol (CDP)



https://chromedevtools.github.io/devtools-protocol/

Perception-Action for Desktop



Shell Commands vs Screenshots



Shell-based	Screenshot-based
Commands and structured output	Pixels, mouse, and keyboard
Fast for files, scripts, and processes	Useful for graphical applications
Precise and easy to automate	Works when no command interface exists
Requires command access	Requires GUI access

Agent S (S1, S2, S3)

Scaling Agents for Computer Use

Gonzalo Gonzalez-Pumariega * **Vincent Tu** * **Chih-Lun Lee** **Jiachen Yang** **Ang Li** **Xin Eric Wang**

Simular Research

Abstract

Computer-use agents (CUAs) hold promise for automating everyday digital tasks, but their performance on long-horizon, complex problems remains unreliable. Single-rollout execution is brittle, with small errors compounding over time and leading to high variance in outcomes. While prior work has attempted to scale within a single rollout, such approaches have yielded limited gains. Scaling over multiple rollouts offers a more promising alternative but doing so effectively is challenging due to the difficulty of evaluating and selecting among long-horizon agent behaviors.



Figure 1. Performance on OSWorld at 100 steps. Our method beats the previous SoTA by 9.2% absolute improvement and surpasses human level performance on OSWorld.

AI-native computer use agent

https://github.com/simular-ai/Agent-S

UI-Tars Desktop



https://github.com/bytedance/UI-TARS-desktop

Claude Computer Use

```python
import anthropic

client = anthropic.Anthropic()

response = client.messages.create(
    model="claude-opus-5-5",
    max_tokens=1024,
    tools=[
        {"type": "computer_toolset_20260801"}
    ],
    messages=[
        {
            "role": "user",
            "content": "Open the browser and search for MIT Media Lab."
        }
    ],
)

print(response)
```

pip install anthropic

PyAutoGUI

```
>>> import pyautogui

>>> screenWidth, screenHeight = pyautogui.size() # Get the size of the primary monitor.
>>> screenWidth, screenHeight
(2560, 1440)

>>> currentMouseX, currentMouseY = pyautogui.position() # Get the XY position of the mouse.
>>> currentMouseX, currentMouseY
(1314, 345)

>>> pyautogui.moveTo(100, 150) # Move the mouse to XY coordinates.

>>> pyautogui.click()          # Click the mouse.
>>> pyautogui.click(100, 200)  # Move the mouse to XY coordinates and click it.
>>> pyautogui.click('button.png') # Find where button.png appears on the screen and click it.

>>> pyautogui.move(400, 0)      # Move the mouse 400 pixels to the right of its current positio
>>> pyautogui.doubleClick()     # Double click the mouse.
>>> pyautogui.moveTo(500, 500, duration=2, tween=pyautogui.easeInOutQuad)  # Use tweening/easi

>>> pyautogui.write('Hello world!', interval=0.25)  # type with quarter-second pause in betwee
>>> pyautogui.press('esc')     # Press the Esc key. All key names are in pyautogui.KEY_NAMES

>>> with pyautogui.hold('shift'):  # Press the Shift key down and hold it.
        pyautogui.press(['left', 'left', 'left', 'left'])  # Press the left arrow key 4 times.
>>> # Shift key is released automatically.

>>> pyautogui.hotkey('ctrl', 'c') # Press the Ctrl-C hotkey combination.

>>> pyautogui.alert('This is the message to display.') # Make an alert box appear and pause the
```

pip install pyautogui

Operating-system Accessibility APIs



https://learn.microsoft.com/en-us/windows/win32/winauto/entry-uiauto-win32
https://developer.apple.com/documentation/accessibility/accessibility-api
https://www.freedesktop.org/wiki/Accessibility/AT-SPI2/

Shell Execution

```python
import subprocess

result = subprocess.run(
    ["ls", "-la"],
    capture_output=True,
    text=True
)

print(result.stdout)
```

Perception-Action for Mobile



MobileRun/ DroidRun (iOS & Android)

agent.py

task test scrape

```python
import asyncio
from mobilerun import MobileAgent, MobileConfig

async def main():
    config = MobileConfig()
    agent = MobileAgent(
        goal="Open Twitter and post 'Hello from mobilerun!'",
        config=config,
    )
    result = await agent.run()

asyncio.run(main())
```

pip install mobilerun

Accessibility Services

Android Accessibility Service

ess UI hierarchy and perform actions across apps



Accessibility Node Tree (Android)



Example (Android – AccessibilityService)

```
override fun onAccessibilityEvent(
  event: AccessibilityEvent
) {
  val root = rootInActiveWindow
  val settingsButton =
  root?.findAccessibilityNodeInfosByText(
     "Settings"
   )?.firstOrNull()
  settingsButton?.performAction(
    AccessibilityNodeInfo.ACTION_CLICK
  )
}
```

Common actions (Android)

```
node.performAction(ACTION_CLICK)  // tap
node.performAction(ACTION_LONG_CLICK)
node.performAction(ACTION_SET_TEXT, text)
node.performAction(ACTION_SCROLL_FORWARD)
```

What Android Accessibility Service provides

- Inspect UI hierarchy (**AccessibilityNodeInfo**)
- Read element properties (text, content description, bounds, enabled, etc.)
- Receive UI events (window changes, focus, clicks, etc.)
- Perform actions (click, long click, type text, scroll, swipe, etc.)
- Works across applications (with user permission)

iOS Accessibility (UIAccessibility / XCUiTest)

ess UI elements and perform actions (primarily via XCUiTest)



Accessibility Element Tree (iOS)



Example (iOS – XCUITest, Swift)

```
let app = XCUIApplication()
app.launch()

let settingsTitle =
  app.staticTexts["Settings"]
XCTAssertTrue(settingsTitle.exists)

let wifiCell = app.cells["Wi-Fi"]
wifiCell.tap()
```

Common actions (iOS – XCUITest)

```
element.tap()                  // tap
element.doubleTap()            // double tap
element.typeText("text")       // type text
element.swipeUp()              // swipe up
element.buttons["OK"].tap()    // tap button
element.cells["Wi-Fi"].tap()   // tap cell
```

What iOS accessibility provides

- **UIAccessibility**: exposes UI information for accessibility technologies (e.g., VoiceOver)
- **XCUITest**: inspect UI elements and perform actions (commonly used for automation)
- Read element properties (label, value, traits, frame, etc.)
- Perform actions (tap, type, swipe, etc.)
- Typically used in a testing environment; cross-app access is more restricted

https://developer.android.com/guide/topics/ui/accessibility/views/service
https://developer.apple.com/documentation/uikit/uiaccessibility

Android Debug Bridge (ADB)

```
# 1. Check device connection
adb devices                                          # List connected Android devices/emulators
adb device                                           # Show the currently selected device

# 2. Shell commands (like a terminal on Android)
adb shell                                            # Open an interactive shell on the device
adb shell ls /sdcard                                 # List files in /sdcard
adb shell pwd                                        # Show current directory
adb shell ps                                         # List running processes
adb shell pm list packages                           # List installed apps
adb shell dumpsys window windows | grep mCurrentFocus # Show the current foreground app

# 3. Install and manage apps
adb install path/to/app.apk                          # Install an APK file
adb uninstall com.example.app                        # Uninstall an app
adb shell pm clear com.example.app                   # Clear app data (like reset)
adb shell am start -n com.example.app/.MainActivity  # Launch a specific activity

# 4. Screen capture and recording
adb shell screencap -p /sdcard/screen.png            # Capture a screenshot on the device
adb pull /sdcard/screen.png ./screen.png             # Copy the screenshot to your computer
adb shell screenrecord /sdcard/demo.mp4              # Record the screen (press Ctrl+C to stop)
adb pull /sdcard/demo.mp4 ./demo.mp4                 # Copy the recording to your computer

# 5. Simulate user input
adb shell input tap 500 800                          # Tap at screen coordinates (500, 800)
adb shell input swipe 100 300 100 800 500            # Swipe from (100,300) to (100,800) over 500ms
adb shell input text "Hello World"                   # Type text (use \s for space)
adb shell input keyevent 66                          # Press keyboard key (e.g., 66 = Enter, 4 = Back)
```

Perception-Action for Wearables

1. Observation / Perception (State)

- **First-person video** — Egocentric view
- **Audio / speech** — Ambient audio, speech
- **Eye gaze** — Gaze direction, focus
- **Hand / body motion** — Gestures, activity
- **Environment context** — Location, surroundings
- **Physiological state** — PPG, heart rate, etc.
- **Device state** — Battery, connectivity

Human → **AI Agent**

Wearable Environment

Wearable state & sensors

- **Cameras** — Egocentric video
- **IMU** — Motion / orientation
- **Microphone** — Audio / speech
- **Physiological** — PPG / heart rate
- **Eye gaze** — Gaze direction
- **Location** — GPS / context

2. Action / Actuation

- **Visual display** — Show information
- **Audio output** — Speak / play sound
- **Haptic feedback** — Vibration / touch
- **Contextual notification** — Alert user
- **Proactive assistance** — Suggestions / guidance
- **Capture / record** — Save media / logs
- **Environment interaction** — React to surroundings
- **Adaptive UI** — Change interface

Smartglasses (Meta RayBan)

VisionClaw

A real-time AI assistant for Meta Ray-Ban smart glasses. See what you see, hear what you say, and take actions on your behalf -- all through voice.



https://github.com/Intent-Lab/VisionClaw

Smartglasses/ Headphones



https://github.com/aisee-community

Smartwatch

ClawWatch

The first intelligent AI agent running natively on a smartwatch.

A voice-controlled smartwatch agent for Wear OS: an on-device LLM assistant living on your Galaxy Watch, with offline speech recognition and no companion app in the loop.

Tap. Speak. Get an answer. No cloud STT, no phone dependency, no latency from middlemen.

ClawWatch bundles NullClaw `v2026.3.7` as a static ARM binary, paired with offline speech recognition (Vosk) and the built-in TTS engine. The live response path now tries NullClaw first again on every query. On Wear OS, NullClaw's `curl` calls are bridged back to the parent Kotlin app for network access, and if the native path fails or times out ClawWatch falls back to the existing Kotlin Anthropic path instead of leaving the watch stuck.

https://developer.android.com/training/wearables/get-started/

Perception-Action for Other Physical Devices



HomeAssistants



https://www.home-assistant.io/integrations/mcp_server

Robot Operating System (ROS 2)



https://github.com/wise-vision/ros2_mcp

Printers

OpenPrinting CUPS

The current standards-based, open source printing system developed by OpenPrinting for Linux® and other Unix®-like operating systems. CUPS uses IPP Everywhere™ to support printing to local and network printers.

Download CUPS V2.4.20

Introduction · History · Setting Up · Printing · Documentation · Platforms

Introduction

CUPS supports printing to:

- AirPrint™ and IPP Everywhere™ printers,
- Network and local (USB) printers with Printer Applications, and
- Network and local (USB) printers with (legacy) PPD-based printer drivers.

CUPS provides the System V ("lp") and Berkeley ("lpr") command-line interfaces, a configurable web interface, a C API, and common print filters, drivers, and backends for printing. The cups-filters project provides additional filters and drivers.

CUPS is licensed under the Apache License Version 2.0 with an exception to allow linking against GNU GPL2-only software.

https://github.com/wise-vision/ros2_mcp

What can go wrong?

Evaluation Environments

Browser-Based





WebArena

VisualWebArena

https://github.com/web-arena-x/webarena

https://github.com/web-arena-x/visualwebarena

The Agent Company

Benchmarking LLM Agents on Consequential Real World Tasks

Frank F. Xu[1*], Yufan Song[2*], Boxuan Li[2*]
Yuxuan Tang[2], Kritanjali Jain[1], Mengxue Bao[2], Zora Z. Wang[1],
Xuhui Zhou[1], Zhitong Guo[1], Murong Cao[2], Mingyang Yang[2],
Hao Yang Lu[2], Amaad Martin[1], Zhe Su[1], Leander Maben[1],
Raj Mehta[1], Wayne Chi[1], Lawrence Jang[1], Yiqing Xie[1]
Shuyan Zhou[3], Graham Neubig[1]
[1]Carnegie Mellon University [2]Independent [3]Duke University
(* Equal contribution)

Home | Paper | Code | Submit | Leaderboard

https://github.com/TheAgentCompany/TheAgentCompany

Desktop-Based

OSWorld 2.0: Benchmarking Computer-Use Agents on Long-Horizon Real-World Tasks

Mengqi Yuan[1*], Zilong Zhou[1*], Xinzhuang Xiong[1*], Weiming Wu[1], Jiayang Sun[1], Jiamin Song[1], Kaiqian Cui[1], Bowen Wang[1], Haoyuan Wu[1], Yitong Li[1], Dunjie Lu[1], Haikong Lu[1], Qi Zhen[1], Xinyuan Wang[1], Jiaqi Deng[1], Yuhao Yang[1], Cheng Chen[2], Boyuan Zheng[1], Alex Su[1], Xiao Yu[3], Hao Zou[3], Saaket Agashe[4], Xing Han Lu[5], Manpreet Kaur[6], Zhengyang Qi[7], Vincent Sunn Chen[7], Frederic Sala[7,8], Dayiheng Liu[9], Junyang Lin, Zhou Yu[3], Yu Su[10,12], Siva Reddy[5], Xin Eric Wang[4,11], Peng Qi[6], Tianbao Xie[1], Tao Yu[1]

[1]XLANG Lab, University of Hong Kong; [2]University of California, San Diego; [3]Columbia University; [4]University of California, Santa Barbara; [5]Mila - Quebec AI Institute; [6]Uniphore; [7]Snorkel AI; [8]University of Wisconsin - Madison; [9]Alibaba Qwen; [10]The Ohio State University; [11]Simular; [12]NeoCognition

[*]Equal contribution

Paper | Code | Data | Task showcase | Explore all task trajectories | Twitter | Discord



https://osworld-v2.xlang.ai/

Desktop-Based

Windows Agent Arena (WAA) is a scalable Windows AI agent platform for testing and benchmarking multi-modal, desktop AI agents. WAA provides researchers and developers with a reproducible and realistic Windows OS environment for AI research, where agentic AI workflows can be tested across a diverse range of tasks.

WAA supports the deployment of agents **at scale** using the Azure ML cloud infrastructure, allowing for the parallel running of multiple agents and delivering quick benchmark results for hundreds of tasks in minutes, not days.

https://github.com/microsoft/WindowsAgentArena

Desktop-Based

TERMINAL-BENCH 4.0

A benchmark to measure and evolve with the frontier of agent work

Run the benchmark >_ View the tasks →

4.0 TABLE PARETO WAFFLE

RANK	MODEL	AGENT	RESOLUTION RATE	RELEASE DATE	TOKENS	COST
1	Opus 5.5 (max)	Claude Code	**64.8%** ± 3.1%	Sep 22, 2026	8.0B	$4.7k
2	Sonnet 5.5 (max)	Claude Code	**61.8%** ± 2.9%	Sep 28, 2026	19.4B	$7.3k
3	GPT-6 Astra (max)	Codex	**58.2%** ± 2.8%	Sep 3, 2026	1.5B	$3.3k
3	GPT-6.1 Sol (max)	Codex	**58.2%** ± 3.1%	Sep 29, 2026	1.5B	$0.6k
5	Fable 5.1 (max)	Claude Code	**57.9%** ± 3.8%	Sep 1, 2026	2.7B	$6.2k

https://www.tbench.ai/

Mobile-Based

AndroidWorld: A Dynamic Benchmarking Environment for Autonomous Agents

Chris Rawles*[1], Yifan Chang†[2], Sarah Clinckemaillie†[2], Jonathan Waltz[2], Gabrielle Lau[2], Marybeth Fair[2], Robert Berry[1], Wei Li[1], Will Bishop[1], Alice Li[1], Folawiyo Campbell-Ajala[1], Divya Tyamagundlu[2], Daniel Toyama[1], Timothy Lillicrap[1], Oriana Riva[1]

[1] Google DeepMind [2] Google
*Lead contributor †Equal contribution

Paper | Code | Data | Leaderboard



https://github.com/google-research/android_world

Privacy Risk

An agent may have access to far more information than it needs to complete a task



- Least Privilege
- Data Minimization
- Trust Boundaries

- Human Approval
- Auditability

Visual Prompt Injection



https://arxiv.org/pdf/2506.02456

Training Computer-Use Models

Imitation Learning Approach



https://arxiv.org/pdf/2306.06070

Supervised Visual Grounding



https://arxiv.org/pdf/2401.10935

World-Model-Based Training



https://arxiv.org/pdf/2608.27508

Examples of Device-Use Agents



Zach Lo | NVIDIA
Michael | NVIDIA

2025-10-31 11:08.52 Fri


reloc
D:\RELOC\Workspace\doom>
Claude Sonnet
playing DOOM
on an ESP32-P4

• PhysiClaw



• iPhone

• Terminal

physiclaw.ai


Watch Aiden navigate home.
A real phone controlled through hardware.
Prompt: navigate me home.

REA: Reverse Engineer Anything

One MCP for reverse engineering across binaries, applications, and runtime behavior.

See a feature you like. Understand how it works, down to the binary level.

npm v6.7.0 | MCP tool catalog | Node.js requirements | ▲ Skills 10.1K | license MIT | Discord 4.5k online

1 GITHUB TRENDING
#1 Repository Of The Day

Website · Guides · Showcases

Quick start · How REA works · What you can analyze · Showcases · FAQ · Documentation

```
npx rea-agents setup
```

> **Important**
>
> Get REA from morluto/rea, rea.tools, or the rea-agents npm package. Follow the ir
> from these official sources. A similar repository name or copied README does no
> official.





GenAI.works

A DEVELOPER USED CLAUDE TO REBUILD 7 ADOBE APPS AND IS GIVING THEM AWAY FOR FREE

OPEN SOURCE, BUILT IN RUST, STILL IN EARLY ALPHA

https://github.com/morluto/rea

Cognitive Augmentation with Device Use Agents?

AiSee: Wearable AI Agent for Low-Vision Users



Accessible Browsers



Phi-Ground: AI-Guided Computer Interaction



When agents operate devices,
how should we design future devices for humans?

Let’s start the tutorial

Assignment

. make an agent operate a device with an existing OS

Thank you and feel free to contact for any questions or ideas!!